





11G_Ant1_High_2462



11N20SISO_Ant1_Low_2412






ANT2

Test Result

TestMode	ChName	Frequency[MHz]	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
11B	Low	2412	-3.96	-53.21	≤ -33.96	PASS
	High	2462	-2.57	-51.56	≤ -32.57	PASS
11G	Low	2412	-7.34	-50.74	≤ -37.34	PASS
	High	2462	-4.64	-52.35	≤ -34.64	PASS
11N20SISO	Low	2412	-6.96	-50.71	≤ -36.96	PASS
	High	2462	-3.98	-52.07	≤ -33.98	PASS


Test Graphs

11B_Ant2_Low_2412




Date: 30 MAY 2026 16:07:38

11B_Ant2_High_2462




Date: 30 MAY 2026 16:11:08

11G_Ant2_Low_2412




Date: 30 MAY 2026 16:13:10

11G_Ant2_High_2462




Date: 30 MAY 2026 16:17:22


11N20SISO_Ant2_Low_2412



Date: 30 MAY 2026 16:19:09



5.8 RF Conducted Spurious Emissions


Test Requirement:	47 CFR Part 15C Section 15.247 (d)
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024
Test Setup:	 $\text{Offset} = \text{cable loss} + \text{attenuation factor}$
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates
Final Test Mode:	Only the worst case is recorded in the report.
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 30 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test Results:	Pass


ANT1

Test Result


TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	-8.05	-8.05	---	PASS
		30~1000	-8.05	-50.85	≤ -38.05	PASS
		1000~26500	-8.05	-48.41	≤ -38.05	PASS
	2437	Reference	-5.76	-5.76	---	PASS
		30~1000	-5.76	-51.68	≤ -35.76	PASS
		1000~26500	-5.76	-48.82	≤ -35.76	PASS
	2462	Reference	-6.12	-6.12	---	PASS
		30~1000	-6.12	-52.28	≤ -36.12	PASS
		1000~26500	-6.12	-48.57	≤ -36.12	PASS
11G	2412	Reference	-9.14	-9.14	---	PASS
		30~1000	-9.14	-51.27	≤ -39.14	PASS
		1000~26500	-9.14	-48.43	≤ -39.14	PASS
	2437	Reference	-7.60	-7.60	---	PASS
		30~1000	-7.60	-52.4	≤ -37.6	PASS
		1000~26500	-7.60	-48.55	≤ -37.6	PASS
	2462	Reference	-7.97	-7.97	---	PASS
		30~1000	-7.97	-51.64	≤ -37.97	PASS
		1000~26500	-7.97	-48.35	≤ -37.97	PASS
11N20SISO	2412	Reference	-10.44	-10.44	---	PASS
		30~1000	-10.44	-52.28	≤ -40.44	PASS
		1000~26500	-10.44	-48.31	≤ -40.44	PASS
	2437	Reference	-7.55	-7.55	---	PASS
		30~1000	-7.55	-51.74	≤ -37.55	PASS
		1000~26500	-7.55	-48.52	≤ -37.55	PASS
	2462	Reference	-7.73	-7.73	---	PASS
		30~1000	-7.73	-51.45	≤ -37.73	PASS
		1000~26500	-7.73	-48.77	≤ -37.73	PASS

Test Graphs







11B_Ant1_2437_0~Reference



11B_Ant1_2437_30~1000




11B_Ant1_2437_1000~26500




Date: 30 MAY 2026 15:33:58

11B_Ant1_2462_0~Reference




Date: 30 MAY 2026 15:35:38


11B_Ant1_2462_30~1000




11B_Ant1_2462_1000~26500



11G_Ant1_2412_0~Reference




11G_Ant1_2412_30~1000




Date: 30 MAY 2026 15:49:14

11G_Ant1_2412_1000~26500




Date: 30 MAY 2026 15:49:24


11G_Ant1_2437_0~Reference




11G_Ant1_2437_30~1000



11G_Ant1_2437_1000~26500




11G_Ant1_2462_0~Reference




Date: 30 MAY 2026 15:51:57

11G_Ant1_2462_30~1000




Date: 30 MAY 2026 15:52:01


11G_Ant1_2462_1000~26500




11N20SISO_Ant1_2412_0~Reference



11N20SISO_Ant1_2412_30~1000




11N20SISO_Ant1_2412_1000~26500




Date: 30 MAY 2026 15:54:20

11N20SISO_Ant1_2437_0~Reference




Date: 30 MAY 2026 15:55:27


11N20SISO_Ant1_2437_30~1000




11N20SISO_Ant1_2437_1000~26500



11N20SISO_Ant1_2462_0~Reference




11N20SISO_Ant1_2462_30~1000



Date: 30 MAY 2026 15:59:34

11N20SISO_Ant1_2462_1000~26500




Date: 30 MAY 2026 15:59:45


ANT2

Test Result


TestMode	Frequency[MHz]	FreqRange [Mhz]	RefLevel [dBm]	Result [dBm]	Limit [dBm]	Verdict
11B	2412	Reference	-7.11	-7.11	---	PASS
		30~1000	-7.11	-51.57	≤ -37.11	PASS
		1000~26500	-7.11	-47.82	≤ -37.11	PASS
	2437	Reference	-5.40	-5.40	---	PASS
		30~1000	-5.40	-51.48	≤ -35.4	PASS
		1000~26500	-5.40	-48.67	≤ -35.4	PASS
	2462	Reference	-5.76	-5.76	---	PASS
		30~1000	-5.76	-50.98	≤ -35.76	PASS
		1000~26500	-5.76	-48.44	≤ -35.76	PASS
11G	2412	Reference	-10.50	-10.50	---	PASS
		30~1000	-10.50	-51.43	≤ -40.5	PASS
		1000~26500	-10.50	-47.8	≤ -40.5	PASS
	2437	Reference	-8.01	-8.01	---	PASS
		30~1000	-8.01	-52.2	≤ -38.01	PASS
		1000~26500	-8.01	-48.72	≤ -38.01	PASS
	2462	Reference	-6.82	-6.82	---	PASS
		30~1000	-6.82	-51.95	≤ -36.82	PASS
		1000~26500	-6.82	-48.65	≤ -36.82	PASS
11N20SISO	2412	Reference	-9.50	-9.50	---	PASS
		30~1000	-9.50	-51.28	≤ -39.5	PASS
		1000~26500	-9.50	-48.22	≤ -39.5	PASS
	2437	Reference	-8.69	-8.69	---	PASS
		30~1000	-8.69	-52.38	≤ -38.69	PASS
		1000~26500	-8.69	-48.72	≤ -38.69	PASS
	2462	Reference	-7.60	-7.60	---	PASS
		30~1000	-7.60	-50.93	≤ -37.6	PASS
		1000~26500	-7.60	-48.59	≤ -37.6	PASS

Test Graphs







11B_Ant2_2437_0~Reference



11B_Ant2_2437_30~1000




11B_Ant2_2437_1000~26500




Date: 30 MAY 2026 16:09:43

11B_Ant2_2462_0~Reference




Date: 30 MAY 2026 16:11:34


11B_Ant2_2462_30~1000




11B_Ant2_2462_1000~26500



11G_Ant2_2412_0~Reference




11G_Ant2_2412_30~1000




Date: 30 MAY 2026 16:13:33

11G_Ant2_2412_1000~26500




Date: 30 MAY 2026 16:13:44


11G_Ant2_2437_0~Reference




11G_Ant2_2437_30~1000



11G_Ant2_2437_1000~26500




11G_Ant2_2462_0~Reference




Date: 30 MAY 2026 16:17:40

11G_Ant2_2462_30~1000




Date: 30 MAY 2026 16:17:45


11G_Ant2_2462_1000~26500




11N20SISO_Ant2_2412_0~Reference



11N20SISO_Ant2_2412_30~1000




11N20SISO_Ant2_2412_1000~26500




Date: 30 MAY 2026 16:19:43

11N20SISO_Ant2_2437_0~Reference




Date: 30 MAY 2026 16:20:36


11N20SISO_Ant2_2437_30~1000




11N20SISO_Ant2_2437_1000~26500



11N20SISO_Ant2_2462_0~Reference





Remark:

Pretest 9kHz to 25GHz, find the highest point when testing, so only the worst data were shown in the test report. Per FCC Part 15.33 (a) and 15.31 (o) ,The amplitude of spurious emissions from intentional radiators which are attenuated more than 20 dB below the permissible value need not be reported unless specifically required elsewhere in this part.

5.9 Radiated Spurious Emissions

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205				
Test Method:	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024				
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver Setup:	Frequency	Detector	RBW	VBW	Remark
	0.009MHz-0.090MHz	Peak	10kHz	30kHz	Peak
	0.009MHz-0.090MHz	Average	10kHz	30kHz	Average
	0.090MHz-0.110MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	0.110MHz-0.490MHz	Peak	10kHz	30kHz	Peak
	0.110MHz-0.490MHz	Average	10kHz	30kHz	Average
	0.490MHz -30MHz	Quasi-peak	10kHz	30kHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	100 kHz	300kHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Limit:	Frequency	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz-0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz-88MHz	100	40.0	Quasi-peak	3
	88MHz-216MHz	150	43.5	Quasi-peak	3
	216MHz-960MHz	200	46.0	Quasi-peak	3
	960MHz-1GHz	500	54.0	Quasi-peak	3
	Above 1GHz	500	54.0	Average	3
	Note: 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.				

Test Setup:




Figure 1. Below 30MHz




Figure 2. 30MHz to 1GHz




Figure 3. Above 1 GHz

Test Procedure:

- a. 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
Note: For the radiated emission test above 1GHz:
Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.


	d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates at lowest, middle and highest channel.
Final Test Mode:	Only the worst case is recorded in the report.
Test Results:	Pass

5.9.1 Radiated emission below 1GHz

ANT1+ANT2

30MHz~1GHz

Vertical



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark	Pol/Phase
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	234.99	13.52	14.70	28.22	46.00	-17.78	Peak	VERTICAL
2	299.32	12.05	16.86	28.91	46.00	-17.09	Peak	VERTICAL
3	501.18	11.83	20.94	32.77	46.00	-13.23	Peak	VERTICAL
4	742.26	14.42	24.44	38.86	46.00	-7.14	Peak	VERTICAL
5 pp	893.86	10.31	29.20	39.51	46.00	-6.49	Peak	VERTICAL
6	965.54	11.89	28.08	39.97	54.00	-14.03	Peak	VERTICAL

Remark:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

Horizontal



	Read			Limit	Over		
Freq	Level	Factor	Level	Line	Limit	Remark	Pol/Phase
MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		
1	144.33	16.39	8.53	24.92	43.50	-18.58 Peak	HORIZONTAL
2	222.95	17.48	13.27	30.75	46.00	-15.25 Peak	HORIZONTAL
3	501.18	12.40	20.94	33.34	46.00	-12.66 Peak	HORIZONTAL
4	744.87	14.54	24.73	39.27	46.00	-6.73 Peak	HORIZONTAL
5 pp	893.86	10.94	29.20	40.14	46.00	-5.86 Peak	HORIZONTAL
6	965.54	11.03	28.08	39.11	54.00	-14.89 Peak	HORIZONTAL

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Factor= Antenna Factor + Cable Factor – Preamplifier Factor,

Level = Read Level + Factor,

Over Limit=Level-Limit Line.

5.9.2 Transmitter emission above 1GHz

ANT1

Test mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.35	-4.26	48.09	74	-25.91	peak	H	1.5	53
4824.000	37.89	-4.26	33.63	54	-20.37	AVG	H	1.5	60
7236.000	50.81	1.18	51.99	74	-22.01	peak	H	1.5	158
7236.000	38.10	1.18	39.28	54	-14.72	AVG	H	1.5	17
4824.000	55.62	-4.26	51.36	74	-22.64	peak	V	1.5	204
4824.000	38.65	-4.26	34.39	54	-19.61	AVG	V	1.5	120
7236.000	51.19	1.18	52.37	74	-21.63	peak	V	1.5	151
7236.000	36.02	1.18	37.20	54	-16.80	AVG	V	1.5	237

Test mode:		802.11b(1Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	51.28	-4.12	47.16	74	-26.84	peak	H	1.5	243
4874.000	37.22	-4.12	33.10	54	-20.90	AVG	H	1.5	199
7311.000	49.71	1.46	51.17	74	-22.83	peak	H	1.5	312
7311.000	35.52	1.46	36.98	54	-17.02	AVG	H	1.5	356
4874.000	53.00	-4.12	48.88	74	-25.12	peak	V	1.5	360
4874.000	37.22	-4.12	33.10	54	-20.90	AVG	V	1.5	163
7311.000	48.52	1.46	49.98	74	-24.02	peak	V	1.5	260
7311.000	35.81	1.46	37.27	54	-16.73	AVG	V	1.5	23

Test mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol. H/V	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)			(m)	(Degree)
4924.000	52.58	-4.03	48.55	74	-25.45	peak	H	1.5	341
4924.000	37.10	-4.03	33.07	54	-20.93	AVG	H	1.5	44
7386.000	50.06	1.66	51.72	74	-22.28	peak	H	1.5	217
7386.000	37.66	1.66	39.32	54	-14.68	AVG	H	1.5	89
4924.000	54.61	-4.03	50.58	74	-23.42	peak	V	1.5	54
4924.000	37.91	-4.03	33.88	54	-20.12	AVG	V	1.5	174
7386.000	49.84	1.66	51.50	74	-22.50	peak	V	1.5	94
7386.000	37.86	1.66	39.52	54	-14.48	AVG	V	1.5	73

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.57	-4.26	48.31	74	-25.69	peak	H	1.5	257
4824.000	36.39	-4.26	32.13	54	-21.87	AVG	H	1.5	154
7236.000	51.52	1.18	52.70	74	-21.30	peak	H	1.5	317
7236.000	38.42	1.18	39.60	54	-14.40	AVG	H	1.5	343
4824.000	55.83	-4.26	51.57	74	-22.43	peak	V	1.5	34
4824.000	39.94	-4.26	35.68	54	-18.32	AVG	V	1.5	79
7236.000	51.64	1.18	52.82	74	-21.18	peak	V	1.5	185
7236.000	36.17	1.18	37.35	54	-16.65	AVG	V	1.5	222

Test mode:		802.11g(6Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	52.23	-4.12	48.11	74	-25.89	peak	H	1.5	290
4874.000	37.03	-4.12	32.91	54	-21.09	AVG	H	1.5	333
7311.000	49.50	1.46	50.96	74	-23.04	peak	H	1.5	40
7311.000	35.14	1.46	36.60	54	-17.40	AVG	H	1.5	106
4874.000	52.78	-4.12	48.66	74	-25.34	peak	V	1.5	233
4874.000	36.71	-4.12	32.59	54	-21.41	AVG	V	1.5	165
7311.000	49.25	1.46	50.71	74	-23.29	peak	V	1.5	133
7311.000	36.05	1.46	37.51	54	-16.49	AVG	V	1.5	130

Test mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)				
4924.000	52.75	-4.03	48.72	74	-25.28	peak	H	1.5	10
4924.000	38.26	-4.03	34.23	54	-19.77	AVG	H	1.5	187
7386.000	50.79	1.66	52.45	74	-21.55	peak	H	1.5	108
7386.000	36.84	1.66	38.50	54	-15.50	AVG	H	1.5	58
4924.000	54.98	-4.03	50.95	74	-23.05	peak	V	1.5	240
4924.000	38.45	-4.03	34.42	54	-19.58	AVG	V	1.5	13
7386.000	49.44	1.66	51.10	74	-22.90	peak	V	1.5	84
7386.000	36.69	1.66	38.35	54	-15.65	AVG	V	1.5	119

Remark:

- 1) The 6Mbps of rate of 802.11g is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

ANT2

Test mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	53.24	-4.26	48.98	74	-25.02	peak	H	1.5	143
4824.000	37.84	-4.26	33.58	54	-20.42	AVG	H	1.5	177
7236.000	52.01	1.18	53.19	74	-20.81	peak	H	1.5	5
7236.000	38.76	1.18	39.94	54	-14.06	AVG	H	1.5	359
4824.000	55.51	-4.26	51.25	74	-22.75	peak	V	1.5	314
4824.000	39.39	-4.26	35.13	54	-18.87	AVG	V	1.5	199
7236.000	50.54	1.18	51.72	74	-22.28	peak	V	1.5	212
7236.000	35.35	1.18	36.53	54	-17.47	AVG	V	1.5	166

Test mode:		802.11b(1Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	52.61	-4.12	48.49	74	-25.51	peak	H	1.5	332
4874.000	36.80	-4.12	32.68	54	-21.32	AVG	H	1.5	244
7311.000	48.73	1.46	50.19	74	-23.81	peak	H	1.5	345
7311.000	35.76	1.46	37.22	54	-16.78	AVG	H	1.5	105
4874.000	53.65	-4.12	49.53	74	-24.47	peak	V	1.5	78
4874.000	36.56	-4.12	32.44	54	-21.56	AVG	V	1.5	64
7311.000	48.92	1.46	50.38	74	-23.62	peak	V	1.5	275
7311.000	35.70	1.46	37.16	54	-16.84	AVG	V	1.5	228

Test mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	51.30	-4.03	47.27	74	-26.73	peak	H	1.5	108
4924.000	37.07	-4.03	33.04	54	-20.96	AVG	H	1.5	49
7386.000	50.40	1.66	52.06	74	-21.94	peak	H	1.5	247
7386.000	37.17	1.66	38.83	54	-15.17	AVG	H	1.5	69
4924.000	53.41	-4.03	49.38	74	-24.62	peak	V	1.5	160
4924.000	38.42	-4.03	34.39	54	-19.61	AVG	V	1.5	206
7386.000	50.83	1.66	52.49	74	-21.51	peak	V	1.5	113
7386.000	37.52	1.66	39.18	54	-14.82	AVG	V	1.5	252

Remark:

- 1) The 1Mbps of rate of 802.11b is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

Test mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	54.13	-4.26	49.87	74	-24.13	peak	H	1.5	184
4824.000	37.67	-4.26	33.41	54	-20.59	AVG	H	1.5	346
7236.000	51.09	1.18	52.27	74	-21.73	peak	H	1.5	237
7236.000	37.12	1.18	38.30	54	-15.70	AVG	H	1.5	89
4824.000	55.76	-4.26	51.50	74	-22.50	peak	V	1.5	340
4824.000	39.76	-4.26	35.50	54	-18.50	AVG	V	1.5	357
7236.000	52.15	1.18	53.33	74	-20.67	peak	V	1.5	33
7236.000	36.66	1.18	37.84	54	-16.16	AVG	V	1.5	141

Test mode:		802.11g(6Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	52.18	-4.12	48.06	74	-25.94	peak	H	1.5	314
4874.000	36.37	-4.12	32.25	54	-21.75	AVG	H	1.5	239
7311.000	49.08	1.46	50.54	74	-23.46	peak	H	1.5	226
7311.000	36.22	1.46	37.68	54	-16.32	AVG	H	1.5	209
4874.000	53.15	-4.12	49.03	74	-24.97	peak	V	1.5	323
4874.000	37.71	-4.12	33.59	54	-20.41	AVG	V	1.5	305
7311.000	49.97	1.46	51.43	74	-22.57	peak	V	1.5	314
7311.000	35.30	1.46	36.76	54	-17.24	AVG	V	1.5	288

Test mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol. H/V	Antenna Height (m)	Table Angle (Degree)
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)				
4924.000	53.20	-4.03	49.17	74	-24.83	peak	H	1.5	166
4924.000	37.02	-4.03	32.99	54	-21.01	AVG	H	1.5	247
7386.000	50.02	1.66	51.68	74	-22.32	peak	H	1.5	24
7386.000	36.58	1.66	38.24	54	-15.76	AVG	H	1.5	31
4924.000	54.77	-4.03	50.74	74	-23.26	peak	V	1.5	137
4924.000	38.19	-4.03	34.16	54	-19.84	AVG	V	1.5	271
7386.000	51.05	1.66	52.71	74	-21.29	peak	V	1.5	148
7386.000	36.96	1.66	38.62	54	-15.38	AVG	V	1.5	240

Remark:

- 1) The 6Mbps of rate of 802.11g is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level =Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

- 3) Scan from 9kHz to 25GHz,The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

ANT1+ANT2

Test mode:		802.11n20(13Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4824.000	52.74	-4.26	48.48	74	-25.52	peak	H	1.5	49
4824.000	37.76	-4.26	33.50	54	-20.50	AVG	H	1.5	37
7236.000	51.57	1.18	52.75	74	-21.25	peak	H	1.5	198
7236.000	38.77	1.18	39.95	54	-14.05	AVG	H	1.5	332
4824.000	54.58	-4.26	50.32	74	-23.68	peak	V	1.5	337
4824.000	38.45	-4.26	34.19	54	-19.81	AVG	V	1.5	198
7236.000	51.55	1.18	52.73	74	-21.27	peak	V	1.5	167
7236.000	36.43	1.18	37.61	54	-16.39	AVG	V	1.5	16

Test mode:		802.11n20(13Mbps)		Test channel:		Middle			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4874.000	53.10	-4.12	48.98	74	-25.02	peak	H	1.5	65
4874.000	36.92	-4.12	32.80	54	-21.20	AVG	H	1.5	260
7311.000	48.94	1.46	50.40	74	-23.60	peak	H	1.5	270
7311.000	36.71	1.46	38.17	54	-15.83	AVG	H	1.5	200
4874.000	52.67	-4.12	48.55	74	-25.45	peak	V	1.5	335
4874.000	37.14	-4.12	33.02	54	-20.98	AVG	V	1.5	37
7311.000	48.74	1.46	50.20	74	-23.80	peak	V	1.5	92
7311.000	35.04	1.46	36.50	54	-17.50	AVG	V	1.5	244

Test mode:		802.11n20(13Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detect or Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
4924.000	52.91	-4.03	48.88	74	-25.12	peak	H	1.5	219
4924.000	38.68	-4.03	34.65	54	-19.35	AVG	H	1.5	239
7386.000	49.71	1.66	51.37	74	-22.63	peak	H	1.5	350
7386.000	36.04	1.66	37.70	54	-16.30	AVG	H	1.5	227
4924.000	53.53	-4.03	49.50	74	-24.50	peak	V	1.5	315
4924.000	37.20	-4.03	33.17	54	-20.83	AVG	V	1.5	104
7386.000	50.39	1.66	52.05	74	-21.95	peak	V	1.5	66
7386.000	37.22	1.66	38.88	54	-15.12	AVG	V	1.5	301

Remark:

- 1) The MCS0 of rate of 802.11n20 is the worst case.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, The disturbance above 13GHz and below 30MHz was very low, and the above harmonics were the highest point could be found when testing, so only the above harmonics had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.

5.10 Restricted bands around fundamental frequency

Test Requirement:	47 CFR Part 15C Section 15.209 and 15.205		
Test Method:	ANSI C63.10 2020		
Test Site:	Measurement Distance: 3m (Semi-Anechoic Chamber)		
Limit:	Frequency	Limit (dBuV/m @3m)	Remark
	30MHz-88MHz	40.0	Quasi-peak Value
	88MHz-216MHz	43.5	Quasi-peak Value
	216MHz-960MHz	46.0	Quasi-peak Value
	960MHz-1GHz	54.0	Quasi-peak Value
	Above 1GHz	54.0	Average Value
		74.0	Peak Value

Test Setup:




Figure 1. 30MHz to 1GHz




Figure 2. Above 1 GHz

Test Procedure:

- 1) Below 1G: The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
 - 2) Above 1G: The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- Note: For the radiated emission test above 1GHz:
- Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
 - The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
 - For each suspected emission, the EUT was arranged to its worst case and

	then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. f. Place a marker at the end of the restricted band closest to the transmit frequency to show compliance. Also measure any emissions in the restricted bands. Save the spectrum analyzer plot. Repeat for each power and modulation for lowest and highest channel g. Test the EUT in the lowest channel, the middle channel, the Highest channel. h. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, And found the X axis positioning which it is worse case . i. Repeat above procedures until all frequencies measured was complete.
Exploratory Test Mode:	Transmitting with all kind of modulations, data rates. Transmitting mode.
Final Test Mode:	Pretest the EUT at Transmitting mode, found the Transmitting mode which it is worse case. Through Pre-scan, find the 1Mbps of rate is the worst case of 802.11b; 6Mbps of rate is the worst case of 802.11g; 6.5Mbps of rate is the worst case of 802.11n(HT20); 13.5Mbps of rate is the worst case of 802.11n(HT40). Only the worst case is recorded in the report.
Test Results:	Pass

ANT1

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390.000	58.32	-9.2	49.12	74	-24.88	peak	H	1.5	65
2390.000	44.15	-9.2	34.95	54	-19.05	AVG	H	1.5	226
2400.000	59.96	-9.39	50.57	74	-23.43	peak	H	1.5	197
2400.000	46.06	-9.39	36.67	54	-17.33	AVG	H	1.5	95
2390.000	58.66	-9.2	49.46	74	-24.54	peak	V	1.5	335
2390.000	44.74	-9.2	35.54	54	-18.46	AVG	V	1.5	21
2400.000	59.46	-9.39	50.07	74	-23.93	peak	V	1.5	34
2400.000	46.01	-9.39	36.62	54	-17.38	AVG	V	1.5	43

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.500	57.43	-9.29	48.14	74	-25.86	peak	H	1.5	321
2483.500	43.51	-9.29	34.22	54	-19.78	AVG	H	1.5	193
2483.500	57.45	-9.29	48.16	74	-25.84	peak	V	1.5	83
2483.500	46.17	-9.29	36.88	54	-17.12	AVG	V	1.5	270

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390.000	58.75	-9.2	49.55	74	-24.45	peak	H	1.5	173
2390.000	44.92	-9.2	35.72	54	-18.28	AVG	H	1.5	188
2400.000	59.74	-9.39	50.35	74	-23.65	peak	H	1.5	275
2400.000	46.89	-9.39	37.50	54	-16.50	AVG	H	1.5	66
2390.000	59.20	-9.2	50.00	74	-24.00	peak	V	1.5	238
2390.000	44.21	-9.2	35.01	54	-18.99	AVG	V	1.5	354
2400.000	59.41	-9.39	50.02	74	-23.98	peak	V	1.5	142
2400.000	46.66	-9.39	37.27	54	-16.73	AVG	V	1.5	177

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.500	58.05	-9.29	48.76	74	-25.24	peak	H	1.5	128
2483.500	43.61	-9.29	34.32	54	-19.68	AVG	H	1.5	115
2483.500	57.99	-9.29	48.70	74	-25.30	peak	V	1.5	190
2483.500	46.18	-9.29	36.89	54	-17.11	AVG	V	1.5	94

ANT2

Test data:

Worse case mode:		802.11b(1Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390.000	59.14	-9.2	49.94	74	-24.06	peak	H	1.5	233
2390.000	44.85	-9.2	35.65	54	-18.35	AVG	H	1.5	180
2400.000	59.74	-9.39	50.35	74	-23.65	peak	H	1.5	105
2400.000	46.93	-9.39	37.54	54	-16.46	AVG	H	1.5	276
2390.000	58.51	-9.2	49.31	74	-24.69	peak	V	1.5	301
2390.000	44.47	-9.2	35.27	54	-18.73	AVG	V	1.5	324
2400.000	59.40	-9.39	50.01	74	-23.99	peak	V	1.5	339
2400.000	46.06	-9.39	36.67	54	-17.33	AVG	V	1.5	314

Worse case mode:		802.11b(1Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.500	57.97	-9.29	48.68	74	-25.32	peak	H	1.5	57
2483.500	44.08	-9.29	34.79	54	-19.21	AVG	H	1.5	335
2483.500	58.28	-9.29	48.99	74	-25.01	peak	V	1.5	327
2483.500	45.67	-9.29	36.38	54	-17.62	AVG	V	1.5	200

Worse case mode:		802.11g(6Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2390.000	58.27	-9.2	49.07	74	-24.93	peak	H	1.5	348
2390.000	44.97	-9.2	35.77	54	-18.23	AVG	H	1.5	233
2400.000	59.37	-9.39	49.98	74	-24.02	peak	H	1.5	13
2400.000	46.78	-9.39	37.39	54	-16.61	AVG	H	1.5	165
2390.000	58.59	-9.2	49.39	74	-24.61	peak	V	1.5	27
2390.000	44.42	-9.2	35.22	54	-18.78	AVG	V	1.5	326
2400.000	60.15	-9.39	50.76	74	-23.24	peak	V	1.5	208
2400.000	46.38	-9.39	36.99	54	-17.01	AVG	V	1.5	46

Worse case mode:		802.11g(6Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector Type	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)		H/V	(m)	(Degree)
2483.500	57.68	-9.29	48.39	74	-25.61	peak	H	1.5	176
2483.500	43.55	-9.29	34.26	54	-19.74	AVG	H	1.5	260
2483.500	57.76	-9.29	48.47	74	-25.53	peak	V	1.5	35
2483.500	46.26	-9.29	36.97	54	-17.03	AVG	V	1.5	55

ANT1+ANT2

Worse case mode:		802.11n(HT20)(13Mbps)		Test channel:		Lowest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2390.000	59.18	-9.2	49.98	74	-24.02	peak	H	1.5	213
2390.000	44.24	-9.2	35.04	54	-18.96	AVG	H	1.5	227
2400.000	60.07	-9.39	50.68	74	-23.32	peak	H	1.5	203
2400.000	46.11	-9.39	36.72	54	-17.28	AVG	H	1.5	128
2390.000	58.69	-9.2	49.49	74	-24.51	peak	V	1.5	299
2390.000	44.90	-9.2	35.70	54	-18.30	AVG	V	1.5	282
2400.000	59.52	-9.39	50.13	74	-23.87	peak	V	1.5	136
2400.000	46.02	-9.39	36.63	54	-17.37	AVG	V	1.5	52

Worse case mode:		802.11n(HT20)(13Mbps)		Test channel:		Highest			
Frequency	Meter Reading	Factor	Emission Level	Limits	Over	Detector	Ant. Pol.	Antenna Height	Table Angle
(MHz)	(dBμV)	(dB)	(dBμV/m)	(dBμV/m)	(dB)	Type	H/V	(m)	(Degree)
2483.500	58.02	-9.29	48.73	74	-25.27	peak	H	1.5	350
2483.500	43.86	-9.29	34.57	54	-19.43	AVG	H	1.5	169
2483.500	58.01	-9.29	48.72	74	-25.28	peak	V	1.5	138
2483.500	46.03	-9.29	36.74	54	-17.26	AVG	V	1.5	303

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor


6 Photographs - EUT Test Setup

6.1 Radiated Spurious Emission

9kHz~30MHz:




30MHz~1GHz:



Above 1GHz:



6.2 Conducted Emission



Page:126 of 138



7 Photographs - EUT Constructional Details


































*** END OF REPORT ***