

FCC 47 CFR MPE REPORT

Chunghsin Technology Group CO.,LTD

50inch FHD DLED TV

Model Number: E2SW5018

Additional Model:ELSJ5017

FCC ID: 2AE2W-E2SW5018

Prepared for:	Chunghsin Technology Group CO.,LTD
	No. 618-2 GONGREN WEST ROAD, JIAOJIANG AREA,
	TAIZHOU CITY, ZHEJIANG, CHINA
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R1804085
Date of Test:	Apr. 26, 2018
Date of Report:	Apr. 28, 2018

Maximum Permissible Exposure

1、Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

(a)、Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

(b)、Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Times E 2 , H 2 or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; *Plane-wave equivalent power density

2、MPE Calculation Method

$$E \text{ (V/m)} = (30 \cdot P \cdot G)^{0.5} / d \quad \text{Power Density: } P_d \text{ (W/m}^2\text{)} = E^2 / 377$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$P_d = (30 \cdot P \cdot G) / (377 \cdot d^2)$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained

3、Conducted Power Result

3.1Antenna a

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	16.33	42.954	16 ± 2	1.21	1.321
	2437	16.74	47.206	16 ± 2	1.21	1.321
	2462	14.51	28.249	14 ± 2	1.21	1.321
IEEE 802.11g	2412	12.44	17.539	12 ± 2	1.21	1.321
	2437	12.45	17.579	12 ± 2	1.21	1.321
	2462	10.35	10.839	10 ± 2	1.21	1.321
IEEE 802.11n HT20	2412	12.09	16.181	12 ± 2	1.21	1.321
	2437	12.06	16.069	12 ± 2	1.21	1.321
	2462	10.18	10.423	10 ± 2	1.21	1.321
IEEE 802.11n HT40	2422	9.65	9.226	9 ± 2	1.21	1.321
	2437	9.28	8.472	9 ± 2	1.21	1.321
	2452	7.76	5.970	7 ± 2	1.21	1.321

3.2Antenna b

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)	Target power (dBm)	Antenna gain	
					(dBi)	(Linear)
IEEE 802.11b	2412	17.04	50.582	17 ± 2	1.21	1.321
	2437	16.73	47.098	16 ± 2	1.21	1.321
	2462	15.37	34.435	15 ± 2	1.21	1.321
IEEE 802.11g	2412	13.39	21.827	13 ± 2	1.21	1.321
	2437	13.13	20.559	13 ± 2	1.21	1.321
	2462	10.69	11.722	10 ± 2	1.21	1.321
IEEE 802.11n HT20	2412	12.86	19.320	12 ± 2	1.21	1.321
	2437	13.04	20.137	13 ± 2	1.21	1.321
	2462	10.49	11.194	10 ± 2	1.21	1.321
IEEE 802.11n HT40	2422	10.10	10.233	10 ± 2	1.21	1.321
	2437	10.27	10.641	10 ± 2	1.21	1.321
	2452	7.98	6.281	7 ± 2	1.21	1.321

4、Calculated Result and Limit

4.1 Antenna a

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	18	1.21	1.321	0.01659	1	Compiles
IEEE 802.11g	14	1.21	1.321	0.00660	1	Compiles
IEEE 802.11n HT20	14	1.21	1.321	0.00660	1	Compiles
IEEE 802.11n HT40	11	1.21	1.321	0.00331	1	Compiles

4.2 Antenna b

Mode	Target power (dBm)	Antenna gain		Power Density (S) (mW/cm ²)	Limited of Power Density (S) (mW/cm ²)	Test Result
		(dBi)	(Linear)			
IEEE 802.11b	19	1.21	1.321	0.02088	1	Compiles
IEEE 802.11g	15	1.21	1.321	0.00831	1	Compiles
IEEE 802.11n HT20	15	1.21	1.321	0.00831	1	Compiles
IEEE 802.11n HT40	12	1.21	1.321	0.00417	1	Compiles

4.3 Antenna a+b

Mode	Power Density (S) (mW/cm ²) Antenna 0	Power Density (S) (mW/cm ²) Antenna 1	Power Density (S) (mW/cm ²) Total	Limited of Power Density (S) (mW/cm ²)	Test Result
IEEE 802.11n HT20	0.00660	0.00831	0.01491	1	Compiles
IEEE 802.11n HT40	0.00331	0.00471	0.00748	1	Compiles