EMC TEST REPORT

Report No.:	SET2015-08706
Product Name:	EYE1
FCC ID:	2AE44EYE1
Model No. :	EYE1
Applicant:	Sioeye LLC
Address:	4265 San Felipe #1100 Houston TX 77027 USA
Received Date:	2015-06-02
Tested Date:	2015-06-03—2015-06-17

Issued by:	CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd.
Lab Location:	Electronic Testing Building, Shahe Road, Xili, Nanshan District, Shenzhen, 518055, P. R. China
	Tel: 86 755 26627338 **Fax:** 86 755 26627238

This test report consists of **21** pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CCIC-SET. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CCIC-SET within 20 days since the date when the report is received. It will not be taken into consideration beyond this limit.

Test Report

Product Name ..... :	EYE1
Model No. ..... :	EYE1
Applicant ..... :	Sioeye LLC
Applicant Address ..... :	4265 San Felipe #1100 Houston TX 77027 USA
Manufacturer ..... :	CK Telecom Limited
Manufacturer Address ..... :	Technology Road.High-Tech Development Zone. Heyuan, Guangdong,P.R.China.
Test Standards ..... :	47 CFR Part 15 Subpart B: Radio Frequency Devices
Test Result ..... :	PASS
Tested by ..... :	Xiao long zhang 2015.06.19 Xiaolong Zhang, Test Engineer
Reviewed by ..... :	Shuangwen zhang 2015.06.19 Shuangwen Zhang, Senior Engineer
Approved by ..... :	Wu Lian 2015.06.19 Wu Li'an, Manager

TABLE OF CONTENTS

1. GENERAL INFORMATION 4

1.1 EUT Description 4

1.2 Test Standards and Results 5

1.3 Facilities and Accreditations 6

1.3.1 Facilities 6

1.3.2 Test Environment Conditions 6

1.3.3 Measurement Uncertainty 6

2. TEST CONDITIONS SETTING 7

2.1 Test Peripherals 7

2.2 Test Mode 7

2.3 Test Setup and Equipments List 8

2.3.1 Conducted Emission 8

2.3.2 Radiated Emission 8

3. 47 CFR PART 15B REQUIREMENTS 11

3.1 Conducted Emission 11

3.1.1 Requirement 11

3.1.2 Test Description 11

3.1.3 Test Result 11

3.2 Radiated Emission 14

3.2.1 Requirement 14

3.2.2 Test Description 15

3.2.3 Test Result 15

4. PHOTOGRAPHS OF THE EUT 19

5. PHOTOGRAPHS OF THE TEST SET-UP 20

Change History		
Issue	Date	Reason for change
1.0	2015.06.19	First edition

1. GENERAL INFORMATION

1.1 EUT Description

EUT Name ..... :	EYE1	
FCC ID ..... :	2AE44EYE1	
Trade Name……..:	SIOEYE	
Brand Name……:	SIOEYE	
Hardware Version ..... :	HICAM-V2.0	
Software Version ..... :	HICAM01A-S10A_Sioeye_L2EN_140_150618	
Power Supply ..... :	Battery	
	Brand Name:	SIOEYE
	Model No.:	EYE1
	Capacitance:	1160 mAh
	Rated Voltage:	3.7V
	Charge Limit:	4.2V
Ancillary Equipment 1 ..... :	USB Cable	

Note1:The EUT is a EYE1, it supports the following operating frequency band: WCDMA850/1900,GPS, 802.11b,802.11g,802.11n/20M,802.11n/40M and bluetooth4.0,LTE 4,17.

Note2:The EUT is equipped with a T-Flash card slot; equipped with a USB port which can be connected to the ancillary equipments; equipped with a earphone port.

Note 3:For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.

1.2 Test Standards and Results

The objective of the report is to perform testing according to 47 CFR Part 15 Subpart B:

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B 2014	Radio Frequency Devices

Test detailed items/section required by FCC rules and results are as below:

No.	Section	Description	Result
1	15.107	Conducted Emission	PASS
2	15.109	Radiated Emission	PASS

NOTE:

(1) The EUT has been tested according to 47 CFR Part 15 Subpart B,Class B.The test procedure is according to ANSI C63.4:2009.

1.3 Facilities and Accreditations

1.3.1 Facilities

CNAS-Lab Code: L1659

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. CCIC is a third party testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L1659. A 12.8*6.8*6.4 (m) fully anechoic chamber was used for the radiated spurious emissions test.

FCC-Registration No.: 406086

CCIC Southern Electronic Product Testing (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 406086, valid time is until October 28, 2017.

1.3.2 Test Environment Conditions

During the measurement, the environmental conditions were within the listed ranges:

Temperature (°C):	15°C - 35°C
Relative Humidity (%):	30% -60%
Atmospheric Pressure (kPa):	86kPa-106kPa

1.3.3 Measurement Uncertainty

The uncertainty is calculated using the methods suggested in the "Guide to the Expression of Uncertainty in Measurement" (GUM) published by ISO.

Uncertainty of Conducted Emission:	Uc = 3.6 dB (k=2)
Uncertainty of Radiated Emission:	Uc = 4.5 dB (k=2)

2. TEST CONDITIONS SETTING

2.1 Test Peripherals

The following is a listing of the EUT and peripherals utilized during the performance of EMC test:

Description	Manufacturer	Model	Serial No.	FCCID /DOC
Notebook	HP	ProBook 6570b	5CB4070N5S	/
Micro SD card	SanDisk	/	/	/
earphone	/	/	A131101551	/
Mouse	Microsoft	1068	/	DOC

2.2 Test Mode

(1) The first test mode

The EUT configuration of the emission tests is TransFlash Card + EUT + Battery + PC.

In this test mode, the EUT with a TransFlash Card embedded is connected with a PC via a USB cable supplied by applicant. During the measurement, the data is transmitting between the PC and the TransFlash Card of the EUT.

(2) The second test mode

The EUT configuration of the emission tests is Internal memory+ EUT + Battery + PC.

In this test mode, the EUT with a Internal memory is connected with a PC via a USB cable supplied by applicant. During the measurement, the data is transmitting between the PC and the Internal memory of the EUT.

NOTE: All test modes are performed, only the worse case（the first test mode）is recorded in this report.

2.3 Test Setup and Equipments List

2.3.1 Conducted Emission

A. Test Setup:



The EUT is placed on a 0.8m high insulating table, which stands on the grounded conducting floor, and keeps 0.4m away from the grounded conducting wall. The EUT is connected to the power mains through a LISN which provides 50Ω/50μH of coupling impedance for the measuring instrument. The Common Antenna is used for the call between the EUT and the System Simulator (SS). A Pulse Limiter is used to protect the measuring instrument. The factors of the whole test system are calibrated to correct the reading.

B. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	ROHDE&SCHWARZ	ESCI	A130901475	2014.09.09	2015.09.08
LISN	ROHDE&SCHWARZ	ENV216	/	2015.04.28	2016.04.27
Cable	MATCHING PAD	W7	/	2015.06.05	2016.06.04

2.3.2 Radiated Emission

A. Test Setup:

1) For radiated emissions from 30MHz to1GHz



2) For radiated emissions above 1GHz



B. Test Procedure

The test is performed in a 3m Semi-Anechoic Chamber; the antenna factor, cable loss and so on of the site (factors) is calculated to correct the reading. The EUT is placed on a 0.8m high insulating Turn Table, and keeps 3m away from the Test Antenna, which is mounted on a

variable-height antenna master tower.

For the test Antenna:

1) In the frequency range above 30MHz, Bi-Log Test Antenna (30MHz to 1GHz) and Horn Test Antenna (above 1GHz) are used. Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength. The emission levels at both horizontal and vertical polarizations should be tested.

C. Equipments List:

Description	Manufacturer	Model	Serial No.	Calibration Date	Calibration Due. Date
Test Receiver	ROHDE&SCHWARZ	ESIB7	A0501375	2015.06.10	2016.06.09
Test Receiver	ROHDE&SCHWARZ	ESIB26	A0304218	2015.06.10	2016.06.09
Semi-Anechoic Chamber	Albatross	9m*6m*6m	A0412372	2015.03.22	2016.03.21
Test Antenna - Bi-Log	HP	CBL6111A	A9704202	2015.06.10	2016.06.09
Test Antenna – Horn	ROHDE&SCHWARZ	HF906	A0304225	2015.06.10	2016.06.09
Anechoic Chamber	Albatross	SAC-5MAC 12.8x6.8x6.4m	A0304210	2015.03.22	2016.03.21
Amplifier 1G~18GHz	ROHDE&SCHWARZ	MITEQ AFS42-00101800	A0509366	2015.06.10	2016.06.09
Amplifier 20M~3GHz	Compliance Direction System	PAP-0203H	A0509377	2015.06.10	2016.06.09
Cable	SUNHNER	SUCOFLEX 100	/	2015.06.10	2016.06.09
Cable	SUNHNER	SUCOFLEX 104	MY1758/4	2015.06.10	2016.06.09

3. 47 CFR PART 15B REQUIREMENTS

3.1 Conducted Emission

3.1.1 Requirement

According to FCC section 15.107, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50μH/50Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

NOTE:

a) The limit subjects to the Class B digital device.

b) The lower limit shall apply at the band edges.

c) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.1.2 Test Description

See section 2.3.1 of this report.

3.1.3 Test Result

The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. All test modes are considered, refer to recorded points and plots below.

A. Test Plot and Suspicious Points:



(Plot A: L Phase)

Conducted Disturbance at Mains Terminals							
L Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.1635	56.30	54.91	1.39	0.1635	55.30	39.52	15.78
0.2175	62.90	51.74	11.16	0.2175	52.90	37.21	15.69
0.2715	61.10	47.23	13.87	0.2715	51.10	35.38	15.72



(Plot B: N Phase)

Conducted Disturbance at Mains Terminals							
N Test Data							
QP				AV			
Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)	Frequency (MHz)	Limits (dBµV)	Measurement Value (dBµV)	Margin (dB)
0.1635	65.30	56.95	8.35	0.1635	55.30	40.53	14.77
0.2175	62.90	52.80	10.10	0.2175	52.90	37.23	15.67
0.2715	61.10	50.85	10.25	0.2715	51.10	35.97	15.13

Test Result: PASS

3.2 Radiated Emission

3.2.1 Requirement

According to FCC section 15.109, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency range (MHz)	Field Strength		Field Strength Limitation at 3m Measurement Dist	
	μV/m	Dist	(uV/m)	(dBuV/m)
0.009 - 0.490	2400/F(kHz)	300m	10000* 2400/F(kHz)	20log 2400/F(kHz) + 80
0.490 - 1.705	2400/F(kHz)	30m	100* 2400/F(kHz)	20log 2400/F(kHz) + 40
1.705 - 30.00	30	30m	100*30	20log 30 + 40
30.0 - 88.0	100	3m	100	20log 100
88.0 - 216.0	150	3m	150	20log 150
216.0 - 960.0	200	3m	200	20log 200
Above 960.0	500	3m	500	20log 500

a) As shown in FCC section 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector. When average radiated emission measurements are specified in this part, including emission measurements below 1000MHz, there also is a limit on the radio frequency emissions, as measured using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit for the frequency being investigated unless a different peak emission limit is otherwise specified in the rules.

b) Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

c) For below 1G :QP detector RBW 120kHz ,VBW 300kHz.

d) For Above 1G: PK detector RBW 1MHz,VBW 3MHz for PK value ;PK detector RBW 1MHz, VBW 10Hz for AV value.

Note:

1) The tighter limit shall apply at the boundary between two frequency range.
2) Limitation expressed in dBuV/m is calculated by 20log Emission Level(uV/m).
3) If measurement is made at 3m distance, then F.S Limitation at 3m distance is adjusted by using the formula of $Ld1 = Ld2 * (d2/d1)^{2.}$
   Example:
   F.S Limit at 30m distance is 30uV/m, then F.S Limitation at 3m distance is adjusted as
   $Ld1 = L1 = 30uV/m * (10)^2 = 100 * 30uV/m.$

3.2.2 Test Description

See section 2.3.2 of this report.

3.2.3 Test Result

The maximum radiated emission is searched using PK, QP and AV detectors; the emission levels more than the limits, and that have narrow margins from the limits will be re-measured with AV and QP detectors. Both the vertical and the horizontal polarizations of the Test Antenna are considered to perform the tests. All test modes are considered, refer to recorded points and plots below.

The amplitude of spurious emissions which are attenuated more than 20 dB below the permissible value need not be reported.

Note: All radiated emission tests were performed in X, Y, Z axis direction, and only the worst axis test condition was recorded in this test report.

B. Test Plots and Suspicious Points:



(Plot C: Test Antenna Vertical 30M - 1G)

Frequency (MHz)	QuasiPeak (dB μ V/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dB μ V/m)	Margin (dB)	Antenna	Verdict
30.0000	33.59	120.000	170.0	40.00	6.41	Vertical	Pass
358.3900	40.15	120.000	180.0	46.00	5.85	Vertical	Pass
795.3600	39.25	120.000	215.0	46.00	6.75	Vertical	Pass



(Plot D: Test Antenna Horizontal 30M - 1G)

Frequency (MHz)	QuasiPeak (dBμV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBμV/m)	Margin (dB)	Antenna	Verdict
206.1500	36.25	120.000	205.0	43.50	7.25	Horizontal	Pass
358.3900	42.36	120.000	185.0	46.00	3.64	Horizontal	Pass
795.3600	39.32	120.000	165.0	46.00	6.68	Horizontal	Pass



(Plot E: Test Antenna Horizontal 1G – 6G)

Frequency (MHz)	PK/AV (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
1110.1400	30.63	1000.000	170.0	54.00	23.37	Horizontal	Pass
1650.1320	31.75	1000.000	200.0	54.00	22.25	Horizontal	Pass
2969.3140	33.55	1000.000	250.0	54.00	20.45	Horizontal	Pass
1110.1400	40.68	1000.000	180.0	74.00	33.32	Horizontal	Pass
1650.1320	43.03	1000.000	150.0	74.00	30.97	Horizontal	Pass
2969.3140	46.56	1000.000	150.0	74.00	27.44	Horizontal	Pass



(Plot F: Test Antenna Vertical 1G – 6G)

Frequency (MHz)	PK/AV (dBµV/m)	Bandwidth (kHz)	Antenna height (cm)	Limit (dBµV/m)	Margin (dB)	Antenna	Verdict
1105.16032	30.09	1000.000	250.0	54.00	23.91	Vertical	Pass
2431.76352	32.70	1000.000	210.0	54.00	21.30	Vertical	Pass
2861.74549	33.65	1000.000	190.0	54.00	20.35	Vertical	Pass
1105.16032	40.46	1000.000	150.0	74.00	33.54	Vertical	Pass
2431.76352	45.78	1000.000	245.0	74.00	28.22	Vertical	Pass
2861.74549	46.10	1000.000	155.0	74.00	27.90	Vertical	Pass

Test Result: PASS

4. PHOTOGRAPHS OF THE EUT

5. PHOTOGRAPHS OF THE TEST SET-UP



Conducted Emission



Radiated Emission of 30M-1G



Radiated Emission of 1-6G

** END OF REPORT **