



Shenzhen GTI Technology Co., Ltd.

1F,2 Block, Jiaquan Building, Guanlan High-tech Park Baoan District,
Shenzhen, Guangdong, China.

Tel: +86-755-27559792

Fax: +86-755-86116468

Report No.: GTI20160197F-4

Page 1 of 17

FCC TEST REPORT

Product name.....: Tablet PC

Trademark: /

Model/Type reference: A723G

Listed Model(s): See the page 6

FCC ID.....: 2AEB5-A723

Test Standards: **47 CFR FCC Part 15 Subpart B - Unintentional Radiators**
ANSI C63.4: 2014

Applicant: AOC

Address of applicant: 14F-5, NO.258, Liancheng Rd., Zhonghe Dist., New Taipei
City, Taiwan

Date of Receipt: Mar. 05, 2016

Date of Test Date.....: Mar. 05, 2016- Mar. 11, 2016


Data of issue.: Mar. 11, 2016

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified above


GENERAL DESCRIPTION OF EUT	
Equipment:	Tablet PC
Model Name:	A723G
Manufacturer:	Shenzhen KTC Technology Co., Ltd.
Manufacturer Address:	Northern Wuhe Road, Gangtoubuji, Longgang, Shenzhen, China
Power Rating:	DC 3.7V from 2700mAh by rechargeable battery DC 5.0V from Adapter

Compiled By:




(Sevin Li)

Reviewed By:



(Tony Wang)

Approved By:



(Walter Chen)

This test report consists of 17 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by GTI. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of compiler, reviewer and approver. Any objections must be raised to GTI within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.



Table of Contents

Page

1. SUMMARY.....	4
1.1 TEST STANDARDS.....	4
1.2 TEST DESCRIPTION	4
1.3 TEST FACILITY.....	4
1.4 MEASUREMENT UNCERTAINTY	4
2. GENERAL INFORMATION.....	6
2.1 ENVIRONMENTAL CONDITIONS	6
2.2 GENERAL DESCRIPTION OF EUT	6
2.3 DESCRIPTION OF TEST MODES.....	7
2.4 DESCRIPTION OF PERIPHERAL DURING TESTING.....	7
2.5 MEASUREMENT INSTRUMENTS LIST.....	8
3. EMC EMISSION TEST	9
3.1 CONDUCTED EMISSION MEASUREMENT	9
3.2 RADIATED EMISSION	12
4. EUT TEST PHOTO	16
5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL	17

1. SUMMARY

1.1 Test Standards

The tests were performed according to following standards:

47 CFR FCC Part 15 Subpart B - Unintentional Radiators

ANSI C63.4: 2014 – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40GHz

1.2 Test Description

Emission Measurement requirements		
Radiated Emission	Part15.109	PASS
Conducted Disturbance	Part15.107	PASS

Remark: The measurement uncertainty is not included in the test result.

1.3 Test Facility

1.3.1 Address of the test laboratory

Shenzhen General Testing & Inspection Technology Co., Ltd.

Add: 1F, 2 Block, Jiaquan Building, Guanlan High-tech Park Baoan District, Shenzhen, Guangdong, China.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9783A

The 3m alternate test site of Shenzhen GTI Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Aug, 2011.

FCC-Registration No.: 214666

Shenzhen GTI Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 214666, Sep 19, 2011

1.4 Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements and is documented in the Shenzhen General Testing & Inspection Technology Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.



Hereafter the best measurement capability for General Testing & Inspection laboratory is reported:

A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U(dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	3.2	

B. Radiated Measurement:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.7 dB	(1)
Radiated Emission	1~18GHz	5.0 dB	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

2. GENERAL INFORMATION

2.1 Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101KPa

2.2 General Description of EUT

Product Name:	Tablet PC
Model/Type reference:	A723G
List Model:	700P***, &&700*****
Model difference:	700P*** (1st* could be 0-99 or A-Z, means different client code; 2nd* could be 0-99 or A-Z or blank, stands for the shape or color of enclosure, no impact on Products safety and EMC characteristics); &&700*****(& could be "A-Z" or "a-z", * could be "0-99", "A-Z", "a-z", "-", "/" or blank, means different client code, no impact on Products safety and EMC characteristics
Power supply:	DC 3.7V from battery, 2700mAh Battery model: 338085
Adapter1 information:	Model: EP29-05015WULZ Input: 100-240, 50/60Hz, 0.35Max Output: 5V ---1500mA
Adapter2 information:	Model: SA69-050150U Input: 100-240, 50/60Hz, 0.30Max Output: 5V ---1500mA
Hardware version:	V10
Software version:	V5.1

Note: For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.

2.3 Description of Test Modes

Frequency range investigated: conduction 150 kHz to 30 MHz; according to 15.33(b), radiation 30MHz-6GHz(30MHz to the 5th harmonic of the highest fundamental frequency).

The Highest operation frequency is 1.2GHz

The device was a Table PC. As the function of the EUT, the operation mode selected to test as follow:

Test Mode	Function	Description
1	USB Data Transfer	Link PC+ WIFI Idle + BT Idle + GPS RX
2	PC Operation	PC Operation + Adapter1
3	PC Operation	PC Operation + Adapter2
Remark: Link with PC means data application transferred mode between EUT and PC		

Test Item	EUT Configure Mode
AC Conducted Emission	Mode 1
Radiated Emissions <1GHz	Mode 1
Radiated Emissions $\geq$ 1GHz	Mode 1

2.4 Description of Peripheral during Testing

No.	Product	Manufacturer	Serial No.	Certification
1	PC	Lenovo	H435	DOC
2	PC Power Supply	Bestec	ATX-250-12Z	DOC
3	Display	DELL	U2412M	DOC
4	Printer	HP	PJ1008	DOC
5	USB Flash	TRANSCEND	TS2GJFV30	DOC
6	Mouse	DELL	N889	DOC
7	Keyboard	DELL	SK-8185	DOC

2.5 Measurement Instruments List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Jan 04,2017
2	LISN	R&S	ENV216	101113	Jan 04,2017
3	EMI Test Receiver	R&S	ESCI	100920	Jan 04,2017
4	Cable	Schwarzbeck	AK9515E	33156	Jan 04,2017

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	EMI Test Receiver	R&S	ESCI	100967	Jan 04,2017
2	Log-Bicon Antenna	Schwarzbeck	CBL6141 A	4180	Jan 04,2017
3	Spectrum Analyzer	Rohde & Schwarz	FSU	100105	Jan 04,2017
4	Horn Antenna	Schwarzbeck	BBHA 9120D	648	Jan 07,2017
5	Pre-Amplifier	HP	8447D	1937A030 50	Jan 04,2017
6	Pre-Amplifier	EMCI	EMC051 835	980075	Jan 04,2017
7	Antenna Mast	UC	UC3000	N/A	N/A
8	Turn Table	UC	UC3000	N/A	N/A
9	Cable Below 1GHz	Schwarzbeck	AK9515E	33155	Jan 04,2017
10	Cable Above 1GHz	Hubersuhner	SUCOFLE X102	DA1580	Jan 04,2017

Note: 1. The Cal. Interval was one year.

3. EMC EMISSION TEST

3.1 Conducted Emission Measurement

LIMIT


For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

FREQUENCY (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 -0.5	79.00	66.00	66 - 56 *	56 - 46 *
0.50 -5.0	73.00	60.00	56.00	46.00
5.0 -30.0	73.00	60.00	60.00	50.00

TEST PROCEDURE

- The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4-2014.
- Support equipment, if needed, was placed as per ANSI C63.4-2014.
- All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4-2014.
- An USB Line connection between the EUT and PC which received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
- All support equipments received AC power from a second LISN, if any.
- The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
- During the above scans, the emissions were maximized by cable manipulation.

TEST SETUP




Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

TEST RESULTS

Test mode:	Mode 1	Polarization:	L
------------	--------	---------------	---

SCAN TABLE: "Vol (9K-30M) FIN-N"

Short Description: 150K-30M Voltage



MEASUREMENT RESULT: "2016030943_fin"

3/9/2016 10:40AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.158000	39.50	9.8	66	26.1	QP	L1	GND
18.170000	37.50	10.8	60	22.5	QP	L1	GND
24.224000	34.60	11.1	60	25.4	QP	L1	GND

MEASUREMENT RESULT: "2016030943_fin2"


3/9/2016 10:40AM

Frequency MHz	Level dBμV	Transd dB	Limit dBμV	Margin dB	Detector	Line	PE
0.250000	35.80	9.7	52	16.0	AV	L1	GND
18.170000	37.40	10.8	50	12.6	AV	L1	GND
24.224000	34.60	11.1	50	15.4	AV	L1	GND

Test mode:	Mode 1	Polarization:	N
------------	--------	---------------	---

SCAN TABLE: "Vol (9K-30M) FIN-N"

Short Description: 150K-30M Voltage


MEASUREMENT RESULT: "2016030944_fin"

3/9/2016 10:44AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.150000	39.00	9.5	66	27.0	QP	N	GND
18.167000	37.90	10.5	60	22.1	QP	N	GND
24.224000	34.20	10.8	60	25.8	QP	N	GND

MEASUREMENT RESULT: "2016030944_fin2"

3/9/2016 10:44AM

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.249000	33.80	9.5	52	18.0	AV	N	GND
18.167000	37.60	10.5	50	12.4	AV	N	GND
24.224000	33.90	10.8	50	16.1	AV	N	GND

3.2 Radiated Emission

LIMITS

LIMITS OF RADIATED EMISSION MEASUREMENT (Below 1000MHz)

FREQUENCY (MHz)	Class A (at 10m)	Class B (at 3m)
	dBuV/m	dBuV/m
30 ~ 88	39.0	40.0
88 ~ 216	43.5	43.5
216 ~ 960	46.5	46.0
Above 960	49.5	54.0

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class A (at 3m) dBuV/m		Class B (at 3m) dBuV/m	
	Peak	Avg	Peak	Avg
Above 1000	80	60	74	54

Notes:

- 1) The limit for radiated test was performed according to as following:
CISPR 22/ FCC PART 15B /ICES-003.
- 2) The tighter limit applies at the band edges.
- 3) Emission level (dBuV/m)=20log Emission level (uV/m).

TEST PROCEDURE

- a) The measuring distance of at 3 m shall be used for measurements at frequency up to 1GHz. For frequencies above 1GHz, any suitable measuring distance may be used.
- b) The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- c) The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured, above 1G Average detector mode will be instead.
- e) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP (AV) Limits and then no additional QP Mode measurement performed.

Note: For the radiated emission test above 1GHz:


Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that

which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.


TEST SETUP

For the actual test configuration, please refer to the related Item –EUT Test Photos.

(A) Radiated Emission Test Set-Up Frequency below 1 GHz




(B) Radiated Emission Test Set-Up Frequency above 1GHz



TEST RESULTS

Test mode:	Mode 1	Polarization:	Horizontal
------------	--------	---------------	------------


Data: 8								
---------	--	--	--	--	--	--	--	--



Trace: (Discrete)


Mark	Frequency MHz	Level dBuV/m	Factor dB/m	Reading dBuV	Limit dBuV/m	Margin dB	Polarization	Detector
1	71.83	31.48	-22.96	54.44	40.00	8.52	HORIZONTAL	Peak
2	199.99	28.38	-17.86	46.24	43.50	15.12	HORIZONTAL	Peak
3	900.15	31.40	-6.92	38.32	46.00	14.60	HORIZONTAL	Peak

Data: 10								
----------	--	--	--	--	--	--	--	--



Trace: (Discrete)

Mark	Frequency MHz	Level dBuV/m	Factor dB/m	Reading dBuV	Limit dBuV/m	Margin dB	Polarization	Detector
1	1395.52	50.23	-13.56	63.79	74.00	23.77	HORIZONTAL	Peak
2	1395.52	32.14	-13.56	45.70	54.00	21.86	HORIZONTAL	Average
3	1501.90	49.89	-13.58	63.47	74.00	24.11	HORIZONTAL	Peak
4	1501.90	29.63	-13.58	43.21	54.00	24.37	HORIZONTAL	Average
5	4988.86	54.88	-4.29	59.17	74.00	19.12	HORIZONTAL	Peak
6	4988.86	39.21	-4.29	43.50	54.00	14.79	HORIZONTAL	Average



4. EUT TEST PHOTO

Conducted Emission



Radiated Emission below 1GHz



Radiated Emission above 1GHz





5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL

Please reference to the test report No.: GTI20160197F-1

*****THE END*****