

FCC RF TEST REPORT

ISSUED BY
Shenzhen BALUN Technology Co., Ltd.



FOR
Tablet

ISSUED TO
AOC

14F-5, NO.258, Liancheng Rd., Zhonghe Dist., New Taipei City, Taiwan



Tested by: Zou Liu
Zou Liu
(Engineer)
Date Oct. 30, 2017

Approved by: Wei Yanquan
Wei Yanquan
(Chief Engineer)
Date Oct. 30, 2017

Report No.: BL-SZ1780425-601
EUT Name: Tablet
Model Name: A731T
Brand Name: AOC
Test Standard: 47 CFR Part 15 Subpart C
FCC ID: 2AEB5-A726W

Test conclusion: Pass
Test Date: Sep. 06, 2017 ~ Oct. 11, 2017
Date of Issue: Oct. 30, 2017

NOTE: This test report of test results only related to testing samples, which can be duplicated completely for the legal use with the approval of the applicant; it shall not be reproduced except in full, without the written approval of Shenzhen BALUN Technology Co., Ltd. BALUN Laboratory. Any objections should be raised within thirty days from the date of issue. To validate the report, please contact us.

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Oct. 30, 2017</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	ADMINISTRATIVE DATA (GENERAL INFORMATION)	6
1.1	Identification of the Testing Laboratory	6
1.2	Identification of the Responsible Testing Location	6
1.3	Laboratory Condition	6
1.4	Announce	6
2	PRODUCT INFORMATION	7
2.1	Applicant Information	7
2.2	Manufacturer Information	7
2.3	Factory Information	7
2.4	General Description for Equipment under Test (EUT)	7
2.5	Ancillary Equipment	8
2.6	Technical Information	9
2.7	Additional Instructions	10
3	SUMMARY OF TEST RESULTS	11
3.1	Test Standards	11
3.2	Verdict	12
4	GENERAL TEST CONFIGURATIONS	13
4.1	Test Environments	13
4.2	Test Equipment List	13
4.3	Measurement Uncertainty	15
4.4	Description of Test Setup	16
4.4.1	For Antenna Port Test	16
4.4.2	For AC Power Supply Port Test	16
4.4.3	For Radiated Test (Below 30 MHz)	17

4.4.4	For Radiated Test (30 MHz-1 GHz)	17
4.4.5	For Radiated Test (Above 1 GHz).....	18
4.5	Measurement Results Explanation Example.....	19
4.5.1	For conducted test items:	19
4.5.2	For radiated band edges and spurious emission test:.....	19
5	TEST ITEMS.....	20
5.1	Antenna Requirements.....	20
5.1.1	Relevant Standards	20
5.1.2	Antenna Anti-Replacement Construction	21
5.1.3	Antenna Gain	21
5.2	Number of Hopping Frequencies	22
5.2.1	Limit.....	22
5.2.2	Test Setup	22
5.2.3	Test Procedure	22
5.2.4	Test Result	22
5.3	Peak Output Power and E.I.R.P.....	23
5.3.1	Test Limit.....	23
5.3.2	Test Setup	23
5.3.3	Test Procedure	23
5.3.4	Test Result	23
5.4	Occupied Bandwidth	24
5.4.1	Limit.....	24
5.4.2	Test Setup	24
5.4.3	Test Procedure	24
5.4.4	Test Result	24
5.5	Carrier Frequency Separation	25
5.5.1	Limit.....	25
5.5.2	Test Setup	25
5.5.3	Test Procedure	25
5.5.4	Test Result	25

5.6	Time of Occupancy (Dwell time)	26
5.6.1	Limit.....	26
5.6.2	Test Setup	26
5.6.3	Test Procedure	26
5.6.4	Test Result	26
5.7	Conducted Spurious Emission & Authorized-band band-edge	27
5.7.1	Limit.....	27
5.7.2	Test Setup	27
5.7.3	Test Procedure	27
5.7.4	Test Result	27
5.8	Conducted Emission	28
5.8.1	Limit.....	28
5.8.2	Test Setup	28
5.8.3	Test Procedure	28
5.8.4	Test Result	28
5.9	Radiated Spurious Emission	29
5.9.1	Limit.....	29
5.9.2	Test Setup	29
5.9.3	Test Procedure	29
5.9.4	Test Result	30
5.10	Band Edge (Restricted-band band-edge).....	31
5.10.1	Limit.....	31
5.10.2	Test Setup	31
5.10.3	Test Procedure	31
5.10.4	Test Result	31
ANNEX A	TEST RESULT	32
A.1	Number of Hopping Frequency	32
A.2	Peak Output Power and E.I.R.P	33
A.3	20 dB and 99% bandwidth	36
A.4	Hopping Frequency Separation.....	39

A.5	Average Time of Occupancy	40
A.6	Conducted Spurious Emissions & Authorized-band band-edge	42
A.7	Conducted Emissions.....	49
A.8	Radiated Spurious Emission	51
A.9	Band Edge (Restricted-band band-edge).....	60
ANNEX B	TEST SETUP PHOTOS	63
ANNEX C	EUT EXTERNAL PHOTOS	63
ANNEX D	EUT INTERNAL PHOTOS	63

1 ADMINISTRATIVE DATA (GENERAL INFORMATION)

1.1 Identification of the Testing Laboratory

Company Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Identification of the Responsible Testing Location

Test Location	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1st FL, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 11524A-1. The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196. The laboratory is a testing organization accredited by American Association for Laboratory Accreditation(A2LA) according to ISO/IEC 17025.The accreditation certificate is 4344.01. The laboratory is a testing organization accredited by China National Accreditation Service for Conformity Assessment (CNAS) according to ISO/IEC 17025. The accreditation certificate number is L6791.
Description	All measurement facilities used to collect the measurement data are located at Block B, FL 1, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China 518055

1.3 Laboratory Condition

Ambient Temperature	20 to 25°C
Ambient Relative Humidity	45% - 55%
Ambient Pressure	100 kPa - 102 kPa

1.4 Announce

- (1) The test report reference to the report template version v5.8.
- (2) The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
- (3) The test report is invalid if there is any evidence and/or falsification.
- (4) The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
- (5) This document may not be altered or revised in any way unless done so by BALUN and all revisions are duly noted in the revisions section.
- (6) Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	AOC
Address	14F-5, NO.258, Liancheng Rd., Zhonghe Dist., New Taipei City, Taiwan

2.2 Manufacturer Information

Manufacturer	Shenzhen Chiptrip Technology Co., Ltd
Address	2nd floor, No.12, Chuangke Town , University Town, Taoyuan Street, Nanshan District, Shenzhen, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Type	Tablet
Model Name Under Test	A731T
Series Model Name	A731T, E732,A726W
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only different on Touch capacitance, Android version and CPU.
Hardware Version	F71NB-V02
Software Version	6.0.1
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A
Network and Wireless connectivity	Bluetooth 2.1 (BR) WIFI 802.11b, 802.11g and 802.11n (HT20)

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	AOC
	Model No.	A726
	Serial No.	N/A
	Capacitance	2500 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	4.2 V
Ancillary Equipment 2	Adapter	
	Brand Name	N/A
	Model No.	WLC0510UU
	Serial No.	N/A
	Rated Input	100-240 V~, 0.2 A, 50/60 Hz
	Rated Output	5 V=, 1.0 A
Ancillary Equipment 3	USB Cable	
	Length (Approx.)	0.8 m

2.6 Technical Information

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8-DPSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	DH5: 1 Mbps 2DH5: 2 Mbps 3DH5: 3 Mbps
Frequency Range	The frequency range used is 2400 MHz to 2483.5 MHz.
Number of channel	79 (at intervals of 1 MHz)
Tested Channel	0 (2402 MHz), 39 (2441 MHz), 78 (2480 MHz)
Antenna Type	PIFA Antenna
Antenna Gain	2.5 dBi (In test items related to antenna gain, the final results reflect this figure.)
Antenna System(MIMO Smart Antenna)	N/A

All channel was listed on the following table:

Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)	Channel number	Freq. (MHz)
0	2402	21	2423	42	2444	63	2465
1	2403	22	2424	43	2445	64	2466
2	2404	23	2425	44	2446	65	2467
3	2405	24	2426	45	2447	66	2468
4	2406	25	2427	46	2448	67	2469
5	2407	26	2428	47	2449	68	2470
6	2408	27	2429	48	2450	69	2471
7	2409	28	2430	49	2451	70	2472
8	2410	29	2431	50	2452	71	2473
9	2411	30	2432	51	2453	72	2474
10	2412	31	2433	52	2454	73	2475
11	2413	32	2434	53	2455	74	2476
12	2414	33	2435	54	2456	75	2477
13	2415	34	2436	55	2457	76	2478
14	2416	35	2437	56	2458	77	2479
15	2417	36	2438	57	2459	78	2480
16	2418	37	2439	58	2460	-	-
17	2419	38	2440	59	2461	-	-
18	2420	39	2441	60	2462	-	-
19	2421	40	2442	61	2463	-	-
20	2422	41	2443	62	2464	-	-


2.7 Additional Instructions

EUT Software Settings:

Mode	☒ Bluetooth test mode loop back enabled. EUT is controlled over CBT / CMU.
------	---

Power level setup in software			
Test Software Version	adb		
Support Units (Software installation media)	Description	Manufacturer	Model
	Laptop	Lenovo	X220
Mode	Channel	Frequency (MHz)	Soft Set
DH5	CH0	2402	TX LEVEL is built-in set parameters and cannot be changed and selected.
	CH39	2441	
	CH78	2480	
2DH5	CH0	2402	
	CH39	2441	
	CH78	2480	
3DH5	CH0	2402	
	CH39	2441	
	CH78	2480	

Run Software:



```

C:\Windows\system32\cmd.exe - adb shell
Microsoft Windows [版本 6.1.7601]
版权所有 (c) 2009 Microsoft Corporation。保留所有权利。

C:\Users\xufeng.luo>adb root
error: device not found

C:\Users\xufeng.luo>adb shell
root@rk312x:/ # rtlbtmp
rtlbtmp
::::::::::::::::::::::::::::::::::::::::::::::::::::::::::
::::::::: Bluetooth MP Test Tool Starting ::::::::::
> enable uart:/dev/ttyS1
enable uart:/dev/ttyS1
> enable[Success:0]
ht_mp_Exec 1
ht_mp_Exec 1
ht_mp_Exec[Success:0]
> ht_mp_Exec,1,0x00
ht_mp_Exec 1
ht_mp_Exec 1
ht_mp_Exec[Success:0]
> ht_mp_Exec,1,0x00

```

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C (10-1-15 Edition)	Miscellaneous Wireless Communications Services
2	FCC PUBLIC NOTICE DA 00-705 (Mar. 30, 2000)	Filling and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems
3	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices

3.2 Verdict

No.	Description	FCC Part No.	ISED Part No.	Channel	Test Result	Verdict	Remark
1	Antenna Requirement	15.203	RSS-247, 5.4 (6)	N/A	--	Pass	Note ¹
2	Number of Hopping Frequencies	15.247(a)	RSS-247, 5.1 (4)	Hopping Mode	ANNEX A.1	Pass	Note ²
3	Peak Output Power and E.I.R.P	15.247(b)	RSS-247, 5.4 (2)	Low/Middle/High	ANNEX A.2	Pass	--
4	Occupied Bandwidth	15.247(a)	RSS-247, 5.1 (1)	Low/Middle/High	ANNEX A.3	Pass	Note ²
5	Carrier Frequency Separation	15.247(a)	RSS-247, 5.1 (2)	Hopping Mode	ANNEX A.4	Pass	Note ²
6	Time of Occupancy (Dwell time)	15.247(a)	RSS-247, 5.1 (4)	Hopping Mode	ANNEX A.5	Pass	Note ²
7	Conducted Spurious Emission & Authorized-band band-edge	15.247(d)	RSS-247, 5.5	Low/Middle/High	ANNEX A.6	Pass	Note ²
8	Conducted Emission	15.207	RSS-GEN, 8.8	Low/Middle/High	ANNEX A.7	Pass	Note ²
9	Radiated Spurious Emission	15.209 15.247(d)	RSS-247, 5.5	Hopping Mode, Low/Middle/High	ANNEX A.8	Pass	Note ²
10	Band Edge(Restricted-band band-edge)	15.209 15.247(d)	RSS-247, 5.5	Hopping Mode, Low/Middle/High	ANNEX A.9	Pass	Note ²
11	Receiver Spurious Emissions	--	RSS-Gen, 7.1.2	--	--	N/A	Note ³

Note ¹: Please refer to section 5.1

Note ²: Because of the modulation of $\Pi/4$ -DQPSK same as 8-DPSK, and the test results are basically the same with them, so we chose 8-DPSK as a typical representative to appear on the report. Another we will show all the modes on the RF output power test item

Note ³: Only radio communication receivers operating in stand-alone mode within the band 30-960 MHz, as well as scanner receivers, are subject to Industry Canada requirements, so this test is not applicable.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	45% - 55%	
Atmospheric Pressure	100 kPa - 102 kPa	
Temperature	NT (Normal Temperature)	+22°C to +25°C
Working Voltage of the EUT	NV (Normal Voltage)	5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	ROHDE&SCHWARZ	FSV-30	103118	2017.06.22	2018.06.21
Switch Unit with OSP-B157	ROHDE&SCHWARZ	OSP120	101270	2017.06.22	2018.06.21
EMI Receiver	KEYSIGHT	N9038A	MY53220118	2017.09.07	2018.09.06
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2017.06.22	2018.06.21
LISN	SCHWARZBECK	NSLK 8127	8127-687	2017.06.22	2018.06.21
Bluetooth Tester	ROHDE&SCHWARZ	CBT	101005	2017.06.22	2018.06.21
Power Splitter	KMW	DCPD-LDC	1305003215	--	--
Power Sensor	ROHDE&SCHWARZ	NRP-Z21	103971	2017.06.22	2018.06.21
Attenuator (20 dB)	KMW	ZA-S1-201	110617091	--	--
Attenuator (6 dB)	KMW	ZA-S1-61	1305003189	--	--
DC Power Supply	ROHDE&SCHWARZ	HMP2020	018141664	2017.06.22	2018.06.21
Temperature Chamber	ANGELANTIONI SCIENCE	NTH64-40A	1310	2017.06.22	2018.06.21
Test Antenna-Loop(9 kHz-30 MHz)	SCHWARZBECK	FMZB 1519	1519-037	2017.06.22	2018.06.21
Test Antenna-Bi-Log(30 MHz-3 GHz)	SCHWARZBECK	VULB 9163	9163-624	2017.06.22	2018.06.21
Test Antenna-Horn(1-18 GHz)	SCHWARZBECK	BBHA 9120D	9120D-1148	2017.06.22	2018.06.21
Test Antenna-Horn(15-26.5 GHz)	SCHWARZBECK	BBHA 9170	9170-305	2017.06.22	2018.06.21
Test Antenna-Horn (18-40 GHz)	A-INFO	LB-180400KF	J211060273	N/A	2018.01.06
Anechoic Chamber	RAINFORD	9m*6m*6m	N/A	2017.02.24	2019.02.23
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	N/A	2016.08.09	2018.08.08
Shielded Enclosure	ChangNing	CN-130701	130703	--	--
Signal Generator	ROHDE&SCHWARZ	SMB100A	177746	2017.06.22	2018.06.21

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Power Amplifier	OPHIR RF	5225F	1037	2017.02.17	2018.02.16
Power Amplifier	OPHIR RF	5273F	1016	2017.02.17	2018.02.16
Directional Coupler	Werlantone	C5982-10	109275	N/A	N/A
Directional Coupler	Werlantone	CHP-273E	S00801z-01	N/A	N/A
Feld Strength Meter	Narda	EP601	511WX5112 9	2017.02.23	2018.02.22
Mouth Simulator	B&K	4227	2423931	2016.11.15	2017.11.14
Sound Calibrator	B&K	4231	2430337	2016.11.09	2017.11.08
Sound Level Meter	B&K	NL-20	00844023	2016.11.11	2017.11.10
Ear Simulator	B&K	4185	2409449	2016.11.15	2017.11.14
Ear Simulator	B&K	4195	2418189	2016.11.15	2017.11.14
Audio analyzer	B&K	UPL 16	100129	2016.11.08	2017.11.07

4.3 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Measurement	Value
Occupied Channel Bandwidth	$\pm 4\%$
RF output power, conducted	± 1.4 dB
Power Spectral Density, conducted	± 2.5 dB
Unwanted Emissions, conducted	± 2.8 dB
All emissions, radiated	± 5.4 dB
Temperature	$\pm 1^{\circ}\text{C}$
Humidity	$\pm 4\%$


4.4 Description of Test Setup

4.4.1 For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.4.2 For AC Power Supply Port Test




(Diagram 2)

4.4.3 For Radiated Test (Below 30 MHz)




(Diagram 3)

4.4.4 For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.4.5 For Radiated Test (Above 1 GHz)



(Diagram 5)

4.5 Measurement Results Explanation Example

4.5.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.5.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b); RSS-247, 5.4 (6)


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	The antenna is welded on the mainboard, can't be replaced by the consumer

Reference Documents	Item
Photo	 The top photograph shows a close-up of a circuit board (mainboard) with a red square box highlighting a specific component. A red arrow points from the text 'RF Chip' to this component. The bottom photograph shows a black rectangular component, likely the antenna, with a red square box highlighting it. A red arrow points from the text 'Antenna' to this component. The component has the text 'SOUTH STAR A726-WIFI' printed on it.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequencies

5.2.1 Limit

FCC §15.247(a) (1) (iii); RSS-247, 5.1 (4)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.4 Test Result

Please refer to ANNEX A.1.

5.3 Peak Output Power and E.I.R.P

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

RSS-247, 5.4 (2)

For FHSs operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W and the e.i.r.p. shall not exceed 4 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W and the e.i.r.p. shall not exceed 0.5 W if the hopset uses less than 75 hopping channels (see Section 5.4(5) for exceptions).

5.3.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.3.3 Test Procedure

The Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.

5.3.4 Test Result

Please refer to ANNEX A.2.

5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a); RSS-247, 5.1 (1)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW = in the range of 1% to 5% of the OBW

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Please refer to ANNEX A.3.

5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a); RSS-247, 5.1 (2)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq 1\%$ of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Please refer to ANNEX A.4.

5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a); RSS-247, 5.1 (4)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

For DH1 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 2) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH3 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 4) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

For DH5 package type

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * (1600 / 6) / \{\text{Number of Hopping Frequency}\} * \{\text{Period}\}$$

$$\{\text{Period}\} = 0.4 \text{ s} * \{\text{Number of Hopping Frequency}\}$$

The lowest, middle and highest channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.

5.6.4 Test Result

Please refer to ANNEX A.5

5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d); RSS-247, 5.5

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.4.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Please refer to ANNEX A.6.

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207; RSS-GEN, 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.4.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX B.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. A device rated for 50/60 Hz operation need not be tested at both frequencies provided the radiated and line conducted emissions are the same at both frequencies.

5.8.4 Test Result

Please refer to ANNEX A.7.

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d); RSS-247, 5.5

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	$2400/F(\text{kHz})$	300
0.490 - 1.705	$24000/F(\text{kHz})$	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength ($\text{dB}\mu\text{V}/\text{m}$) = $20 \cdot \log[\text{Field Strength } (\mu\text{V}/\text{m})]$.
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: $54\text{dB}\mu\text{V}/\text{m}@3\text{m}$ (AV) and $74\text{dB}\mu\text{V}/\text{m}@3\text{m}$ (PK).

5.9.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Please refer to ANNEX A.8.

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.10.2 Test Setup

See section 4.4.3 to 4.4.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX B.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Please refer to ANNEX A.9.

ANNEX A TEST RESULT


A.1 Number of Hopping Frequency

Test Data


Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	79	15	Pass
8-DPSK	2400 - 2483.5	79	15	Pass

Test plots


GFSK 2.4 GHz ~ 2.4415 GHz




GFSK 2.4415 GHz ~ 2.4835 GHz



8-DPSK 2.4 GHz ~ 2.4415 GHz



8-DPSK 2.4415 GHz ~ 2.4835 GHz



A.2 Peak Output Power and E.I.R.P


Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	GFSK		dBm	mW	
	dBm	mW			
Low	8.82	7.62	30	1000	Pass
Middle	9.06	8.05			Pass
High	9.90	9.77			Pass

Channel	Measured Output Peak Power				Limit		Verdict
	π/4-DQPSK		8-DPSK		dBm	mW	
	dBm	mW	dBm	mW			
Low	10.11	10.26	10.63	11.56	21	125	Pass
Middle	10.23	10.54	10.71	11.78			Pass
High	10.98	12.53	11.45	13.96			Pass


Test plots

GFSK LOW CHANNEL




Date: 28 SEP 2017 17:16:43

GFSK MIDDLE CHANNEL




Date: 28 SEP 2017 17:26:58

GFSK HIGH CHANNEL




Date: 28 SEP 2017 17:31:54

II/4-DQPSK LOW CHANNEL




Date: 28 SEP 2017 17:37:27

II/4-DQPSK MIDDLE CHANNEL




Date: 28 SEP 2017 17:37:57

$\pi/4$ -DQPSK HIGH CHANNEL




Date: 28 SEP 2017 17:38:23

8-DPSK LOW CHANNEL




Date: 28 SEP 2017 17:39:01

8-DPSK MIDDLE CHANNEL



Date: 28 SEP 2017 17:50:52

8-DPSK HIGH CHANNEL



Date: 28 SEP 2017 17:54:11

A.3 20 dB and 99% bandwidth


Test Data

GFSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	0.965088	0.850941
Middle	0.952148	0.837916
High	0.952148	0.842258
8-DPSK		
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low	1.265137	1.146165
Middle	1.260986	1.150507
High	1.260742	1.150507


Test plots

20 dB Bandwidth


GFSK LOW CHANNEL




GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



8-DPSK LOW CHANNEL



Date: 28 SEP 2017 17:39:57

8-DPSK MIDDLE CHANNEL



Date: 28 SEP 2017 17:51:48

8-DPSK HIGH CHANNEL



Date: 28 SEP 2017 17:55:07

99% Bandwidth

GFSK LOW CHANNEL




Date: 28 SEP 2017 17:18:36

GFSK MIDDLE CHANNEL



Date: 28 SEP 2017 17:28:50

GFSK HIGH CHANNEL



Date: 28 SEP 2017 17:33:45

8-DPSK LOW CHANNEL




Date: 28 SEP 2017 17:40:53

8-DPSK MIDDLE CHANNEL



Date: 28 SEP 2017 17:52:44

8-DPSK HIGH CHANNEL



Date: 28 SEP 2017 17:56:03

A.4 Hopping Frequency Separation


Test Data

Note: The systems operate with an output power no greater than 125 mw, The data provided in the section A.2.

Mode	Frequency separation (MHz)	Max 20 dB Bandwidth (MHz)	Two-thirds of the 20 dB bandwidth (MHz)	Verdict
GFSK	1.0033	0.965	0.643	Pass
8-DPSK	1.0033	1.265	0.843	Pass


Test Plots

GFSK



Date: 28 SEP 2017 17:22:37

8-DPSK



Date: 28 SEP 2017 18:00:38


A.5 Average Time of Occupancy

Test Data

GFSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38070	121.828	0.4	Pass
DH 3	1.62900	260.648	0.4	Pass
DH 5	2.87467	306.641	0.4	Pass
8-DPSK				
DH Packet	Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
DH 1	0.38953	124.653	0.4	Pass
DH 3	1.63742	261.995	0.4	Pass
DH 5	2.88267	307.494	0.4	Pass


Test Plots

GFSK DH1




Date: 28 SEP 2017 18:05:29

GFSK DH3




Date: 28 SEP 2017 18:06:08


GFSK DH5




8-DPSK DH1



8-DPSK DH3



8-DPSK DH5



A.6 Conducted Spurious Emissions & Authorized-band band-edge

Test Data


GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-32.13	8.17	-11.83	Pass
Middle	-32.39	8.38	-11.62	Pass
High	-31.57	9.13	-10.87	Pass
8-DPSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-33.18	7.85	-12.15	Pass
Middle	-31.91	8.12	-11.88	Pass
High	-32.03	8.91	-11.09	Pass
Hopping Mode				
Mode	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-32.26	8.78	-11.22	Pass
8-DPSK	-32.74	8.98	-11.02	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE



GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz



GFSK MIDDLE CHANNEL, CARRIER LEVEL




GFSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:30:58

GFSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 28 SEP 2017 17:31:19

GFSK HIGH CHANNEL, CARRIER LEVEL




Date: 28 SEP 2017 17:33:59

GFSK HIGH CHANNEL , BAND EDGE




Date: 28 SEP 2017 17:36:49

GFSK HIGH CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:34:51

GFSK HIGH CHANNEL , SPURIOUS 3 GHz ~ 25 GHz




Date: 28 SEP 2017 17:35:44

8-DPSK LOW CHANNEL, CARRIER LEVEL




Date: 28 SEP 2017 17:48:41

8-DPSK LOW CHANNEL, BAND EDGE




Date: 28 SEP 2017 17:50:19

8-DPSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:49:27

8-DPSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




Date: 28 SEP 2017 17:49:49

8-DPSK MIDDLE CHANNEL, CARRIER LEVEL




Date: 28 SEP 2017 17:52:53

8-DPSK MIDDLE CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:53:30

8-DPSK MIDDLE CHANNEL , SPURIOUS 3 GHz ~ 25 GHz



Date: 28 SEP 2017 17:53:46

8-DPSK HIGH CHANNEL, CARRIER LEVEL




Date: 28 SEP 2017 17:56:24

8-DPSK HIGH CHANNEL , BAND EDGE




Date: 28 SEP 2017 17:58:33

8-DPSK HIGH CHANNEL , SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:57:52

8-DPSK HIGH CHANNEL , SPURIOUS 3 GHz ~ 25 GHz



Date: 28 SEP 2017 17:58:08

GFSK HOPPING, CARRIER LEVEL




Date: 28 SEP 2017 17:22:56

GFSK HOPPING BAND EDGE (LOW)




Date: 28 SEP 2017 17:25:27

GFSK HOPPING BAND EDGE (HIGH)




Date: 28 SEP 2017 17:25:55

GFSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz




Date: 28 SEP 2017 17:24:03

GFSK Hopping Mode, SPURIOUS 30 GHz ~ 25 GHz




Date: 28 SEP 2017 17:24:38

8-DPSK HOPPING, CARRIER LEVEL




Date: 28 SEP 2017 18:00:55

8-DPSK Hopping BAND EDGE (LOW)




Date: 28 SEP 2017 18:03:27

8-DPSK Hopping BAND EDGE (HIGH)




Date: 28 SEP 2017 18:03:54

8-DPSK Hopping Mode, SPURIOUS 30 MHz ~ 3 GHz



Date: 28 SEP 2017 18:02:13

8-DPSK Hopping Mode, SPURIOUS 30 GHz ~ 25 GHz



Date: 28 SEP 2017 18:02:38


A.7 Conducted Emissions

Note¹: The EUT is working in the Normal link mode.

Note²: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 60 Hz and 240 VAC, 50 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.


Test Data and Plots

PHASE L



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	44.1	10.29	65.5	21.40	Peak	L Line	Pass
1**	0.160	33.0	10.29	55.5	22.50	AV	L Line	Pass
2	0.280	40.2	10.51	60.8	20.60	Peak	L Line	Pass
2**	0.280	27.7	10.51	50.8	23.10	AV	L Line	Pass
3	0.402	44.5	9.52	57.8	13.30	Peak	L Line	Pass
3**	0.402	26.8	9.52	47.8	21.00	AV	L Line	Pass
4	0.482	50.6	11.13	56.3	5.70	Peak	L Line	Pass
4**	0.482	31.4	11.13	46.3	14.90	AV	L Line	Pass
5	1.214	44.1	10.05	56.0	11.90	Peak	L Line	Pass
5**	1.214	24.5	10.05	46.0	21.50	AV	L Line	Pass
6	2.224	48.4	10.73	56.0	7.60	Peak	L Line	Pass
6**	2.224	29.2	10.73	46.0	16.80	AV	L Line	Pass

PHASE N



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.160	46.8	10.29	65.5	18.70	Peak	N Line	Pass
1**	0.160	37.5	10.29	55.5	18.00	AV	N Line	Pass
2	0.198	43.3	9.38	63.7	20.40	Peak	N Line	Pass
2**	0.198	35.3	9.38	53.7	18.40	AV	N Line	Pass
3	0.476	45.8	11.04	56.4	10.60	Peak	N Line	Pass
3**	0.476	42.4	11.04	46.4	4.00	AV	N Line	Pass
4	0.518	45.5	10.11	56.0	10.50	Peak	N Line	Pass
4**	0.518	40.8	10.11	46.0	5.20	AV	N Line	Pass
5	2.320	44.1	10.67	56.0	11.90	Peak	N Line	Pass
5**	2.320	34.8	10.67	46.0	11.20	AV	N Line	Pass
6	11.464	36.6	10.56	60.0	23.40	Peak	N Line	Pass
6**	11.464	23.7	10.56	50.0	26.30	AV	N Line	Pass


A.8 Radiated Spurious Emission

Duty cycle correction factor for average measurement.

Note:


1. Duty cycle = on time/100 milliseconds = $3 * 2.87467 / 100 = 8.62 \%$
2. Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -21.29 \text{ dB}$
3. DH5 has the highest duty cycle and is reported.

DH5 on time/100 ms (One Pulse) Plot on Channel 39



Date: 28 SEP.2017 18:06:41

DH5 on time/100 ms (Count Pulses) Plot on Channel 39



Date: 28 SEP.2017 17:26:07

Test Data and Plots


Note 1: The symbol of “--” in the table which means not application.

Note 2: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note 3: The EUT is working in the Normal link mode below 1 GHz.


The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

30 MHz to 1 GHz, ANT V



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	30.000	22.52	-22.38	30.0	7.48	Peak	7.00	100	Vertical	Pass
2	51.340	22.49	-19.07	30.0	7.51	Peak	295.00	200	Vertical	Pass
3	69.043	24.31	-22.46	30.0	5.69	Peak	0.00	200	Vertical	Pass
4	77.772	21.85	-24.76	30.0	8.15	Peak	179.00	200	Vertical	Pass
5	135.730	18.84	-23.42	33.5	14.66	Peak	150.00	100	Vertical	Pass
6	226.182	20.07	-18.71	36.0	15.93	Peak	0.00	200	Vertical	Pass

30 MHz to 1 GHz, ANT H



Test Data and Plots (1 GHz ~ 10th Harmonic)

Note: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

1 GHz to 25 GHz, ANT V GFSK Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1827.49	51.20	-3.85	74	22.80	Peak	105.3	150	Vertical	Pass
2	2402.00	90.56	0.37	74	-16.56	Peak	23.4	150	Vertical	N/A
3	5835.52	52.30	14.78	74	21.70	Peak	12.4	150	Vertical	Pass
4	7123.13	50.87	20.33	74	23.13	Peak	232.1	150	Vertical	Pass
5	16462.56	43.81	11.69	74	30.19	Peak	8.8	150	Vertical	Pass
6	18896.01	51.37	10.36	74	22.63	Peak	351	150	Vertical	Pass

1 GHz to 25 GHz, ANT H GFSK Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1898.70	46.38	-3.41	74	27.62	Peak	229.9	150	Horizontal	Pass
2	2402.00	102.07	0.38	74	-28.07	Peak	176.8	150	Horizontal	N/A
3	5994.47	52.17	14.93	74	21.83	Peak	47.4	150	Horizontal	Pass
4	8010.40	44.05	14.21	74	29.95	Peak	312.2	150	Horizontal	Pass
5	17003.33	46.11	9.15	74	27.89	Peak	95.8	150	Horizontal	Pass
6	24520.80	45.97	8.84	74	28.03	Peak	177.1	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V GFSK Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1828.28	49.76	-3.87	74	24.24	Peak	72.5	150	Vertical	Pass
2	2440.63	89.82	0.39	74	-15.82	Peak	329.3	150	Vertical	N/A
3	5833.97	52.65	14.78	74	21.35	Peak	307.2	150	Vertical	Pass
4	8819.05	45.09	19.17	74	28.91	Peak	333.8	150	Vertical	Pass
5	16639.35	48.11	9.57	74	25.89	Peak	135.6	150	Vertical	Pass
6	20178.04	48.05	11.73	74	25.96	Peak	310.5	150	Vertical	Pass

1 GHz to 25 GHz, ANT H GFSK Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1900.22	45.11	-3.40	74	28.89	Peak	46.7	150	Horizontal	Pass
2	2440.22	102.59	0.37	74	-28.59	Peak	117	150	Horizontal	N/A
3	5994.75	52.07	14.91	74	21.93	Peak	244.2	150	Horizontal	Pass
4	8673.05	45.33	20.13	74	28.67	Peak	164.2	150	Horizontal	Pass
5	13696.34	45.60	20.64	74	28.40	Peak	247.1	150	Horizontal	Pass
6	23452.58	50.33	10.86	74	23.67	Peak	336.7	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V GFSK High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1826.72	51.62	-3.87	74	22.38	Peak	259.6	150	Vertical	Pass
2	2480.49	89.84	0.38	74	-15.84	Peak	305.9	150	Vertical	N/A
3	5832.16	52.65	14.79	74	21.35	Peak	2.1	150	Vertical	Pass
4	7931.78	44.38	14.51	74	29.62	Peak	278.6	150	Vertical	Pass
5	13696.34	45.37	20.65	74	28.63	Peak	6.3	150	Vertical	Pass
6	24091.51	48.07	12.04	74	25.93	Peak	117.6	150	Vertical	Pass

1 GHz to 25 GHz, ANT H GFSK High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1900.06	46.17	-3.40	74	27.83	Peak	265.4	150	Horizontal	Pass
2	2480.10	102.30	0.37	74	-28.30	Peak	177.7	150	Horizontal	N/A
3	5990.85	52.61	14.86	74	21.39	Peak	155.6	150	Horizontal	Pass
4	10189.27	48.57	16.96	74	25.43	Peak	275.6	150	Horizontal	Pass
5	12637.69	46.84	10.32	74	27.16	Peak	223.7	150	Horizontal	Pass
6	20287.85	43.11	8.27	74	30.89	Peak	347.7	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V 8-DPSK Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1825.67	49.78	-3.82	74	24.22	Peak	267.7	150	Vertical	Pass
2	2402.00	90.57	0.38	74	-16.57	Peak	180.1	150	Vertical	N/A
3	5833.38	52.38	14.78	74	21.62	Peak	14.4	150	Vertical	Pass
4	8863.98	44.84	14.95	74	29.16	Peak	273.1	150	Vertical	Pass
5	15329.04	46.81	9.18	74	27.19	Peak	164.2	150	Vertical	Pass
6	18792.01	42.92	9.50	74	31.08	Peak	7.9	150	Vertical	Pass

1 GHz to 25 GHz, ANT H 8-DPSK Low Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1897.28	46.10	-3.41	74	27.90	Peak	172.5	150	Horizontal	Pass
2	2402.00	101.62	0.37	74	-27.62	Peak	56.8	150	Horizontal	N/A
3	5992.73	52.46	14.96	74	21.54	Peak	321.1	150	Horizontal	Pass
4	10425.13	44.27	14.84	74	29.73	Peak	182.8	150	Horizontal	Pass
5	14715.47	44.22	8.72	74	29.79	Peak	88.8	150	Horizontal	Pass
6	20527.45	44.06	13.17	74	29.94	Peak	195.6	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V 8-DPSK Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1825.53	51.00	-3.82	74	23.00	Peak	336.4	150	Vertical	Pass
2	2440.53	89.10	0.39	74	-15.10	Peak	260.2	150	Vertical	N/A
3	5830.15	52.96	14.78	74	21.04	Peak	236.6	150	Vertical	Pass
4	7639.77	42.17	14.77	74	31.83	Peak	337.1	150	Vertical	Pass
5	15661.81	42.93	9.96	74	31.07	Peak	258.7	150	Vertical	Pass
6	20357.74	47.26	11.73	74	26.75	Peak	220.1	150	Vertical	Pass

1 GHz to 25 GHz, ANT H 8-DPSK Middle Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1896.46	46.65	-3.31	74	27.35	Peak	6.7	150	Horizontal	Pass
2	2440.09	101.95	0.38	74	-27.95	Peak	328.1	150	Horizontal	N/A
3	5996.29	52.90	14.91	74	21.10	Peak	78.1	150	Horizontal	Pass
4	8616.89	48.91	14.25	74	25.09	Peak	161.3	150	Horizontal	Pass
5	15651.41	46.53	20.72	74	27.47	Peak	232.5	150	Horizontal	Pass
6	19039.93	46.66	11.59	74	27.34	Peak	133.4	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V 8-DPSK High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1826.57	50.05	-3.87	74	23.95	Peak	348.7	150	Vertical	Pass
2	2480.86	89.48	0.41	74	-15.48	Peak	242.2	150	Vertical	N/A
3	5833.05	52.50	14.78	74	21.50	Peak	332.8	150	Vertical	Pass
4	6561.56	46.10	19.17	74	27.90	Peak	274	150	Vertical	Pass
5	15807.40	42.13	11.73	74	31.87	Peak	334.9	150	Vertical	Pass
6	19818.64	48.56	11.33	74	25.44	Peak	167.5	150	Vertical	Pass

1 GHz to 25 GHz, ANT H 8-DPSK High Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1896.89	46.84	-3.31	74	27.16	Peak	315.9	150	Horizontal	Pass
2	2480.66	101.73	0.38	74	-27.73	Peak	53.1	150	Horizontal	N/A
3	5993.30	52.58	14.96	74	21.42	Peak	259.9	150	Horizontal	Pass
4	11312.40	45.34	15.02	74	28.66	Peak	294.2	150	Horizontal	Pass
5	13613.15	44.00	9.06	74	30.00	Peak	253.9	150	Horizontal	Pass
6	20597.34	45.84	9.63	74	28.16	Peak	356.7	150	Horizontal	Pass

Hopping Mode:

1 GHz to 25 GHz, ANT V GFSK(Hopping) Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1827.97	50.18	-3.88	74	23.82	Peak	17.4	150	Vertical	Pass
2	2440.98	89.41	0.44	74	-15.41	Peak	309.7	150	Vertical	N/A
3	5833.71	52.49	14.79	74	21.51	Peak	198.4	150	Vertical	Pass
4	8976.29	42.41	16.96	74	31.59	Peak	188.2	150	Vertical	Pass
5	12716.31	43.81	12.09	74	30.20	Peak	309.9	150	Vertical	Pass
6	18740.02	43.63	9.70	74	30.38	Peak	123.3	150	Vertical	Pass

1 GHz to 25 GHz, ANT H GFSK(Hopping) Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1897.08	46.07	-3.40	74	27.93	Peak	199.9	150	Horizontal	Pass
2	2440.96	103.07	0.44	74	-29.07	Peak	279	150	Horizontal	N/A
3	5992.48	52.79	14.96	74	21.21	Peak	358.7	150	Horizontal	Pass
4	11065.31	42.52	20.21	74	31.48	Peak	205.3	150	Horizontal	Pass
5	12132.28	45.30	11.85	74	28.70	Peak	341.3	150	Horizontal	Pass
6	20577.37	44.06	10.76	74	29.94	Peak	82.6	150	Horizontal	Pass

1 GHz to 25 GHz, ANT V 8-DPSK(Hopping) Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1827.07	49.97	-3.88	74	24.03	Peak	177	150	Vertical	Pass
2	2440.31	88.79	0.38	74	-14.79	Peak	239	150	Vertical	N/A
3	5832.69	52.84	14.79	74	21.16	Peak	12.5	150	Vertical	Pass
4	10739.60	48.10	18.20	74	25.90	Peak	97.4	150	Vertical	Pass
5	17440.10	43.70	12.72	74	30.30	Peak	338.9	150	Vertical	Pass
6	20227.95	47.64	10.97	74	26.36	Peak	286.2	150	Vertical	Pass

1 GHz to 25 GHz, ANT H 8-DPSK(Hopping) Channel

No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (o)	Height (cm)	ANT	Verdict
1	1895.88	45.55	-3.34	74	28.45	Peak	67.6	150	Horizontal	Pass
2	2440.75	102.67	0.38	74	-28.67	Peak	64.1	150	Horizontal	N/A
3	5994.18	52.37	14.96	74	21.63	Peak	216.1	150	Horizontal	Pass
4	11480.87	46.25	14.51	74	27.75	Peak	161.7	150	Horizontal	Pass
5	15048.25	43.62	19.46	74	30.38	Peak	184.4	150	Horizontal	Pass
6	21775.37	46.09	11.14	74	27.91	Peak	140.9	150	Horizontal	Pass

A.9 Band Edge (Restricted-band band-edge)

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Test Mode	Test Channel	Frequency (MHz)	Level (dBuV/m)	Limit Line (dBuV/m)	Margin (dB)	Remark	Verdict
GFSK	Low	2390.00	45.26	74	28.74	PEAK	Pass
		2390.00	N/A	54	N/A	AVERAGE	Pass
GFSK	HIGH	2483.50	51.28	74	22.72	PEAK	Pass
		2483.50	N/A	54	N/A	AVERAGE	Pass
8-DPSK	Low	2390.00	44.51	74	29.50	PEAK	Pass
		2390.00	N/A	54	N/A	AVERAGE	Pass
8-DPSK	HIGH	2483.50	50.77	74	23.23	PEAK	Pass
		2483.50	N/A	54	N/A	AVERAGE	Pass
GFSK(Hopping)	Low	2390.00	42.78	74	31.22	PEAK	Pass
		2390.00	N/A	54	N/A	AVERAGE	Pass
GFSK(Hopping)	HIGH	2483.50	49.84	74	24.16	PEAK	Pass
		2483.50	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	Low	2390.00	42.84	74	31.16	PEAK	Pass
		2390.00	N/A	54	N/A	AVERAGE	Pass
8-DPSK (Hopping)	HIGH	2483.50	45.23	74	28.77	PEAK	Pass
		2483.50	N/A	54	N/A	AVERAGE	Pass

Test Plots


GFSK LOW CHANNEL , PEAK




GFSK HIGH CHANNEL , PEAK



8-DPSK LOW CHANNEL , PEAK




8-DPSK HIGH CHANNEL , PEAK




Hopping Mode:


GFSK LOW FREQUENCY BAND, PEAK




GFSK HIGH FREQUENCY BAND, PEAK



8-DPSK LOW FREQUENCY BAND, PEAK



8-DPSK HIGH FREQUENCY BAND, PEAK



ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SZ180425-AR.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL- SZ180425-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL- SZ180425-AI.PDF”.

--END OF REPORT--