

FCC Test Report for Part 15.247 (DTS)

Product name : SmartTAG Bluetooth Low Energy
Applicant : Wistiki SAS Company
FCC ID : 2AEBR-WISTIKI-V4

Test report No. : 170901627 09 Ver 2.00

Laboratory information

Accreditation

Telefication is designated by the FCC as an Accredited Test Firm for compliance testing of equipment subject to Certification under Parts 15 & 18. The Designation number is: NL0001

The Industry Canada registration number for the 3 meter test chamber of Telefication is: 4173A-1.

Documentation

Telefication complies with the accreditation criteria for test laboratories as laid down in ISO/IEC 17025:2005. The accreditation covers the quality system of the laboratory as well as the specific activities as described in the authorized annex bearing the accreditation number L021 and is granted on 30 November 1990 by the Dutch Council For Accreditation (RvA: Raad voor Accreditatie).

The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 10 years at Telefication Netherlands

Testing Location

Test Site	Telefication BV
Test Site location	Edisonstraat 12a 6902 PK Zevenaar The Netherlands Tel. +31889983600 Fax. +31316583189
Test Site FCC	NL0001

Revision History

Version	Date	Remarks	By
v0.50	31-05-2018	First draft	PS
v1.00	02-08-2018	Initial release	PS
v2.00	29-10-2018	Added sample calculation and corrected FCC ID.	PS

Table of Contents

Revision History	2
Summary of Test results.....	5
1 General Description.....	6
1.1 Applicant.....	6
1.2 Manufacturer	6
1.3 Tested Equipment Under Test (EUT)	6
1.4 Product specifications of Equipment under test	7
1.5 Modification of the Equipment Under Test (EUT).....	7
1.6 Observations and remarks.....	7
1.7 Environmental conditions.....	7
1.8 Measurement Standards	7
1.9 Applicable Standards	7
1.10 Conclusions.....	8
2 Test configuration of the Equipment Under Test	9
2.1 Test mode	9
2.2 Tested channels and Data rates	9
2.3 Conducted Test setup.....	9
2.4 Radiated Test setup	10
2.5 Equipment used in the test configuration	11
2.6 Sample calculation.....	11
3 Test results	12
3.1 DTS bandwidth Measurement.....	12
3.1.1 Limit.....	12
3.1.2 Measurement instruments	12
3.1.3 Test setup.....	12
3.1.4 Test procedure	12
3.1.5 Test Results of the DTS bandwidth measurement	12
3.1.6 Plots of the DTS bandwidth Measurement	13
3.2 Peak Output Power Measurement.....	14
3.2.1 Limit.....	14
3.2.2 Measurement instruments	14
3.2.3 Test setup.....	14
3.2.4 Test procedure	14
3.2.5 Test results of Peak Output Power Measurement	14
3.2.6 Plots of Output Power Measurement	15
3.3 Power Spectral Density.....	16
3.3.1 Limit.....	16

3.3.2	Measurement instruments	16
3.3.3	Test setup	16
3.3.4	Test procedure	16
3.3.5	Test results of Power Spectral Density Measurement	16
3.4	Conducted spurious emissions at the antenna connector	17
3.4.1	Limits	17
3.4.2	Measurement instruments	17
3.4.3	Test setup	17
3.4.4	Test procedure	17
3.4.5	Measurement Uncertainty	17
3.4.6	Plots of the conducted spurious emissions at the antenna connector	18
3.5	Radiated spurious emissions measurement (cabinet radiation) (incl. restricted band spurious emissions)	19
3.5.1	Limits	19
3.5.2	Measurement instruments	19
3.5.3	Test setup	19
3.5.4	Test procedure	19
3.5.5	Note	19
3.5.6	Plots of the Radiated Spurious Emissions Measurement	20
3.5.7	Measurement Uncertainty	24

Summary of Test results

FCC	Description	Section in report	Verdict
15.247(a)	6dB Bandwidth	3.1	Pass
15.247(b)	Peak output power	3.2	Pass
15.247(e)	Power spectral density	3.3	Pass
15.247(d)	Band edge emissions	--	NA ^{Note}
15.247(d)	Conducted spurious emissions	3.4	Pass
15.209 (a)	Radiated Spurious emissions (incl. restricted bands) (cabinet radiation)	3.5	Pass

Note; Not applicable, since the DTS bandwidth edges do not fall within 2 MHz of the authorized band edges.

1 General Description

1.1 Applicant

Client name:	Wistiki SaS Company
Address	rue du Faubourg Pioissonnière, Paris, France
Zip code:	75010
Telephone:	+33 650102272
Contact name:	H. Lussato
E-mail:	hugo.lussato@wistiki.com

1.2 Manufacturer

Manufacturer name:	Robert Bosch France SAS
Address:	15, rue Charles de Coulomb, Mondeville, France
Zip code:	14125
Contact name::	J. Poux
E-mail:	Joel.Poux@fr.bosch.com

1.3 Tested Equipment Under Test (EUT)

Product name:	SmartTAG Bluetooth Low Energy
Brand name:	WISTIKI
Product type:	2.4 GHz data transmission equipment
FCC ID:	2AEBR-WISTIKI-V4
Model(s):	HOPLA
Software version:	1.1.2
Hardware version:	BSX0604-1 BU136v3
Date of receipt	19-03-2018
Tests started:	24-05-2018
Testing ended:	01-06-2018

1.4 Product specifications of Equipment under test

Tx Frequency range (MHz):	2402 – 2480
Rx frequency range (MHz):	2402 – 2480
Maximum output power to antenna (dBm):	0
Antenna type :	PCB printed (meander)
Antenna gain (dBi):	2
Type of modulation:	GFSK

1.5 Modification of the Equipment Under Test (EUT)

None.

1.6 Observations and remarks

The tested sample was modified to include a temporary antenna connector.

1.7 Environmental conditions

Test date	24-05-2018	01-06-2018
Ambient temperature	25.0 °C	27.5 °C
Humidity	44.6 % RH	51.5 % RH

1.8 Measurement Standards

- FCC KDB Publication No. 558074 D01DTS Meas. Guidance V04
- ANSI C63.10:2013

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standard(s):

- FCC Part 15 Subpart C §15.247

1.10 Conclusions

The sample of the product showed NO NON-COMPLIANCES to the specifications stated in paragraph 1.9 of this report.

The results of the test as stated in this report, are exclusively applicable to the product items as identified in this report. Telefication accepts no responsibility for any properties of product items in this test report, which are not supported by the tests as specified in paragraph 1.9 "*Applicable standards*".

All tests are performed by:

Name : ing. P.A. Suringa

Review of test methods and report by:

Name : ing R. van Barneveld

The above conclusions have been verified by the following signatory:

Date : 29-10-2018

Name : ing. K.A. Roes

Function : Coordinator Radio Laboratory

Signature :



2 Test configuration of the Equipment Under Test

2.1 Test mode

The applicant provided test mode firmware for the EUT, in which it was possible to configure the EUT into different test channels.

2.2 Tested channels and Data rates

Technology	Channels	Frequency (MHz)	Data rate
Bluetooth Low Energy	37	2402	1 Mbps
	17	2440	1 Mbps
	39	2480	1 Mbps


2.3 Conducted Test setup

RF tests at antenna connector




2.4 Radiated Test setup

Radiated emissions test setup 30 MHz - 1 GHz



Radiated emissions test setup above 1 GHz



2.5 Equipment used in the test configuration

Description	Manufacturer	Model	ID	Used at Par.
Spectrum Analyzer	Rohde & Schwarz	FSP40	TE11125	3.1, 3.4, 3.5
Spectrum Analyzer	Rohde & Schwarz	ESCI	TE11128	3.2
Biconilog Antenna	Chase	CBL6112A	TE00967	3.5
Horn Antenna	EMCO The Electro – Mechanics Co	3115	TE00531	3.5
SAC Chamber	Comtest Engineering BV	-	TE00861	3.5
Measurement software	Dare	Radimation	Version 2016.2.8	3.5
Pre-amplifier	Miteq	AFS42-041001800-28-10P-42	TE11132	3.5

2.6 Sample calculation

Maximum Field Strength Measurement value:

Frequency (GHz)	Polarization	Height(m)	Peak (dBμV/m)
1.895	Vertical	2	45.7

The following relation applies:

$$E \text{ (dB}\mu\text{V/m)} = U \text{ (dB}\mu\text{V)} + AF \text{ (dB/m)} - G \text{ (dB)} + CL \text{ (dB)}$$

Where:

E = Electric field strength

U = Measuring receiver voltage

AF = Antenna factor

G = Gain of the pre-amplifier

CL = Cable loss

$$(45.7 = 36.6 + 27.8 - 39.6 + 2.7)$$

3 Test results

3.1 DTS bandwidth Measurement

3.1.1 Limit

The minimum 6 dB Bandwidth shall be at least 500 kHz.

3.1.2 Measurement instruments

The measurement instruments are listed in chapter 2.5 of this report.

3.1.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

3.1.4 Test procedure

The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.


IRN 017_10 Occupied bandwidth (Hz) – Method 4.

3.1.5 Test Results of the DTS bandwidth measurement


Technology Std.	Channel	Frequency (MHz)	Data rate	DTS bandwidth (kHz)
Bluetooth Low Energy	37	2402	1 Mbps	760
	17	2440	1 Mbps	760
	39	2480	1 Mbps	760
Uncertainty	± 81 kHz			

3.1.6 Plots of the DTS bandwidth Measurement


(Channel 37)



(Channel 17)



(Channel 39)



3.2 Peak Output Power Measurement

3.2.1 Limit

For systems using digital modulation in the 2400-2483.5 MHz, the limit for the peak output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point to point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measurement instruments

The measurement instruments are listed in chapter 2.5 of this report.

3.2.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

3.2.4 Test procedure


The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v04.
IRN 014_14 RF Power (W) – method 9.

3.2.5 Test results of Peak Output Power Measurement


Technology Std.	Channel	Peak method		
		Frequency (MHz)	Data rate	Peak output power (dBm eirp)
Bluetooth Low Energy	37	2402	1 Mbps	-2.02 + 2 = -0.02
	17	2440	1 Mbps	-2.06 + 2 = -0.06
	39	2480	1 Mbps	-2.09 + 2 = -0.09
Uncertainty	±0.71 dB			

3.2.6 Plots of Output Power Measurement


Peak Output Power (Channel 37)



Peak Output Power (Channel 17)



Peak Output Power (Channel 39)



3.3 Power Spectral Density

3.3.1 Limit

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measurement instruments

Not applicable.

3.3.3 Test setup

Not applicable.

3.3.4 Test procedure

Not applicable.

3.3.5 Test results of Power Spectral Density Measurement

Since the peak output power values are below 0 dBm, the power spectral density limit is considered to be met.

3.4 Conducted spurious emissions at the antenna connector

3.4.1 Limits

In any 100 kHz bandwidth outside the operating frequency band, the RF power shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either a RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

Attenuation below the general limits specified in §15.209 (a) is not required.

3.4.2 Measurement instruments

The measurement instruments are listed in chapter 2.5 of this report.

3.4.3 Test setup

The test setup is as shown in chapter 2.3 of this report.

3.4.4 Test procedure


According to KDB Publication 558074 v04, section 11.0.
IRN 016_10 Spurious emission (W) – method 1.

3.4.5 Measurement Uncertainty


+ 1.1/ - 1.1 dB.

3.4.6 Plots of the conducted spurious emissions at the antenna connector


(Channel 37)



(Channel 17)



(Channel 39)



3.5 Radiated spurious emissions measurement (cabinet radiation) (incl. restricted band spurious emissions)

3.5.1 Limits

Radiated emissions must comply with the limits specified in §15.209(a) (see below).

Frequency (MHz)	Field strength ($\mu\text{V/m}$)	Measurement distance(m)
0.009 – 0.490	$2400/F(\text{kHz})$	300
0.490 – 1.705	$24000/F(\text{kHz})$	30
1.705 - 30	30	30
30 -88	100	3
88 - 216	150	3
216-960	200	3
Above 960	500	3

3.5.2 Measurement instruments

The measurement instruments are listed in chapter 2.5 of this report.

3.5.3 Test setup

The test setup is as shown in chapter 2.4 of this report.

3.5.4 Test procedure

The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz.

Radiated emission limits in these three bands are based on measurements employing an average detector.

Other details are according to KDB Publication 558074 V03r05, sections 11.3 and 12.1.

IRN 016_10 Spurious emission (W) – method 1.


3.5.5 Note

- In the frequency range of 1 – 18 GHz the green trace is measured using a peak detector and the red trace is measured using an average detector. The top limit line represent the peak limit and the bottom limit represents the average limit.


3.5.6 Plots of the Radiated Spurious Emissions Measurement

30 – 1000 MHz

Vertical polarization




Horizontal polarization




1 – 18 GHz

Vertical polarization



Note: emission peaks in the 2.4 GHz band are not subject to the limit.

Horizontal polarization



Note: emission peaks in the 2.4 GHz band are not subject to the limit.

18 GHz to 26.5 GHz

Measurements in this frequency range are already performed on the temporary antenna connector, see section 3.4. As no spurious emissions above the test system noise floor are observed, the radiated measurements are omitted.

3.5.7 Measurement Uncertainty

Measurement uncertainty Radiated emissions below 1 GHz

Horizontal polarization	
30 – 200 MHz	4.5 dB
200 – 1000 MHz	3.6 dB
Vertical polarization	
30 – 200 MHz	5.4 dB
200 – 1000 MHz	4.6 dB

Measurement uncertainty Radiated emissions above 1 GHz

1000- 18000 MHz	5.7 dB
-----------------	--------