Test Report

Date : 2018-10-18
No. : HMD18080002

Applicant	:	POECES Audio Co., Ltd. Joinin Hub Building Room 413, Xin'an 6th Road, Bao'an District, Shenzhen, PRC
Supplier / Manufacturer	:	POECES Audio Co., Ltd. Joinin Hub Building Room 413, Xin'an 6th Road, Bao'an District, Shenzhen, PRC
Description of Sample(s)	:	Submitted sample(s) said to be Product: Wireless charging base speaker Brand Name: POECES Model No.: SQUARE FCC ID: 2AEBS20181022
Date Samples Received	:	2018-07-30
Date Tested	:	2018-08-08 to 2018-10-18
Investigation Requested	:	Perform Electro Magnetic Interference measurement in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2017 and ANSI C63.10:2013 for FCC Certification.
Conclusions	:	The submitted product COMPLIED with the requirements of Federal Communications Commission [FCC] Rules and Regulations Part 15. The tests were performed in accordance with the standards described above and on Section 2.2 in this Test Report.
Remarks	:	Bluetooth FHSS (GFSK / π/4-DQPSK) For additional model(s) details, see page 3.

CHEUNG Chi, Kenneth
Authorized Signatory

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

CONTENT:

	Cover	Page 1 of 77
	Content	Page 2 of 77
1.0	**General Details**	
1.1	Test Laboratory	Page 3 of 77
1.2	Equipment Under Test [EUT] Description of EUT operation	Page 3 of 77
1.3	Date of Order	Page 3 of 77
1.4	Submitted Sample(s)	Page 3 of 77
1.5	Test Duration	Page 3 of 77
1.6	Country of Origin	Page 3 of 77
1.7	RF Module Details	Page 4 of 77
1.8	Antenna Details	Page 4 of 77
2.0	**Technical Details**	
2.1	Investigations Requested	Page 5 of 77
2.2	Test Standards and Results Summary	Page 5 of 77
2.3	Table for Test Modes	Page 6 of 77
3.0	**Test Results**	
3.1	Emission	Page 7-72 of 77
Appendix A List of Measurement Equipment		Page 73 of 77
Appendix B Photograph(s) of Product		Page 74-77 of 77

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

1.0 General Details

1.1 Test Laboratory

The Hong Kong Standards and Testing Centre Ltd.
EMC Laboratory
10 Dai Wang Street, Taipo Industrial Estate, New Territories, Hong Kong
Telephone: 852 2666 1888
Fax: 852 2664 4353

1.2 Equipment Under Test [EUT]

Description of Sample(s)

Product:	Wireless charging base speaker
Additional Product:	Wireless power bank speaker
Manufacturer:	POECES Audio Co., Ltd. Joinin Hub Building Room 413, Xin'an 6th Road, Bao'an District, Shenzhen, PRC
Brand Name:	POECES
Model Number:	SQUARE
Additional Model Number:	SQUAREQ
Rating:	Input: 100-240Va.c. 50/60Hz 1.2A; Output: 9Vd.c. 3A.

The AC/DC adaptor was provided by the applicant with following details:
Brand name: N/A; Model no.: GEO361T-090300

1.2.1 Description of EUT Operation

The Equipment Under Test (EUT) is a Wireless charging base speaker. The transmission signal is digital modulated with channel frequency range 2402-2480MHz. The R.F. signal was modulated by IC; the type of modulation used was frequency hopping spread spectrum Modulation.

1.3 Date of Order

2018-07-30

1.4 Submitted Sample(s):

1 Sample

1.5 Test Duration

2018-08-08 to 2018-10-18

1.6 Country of Origin

China

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to "Conditions of Issuance of Test Reports" section or Website.

1.7 RF Module Details

Module Model Number:	AC6901A
Module FCC ID:	N/A
Module Transmission Type:	Bluetooth V4.2
Modulation:	FHSS (GFSK / π/4-DQPSK)
Data Rates:	1MBps: GFSK
	2 MBps: π/4-DQPSK
Frequency Range:	2400-2483.5MHz
Carrier Frequencies:	2402MHz – 2480MHz

Module Specification (specification provided by manufacturer)

1.8 Antenna Details

Antenna Type:	PCB antenna
Antenna Gain:	0dBi

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

2.0 Technical Details

2.1 Investigations Requested

Perform Electromagnetic Interference measurements in accordance with FCC 47CFR [Codes of Federal Regulations] Part 15: 2017 Regulations and ANSI C63.10:2013for FCC Certification.
According FCC KDB 558074 DTS Measurement Guidance, Duty cycle ≧98%.
The device was realized by test software.

2.2 Test Standards and Results Summary Tables

EMISSION
Results Summary

Test Condition	Test Requirement	Test Method	Class / Severity	Test Result		
				Pass	Failed	N/A
Maximum Peak Conducted Output Power	FCC 47CFR 15.247(b)(1)	ANSI C63.10: 2013	N/A	☒	☐	☐
Radiated Spurious Emissions	FCC 47CFR 15.209	ANSI C63.10: 2013	N/A	☒	☐	☐
AC Mains Conducted Emissions	FCC 47CFR 15.207	ANSI C63.10: 2013	N/A	☒	☐	☐
Number of Hopping Frequency	FCC 47CFR 15.247 (b)(1)	ANSI C63.10: 2013	N/A	☒	☐	☐
20dB Bandwidth	FCC 47CFR 15.247(a)(2)	ANSI C63.10: 2013	N/A	☒	☐	☐
Hopping Channel Separation	FCC 47CFR 15.247(a)(1)	ANSI C63.10: 2013	N/A	☒	☐	☐
Band-edge measurement (Radiated)	FCC 47CFR 15.247(d)	ANSI C63.10: 2013	N/A	☒	☐	☐
Pseudorandom Hopping Algorithm	FCC 47CFR 15.247(a)(1)	N/A	N/A	☒	☐	☐
Time of Occupancy (Dwell Time)	FCC 47CFR 15.247(a)(1)(iii)	ANSI C63.10: 2013	N/A	☒	☐	☐
Antenna requirement	FCC 47CFR 15.203	N/A	N/A	☒	☐	☐

Note: N/A - Not Applicable

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

2.3 Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate in the table below is the worst case rate with respect to the specific test item.
Investigation has been done on all the possible configurations for searching the worst cases.
The device was realized by test software.
The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate
Maximum Peak Conducted Output Power	GFSK / π/4-DQPSK	1MBps / 2MBps
Hopping Channel Separation	GFSK / π/4-DQPSK	1MBps / 2MBps
Number of Hopping Frequency	GFSK / π/4-DQPSK	1MBps / 2MBps
Time of Occupancy(Dwell Time)	π/4-DQPSK (DH1 / DH3 / DH5)	2MBps
Radiated Spurious Emissions	GFSK / π/4-DQPSK	1MBps / 2MBps
Band-edge compliance of Conducted Emission	GFSK / π/4-DQPSK	1MBps / 2MBps

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.0 Test Results

3.1 Emission

3.1.1 Maximum Peak Conducted Output Power

Test Requirement:	FCC 47CFR 15.247(b) (1)
Test Method:	ANSI C63.10: 2013
Test Date:	2018-08-10
Mode of Operation:	Tx mode

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Test Method:

A temporary antenna connector was soldered to the RF output. The RF output of the EUT was connected to the spectrum analyzer. All the attenuation or cable loss will be added to the measured maximum output power. The results are recorded in Watt.

Spectrum Analyzer Setting:

RBW = 3 MHz, VBW= 3MHz, Sweep = Auto, Span: Approximately five times the 20 dB bandwidth
Detector = Peak, Trace = Max. hold

Test Setup:



Note: a temporary antenna connector was soldered to the RF output.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Limits for Maximum Peak Conducted Output Power [FCC 47CFR 15.247]:

The maximum peak output power shall not exceeded the following limits: For frequency hopping systems employing at least 75 hopping channels: 1 Watt For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 Watts For Digital Transmission systems in 2400-2483.5 MHz Band: 1 Watt

Results of Bluetooth Communication mode (GFSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000323

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000301

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000249

Results of Bluetooth Communication mode (π/4-DQPSK) (Fundamental Power): Pass

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2402	0.000425

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2441	0.000396

Transmitter Frequency (MHz)	Maximum conducted output power (Watt)
2480	0.000327

Calculated measurement uncertainty : 30MHz to 1GHz 1.7dB
1GHz to 18GHz 1.7dB

Remark:
1. All test data for each data rate were verified, but only the worst case was reported.
2. The EUT is programmed to transmit signals continuously for all testing.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Test plot of Maximum Peak Conducted Output Power :

Bluetooth Communication mode (GFSK, 2402MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Bluetooth Communication mode (GFSK, 2441MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Bluetooth Communication mode (GFSK, 2480MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Bluetooth Communication mode (π/4 DQPSK, 2402MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Bluetooth Communication mode (π/4 DQPSK, 2441MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Bluetooth Communication mode (π/4 DQPSK, 2480MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.2 Radiated Spurious Emissions

Test Requirement:	FCC 47CFR 15.209
Test Method:	ANSI C63.10:2013
Test Date:	2018-08-08 to 2018-10-18
Mode of Operation:	Tx mode / Bluetooth Communication mode (GFSK)

Ambient Temperature: 24℃ Relative Humidity: 52% Atmospheric Pressure: 101 kPa

Test Method:

For emission measurements at or below 1 GHz, the sample was placed 0.8m above the ground plane of semi-anechoic Chamber*. For emission measurements above 1 GHz, the sample was placed 1.5m above the ground plane of semi-anechoic Chamber*. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.

* Semi-Anechoic chamber located on the G/F of The Hong Kong Standards and Testing Centre Ltd. with a metal ground plane filed with the FCC pursuant to section 2.948 of the FCC rules, with Registration Number: 607756.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Spectrum Analyzer Setting:

9KHz – 30MHz (Pk & Av)	RBW:	10kHz
	VBW:	30kHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold
30MHz – 1GHz (QP)	RBW:	120kHz
	VBW:	120kHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold
Above 1GHz (Pk)	RBW:	1MHz
	VBW:	1MHz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold
Above 1GHz (Av)	RBW:	1MHz
	VBW:	10Hz
	Sweep:	Auto
	Span:	Fully capture the emissions being measured
	Trace:	Max. hold

Test Setup:



- Absorbers placed on top of the ground plane are for measurements above 1000MHz only.
- Measurements between 30MHz to 1000MHz made with Bi-log antennas, above 1000MHz horn antennas are used, 9kHz to 30MHz loop antennas are used.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Frequency Range	Quasi-Peak Limits
[MHz]	[μV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Result of Tx mode (2402.0 MHz) (GFSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (GFSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
4804.0	15.5	41.5	57.0	74.0	17.0	Vertical
4804.0	13.1	42.4	55.5	74.0	18.5	Horizontal
7206.0	8.3	45.1	53.4	74.0	20.6	Vertical
7206.0	4.3	46.2	50.5	74.0	23.5	Horizontal
9608.0	8.2	48.0	56.2	74.0	17.8	Vertical
9608.0	5.4	48.8	54.2	74.0	19.8	Horizontal
12010.0	3.3	51.8	55.1	74.0	18.9	Vertical
12010.0	-1.0	52.4	51.4	74.0	22.6	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4804.0	1.8	41.5	43.3	54.0	10.7	Vertical
4804.0	-1.1	42.4	41.3	54.0	12.7	Horizontal
7206.0	-4.5	45.1	40.6	54.0	13.4	Vertical
7206.0	-8.9	46.2	37.3	54.0	16.7	Horizontal
9608.0	-5.3	48.0	42.7	54.0	11.3	Vertical
9608.0	-7.7	48.8	41.1	54.0	12.9	Horizontal
12010.0	-9.5	51.8	42.3	54.0	11.7	Vertical
12010.0	-15.3	52.4	37.13	54.0	16.9	Horizontal

Result of Tx mode (2441.0 MHz) (GFSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2441.0 MHz) (GFSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4882.0	15.2	41.6	56.8	74.0	17.2	Vertical
4882.0	11.1	42.5	53.6	74.0	20.4	Horizontal
7323.0	7.0	45.2	52.2	74.0	21.8	Vertical
7323.0	4.2	46.3	50.5	74.0	23.5	Horizontal
9764.0	7.7	48.1	55.8	74.0	18.2	Vertical
9764.0	3.7	48.9	52.6	74.0	21.4	Horizontal
12205.0	4.5	51.6	56.1	74.0	17.9	Vertical
12205.0	0.8	52.5	53.3	74.0	20.7	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dB	E-Field Polarity
4882.0	0.1	41.6	41.7	54.0	12.3	Vertical
4882.0	-4.2	42.5	38.3	54.0	15.7	Horizontal
7323.0	-8.1	45.2	37.1	54.0	16.9	Vertical
7323.0	-9.6	46.3	36.7	54.0	17.3	Horizontal
9764.0	-8.3	48.1	39.8	54.0	14.2	Vertical
9764.0	-9.2	48.9	39.8	54.0	14.3	Horizontal
12205.0	-10.7	51.6	41.0	54.0	13.1	Vertical
12205.0	-12.7	52.5	39.8	54.0	14.2	Horizontal

Result of Tx mode (2480.0 MHz) (GFSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2480.0 MHz) (GFSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4960.0	12.8	41.4	54.2	74.0	19.8	Vertical
4960.0	10.9	42.7	53.6	74.0	20.4	Horizontal
7440.0	7.2	45.6	52.8	74.0	21.3	Vertical
7440.0	3.7	46.5	50.2	74.0	23.8	Horizontal
9920.0	6.5	48.6	55.1	74.0	18.9	Vertical
9920.0	3.95	49.7	53.7	74.0	20.4	Horizontal
12400.0	2.6	51.7	54.3	74.0	19.7	Vertical
12400.0	-1.1	52.7	51.6	74.0	22.4	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4960.0	-0.8	41.4	40.6	54.0	13.4	Vertical
4960.0	-0.6	42.7	42.1	54.0	11.9	Horizontal
7440.0	-9.2	45.6	36.4	54.0	17.6	Vertical
7440.0	-11.7	46.5	34.8	54.0	19.2	Horizontal
9920.0	-8.1	48.6	40.5	54.0	13.5	Vertical
9920.0	-11.4	49.7	38.3	54.0	15.7	Horizontal
12400.0	-13.4	51.7	38.3	54.0	15.7	Vertical
12400.0	-16.6	52.7	36.1	54.0	17.9	Horizontal

Result of Tx mode (2402.0 MHz) (π/4-DQPSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2402.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4804.0	15.3	41.5	56.8	74.0	17.2	Vertical
4804.0	12.2	42.4	54.6	74.0	19.4	Horizontal
7206.0	9.9	45.1	55.0	74.0	19.0	Vertical
7206.0	6.1	46.2	52.3	74.0	21.7	Horizontal
9608.0	8.5	48.0	56.5	74.0	17.5	Vertical
9608.0	4.3	48.8	53.1	74.0	20.9	Horizontal
12010.0	3.7	51.8	55.5	74.0	18.5	Vertical
12010.0	-2.0	52.4	50.4	74.0	23.6	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4804.0	1.5	41.5	43.0	54.0	11.0	Vertical
4804.0	-1.9	42.4	40.5	54.0	13.5	Horizontal
7206.0	-2.9	45.1	42.2	54.0	11.8	Vertical
7206.0	-7.1	46.2	39.1	54.0	14.9	Horizontal
9608.0	-5.1	48.0	42.9	54.0	11.1	Vertical
9608.0	-8.8	48.8	40.0	54.0	14.0	Horizontal
12010.0	-9.1	51.8	42.7	54.0	11.3	Vertical
12010.0	-16.3	52.4	36.07	54.0	17.9	Horizontal

Result of Tx mode (2441.0 MHz) (π/4-DQPSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2441.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4882.0	14.9	41.6	56.5	74.0	17.5	Vertical
4882.0	10.2	42.5	52.7	74.0	21.3	Horizontal
7323.0	6.3	45.2	51.5	74.0	22.5	Vertical
7323.0	4.6	46.3	50.9	74.0	23.1	Horizontal
9764.0	8.2	48.1	56.3	74.0	17.7	Vertical
9764.0	2.9	48.9	51.8	74.0	22.2	Horizontal
12205.0	4.4	51.6	56.0	74.0	18.0	Vertical
12205.0	0.1	52.5	52.6	74.0	21.4	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBuV	Correction Factor dB/m	Field Strength dBuV/m	Limit @3m dBuV/m	Margin dB	E-Field Polarity
4882.0	-0.2	41.6	41.4	54.0	12.6	Vertical
4882.0	-5.2	42.5	37.4	54.0	16.7	Horizontal
7323.0	-8.8	45.2	36.4	54.0	17.6	Vertical
7323.0	-9.2	46.3	37.1	54.0	16.9	Horizontal
9764.0	-6.4	48.1	41.7	54.0	12.3	Vertical
9764.0	-10.0	48.9	38.9	54.0	15.1	Horizontal
12205.0	-10.8	51.6	40.8	54.0	13.2	Vertical
12205.0	-13.3	52.5	39.2	54.0	14.8	Horizontal

Result of Tx mode (2480.0 MHz) (π/4-DQPSK) (9kHz – 30MHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level dBuV	Correction Factor dB/m	Field Strength dBuV/m	Field Strength uV/m	Limit uV/m	E-Field Polarity
Emissions detected are more than 20 dB below the FCC Limits						

Result of Tx mode (2480.0 MHz) (π/4-DQPSK) (Above 1GHz): Pass

Field Strength of Spurious Emissions Peak Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4960.0	13.4	41.4	54.8	74.0	19.2	Vertical
4960.0	9.7	42.7	52.4	74.0	21.6	Horizontal
7440.0	8.6	45.6	54.2	74.0	19.8	Vertical
7440.0	5.1	46.5	51.6	74.0	22.5	Horizontal
9920.0	7.6	48.6	56.2	74.0	17.8	Vertical
9920.0	4.32	49.7	54.0	74.0	20.0	Horizontal
12400.0	3.6	51.7	55.3	74.0	18.7	Vertical
12400.0	-1.0	52.7	51.7	74.0	22.3	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Spurious Emissions Average Value						
Frequency MHz	Measured Level @3m dBµV	Correction Factor dB/m	Field Strength dBµV/m	Limit @3m dBµV/m	Margin dB	E-Field Polarity
4960.0	-0.3	41.4	41.1	54.0	12.9	Vertical
4960.0	-4.9	42.7	37.8	54.0	16.2	Horizontal
7440.0	-7.8	45.6	37.8	54.0	16.2	Vertical
7440.0	-10.3	46.5	36.2	54.0	17.8	Horizontal
9920.0	-7.0	48.6	41.6	54.0	12.4	Vertical
9920.0	-11.0	49.7	38.7	54.0	15.3	Horizontal
12400.0	-12.4	51.7	39.3	54.0	14.7	Vertical
12400.0	-16.5	52.7	36.2	54.0	17.8	Horizontal

Remarks:
No additional spurious emissions found between lowest internal used/generated frequency and 30 MHz

* Denotes restricted band of operation.
Measurements were made using a peak detector. Any emission less than 1000MHz and falling within the restricted bands of FCC Rules Part 15 Section 15.205 and the limits of FCC Rules Part 15 Section 15.209 were applied.

Correction Factor included Antenna Factor and Cable Attenuation.

Calculated measurement uncertainty (9kHz-30MHz): 2.0dB
(30MHz -1GHz): 4.9dB
(1GHz -6GHz): 4.02dB
(6GHz -26.5GHz): 4.03dB

Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Radiated Emissions Measurement:

Limit：

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).

Result： RF Radiated Emissions (Lowest)-GFSK

Field Strength of Band-edge Compliance Peak Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2390.0	20.1	36.8	56.9	74.0	17.1	Vertical
2390.0	19.4	36.4	55.8	74.0	18.2	Horizontal

Field Strength of Band-edge Compliance Average Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2390.0	4.8	36.8	41.6	54.0	12.5	Vertical
2390.0	2.9	36.4	39.3	54.0	14.7	Horizontal

Result： RF Radiated Emissions (Highest) -GFSK

Field Strength of Band-edge Compliance Peak Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2483.5	16.2	36.8	53.0	74.0	21.0	Vertical
2483.5	15.4	36.4	51.8	74.0	22.3	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Field Strength of Band-edge Compliance Average Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2483.5	-0.3	36.8	36.5	54.0	17.5	Vertical
2483.5	-1.4	36.4	35.0	54.0	19.0	Horizontal

Result: RF Radiated Emissions (Lowest)- π/4-DQPSK

Field Strength of Band-edge Compliance Peak Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2390.0	20.0	36.8	56.8	74.0	17.2	Vertical
2390.0	19.1	36.4	55.5	74.0	18.6	Horizontal

Field Strength of Band-edge Compliance Average Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2390.0	4.6	36.8	41.4	54.0	12.6	Vertical
2390.0	2.6	36.4	39.0	54.0	15.0	Horizontal

Result: RF Radiated Emissions (Highest) -π/4-DQPSK

Field Strength of Band-edge Compliance Peak Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2483.5	16.9	36.8	53.7	74.0	20.3	Vertical
2483.5	14.7	36.4	51.1	74.0	22.9	Horizontal

Field Strength of Band-edge Compliance Average Value						
Frequency MHz	Measured Level @3m dBμV	Correction Factor dB/m	Field Strength dBμV/m	Limit @3m dBμV/m	Margin dB	E-Field Polarity
2483.5	0.4	36.8	37.2	54.0	16.8	Vertical
2483.5	-2.1	36.4	34.3	54.0	19.7	Horizontal

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Ambient temperature 25°C Relative humidity 57%

Frequency Range	Quasi-Peak Limits
[MHz]	[μV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results of Bluetooth mode (Output: Full Load)(GFSK 2402.0 MHz) (30MHz – 1GHz): Pass

Please refer to the following table for result details(The data is the worst cases)

Horizontal



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Result of Bluetooth mode (Output: Full Load) (GFSK 2402.0 MHz) (30MHz – 1GHz): Pass

Radiated Emissions Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dBμV/m	Limit @3m dBμV/m	Level @3m μV/m	Limit @3m μV/m
196.1	Horizontal	36.5	43.5	66.8	150
258.5	Horizontal	37.6	46.0	75.9	200
288.9	Horizontal	40.0	46.0	100.0	200

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Limits for Radiated Emissions FCC 47 CFR 15.247 Class B]:

Ambient temperature 25°C Relative humidity 57%

Frequency Range	Quasi-Peak Limits
[MHz]	[μV/m]
0.009-0.490	2400/F (kHz)
0.490-1.705	24000/F (kHz)
1.705-30	30
30-88	100
88-216	150
216-960	200
Above960	500

The emission limits shown in the above table are based on measurement employing a CISPR quasi-peak detector and above 1000MHz are based on measurements employing an average detector.

Results of Bluetooth mode(Output: Full Load) (GFSK 2402.0 MHz) (30MHz – 1GHz): Pass

Please refer to the following table for result details(The data is the worst cases)

Vertical



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Result of Bluetooth mode(Output: Full Load) (GFSK 2402.0 MHz) (30MHz – 1GHz): Pass

Radiated Emissions Quasi-Peak					
Emission Frequency MHz	E-Field Polarity	Level @3m dBμV/m	Limit @3m dBμV/m	Level @3m μV/m	Limit @3m μV/m
50.4	Vertical	38.5	40.0	84.1	100
59.3	Vertical	37.3	40.0	73.3	100
61.9	Vertical	37.0	40.0	70.8	100

Remarks:
Calculated measurement uncertainty (30MHz – 1GHz): 4.9dB
Emissions in the vertical and horizontal polarizations have been investigated and the worst-case test results are recorded in this report.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.3 AC Mains Conducted Emissions (0.15MHz to 30MHz)

Test Requirement:	FCC 47CFR 15.207
Test Method:	ANSI C63.10:2013
Test Date:	2018-09-27
Mode of Operation:	Bluetooth mode
Test Voltage:	120Va.c. 60Hz

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Test Method:

The test was performed in accordance with ANSI ANSI C63.10:2013, with the following: an initial measurement was performed in peak and average detection mode on the live line, any emissions recorded within 30dB of the relevant limit line were re-measured using quasi-peak and average detection on the live and neutral lines with the worst case recorded in the table of results.

Receiver Setting:

Bandw. = 9 kHz, Meas. Time= 10.0 ms, Step Width = 5.0kHz
Detector = MaxPeak and CISPR AV

Test Setup:



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Limits for Conducted Emissions (FCC 47 CFR 15.207):

Frequency Range [MHz]	Quasi-Peak Limits [dBμV]	Average [dBμV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.

Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of Bluetooth mode(Output: Full Load) (L): PASS
Please refer to the following diagram for individual results.



Conductor Live or Neutral	Frequency MHz	Quasi-peak Level dBμV	Quasi-peak Limit dBμV	Average Level dBμV	Average Limit dBμV
Live	0.160	61.0	66.0	-*-	-*-
Live	2.935	27.7	56.0	-*-	-*-
Live	16.785	47.9	60.0	-*-	-*-
Live	0.160	-*-	-*-	41.4	56.0
Live	3.065	-*-	-*-	23.8	46.0
Live	16.940	-*-	-*-	39.2	50.0

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Frequency Range [MHz]	Quasi-Peak Limits [dBμV]	Average [dBμV]
0.15-0.5	66 to 56*	56 to 46*
0.5-5.0	56	46
5.0-30.0	60	50

* Decreases with the logarithm of the frequency.
Limits for Conducted Emissions Test, please refer to limit lines (Quasi-Peak and Average) in the following diagram.

Results of Bluetooth mode(Output: Full Load) (N): PASS
Please refer to the following diagram for individual results.



Conductor Live or Neutral	Frequency MHz	Quasi-peak Level dBμV	Quasi-peak Limit dBμV	Average Level dBμV	Average Limit dBμV
Neutral	0.155	59.9	66.0	-*-	-*-
Neutral	4.940	29.2	56.0	-*-	-*-
Neutral	16.850	43.9	60.0	-*-	-*-
Neutral	0.155	-*-	-*-	38.0	56.0
Neutral	4.855	-*-	-*-	23.0	46.0
Neutral	16.615	-*-	-*-	35.0	50.0

Remarks:
Calculated measurement uncertainty (0.15MHz – 30MHz): 3.25dB
-*- Emission(s) that is far below the corresponding limit line.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.4 Number of Hopping Frequency

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Limit of Number of Hopping Frequency

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels

Test Method:

The RF output of the EUT was connected to the spectrum analyzer by a low loss cable.

Spectrum Analyzer Setting:

RBW = 300kHz, VBW ≥ RBW, Sweep = Auto, Span = the frequency band of operation
Detector = Peak, Trace = Max. hold

Test Setup:
As Test Setup of clause 3.1.1 in this test report.

Measurement Data:
GFSK: 79 of 79 Channel



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

π/4-DQPSK: 79 of 79 Channel



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.5 20dB Bandwidth

Test Requirement:	FCC 47CFR 15.247(a)(1)
Test Method:	ANSI C63.10:2013
Test Date:	2018-08-08
Mode of Operation:	Tx mode

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Remark:
The result has been done on all the possible configurations for searching the worst cases.

Test Method:

The bandwidth is measured at an amplitude level reduced from the reference level by a specified ratio. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst-case (i.e. the widest) bandwidth.

Spectrum Analyzer Setting:

RBW = 30kHz, VBW ≥ RBW, Sweep = Auto, Span = two times and five times the OBW
Detector = Peak, Trace = Max. hold

Test Setup:

As Test Setup of clause 3.1.1 in this test report.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.086	Within 2400-2483.5

(Lowest Operating Frequency) - (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.086	Within 2400-2483.5

(Middle Operating Frequency) - (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.086	Within 2400-2483.5

(Highest Operating Frequency) - (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2402	1.368	Within 2400-2483.5

(Lowest Operating Frequency) - (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2441	1.368	Within 2400-2483.5

(Middle Operating Frequency) - (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fundamental Frequency [MHz]	20dB Bandwidth [MHz]	FCC Limits [MHz]
2480	1.368	Within 2400-2483.5

(Highest Operating Frequency) - (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.6 Hopping Channel Separation

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Requirements:

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

Spectrum Analyzer Setting:

RBW = 300kHz, VBW ≥ RBW, Sweep = Auto,
Span = Wide enough to captur the peaks of two adjacent channels
Detector = Peak, Trace = Max. hold

Limit:

The measured maximum bandwidth * 2/3 = 1.086MHz * 2/3 =724kHz (GFSK)

The measured maximum bandwidth * 2/3 = 1.368MHz * 2/3 =912kHz (π/4 DQPSK)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>724.0kHz) （Lowest） (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>724.0kHz) （Mid） (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>724.0kHz) （Highest） (GFSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>912kHz) （Lowest） (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>912kHz) （Mid） (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Channel separation = 1MHz (>912kHz) （Highest） (π/4 DQPSK)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.7 Band-edge Compliance of RF Conducted Emissions Measurement:

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Limit：
In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.
According to the test method DA 00-705.

Spectrum Analyzer Setting:
RBW = 100kHz, VBW= 300kHz, Sweep = Coupled,
Span = Wide enough to captur the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
Detector = Peak, Trace = Max. hold

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Conducted Emission Attenuated below the Fundamental [dB]
2400 – Lowest Fundamental (2402)	33.37

Band-edge Compliance of RF Emissions – Lowest (GFSK) (Hopping on)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Conducted Emission Attenuated below the Fundamental [dB]
2400 – Lowest Fundamental (2402)	30.63

Band-edge Compliance of RF Emissions – Lowest (GFSK) (Hopping off)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Conducted Emission Attenuated below the Fundamental [dB]
2483.5 - Highest Fundamental (2480)	50.19

Band-edge Compliance of RF Emissions – Highest (GFSK) (Hopping on)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2483.5 - Highest Fundamental (2480)	49.17

Band-edge Compliance of RF Emissions – Highest (GFSK) (Hopping off)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400 – Lowest Fundamental (2402)	33.16

Band-edge Compliance of RF Emissions – Lowest (π/4 DQPSK) (Hopping on)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2400 – Lowest Fundamental (2402)	30.62

Band-edge Compliance of RF Emissions – Lowest (π/4 DQPSK) (Hopping off)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2483.5 - Highest Fundamental (2480)	50.79

Band-edge Compliance of RF Emissions – Highest (π/4 DQPSK) (Hopping on)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Frequency Range [MHz]	Radiated Emission Attenuated below the Fundamental [dB]
2483.5 - Highest Fundamental (2480)	49.51

Band-edge Compliance of RF Emissions – Highest (π/4 DQPSK) (Hopping off)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Conducted Emissions Measurement:

Limit：

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required.

Remark: Emissions under the fixed frequency mode and hopping mode have been investigated, the worst-case measurement results were recorded in the test report

Band-edge Compliance of RF Emissions – (GFSK 2402MHz) (the worst case)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Band-edge Compliance of RF Emissions – (π/4-DQPSK 2402MHz) (the worst case)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.8 Time of Occupancy (Dwell Time)

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Requirements:
The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channel employed.
No requirements for Digital Transmission System.

Spectrum Analyzer Setting:
RBW = 300kHz, VBW⩾RBW,
Sweep = A longer sweep time to show two successive hops on a channel,
Span = Zero, Detector = Peak, Trace = Max. hold

Dwell Time = Pulse Duration * hop rate / number of channel * observation duration
Observed duration: 0.4s x 79 = 31.6s

Measurement Data:
Channel Occupied in π/4-DQPSK: 79 of 79 Channel



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

DH5 Packet:

DH5 Packet permit maximum 1600/79/6 = 3.37 hops per second in each channel (5 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times 3.37 x 31.6 = 106.6 within 31.6 seconds

Fig. A
[Pulse duration of Lowest Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. B
[Pulse duration of Middle Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. C
[Pulse duration of Highest Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

DH3 Packet:

DH3 Packet permit maximum 1600/79/4 = 5.06 hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times 5.06 x 31.6 = 160 within 31.6 seconds

Fig. D
[Pulse duration of Lowest Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. E
[Pulse duration of Middle Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. F
[Pulse duration of Highest Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

DH1 Packet:

DH1 Packet permit maximum 1600/79/2 = 10.12 hops per second in each channel (3 time slots RX, 1 time slot TX). The Dwell time is the time duration of the pulse times 10.12 x 31.6 = 320 within 31.6 seconds

Fig. G
[Pulse duration of Lowest Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. H
[Pulse duration of Middle Channel]



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Fig. I
[Pulse duration of Highest Channel]



Time of occupancy (Dwell Time):

Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Results
DH5	2402	2.930	0.312	0.400	Complies
DH5	2441	2.940	0.313	0.400	Complies
DH5	2480	2.940	0.313	0.400	Complies
DH3	2402	1.680	0.269	0.400	Complies
DH3	2441	1.680	0.269	0.400	Complies
DH3	2480	1.680	0.269	0.400	Complies
DH1	2402	0.430	0.138	0.400	Complies
DH1	2441	0.430	0.138	0.400	Complies
DH1	2480	0.430	0.138	0.400	Complies

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.9 Channel Centre Frequency

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Requirements:
Frequency hopping system in the 2400-2483.5MHz band shall use at least 79 (Channel 1 to 79) non-overlapping channels.

The EUT operates in according with the Bluetooth system specification within the 2400 - 2483.5 MHz frequency band.
RF channels for Bluetooth systems are spaced 1 MHz and are ordered in channel number k. In order to comply with out-of-band regulations, a lower frequency guard band of 2.0 MHz and a higher frequency guard band of 3.5MHz is used.

The operating frequencies of each channel are as follows:

First RF channel start from 2400MHz + 2MHz guard band = 2402MHz
Frequency of RF Channel = 2402+k MHz, k = 1,…,79 (Channel separation = 1MHz)

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.10 Pseudorandom Hopping Algorithm

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Requirements:
The channel frequencies shall be selected from a pseudorandom ordered list of hopping frequencies. Each frequency must be used equally by the transmitter.

EUT Pseudorandom Hopping Algorithm
The EUT is a Bluetooth device, the Pseudo-random hopping pattern; hopping characteristics and algorithm are based on the Bluetooth specification.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

3.1.11 Antenna Requirement

Ambient Temperature: 25℃ Relative Humidity: 51% Atmospheric Pressure: 101 kPa

Test Requirements: § 15.203

Test Specification:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Test Results:

This is PCB antenna. There is no external antenna, the antenna gain = 0dBi. User is unable to remove or changed the Antenna.

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Appendix A

List of Measurement Equipment

Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM215	MULTIDEVICE CONTROLLER	EMCO	2090	00024676	N/A	N/A
EM217	ELECTRIC POWERED TURNTABLE	EMCO	2088	00029144	N/A	N/A
EM218	ANECHOIC CHAMBER	ETS-LINDGREN	FACT-3	--	2018/01/24	2019/01/24
EM356	ANTENNA POSITIONING TOWER	ETS-LINDGREN	2171B	00150346	N/A	N/A
EM354	BICONILOG ANTENNA	ETS-LINDGREN	3143B	00142073	2018/03/29	2020/03/29
EM229	EMI TEST RECEIVER	R&S	ESIB40	100248	2018/06/01	2019/06/01
EM276	BROADBAND HORN ANTENNA	A-INFOMW	JXTXLB-10180-SF	J2031090903007	2018/04/27	2020/04/27
EM300	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-09	00130130	2018/05/13	2019/05/13
EM301	PYRAMIDAL STANDARD GAIN HORN ANTENNA	ETS-LINDGREN	3160-10	00130988	2018/05/13	2019/05/13
EM302	PRECISION OMNIDIRECTIONAL DIPOLE (1 – 6GHZ)	SEIBERSDORF LABORATORIES	POD 16	161806/L	2018/05/11	2020/05/11
EM303	PRECISION OMNIDIRECTIONAL DIPOLE (6 – 18GHZ)	SEIBERSDORF LABORATORIES	POD 618	6181908/L	2018/05/11	2020/05/11
EM353	LOOP ANTENNA	ETS_LINDGREN	6502	00206533	2018/04/16	2020/04/16
EM045	POWER METER	ROHDE & SCHWARZ	NRVD	843246/028	2018/06/01	2020/06/01

Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL	DUE CAL
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	2017/11/29	2018/11/29
EM145	EMI TEST RECEIVER	R & S	ESCS 30	830245/021	2018/06/01	2019/06/01
EM179	IMPULSE LIMITER	ROHDE & SCHWARZ	ESH3-Z2	357-8810.52/54	2018/01/11	2019/01/11
EM154	SHIELDING ROOM	SIEMENS MATSUSHITA COMPONENTS	N/A	803-740-057-99A	2017/02/02	2022/02/02
N/A	MEASUREMENT AND EVALUATION SOFTWARE	ROHDE & SCHWARZ	BSIB-K1	V1.20	N/A	N/A

Remarks:-

CM Corrective Maintenance
N/A Not Applicable
TBD To Be Determined

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Appendix B

Photographs of EUT

View of the product

View of the product

Inside View of the product

Inner Circuit Top View



Inner Circuit Bottom View



Inner Circuit Top View



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Photographs of EUT

Inner Circuit Bottom View



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Photographs of EUT

Measurement of Radiated Emission Test Set Up (9kHz to 30MHz)



Measurement of Radiated Emission Test Set Up (30MHz to 1000MHz)



This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Photographs of EUT

Measurement of Radiated Emission Test Set Up (Above 1000MHz)



Measurement of Conducted Emission Test Set Up



******* End of Test Report *******

This report shall not be reproduced unless with prior written approval from The Hong Kong Standards and Testing Centre Limited.
For Conditions of Issuance of this test report, please refer to “Conditions of Issuance of Test Reports” section or Website.

Conditions of Issuance of Test Reports

1. All samples and goods are accepted by The Hong Kong Standards & Testing Centre Limited (the "Company") solely for testing and reporting in accordance with the following terms and conditions. The Company provides its services on the basis that such terms and conditions constitute express agreement between the Company and any person, firm or company requesting its services (the "Clients").

2. Any report issued by the Company as a result of this application for testing service (the "Report") shall be issued in confidence to the Clients and the Report will be strictly treated as such by the Company. It may not be reproduced either in its entirety or in part and it may not be used for advertising or other unauthorized purposes without the written consent of the Company. The Clients to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Company to his customer, supplier or other persons directly concerned. The Company will not, without the consent of the Clients, enter into any discussion or correspondence with any third party concerning the contents of the Report, unless required by the relevant governmental authorities, laws or court orders.

3. The Company shall not be called or be liable to be called to give evidence or testimony on the Report in a court of law without its prior written consent, unless required by the relevant governmental authorities, laws or court orders.

4. The Report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Company and is stated as such in the Report.

5. In the event of the improper use the report as determined by the Company, the Company reserves the right to withdraw it, and to adopt any other additional remedies which may be appropriate.

6. Sample submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Company.

7. The Company will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication whatsoever about its said tests or investigations.

8. Clients wishing to use the Report in court proceedings or arbitration shall inform the Company to that effect prior to submitting the sample for testing.

9. Subject to the variable length of retention time for test data and report stored hereinto as to otherwise specifically required by individual accreditation authorities, the Company will only keep the supporting test data and information of this test report for a period of three years. The data and information will be disposed of after the aforementioned retention period has elapsed. Under no circumstances shall we provide any data and information which has been disposed of after the retention period. Under no circumstances shall we be liable for damages of any kind, including (but not limited to) compensatory damages, lost profits, lost data, or any form of special, incidental, indirect, consequential or punitive damages of any kind, whether based on breach of contract of warranty, tort (including negligence), product liability or otherwise, even if we are informed in advance of the possibility of such damages.

10. Issuance records of the Report are available on the internet at www.stc-group.org. Further enquiry of validity or verification of the Reports should be addressed to the Company.