

RF EXPOSURE EVALUATION

EUT Specification

EUT	Levitating Bluetooth Speaker
Frequency band (Operating)	☐ WLAN: 2.412GHz ~ 2.462GHz ☐ WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz ☐ WLAN: 5.745GHz ~ 5825GHz ☒ Others(Bluetooth: 2.402GHz ~ 2.480GHz)
Device category	☐ Portable (<20cm separation) ☒ Mobile (>20cm separation) ☐ Others ____
Antenna diversity	☒ Single antenna ☐ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Max. output power	-2.44dBm(0.57mW) for BT 2.1+EDR 3.45dBm(2.21mW) for BLE
Antenna gain	0dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE, $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm (mW/cm^2)	Power density Limits (mW/cm^2)
GFSK						
Low	2402.00	-5.78	± 0.2	0.28	$5.50e-5$	1
Middle	2441.00	-4.47	± 0.2	0.37	$7.44e-5$	1
High	2480.00	-4.28	± 0.2	0.39	$7.78e-5$	1
$\pi/4$ -DQPSK						
Low	2402.00	-6.52	± 0.2	0.23	$4.64e-5$	1
Middle	2441.00	-4.91	± 0.2	0.34	$6.73e-5$	1
High	2480.00	-4.71	± 0.2	0.35	$7.04e-5$	1
8DPSK						
Low	2402.00	-3.71	± 0.2	0.45	$8.87e-5$	1
Middle	2441.00	-2.44	± 0.2	0.60	$1.19e-4$	1
High	2480.00	-2.76	± 0.2	0.55	$1.10e-4$	1
BLE GFSK						
Low	2402.00	1.38	± 0.2	1.44	$2.86e-4$	1
Middle	2442.00	2.70	± 0.2	1.95	$3.88e-4$	1
High	2480.00	3.45	± 0.2	2.32	$4.61e-4$	1