

Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g SAR and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where:

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mod e	P_{max} Conducte d power (dBm)	P_{max} Conducte d power (mW)	Tune- up (dBm)	Tune -up (mW)	Distanc e (mm)	f (GHz)	Calculatio n Result	SAR Exclusio n threshold	SAR test exclusio n
BT	1.37	1.37	2	1.58	<5	2.480	0.5	3.0	Yes

NOTE: Standalone SAR test exclusion for BT

When standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}/x}] \leq 1.6$ W/kg for test separation distances ≤ 50 mm, where $x = 7.5$ for 1-g SAR and $x = 18.75$ for 10-g SAR.

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Mode	P_{max} Conducted power (dBm)	P_{max} Conducted power (mW)	Tune-up (dBm)	Tune- up (mW)	Distance (mm)	f (GHz)	x	Estimated SAR (W/Kg)
BT	1.37	1.37	2	1.58	<5	2.480	7.5	0.066

NOTE: Estimated SAR calculation for BT

Conclusion:

For the max result : $0.066\text{W/Kg} \leq \text{FCC Limit } 1.6\text{W/Kg}$ for 1g SAR.

Jason chen

Signature:

Date: 2016-8-19

NAME AND TITLE (Please print or type): Jason Chen /Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.