

TEST REPORT

FCC ID: 2AEF5M10G1BA01

Product: Minno10

Model No.: M10G1BA01

Additional Model No.: A10G1BA01

Trade Mark: Minno, Armtab

Report No.: TCT150225E013

Issued Date: Apr. 20, 2015

Issued for:

Minno LLC

421 North Milpas Street, Santa Barbara, CA 93103 U.S.A.

Issued By:

Shenzhen Tongce Testing Lab.

1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

TEL: +86-755-27673339

FAX: +86-755-27673332

Note: This report shall not be reproduced except in full, without the written approval of Shenzhen Tongce Testing Lab.

This document may be altered or revised by Shenzhen Tongce Testing Lab. personnel only, and shall be noted in the revision section of the document. The test results in the report only apply to the tested sample.

TABLE OF CONTENTS

1. Test Certification.....	3
2. Test Result Summary	4
3. EUT Description	5
4. Genera Information.....	6
4.1. TEST ENVIRONMENT AND MODE	6
4.2. DESCRIPTION OF SUPPORT UNITS	6
5. Facilities and Accreditations	7
5.1. FACILITIES.....	7
5.2. LOCATION	7
5.3. MEASUREMENT UNCERTAINTY	7
6. Test Results and Measurement Data	8
6.1. ANTENNA REQUIREMENT	8
6.2. CONDUCTED EMISSION.....	9
6.3. CONDUCTED OUTPUT POWER.....	13
6.4. 20dB OCCUPY BANDWIDTH.....	15
6.5. CARRIER FREQUENCIES SEPARATION	20
6.6. HOPPING CHANNEL NUMBER.....	25
6.7. DWELL TIME.....	28
6.8. PSEUDORANDOM FREQUENCY HOPPING SEQUENCE.....	31
6.9. CONDUCTED BAND EDGE MEASUREMENT	32
6.10. CONDUCTED SPURIOUS EMISSION MEASUREMENT	36
6.11. RADIATED SPURIOUS EMISSION MEASUREMENT	40
7. Photographs of Test Configuration	47
8. Photographs of EUT	49

1. Test Certification

Product:	Minno10
Model No.:	M10G1BA01
Additional Model No.	A10G1BA01
Applicant:	Minno LLC
Address:	421 North Milpas Street, Santa Barbara, CA 93103 U.S.A.
Manufacturer:	Shenzhen Longhorn Technology Co.,Ltd.
Address:	Longhorn Hi-Tech Estate, Gongyeyuan Rd., Dalang Street, Baoan, Shenzhen, China.
Date of Test:	Mar. 02 – Mar. 31, 2015
Applicable Standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247

The above equipment has been tested by Shenzhen Tongce Testing Lab. and found compliance with the requirements set forth in the technical standards mentioned above. The results of testing in this report apply only to the product/system, which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Tested By: 
_____ **SKY**

Date: Mar. 31, 2015

Reviewed By: 
_____ **Joe Zhou**

Date: Apr. 17, 2015

Approved By: 
_____ **Tomsin**

Date: Apr. 20, 2015

2. Test Result Summary

Requirement	CFR 47 Section	Result
Antenna Requirement	§15.203/§15.247 (c)	PASS
AC Power Line Conducted Emission	§15.207	PASS
Conducted Peak Output Power	§15.247 (b)(1)	PASS
20dB Occupied Bandwidth	§15.247 (a)(1)	PASS
Carrier Frequencies Separation	§15.247 (a)(1)	PASS
Hopping Channel Number	§15.247 (a)(1)	PASS
Dwell Time	§15.247 (a)(1)	PASS
Radiated Emission	§15.205/§15.209	PASS
Band Edge	§15.247(d)	PASS

Note:

1. PASS: Test item meets the requirement.
2. Fail: Test item does not meet the requirement.
3. N/A: Test case does not apply to the test object.
4. The test result judgment is decided by the limit of test standard.

3. EUT Description

Product Name:	Minno10
Model :	M10G1BA01
Additional Model:	A10G1BA01
Trade Mark:	Minno, Armtab
Operation Frequency:	2402MHz~2480MHz
Transfer Rate:	1/2/3 Mbits/s
Number of Channel:	79
Modulation Type:	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology:	FHSS
Antenna Type:	Internal Antenna
Antenna Gain:	1.6dBi
Power Supply:	Rechargeable Li-ion Battery DC 3.7V, 4000mAh
Remark:	All models above are identical in interior structure, electrical circuits and components, and just differ in look and model for the marketing requirement.

Operation Frequency each of channel for GFSK, $\pi/4$ -DQPSK, 8DPSK

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
0	2402MHz	20	2422MHz	40	2442MHz	60	2462MHz
1	2403MHz	21	2423MHz	41	2443MHz	61	2463MHz
...	...	...	...	...	...	...	...
10	2412MHz	30	2432MHz	50	2452MHz	70	2472MHz
11	2413MHz	31	2433MHz	51	2453MHz	71	2473MHz
...	...	...	...	...	...	...	...
18	2420MHz	38	2440MHz	58	2460MHz	78	2480MHz
19	2421MHz	39	2441MHz	59	2461MHz	-	

Remark: Channel 0, 39 & 78 have been tested for GFSK, $\pi/4$ -DQPSK, 8DPSK modulation mode.

4. General Information

4.1. Test environment and mode

Operating Environment:	
Temperature:	24.0 °C
Humidity:	54 % RH
Atmospheric Pressure:	1010 mbar
Test Mode:	
Operation mode:	Keep the EUT in continuous transmitting with modulation
The sample was placed 0.8m above the ground plane of 3m chamber. Measurements in both horizontal and vertical polarities were performed. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, rotating the turntable, varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The emissions worst-case are shown in Test Results of the following pages.	

4.2. Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Equipment	Model No.	Serial No.	FCC ID	Trade Name
/	/	/	/	/

Note:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

5. Facilities and Accreditations

5.1. Facilities

The test facility is recognized, certified, or accredited by the following organizations:

- FCC - Registration No.: 572331

Shenzhen Tongce Testing Lab

The 3m Semi-anechoic chamber has been registered and fully described in a report with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files.

- IC - Registration No.: 10668A-1

The 3m Semi-anechoic chamber of Shenzhen TCT Testing Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing

- CNAS - Registration No.: CNAS L6165

Shenzhen TCT Testing Technology Co., Ltd. is accredited to ISO/IEC 17025:2005 General Requirements for the Competence of Testing and Calibration laboratories for the competence of testing. The Registration No. is CNAS L6165.

5.2. Location

Shenzhen Tongce Testing Lab

Address: 1F, Leinuo Watch Building, Fuyong Town, Baoan Dist, Shenzhen, China

Tel: 86-755-36638142


5.3. Measurement Uncertainty

The reported uncertainty of measurement $y \pm U$, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95 %.

No.	Item	MU
1	Conducted Emission	$\pm 2.56\text{dB}$
2	RF power, conducted	$\pm 0.12\text{dB}$
3	Spurious emissions, conducted	$\pm 0.11\text{dB}$
4	All emissions, radiated(<1G)	$\pm 3.92\text{dB}$
5	All emissions, radiated(>1G)	$\pm 4.28\text{dB}$
6	Temperature	$\pm 0.1^{\circ}\text{C}$
7	Humidity	$\pm 1.0\%$


6. Test Results and Measurement Data

6.1. Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. 15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
E.U.T Antenna:	
The Bluetooth antenna is an internal PCB antenna which permanently attached, and the best case gain of the antenna is 1.6 dBi.	
	

6.2. Conducted Emission

6.2.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.207														
Test Method:	ANSI C63.4:2009														
Frequency Range:	150 kHz to 30 MHz														
Receiver setup:	RBW=9 kHz, VBW=30 kHz, Sweep time=auto														
Limits:	<table><tr><th rowspan="2">Frequency range (MHz)</th><th colspan="2">Limit (dBuV)</th></tr><tr><th>Quasi-peak</th><th>Average</th></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table>	Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)														
	Quasi-peak	Average													
0.15-0.5	66 to 56*	56 to 46*													
0.5-5	56	46													
5-30	60	50													
Test Setup:	Reference Plane  Remark: E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m														
Test Mode:	Refer to section 5.4 for details														
Test Procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2009 on conducted measurement.														
Test Result:	PASS														

6.2.2. Test Instruments


Conducted Emission Shielding Room Test Site (843)				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCS30	100139	Sep. 16, 2015
LISN	Schwarzbeck	NSLK 8126	8126453	Sep. 29, 2015
Coax cable	TCT	N/A	N/A	Sep. 15, 2015
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.2.3. Test data

Please refer to following diagram for individual

Conducted Emission on Line Terminal of the power line (150 kHz to 30MHz)



Site Chamber #1

Phase: L1

Temperature: 25 (C)


Limit: FCC PART15 Conduction(QP)

Power: AC 120V/60Hz

Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1539	24.60	11.49	36.09	65.78	-29.69	QP	
2		0.1539	6.57	11.49	18.06	55.78	-37.72	AVG	
3		0.3180	21.25	11.40	32.65	59.76	-27.11	QP	
4		0.3180	6.70	11.40	18.10	49.76	-31.66	AVG	
5		1.2477	16.14	11.29	27.43	56.00	-28.57	QP	
6		1.2477	5.91	11.29	17.20	46.00	-28.80	AVG	
7		2.7359	14.85	11.41	26.26	56.00	-29.74	QP	
8		2.7359	4.90	11.41	16.31	46.00	-29.69	AVG	
9		6.2852	19.44	10.80	30.24	60.00	-29.76	QP	
10		6.2852	3.80	10.80	14.60	50.00	-35.40	AVG	
11	*	20.2109	22.80	10.54	33.34	60.00	-26.66	QP	
12		20.2109	5.51	10.54	16.05	50.00	-33.95	AVG	

Conducted Emission on Neutral Terminal of the power line (150 kHz to 30MHz)



Site Chamber #1

Phase: **N**

Temperature: 25 (C)

Limit: FCC PART15 Conduction(QP)

Power: AC 120V/60Hz

Humidity: 55 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.1812	22.90	11.50	34.40	64.43	-30.03	QP	
2		0.1812	6.76	11.50	18.26	54.43	-36.17	AVG	
3		0.3023	19.44	11.43	30.87	60.18	-29.31	QP	
4		0.3023	8.07	11.43	19.50	50.18	-30.68	AVG	
5		0.5797	21.89	11.27	33.16	56.00	-22.84	QP	
6	*	0.5797	16.46	11.27	27.73	46.00	-18.27	AVG	
7		2.7516	15.76	11.41	27.17	56.00	-28.83	QP	
8		2.7516	8.56	11.41	19.97	46.00	-26.03	AVG	
9		6.0703	21.49	10.78	32.27	60.00	-27.73	QP	
10		6.0703	5.76	10.78	16.54	50.00	-33.46	AVG	
11		21.4727	22.74	10.62	33.36	60.00	-26.64	QP	
12		21.4727	8.53	10.62	19.15	50.00	-30.85	AVG	

Note:

Freq. = Emission frequency in MHz

Reading level (dBuV) = Receiver reading

Corr. Factor (dB) = Antenna factor + Cable loss

Measurement (dBuV) = Reading level (dBuV) + Corr. Factor (dB)

Limit (dBuV) = Limit stated in standard

Margin (dB) = Measurement (dBuV) – Limits (dBuV)


Q.P. =Quasi-Peak

AVG =average

* is meaning the worst frequency has been tested in the frequency range 150 kHz to 30MHz.

6.3. Conducted Output Power

6.3.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	Section 15.247 (b) The maximum peak conducted output power of the intentional radiator shall not exceed the following: (1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.
Test Setup:	 <pre> graph LR PM[Power Meter] --- A[Attenuator] --- EUT[EUT] </pre>
Test Mode:	Refer to section 4.1 for details
Test Procedure:	1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. 2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Measure the conducted output power with cable loss and record the results in the test report. 5. Measure and record the results in the test report.
Test Result:	PASS

6.3.2. Test Instruments

Equipment	Manufacturer	Model	Serial Number	Calibration Due
Power Meter	Anritsu	ML2495A	1005002	Dec. 11, 2015
Pulse Power Sensor	Anritsu	MA2411B	0917070	Dec. 11, 2015

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.3.3. Test Data

GFSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	4.17	20.97	PASS
Middle	4.35	20.97	PASS
Highest	3.62	20.97	PASS

Pi/4DQPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.25	20.97	PASS
Middle	3.57	20.97	PASS
Highest	2.92	20.97	PASS

8DPSK mode			
Test channel	Peak Output Power (dBm)	Limit (dBm)	Result
Lowest	3.27	20.97	PASS
Middle	3.60	20.97	PASS
Highest	2.95	20.97	PASS

6.4. 20dB Occupy Bandwidth

6.4.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	N/A
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Non-hopping mode
Test Procedure:	1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement. Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel; RBW$\geq$1% of the 20 dB bandwidth; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold. 5. Measure and record the results in the test report.
Test Result:	PASS

6.4.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ROHDE&SCH WARZ	FSU3	1166.1660.03	Sep.16, 2015

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).


6.4.3. Test data

Test channel	20dB Occupy Bandwidth (kHz)			
	GFSK	$\pi/4$ -DQPSK	8DPSK	Conclusion
Lowest	737.18	1137.82	1141.83	PASS
Middle	745.19	1137.82	1137.82	PASS
Highest	741.19	1133.81	1129.81	PASS

Test plots as follows:


GFSK Modulation

Lowest channel




Date: 14.MAR.2015 16:40:00

Middle channel



Date: 14.MAR.2015 16:43:00


Highest channel



Date: 14.MAR.2015 16:43:53


Pi/4DQPSK Modulation

Lowest channel




Date: 14.MAR.2015 16:47:27

Middle channel



Date: 14.MAR.2015 16:46:51


Highest channel



Date: 14.MAR.2015 16:46:00


8DPSK Modulation

Lowest channel




Date: 14.MAR.2015 16:49:23

Middle channel



Date: 14.MAR.2015 16:50:59

Highest channel



Date: 14.MAR.2015 16:51:43

6.5. Carrier Frequencies Separation

6.5.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Hopping mode
Test Procedure:	1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = wide enough to capture the peaks of two adjacent channels; RBW$\geq$1% of the span; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold. 6. Measure and record the results in the test report.
Test Result:	PASS

6.5.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ROHDE&SCH WARZ	FSU3	1166.1660.03	Sep.16, 2015

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.5.3. Test data

GFSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	611.65	PASS
Middle	1002	611.65	PASS
Highest	1002	611.65	PASS

Pi/4 DQPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	846.69	PASS
Middle	997.6	846.69	PASS
Highest	1002	846.69	PASS

8DPSK mode			
Test channel	Carrier Frequencies Separation (kHz)	Limit (kHz)	Result
Lowest	1002	817.31	PASS
Middle	1002	817.31	PASS
Highest	1002	817.31	PASS


Note: According to section 6.4

Mode	20dB bandwidth (kHz) (worse case)	Limit (kHz) (Carrier Frequencies Separation)
GFSK	745.19	611.65
$\pi/4$ -DQPSK	1137.82	846.69
8DPSK	1141.83	817.31

Test plots as follows:


GFSK Modulation

Lowest channel




Date: 14.MAR.2015 16:57:39

Middle channel



Date: 14.MAR.2015 16:59:10


Highest channel



Date: 14.MAR.2015 17:00:18


Pi/4DQPSK Modulation

Lowest channel




Date: 14.MAR.2015 17:06:39

Middle channel



Date: 14.MAR.2015 17:08:01


Highest channel



Date: 14.MAR.2015 17:09:38


8DPSK Modulation

Lowest channel




Date: 14.MAR.2015 17:13:52

Middle channel



Date: 14.MAR.2015 17:12:50

Highest channel



Date: 14.MAR.2015 17:10:54

6.6. Hopping Channel Number

6.6.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Hopping mode
Test Procedure:	1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW $\geq 1\%$ of the span; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold. 6. The number of hopping frequency used is defined as the number of total channel. 7. Record the measurement data derived from spectrum analyzer.
Test Result:	PASS

6.6.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ROHDE&SCH WARZ	FSU3	1166.1660.03	Sep.17, 2015


Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.6.3. Test data

Mode	Hopping channel numbers	Limit	Result
8DPSK,GFSK, P/4-DQPSK	79	15	PASS


Test plots as follows:

GFSK




Date: 16.MAR.2015 08:41:44

Pi/4DQPSK



Date: 16.MAR.2015 08:34:42

8DPSK



Date: 14.MAR.2015 17:24:13

6.7. Dwell Time

6.7.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Hopping mode
Test Procedure:	1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines. 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Enable the EUT hopping function. 5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW ≥ RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold. 6. Measure and record the results in the test report.
Test Result:	PASS

6.7.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ROHDE&SCH WARZ	FSU3	1166.1660.03	Sep.17, 2015

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.7.3. Test Data

Mode	Packet	Hops Over Occupancy Time (hops)	Package Transfer Time (ms)	Dwell time (second)	Limit (second)	Result
GFSK	DH5	106.67	2.94	0.31	0.4	PASS
$\pi/4$ -DQPSK	2-DH5	106.67	2.93	0.31	0.4	PASS
8DPSK	3-DH5	106.67	2.92	0.31	0.4	PASS


Note: 1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels.

With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops

2. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time


Test plots as follows:

GFSK




Date: 16.MAR.2015 08:44:47

Pi/4DQPSK



Date: 16.MAR.2015 08:47:16

8DPSK



Date: 16.MAR.2015 08:51:32

6.8. Pseudorandom Frequency Hopping Sequence

Test Requirement:

FCC Part15 C Section 15.247 (a)(1) requirement:


Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.

Alternatively. Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a Pseudorandom ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

EUT Pseudorandom Frequency Hopping Sequence


The pseudorandom sequence may be generated in a nine-stage shift register whose 5th and 9th stage outputs are added in a modulo-two addition stage. And the result is fed back to the input of the first stage. The sequence begins with the first one of 9 consecutive ones; i.e. the shift register is initialized with nine ones.

- Number of shift register stages: 9
- Length of pseudo-random sequence: $2^9 - 1 = 511$ bits
- Longest sequence of zeros: 8 (non-inverted signal)



Linear Feedback Shift Register for Generation of the PRBS sequence

An example of Pseudorandom Frequency Hopping Sequence as follow:



Each frequency used equally on the average by each transmitter.
The system receivers have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6.9. Conducted Band Edge Measurement

6.9.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Non-hopping mode and hopping mode
Test Procedure:	1. The testing follows the guidelines in Band-edge Compliance of RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines. 2. Set to the maximum power setting and enable the EUT transmit continuously. 3. Set RBW = 100 kHz ($\geq 1\%$ span=10MHz), VBW = 300 kHz ($\geq$RBW). Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used. 4. Enable hopping function of the EUT and then repeat step 2 and 3. 5. Measure and record the results in the test report.
Test Result:	PASS





6.9.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	ROHDE&SCH WARZ	FSU3	1166.1660.03	Sep.17, 2015





Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.9.3. Test Data





GFSK Modulation

Test channel:	Lowest channel
 Date: 16.MAR.2015 09:12:45	 Date: 16.MAR.2015 09:16:57
No-hopping mode	Hopping mode
Test channel:	Highest channel
 Date: 16.MAR.2015 09:14:20	 Date: 16.MAR.2015 09:16:06
No-hopping mode	Hopping mode

Pi/4DQPSK Modulation

Test channel:	Lowest channel
 Ref 15 dBm *Att 20 dB *RBW 300 kHz *VBW 100 kHz SWT 5 ms Marker 2 [T1] -56.79 dBm 2.400000000 GHz Offset 0.5 dB Marker 1 [T1] -74.11 dBm 2.401954731 GHz D1 -24.11 dBm Center 2.3565 GHz 9.3 MHz/ Span 93 MHz Date: 16.MAR.2015 09:02:58	 Ref 15 dBm *Att 20 dB *RBW 300 kHz *VBW 100 kHz SWT 5 ms Marker 2 [T1] -63.11 dBm 2.400000000 GHz Offset 0.5 dB Marker 1 [T1] -74.11 dBm 2.402254800 GHz D1 -25.93 dBm Center 2.3565 GHz 9.3 MHz/ Span 93 MHz Date: 16.MAR.2015 09:04:41
No-hopping mode	Hopping mode
Test channel:	Highest channel
 Ref 15 dBm *Att 20 dB *RBW 100 kHz *VBW 300 kHz SWT 10 ms Marker 2 [T1] -61.02 dBm 2.483500000 GHz Offset 0.5 dB Marker 1 [T1] -74.11 dBm 2.479843460 GHz D1 -25.14 dBm Start 2.479 GHz 2.1 MHz/ Stop 2.5 GHz Date: 16.MAR.2015 09:10:13	 Ref 15 dBm *Att 20 dB *RBW 300 kHz *VBW 100 kHz SWT 2.5 ms Marker 2 [T1] -65.54 dBm 2.483500000 GHz Offset 0.5 dB Marker 1 [T1] -74.11 dBm 2.479100962 GHz D1 -25.29 dBm Start 2.479 GHz 2.1 MHz/ Stop 2.5 GHz Date: 16.MAR.2015 09:07:10
No-hopping mode	Hopping mode

8DPSK Modulation

Test channel:	Lowest channel
 Ref 15 dBm Offset 0.5 dB Att 20 dB RBW 300 kHz Marker 1 [T1] -3.86 dBm 2.481956731 GHz VBW 100 kHz SWT 5 ms Start 2.31 GHz 9.3 MHz/ Stop 2.483 GHz Date: 16.MAR.2015 08:59:39	 Ref 15 dBm Offset 0.5 dB Att 20 dB RBW 300 kHz Marker 2 [T1] -3.98 dBm 2.483000000 GHz VBW 100 kHz SWT 5 ms Start 2.31 GHz 9.3 MHz/ Stop 2.483 GHz Date: 16.MAR.2015 09:00:58
No-hopping mode	Hopping mode
Test channel:	Highest channel
 Ref 15 dBm Offset 0.5 dB Att 20 dB RBW 300 kHz Marker 2 [T1] -3.71 dBm 2.479887692 GHz VBW 100 kHz SWT 2.5 ms Start 2.479 GHz 2.1 MHz/ Stop 2.5 GHz Date: 16.MAR.2015 08:57:55	 Ref 15 dBm Offset 0.5 dB Att 20 dB RBW 300 kHz Marker 2 [T1] -6.77 dBm 2.480116577 GHz VBW 100 kHz SWT 2.5 ms Start 2.479 GHz 2.1 MHz/ Stop 2.5 GHz Date: 16.MAR.2015 08:55:39
No-hopping mode	Hopping mode

6.10. Conducted Spurious Emission Measurement

6.10.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.4:2009 and DA00-705
Limit:	In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.
Test Setup:	 Spectrum Analyzer EUT
Test Mode:	Non-hopping mode
Test Procedure:	1. The testing follows the guidelines in Spurious RF Conducted Emissions of FCC Public Notice DA 00-705 Measurement Guidelines 2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement. 3. Set to the maximum power setting and enable the EUT transmit continuously. 4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. 5. Measure and record the results in the test report. 6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
Test Result:	PASS

6.10.2. Test Instruments


RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Oct. 21, 2015

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.10.3. Test Data

GFSK mode


Lowest Channel



Middle Channel




Highest Channel




Pi/4DQPSK mode


Lowest Channel



Middle Channel




Highest Channel




8DPSK mode


Lowest Channel



Middle Channel






Highest Channel



6.11. Radiated Spurious Emission Measurement

6.11.1. Test Specification

Test Requirement:	FCC Part15 C Section 15.209		
Test Method:	ANSI C63.4: 2009 and ANSI C63.10-2013		
Frequency Range:	9 kHz to 25 GHz		
Measurement Distance:	3 m		
Antenna Polarization:	Horizontal & Vertical		
Limit:	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
	0.009-0.490	2400/F(KHz)	300
	0.490-1.705	24000/F(KHz)	30
	1.705-30	30	30
	30-88	100	3
	88-216	150	3
	216-960	200	3
	Above 960	500	3
	Frequency	Field Strength (microvolts/meter)	Measurement Distance (meters)
	Above 1GHz	500	3
		5000	3
			Average
			Peak
Test setup:	For radiated emissions below 30MHz		
			
	30MHz to 1GHz		
			
	Above 1GHz		

	 The diagram illustrates the test setup. An Equipment Under Test (EUT) is placed on a turntable at a height of 1.5m. The turntable is 3m away from a horn antenna mounted on an antenna tower. A ground reference plane is indicated. The test receiver, pre-amplifier, and controller are connected to the antenna tower.
Test Mode:	Non-hopping mode
Test Procedure:	1. The testing follows the guidelines in Spurious Radiated Emissions of FCC Public Notice DA 00-705 Measurement Guidelines. 2. The EUT was placed on a turntable with 0.8m above ground for below 1GHz, 1.5m for above 1GHz 3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower. 4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines. 5. Set to the maximum power setting and enable the EUT transmit continuously. 6. Use the following spectrum analyzer settings: (1) Span shall wide enough to fully capture the emission being measured; (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$, RBW=1MHz for $f > 1 \text{ GHz}$; VBW$\geq$RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak (3) For average measurement: use duty cycle correction factor method per 15.35(c). Duty cycle = On time/100 milliseconds $\text{On time} = N1 \cdot L1 + N2 \cdot L2 + \dots + Nn-1 \cdot Ln-1 + Nn \cdot Ln$ Where N1 is number of type 1 pulses, L1 is length of type 1 pulses, etc. Average Emission Level = Peak Emission Level + $20 \cdot \log(\text{Duty cycle})$ Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
Test results:	PASS

6.11.2. Test Instruments


Radiated Emission Test Site (966)				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
ESPI Test Receiver	ROHDE&SCHW ARZ	ESVD	100008	Sep.16 , 2015
Spectrum Analyzer	ROHDE&SCHW ARZ	FSEM	848597/001	Sep.16 , 2015
Spectrum Analyzer	ROHDE&SCHW ARZ	FSU3	1166.1660.03	Sep.17 , 2015
Spectrum Analyzer	Agilent	N9020A	MY49100060	Oct. 21 , 2015
Pre-amplifier	EM Electronics Corporation CO.,LTD	EM30265	07032613	Sep.16 , 2015
Pre-amplifier	HP	8447D	2727A05017	Sep.16 , 2015
Loop antenna	ZHINAN	ZN30900A	12024	Dec.14 , 2015
Broadband Antenna	Schwarzbeck	VULB9163	340	Sep.16 , 2015
Horn Antenna	Schwarzbeck	BBHA 9120D	631	Sep.16 , 2015
Coax cable	TCT	N/A	N/A	Sep.15 , 2015
Coax cable	TCT	N/A	N/A	Sep.15 , 2015
Coax cable	TCT	N/A	N/A	Sep.15 , 2015
Coax cable	TCT	N/A	N/A	Sep.15 , 2015
EMI Test Software	Shurple Technology	EZ-EMC	N/A	N/A

Note: The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

6.11.3. Test Data


Duty cycle correction factor for average measurement

DH5 on time (One Pulse) Plot on Channel 01



Date: 16.MAR.2015 13:26:49

DH5 on time (Count Pulses) Plot on Channel 01




Date: 16.MAR.2015 13:28:36

Note:

1. Worst case Duty cycle = on time/100 milliseconds = 2.988/ 100 = 0.02988
2. Worst case Duty cycle correction factor = $20 \cdot \log(\text{Duty cycle}) = -30.49\text{dB}$
3. DH5 has the highest duty cycle worst case and is reported.
4. The average levels were calculated from the peak level corrected with duty cycle correction factor (-30.49dB) derived from $20 \log(\text{dwell time}/100\text{ms})$. This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

Below 1GHz

Horizontal:



Site

Polarization: **Horizontal**

Temperature: 23


Limit: FCC Part 15B Class B RE_3 m

Power: AC 120V/60Hz

Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		33.8066	33.75	-13.25	20.50	40.00	-19.50	peak	0	
2	*	48.0392	37.99	-12.12	25.87	40.00	-14.13	peak	0	
3		91.0574	31.24	-12.82	18.42	43.50	-25.08	peak	0	
4		198.6424	26.75	-11.77	14.98	43.50	-28.52	peak	0	
5		484.9067	27.22	-3.46	23.76	46.00	-22.24	peak	0	
6		925.6132	27.30	3.54	30.84	46.00	-15.16	peak	0	

Vertical:



Site

Polarization: **Vertical**

Temperature: 23

Limit: FCC Part 15B Class B RE_3 m

Power: AC 120V/60Hz

Humidity: 50 %

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree	Comment
1		30.6390	44.29	-13.64	30.65	40.00	-9.35	peak	0	
2	*	43.8451	44.13	-12.30	31.83	40.00	-8.17	peak	0	
3		57.2653	33.19	-12.59	20.60	40.00	-19.40	peak	0	
4		91.6994	28.90	-12.72	16.18	43.50	-27.32	peak	0	
5		263.1154	27.28	-9.51	17.77	46.00	-28.23	peak	0	
6		713.6915	27.14	0.31	27.45	46.00	-18.55	peak	0	

Note: 1. The low frequency, which started from 9KHz~30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported
2. Measurements were conducted in all three channels (high, middle, low), and the worst case GFSK Mode (Middle channel) was submitted only.

Above 1GHz

Modulation Type: 8DPSK

Low channel: 2402 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
1303.12	H	48.97	---	-4.20	44.77	---	74	54	-9.23
4804.00	H	50.28	---	-3.94	46.34	---	74	54	-7.66
7206.00	H	44.89	---	0.52	45.41	---	74	54	-8.59
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
1304.09	V	48.11	---	-4.25	43.86	---	74	54	-10.14
4804.00	V	50.92	---	-3.94	46.98	---	74	54	-7.02
7206.00	V	44.54	---	0.59	45.13	---	74	54	-8.87
---	V	---	---	---	---	---	---	---	---
---	V	---	---	---	---	---	---	---	---

Middle channel: 2441 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
1241.87	H	49.26	---	-4.20	45.06	---	74	54	-8.94
4882.00	H	51.60	---	-3.98	47.62	---	74	54	-6.38
7323.00	H	46.19	---	0.56	46.75	---	74	54	-7.25
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
1306.45	V	48.64	---	-4.25	44.39	---	74	54	-9.61
4882.00	V	51.02	---	-3.98	47.04	---	74	54	-6.96
7323.00	V	45.40	---	0.57	45.97	---	74	54	-8.03
---	V	---	---	---	---	---	---	---	---
---	---	---	---	---	---	---	---	---	---

High channel: 2480 MHz

Frequency (MHz)	Ant. Pol. H/V	Peak reading (dBμV)	AV reading (dBμV)	Correction Factor (dB/m)	Emission Level		Peak limit (dBμV/m)	AV limit (dBμV/m)	Margin (dB)
					Peak (dBμV/m)	AV (dBμV/m)			
1303.34	H	48.05	---	-4.20	43.85	---	74	54	-10.15
4960.00	H	49.60	---	-3.98	45.62	---	74	54	-8.38
7440.00	H	44.49	---	0.52	45.01	---	74	54	-8.99
---	H	---	---	---	---	---	---	---	---
---	H	---	---	---	---	---	---	---	---
1309.82	V	48.57	---	-4.25	44.32	---	74	54	-9.68
4960.00	V	50.13	---	-3.98	46.15	---	74	54	-7.85
7440.00	V	45.21	---	0.57	45.78	---	74	54	-8.22
---	V	---	---	---	---	---	---	---	---
---	V	---	---	---	---	---	---	---	---

Note:


1. Emission Level=Peak Reading + Correction Factor; Correction Factor= Antenna Factor + Cable loss – Pre-amplifier
2. Margin (dB) = Emission Level (Peak) (dBμV/m)-Average limit (dBμV/m)
3. The emission levels of other frequencies are very lower than the limit and not show in test report.
4. Measurements were conducted from 1 GHz to the 10th harmonic of highest fundamental frequency.
5. Data of measurement shown "—" in the above table mean that the reading of emissions is attenuated more than 20 dB below the limits or the field strength is too small to be measured.


7. Photographs of Test Configuration

Conducted Emission



Radiated Emission





8. Photographs of EUT

Please refer to report TCT150225E026

*******END OF REPORT*******