Certificate #6613.01

FCC TEST REPORT

(Part 15, Subpart C)

Applicant:	Cohda Wireless Pty Ltd.
Address:	27 Greenhill Road Wayville SA 5034 Australia

Manufacturer or Supplier:	Cohda Wireless Pty Ltd.
Address:	27 Greenhill Road Wayville SA 5034 Australia
Product:	Road-Side (Transceiver) Unit for infrastructure.
Brand Name:	Cohda Wireless
Model Name:	MK6 RSU
Series Model	MK6 RSU
FCC ID:	2AEGPMK6RSU
Date of tests:	Jun. 26, 2023 ~ Nov. 27, 2023

The tests have been carried out according to the requirements of the following standard:

☒ **FCC Part 15, Subpart C, Section 15.247**

☒ **ANSI C63.10-2013**

CONCLUSION: The submitted sample was found to <u>COMPLY</u> with the test requirement

Prepared by Chao Wu Engineer / Mobile Department	Approved by Peibo Sun Manager / Mobile Department
Chao Wu Date: Nov. 27, 2023	Sun Peibo Date: Nov. 27, 2023

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/ and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD 4
1 SUMMARY OF TEST RESULTS 5
1.1 MEASUREMENT UNCERTAINTY 6
2 GENERAL INFORMATION 7
2.1 GENERAL DESCRIPTION OF EUT 7
2.2 DESCRIPTION OF TEST MODES 9
2.2.1 CONFIGURATION OF SYSTEM UNDER TEST 10
2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL 10
2.3 DUTY CYCLE OF TEST SIGNAL 14
2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS 15
2.5 DESCRIPTION OF SUPPORT UNITS 15
3 TEST TYPES AND RESULTS 16
3.1 CONDUCTED EMISSION MEASUREMENT 16
3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 16
3.1.2 TEST INSTRUMENTS 16
3.1.3 TEST PROCEDURES 17
3.1.4 DEVIATION FROM TEST STANDARD 17
3.1.5 TEST SETUP 18
3.1.6 EUT OPERATING CONDITIONS 18
3.1.7 TEST RESULTS 19
3.2 RADIATED EMISSION MEASUREMENT 21
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT 21
3.2.2 TEST INSTRUMENTS 22
3.2.3 TEST PROCEDURES 23
3.2.4 DEVIATION FROM TEST STANDARD 23
3.2.5 TEST SETUP 24
3.2.6 EUT OPERATING CONDITIONS 25
3.2.7 TEST RESULTS 26
3.3 6 DB BANDWIDTH MEASUREMENT 80
3.3.1 LIMITS OF 6DB BANDWIDTH MEASUREMENT 80
3.3.2 TEST INSTRUMENTS 80
3.3.3 TEST PROCEDURE 81
3.3.4 DEVIATION FROM TEST STANDARD 82
3.3.5 TEST SETUP 82
3.3.6 EUT OPERATING CONDITIONS 82

3.3.7 TEST RESULTS 83
3.4 CONDUCTED OUTPUT POWER 84
3.4.1 LIMITS OF CONDUCTED OUTPUT POWER MEASUREMENT 84
3.4.2 TEST SETUP 84
3.4.3 TEST INSTRUMENTS 84
3.4.4 TEST PROCEDURES 84
3.4.5 DEVIATION FROM TEST STANDARD 84
3.4.6 EUT OPERATING CONDITIONS 84
3.4.7 TEST RESULTS 85
3.4.7.1 MAXIMUM PEAK OUTPUT POWER 85
3.4.7.2 AVERAGE OUTPUT POWER (FOR REFERENCE) 86
3.5 POWER SPECTRAL DENSITY MEASUREMENT 87
3.5.1 LIMITS OF POWER SPECTRAL DENSITY MEASUREMENT 87
3.5.2 TEST SETUP 87
3.5.3 TEST INSTRUMENTS 87
3.5.4 TEST PROCEDURE 87
3.5.5 DEVIATION FROM TEST STANDARD 87
3.5.6 EUT OPERATING CONDITION 87
3.5.7 TEST RESULTS 88
3.6 OUT OF BAND EMISSION MEASUREMENT 89
3.6.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 89
3.6.2 TEST SETUP 89
3.6.3 TEST INSTRUMENTS 89
3.6.4 TEST PROCEDURE 89
3.6.5 DEVIATION FROM TEST STANDARD 90
3.6.6 EUT OPERATING CONDITION 90
3.6.7 TEST RESULTS 90
4 PHOTOGRAPHS OF THE TEST CONFIGURATION 91
5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB92

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
PSU-QSU2306260109RF09	Original release	Nov. 27, 2023

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC PART 15, SUBPART C (SECTION 15.247)			
STANDARD SECTION	**TEST TYPE AND LIMIT**	**RESULT**	**Test lab***
15.207	AC Power Conducted Emission	Compliance	A
15.205 15.209	Radiated Emissions	Compliance	A
15.247(d)	Out of band Emission Measurement	See Note 1	--
15.247(a)(2)	6dB bandwidth	See Note 1	--
15.247(b)	Conducted Output power	See Note 2	--
15.247(e)	Power Spectral Density	See Note 1	--
15.203	Antenna Requirement	See Note 1	--

Note：1. Refer to the module report (Report No.: FR740702AC& FR740702AE, Model Name: ST60-SIPT, FCC ID: SQG-60SIPT).

2. This report verifies output power and the verify results are lower than the module report, so the results of output power please Refer to the module report (Report No.: FR740702AC& FR740702AE, Model Name: ST60-SIPT, FCC ID: SQG-60SIPT).

3. WLAN 2.4G supports SISO&MIMO mode，the whole testing have assessed the MIMO mode by referring to their maximum conducted power.

4. For WIFI-2.4G, RSE had been tested on SISO&MIMO mode of EUT. The worst case was found on MIMO mode, only the worst case data had been reported in the report.

5. This DUT can only operate on authorized spectrum in the US. When set up the router for unauthorized bands, failed to connect, the unauthorized bands are not available.

***Test Lab Information Reference**

Lab A:

Huarui 7Layers High Technology (Suzhou) Co., Ltd.

Lab Address:

Tower N, Innovation Center, 88 Zhuyi Road, High-tech District, Suzhou City, Anhui Province

Accredited Test Lab Cert 6613.01

The FCC Site Registration No. is 434559; The Designation No. is CN1325.

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
AC Power Conducted emissions	±2.70dB
Radiated emissions (30MHz~1GMHz)	±4.98dB
Radiated emissions (1GMHz ~6GMHz)	±4.70dB
Radiated emissions (6GMHz ~18GMHz)	±4.60dB
Radiated emissions (18GMHz ~40GMHz)	±4.12dB
Conducted emissions	±4.01dB
Occupied Channel Bandwidth	±43.58KHz
Conducted Output power	±2.06dB
Power Spectral Density	±0.85 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k = 2.

2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT*	Road-Side (Transceiver) Unit for infrastructure.
BRAND NAME*	Cohda Wireless
MODEL NAME*	MK6 RSU
SERIES MODEL*	MK6 RSU
NOMINAL VOLTAGE*	48Vdc(POE Adapter)
MODULATION *	DSSS, OFDM, GFSK
TRANSMISSION RATE*	802.11b: 11/ 5.5/ 2.0 / 1.0 Mbps 802.11g: 54/ 48/ 36 / 24 / 18 / 9/ 6 Mbps 802.11n20: up to 72.2 Mbps 802.11n40: up to 150 Mbps BT_LE: 1 Mbps
OPERATING FREQUENCY*	2412-2462MHz for 11b/g/n(HT20/40) 2402-2480MHz for BT-LE(GFSK)
MAX. OUTPUT POWER	WLAN: 872.157mW (Maximum) BT-LE: 12.02mW (Maximum)
ANTENNA TYPE*	ANT 1: Monopole Antenna with 2dBi gain for WIFI& BT-LE ANT2: Monopole Antenna with 2dBi gain for WIFI
HW VERSION*	Rev 1.0
SW VERSION*	19.Release.134186
I/O PORTS*	Refer to user's manual
CABLE SUPPLIED*	N/A

NOTE:

1. ***Since the above data and/or information is provided by the client relevant results or conclusions of this report are only made for these data and/or information , Test Lab is not responsible for the authenticity, integrity and results of the data and information and/or the validity of the conclusion.

2. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

3. The EUT incorporates a MIMO function. Physically, the EUT provides two transmitters and two receivers.

MODULATION MODE	TX/RX FUNCTION
802.11b	2TX /2RX
802.11g	2TX /2RX
802.11n (20MHz)	2TX /2RX
802.11n (40MHz)	2TX /2RX
BT_LE(1MHz)	1TX /1RX

List of Accessory:

ACCESSORIES	MANUFACTURER	MODEL
2x Antenna for LTE/2G/3G/CDMA	Taoglas	TG.80.4H31
2x Antenna for WLAN/BT	HUBER+SUHNER	1399.17.0224
2x Antenna for DSRC	Taoglas	TD.80.6H31
1x Antenna for GNSS	Taoglas	TLS.40.1F11
1xM12 field attachable connector	Amphenol	MSXS-08BMMD-SL8001

2.2 DESCRIPTION OF TEST MODES

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
1	2412 MHz	7	2442 MHz
2	2417 MHz	8	2447 MHz
3	2422 MHz	9	2452 MHz
4	2427 MHz	10	2457 MHz
5	2432 MHz	11	2462 MHz
6	2437 MHz		

7 channels are provided for 802.11n (HT40):

CHANNEL	FREQUENCY	CHANNEL	FREQUENCY
3	2422 MHz	7	2442 MHz
4	2427 MHz	8	2447 MHz
5	2432 MHz	9	2452 MHz
6	2437 MHz		

40 channels are provided for BT-LE (GFSK):

CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)	CHANNEL	FREQ. (MHZ)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

2.2.1 CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photographs of the test configuration for reference.

2.2.2 TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports.
The worst case was found when positioned on Y axis for radiated emission. Following test modes were selected for the final test, and the final worst case is marked in boldface and recorded in the report:

EUT CONFIGURE MODE	APPLICABLE TO				MODE
	RE<1G	RE≥1G	PLC	APCM	
-	√	√	√	√	-

Where **RE<1G:** Radiated Emission below 1GHz **RE≥1G:** Radiated Emission above 1GHz
PLC: Power Line Conducted Emission **APCM:** Antenna Port Conducted Measurement

NOTE: No need to concern of Conducted Emission due to the EUT is powered by battery.

RADIATED EMISSION TEST (BELOW 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n HT40	1 to 11	6	OFDM	MCS0
BT-LE	0 to 39	19	GFSK	1.0

RADIATED EMISSION TEST (ABOVE 1GHz):

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1

POWER LINE CONDUCTED EMISSION TEST

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11n HT20	1 to 11	11	OFDM	MCS0

BANDEDGE MEASUREMENT:

☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).

☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1

ANTENNA PORT CONDUCTED MEASUREMENT:

☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
☒ Following channel(s) was (were) selected for the final test as listed below.

MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)
802.11b	1 to 11	1, 6, 11	DSSS	1.0
802.11g	1 to 11	1, 6, 11	OFDM	6.0
802.11n HT20	1 to 11	1, 6, 11	OFDM	MCS0
802.11n HT40	3 to 9	3,6,9	OFDM	MCS0
BT-LE	0 to 39	0,19, 39	GFSK	1

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE	TESTED BY
RE<1G	23deg. C, 70%RH	DC 48V By POE Adapter	Chao Wu
RE≥1G	23deg. C, 70%RH	DC 48V By POE Adapter	Chao Wu
PLC	25deg. C, 52%RH	DC 48V By POE Adapter	Chao Wu
APCM	25deg. C, 60%RH	DC 48V By POE Adapter	Chao Wu

2.3 Duty Cycle of Test Signal

Please Refer to the module report (Report No.: FR740702AC& FR740702AE, Model Name: ST60-SIPT, FCC ID: SQG-60SIPT).

2.4 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

KDB 558074 D01 DTS Meas Guidance v05r02

ANSI C63.10-2013

Note：

1. All test items have been performed and recorded as per the above standards.
2. The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (Certification). The test report has been issued separately.

2.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	Laptop	Lenovo	ThinkPad E14	HRSW00024	N/A
2	POE Adapter	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

3 TEST TYPES AND RESULTS

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBμV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

NOTE: 1.The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

3.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR3	102749	Feb.25,22	Feb.24,24
ELEKTRA test software	Rohde&Schwarz	ELEKTRA	NA	N/A	N/A
LISN network	Rohde&Schwarz	ENV216	102640	Feb.17,22	Feb.16,24
CABLE	Rohde&Schwarz	W61.01	N/A	Apr.28,23	Oct.27,23
CABLE	Rohde&Schwarz	W61.01	N/A	Oct.27,23	Apr.26,24
CABLE	Rohde&Schwarz	W601	N/A	Apr.28,23	Oct.27,23
CABLE	Rohde&Schwarz	W601	N/A	Oct.27,23	Apr.26,24

NOTE:

1. The test was performed in CE shielded room.
2. The calibration interval of the above test instruments is 6 months or 24 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

3.1.3 TEST PROCEDURES

a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.

b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.

c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: All modes of operation were investigated and the worst-case emissions are reported.

3.1.4 DEVIATION FROM TEST STANDARD

No deviation.

3.1.5 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.1.6 EUT OPERATING CONDITIONS

a. Turned on the power and connected of all equipment.

b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.

3.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA:

Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	DC 48V	**Environmental Conditions**	25deg. C, 55%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dBµV]	QPK Limit [dBµV]	QPK Margin [dB]	CAV Level [dBµV]	CAV: AVG Limit [dBµV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.150	50.74	66.00	15.26	34.74	56.00	21.26	12.57	L1	9.000
1	0.389	36.57	58.10	21.53	32.80	48.10	15.30	11.77	L1	9.000
1	1.019	23.06	56.00	32.94	14.48	46.00	31.52	11.75	L1	9.000
1	2.355	28.70	56.00	27.30	22.34	46.00	23.66	11.77	L1	9.000
1	7.022	35.46	60.00	24.54	29.06	50.00	20.94	11.81	L1	9.000
1	26.012	28.42	60.00	31.58	22.51	50.00	27.49	11.90	L1	9.000

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.



Frequency Range	150KHz ~ 30MHz	**Detector Function & Resolution Bandwidth**	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	DC 48V	**Environmental Conditions**	25deg. C, 55%RH
Tested By	Chao Wu		

Rg	Frequency [MHz]	QPK Level [dBμV]	QPK Limit [dBμV]	QPK Margin [dB]	CAV Level [dBμV]	CAV: AVG Limit [dBμV]	CAV Margin [dB]	Correction [dB]	Line	Meas. BW [kHz]
1	0.155	50.19	65.75	15.56	34.00	55.75	21.75	12.14	N	9.000
1	0.393	36.21	58.00	21.79	31.57	48.00	16.43	12.82	N	9.000
1	1.082	24.18	56.00	31.82	15.90	46.00	30.10	12.74	N	9.000
1	2.279	31.57	56.00	24.43	26.38	46.00	19.62	12.74	N	9.000
1	6.491	37.04	60.00	22.96	30.34	50.00	19.66	12.78	N	9.000
1	26.534	28.48	60.00	31.52	22.50	50.00	27.50	12.88	N	9.000

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Limit value -Emission level
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

3.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Pre-Amplifier	R&S	SCU18F1	100815	Aug.30,22	Aug.29,24
Pre-Amplifier	R&S	SCU08F1	101028	Sep.16,22	Sep.15,24
Signal Generator	R&S	SMB100A	182185	Feb.16,22	Feb.15,24
3m Fully-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-01Chamber	Nov.25,22	Nov.24,25
3m Semi-anechoic Chamber	TDK	9m*6m*6m	HRSW-SZ-EMC-02Chamber	Nov.25,22	Nov.24,25
EMI TEST Receiver	R&S	ESW44	101973	Feb.25,22	Feb.24,24
Bilog Antenna	SCHWARZBECK	VULB 9163	1264	Feb.28,22	Feb.27,24
Horn Antenna	ETS-LINDGREN	3117	227836	Aug.22,22	Aug.21,24
Horn Antenna (18GHz-40GHz)	Steatite Q-par Antennas	QMS 00880	23486	Feb.23,22	Feb.22,24
Horn Antenna	Steatite Q-par Antennas	QMS 00208	23485	Aug.22,22	Aug.21,24
Loop Antenna	SCHWARZ	HFH2-Z2/Z2E	100976	Feb.23,22	Feb.22,24
WIDEBANDRADIO COMMUNICATION TESTER	R&S	CMW500	169399	Jun.27,22	Jun.26,24
Test Software	ELEKTRA	ELEKTRA4.32	N/A	N/A	N/A
Open Switch and Control Unit	R&S	OSP220	101964	N/A	N/A
DC Source	HYELEC	HY3010B	551016	Aug.31,22	Aug.30,24
Hygrothermograph	DELI	20210528	SZ014	Sep.06,22	Sep.05,24
PC	LENOVO	E14	HRSW0024	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-7.00M	N/A	N/A	N/A
TMC-AMI18843A(CABLE)	R&S	HF290-NMNM-4.00M	N/A	N/A	N/A
CABLE	R&S	W13.02	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W13.02	N/A	Oct.27,23	Apr.26,24
CABLE	R&S	W12.14	N/A	Apr.28,23	Oct.27,23
CABLE	R&S	W12.14	N/A	Oct.27,23	Apr.26,24

NOTE: 1. The calibration interval of the above test instruments is 6 months or 24 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.

2. The test was performed in 3m Chamber.

3. The FCC Site Registration No. is 525120; The Designation No. is CN1171.

3.2.3 TEST PROCEDURES

a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor (10 log(1/duty cycle)).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle ≥ 98%) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

3.2.4 DEVIATION FROM TEST STANDARD

No deviation

3.2.5 TEST SETUP

<Frequency Range 9KHz~30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.6 EUT OPERATING CONDITIONS

a. Set the EUT under full load condition and placed them on a testing table.

b. Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.

c. The necessary accessories enable the EUT in full functions.

3.2.7 TEST RESULTS

NOTE ：The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA:

30 MHz – 1GHz data:

802.11n (40MHz)-MIMO

CHANNEL	TX Channel 6	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	40.622	28.35	40.00	11.65	-8.21	H	232.6	2	120.000
1	66.278	38.31	40.00	1.69	-10.17	H	232.6	2	120.000
1	101.877	35.08	43.50	8.42	-9.21	H	355.4	2	120.000
1	168.468	22.03	43.50	21.47	-11.20	H	168	1	120.000
1	267.311	31.96	46.00	14.04	-6.70	H	5.1	1	120.000
1	822.199	33.95	46.00	12.05	1.38	H	359	2	120.000

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.



CHANNEL	TX Channel 6	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	QPK Level [dBμV/m]	QPK Limit [dBμV/m]	QPK Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]	Meas. BW [kHz]
1	45.957	28.53	40.00	11.47	-7.48	V	355.5	2	120.000
1	98.434	33.39	43.50	10.11	-9.55	V	231.4	2	120.000
1	206.637	21.69	43.50	21.81	-8.66	V	102.2	2	120.000
1	307.663	30.14	46.00	15.86	-5.42	V	355.5	2	120.000
1	574.995	25.44	46.00	20.56	-2.52	V	1	2	120.000
1	812.548	29.46	46.00	16.54	1.20	V	359	2	120.000

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Emission level – Limit value.



ABOVE 1GHz WORST-CASE DATA:

Note: 1. For radiated emissions testing，the full testing range of different modes have been scanned，only the worst case harmonic data is reported in the sheet.

2. All other emissions were greater than 20dB below the limit was not recorded

802.11b-MIMO:

CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,387.500	51.86	74.00	22.14	6.84	H	133.2	1
1	2,390.000	48.98	74.00	25.02	6.84	H	178.7	1
1	2,413.500	103.92			6.95	H	178.7	1



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,387.000	38.47	54.00	15.53	6.84	H	5	1
1	2,390.000	34.26	54.00	19.74	6.84	H	359.1	1
1	2,413.000	91.92			6.94	H	359.1	1

CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,386.500	50.17	74.00	23.83	6.84	V	262.6	2
1	2,390.000	48.16	74.00	25.84	6.84	V	359	2
1	2,413.500	99.86			6.95	V	262.6	2



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,385.500	32.43	54.00	21.57	6.84	V	359	1
1	2,390.000	32.57	54.00	21.43	6.84	V	359	1
1	2,411.500	85.17			6.93	V	359	1

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

CHANNEL	TX Channel 6	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.10	74.00	23.90	38.58	54.00	15.42	14.98	H	359.1	1
4	6,301.500	53.65	74.00	20.35	40.27	54.00	13.73	17.94	H	336.5	1



CHANNEL	TX Channel 6	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,873.500	50.18	74.00	23.82	38.78	54.00	15.22	14.97	V	1	2
4	7,267.000	54.26	74.00	19.74	40.33	54.00	13.67	18.06	V	1	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

CHANNEL	TX Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,460.500	107.19			7.03	H	216	2
2	2,483.500	50.96	74.00	23.04	6.99	H	305.4	1
2	2,486.000	52.98	74.00	21.02	7.00	H	305.4	1

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,461.000	99.67			7.03	H	336.4	1
2	2,483.500	39.83	54.00	14.17	6.99	H	355.6	2
2	2,486.500	43.94	54.00	10.06	7.00	H	355.6	2



CHANNEL	TX Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,463.500	107.23			7.01	V	1.9	2
2	2,483.500	53.19	74.00	20.81	6.99	V	17.1	2
2	2,486.000	55.67	74.00	18.33	7.00	V	17.1	2

Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,462.500	102.61			7.02	V	0.9	2
2	2,483.500	41.19	54.00	12.81	6.99	V	1.1	2
2	2,486.500	46.46	54.00	7.54	7.00	V	14.2	2

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

802.11g-MIMO

CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,384.000	59.55	74.00	14.45	6.84	H	166.6	1
1	2,390.000	63.53	74.00	10.47	6.84	H	166.6	1
1	2,415.000	103.22			6.96	H	166.6	1



Rg	Frequency [MHz]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,384.500	36.54	54.00	17.46	6.84	H	255.4	2
1	2,390.000	38.83	54.00	15.17	6.84	H	255.4	2
1	2,407.000	88.63			6.90	H	255.4	2



CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,384.000	58.47	74.00	15.53	6.84	V	1	2
1	2,390.000	62.36	74.00	11.64	6.84	V	1	2
1	2,415.500	104.28			6.96	V	1	2



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,385.500	39.51	54.00	14.49	6.84	V	21.5	2
1	2,390.000	42.26	54.00	11.74	6.84	V	0.9	2
1	2,415.000	93.45			6.96	V	0.9	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

CHANNEL	TX Channel 6	**DETECTOR FUNCTION**	Quasi-Peak (QP)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	AVG Level [dBµV/m]	AVG Limit [dBµV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	49.03	74.00	24.97	38.49	54.00	15.51	14.98	H	134.5	2
3	5,778.000	54.51	74.00	19.49	40.54	54.00	13.46	16.74	H	359	2



CHANNEL	TX Channel 6	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
3	4,874.000	50.14	74.00	23.86	38.48	54.00	15.52	14.98	V	1	1
4	7,347.500	53.72	74.00	20.28	40.11	54.00	13.89	17.95	V	359	2



REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

CHANNEL	TX Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBμV/m]	PK+ Limit [dBμV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,465.500	104.28			7.00	H	225.5	2
2	2,483.500	60.05	74.00	13.95	6.99	H	318.7	2
2	2,485.000	57.75	74.00	16.25	7.00	H	225.5	2



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,465.000	90.82			7.00	H	184.9	2
2	2,483.500	43.00	54.00	11.00	6.99	H	244.6	2
2	2,485.000	39.26	54.00	14.74	7.00	H	355	2

CHANNEL	TX Channel 11	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,465.000	103.71			7.00	V	1	2
2	2,483.500	60.74	74.00	13.26	6.99	V	355.6	2
2	2,484.000	60.88	74.00	13.12	6.99	V	355.6	2



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,465.000	93.38			7.00	V	1	2
2	2,483.500	41.33	54.00	12.67	6.99	V	355	2
2	2,485.000	41.39	54.00	12.61	7.00	V	12.9	2

REMARKS:

1. Emission Level = Read Level+ Antenna Factor + Cable Loss- Preamp Factor
   Margin value = Limit value – Emission level..
2. 2412MHz: Fundamental frequency.

802.11n (20MHz)-MIMO

CHANNEL	TX Channel 1	**DETECTOR FUNCTION**	Peak (PK) Average (AV)
FREQUENCY RANGE	1GHz ~ 25GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

Rg	Frequency [MHz]	PK+ Level [dBµV/m]	PK+ Limit [dBµV/m]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.500	53.15	74.00	20.85	6.84	H	224.4	2
1	2,390.000	52.15	74.00	21.85	6.84	H	224.4	2
1	2,420.500	97.87			7.00	H	276.7	1



Rg	Frequency [MHz]	AVG Level [dBμV/m]	AVG Limit [dBμV/m]	AVG Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
1	2,388.000	36.86	54.00	17.14	6.84	H	107	1
1	2,390.000	36.23	54.00	17.77	6.84	H	107	1
1	2,420.500	89.43			7.00	H	218.2	1