

WaveLynx Technologies Corporation RF Exposure Exhibit

SCOPE OF WORK

EMC TESTING – Door Lock, Model(s): Mortise Sectional, Mortise Escutcheon, Exit Trim, Cylindrical

REPORT NUMBER

104902494MPK-010

ISSUE DATE

October 28, 2022

REVISED DATE

N/A

PAGES

10

DOCUMENT CONTROL NUMBER

Non-Specific Radio Report Shell Rev. December 2017 MPK
© 2017 INTERTEK



RF Exposure Exhibit (Mobile Devices)

Report Number: 104902494MPK-010

Project Number: G104902494

Report Issue Date: October 28, 2022

Testing performed on the
Door Lock

Model(s): Mortise Sectional,
Mortise Escutcheon,
Exit Trim,
Cylindrical

FCC ID: 2AEI3-HB01-HL01

IC: 20063-WLTHB01HL01

to

47CFR 2.1091

RSS-102 Issue 5

for

WaveLynx Technologies Corporation

Tested by:

Intertek
1365 Adams Court
Menlo Park, CA 94025 USA

Client:

WaveLynx Technologies Corporation
100 Technology Drive, Suite 130B
Broomfield, CO 80021 USA

Report prepared by:



Kenneth Roque / EMC Project Engineer

Report reviewed by:



Anderson Sounpganya / EMC Team Leader

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. This report must not be used to claim product endorsement by A2LA, NIST nor any other agency of the U.S. Government.

Report No. 104902494MPK-010	
Equipment Under Test:	Door Lock
Model Number:	Mortise Sectional, Mortise Escutcheon, Exit Trim, Cylindrical
Applicant:	WaveLynx Technologies Corporation
Contact:	Daniel Field
Address:	100 Technology Drive, Suite 130B Broomfield, CO 80021 USA
Country:	USA
Tel. Number:	1 (530) 391-1155
Email:	danielfield@wavelynxtech.com
Applicable Regulation:	47CFR 2.1091 RSS-102 Issue 5

We attest to the accuracy of this report:



Kenneth Roque
EMC Project Engineer



Anderson Sounpganya
EMC Team Leader

TABLE OF CONTENTS

WaveLynx Technologies Corporation.....	1
1.0 RF Exposure Summary	5
2.0 RF Exposure Limits	5
3.0 Test Results (Mobile Configuration).....	7
Appendix A: Power Density Calculation	9
4.0 Document History.....	10

1.0 RF Exposure Summary

Test	Reference FCC	Reference Industry Canada	Result
Radio frequency Radiation Exposure Evaluation	47 CFR§2.1091	RSS-102 Issue 5	Complies

2.0 RF Exposure Limits

In this document, we evaluate the RF Exposure to human body due the intentional transmission from the transmitter (EUT). The limits for Maximum Permissible Exposure (MPE) specified in FCC 1.1310 and RSS-102 are followed.

2.1 FCC Limits

According to FCC 1.1310 table 1: The criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
(A)Limits For Occupational / Control Exposures				
0.3 – 3.0	614	1.63	*100	6
3.0 – 30	1842/f	4.89/f	*900/f ²	6
30-300	61.4	0.163	1.0	6
300 - 1500	...	...	F/300	6
1500 - 100,000	...	...	5	6
(B)Limits For General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*100	30
1.34 – 30	824/f	2.19/f	*180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 - 1500	...	...	F/1500	30
1500 - 100,000	...	...	1.0	30

F = Frequency in MHz

* = plane wave equivalent density

2.2 Industry Canada Limits

According to RSS-102, Industry Canada has adopted the SAR and RF field strength limits established in Health Canada's RF exposure guideline, Safety Code 6.

Table 4: RF Field Strength Limits for Devices Used by the General Public (Uncontrolled Environment)				
Frequency Range	Electric Field	Magnetic Field	Power Density	Reference Period
(MHz)	(V/m rms)	(A/m rms)	(W/m ²)	(minutes)
0.003-10	83	90	-	Instantaneous*
0.1-10	-	0.73/ f	-	6**
1.1-10	87/ f ^{0.5}	-	-	6**
10-20	27.46	0.0728	2	6
20-48	58.07/ f ^{0.25}	0.1540/ f ^{0.25}	8.944/ f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150000	61.4	0.163	10	616000/ f ^{1.2}
150000-300000	0.158 f ^{0.5}	4.21 x 10 ⁻⁴ f ^{0.5}	6.67 x 10 ⁻⁵ f	616000/ f ^{1.2}
Note: f is frequency in MHz. * Based on nerve stimulation (NS). ** Based on specific absorption rate (SAR).				

3.0 Test Results (Mobile Configuration)

3.1 Classification

Radio is installed inside a mobile host device. The antenna of the product, under normal use condition, is at least 20 cm away from the body of the user and accessible to the end user. Warning statement to the user for keeping at least 20 cm or more separation distance with the antenna should be included in user's manual.

3.2 EIRP calculations

The Door Lock, Model(s): Mortise Sectional, Mortise Escutcheon, Exit Trim, and Cylindrical consists of two radios: 13.56 MHz RFID, and 2.4 GHz BLE.

For RF exposure compliance refer to reports below:

Radio	FCC ID	Report Number
13.56 MHz – RFID	2AEI3-HB01-HL01	104902494MPK-001
2.4 GHz - BLE	SQGBL5340	FR112703AE

3.3 Maximum RF Power

Frequency Range (MHz)	Peak FS @ 10m (dBμV/m)	Note
13.56	34.56	FS measurement was taken from Report #104902494MPK-001. The worst case power measurement was used.

Frequency Range (MHz)	RF Output ¹ (dBm)	Antenna Gain ¹ (dBi)	Note ¹
2402 – 2480	3.15	2.0	Conducted power measurements were taken from Report #FR112703AE.

¹As declared by the manufacturer. Intertek takes no responsibility for the accuracy of this information.

3.4 RF Exposure Calculation

3.4.1 RF Exposure calculation for 13.56 MHz – RFID

Frequency Range (MHz)	Peak FS @3m (dBμV/m)	Peak FS @20 cm* (dBμV/m)	Peak FS @20 cm (V/m)	RSS Limit (V/m)	FCC Limit (V/m)	Results
13.56	34.56	102.52	0.14	27.46	60.77	Complies

Note: Peak FS measurement was taken from Report #104902494MPK-001.

* Distance Correction Factor was used.

3.4.2 RF Exposure calculation for 2.4 GHz – BLE

Frequency Range (MHz)	EIRP ¹	EIRP ¹	Power Density (mW/cm ²)	FCC Limit (mW/cm ²)
	(dBm)	(mW)	@20 cm	
2402 – 2480	5.15	3.2734	0.0007	1.0000

Note: Antenna gains below 0 are considered as 0dBi.

Frequency Range (MHz)	EIRP ¹	EIRP ¹	Power Density (W/m ²)	RSS Limit (W/m ²)
	(dBm)	(mW)	@20 cm	
2402 – 2480	5.15	3.2734	0.0065	5.4742

Note: Antenna gains below 0 are considered as 0dBi.

Appendix A: Power Density Calculation

The Power Density can be calculated using the formula

$$S = \text{EIRP} / 4\pi D^2$$

Where: S is Power Density in mW/cm²

D is the distance from the antenna in cm.

4.0 Document History

Revision/ Job Number	Writer Initials	Reviewers Initials	Date	Change
1.0 / G104902494	KR	AS	October 28, 2022	Original Document