FCC RADIO TEST REPORT

FCC ID	:	**2AEM4-NV01**
Equipment	:	**Wireless Router**
Brand Name	:	**eero**
Model Name	:	**NV01**
Applicant	:	**eero LLC** **660 3rd St Fl 4, San Francisco, California, 94107, United States**
Manufacturer	:	**eero LLC** **660 3rd St Fl 4, San Francisco, California, 94107, United States**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Jul. 18, 2025 and testing was performed from Jul. 18, 2025 to Sep. 24, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory
No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1 General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Modification of EUT 5
1.3 Testing Location 5
1.4 Applicable Standards 6
2 Test Configuration of Equipment Under Test **7**
2.1 Carrier Frequency Channel 7
2.2 Test Mode 8
2.3 Connection Diagram of Test System 9
2.4 Support Unit used in test configuration and system 9
2.5 EUT Operation Test Setup 10
2.6 Measurement Results Explanation Example 10
3 Test Result **11**
3.1 6dB and 99% Bandwidth Measurement 11
3.2 Output Power Measurement 12
3.3 Power Spectral Density Measurement 13
3.4 Conducted Band Edges and Spurious Emission Measurement 14
3.5 Radiated Band Edges and Spurious Emission Measurement 15
3.6 AC Conducted Emission Measurement 20
3.7 Antenna Requirements 22
4 List of Measuring Equipment **23**
5 Measurement Uncertainty **25**
Appendix A. Conducted Test Results
Appendix B. AC Conducted Emission Test Result
Appendix C. Radiated Spurious Emission Test Result
Appendix D. Duty Cycle Plots
Appendix E. Setup Photographs

History of this test report

Report No.	Version	Description	Issue Date
FR562407A	01	Initial issue of report	Sep. 17, 2025
FR562407A	02	Revise Summary of Test Result, List of Measuring Equipment and Appendix A This report is an updated version, replacing the report issued on Sep. 17, 2025.	Sep. 25, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”.

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Avis Chuang

Report Producer: Freda Wu

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth-LE, IEEE 802.15.4, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax/be, Wi-Fi 5GHz 802.11a/n/ac/ax/be, Wi-Fi 6GHz 802.11ax/be **Antenna Type** Bluetooth: PIFA Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	5.2

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	CO05-HY (TAF Code: 1190)
Remark	The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	TH05-HY, 03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- FCC KDB 414788 D01 Radiated Test Site v01r01
- FCC Part 15 Subpart C §15.247
- ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
Conducted Test Cases	**Bluetooth – LE / GFSK**
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
AC Conducted Emission	Mode 1: Bluetooth Tx - LE 1M CH19 + LAN Link + AC Adapter (Luxshare_27W_Type A plug) (C210001)
Remark: 1. For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power. 2. The detailed Radiated test modes are shown in Appendix C.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Notebook	DELL	Latitude 3420	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
2.	PC	msi	PRO DP1 80A7	FCC DoC	N/A	Unshielded, 1.8 m
3.	PC	Lenovo	P320	FCC DoC	N/A	Unshielded, 1.8 m

2.5 EUT Operation Test Setup

The RF test items, utility “RadioControlConsole.exe (v4.0.0.0)” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW ≥ 3 * RBW. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
   For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) ≥ 3 * RBW.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as "-".
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as "-".
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW = 100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW = 3 MHz for f ≥ 1 GHz for peak measurement.

   For average measurement:

   The procedure for method trace averaging is as follows:

   a) RBW = 1 MHz.
   b) VBW ≥ [3 × RBW].
   c) Detector = RMS (power averaging), if [span / (# of points in sweep)] ≤ RBW / 2. Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
   d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging.
   e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / *D*, where *D* is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:

i. If power averaging (rms) mode was used in the preceding step e), then the correction factor is [10 log (1 / *D*)], where *D* is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

ii. If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

3.5.4 Test Setup

For radiated test below 30MHz



For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
6. The frequency range from 150 kHz to 30 MHz is scanned.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.

4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01 N-06	37059 & 01	30MHz~1GHz	Nov. 27, 2024	Jul. 18, 2025~ Aug. 08, 2025	Nov. 26, 2025	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 18, 2024	Jul. 18, 2025~ Aug. 08, 2025	Dec. 17, 2025	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-01620	1GHz~18GHz	Aug. 28, 2024	Jul. 18, 2025~ Aug. 08, 2025	Aug. 27, 2025	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	00994	18GHz~40GHz	Jan. 09, 2025	Jul. 18, 2025~ Aug. 08, 2025	Jan. 08, 2025	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Dec. 07, 2024	Jul. 18, 2025~ Aug. 08, 2025	Dec. 06, 2025	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Mar. 24, 2025	Jul. 18, 2025~ Aug. 08, 2025	Mar. 23, 2026	Radiation (03CH11-HY)
Preamplifier	E-INSTRUMENT TECH LTD.	ERA-100M-18G-56-01-A70	EC1900249	1GHz~18GHz	Jan. 21, 2025	Jul. 18, 2025~ Aug. 08, 2025	Jan. 20, 2026	Radiation (03CH11-HY)
Preamplifier	EMEC	EM18G40G	060871	18GHz~40GHz	Aug. 23, 2024	Jul. 18, 2025~ Aug. 08, 2025	Aug. 22 2025	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz~44GHz	Oct. 14, 2024	Jul. 18, 2025~ Aug. 08, 2025	Oct. 13, 2025	Radiation (03CH11-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY53290053	20Hz~26.5GHz	Sep. 09, 2024	Jul. 18, 2025~ Aug. 08, 2025	Sep. 08, 2025	Radiation (03CH11-HY)
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 18, 2025~ Aug. 08, 2025	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Jul. 18, 2025~ Aug. 08, 2025	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Jul. 18, 2025~ Aug. 08, 2025	N/A	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001053	N/A	N/A	Jul. 18, 2025~ Aug. 08, 2025	N/A	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303B	TP200880	N/A	Aug. 29, 2024	Jul. 18, 2025~ Aug. 08, 2025	Aug. 28,2025	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804013/2	30M~40G	Mar. 05, 2025	Jul. 18, 2025~ Aug. 08, 2025	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 05, 2025	Jul. 18, 2025~ Aug. 08, 2025	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	30M~40G	Mar. 05, 2025	Jul. 18, 2025~ Aug. 08, 2025	Mar. 04, 2026	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	805139 2	30M~40G	May 10, 2025	Jul. 18, 2025~ Aug. 08, 2025	May 09, 2026	Radiation (03CH11-HY)
Filter	Wainwright	WHKX12-2700-3000-18000-60SS	SN3	3GHz High Pass Filter	Sep. 10, 2024	Jul. 18, 2025~ Aug. 08, 2025	Sep. 09, 2025	Radiation (03CH11-HY)

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Filter	Wainwright	WHKX8-5872.5-6750-18000-40SS	SN3	6.75GHz High Pass Filter	Sep. 10, 2024	Jul. 18, 2025~ Aug. 08, 2025	Sep. 09, 2025	Radiation (03CH11-HY)
Filter	Wainwright	WLK4-1000-1530-8000-40SS	SN11	1.53GHz Low Pass Filter	Sep. 10, 2024	Jul. 18, 2025~ Aug. 08, 2025	Sep. 09, 2025	Radiation (03CH11-HY)
Attenuator	HONOVA	5910 SMA-50-005	0028	N/A	Sep. 10, 2024	Jul. 18, 2025~ Aug. 08, 2025	Sep. 09, 2025	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Aug. 18, 2025~ Sep. 24, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3008W	RPR8W-2301001(NO:146)	10MHz~8GHz	Jan. 17, 2025	Aug. 18, 2025~ Sep. 24, 2025	Jan. 16, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101467	10Hz~44GHz	Jan. 14, 2025	Aug. 18, 2025~ Sep. 24, 2025	Jan. 13, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Aug. 18, 2025~ Sep. 24, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_250613	N/A	Conducted Other Test Item	N/A	Aug. 18, 2025~ Sep. 24, 2025	N/A	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Aug. 21, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 10, 2024	Aug. 21, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Aug. 21, 2025	Jun. 25, 2026	Conduction (CO05-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	9kHz~30MHz	Mar. 26, 2025	Aug. 21, 2025	Mar. 25, 2026	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Jul. 25, 2025	Aug. 21, 2025	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Aug. 21, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 29, 2025	Aug. 21, 2025	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	9KHz - 30MHz	Oct. 15, 2024	Aug. 21, 2025	Oct. 14, 2025	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.7 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	6.4 dB

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.1 dB

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.3 dB

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.3 dB

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sylvia Li	Temperature:	21~25	°C
Test Date:	2025/08/18~2025/08/19	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.047	0.694	0.50	Pass
BLE	1Mbps	1	19	2440	1.048	0.696	0.50	Pass
BLE	1Mbps	1	39	2480	1.048	0.695	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	17.60	30.00	5.20	22.80	36.00	Pass
BLE	1Mbps	1	19	2440	17.80	30.00	5.20	23.00	36.00	Pass
BLE	1Mbps	1	39	2480	17.80	30.00	5.20	23.00	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	17.83	6.76	5.20	8.00	Pass
BLE	1Mbps	1	19	2440	18.03	6.88	5.20	8.00	Pass
BLE	1Mbps	1	39	2480	18.02	6.71	5.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Report Number : FR562407A

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.102	1.361	0.50	Pass
BLE	2Mbps	1	19	2440	2.091	1.374	0.50	Pass
BLE	2Mbps	1	39	2480	2.101	1.382	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	17.60	30.00	5.20	22.80	36.00	Pass
BLE	2Mbps	1	19	2440	17.80	30.00	5.20	23.00	36.00	Pass
BLE	2Mbps	1	39	2480	16.10	30.00	5.20	21.30	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	17.09	2.98	5.20	8.00	Pass
BLE	2Mbps	1	19	2440	17.68	3.31	5.20	8.00	Pass
BLE	2Mbps	1	39	2480	15.06	1.43	5.20	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

Number of TX = 1, Ant.3 (Measured)

6dB Bandwidth

<1Mbps>

6 dB Bandwidth Plot on Channel 0	6 dB Bandwidth Plot on Channel 19
	
6 dB Bandwidth Plot on Channel 39	
	

<2Mbps>

6 dB Bandwidth Plot on Channel 0	6 dB Bandwidth Plot on Channel 19
	
6 dB Bandwidth Plot on Channel 39	
	

99% Occupied Bandwidth

<1Mbps>

99% Occupied Bandwidth Plot on Channel 0	99% Occupied Bandwidth Plot on Channel 19
	
99% Occupied Bandwidth Plot on Channel 39	
	

<2Mbps>

99% Occupied Bandwidth Plot on Channel 0	99% Occupied Bandwidth Plot on Channel 19
	
99% Occupied Bandwidth Plot on Channel 39	
	

Power Spectral Density (dBm/3kHz)

<1Mbps>

Power Density (dBm/3kHz) Plot Channel 0	Power Density (dBm/3kHz) Plot Channel 19
	
Power Density (dBm/3kHz) Plot Channel 39	
	

<2Mbps>

Power Density (dBm/3kHz) Plot Channel 0	Power Density (dBm/3kHz) Plot Channel 19
	
Power Density (dBm/3kHz) Plot Channel 39	
	

Band Edge and Conducted Spurious Emission

<1Mbps>

Channel 0	
100kHz PSD reference Level Plot	**Plot on Channel 0**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 19	
100kHz PSD reference Level Plot	**Plot on Channel 19**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 39	
100kHz PSD reference Level Plot	**Plot on Channel 39**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

<2Mbps>

Channel 0	
100kHz PSD reference Level Plot	**Plot on Channel 0**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 19	
100kHz PSD reference Level Plot	**Plot on Channel 19**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Channel 39	
100kHz PSD reference Level Plot	**Plot on Channel 39**
	
Spurious Emission 30MHz~1GHz Plot	**Spurious Emission 1GHz~26.5GHz Plot**
	

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Brian Chen	**Temperature :**	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO :	562407
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.72	55.88	26.16	L1	OFF	19.8
0.152250	41.71	---	65.88	24.17	L1	OFF	19.8
0.161250	---	28.83	55.40	26.57	L1	OFF	19.8
0.161250	43.85	---	65.40	21.55	L1	OFF	19.8
0.485250	---	29.29	46.25	16.96	L1	OFF	19.8
0.485250	30.96	---	56.25	25.29	L1	OFF	19.8
0.555000	---	24.52	46.00	21.48	L1	OFF	19.8
0.555000	32.06	---	56.00	23.94	L1	OFF	19.8
2.694750	---	25.34	46.00	20.66	L1	OFF	20.0
2.694750	27.37	---	56.00	28.63	L1	OFF	20.0
6.771750	---	26.10	50.00	23.90	L1	OFF	20.3
6.771750	27.49	---	60.00	32.51	L1	OFF	20.3

EUT Information

Report NO :	562407
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	29.87	55.88	26.01	N	OFF	19.8
0.152250	42.49	---	65.88	23.39	N	OFF	19.8
0.161250	---	28.51	55.40	26.89	N	OFF	19.8
0.161250	41.63	---	65.40	23.77	N	OFF	19.8
0.195000	---	28.82	53.82	25.00	N	OFF	19.8
0.195000	38.24	---	63.82	25.58	N	OFF	19.8
0.543750	---	32.01	46.00	13.99	N	OFF	19.8
0.543750	34.66	---	56.00	21.34	N	OFF	19.8
1.322250	---	23.92	46.00	22.08	N	OFF	19.9
1.322250	25.59	---	56.00	30.41	N	OFF	19.9
15.067500	---	25.57	50.00	24.43	N	OFF	20.6
15.067500	27.13	---	60.00	32.87	N	OFF	20.6

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Daniel Lee, Fu Chen and Troye Hsieh	Temperature :	19.1~20.9°C
		Relative Humidity :	51.4~66.5%

Note symbol

-L	**Low channel location**
-R	**High channel location**

C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	3	Bluetooth-LE_GSFK	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	3	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	3	Bluetooth-LE_GSFK	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	3	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
Mode 7	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	2Mbps	-	SHF
Mode 8	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	2Mbps	-	LF

C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
1	Bluetooth-LE_GSFK	00	-	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	00	12010.00	50.24	54.00	-3.76	V	Avg.	Pass	-	Harmonic
2	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	12200.00	50.54	54.00	-3.46	V	Avg.	Pass	-	Harmonic
3	Bluetooth-LE_GSFK	39	2483.52	52.43	54.00	-1.57	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GSFK	39	12400.00	49.40	54.00	-4.60	V	Avg.	Pass	-	Harmonic
4	Bluetooth-LE_GSFK	00	2369.34	46.54	54.00	-7.46	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GSFK	00	12010.00	50.00	54.00	-4.00	V	Avg.	Pass	-	Harmonic
5	Bluetooth-LE_GSFK	19	2488.60	44.06	54.00	-9.94	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GSFK	19	12200.00	49.52	54.00	-4.48	V	Avg.	Pass	-	Harmonic

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
6	Bluetooth-LE_GSFK	39	2483.52	53.67	54.00	-0.33	V	Avg.	Pass	-	Band Edge
	Bluetooth-LE_GSFK	39	12400.00	50.86	54.00	-3.14	V	Avg.	Pass	-	Harmonic
7	Bluetooth-LE_GSFK	39	19840.00	33.91	54.00	-20.09	H	Avg.	Pass	-	SHF
8	Bluetooth-LE_GSFK	39	30.97	33.28	40.00	-6.72	H	Peak	Pass	-	LF

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 1 Setting : 18 : The unwanted signal "7206,9608,14412,16814 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 46.11 74.00 -27.89 69.71 32.32 10.34 66.76 0.50 250 3 Peak 2 4804.00 43.11 54.00 -10.89 66.71 32.32 10.34 66.76 0.50 250 3 Average 3 7206.00 43.18 ------ ------ 58.04 36.80 13.64 65.65 0.35 400 321 Peak 4 9608.00 46.16 ------ ------ 59.11 38.17 15.73 67.34 0.49 300 310 Peak 5 12010.00 52.19 74.00 -21.81 61.00 38.82 17.94 65.90 0.33 300 331 Peak 6 12010.00 46.50 54.00 -7.50 55.31 38.82 17.94 65.90 0.33 300 331 Average 7 14412.00 52.69 ------ ------ 57.97 40.20 19.98 65.99 0.53 100 17 Peak 8 16814.00 53.12 ------ ------ 59.43 37.98 21.39 66.25 0.57 400 50 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 1 Setting : 18 : The unwanted signal "7206,9608,14412,16814 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 45.75 74.00 -28.25 69.35 32.32 10.34 66.76 0.50 150 346 Peak 2 4804.00 43.08 54.00 -10.92 66.68 32.32 10.34 66.76 0.50 150 346 Average 3 7206.00 44.36 ------ ------ 59.22 36.80 13.64 65.65 0.35 377 360 Peak 4 9608.00 50.14 ------ ------ 63.09 38.17 15.73 67.34 0.49 393 360 Peak 5 12010.00 55.16 74.00 -18.84 63.97 38.82 17.94 65.90 0.33 200 5 Peak 6 12010.00 50.24 54.00 -3.76 59.05 38.82 17.94 65.90 0.33 200 5 Average 7 14412.00 53.86 ------ ------ 59.14 40.20 19.98 65.99 0.53 200 23 Peak 8 16814.00 53.80 ------ ------ 60.11 37.98 21.39 66.25 0.57 360 360 Peak

Remark: The unwanted signal 7206.000MHz、9608.000MHz、14412.000MHz、16814.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 1 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 1 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 1 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 1 Setting : 18

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 2 Setting : 18 : The unwanted signal "9760 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 41.76 74.00 -32.24 64.54 32.72 10.66 66.70 0.54 -- -- Peak 2 7320.00 46.47 74.00 -27.53 61.44 36.76 13.74 65.78 0.31 300 348 Peak 3 7320.00 41.98 54.00 -12.02 56.95 36.76 13.74 65.78 0.31 300 348 Average 4 9760.00 51.76 ------ ------ 64.78 38.00 16.02 67.40 0.36 200 343 Peak 5 12200.00 51.25 74.00 -22.75 59.71 39.00 18.13 65.94 0.35 200 40 Peak 6 12200.00 47.02 54.00 -6.98 55.48 39.00 18.13 65.94 0.35 200 40 Average	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 2 Setting : 18 : The unwanted signal "9760 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 41.70 74.00 -32.30 64.48 32.72 10.66 66.70 0.54 -- -- Peak 2 7320.00 47.74 74.00 -26.26 62.71 36.76 13.74 65.78 0.31 399 0 Peak 3 7320.00 42.90 54.00 -11.10 57.87 36.76 13.74 65.78 0.31 399 0 Average 4 9760.00 51.29 ------ ------ 64.31 38.00 16.02 67.40 0.36 300 333 Peak 5 12200.00 55.93 74.00 -18.07 64.39 39.00 18.13 65.94 0.35 200 331 Peak 6 12200.00 50.54 54.00 -3.46 59.00 39.00 18.13 65.94 0.35 200 331 Average

Remark: The unwanted signal 9760.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 2 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 2 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 2 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 2 Setting : 18

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.58 61.18 74.00 -12.82 49.56 27.84 6.87 33.12 10.03 100 26 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 115.74 ------ ------ 104.16 27.80 6.87 33.12 10.03 100 26 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.58 50.49 54.00 -3.51 38.87 27.84 6.87 33.12 10.03 100 26 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 110.75 ------ ------ 99.17 27.80 6.87 33.12 10.03 100 26 Average

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 64.47 74.00 -9.53 52.85 27.84 6.87 33.12 10.03 121 16 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 118.01 ------ ------ 106.43 27.80 6.87 33.12 10.03 121 16 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 52.43 54.00 -1.57 40.81 27.84 6.87 33.12 10.03 121 16 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 3 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 113.02 ------ ------ 101.44 27.80 6.87 33.12 10.03 121 16 Average

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 3 Setting : 18 : The unwanted signal "9920 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.67 74.00 -31.33 64.70 33.02 11.01 66.63 0.57 -- -- Peak 2 7440.00 46.36 74.00 -27.64 61.87 36.24 13.86 65.93 0.32 300 348 Peak 3 7440.00 44.23 54.00 -9.77 59.74 36.24 13.86 65.93 0.32 300 348 Average 4 9920.00 52.95 ------ ------ 65.89 38.06 16.14 67.47 0.33 200 342 Peak 5 12400.00 54.20 74.00 -19.80 62.59 38.90 18.32 65.98 0.37 300 334 Peak 6 12400.00 47.51 54.00 -6.49 55.90 38.90 18.32 65.98 0.37 300 334 Average	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 3 Setting : 18 : The unwanted signal "9920 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.60 74.00 -31.40 64.63 33.02 11.01 66.63 0.57 -- -- Peak 2 7440.00 47.24 74.00 -26.76 62.75 36.24 13.86 65.93 0.32 -- -- Peak 3 9920.00 52.04 ------ ------ 64.98 38.06 16.14 67.47 0.33 -- -- Peak 4 12400.00 55.61 74.00 -18.39 64.00 38.90 18.32 65.98 0.37 200 328 Peak 5 12400.00 49.40 54.00 -4.60 57.79 38.90 18.32 65.98 0.37 200 328 Average

Remark: The unwanted signal 9920.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 3 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 3 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 3 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 3 Setting : 18

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.71 55.38 74.00 -18.62 44.61 27.20 6.77 33.22 10.02 100 27 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 112.91 ------ ------ 101.85 27.40 6.82 33.19 10.03 100 27 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.43 44.54 54.00 -9.46 33.77 27.20 6.77 33.22 10.02 100 27 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 107.77 ------ ------ 96.71 27.40 6.82 33.19 10.03 100 27 Average

Mode	4	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.25 56.31 74.00 -17.69 45.54 27.20 6.77 33.22 10.02 123 13 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 117.05 ------ ------ 105.99 27.40 6.82 33.19 10.03 123 13 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.34 46.54 54.00 -7.46 35.77 27.20 6.77 33.22 10.02 123 13 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 4 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 111.94 ------ ------ 100.88 27.40 6.82 33.19 10.03 123 13 Average

Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 4 Setting : 18 : The unwanted signal "7206,9608,14412,16814 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 46.34 74.00 -27.66 69.94 32.32 10.34 66.76 0.50 250 11 Peak 2 4804.00 42.29 54.00 -11.71 65.89 32.32 10.34 66.76 0.50 250 11 Average 3 7206.00 44.12 ------ ------ 58.98 36.80 13.64 65.65 0.35 399 360 Peak 4 9608.00 48.32 ------ ------ 61.27 38.17 15.73 67.34 0.49 200 290 Peak 5 12010.00 51.69 74.00 -22.31 60.50 38.82 17.94 65.90 0.33 300 329 Peak 6 12010.00 47.97 54.00 -6.03 56.78 38.82 17.94 65.90 0.33 300 329 Average 7 14412.00 54.76 ------ ------ 60.04 40.20 19.98 65.99 0.53 400 342 Peak 8 16814.00 52.16 ------ ------ 58.47 37.98 21.39 66.25 0.57 400 45 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 4 Setting : 18 : The unwanted signal "7206,9608,14412,16814 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 46.42 74.00 -27.58 70.02 32.32 10.34 66.76 0.50 250 335 Peak 2 4804.00 42.61 54.00 -11.39 66.21 32.32 10.34 66.76 0.50 250 335 Average 3 7206.00 46.25 ------ ------ 61.11 36.80 13.64 65.65 0.35 365 360 Peak 4 9608.00 51.15 ------ ------ 64.10 38.17 15.73 67.34 0.49 393 360 Peak 5 12010.00 55.83 74.00 -18.17 64.64 38.82 17.94 65.90 0.33 200 329 Peak 6 12010.00 50.00 54.00 -4.00 58.81 38.82 17.94 65.90 0.33 200 329 Average 7 14412.00 55.15 ------ ------ 60.43 40.20 19.98 65.99 0.53 200 51 Peak 8 16814.00 55.40 ------ ------ 61.71 37.98 21.39 66.25 0.57 319 360 Peak

Remark: The unwanted signal 7206.000MHz、9608.000MHz、14412.000MHz、16814.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	4	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH00_2402MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 4 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 4 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 4 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 4 Setting : 18

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2376.95 53.83 74.00 -20.17 43.04 27.20 6.78 33.21 10.02 100 32 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 113.24 ------ ------ 101.93 27.60 6.84 33.16 10.03 100 32 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2376.04 43.10 54.00 -10.90 32.31 27.20 6.78 33.21 10.02 100 32 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 107.77 ------ ------ 96.46 27.60 6.84 33.16 10.03 100 32 Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2488.36 55.45 74.00 -18.55 43.78 27.88 6.87 33.11 10.03 100 32 Peak	Blank
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2489.50 43.37 54.00 -10.63 31.68 27.90 6.87 33.11 10.03 100 32 Average	Blank

Mode	5	
	Band Edge - L	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2376.43 54.95 74.00 -19.05 44.16 27.20 6.78 33.21 10.02 211 32 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 116.09 ------ ------ 104.78 27.60 6.84 33.16 10.03 211 32 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2376.04 43.84 54.00 -10.16 33.05 27.20 6.78 33.21 10.02 211 32 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2440.00 110.97 ------ ------ 99.66 27.60 6.84 33.16 10.03 211 32 Average

Mode	5	
	Band Edge - R	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 5 Setting : 18 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2491.42 55.28 74.00 -18.72 43.59 27.90 6.87 33.11 10.03 211 32 Peak	Blank
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 5 Setting : 18 Limit Read Ant Cable Preamp Aux APos TPos Freq Level Line Margin Level Factor Loss Factor Factor Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2488.60 44.06 54.00 -9.94 32.38 27.89 6.87 33.11 10.03 211 32 Average	Blank

Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 5 Setting : 18 : The unwanted signal "9760 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). 1 4880.00 41.19 74.00 -32.81 63.97 32.72 10.66 66.70 0.54 -- -- Peak 2 7320.00 47.94 74.00 -26.06 62.91 36.76 13.74 65.78 0.31 250 351 Peak 3 7320.00 44.21 54.00 -9.79 59.18 36.76 13.74 65.78 0.31 250 351 Average 4 9760.00 52.42 ------ ------ 65.44 38.00 16.02 67.40 0.36 200 25 Peak 5 12200.00 53.67 74.00 -20.33 62.13 39.00 18.13 65.94 0.35 350 327 Peak 6 12200.00 46.60 54.00 -7.40 55.06 39.00 18.13 65.94 0.35 350 327 Average	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 5 Setting : 18 : The unwanted signal "9760,14640 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). 1 4880.00 41.94 74.00 -32.06 64.72 32.72 10.66 66.70 0.54 -- -- Peak 2 7320.00 47.42 74.00 -26.58 62.39 36.76 13.74 65.78 0.31 382 0 Peak 3 7320.00 43.46 54.00 -10.54 58.43 36.76 13.74 65.78 0.31 382 0 Average 4 9760.00 52.13 ------ ------ 65.15 38.00 16.02 67.40 0.36 366 360 Peak 5 12200.00 55.46 74.00 -18.54 63.92 39.00 18.13 65.94 0.35 100 350 Peak 6 12200.00 49.52 54.00 -4.48 57.98 39.00 18.13 65.94 0.35 100 350 Average 7 14640.00 53.70 ------ ------ 59.09 40.10 20.04 66.07 0.54 100 53 Peak

Remark: The unwanted signal 9760.000MHz、14640.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	5	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH19_2440MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 5 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 5 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 5 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 5 Setting : 18

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 62.77 74.00 -11.23 51.15 27.84 6.87 33.12 10.03 101 27 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 113.29 ------ ------ 101.71 27.80 6.87 33.12 10.03 101 27 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.54 52.25 54.00 -1.75 40.63 27.84 6.87 33.12 10.03 101 27 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 108.01 ------ ------ 96.43 27.80 6.87 33.12 10.03 101 27 Average

Mode	6	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 65.81 74.00 -8.19 54.19 27.84 6.87 33.12 10.03 286 23 Peak	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : PEAK Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 116.62 ------ ------ 105.04 27.80 6.87 33.12 10.03 286 23 Peak
Avg	 Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2483.52 53.67 54.00 -0.33 42.05 27.84 6.87 33.12 10.03 286 23 Average	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto Detector : RMS Mode : 7 Setting : 18 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 111.45 ------ ------ 99.87 27.80 6.87 33.12 10.03 286 23 Average

Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak Avg	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 HORIZONTAL Mode : 7 Setting : 18 : The unwanted signal "9920 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 41.81 74.00 -32.19 63.84 33.02 11.01 66.63 0.57 -- -- Peak 2 7440.00 47.95 74.00 -26.05 63.46 36.24 13.86 65.93 0.32 250 351 Peak 3 7440.00 44.51 54.00 -9.49 60.02 36.24 13.86 65.93 0.32 250 351 Average 4 9920.00 55.83 ------ ------ 68.77 38.06 16.14 67.47 0.33 200 343 Peak 5 12400.00 55.28 74.00 -18.72 63.67 38.90 18.32 65.98 0.37 200 35 Peak 6 12400.00 48.72 54.00 -5.28 57.11 38.90 18.32 65.98 0.37 200 35 Average	 Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL Mode : 7 Setting : 18 : The unwanted signal "9920 MHz" can be ignored since it falls within : the non-restricted band and meet the requirements of 15.247 (d). Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 42.49 74.00 -31.51 64.52 33.02 11.01 66.63 0.57 -- -- Peak 2 7440.00 49.34 74.00 -24.66 64.85 36.24 13.86 65.93 0.32 400 0 Peak 3 7440.00 44.42 54.00 -9.58 59.93 36.24 13.86 65.93 0.32 400 0 Average 4 9920.00 54.16 ------ ------ 67.10 38.06 16.14 67.47 0.33 253 0 Peak 5 12400.00 56.79 74.00 -17.21 65.18 38.90 18.32 65.98 0.37 300 356 Peak 6 12400.00 50.86 54.00 -3.14 59.25 38.90 18.32 65.98 0.37 300 356 Average

Remark: The unwanted signal 9920.000MHz can be ignored since it falls within the non-restricted band and meet the requirements of 15.247 (d).

Mode	6	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
14.47G ~14.5G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 7 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 7 Setting : 18
17.7G ~18G Avg	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 HORIZONTAL Mode : 7 Setting : 18	 Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL Mode : 7 Setting : 18

Mode	7	
	SHF	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
Peak	 Site : 03CH11-HY Condition: PEAK_74 1m SHF_00994_250109 HORIZONTAL Mode : 8 Setting :	 Site : 03CH11-HY Condition: PEAK_74 1m SHF_00994_250109 VERTICAL Mode : 8 Setting :

Horizontal:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	19840.00	42.96	74.00	-31.04	45.67	38.50	23.32	54.99	-9.54	100	313	Peak
2	19840.00	33.91	54.00	-20.09	36.62	38.50	23.32	54.99	-9.54	100	313	Average

Vertical:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	19840.00	38.07	74.00	-35.93	40.78	38.50	23.32	54.99	-9.54	--	--	Peak

Mode	8	
	LF	
	2400-2483.5_Bluetooth-LE_GSFK _CH39_2480MHz	
ANT	3	
Pol.	Horizontal	Vertical
QP/ Peak	 Site : 03CH11-HY Condition: QP 3m BILOG_37059&01_241127 HORIZONTAL Mode : 9 Setting :	 Site : 03CH11-HY Condition: QP 3m BILOG_37059&01_241127 VERTICAL Mode : 9 Setting :

Horizontal:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	30.97	33.28	40.00	-6.72	40.58	24.21	0.83	32.41	0.07	--	--	Peak
2	125.06	22.30	43.50	-21.20	35.34	17.64	1.57	32.30	0.05	--	--	Peak
3	272.50	19.84	46.00	-26.16	30.75	18.87	2.30	32.20	0.12	--	--	Peak
4	498.51	23.78	46.00	-22.22	28.63	24.12	3.11	32.20	0.12	--	--	Peak
5	746.83	28.43	46.00	-17.57	28.16	28.39	3.78	32.10	0.20	--	--	Peak
6	947.62	33.02	46.00	-12.98	28.63	30.82	4.28	30.92	0.21	--	--	Peak

Vertical:

	Freq	Level	Limit Line	Margin	Read Level	Ant Factor	Cable Loss	Preamp Factor	Aux Factor	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	30.97	33.22	40.00	-6.78	40.52	24.21	0.83	32.41	0.07	--	--	Peak
2	98.87	27.34	43.50	-16.16	42.10	16.07	1.44	32.31	0.04	--	--	Peak
3	267.65	18.91	46.00	-27.09	29.30	19.40	2.28	32.20	0.13	--	--	Peak
4	515.00	23.33	46.00	-22.67	27.99	24.26	3.16	32.19	0.11	--	--	Peak
5	755.56	28.86	46.00	-17.14	28.56	28.38	3.80	32.08	0.20	--	--	Peak
6	942.77	32.06	46.00	-13.94	27.97	30.58	4.27	30.97	0.21	--	--	Peak

Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	Duty Factor(dB)
Bluetooth - LE for 1Mbps	100.00	-	0.00
Bluetooth - LE for 2Mbps	100.00	-	0.00

Bluetooth - LE for 1Mbps	Bluetooth - LE for 2Mbps
	

———THE END———