



Kenbotong Technology Co., Ltd.

SPECIFICATION

Vendor Name	Shenzhen kenhaitong antenna technology co,Ltd.				
Customer Name	Particle				
Sample Name	MonitorOne-4G				
Part Number					
Specification					
Inspection Item	Performance	Total Appearance	structure	Others	Inspection Result
Remark					
QA Audit		Engineer Audit		Sales Confirm	
The following are filled by Customer					
Customer Evaluation					
Signation/ Chapter by Customer	date:				

Kenbotong Technology Co., Ltd.

1、Antenna Picture



Kenbotong Technology Co., Ltd.


2.Measurement information

Band	700/960	1710/2170
Frequency (MHz)	700–960	1710–2170
Max VSWR	≤3.6	≤1.5
Max Return loss (dB)	–8	–13
Peak Gain (dBi)	1.7	3.47
Efficiency (%)	55	53
Average Gain (dB)	0.5	2
Radiation Properties	Omnidirectional	
Max Input Power (watts)	5	
Polarization	Linear	
Impedance (Ohms)	50 Ohms	
MECHANICAL		
Dimensions (mm)	80.21*21.1*0.8mm	
Material	Flexible Polymer	
Connector and Cable	U.FL and 1.13mm mini coax	
Cable Length	49mm	
ENVIRONMENTAL		
Operation Temperature	–40℃ to 85℃	
Storage Temperature	–40℃ to 85℃	
Relative Humidity	–40℃ to 95℃	
ROHS Compliant	YES	

Kenbotong Technology Co., Ltd.


3. Antenna Parameters

VSWR




Kenbotong Technology Co., Ltd.

Radiation Pattern




Kenbotong Technology Co., Ltd.

Radiation Pattern at 700–960 MHz of Antenna




Radiation Pattern at 1710–2170 MHz of Antenna







Kenbotong Technology Co., Ltd.

5、Mechanical Drawing



Kenbotong Technology Co., Ltd.

6、Packaging

Packaging					
Customer Name:particle		name: MonitorOne-4G天线		Code:	TEST: A
	Code	name	size	quantities	
	PE	PE bag	230*330*0.12	1/100	
	SYC-BZ-01	Paper box	270*250*130	1/5000	
S T e p s					N O T I C E
	 5000PCS				
compile		approval		MADE	DATE