

FCC TEST REPORT

(PART 22)


Applicant:	Particle Industries, Inc
Address:	325 9th Street, San Francisco, CA 94103, United States Of America

Manufacturer or Supplier:	Particle Industries, Inc
Address:	325 9th Street, San Francisco, CA 94103, United States Of America
Product:	M SoM
Brand Name:	Particle
Model Name:	M404
FCC ID:	2AEMI-M404
Date of tests:	Dec. 27, 2023 ~ Jan. 02, 2024

The tests have been carried out according to the requirements of the following standard:

- ☒ **FCC PART 22, Subpart H** ☒ **FCC Part 2**
☒ **ANSI/TIA/EIA-603-D** ☒ **ANSI C63.26-2015**
☒ **ANSI/TIA/EIA-603-E**

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Prepared by Simon Wang Engineer / Mobile Department	Approved by Luke Lu Manager / Mobile Department
	
Date: Jan. 02, 2024	Date: Jan. 02, 2024

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1 SUMMARY OF TEST RESULTS.....	4
1.1 MEASUREMENT UNCERTAINTY	5
1.2 TEST SITE AND INSTRUMENTS	6
2 GENERAL INFORMATION	7
2.1 GENERAL DESCRIPTION OF EUT	7
2.2 CONFIGURATION OF SYSTEM UNDER TEST	10
2.3 DESCRIPTION OF SUPPORT UNITS	11
2.4 TEST ITEM AND TEST CONFIGURATION.....	11
2.5 EUT OPERATING CONDITIONS.....	14
2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS	15
3 TEST TYPES AND RESULTS.....	15
3.1 OUTPUT POWER MEASUREMENT	16
3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT	16
3.1.2 TEST PROCEDURES	16
3.1.3 TEST SETUP	17
3.1.4 TEST RESULTS	17
3.2 RADIATED EMISSION MEASUREMENT	29
3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT	29
3.2.2 TEST PROCEDURES	29
3.2.3 DEVIATION FROM TEST STANDARD	29
3.2.4 TEST SETUP	30
3.2.5 TEST RESULTS	32
4 PHOTOGRAPHS OF THE TEST CONFIGURATION	60
5 INFORMATION ON THE TESTING LABORATORIES	61
6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	62



Test Report No.: W7L-P23120015RF01

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
W7L-P23120015RF01	Original release	Jan. 02, 2024

1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 22 & Part 2		
STANDARD SECTION	TEST TYPE	RESULT
§2.1046	Conducted Output Power	Compliance
§22.913 (a)(5)	Effective Radiated Power	Compliance
§2.1055 §22.355	Frequency Stability	See Note
§2.1049	Occupied Bandwidth	See Note
§22.913 (d)	Peak to average ratio*	See Note
§22.917(a)	Band Edge Measurements	See Note
§2.1051 §22.917(a)	Conducted Spurious Emissions	See Note
§2.1053 §22.917(a)	Radiated Spurious Emissions	Compliance

* Refer to KDB 971168 D01 Power Meas License Digital Systems v03r01.

Note : please refer to the module report R2108A0767-R1V1 (FCC ID: XMR202005BG95M5)

1.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	UNCERTAINTY
Maximum Peak Output Power	$\pm 2.06\text{dB}$
Radiated emissions (9KHz~30MHz)	$\pm 2.68\text{dB}$
Radiated emissions (30MHz~1GHz)	$\pm 4.98\text{dB}$
Radiated emissions (1GHz ~6GHz)	$\pm 4.70\text{dB}$
Radiated emissions (6GHz ~18GHz)	$\pm 4.60\text{dB}$
Radiated emissions (18GHz ~40GHz)	$\pm 4.12\text{dB}$

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

1.2 TEST SITE AND INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
MXE EMI Receiver	KEYSIGHT	N9038A-544	MY54450026	Mar. 28,23	Mar. 27,24
EXA Signal Analyzer	KEYSIGHT	N9010A-544	MY54510355	May.10,23	May.09,24
Loop Antenna	Schwarzbeck	FMZB 1519B	00173	Sep.03,23	Sep.02,24
Bilog Antenna	ETS-LINDGRE N	3143B	00161965	Feb. 18,23	Feb. 17,24
Horn Antenna	ETS-LINDGRE N	3117	00168692	Feb. 18,23	Feb. 17,24
Horn Antenna (18GHz-40GHz)	N/A	QWH-SL-18-40-K- SG/QMS-00361	15433	Sep.04, 23	Sep.03, 24
Radio Communication Analyzer	ANRITSU	MT8820C	6201465426	Feb. 14,23	Feb. 13,24
Signal Pre-Amplifier	EMSI	EMC 9135	980249	May. 06,23	May. 05,24
Signal Pre-Amplifier	EMSI	EMC 012645B	980257	May.10,23	May.09,24
Signal Pre-Amplifier	EMSI	EMC 184045B	980259	Feb. 17,23	Feb.16,24
3m Semi-anechoic Chamber	ETS-LINDGRE N	9m*6m*6m	Euroshieldpn- CT0001143-121 6	Nov. 14,23	Nov. 13,26
Test Software	E3	V 9.160323	N/A	N/A	N/A
Test Software	JS1120	3.1.36	N/A	N/A	N/A
10dB Attenuator	JFW/USA	50HF-010-SMA	50HF-010-SMA	May. 06,23	May. 05,24
Power Meter	Anritsu	ML2495A	1506002	Feb. 14,23	Feb. 13,24
Power Sensor	Anritsu	MA2411B	1339352	Feb. 14,23	Feb. 13,24
Temperature Chamber	ESPEC	SH-242	93000855	May. 06,23	May. 05,24
MXG Analog Microvave Signal Generator	KEYSIGHT	N5183A	MY50143024	Feb. 14,23	Feb. 13,24
Base station R&S CMW500	Rohde&Schwa rz	CMW500	153085	May.10,23	May.09,24
DC Source	Kikusui/JP	PMX18-5A	N/A	Aug. 11,23	Aug. 10,24

- NOTE:**
1. The calibration interval of the above test instruments is 12 months or 36 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
 2. The test was performed in 3m Semi-anechoic Chamber and RF Oven Room.
 3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 525120; The Designation No. is CN1171.



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	M SoM	
BRAND NAME	Particle	
MODEL NAME	M404	
NOMINAL VOLTAGE	VCC: 3.8V. 3V3:3.3V	
MODULATION TYPE	GSM/GPRS/EDGE	GMSK, 8PSK
	LTE	QPSK, 16QAM
FREQUENCY RANGE	GSM/EDGE	824.2MHz ~ 848.8MHz
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE Band 5 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE Band 5 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE Band 5 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	824.7MHz ~ 848.3MHz
	LTE Band 26 (Channel Bandwidth: 3MHz)	825.5MHz ~ 847.5MHz
	LTE Band 26 (Channel Bandwidth: 5MHz)	826.5MHz ~ 846.5MHz
	LTE Band 26 (Channel Bandwidth: 10MHz)	829MHz ~ 844MHz
	LTE Band 26 (Channel Bandwidth: 15MHz)	831.5MHz ~ 841.5MHz
MAX. ERP POWER	GSM	2013.72mW
	EDGE	505.82mW
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	243.22mW
	LTE Band 5 (Channel Bandwidth: 3MHz)	243.78mW
	LTE Band 5 (Channel Bandwidth: 5MHz)	246.04mW
	LTE Band 5 (Channel Bandwidth: 10MHz)	247.17mW
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	282.49mW
	LTE Band 26 (Channel Bandwidth: 3MHz)	279.9mW
	LTE Band 26 (Channel Bandwidth: 5MHz)	283.14mW



	LTE Band 26 (Channel Bandwidth: 10MHz)	285.1mW
	LTE Band 26 (Channel Bandwidth: 15MHz)	286.42mW
EMISSION DESIGNATOR GOGN	GSM	246KGXW
	GPRS	248KGXW
	EDGE	248KG7W
	LTE Band 5 (Channel Bandwidth: 1.4MHz)	QPSK: 1M11G7D
		16QAM: 940KW7D
		64QAM: /
	LTE Band 5 (Channel Bandwidth: 3MHz)	QPSK: 1M10G7D
		16QAM: 953KW7D
		64QAM: /
	LTE Band 5 (Channel Bandwidth: 5MHz)	QPSK: 1M10G7D
		16QAM: 951KW7D
		64QAM: /
	LTE Band 5 (Channel Bandwidth: 10MHz)	QPSK: 1M12G7D
		16QAM: 962KW7D
		64QAM: /
	LTE Band 26 (Channel Bandwidth: 1.4MHz)	QPSK: 1M11G7D
		16QAM: 940KW7D
		64QAM: /
	LTE Band 26 (Channel Bandwidth: 3MHz)	QPSK: 1M10G7D
		16QAM: 941KW7D
		64QAM: /
	LTE Band 26 (Channel Bandwidth: 5MHz)	QPSK: 1M11G7D
		16QAM: 947KW7D
		64QAM: /
	LTE Band 26 (Channel Bandwidth: 10MHz)	QPSK: 1M12G7D
		16QAM: 960KW7D
		64QAM: /
	LTE Band 26 (Channel Bandwidth: 15MHz)	QPSK: 1M13G7D
		16QAM: 961KW7D
		64QAM: /
ANTENNA TYPE	Fixed External Antenna with 2.8dBi gain for GSM850 /LTE B5/LTE B26	
HW VERSION	v0.2	



SW VERSION	v5.5.2
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A
EXTREME TEMPERATURE	-35-75 °C
EXTREME VOLTAGE	VCC: 3.3V. 3V3:3.0V- VCC: 4.3V. 3V3:3.6V


NOTE:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
2. The EUT incorporates a SISO function. Physically, the EUT provides one completed transmitter and one receiver.

MODULATION MODE	TX FUNCTION
GSM/GPRS/EDGE	1TX/1RX
LTE	1TX/1RX

3. For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
4. Antenna gain and EUT conducted cable loss are provided by the customer, and the laboratory will record the results based on these items that involve these two parameters.

2.2 CONFIGURATION OF SYSTEM UNDER TEST FOR RADIATION EMISSION



2.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	AC Adapter	TRI-MAG	L6R30-240	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A

2.4 TEST ITEM AND TEST CONFIGURATION

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports. The worst case in ERP and radiated emission was found when positioned on X-plane for GSM /EDGE /LTE. Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	DESCRIPTION
A	EUT + Adapter with GSM or LTE link

GSM MODE

EUT CONFIGURE MODE	TEST ITEM	AVAILABLE CHANNEL	TESTED CHANNEL	MODE
A	ERP	128 to 251	128, 190, 251	GSM,EDGE
A	RADIATED EMISSION	128 to 251	128, 190, 251	GSM,EDGE

LTE BAND 5 MODE

EUT CONFIGURE MODE	TEST ITEM	Available Channel	Tested Channel	Channel bandwidth	modulation	mode
A	ERP	20407 to 20643	20407, 20525, 20643	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		20415 to 20635	20415, 20525, 20635	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		20425 to 20625	20425, 20525, 20625	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		20450 to 20600	20450, 20525, 20600	10MHz	QPSK,16QAM	1 RB / 0 RB Offset

Note: 1.This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

2. LTE Band 5 are covered by LTE Band 26, Because it is a subset of LTE Band 26 with the same output power and supported bandwidths, So the Radiated Emission test data please refer to LTE Band 26.

LTE BAND 26 MODE

EUT CONFIGURE MODE	TEST ITEM	Available Channel	Tested Channel	Channel bandwidth	modulation	mode
A	ERP	26797 to 27033	26797, 26915, 27033	1.4MHz	QPSK,16QAM	1 RB / 0 RB Offset
		26805 to 27025	26805, 26915, 27025	3MHz	QPSK,16QAM	1 RB / 0 RB Offset
		26815 to 27015	26815, 26915, 27015	5MHz	QPSK,16QAM	1 RB / 0 RB Offset
		26840 to 26990	26840, 26915, 26990	10MHz	QPSK,16QAM	1 RB / 0 RB Offset
		26865 to 26965	26865, 26915, 26965	15MHz	QPSK,16QAM	1 RB / 0 RB Offset
A	RADIATED EMISSION	26797 to 27033	26915	1.4MHz	QPSK	1 RB / 0 RB Offset
		26805 to 27025	26805, 26915, 27025	3MHz	QPSK	1 RB / 0 RB Offset
		26815 to 27015	26915	5MHz	QPSK	1 RB / 0 RB Offset
		26840 to 26990	26915	10MHz	QPSK	1 RB / 0 RB Offset
		26865 to 26965	26915	15MHz	QPSK	1 RB / 0 RB Offset

Note: This device was tested under all bandwidths, RB configurations and modulations. The worst case was found in QPSK modulation.

TEST CONDITION:

TEST ITEM	ENVIRONMENTAL CONDITIONS	INPUT POWER	TESTED BY
ERP	23deg. C, 70%RH	3.8V	Jace Hu
RADIATED EMISSION	23deg. C, 70%RH	AC 120V/60Hz	Jace Hu

2.5 EUT OPERATING CONDITIONS

The EUT makes a call to the communication simulator. The communication simulator station system controlled a EUT to export maximum output power under transmission mode and specific channel frequency

2.6 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC 47 CFR Part 2

FCC 47 CFR Part 22

KDB 971168 D01 Power Meas License Digital Systems v03r01

ANSI/TIA/EIA-603-D

ANSI/TIA/EIA-603-E

ANSI C63.26-2015

NOTE: All test items have been performed and recorded as per the above standards.

3 TEST TYPES AND RESULTS

3.1 OUTPUT POWER MEASUREMENT

3.1.1 LIMITS OF OUTPUT POWER MEASUREMENT

Mobile / Portable station are limited to 7 watts e.r.p.

3.1.2 TEST PROCEDURES

EIRP / ERP MEASUREMENT:

Per KDB 971168 D01 Power Meas License Digital Systems v03r01 or subclause 5.2.5.5 of ANSI C63.26-2015, the relevant equation for determining the ERP or EIRP from the conducted RF output power measured using the guidance provided above is:

$$\text{ERP or EIRP} = P_{\text{Meas}} + G_T - L_C$$

Where:

ERP or EIRP = effective radiated power or equivalent isotropically radiated power, respectively

(expressed in the same units as P_{Meas} , typically dBW or dBm);

P_{Meas} = measured transmitter output power or PSD, in dBm or dBW;

G_T = gain of the transmitting antenna, in dBd (ERP) or dBi (EIRP);

L_C = signal attenuation in the connecting cable between the transmitter and antenna, in dB.


CONDUCTED POWER MEASUREMENT:

The EUT was set up for the maximum power with WCDMA link data modulation and link up with simulator. Set the EUT to transmit under low, middle and high channel and record the power level shown on simulator.

3.1.3 TEST SETUP

EIRP / ERP Measurement:

CONDUCTED POWER MEASUREMENT:



3.1.4 TEST RESULTS

CONDUCTED OUTPUT POWER (dBm)

Band	GSM850		
Channel	128	190	251
Frequency (MHz)	824.2	836.4	848.8
GSM	32.21	32.33	32.37
GPRS (GMSK, 1Tx-slot)	32.23	32.34	32.39
GPRS (GMSK, 2Tx-slot)	31.51	31.61	31.66
GPRS (GMSK, 3Tx-slot)	30.08	30.18	30.25
GPRS (GMSK, 4Tx-slot)	28.92	28.51	28.59
EDGE (8PSK, 1Tx-slot)	26.39	26.11	26.19
EDGE (8PSK, 2Tx-slot)	26.39	26.04	25.86
EDGE (8PSK, 3Tx-slot)	24.81	24.24	24.09
EDGE (8PSK, 4Tx-slot)	23.99	23.60	23.59



LTE Band 5

Band/BW	Modulation	RB Size	RB Offset	Low CH 20407	Mid CH 20525	High CH 20643
				Frequency 824.7 MHz	Frequency 836.5 MHz	Frequency 848.3 MHz
5/ 1.4	QPSK	1	0	22.95	23.08	23.20
		1	5	22.92	23.15	23.13
		3	0	22.96	23.15	23.21
		3	3	22.94	23.14	23.14
		6	0	21.90	22.12	22.19
	16QAM	1	0	22.95	23.04	23.21
		1	5	22.82	23.15	23.10
		3	0	22.89	23.07	23.18
		3	3	22.88	23.01	23.20
		5	0	21.87	22.01	22.15

Band/BW	Modulation	RB Size	RB Offset	Low CH 20415	Mid CH 20525	High CH 20635
				Frequency 825.5 MHz	Frequency 836.5 MHz	Frequency 847.5 MHz
5/ 3	QPSK	1	0	22.85	23.17	23.15
		1	5	22.88	23.14	23.22
		3	0	22.86	23.07	23.12
		3	3	22.81	23.07	23.13
		6	0	21.85	22.16	22.23
	16QAM	1	0	22.88	23.09	23.13
		1	5	22.89	23.15	23.11
		3	0	22.86	23.15	23.11
		3	3	22.88	23.12	23.21
		5	0	21.93	22.14	22.20

Band/BW	Modulation	RB Size	RB Offset	Low CH 20425	Mid CH 20525	High CH 20625
				Frequency 826.5 MHz	Frequency 836.5 MHz	Frequency 846.5 MHz
5/ 5	QPSK	1	0	22.91	23.11	23.14
		1	5	22.93	23.15	23.13
		3	0	22.92	23.15	23.26
		3	3	22.82	23.07	23.12
		6	0	21.85	22.07	22.13
	16QAM	1	0	22.84	23.07	23.24
		1	5	22.94	23.10	23.21
		3	0	22.84	23.10	23.12
		3	3	22.92	23.02	23.20
		5	0	21.85	22.02	22.15

Band/BW	Modulation	RB Size	RB Offset	Low CH 20450	Mid CH 20525	High CH 20600
				Frequency 829 MHz	Frequency 836.5 MHz	Frequency 844 MHz
5/ 10	QPSK	1	0	23.00	23.21	23.28
		1	5	22.97	23.20	23.27
		3	0	22.98	23.17	23.27
		3	3	22.95	23.19	23.25
		6	0	21.95	22.20	22.24
	16QAM	1	0	22.98	23.18	23.26
		1	5	22.96	23.19	23.25
		3	0	22.99	23.18	23.23
		3	3	22.94	23.16	23.26
		5	0	21.95	22.15	22.24



LTE BAND 26

Band/BW	Modulation	RB Size	RB Offset	Low CH 26797	Mid CH 26915	High CH 27033
				Frequency 824.7 MHz	Frequency 836.5 MHz	Frequency 848.3 MHz
26/ 1.4	QPSK	1	0	23.51	23.69	23.81
		1	5	23.57	23.63	23.86
		3	0	23.48	23.62	23.85
		3	3	23.45	23.62	23.84
		6	0	22.63	22.67	22.83
	16QAM	1	0	23.55	23.64	23.80
		1	5	23.56	23.65	23.83
		3	0	23.53	23.67	23.80
		3	3	23.46	23.59	23.76
		5	0	22.49	22.67	22.78

Band/BW	Modulation	RB Size	RB Offset	Low CH 26805	Mid CH 26915	High CH 27025
				Frequency 825.5 MHz	Frequency 836.5 MHz	Frequency 847.5 MHz
26/ 3	QPSK	1	0	23.48	23.66	23.81
		1	5	23.52	23.72	23.78
		3	0	23.55	23.63	23.81
		3	3	23.56	23.71	23.77
		6	0	22.49	22.65	22.88
	16QAM	1	0	23.46	23.54	23.77
		1	5	23.57	23.71	23.73
		3	0	23.52	23.65	23.77
		3	3	23.52	23.58	23.82
		5	0	22.56	22.57	22.76

Band/BW	Modulation	RB Size	RB Offset	Low CH 26815	Mid CH 26915	High CH 27015
				Frequency 826.5 MHz	Frequency 836.5 MHz	Frequency 846.5 MHz
26/ 5	QPSK	1	0	23.42	23.56	23.79
		1	5	23.50	23.67	23.78
		3	0	23.42	23.70	23.73
		3	3	23.51	23.76	23.87
		6	0	22.53	22.63	22.81
	16QAM	1	0	23.45	23.63	23.85
		1	5	23.60	23.60	23.87
		3	0	23.51	23.60	23.81
		3	3	23.55	23.64	23.81
		5	0	22.56	22.66	22.85

Band/BW	Modulation	RB Size	RB Offset	Low CH 26840	Mid CH 26915	High CH 26990
				Frequency 829 MHz	Frequency 836.5 MHz	Frequency 844 MHz
26/10	QPSK	1	0	23.43	23.66	23.74
		1	5	23.45	23.62	23.87
		3	0	23.43	23.62	23.80
		3	3	23.53	23.63	23.90
		6	0	22.55	22.70	22.74
	16QAM	1	0	23.47	23.63	23.84
		1	5	23.53	23.62	23.73
		3	0	23.55	23.68	23.75
		3	3	23.57	23.70	23.74
		5	0	22.47	22.66	22.86



Band/BW	Modulation	RB Size	RB Offset	Low CH 26865	Mid CH 26915	High CH 26965
				Frequency 831.5 MHz	Frequency 836.5 MHz	Frequency 841.5 MHz
26/ 15	QPSK	1	0	23.55	23.71	23.89
		1	5	23.59	23.75	23.90
		3	0	23.57	23.73	23.86
		3	3	23.60	23.77	23.92
		6	0	22.64	22.72	22.89
	16QAM	1	0	23.59	23.69	23.87
		1	5	23.61	23.72	23.88
		3	0	23.57	23.70	23.86
		3	3	23.58	23.71	23.89
		5	0	22.60	22.69	22.91

ERP POWER (dBm)

GSM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
128	824.2	32.23	2.8	32.88	1940.89	7
189	836.4	32.34	2.8	32.99	1990.67	7
251	848.8	32.39	2.8	33.04	2013.72	7

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

EDGE

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
128	824.2	26.39	2.8	27.04	505.82	7
189	836.4	26.11	2.8	26.76	474.24	7
251	848.8	26.19	2.8	26.84	483.06	7

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

LTE BAND 5

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20407	824.7	22.96	2.8	23.61	229.61	7
20525	836.5	23.15	2.8	23.8	239.88	7
20643	848.3	23.21	2.8	23.86	243.22	7

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20407	824.7	22.95	2.8	23.6	229.09	7
20525	836.5	23.15	2.8	23.8	239.88	7
20643	848.3	23.21	2.8	23.86	243.22	7

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20415	825.5	22.88	2.8	23.53	225.42	7
20525	836.5	23.17	2.8	23.82	240.99	7
20635	847.5	23.22	2.8	23.87	243.78	7

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20415	825.5	22.89	2.8	23.54	225.94	7
20525	836.5	23.15	2.8	23.8	239.88	7
20635	847.5	23.21	2.8	23.86	243.22	7

**CHANNEL BANDWIDTH: 5MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20425	826.5	22.93	2.8	23.58	228.03	7
20525	836.5	23.15	2.8	23.8	239.88	7
20625	846.5	23.26	2.8	23.91	246.04	7

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20425	826.5	22.94	2.8	23.59	228.56	7
20525	836.5	23.1	2.8	23.75	237.14	7
20625	846.5	23.24	2.8	23.89	244.91	7

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20450	829.0	23	2.8	23.65	231.74	7
20525	836.5	23.21	2.8	23.86	243.22	7
20600	844.0	23.28	2.8	23.93	247.17	7

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
20450	829.0	22.99	2.8	23.64	231.21	7
20525	836.5	23.19	2.8	23.84	242.1	7
20600	844.0	23.26	2.8	23.91	246.04	7

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

LTE BAND 26

CHANNEL BANDWIDTH: 1.4MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26797	824.7	23.57	2.8	24.22	264.24	7
26915	836.5	23.69	2.8	24.34	271.64	7
27033	848.3	23.86	2.8	24.51	282.49	7

CHANNEL BANDWIDTH: 1.4MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26797	824.7	23.56	2.8	24.21	263.63	7
26915	836.5	23.67	2.8	24.32	270.4	7
27033	848.3	23.83	2.8	24.48	280.54	7

CHANNEL BANDWIDTH: 3MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26805	825.5	23.56	2.8	24.21	263.63	7
26915	836.5	23.72	2.8	24.37	273.53	7
27025	847.5	23.81	2.8	24.46	279.25	7

CHANNEL BANDWIDTH: 3MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26805	825.5	23.57	2.8	24.22	264.24	7
26915	836.5	23.71	2.8	24.36	272.9	7
27025	847.5	23.82	2.8	24.47	279.9	7

**CHANNEL BANDWIDTH: 5MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26815	826.5	23.51	2.8	24.16	260.62	7
26915	836.5	23.76	2.8	24.41	276.06	7
27015	846.5	23.87	2.8	24.52	283.14	7

CHANNEL BANDWIDTH: 5MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26815	826.5	23.6	2.8	24.25	266.07	7
26915	836.5	23.64	2.8	24.29	268.53	7
27015	846.5	23.87	2.8	24.52	283.14	7

CHANNEL BANDWIDTH: 10MHz QPSK

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26840	829	23.53	2.8	24.18	261.82	7
26915	836.5	23.66	2.8	24.31	269.77	7
26990	844	23.9	2.8	24.55	285.1	7

CHANNEL BANDWIDTH: 10MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26840	829	23.57	2.8	24.22	264.24	7
26915	836.5	23.7	2.8	24.35	272.27	7
26990	844	23.84	2.8	24.49	281.19	7

**CHANNEL BANDWIDTH: 15MHz QPSK**

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26865	831.5	23.6	2.8	24.25	266.07	7
26915	836.5	23.77	2.8	24.42	276.69	7
26965	841.5	23.92	2.8	24.57	286.42	7

CHANNEL BANDWIDTH: 15MHz 16QAM

Channel	Frequency (MHz)	Conducted Power (dBm)	G _T -L _C (dB)	ERP (dBm)	ERP (mW)	Limit (W)
26865	831.5	23.61	2.8	24.26	266.69	7
26915	836.5	23.72	2.8	24.37	273.53	7
26965	841.5	23.89	2.8	24.54	284.45	7

REMARKS: ERP Output Power (dBm) = EIRP (dBm) -2.15(dB).

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB. The emission limit equal to -13dBm .

3.2.2 TEST PROCEDURES

- a. Substitution method is used for E.I.R.P measurement. In the semi-anechoic chamber, EUT placed on the 0.8m height of Turn Table, rotated the table around 360 degrees to search the maximum radiation power and receiver antenna shall be rotated vertical and horizontal polarization and moved height from 1m to 4m to find the maximum polar radiated power. The "Read Value" is the spectrum reading the maximum power value.
- b. The substitution horn antenna is substituted for EUT at the same position and signals generator export the CW signal to the substitution antenna via a TX cable. Rotated the Turn Table and moved receiving antenna to find the maximum radiation power. Adjust output power level of S.G to get a Value of spectrum reading equal to "Read Value" of step a. Record the power level of S.G
- c. $\text{EIRP} = \text{Output power level of S.G} - \text{TX cable loss} + \text{Antenna gain of substitution horn}$.
- d. E.R.P power can be calculated form E.I.R.P power by subtracting the gain of dipole, $\text{E.R.P power} = \text{E.I.P.R power} - 2.15\text{dBi}$.


NOTE: The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1MHz/3MHz.

3.2.3 DEVIATION FROM TEST STANDARD


No deviation

3.2.4 TEST SETUP


< Frequency Range below 30MHz >



< Frequency Range 30MHz~1GHz >



<Frequency Range above 1GHz>



Note: Above 1G is a directional antenna

Depends on the EUT height and the antenna 3dB beamwidth both, refer to section 7.3 of CISPR 16-2-3.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

3.2.5 TEST RESULTS

NOTE : The 9K~30MHz amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required in the report.

BELOW 1GHz WORST-CASE DATA


30 MHz – 1GHz data:

EDGE 850:

CHANNEL BANDWIDTH: 128 ~ 251


MODE	TX channel 190	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	62.980	-66.22	-53.84	-13.00	-53.22	-12.38	Peak	Horizontal
2	121.180	-61.02	-45.30	-13.00	-48.02	-15.72	Peak	Horizontal
3	191.020	-67.51	-51.70	-13.00	-54.51	-15.81	Peak	Horizontal
4	262.800	-61.75	-51.17	-13.00	-48.75	-10.58	Peak	Horizontal
5 PP	317.120	-56.44	-47.96	-13.00	-43.44	-8.48	Peak	Horizontal
6	448.070	-66.10	-60.10	-13.00	-53.10	-6.00	Peak	Horizontal



MODE	TX channel 190	FREQUENCY RANGE	Below 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	62.980	-55.69	-36.75	-13.00	-42.69	-18.94	Peak	Vertical
2	141.550	-59.96	-45.55	-13.00	-46.96	-14.41	Peak	Vertical
3	168.710	-58.57	-47.62	-13.00	-45.57	-10.95	Peak	Vertical
4	252.130	-60.96	-57.23	-13.00	-47.96	-3.73	Peak	Vertical
5	349.130	-61.19	-57.42	-13.00	-48.19	-3.77	Peak	Vertical
6	449.040	-60.85	-56.17	-13.00	-47.85	-4.68	Peak	Vertical





ABOVE 1GHz DATA


Note: For higher frequency, the emission is too low to be detected.

GPRS 850

CH 128:


MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648.400	-55.51	-59.17	-13.00	-42.51	3.66	Peak	Horizontal
2 PP	2472.000	-54.03	-60.05	-13.00	-41.03	6.02	Peak	Horizontal



MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1648.000	-55.42	-58.81	-13.00	-42.42	3.39	Peak	Vertical
2 PP	2472.600	-53.87	-59.55	-13.00	-40.87	5.68	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-P23120015RF01

CH 190:


MODE	TX channel 190	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1672.800	-55.46	-59.20	-13.00	-42.46	3.74	Peak	Horizontal
2 PP	2512.000	-53.52	-59.67	-13.00	-40.52	6.15	Peak	Horizontal



MODE	TX channel 190	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1672.000	-55.76	-59.19	-13.00	-42.76	3.43	Peak	Vertical
2	PP 2509.200	-52.40	-58.24	-13.00	-39.40	5.84	Peak	Vertical






CH 251:

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHZ
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1696.000	-55.89	-59.70	-13.00	-42.89	3.81	Peak	Horizontal
2 PP	2546.400	-53.20	-59.50	-13.00	-40.20	6.30	Peak	Horizontal






BUREAU
VERITAS

Test Report No.: W7L-P23120015RF01

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1697.600	-55.46	-58.93	-13.00	-42.46	3.47	Peak	Vertical
2 PP	2544.000	-53.56	-59.61	-13.00	-40.56	6.05	Peak	Vertical




EDGE 850:

CH 128:


MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
Freq	Level	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
MHz	dBm/m	dBm	dBm/m	dB	dB/m			
1 PP 1648.000	-27.64	-31.30	-13.00	-14.64	3.66	Peak		Horizontal
2 2472.600	-43.79	-49.82	-13.00	-30.79	6.03	Peak		Horizontal



MODE	TX channel 128	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1648.400	-33.07	-36.46	-13.00	-20.07	3.39	Peak	Vertical
2	2472.000	-49.73	-55.41	-13.00	-36.73	5.68	Peak	Vertical




CH 190:

MODE	TX channel 190	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1672.000	-28.24	-31.97	-13.00	-15.24	3.73	Peak	Horizontal
2	2509.200	-46.51	-52.65	-13.00	-33.51	6.14	Peak	Horizontal




MODE	TX channel 190	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			



CH 251:

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			






BUREAU
VERITAS

Test Report No.: W7L-P23120015RF01

MODE	TX channel 251	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1696.000	-33.70	-37.17	-13.00	-20.70	3.47	Peak	Vertical
2	2544.000	-48.75	-54.80	-13.00	-35.75	6.05	Peak	Vertical






LTE Band 26

CHANNEL BANDWIDTH: 1.4MHz / QPSK

CH26915


MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1673.000	-38.75	-42.49	-13.00	-25.75	3.74	Peak	Horizontal
2	2512.000	-45.67	-51.82	-13.00	-32.67	6.15	Peak	Horizontal



MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1672.000	-41.15	-44.58	-13.00	-28.15	3.43	Peak	Vertical
2	2509.500	-53.63	-59.47	-13.00	-40.63	5.84	Peak	Vertical



CHANNEL BANDWIDTH: 3MHz / QPSK
CH 26805


MODE	TX channel 26805	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase	
MHz	dBm/m	dBm	dBm/m	dB	dB/m			
1 PP 1648.000	-40.96	-44.62	-13.00	-27.96	3.66	Peak	Horizontal	
2 2476.500	-46.70	-52.74	-13.00	-33.70	6.04	Peak	Horizontal	



MODE	TX channel 26805	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1651.000	-41.19	-44.58	-13.00	-28.19	3.39	Peak	Vertical
2		2480.000	-48.74	-54.45	-13.00	-35.74	5.71	Peak	Vertical



CH 26915


MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1672.000	-35.86	-39.59	-13.00	-22.86	3.73	Peak	Horizontal
2		2509.500	-47.13	-53.27	-13.00	-34.13	6.14	Peak	Horizontal



MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1673.000	-40.73	-44.16	-13.00	-27.73	3.43	Peak	Vertical
2		2512.000	-49.08	-54.93	-13.00	-36.08	5.85	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P23120015RF01

CH 27025


MODE	TX channel 27025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1695.000	-36.96	-40.76	-13.00	-23.96	3.80	Peak	Horizontal
2		2544.000	-47.11	-53.40	-13.00	-34.11	6.29	Peak	Horizontal



MODE	TX channel 27025	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	1696.000	-46.34	-49.81	-13.00	-33.34	3.47	Peak	Vertical
2		2542.500	-47.59	-53.63	-13.00	-34.59	6.04	Peak	Vertical






**BUREAU
VERITAS**

Test Report No.: W7L-P23120015RF01

CHANNEL BANDWIDTH: 5MHz / QPSK


MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

			Read	Limit	Over			
	Freq	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	1673.000	-38.88	-42.62	-13.00	-25.88	3.74	Peak	Horizontal
2	2512.000	-46.27	-52.42	-13.00	-33.27	6.15	Peak	Horizontal



MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


			Read	Limit	Over			
Freq	Level	Level	Level	Line	Limit	Factor	Remark	Pol/Phase
MHz	dBm/m	dBm	dBm/m	dB	dB	dB/m		
1 PP 1672.000	-41.82	-45.25	-13.00	-28.82	3.43	Peak	Vertical	
2 2509.500	-51.72	-57.56	-13.00	-38.72	5.84	Peak	Vertical	



CHANNEL BANDWIDTH: 10MHz / QPSK


MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1673.000	-54.48	-58.22	-13.00	-41.48	3.74	Peak	Horizontal
2 PP	2512.000	-53.29	-59.44	-13.00	-40.29	6.15	Peak	Horizontal




MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1672.000	-55.51	-58.94	-13.00	-42.51	3.43	Peak	Vertical
2 PP	2509.500	-54.02	-59.86	-13.00	-41.02	5.84	Peak	Vertical




CHANNEL BANDWIDTH: 15MHz / QPSK

MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			



MODE	TX channel 26915	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	AC 120V/60HZ
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	1673.000	-54.70	-58.13	-13.00	-41.70	3.43	Peak	Vertical
2 PP	2512.000	-54.10	-59.95	-13.00	-41.10	5.85	Peak	Vertical





Test Report No.: W7L-P23120015RF01

4 PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



Test Report No.: W7L-P23120015RF01

5 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.

6 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--END--