

FCC PART 15.247


TEST REPORT

For

MAXWEST INTERNATIONAL LIMITED

No.1, Longgang Road, Buji, Longgang, ShenzhenCity, Guangdong Province, P.R. China

FCC ID: 2AEN3GRAVITY5

Report Type: Original Report	Product Type: Mobile Phone
Test Engineer:	Dean Liu 
Report Number:	RDG150807007-00B
Report Date:	2015-08-17
Reviewed By:	Sula Huang  RF Leader
Test Laboratory:	Bay Area Compliance Laboratories Corp. (Dongguan) No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China Tel: +86-769-86858888 Fax: +86-769-86858891 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Dongguan). This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION	5
EQUIPMENT MODIFICATIONS	5
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS	8
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	9
APPLICABLE STANDARD	9
FCC §15.203 - ANTENNA REQUIREMENT.....	10
APPLICABLE STANDARD	10
ANTENNA CONNECTOR CONSTRUCTION	10
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	11
APPLICABLE STANDARD	11
MEASUREMENT UNCERTAINTY	11
EUT SETUP	11
EMI TEST RECEIVER SETUP.....	12
TEST PROCEDURE	12
CORRECTED AMPLITUDE & MARGIN CALCULATION	12
TEST EQUIPMENT LIST AND DETAILS.....	13
TEST RESULTS SUMMARY	13
TEST DATA	13
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	18
APPLICABLE STANDARD	18
MEASUREMENT UNCERTAINTY	18
EUT SETUP	18
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	19
TEST PROCEDURE	19
CORRECTED AMPLITUDE & MARGIN CALCULATION	20
TEST EQUIPMENT LIST AND DETAILS.....	20
TEST RESULTS SUMMARY	20
TEST DATA	20
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST EQUIPMENT LIST AND DETAILS.....	34
TEST DATA	34
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	43

APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST EQUIPMENT LIST AND DETAILS.....	43
TEST DATA	43
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	46
APPLICABLE STANDARD	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS.....	46
TEST DATA	46
FCC §15.247(e) - POWER SPECTRAL DENSITY	52
APPLICABLE STANDARD	52
TEST PROCEDURE	52
TEST EQUIPMENT LIST AND DETAILS.....	52
TEST DATA	52

FINAL

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The MAXWEST INTERNATIONAL LIMITED's product, model number: Gravity 5 (FCC ID: 2AEN3GRAVITY5) (the "EUT") in this report was a Mobile Phone (named Gravity 5 by applicant), which was measured approximately: 14.6cm (L) x 7.35 cm (W) x 0.85 cm (H), rated input voltage: DC3.7V rechargeable Li-ion battery or DC5.0V charging from adapter.

Adapter information:

CHARGING ADAPTOR

Input: AC100-240V, 50/60 Hz, 0.2A;

Output: DC 5V, 1000mAh

All measurement and test data in this report was gathered from production sample serial number: 150807007 (Assigned by applicant). The EUT was received on 2015-08-10.

Objective

This report is prepared on behalf of MAXWEST INTERNATIONAL LIMITED in accordance with Part 2, Subpart J, Part 15, Subparts A, B and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID:2AEN3GRAVITY5.

FCC Part 15C DSS submissions with FCC ID:2AEN3GRAVITY5.

FCC Part 22H, 24E PCE submissions with FCC ID:2AEN3GRAVITY5.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2009, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed and Bay Area Compliance Laboratories Corp. (Dongguan).

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Dongguan) to collect test data is located on the No.69 Pulongcun, Puxinhu Industrial Zone, Tangxia, Dongguan, Guangdong, China

Test site at Bay Area Compliance Laboratories Corp. (Dongguan) has been fully described in reports submitted to the Federal Communications Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 06, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 273710. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer.
For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11.
For 802.11n ht40 mode were tested with Channel 3, 6 and 9.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power with 100% duty cycle) was setting by the software as following table:

Test Mode	Test Software Version	Engineering Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	10.5	10.5	10
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	10	10	9.5
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	10.5	10.5	10
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	11.5	11.5	11.5
BLE	Test Frequency	2402MHz	2440MHz	2480MHz
	BLE	N/A	N/A	N/A


Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	1.1	USB Port of Adater	EUT
Earphone Cable	No	No	1.2	Audio Port of EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.247(d)	Spurious Emissions at Antenna Port	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE**Applicable Standard**

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v05r02:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

The maximum peak output power = 9.68 dBm (9.29 mW) at 2437 MHz

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 9.29/5 \cdot (\sqrt{2.437}) = 2.90 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one integral antenna arrangement for WiFi/BT, which was permanently attached and the antenna gain is -1.2 dBi, fulfill the requirement of this section. Please refer to the EUT photos.

Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cispr} of Table 1, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cispr} of Table 1, then:


- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cispr})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of conducted disturbance at mains port using AMN at Bay Area Compliance Laboratories Corp. (Dongguan) is 3.46 dB (150 kHz to 30 MHz).

Table 1 – Values of U_{cispr}

Measurement	U_{cispr}
Conducted disturbance at mains port using AMN (150 kHz to 30 MHz)	3.4 dB

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCS 30	830245/006	2014-10-20	2015-10-20
R&S	L.I.S.N	ESH2-Z5	892107/021	2015-06-09	2016-06-09
R&S	Two-line V-network	ENV 216	3560.6550.12	2014-12-11	2015-12-11
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207, with the worst margin reading of:

13.7 dB at 0.604902 MHz in the **Neutral** conducted mode for Wi-Fi.


Test Data**Environmental Conditions**

Temperature:	29.9°C
Relative Humidity:	57 %
ATM Pressure:	99.9 kPa

The testing was performed by Dean Liu on 2015-08-13.


Test Mode: Transmitting (Wi-Fi)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.390261	37.0	9.000	L1	9.8	21.1	58.1	Compliance
0.446873	31.9	9.000	L1	9.8	25.0	56.9	Compliance
0.609741	39.2	9.000	L1	9.8	16.8	56.0	Compliance
0.872708	37.3	9.000	L1	9.8	18.7	56.0	Compliance
1.453260	32.9	9.000	L1	9.8	23.1	56.0	Compliance
1.573796	30.8	9.000	L1	9.8	25.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.319773	25.5	9.000	L1	9.8	24.2	49.7	Compliance
0.354674	28.1	9.000	L1	9.8	20.7	48.9	Compliance
0.422630	26.2	9.000	L1	9.8	21.2	47.4	Compliance
0.634524	16.6	9.000	L1	9.8	29.4	46.0	Compliance
0.845331	26.0	9.000	L1	9.8	20.0	46.0	Compliance
1.407671	18.3	9.000	L1	9.8	27.7	46.0	Compliance


AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.465037	41.1	9.000	N	9.8	15.5	56.6	Compliance
0.604902	42.3	9.000	N	9.8	13.7	56.0	Compliance
0.676289	41.7	9.000	N	9.8	14.3	56.0	Compliance
0.715082	41.8	9.000	N	9.8	14.2	56.0	Compliance
0.750100	41.5	9.000	N	9.8	14.5	56.0	Compliance
0.858911	39.8	9.000	N	9.8	16.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.387164	24.7	9.000	N	9.8	23.5	48.1	Compliance
0.461346	22.1	9.000	N	9.8	24.6	46.7	Compliance
0.604902	29.6	9.000	N	9.8	16.4	46.0	Compliance
1.239175	28.5	9.000	N	9.8	17.5	46.0	Compliance
1.385415	27.8	9.000	N	9.8	18.2	46.0	Compliance
2.344095	8.5	9.000	N	9.8	37.5	46.0	Compliance


Test Mode: Transmitting (BLE)

AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.402900	35.9	9.000	L1	9.8	21.9	57.8	Compliance
0.426011	39.8	9.000	L1	9.8	17.6	57.3	Compliance
0.461346	39.6	9.000	L1	9.8	17.1	56.7	Compliance
0.639600	40.8	9.000	L1	9.8	15.2	56.0	Compliance
0.893821	35.7	9.000	L1	9.8	20.3	56.0	Compliance
1.385415	32.1	9.000	L1	9.8	23.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.426011	29.2	9.000	L1	9.8	18.2	47.3	Compliance
0.495646	30.2	9.000	L1	9.8	15.8	46.1	Compliance
0.567545	29.5	9.000	L1	9.8	16.5	46.0	Compliance
0.604902	31.4	9.000	L1	9.8	14.6	46.0	Compliance
0.639600	14.0	9.000	L1	9.8	32.0	46.0	Compliance
0.676289	28.5	9.000	L1	9.8	17.5	46.0	Compliance

AC120 V, 60 Hz, Neutral:

Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.465037	41.2	9.000	N	9.8	15.4	56.6	Compliance
0.572086	41.4	9.000	N	9.8	14.6	56.0	Compliance
0.604902	41.2	9.000	N	9.8	14.8	56.0	Compliance
0.676289	41.0	9.000	N	9.8	15.0	56.0	Compliance
0.715082	41.8	9.000	N	9.8	14.2	56.0	Compliance
0.750100	41.5	9.000	N	9.8	14.5	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.393383	21.7	9.000	N	9.8	26.3	48.0	Compliance
0.465037	22.3	9.000	N	9.8	24.3	46.6	Compliance
0.499611	28.2	9.000	N	9.8	17.8	46.0	Compliance
0.715082	28.7	9.000	N	9.8	17.3	46.0	Compliance
0.750100	27.0	9.000	N	9.8	19.0	46.0	Compliance
1.289541	28.0	9.000	N	9.8	18.0	46.0	Compliance

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard

FCC §15.247 (d); §15.209; §15.205;

Measurement Uncertainty

Compliance or non-compliance with a disturbance limit shall be determined in the following manner:

If U_{lab} is less than or equal to U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level exceeds the disturbance limit.

If U_{lab} is greater than U_{cisp} of Table 2, then:

- compliance is deemed to occur if no measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit;
- non-compliance is deemed to occur if any measured disturbance level, increased by $(U_{lab} - U_{cisp})$, exceeds the disturbance limit.

Based on CISPR 16-4-2-2011, measurement uncertainty of radiated emission at a distance of 3m at Bay Area Compliance Laboratories Corp. (Dongguan) is:

30M~200MHz: 5.0 dB

200M~1GHz: 6.2 dB

1G~6GHz: 4.45 dB


6G~18GHz: 5.23 dB


Table 2 – Values of U_{cisp}

Measurement	U_{cisp}
Radiated disturbance (electric field strength at an OATS or in a SAC) (30 MHz to 1000 MHz)	6.3 dB
Radiated disturbance (electric field strength in a FAR) (1 GHz to 6 GHz)	5.2 dB
Radiated disturbance (electric field strength in a FAR) (6 GHz to 18 GHz)	5.5 dB

EUT Setup

Below 1GHz:



Above 1GHz:

The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2009. The specification used was the FCC 15.209, and FCC 15.247 limits. The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

During the radiated emission test, the adapter was connected to the first AC floor outlet and the other support equipments were connected to the second AC floor outlet.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	EMI Test Receiver	ESCI	100224	2015-05-09	2016-05-09
Sunol Sciences	Antenna	JB3	A060611-3	2014-07-28	2017-07-27
HP	Amplifier	8447E	2434A02181	2014-09-01	2015-09-01
R&S	Spectrum Analyzer	E4440A	SG43360054	2014-12-04	2015-12-04
ETS LINDGREN	Horn Antenna	3115	000 527 35	2012-09-06	2015-09-06
Mini-Circuit	Amplifier	ZVA-213-S+	054201245	2015-02-19	2016-02-19
R&S	Spectrum Analyzer	FSP 38	100478	2015-05-09	2016-05-09
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-01 1304	2014-06-16	2017-06-15
Quinstar	Amplifier	QLW-18405536-JO	15964001001	2014-09-06	2015-09-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Section 15.205, 15.209 and 15.247, with the worst margin reading of:

8.95 dB at 54.25 MHz in the **Horizontal** polarization for WiFi Mode (802.11g)

Test Data

Environmental Conditions

Temperature:	27.2-27.3 °C
Relative Humidity:	57-59 %
ATM Pressure:	99.9-100.2 kPa

* The testing was performed by Dean Liu on 2015-08-14&2015-08-15.

Test Mode: Transmitting

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	61.47	PK	H	25.67	3.68	0.00	90.82	N/A	N/A
2412	57.28	AV	H	25.67	3.68	0.00	86.63	N/A	N/A
2412	59.71	PK	V	25.67	3.68	0.00	89.06	N/A	N/A
2412	55.86	AV	V	25.67	3.68	0.00	85.21	N/A	N/A
2390	26.93	PK	H	25.61	3.63	0.00	56.17	74.00	17.83
2390	13.55	AV	H	25.61	3.63	0.00	42.79	54.00	11.21
4824	31.61	PK	H	30.64	5.03	27.41	39.87	74.00	34.13
4824	18.31	AV	H	30.64	5.03	27.41	26.57	54.00	27.43
7236	32.66	PK	H	34.17	6.65	25.90	47.58	74.00	26.42
7236	18.78	AV	H	34.17	6.65	25.90	33.70	54.00	20.30
9648	30.5	PK	H	36.06	8.55	27.46	47.65	74.00	26.35
9648	16.14	AV	H	36.06	8.55	27.46	33.29	54.00	20.71
3582	38.6	PK	H	28.98	4.58	27.26	44.90	74.00	29.10
3582	25.82	AV	H	28.98	4.58	27.26	32.12	54.00	21.88
54.25	43.5	QP	H	7.7	0.96	21.41	30.75	40.00	9.25
Middle Channel: 2437 MHz									
2437	61.95	PK	H	25.74	3.75	0.00	91.44	N/A	N/A
2437	57.53	AV	H	25.74	3.75	0.00	87.02	N/A	N/A
2437	59.88	PK	V	25.74	3.75	0.00	89.37	N/A	N/A
2437	56.08	AV	V	25.74	3.75	0.00	85.57	N/A	N/A
4874	32.05	PK	H	30.77	5.14	27.42	40.54	74.00	33.46
4874	18.49	AV	H	30.77	5.14	27.42	26.98	54.00	27.02
7311	32.86	PK	H	34.35	6.74	25.88	48.07	74.00	25.93
7311	18.87	AV	H	34.35	6.74	25.88	34.08	54.00	19.92
9748	30.74	PK	H	36.30	8.61	27.24	48.41	74.00	25.59
9748	16.43	AV	H	36.30	8.61	27.24	34.10	54.00	19.90
3085	33.74	PK	H	27.47	6.78	27.46	40.53	74.00	33.47
3085	20.99	AV	H	27.47	6.78	27.46	27.78	54.00	26.22
3632	38.53	PK	H	29.09	4.57	27.29	44.90	74.00	29.10
3632	26.27	AV	H	29.09	4.57	27.29	32.64	54.00	21.36
54.25	43.4	QP		7.7	0.96	21.41	30.65	40.00	9.35
High Channel: 2462 MHz									
2462	61.84	PK	H	25.80	3.75	0.00	91.39	N/A	N/A
2462	58.01	AV	H	25.80	3.75	0.00	87.56	N/A	N/A
2462	59.62	PK	V	25.80	3.75	0.00	89.17	N/A	N/A
2462	55.82	AV	V	25.80	3.75	0.00	85.37	N/A	N/A
2483.5	26.92	PK	H	25.86	3.67	0.00	56.45	74.00	17.55
2483.5	13.97	AV	H	25.86	3.67	0.00	43.50	54.00	10.50
4924	31.99	PK	H	30.90	5.34	27.43	40.80	74.00	33.20
4924	18.41	AV	H	30.90	5.34	27.43	27.22	54.00	26.78
7386	32.73	PK	H	34.53	6.83	25.86	48.23	74.00	25.77
7386	19.05	AV	H	34.53	6.83	25.86	34.55	54.00	19.45
9848	30.78	PK	H	36.54	8.66	26.94	49.04	74.00	24.96
9848	16.44	AV	H	36.54	8.66	26.94	34.70	54.00	19.30
3683	38.71	PK	H	29.20	4.60	27.32	45.19	74.00	28.81
3683	26.07	AV	H	29.20	4.60	27.32	32.55	54.00	21.45
54.25	43.7	QP	H	7.7	0.96	21.41	30.95	40.00	9.05

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	62.38	PK	H	25.67	3.68	0.00	91.73	N/A	N/A
2412	51.51	AV	H	25.67	3.68	0.00	80.86	N/A	N/A
2412	60.06	PK	V	25.67	3.68	0.00	89.41	N/A	N/A
2412	49.3	AV	V	25.67	3.68	0.00	78.65	N/A	N/A
2390	26.59	PK	H	25.61	3.63	0.00	55.83	74.00	18.17
2390	13.28	AV	H	25.61	3.63	0.00	42.52	54.00	11.48
4824	31.87	PK	H	30.64	5.03	27.41	40.13	74.00	33.87
4824	18.19	AV	H	30.64	5.03	27.41	26.45	54.00	27.55
7236	32.05	PK	H	34.17	6.65	25.90	46.97	74.00	27.03
7236	18.46	AV	H	34.17	6.65	25.90	33.38	54.00	20.62
9648	30.31	PK	H	36.06	8.55	27.46	47.46	74.00	26.54
9648	17.17	AV	H	36.06	8.55	27.46	34.32	54.00	19.68
3582	35.64	PK	H	28.98	4.58	27.26	41.94	74.00	32.06
3582	22.79	AV	H	28.98	4.58	27.26	29.09	54.00	24.91
54.25	43.8	QP	H	7.70	0.96	21.41	31.05	40.00	8.95
Middle Channel: 2437 MHz									
2437	62.9	PK	H	25.74	3.75	0.00	92.39	N/A	N/A
2437	51.68	AV	H	25.74	3.75	0.00	81.17	N/A	N/A
2437	60.25	PK	V	25.74	3.75	0.00	89.74	N/A	N/A
2437	49.5	AV	V	25.74	3.75	0.00	78.99	N/A	N/A
4874	31.94	PK	H	30.77	5.14	27.42	40.43	74.00	33.57
4874	18.66	AV	H	30.77	5.14	27.42	27.15	54.00	26.85
7311	32.36	PK	H	34.35	6.74	25.88	47.57	74.00	26.43
7311	18.74	AV	H	34.35	6.74	25.88	33.95	54.00	20.05
9748	30.78	PK	H	36.30	8.61	27.24	48.45	74.00	25.55
9748	17.62	AV	H	36.30	8.61	27.24	35.29	54.00	18.71
2950	36.17	PK	H	27.07	6.61	27.54	42.31	74.00	31.69
2950	23.26	AV	H	27.07	6.61	27.54	29.40	54.00	24.60
3632	34.31	PK	H	29.09	4.57	27.29	40.68	74.00	33.32
3632	21.19	AV	H	29.09	4.57	27.29	27.56	54.00	26.44
54.25	43.7	QP	H	7.70	0.96	21.41	30.95	40.00	9.05
High Channel: 2462 MHz									
2462	63.55	PK	H	25.80	3.75	0.00	93.10	N/A	N/A
2462	52.19	AV	H	25.80	3.75	0.00	81.74	N/A	N/A
2462	61.3	PK	V	25.80	3.75	0.00	90.85	N/A	N/A
2462	50.04	AV	V	25.80	3.75	0.00	79.59	N/A	N/A
2483.5	27.28	PK	H	25.86	3.67	0.00	56.81	74.00	17.19
2483.5	14.06	AV	H	25.86	3.67	0.00	43.59	54.00	10.41
4924	32.14	PK	H	30.90	5.34	27.43	40.95	74.00	33.05
4924	18.57	AV	H	30.90	5.34	27.43	27.38	54.00	26.62
7386	32.34	PK	H	34.53	6.83	25.86	47.84	74.00	26.16
7386	18.78	AV	H	34.53	6.83	25.86	34.28	54.00	19.72
9848	30.74	PK	H	36.54	8.66	26.94	49.00	74.00	25.00
9848	17.56	AV	H	36.54	8.66	26.94	35.82	54.00	18.18
3683	36.13	PK	H	29.20	4.60	27.32	42.61	74.00	31.39
3683	23.42	AV	H	29.20	4.60	27.32	29.90	54.00	24.10
54.25	43.7	QP	H	7.70	0.96	21.41	30.95	40.00	9.05

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	61.8	PK	H	25.67	3.68	0.00	91.15	N/A	N/A
2412	50.04	AV	H	25.67	3.68	0.00	79.39	N/A	N/A
2412	59.52	PK	V	25.67	3.68	0.00	88.87	N/A	N/A
2412	48.89	AV	V	25.67	3.68	0.00	78.24	N/A	N/A
2390	26.88	PK	H	25.61	3.63	0.00	56.12	74.00	17.88
2390	13.35	AV	H	25.61	3.63	0.00	42.59	54.00	11.41
4824	31.65	PK	H	30.64	5.03	27.41	39.91	74.00	34.09
4824	18.2	AV	H	30.64	5.03	27.41	26.46	54.00	27.54
7236	31.69	PK	H	34.17	6.65	25.90	46.61	74.00	27.39
7236	18.32	AV	H	34.17	6.65	25.90	33.24	54.00	20.76
9648	30.16	PK	H	36.06	8.55	27.46	47.31	74.00	26.69
9648	16.94	AV	H	36.06	8.55	27.46	34.09	54.00	19.91
3582	35.59	PK	H	28.98	4.58	27.26	41.89	74.00	32.11
3582	22.65	AV	H	28.98	4.58	27.26	28.95	54.00	25.05
54.25	43.6	QP	H	7.70	0.96	21.41	30.85	40.00	9.15
Middle Channel: 2437 MHz									
2437	62.11	PK	H	25.74	3.75	0.00	91.60	N/A	N/A
2437	50.33	AV	H	25.74	3.75	0.00	79.82	N/A	N/A
2437	59.89	PK	V	25.74	3.75	0.00	89.38	N/A	N/A
2437	48.99	AV	V	25.74	3.75	0.00	78.48	N/A	N/A
4874	31.88	PK	H	30.77	5.14	27.42	40.37	74.00	33.63
4874	18.2	AV	H	30.77	5.14	27.42	26.69	54.00	27.31
7311	32	PK	H	34.35	6.74	25.88	47.21	74.00	26.79
7311	18.45	AV	H	34.35	6.74	25.88	33.66	54.00	20.34
9748	30.29	PK	H	36.30	8.61	27.24	47.96	74.00	26.04
9748	17.25	AV	H	36.30	8.61	27.24	34.92	54.00	19.08
2005	35.64	PK	H	24.61	3.16	27.48	35.93	74.00	38.07
2005	23.06	AV	H	24.61	3.16	27.48	23.35	54.00	30.65
3632	34.22	PK	H	29.09	4.57	27.29	40.59	74.00	33.41
3632	21.02	AV	H	29.09	4.57	27.29	27.39	54.00	26.61
54.25	43.4	QP	H	7.70	0.96	21.41	30.65	40.00	9.35
High Channel: 2462 MHz									
2462	62.85	PK	H	25.80	3.75	0.00	92.40	N/A	N/A
2462	51.61	AV	H	25.80	3.75	0.00	81.16	N/A	N/A
2462	60.64	PK	V	25.80	3.75	0.00	90.19	N/A	N/A
2462	49.37	AV	V	25.80	3.75	0.00	78.92	N/A	N/A
2483.5	27.68	PK	H	25.86	3.67	0.00	57.21	74.00	16.79
2483.5	13.9	AV	H	25.86	3.67	0.00	43.43	54.00	10.57
4924	32.05	PK	H	30.90	5.34	27.43	40.86	74.00	33.14
4924	18.57	AV	H	30.90	5.34	27.43	27.38	54.00	26.62
7386	32.45	PK	H	34.53	6.83	25.86	47.95	74.00	26.05
7386	18.86	AV	H	34.53	6.83	25.86	34.36	54.00	19.64
9848	30.64	PK	H	36.54	8.66	26.94	48.90	74.00	25.10
9848	17.72	AV	H	36.54	8.66	26.94	35.98	54.00	18.02
3682	36.22	PK	H	29.20	4.60	27.32	42.70	74.00	31.30
3682	23.38	AV	H	29.20	4.60	27.32	29.86	54.00	24.14
54.25	43.7	QP	H	7.70	0.96	21.41	30.95	40.00	9.05

802.11 n ht40 Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	63.02	PK	H	25.70	3.71	0.00	92.43	N/A	N/A
2422	50.92	AV	H	25.70	3.71	0.00	80.33	N/A	N/A
2422	60.51	PK	V	25.70	3.71	0.00	89.92	N/A	N/A
2422	48.3	AV	V	25.70	3.71	0.00	77.71	N/A	N/A
2390	28.08	PK	H	25.61	3.63	0.00	57.32	74.00	16.68
2390	13.77	AV	H	25.61	3.63	0.00	43.01	54.00	10.99
4844	31.41	PK	H	30.69	4.99	27.42	39.67	74.00	34.33
4844	18	AV	H	30.69	4.99	27.42	40.20	54.00	13.80
7266	31.94	PK	H	34.24	6.68	25.89	33.26	74.00	40.74
7266	18.23	AV	H	34.24	6.68	25.89	33.26	54.00	20.74
9688	30.04	PK	H	36.15	8.58	27.37	47.40	74.00	26.60
9688	17.13	AV	H	36.15	8.58	27.37	34.49	54.00	19.51
3582	35.41	PK	H	28.98	4.58	27.26	41.71	74.00	32.29
3582	22.85	AV	H	28.98	4.58	27.26	29.15	54.00	24.85
54.25	43.4	QP	H	7.70	0.96	21.41	30.65	40.00	9.35
Middle Channel: 2437 MHz									
2437	62.89	PK	H	25.74	3.75	0.00	92.38	N/A	N/A
2437	50.45	AV	H	25.74	3.75	0.00	79.94	N/A	N/A
2437	60.13	PK	V	25.74	3.75	0.00	89.62	N/A	N/A
2437	47.77	AV	V	25.74	3.75	0.00	77.26	N/A	N/A
4874	31.51	PK	H	30.77	5.14	27.42	40.00	74.00	34.00
4874	17.98	AV	H	30.77	5.14	27.42	26.47	54.00	27.53
7311	31.92	PK	H	34.35	6.74	25.88	47.13	74.00	26.87
7311	18.28	AV	H	34.35	6.74	25.88	33.49	54.00	20.51
9748	30.17	PK	H	36.30	8.61	27.24	47.84	74.00	26.16
9748	17.08	AV	H	36.30	8.61	27.24	34.75	54.00	19.25
1810	35.59	PK	H	24.22	2.69	27.53	34.97	74.00	39.03
1810	22.77	AV	H	24.22	2.69	27.53	22.15	54.00	31.85
3632	33.8	PK	H	29.09	4.57	27.29	40.17	74.00	33.83
3632	20.88	AV	H	29.09	4.57	27.29	27.25	54.00	26.75
54.25	43.5	QP	H	7.70	0.96	21.41	30.75	40.00	9.25
High Channel: 2452 MHz									
2452	63.54	PK	H	25.78	3.78	0.00	93.10	N/A	N/A
2452	51.25	AV	H	25.78	3.78	0.00	80.81	N/A	N/A
2452	61.06	PK	V	25.78	3.78	0.00	90.62	N/A	N/A
2452	48.87	AV	V	25.78	3.78	0.00	78.43	N/A	N/A
2483.5	27.81	PK	H	25.86	3.67	0.00	57.34	74.00	16.66
2483.5	14.14	AV	H	25.86	3.67	0.00	43.67	54.00	10.33
4904	31.68	PK	H	30.85	5.31	27.43	40.41	74.00	33.59
4904	18.41	AV	H	30.85	5.31	27.43	27.14	54.00	26.86
7356	32.23	PK	H	34.45	6.79	25.87	47.60	74.00	26.40
7356	18.58	AV	H	34.45	6.79	25.87	33.95	54.00	20.05
9808	30.47	PK	H	36.44	8.64	27.09	48.46	74.00	25.54
9808	17.39	AV	H	36.44	8.64	27.09	35.38	54.00	18.62
3683	35.89	PK	H	29.20	4.60	27.32	42.37	74.00	31.63
3683	23.12	AV	H	29.20	4.60	27.32	29.60	54.00	24.40
54.25	43.3	QP	H	7.7	0.96	21.41	30.55	40.00	9.45

BLE Mode


Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector (PK/QP/AV)	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	59.08	PK	H	25.65	3.66	0.00	88.39	N/A	N/A
2402	54.17	AV	H	25.65	3.66	0.00	83.48	N/A	N/A
2402	58.69	PK	V	25.65	3.66	0.00	88.00	N/A	N/A
2402	53.85	AV	V	25.65	3.66	0.00	83.16	N/A	N/A
2390	26.43	PK	H	25.61	3.63	0.00	55.67	74.00	18.33
2390	13.45	AV	H	25.61	3.63	0.00	42.69	54.00	11.31
4804	32.48	PK	H	30.59	5.06	27.41	40.72	74.00	33.28
4804	19.09	AV	H	30.59	5.06	27.41	27.33	54.00	26.67
7206	33.5	PK	H	34.09	6.61	25.91	48.29	74.00	25.71
7206	20.57	AV	H	34.09	6.61	25.91	35.36	54.00	18.64
9608	30.01	PK	H	35.96	8.53	27.55	46.95	74.00	27.05
9608	18.47	AV	H	35.96	8.53	27.55	35.41	54.00	18.59
1960	35.43	PK	H	24.52	3.00	27.49	35.46	74.00	38.54
1960	22.93	AV	H	24.52	3.00	27.49	22.96	54.00	31.04
54.25	43.3	QP	H	7.7	0.96	21.41	30.55	40.00	9.45
Middle Channel: 2440 MHz									
2440	59.39	PK	H	25.74	3.76	0.00	88.89	N/A	N/A
2440	54.5	AV	H	25.74	3.76	0.00	84.00	N/A	N/A
2440	58.07	PK	V	25.74	3.76	0.00	87.57	N/A	N/A
2440	52.86	AV	V	25.74	3.76	0.00	82.36	N/A	N/A
4880	32.41	PK	H	30.79	5.18	27.42	40.96	74.00	33.04
4880	19.24	AV	H	30.79	5.18	27.42	27.79	54.00	26.21
7320	33.78	PK	H	34.37	6.75	25.88	49.02	74.00	24.98
7320	20.86	AV	H	34.37	6.75	25.88	36.10	54.00	17.90
9760	30.15	PK	H	36.32	8.62	27.21	47.88	74.00	26.12
9760	18.7	AV	H	36.32	8.62	27.21	36.43	54.00	17.57
1960	35.57	PK	H	24.52	3.00	27.49	35.60	74.00	38.40
1960	23.2	AV	H	24.52	3.00	27.49	23.23	54.00	30.77
3115	33.15	PK	H	27.57	6.88	27.44	40.16	74.00	33.84
3115	21.16	AV	H	27.57	6.88	27.44	28.17	54.00	25.83
54.25	43.4	QP	H	7.7	0.96	21.41	30.65	40.00	9.35
High Channel: 2480 MHz									
2480	59.4	PK	H	25.85	3.68	0.00	88.93	N/A	N/A
2480	54.57	AV	H	25.85	3.68	0.00	84.10	N/A	N/A
2480	58.43	PK	V	25.85	3.68	0.00	87.96	N/A	N/A
2480	53.29	AV	V	25.85	3.68	0.00	82.82	N/A	N/A
2483.5	27.08	PK	H	25.86	3.67	0.00	56.61	74.00	17.39
2483.5	14.32	AV	H	25.86	3.67	0.00	43.85	54.00	10.15
4960	32.58	PK	H	31.00	5.34	27.43	41.49	74.00	32.51
4960	19.22	AV	H	31.00	5.34	27.43	28.13	54.00	25.87
7440	33.72	PK	H	34.66	6.89	25.97	49.30	74.00	24.70
7440	20.88	AV	H	34.66	6.89	25.97	36.46	54.00	17.54
9920	30.18	PK	H	36.71	8.71	26.66	48.94	74.00	25.06
9920	18.71	AV	H	36.71	8.71	26.66	37.47	54.00	16.53
1960	35.55	PK	H	24.52	3.00	27.49	35.58	74.00	38.42
1960	23.14	AV	H	24.52	3.00	27.49	23.17	54.00	30.83
54.25	43.6	QP	H	7.7	0.96	21.41	30.85	40.00	9.15

Conducted Spurious Emissions at Antenna Port


802.11b Low Channel




802.11b Middle Channel




802.11b High Channel




802.11g Low Channel



802.11g Middle Channel




802.11g High Channel




802.11n ht20 Low Channel

Fundamental




802.11n ht20 Middle Channel


Fundamental




802.11n ht20 High Channel




802.11n ht40 Low Channel




802.11n ht40 Middle Channel




802.11n ht40 High Channel




BLE Low Channel



BLE Middle Channel



BLE High Channel



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

- Set RBW = 100 kHz.
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Allow the trace to stabilize.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.2-27.3 °C
Relative Humidity:	48-50 %
ATM Pressure:	99.8-100 kPa


* The testing was performed by Dean Liu from 2015-08-12&2015-08-14.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	10.08	≥ 0.5
	Middle	2437	10.08	≥ 0.5
	High	2462	10.08	≥ 0.5
802.11g	Low	2412	16.64	≥ 0.5
	Middle	2437	16.64	≥ 0.5
	High	2462	16.64	≥ 0.5
802.11n20	Low	2412	17.92	≥ 0.5
	Middle	2437	17.84	≥ 0.5
	High	2462	17.92	≥ 0.5
802.11n40	Low	2422	36.64	≥ 0.5
	Middle	2437	36.64	≥ 0.5
	High	2452	36.64	≥ 0.5
BLE	Low	2402	0.684	≥ 0.5
	Middle	2440	0.708	≥ 0.5
	High	2480	0.676	≥ 0.5

802.11b Low Channel




Date: 12.AUG.2015 16:31:39

802.11b Middle Channel




Date: 12.AUG.2015 16:35:22

802.11b High Channel




Date: 12.AUG.2015 16:37:50

802.11g Low Channel




Date: 12.AUG.2015 16:40:46

802.11g Middle Channel




Date: 12.AUG.2015 16:43:51

802.11g High Channel




Date: 12.AUG.2015 16:48:51

802.11n ht20 Low Channel




Date: 12.AUG.2015 16:59:56

802.11n ht20 Middle Channel




Date: 12.AUG.2015 17:04:22

802.11n ht20 High Channel




Date: 12.AUG.2015 17:27:03

802.11n ht40 Low Channel




Date: 12.AUG.2015 17:29:10


802.11n ht40 Middle Channel



Date: 12.AUG.2015 17:37:52


802.11n ht40 High Channel

Date: 12.AUG.2015 17:40:26

BLE Low Channel


Date: 12.AUG.2015 19:19:28

BLE Middle Channel



Date: 14.AUG.2015 16:28:29

BLE High Channel



Date: 12.AUG.2015 19:21:34

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54210016	2014-11-03	2015-11-03
Agilent	Wideband Power Sensor	N1921A	MY54170013	2014-11-03	2015-11-03
Agilent	P-Series Power Meter	N1912A	MY5000448	2014-11-03	2015-11-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	27.3 °C
Relative Humidity:	48 %
ATM Pressure:	9.9 kPa

* The testing was performed by Dean Liu on 2015-08-13.

Test Mode: Transmitting (Wi-Fi)

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	10.23	30	PASS
	Middle	2437	10.61	30	PASS
	High	2462	10.59	30	PASS
802.11g	Low	2412	12.74	30	PASS
	Middle	2437	12.49	30	PASS
	High	2462	12.19	30	PASS
802.11n20	Low	2412	12.69	30	PASS
	Middle	2437	12.93	30	PASS
	High	2462	12.48	30	PASS
802.11n40	Low	2422	14.96	30	PASS
	Middle	2437	14.98	30	PASS
	High	2452	15.22	30	PASS

Test mode	Channel	Frequency	Max Conducted Average Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
802.11b	Low	2412	9.26	30	PASS
	Middle	2437	9.68	30	PASS
	High	2462	9.55	30	PASS
802.11g	Low	2412	9.23	30	PASS
	Middle	2437	9.02	30	PASS
	High	2462	8.76	30	PASS
802.11n20	Low	2412	9.15	30	PASS
	Middle	2437	9.48	30	PASS
	High	2462	9.09	30	PASS
802.11n40	Low	2422	8.79	30	PASS
	Middle	2437	8.73	30	PASS
	High	2452	9.07	30	PASS

Test Mode: Transmitting (BLE)

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency	Max Peak Conducted Output Power	Limit	Result
		(MHz)	(dBm)	(dBm)	
BLE	Low	2402	-10.63	30	PASS
	Middle	2440	-10.55	30	PASS
	High	2480	-10.81	30	PASS

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions


Temperature:	27.5~28.3°C
Relative Humidity:	53~56%
ATM Pressure:	100.2~100.4 kPa

* The testing was performed by Dean Liu on 2015-08-12 and 2015-08-18.

Test mode: Transmitting


Test Result: Compliant. Please refer to following plots.

802.11b: Band Edge, Left Side




Date: 12.AUG.2015 16:33:27

802.11b: Band Edge, Right Side




Date: 12.AUG.2015 16:39:40

802.11g: Band Edge, Left Side




Date: 12.AUG.2015 16:42:56

802.11g: Band Edge, Right Side




Date: 12.AUG.2015 16:48:08

802.11n ht20 Band Edge, Left Side




Date: 12.AUG.2015 16:54:00

802.11n ht20 Band Edge, Right Side




Date: 12.AUG.2015 17:28:15

802.11n ht40 Band Edge, Left Side




Date: 12.AUG.2015 17:31:19

802.11n ht40 Band Edge, Right Side




Date: 12.AUG.2015 17:43:07

BLE Band Edge , Left Side



Date: 12.AUG.2015 19:20:28

BLE Band Edge, Right Side



Date: 18.AUG.2015 21:38:13

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to KDB 558074 D01 DTS Meas Guidance v03r03

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- Set the VBW $\geq 3 \times \text{RBW}$.
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
R&S	Spectrum Analyzer	FSEM	DE31388	2015-05-09	2016-05-09

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Dongguan) attests that all calibrations have been performed, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	30.3 °C
Relative Humidity:	53%
ATM Pressure:	100.2 kPa


* The testing was performed by Dean Liu on 2015-08-12.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-21.87	≤ 8
	Middle	2437	-21.65	≤ 8
	High	2462	-21.66	≤ 8
802.11g	Low	2412	-21.98	≤ 8
	Middle	2437	-22.02	≤ 8
	High	2462	-22.25	≤ 8
802.11n20	Low	2412	-21.33	≤ 8
	Middle	2437	-21.67	≤ 8
	High	2462	-21.94	≤ 8
802.11n40	Low	2422	-22.82	≤ 8
	Middle	2437	-22.73	≤ 8
	High	2452	-22.23	≤ 8
BLE	Low	2402	-25.76	≤ 8
	Middle	2440	-25.76	≤ 8
	High	2480	-25.88	≤ 8

Power Spectral Density, 802.11b Low Channel




Date: 12.AUG.2015 16:33:04

Power Spectral Density, 802.11b Middle Channel




Date: 12.AUG.2015 16:36:46

Power Spectral Density, 802.11b High Channel




Date: 12.AUG.2015 16:39:12

Power Spectral Density, 802.11g Low Channel




Date: 12.AUG.2015 16:42:26

Power Spectral Density, 802.11g Middle Channel




Date: 12.AUG.2015 16:45:21

Power Spectral Density, 802.11g High Channel




Date: 12.AUG.2015 16:50:17

Power Spectral Density, 802.11n ht20 Low Channel




Date: 12.AUG.2015 17:01:29

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 12.AUG.2015 17:05:51

Power Spectral Density, 802.11n ht20 High Channel




Date: 12.AUG.2015 17:27:54

Power Spectral Density, 802.11n ht40 Low Channel




Date: 12.AUG.2015 17:30:55

Power Spectral Density, 802.11n ht40 Middle Channel




Date: 12.AUG.2015 17:39:25

Power Spectral Density, 802.11n ht40 High Channel




Date: 12.AUG.2015 17:42:44

Power Spectral Density, BLE Low Channel




Date: 12.AUG.2015 19:20:07

Power Spectral Density, BLE Middle Channel



Date: 14.AUG.2015 16:40:38

Power Spectral Density, BLE High Channel



Date: 12.AUG.2015 19:22:15

***** END OF REPORT *****