



FCC PART 15.247

TEST REPORT

For

MAXWEST INTERNATIONAL LIMITED.

No.1, Longgang Road, Buji, Longgang, Shenzhen City, Guangdong Province, P.R. China

FCC ID: 2AEN3NITRO7LTE

Report Type: Original Report	Product Name: Tablet
Test Engineer: <u>Kevin Hu</u> 	
Report Number: <u>RDG170426001C</u>	
Report Date: <u>2017-05-24</u>	
Reviewed By: <u>Henry Ding</u>  EMC Leader	
Test Laboratory: Bay Area Compliance Laboratories Corp. (Chengdu) No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China Tel: 028-65523123, Fax: 028-65525125 www.baclcorp.com	

Note: This test report was prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. (Chengdu). Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. This report was valid only with a valid digital signature.

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S)	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
EXTERNAL CABLE	10
BLOCK DIAGRAM OF TEST SETUP	11
SUMMARY OF TEST RESULTS	12
FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE	13
APPLICABLE STANDARD	13
FCC §15.203 - ANTENNA REQUIREMENT	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP	15
TEST PROCEDURE	15
CORRECTED AMPLITUDE & MARGIN CALCULATION	16
TEST EQUIPMENT LIST AND DETAILS	16
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
CORRECTED AMPLITUDE & MARGIN CALCULATION	21
TEST EQUIPMENT LIST AND DETAILS	22
TEST DATA	22
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH	28
APPLICABLE STANDARD	28
TEST PROCEDURE	28
TEST EQUIPMENT LIST AND DETAILS	28
TEST DATA	28
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER	37
APPLICABLE STANDARD	37
TEST PROCEDURE	37
TEST EQUIPMENT LIST AND DETAILS	37
TEST DATA	38
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE	39

APPLICABLE STANDARD.....	39
TEST PROCEDURE	39
TEST EQUIPMENT LIST AND DETAILS	39
TEST DATA	40
FCC §15.247(e) - POWER SPECTRAL DENSITY	46
APPLICABLE STANDARD.....	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS	46
TEST DATA	46

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The **MAXWEST INTERNATIONAL LIMITED.**'s product, model number: **Nitro Phablet 7 LTE (FCC ID: 2AEN3NITRO7LTE)** (the "EUT") in this report was a **Tablet**, which was measured approximately: 19.6 cm (L) × 11.3 cm (W) × 2.1 cm (H), rated input voltage: DC3.7V battery or DC5V from adapter.

Adapter information:

Input: 100-240V/AC 0.3A 50/60Hz

Output: DC5V 2000mA

**All measurement and test data in this report was gathered from final production sample, serial number: 170426001 (assigned by the BACL, Chengdu). It may have deviation from any other sample. The EUT supplied by the applicant was received on 2017-05-02, and EUT conformed to test requirement.*

Objective

This report is prepared on behalf of **MAXWEST INTERNATIONAL LIMITED.** in accordance with Part 2, Subpart J, Part 15, Subparts A, and C of the Federal Communications Commission's rules

The tests were performed in order to determine the compliance of the EUT with FCC Rules Part 15-Subpart C, section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP submissions with FCC ID: 2AEN3NITRO7LTE.

FCC Part 15C DSS submissions with FCC ID: 2AEN3NITRO7LTE.

FCC Part 22H, 24E, 27 PCE submissions with FCC ID: 2AEN3NITRO7LTE.

Test Methodology

All measurements detailed in this Test Report were performed in accordance with ANSI C63.10-2013 "American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices".

All of the measurements detailed in this Test Report were performed by Bay Area Compliance Laboratories Corp. (Chengdu).

The Bay Area Compliance Laboratories Corp. Chengdu's measurement Uncertainties (calculated for a k=2 Coverage Factor corresponding to approximately 95% Coverage) were as follows:

- For all of the AC Line Conducted Emissions Tests reported herein: ± 3.17 dB.
- For of all of the Direct Antenna Conducted Emissions Tests reported herein: ± 0.56 dB.
- For of all of the direct Radiated Emissions Tests reported herein are:
 - 30 MHz to 200 MHz: ± 4.7 dB;
 - 200 MHz to 1 GHz: ± 6.0 dB;
 - 1 GHz to 6 GHz: ± 5.13 dB; and,
 - 6 GHz to 40 GHz: ± 5.47 dB.

And the uncertainty will not be taken into consideration for all test data recorded in the report.

Test Facility

The test site used by BACL to collect test data is located in the No.5040, Huilongwan Plaza, No.1, Shawan Road, Jinniu District, Chengdu, Sichuan, China.

Test site at BACL has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on April 24, 2015. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 560332. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in testing mode, which was provided by manufacturer. For 2.4GHz band, 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

For 802.11b, 802.11g, and 802.11n ht20 modes were tested with channel 1, 6 and 11. For 802.11n ht40 mode was tested with channel 3, 6, 9.

The worst-case data rates are determined to be as follows for each mode based upon investigations by measuring the average power and PSD across all data rates bandwidths, and modulations.

For Bluetooth LE mode, 40 channels are provided for testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	...	...
...	...	...	...
...	...	...	...
..	...	38	2478
19	2440	39	2480

EUT was tested with channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

The worst condition (maximum power) was setting by the Engineer Mode as following table:


Test Mode	Test Software Version	Engineer Mode		
802.11b	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	1Mbps	1Mbps	1Mbps
	Power Level Setting	16	15.5	15.5
802.11g	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	6Mbps	6Mbps	6Mbps
	Power Level Setting	16	15.5	15.5
802.11n ht20	Test Frequency	2412MHz	2437MHz	2462MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	16.5	16	16
802.11n ht40	Test Frequency	2422MHz	2437MHz	2452MHz
	Data Rate	MCS0	MCS0	MCS0
	Power Level Setting	16.5	15.5	16

Note: BLE mode configured as maximum power by the system default setting.

The maximum duty cycle as following table:


Test mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
802.11b	100	100	100%
802.11g	100	100	100%
802.11n ht20	100	100	100%
802.11n ht40	100	100	100%
BLE	0.402	0.63	63.81%

802.11b




Date: 9.MAY.2017 10:47:45

802.11g




Date: 9.MAY.2017 10:46:54

802.11n ht20




Date: 9.MAY.2017 10:46:18

802.11n ht40



Date: 9.MAY.2017 10:45:35

BLE




Date: 9.MAY.2017 10:50:25

External Cable

Cable Description	Shielding Type	Ferrite Core	Length (m)	From Port	To
USB Cable	Yes	No	0.9	USB Port of PC	EUT
Earphone	no	no	1.2	EUT	Earphone

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i) & §1.1310 & §2.1093	RF Exposure	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum conducted output power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

FCC §15.247 (i) & §1.1310 & §2.1093- RF EXPOSURE

Applicable Standard

According to §15.247(i) and §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB447498 D01 General RF Exposure Guidance v06:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Measurement Result

For WiFi mode

The max tune-up conducted power is 9.4 dBm (8.71 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 8.71/5 \cdot (\sqrt{2.462}) = 2.7 \leq 3.0$

For bluetooth LE mode

The max tune-up conducted power is -2.7 dBm (0.54 mW).

$[(\text{max. power of channel, mW})/(\text{min. test separation distance, mm})][\sqrt{f(\text{GHz})}]$
 $= 0.54/5 \cdot (\sqrt{2.48}) = 0.2 < 3.0$

So the stand-alone SAR evaluation is not necessary.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

Antenna Connector Construction

The EUT has one internal antenna arrangement for Wifi/BT, and the antenna gain is 1.0dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

The adapter was connected to a 120 V/60 Hz AC power source

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the first LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Amplitude & Margin Calculation

The basic equation is as follows:

$$V_C = V_R + A_C + VDF$$

$$C_f = A_C + VDF$$

Herein,

V_C (cord. Reading): corrected voltage amplitude

V_R : reading voltage amplitude

A_C : attenuation caused by cable loss

VDF: voltage division factor of AMN

C_f : Correction Factor

The “**Margin**” column of the following data tables indicates the degree of compliance within the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS 30	836858/0016	2016-12-02	2017-12-01
Rohde & Schwarz	L.I.S.N.	ENV216	100018	2016-12-02	2017-12-01
SOLAR ELECTRONICS	L.I.S.N.	9252-50-24-BNC	984413	2016-12-02	2017-12-01
Rohde & Schwarz	PULSE LIMITER	ESH3Z2	DE14781	2016-10-31	2017-10-30
Unknown	Conducted Cable	Unknown	NO.5	2016-11-10	2017-11-09
R&S	Test Software	EMC32	Version8.53.0	N/A	N/A

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	47.9 %
ATM Pressure:	100.4 kPa

The testing was performed by Kevin Hu on 2017-05-05.

Test Mode: Transmitting (Wi-Fi b mode was the worst)


AC120 V, 60 Hz, Line:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.665597	33.6	9.000	L1	19.7	22.4	56.0	Compliance
0.709407	33.8	9.000	L1	19.7	22.2	56.0	Compliance
0.812315	34.5	9.000	L1	19.7	21.5	56.0	Compliance
0.838622	37.3	9.000	L1	19.7	18.7	56.0	Compliance
0.858911	34.7	9.000	L1	19.7	21.3	56.0	Compliance
0.908180	34.1	9.000	L1	19.7	21.9	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.660314	22.2	9.000	L1	19.7	23.8	46.0	Compliance
0.805868	19.8	9.000	L1	19.7	26.2	46.0	Compliance
0.838622	23.6	9.000	L1	19.7	22.4	46.0	Compliance
1.190776	26.6	9.000	L1	19.7	19.4	46.0	Compliance
1.239175	28.8	9.000	L1	19.7	17.2	46.0	Compliance
1.289541	27.8	9.000	L1	19.7	18.2	46.0	Compliance

AC120 V, 60 Hz, Neutral:



Frequency (MHz)	QuasiPeak (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.799472	33.6	9.000	N	19.6	22.4	56.0	Compliance
0.825364	35.3	9.000	N	19.6	20.7	56.0	Compliance
0.865782	35.2	9.000	N	19.6	20.8	56.0	Compliance
1.007300	35.2	9.000	N	19.7	20.8	56.0	Compliance
1.239175	37.0	9.000	N	19.6	19.0	56.0	Compliance
3.575883	32.8	9.000	N	19.7	23.2	56.0	Compliance

Frequency (MHz)	Average (dBμV)	Bandwidth (kHz)	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)	Comment
0.629488	25.1	9.000	N	19.6	20.9	46.0	Compliance
0.670921	25.7	9.000	N	19.6	20.3	46.0	Compliance
0.687153	22.1	9.000	N	19.6	23.9	46.0	Compliance
0.922769	23.1	9.000	N	19.7	22.9	46.0	Compliance
1.239175	31.3	9.000	N	19.6	14.7	46.0	Compliance
1.289541	30.3	9.000	N	19.6	15.7	46.0	Compliance


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

30MHz-1000MHz:

Detector	RBW	Video B/W	IF B/W
QP	120 kHz	300 kHz	120kHz

1GHz- 25GHz:

Detector	Duty cycle	RBW	Video B/W
PK	Any	1MHz	3 MHz
Ave.	>98%	1MHz	10 Hz
	<98%	1MHz	1/T

Note: T is minimum transmission duration

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Loss and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Loss} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Amplifier	8447D	2944A10442	2016-12-02	2017-12-01
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Sunol Sciences	Broadband Antenna	JB3	A121808	2016-04-10	2019-04-09
Rohde & Schwarz	Spectrum Analyzer	FSEM30	100018	2016-12-02	2017-12-01
ETS	Horn Antenna	3115	003-6076	2016-12-02	2017-12-01
Ducommun Technologies	Horn Antenna	ARH-4223-02	1007726-0113024	2014-06-16	2017-06-15
Mini-circuits	Amplifier	ZVA-183-S+	771001215	2016-05-20	2017-05-19
HP	Amplifier	8449B	3008A00277	2016-12-02	2017-12-01
EMCT	Semi-Anechoic Chamber	966	966-1	2015-04-24	2018-04-23
Unknown	RF Cable (below 1GHz)	Unknown	NO.1	2016-11-10	2017-11-09
Unknown	RF Cable (below 1GHz)	Unknown	NO.4	2016-11-10	2017-11-09
Unknown	RF Cable (above 1GHz)	Unknown	NO.2	2016-11-10	2017-11-09

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26.3 °C
Relative Humidity:	56 %
ATM Pressure:	100.1 kPa

* The testing was performed by Kevin Hu on 2017-05-10.

Test Mode: Transmitting

30MHz-25GHz:

802.11b Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	73.8	PK	H	23.50	3.00	0.00	100.30	N/A	N/A
2412	70.12	AV	H	23.50	3.00	0.00	96.62	N/A	N/A
2412	72.04	PK	V	23.50	3.00	0.00	98.54	N/A	N/A
2412	67.31	AV	V	23.50	3.00	0.00	93.81	N/A	N/A
2390	28.52	PK	H	23.57	3.00	0.00	55.09	74.00	18.91
2390	15.56	AV	H	23.57	3.00	0.00	42.13	54.00	11.87
4824	49.46	PK	H	30.84	5.11	26.87	58.54	74.00	15.46
4824	36.82	AV	H	30.84	5.11	26.87	45.90	54.00	8.10
7236	35.42	PK	H	34.77	6.18	26.36	50.01	74.00	23.99
7236	24.05	AV	H	34.77	6.18	26.36	38.64	54.00	15.36
1545	40.77	PK	H	24.17	2.70	26.37	41.27	74.00	32.73
1545	29.08	AV	H	24.17	2.70	26.37	29.58	54.00	24.42
86.26	34.6	QP	H	8.40	0.64	28.36	15.28	40.00	24.72
41.64	35	QP	H	13.90	0.32	28.52	20.70	40.00	19.30
Middle Channel: 2437 MHz									
2437	74.03	PK	H	23.41	3.00	0.00	100.44	N/A	N/A
2437	69.79	AV	H	23.41	3.00	0.00	96.20	N/A	N/A
2437	73.06	PK	V	23.41	3.00	0.00	99.47	N/A	N/A
2437	68.22	AV	V	23.41	3.00	0.00	94.63	N/A	N/A
4874	48.71	PK	H	31.00	5.09	26.87	57.93	74.00	16.07
4874	36.64	AV	H	31.00	5.09	26.87	45.86	54.00	8.14
7311	35.54	PK	H	34.92	6.21	26.40	50.27	74.00	23.73
7311	24.15	AV	H	34.92	6.21	26.40	38.88	54.00	15.12
1573	40.95	PK	H	24.22	2.73	26.40	41.50	74.00	32.50
1573	29.54	AV	H	24.22	2.73	26.40	30.09	54.00	23.91
2117	42.67	PK	H	24.50	3.04	26.84	43.37	74.00	30.63
2117	31.12	AV	H	24.50	3.04	26.84	31.82	54.00	22.18
86.26	34.9	QP	H	8.40	0.64	28.36	15.58	40.00	24.42
41.64	35.2	QP	H	13.90	0.32	28.52	20.90	40.00	19.10
High Channel: 2462 MHz									
2462	74.50	PK	H	23.33	2.99	0.00	100.82	N/A	N/A
2462	70.16	AV	H	23.33	2.99	0.00	96.48	N/A	N/A
2462	73.44	PK	V	23.33	2.99	0.00	99.76	N/A	N/A
2462	68.01	AV	V	23.33	2.99	0.00	94.33	N/A	N/A
2483.5	31.03	PK	H	23.26	2.99	0.00	57.28	74.00	16.72
2483.5	18.17	AV	H	23.26	2.99	0.00	44.42	54.00	9.58
4924	49.37	PK	H	31.16	5.07	26.88	58.72	74.00	15.28
4924	37.96	AV	H	31.16	5.07	26.88	47.31	54.00	6.69
7386	35.44	PK	H	35.07	6.25	26.43	50.33	74.00	23.67
7386	23.98	AV	H	35.07	6.25	26.43	38.87	54.00	15.13
1635	40.90	PK	H	24.32	2.77	26.46	41.53	74.00	32.47
1635	28.77	AV	H	24.32	2.77	26.46	29.40	54.00	24.60
86.26	34.9	QP	H	8.40	0.64	28.36	15.58	40.00	24.42
41.64	34.8	QP	H	13.90	0.32	28.52	20.50	40.00	19.50

802.11g Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	72.71	PK	H	23.50	3.00	0.00	99.21	N/A	N/A
2412	62.97	AV	H	23.50	3.00	0.00	89.47	N/A	N/A
2412	70.85	PK	V	23.50	3.00	0.00	97.35	N/A	N/A
2412	60.63	AV	V	23.50	3.00	0.00	87.13	N/A	N/A
2390	31.82	PK	H	23.57	3.00	0.00	58.39	74.00	15.61
2390	17.43	AV	H	23.57	3.00	0.00	44.00	54.00	10.00
4824	49.01	PK	H	30.84	5.11	26.87	58.09	74.00	15.91
4824	36.66	AV	H	30.84	5.11	26.87	45.74	54.00	8.26
7236	35.03	PK	H	34.77	6.18	26.36	49.62	74.00	24.38
7236	23.42	AV	H	34.77	6.18	26.36	38.01	54.00	15.99
3475	34.43	PK	H	26.86	4.14	26.58	38.85	74.00	35.15
3475	22.66	AV	H	26.86	4.14	26.58	27.08	54.00	26.92
86.26	35	QP	H	8.40	0.64	28.36	15.68	40.00	24.32
41.64	34.9	QP	H	13.90	0.32	28.52	20.60	40.00	19.40
Middle Channel: 2437 MHz									
2437	75.03	PK	H	23.41	3.00	0.00	101.44	N/A	N/A
2437	64.11	AV	H	23.41	3.00	0.00	90.52	N/A	N/A
2437	72.82	PK	V	23.41	3.00	0.00	99.23	N/A	N/A
2437	62.86	AV	V	23.41	3.00	0.00	89.27	N/A	N/A
4874	48.57	PK	H	31.00	5.09	26.87	57.79	74.00	16.21
4874	37.28	AV	H	31.00	5.09	26.87	46.50	54.00	7.50
7311	35.12	PK	H	34.92	6.21	26.40	49.85	74.00	24.15
7311	24.79	AV	H	34.92	6.21	26.40	39.52	54.00	14.48
3475	34.55	PK	H	26.86	4.14	26.58	38.97	74.00	35.03
3475	22.27	AV	H	26.86	4.14	26.58	26.69	54.00	27.31
3747	36.26	PK	H	27.99	4.55	26.57	42.23	74.00	31.77
3747	23.62	AV	H	27.99	4.55	26.57	29.59	54.00	24.41
86.26	34.7	QP	H	8.40	0.64	28.36	15.38	40.00	24.62
41.64	35.1	QP	H	13.90	0.32	28.52	20.80	40.00	19.20
High Channel: 2462 MHz									
2462	74.5	PK	H	23.33	2.99	0.00	100.82	N/A	N/A
2462	64.34	AV	H	23.33	2.99	0.00	90.66	N/A	N/A
2462	72.93	PK	V	23.33	2.99	0.00	99.25	N/A	N/A
2462	62.45	AV	V	23.33	2.99	0.00	88.77	N/A	N/A
2483.5	37.99	PK	H	23.26	2.99	0.00	64.24	74.00	9.76
2483.5	18.83	AV	H	23.26	2.99	0.00	45.08	54.00	8.92
4924	48.31	PK	H	31.16	5.07	26.88	57.66	74.00	16.34
4924	36.67	AV	H	31.16	5.07	26.88	46.02	54.00	7.98
7386	35.49	PK	H	35.07	6.25	26.43	50.38	74.00	23.62
7386	24.03	AV	H	35.07	6.25	26.43	38.92	54.00	15.08
3475	34.09	PK	H	26.86	4.14	26.58	38.51	74.00	35.49
3475	22.53	AV	H	26.86	4.14	26.58	26.95	54.00	27.05
86.26	35	QP	H	8.40	0.64	28.36	15.68	40.00	24.32
41.64	34.7	QP	H	13.90	0.32	28.52	20.40	40.00	19.60

802.11 n ht20 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2412 MHz									
2412	72.66	PK	H	23.50	3.00	0.00	99.16	N/A	N/A
2412	62.1	AV	H	23.50	3.00	0.00	88.60	N/A	N/A
2412	71.02	PK	V	23.50	3.00	0.00	97.52	N/A	N/A
2412	59.87	AV	V	23.50	3.00	0.00	86.37	N/A	N/A
2390	32.4	PK	H	23.57	3.00	0.00	58.97	74.00	15.03
2390	18.17	AV	H	23.57	3.00	0.00	44.74	54.00	9.26
4824	49.83	PK	H	30.84	5.11	26.87	58.91	74.00	15.09
4824	37.43	AV	H	30.84	5.11	26.87	46.51	54.00	7.49
7236	35.27	PK	H	34.77	6.18	26.36	49.86	74.00	24.14
7236	24.74	AV	H	34.77	6.18	26.36	39.33	54.00	14.67
3475	34.27	PK	H	26.86	4.14	26.58	38.69	74.00	35.31
3475	21.86	AV	H	26.86	4.14	26.58	26.28	54.00	27.72
86.26	35	QP	H	8.40	0.64	28.36	15.68	40.00	24.32
41.64	34.9	QP	H	13.90	0.32	28.52	20.60	40.00	19.40
Middle Channel: 2437 MHz									
2437	73.7	PK	H	23.41	3.00	0.00	100.11	N/A	N/A
2437	63.89	AV	H	23.41	3.00	0.00	90.30	N/A	N/A
2437	72.3	PK	V	23.41	3.00	0.00	98.71	N/A	N/A
2437	61.81	AV	V	23.41	3.00	0.00	88.22	N/A	N/A
4874	48.71	PK	H	31.00	5.09	26.87	57.93	74.00	16.07
4874	36.93	AV	H	31.00	5.09	26.87	46.15	54.00	7.85
7311	36.03	PK	H	34.92	6.21	26.40	50.76	74.00	23.24
7311	24.64	AV	H	34.92	6.21	26.40	39.37	54.00	14.63
3475	34.25	PK	H	26.86	4.14	26.58	38.67	74.00	35.33
3475	22.79	AV	H	26.86	4.14	26.58	27.21	54.00	26.79
3747	36.27	PK	H	27.99	4.55	26.57	42.24	74.00	31.76
3747	24.39	AV	H	27.99	4.55	26.57	30.36	54.00	23.64
86.26	34.8	QP	H	8.40	0.64	28.36	15.48	40.00	24.52
41.64	35.1	QP	H	13.90	0.32	28.52	20.80	40.00	19.20
High Channel: 2462 MHz									
2462	75.01	PK	H	23.33	2.99	0.00	101.33	N/A	N/A
2462	64.83	AV	H	23.33	2.99	0.00	91.15	N/A	N/A
2462	73.25	PK	V	23.33	2.99	0.00	99.57	N/A	N/A
2462	63.39	AV	V	23.33	2.99	0.00	89.71	N/A	N/A
2483.5	38.9	PK	H	23.26	2.99	0.00	65.15	74.00	8.85
2483.5	19.45	AV	H	23.26	2.99	0.00	45.70	54.00	8.30
4924	48.43	PK	H	31.16	5.07	26.88	57.78	74.00	16.22
4924	37.98	AV	H	31.16	5.07	26.88	47.33	54.00	6.67
7386	35.93	PK	H	35.07	6.25	26.43	50.82	74.00	23.18
7386	23.6	AV	H	35.07	6.25	26.43	38.49	54.00	15.51
3475	34.44	PK	H	26.86	4.14	26.58	38.86	74.00	35.14
3475	22.08	AV	H	26.86	4.14	26.58	26.50	54.00	27.50
86.26	34.7	QP	H	8.40	0.64	28.36	15.38	40.00	24.62
41.64	35.2	QP	H	13.90	0.32	28.52	20.90	40.00	19.10

802.11 n ht40 Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2422 MHz									
2422	71.81	PK	H	23.47	3.00	0.00	98.28	N/A	N/A
2422	61.65	AV	H	23.47	3.00	0.00	88.12	N/A	N/A
2422	70.86	PK	V	23.47	3.00	0.00	97.33	N/A	N/A
2422	60.48	AV	V	23.47	3.00	0.00	86.95	N/A	N/A
2390	34.99	PK	H	23.57	3.00	0.00	61.56	74.00	12.44
2390	19.35	AV	H	23.57	3.00	0.00	45.92	54.00	8.08
4844	46.19	PK	H	30.90	5.10	26.87	55.32	74.00	18.68
4844	35.23	AV	H	30.90	5.10	26.87	44.36	54.00	9.64
7266	35.74	PK	H	34.83	6.19	26.38	50.38	74.00	23.62
7266	24.38	AV	H	34.83	6.19	26.38	39.02	54.00	14.98
3475	34.55	PK	H	26.86	4.14	26.58	38.97	74.00	35.03
3475	23.86	AV	H	26.86	4.14	26.58	28.28	54.00	25.72
86.26	35.1	QP	H	8.40	0.64	28.36	15.78	40.00	24.22
41.64	34.7	QP	H	13.90	0.32	28.52	20.40	40.00	19.60
Middle Channel: 2437 MHz									
2437	71.92	PK	H	23.41	3.00	0.00	98.33	N/A	N/A
2437	61.96	AV	H	23.41	3.00	0.00	88.37	N/A	N/A
2437	71.3	PK	V	23.41	3.00	0.00	97.71	N/A	N/A
2437	60.79	AV	V	23.41	3.00	0.00	87.20	N/A	N/A
4874	49.3	PK	H	31.00	5.09	26.87	58.52	74.00	15.48
4874	36.25	AV	H	31.00	5.09	26.87	45.47	54.00	8.53
7311	35.17	PK	H	34.92	6.21	26.40	49.90	74.00	24.10
7311	24.46	AV	H	34.92	6.21	26.40	39.19	54.00	14.81
3475	34.5	PK	H	26.86	4.14	26.58	38.92	74.00	35.08
3475	23.36	AV	H	26.86	4.14	26.58	27.78	54.00	26.22
3747	35.75	PK	H	27.99	4.55	26.57	41.72	74.00	32.28
3747	24.03	AV	H	27.99	4.55	26.57	30.00	54.00	24.00
86.26	34.6	QP	H	8.40	0.64	28.36	15.28	40.00	24.72
41.64	35.1	QP	H	13.90	0.32	28.52	20.80	40.00	19.20
High Channel: 2452 MHz									
2452	72.75	PK	H	23.36	3.00	0.00	99.11	N/A	N/A
2452	62.36	AV	H	23.36	3.00	0.00	88.72	N/A	N/A
2452	71.67	PK	V	23.36	3.00	0.00	98.03	N/A	N/A
2452	61.21	AV	V	23.36	3.00	0.00	87.57	N/A	N/A
2483.5	44.99	PK	H	23.26	2.99	0.00	71.24	74.00	2.76
2483.5	22.45	AV	H	23.26	2.99	0.00	48.70	54.00	5.30
4904	49.84	PK	H	31.09	5.08	26.87	59.14	74.00	14.86
4904	36.88	AV	H	31.09	5.08	26.87	46.18	54.00	7.82
7356	35.48	PK	H	35.01	6.23	26.42	50.30	74.00	23.70
7356	25.03	AV	H	35.01	6.23	26.42	39.85	54.00	14.15
3475	34.09	PK	H	26.86	4.14	26.58	38.51	74.00	35.49
3475	23.32	AV	H	26.86	4.14	26.58	27.74	54.00	26.26
86.26	35	QP	H	8.40	0.64	28.36	15.68	40.00	24.32
41.64	34.8	QP	H	13.90	0.32	28.52	20.50	40.00	19.50

BLE Mode

Frequency (MHz)	Receiver		Rx Antenna		Cable loss (dB)	Amplifier Gain (dB)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	Detector	Polar (H/V)	Factor (dB)					
Low Channel: 2402 MHz									
2402	64.16	PK	H	23.53	3.00	0.00	90.69	N/A	N/A
2402	58.91	AV	H	23.53	3.00	0.00	85.44	N/A	N/A
2402	57.68	PK	V	23.53	3.00	0.00	84.21	N/A	N/A
2402	52.35	AV	V	23.53	3.00	0.00	78.88	N/A	N/A
2390	27.93	PK	H	23.57	3.00	0.00	54.50	74.00	19.50
2390	15.39	AV	H	23.57	3.00	0.00	41.96	54.00	12.04
4804	37.42	PK	H	30.77	5.12	26.87	46.44	74.00	27.56
4804	25.44	AV	H	30.77	5.12	26.87	34.46	54.00	19.54
7206	35.45	PK	H	34.71	6.16	26.35	49.97	74.00	24.03
7206	24.61	AV	H	34.71	6.16	26.35	39.13	54.00	14.87
1507	28.18	PK	H	24.11	2.68	26.34	28.63	74.00	45.37
1507	17.8	AV	H	24.11	2.68	26.34	18.25	54.00	35.75
80.44	33.9	QP	H	8.14	0.46	28.39	14.11	40.00	25.89
33.88	32.8	QP	H	20.28	0.37	28.56	24.89	40.00	15.11
Middle Channel: 2440 MHz									
2440	63.93	PK	H	23.40	3.00	0.00	90.33	N/A	N/A
2440	59.5	AV	H	23.40	3.00	0.00	85.90	N/A	N/A
2440	58.24	PK	V	23.40	3.00	0.00	84.64	N/A	N/A
2440	52.55	AV	V	23.40	3.00	0.00	78.95	N/A	N/A
4880	36.54	PK	H	31.02	5.09	26.87	45.78	74.00	28.22
4880	25.39	AV	H	31.02	5.09	26.87	34.63	54.00	19.37
7320	35.61	PK	H	34.94	6.22	26.40	50.37	74.00	23.63
7320	24.27	AV	H	34.94	6.22	26.40	39.03	54.00	14.97
4419	21.12	PK	H	29.67	5.21	26.80	29.20	74.00	44.80
4419	9.34	AV	H	29.67	5.21	26.80	17.42	54.00	36.58
2165	40.9	PK	H	24.34	3.03	26.84	41.43	74.00	32.57
2165	29.66	AV	H	24.34	3.03	26.84	30.19	54.00	23.81
80.44	33.7	QP	H	8.14	0.46	28.39	13.91	40.00	26.09
33.88	32.9	QP	H	20.28	0.37	28.56	24.99	40.00	15.01
High Channel: 2480 MHz									
2480	61.79	PK	H	23.27	2.99	0.00	88.05	N/A	N/A
2480	55.93	AV	H	23.27	2.99	0.00	82.19	N/A	N/A
2480	55.16	PK	V	23.27	2.99	0.00	81.42	N/A	N/A
2480	49.98	AV	V	23.27	2.99	0.00	76.24	N/A	N/A
2483.5	28.26	PK	H	23.26	2.99	0.00	54.51	74.00	19.49
2483.5	16.55	AV	H	23.26	2.99	0.00	42.80	54.00	11.20
4960	37.54	PK	H	31.27	5.05	26.88	46.98	74.00	27.02
4960	25.7	AV	H	31.27	5.05	26.88	35.14	54.00	18.86
7440	36.66	PK	H	35.18	6.27	26.45	51.66	74.00	22.34
7440	24.95	AV	H	35.18	6.27	26.45	39.95	54.00	14.05
1712	29.21	PK	H	24.44	2.83	26.54	29.94	74.00	44.06
1712	17.94	AV	H	24.44	2.83	26.54	18.67	54.00	35.33
80.44	34.1	QP	H	8.14	0.46	28.39	14.31	40.00	25.69
33.88	33.1	QP	H	20.28	0.37	28.56	25.19	40.00	14.81


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B “Implementation of traceability policy in accredited laboratories”.

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	51.9 %
ATM Pressure:	100.2 kPa


* The testing was performed by Kevin Hu on 2017-05-09.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots.


Test mode	Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Limit (MHz)
802.11b	Low	2412	9.60	≥0.5
	Middle	2437	9.36	≥0.5
	High	2462	9.60	≥0.5
802.11g	Low	2412	16.16	≥0.5
	Middle	2437	16.40	≥0.5
	High	2462	16.40	≥0.5
802.11n20	Low	2412	17.28	≥0.5
	Middle	2437	17.44	≥0.5
	High	2462	17.68	≥0.5
802.11n40	Low	2422	36.64	≥0.5
	Middle	2437	35.68	≥0.5
	High	2452	36.48	≥0.5
BLE	Low	2402	0.68	≥0.5
	Middle	2440	0.69	≥0.5
	High	2480	0.70	≥0.5

802.11b Low Channel




Date: 9.MAY.2017 10:13:47

802.11b Middle Channel




Date: 9.MAY.2017 10:15:49

802.11b High Channel




Date: 9.MAY.2017 10:18:22

802.11g Low Channel




Date: 9.MAY.2017 10:20:12

802.11g Middle Channel




Date: 9.MAY.2017 10:22:06

802.11g High Channel




Date: 9.MAY.2017 10:23:53

802.11n ht20 Low Channel




Date: 9.MAY.2017 10:26:06

802.11n ht20 Middle Channel




Date: 9.MAY.2017 10:28:04

802.11n ht20 High Channel




Date: 9.MAY.2017 10:29:36

802.11n ht40 Low Channel




Date: 9.MAY.2017 10:32:35

802.11n ht40 Middle Channel




Date: 9.MAY.2017 10:35:19

802.11n ht40 High Channel




Date: 9.MAY.2017 10:37:18

BLE Low Channel




Date: 9.MAY.2017 09:54:25

BLE Middle Channel



Date: 9.MAY.2017 09:58:17

BLE High Channel



Date: 9.MAY.2017 09:59:19


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to test equipment.
3. Add a correction factor to the display.
4. Set the power Meter to test Peak output power, record the result as peak power.
5. Set the power meter to test average output power, record the result as average power.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Agilent	Wideband Power Sensor	N1921A	MY54170074	2017-01-03	2018-01-02
Agilent	P-Series Power Meter	N1912A	MY5000798	2017-01-03	2018-01-02
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	51.9 %
ATM Pressure:	100.2 kPa

* The testing was performed by Kevin Hu on 2017-05-09.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table.

Test mode	Channel	Frequency (MHz)	Max Peak Conducted Output Power (dBm)	Max Conducted Average Output Power (dBm)	Limit (dBm)
802.11b	Low	2412	13.4	9.35	30
	Middle	2437	12.83	9.32	30
	High	2462	12.89	9.24	30
802.11g	Low	2412	17.18	9.07	30
	Middle	2437	17.28	9.22	30
	High	2462	17.4	9.20	30
802.11n20	Low	2412	17.8	9.16	30
	Middle	2437	17.99	9.36	30
	High	2462	18.28	9.34	30
802.11n40	Low	2422	18.02	9.30	30
	Middle	2437	17.77	9.26	30
	High	2452	18.2	9.44	30
BLE	Low	2402	-3.81	/	30
	Middle	2440	-2.89	/	30
	High	2480	-6.00	/	30

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure


1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	C-2	Each Time	/


*** Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

802.11b: Band Edge, Right Side




Date: 9.MAY.2017 10:19:23

802.11g: Band Edge, Left Side




Date: 9.MAY.2017 10:21:21

802.11g: Band Edge, Right Side




Date: 9.MAY.2017 10:24:51

802.11n ht20 Band Edge, Left Side




Date: 9.MAY.2017 10:27:11

802.11n ht20 Band Edge, Right Side




Date: 9.MAY.2017 10:30:43

802.11n ht40 Band Edge, Left Side




Date: 9.MAY.2017 10:34:02

802.11n ht40 Band Edge, Right Side




Date: 9.MAY.2017 10:38:43

BLE Band Edge , Left Side



Date: 9.MAY.2017 09:55:17



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to 1.5 times the DTS bandwidth.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	100028	2016-12-02	2017-12-01
Unknown	RF Cable	Unknown	C-2	Each Time	/

* **Statement of Traceability:** BACL(Chengdu) attests that all of the calibrations on the equipment items listed above were traceable to NIM or to another internationally recognized National Metrology Institute (NMI), and were compliant with the NIST HB 150-2016 Normative Annex B "Implementation of traceability policy in accredited laboratories".

Test Data

Environmental Conditions

Temperature:	26 °C
Relative Humidity:	51.9 %
ATM Pressure:	100.2 kPa


* The testing was performed by Kevin Hu on 2017-05-09.

Test Mode: Transmitting

Test Result: Compliant. Please refer to the following table and plots


Test mode	Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b	Low	2412	-17.92	≤8
	Middle	2437	-18.54	≤8
	High	2462	-18.46	≤8
802.11g	Low	2412	-17.5	≤8
	Middle	2437	-17.96	≤8
	High	2462	-17.69	≤8
802.11n20	Low	2412	-17.39	≤8
	Middle	2437	-17.22	≤8
	High	2462	-15.85	≤8
802.11n40	Low	2422	-19.15	≤8
	Middle	2437	-19.67	≤8
	High	2452	-20.01	≤8
BLE	Low	2402	-19.41	≤8
	Middle	2440	-18.47	≤8
	High	2480	-21.62	≤8

Power Spectral Density, 802.11b Low Channel




Date: 9.MAY.2017 10:14:26

Power Spectral Density, 802.11b Middle Channel




Date: 9.MAY.2017 10:16:28

Power Spectral Density, 802.11b High Channel




Date: 9.MAY.2017 10:19:01

Power Spectral Density, 802.11g Low Channel




Date: 9.MAY.2017 10:20:58

Power Spectral Density, 802.11g Middle Channel




Date: 9.MAY.2017 10:22:48

Power Spectral Density, 802.11g High Channel




Date: 9.MAY.2017 10:24:35

Power Spectral Density, 802.11n ht20 Low Channel




Date: 9.MAY.2017 10:26:53

Power Spectral Density, 802.11n ht20 Middle Channel




Date: 9.MAY.2017 10:28:45

Power Spectral Density, 802.11n ht20 High Channel




Date: 9.MAY.2017 10:30:20

Power Spectral Density, 802.11n ht40 Low Channel




Date: 9.MAY.2017 10:33:44

Power Spectral Density, 802.11n ht40 Middle Channel




Date: 9.MAY.2017 10:36:17

Power Spectral Density, 802.11n ht40 High Channel




Date: 9.MAY.2017 10:38:27

Power Spectral Density, BLE Low Channel




Date: 9.MAY.2017 09:54:59

Power Spectral Density, BLE Middle Channel



Date: 9.MAY.2017 09:58:50

Power Spectral Density, BLE High Channel



Date: 9.MAY.2017 09:59:52

***** END OF REPORT *****