

FCC ID: 2AEOTSDRB  
 IC: 20402-SDRB  
 HVIN: SDR\_BT  
 PMN: SDR



### Techologies:

| Technologies: | Max. Power: (AVG)     | Max. Gain: | Min. Pathloss: |
|---------------|-----------------------|------------|----------------|
| BT 2G4        | 12 dBm ± 1 dB (cond.) | 0.5 dBi    | -/-            |
| K - band      | 20 dBm (EIRP)         | -/-        | -/-            |

### Prediction of MPE limit at given distance - FCC

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4\pi R^2$$

where: S = Power density  
 P = Power input to the antenna  
 G = Antenna gain  
 R = Distance to the center of radiation of the antenna

The table below is excerpted from Table 1B of 47 CFR 1.1310 titled "Limits for Maximum Permissible Exposure (MPE), Limits for General Population/Uncontrolled Exposure"

| Frequency Range (MHz) | Power Density (mW/cm <sup>2</sup> ) | Averaging Time (minutes) |
|-----------------------|-------------------------------------|--------------------------|
| 300 -1500             | f/1500                              | 30                       |
| 1500 - 100000         | 1.0                                 | 30                       |

where f = Frequency (MHz)

### Prediction: worst case

|   |                                     | < 1500 MHz | > 1500 MHz                    | > 1500 MHz                    |
|---|-------------------------------------|------------|-------------------------------|-------------------------------|
|   |                                     | -/-        | BT                            | K - band                      |
| P | Max power input to the antenna      | -/-        | 13 dBm                        | 20 dBm (EIRP)                 |
| R | Distance                            | -/-        | 20 cm                         | 20 cm                         |
| G | Antenna gain                        | -/-        | 0.5 dBi                       | -/- dBi                       |
| S | MPE limit for uncontrolled exposure | -/-        | 1 mW/cm <sup>2</sup>          | 1 mW/cm <sup>2</sup>          |
|   | <b>Calculated power density:</b>    | -/-        | <b>0.00 mW/cm<sup>2</sup></b> | <b>0.02 mW/cm<sup>2</sup></b> |
|   | <b>Colocation BT + K - band</b>     | -/-        | <b>0.45 %</b>                 | <b>2 %</b>                    |
|   |                                     | -/-        | <b>2.45 %</b>                 |                               |

**This prediction demonstrates the following:**

The power density levels for FCC at a distance of 20 cm are below the maximum levels allowed by regulations.

## Prediction of MPE limit at given distance - IC

RSS-102, Issue 5, 2.5.2

RF exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm, except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 1 W (adjusted for tune-up tolerance);
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $4.49/f^{0.5} \text{ W}$  (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance);
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834} \text{ W}$  (adjusted for tune-up tolerance), where  $f$  is in MHz;
- at or above 6 GHz and the source-based, time-averaged maximum e.i.r.p. of the device is equal to or less than 5 W (adjusted for tune-up tolerance).

### Prediction: worst case

|   |                                     | BT             | K - band       | -/- | -/- |
|---|-------------------------------------|----------------|----------------|-----|-----|
| P | Max power input to the antenna      | 13 dBm         | 20 dBm         | -/- | -/- |
| G | Antenna gain                        | 0.5 dBi        | -/- dBi        | -/- | -/- |
| S | MPE limit for uncontrolled exposure | 2676 mW        | 100 mW         | -/- | -/- |
|   | <b>Calculated output power:</b>     | <b>22.4 mW</b> | <b>19.1 mW</b> | -/- | -/- |
|   | <b>Colocation BT + K - band</b>     | <b>0.84 %</b>  | <b>19.2 %</b>  | -/- | -/- |
|   |                                     | <b>20.0 %</b>  |                | -/- | -/- |

**Conclusion:** for applications where minimum distance to radiating element is 20cm Annex C of RSS-102 should be filled out.

p.o.  cn=Marco Bertolino, o=CETECOM ICT Services GmbH, ou=BTL-100826, email=marco.bertolino@cetecom.com, c=DE  
2015.08.18 07:51:09 +02'00'

Meheza Walla  
Cetecom ICT Services GmbH