

High Definition Digital Video Recorder

User's Manual Installation Manual



Thank you for using our High Definition Video Recorder. This manual is applicable for hard disk models. Please read this User's Manual carefully to ensure that you can use the device correctly and safely. The contents of this manual are subject to be changed without notice.

Warning

This device is NOT of waterproof; to prevent it from any accident of fire or electric shock, please do NOT put any container with water on the device or nearby. Do not expose the device to moisture, or extreme temperatures.



This lightning flash with arrow symbol within an equilateral triangle is intended to alert users that there might be uninsulated dangerous voltage which may cause

CAUTION

**RISK OF ELECTRIC SHOCK
DO NOT OPEN**

To prevent from the risk of electric shock, do NOT remove top cover or back cover. There is NO user-serviceable part inside. Ask for service from qualified maintenance man.



The exclamation point within an equilateral triangle is intended to alert users the important operating and maintenance(servicing) instructions in this manual.



Important notice:

1. Please read over all cautions.
2. Please keep this manual for reference in the future.
3. Please notice all warning information.
4. Please strictly follow the instructions in this manual while operating.
5. Please NEVER put this device under the place which is easily poured by water.
6. Please do NOT use abrasive chemicals, cleaning solvents or strong detergents to clean the device. Wipe the device with a soft and dry cloth.
7. Please do NOT get the gate of airiness heat exchange closed.
8. Please leave the device far away from hot and high temperature environment.
9. Install the device with the accessories coming with it.
10. Please take care when moving the device, make sure of security, and avoid being damaged by dropping from high place.
11. Call for qualified maintenance man to repair when needed.
12. The device can only be installed horizontally. Installed vertically or out of the horizontal could hurt person or damage the device or/and its parts.

TABLE OF CONTENTS

1. GENERAL INTRODUCTION	4
2. PRODUCT FIGURES	6
2.1 FRONT PANEL	6
2.2 REAR PANEL	7
3. INITIAL SET UP	8
3.1 TAMPER-PROOF CASE MOUNTING	8
3.2 POWER CONNECTION	9
3.2.1. Use Ignition Switch to Turn On/Off DVR System	9
3.2.2. Turn On / Off DVR System Automatically	9
3.3 CAMERA CONNECTION	10
3.4 SENSOR HARNESS CONNECTION	11
GPS Connection (Option)	11
3.5 EVENT BUTTON AND CABLE CONNECTION (OPTION)	12
4. CONNECT THE HDVR TO A PC WITH NETWORK.....	13
4.1 DOWNLOAD AND INSTALL THE VLC PLAYER INTO YOUR COMPUTER	13
4.2 CONNECT THE HDVR WITH NETWORK.....	13
4.3 USE A WEB BROWSER TO ACCESS DVR FOR LIVE VIEW OR SETTING.....	13
5. BASIC OPERATION AND MENU SYSTEM.....	13
5.1 HARD DISK FORMATTING.....	13
5.2 SET UP RECORDING	15
5.3 SETUP YOUR CAMERAS	16
5.4 SETUP ALARMS	17
5.5 SETUP MOTION DETECTION	17
5.6 SETUP POWER	18
5.7 SETUP VEHICLE PARAMETERS	19
5.8 SETUP GPS PARAMETERS.....	19
5.10 SETUP SCHEDULE RECORD	21
5.11 NETWORK SETTING	22
5.13 SET UP DATE AND TIME	23
5.14 UPGRADE THE FIRMWARE	24
5.15 RESET THE HDVR.....	25
5.16 USER MANAGEMENT	26
6. SPECIFICATION	27
7. LIST OF STANDARD ACCESSORIES	29
8. TROUBLE SHOOTING.	30

1. General Introduction

The HDVR series mobile digital video recorder is a compact, full-featured H.264 1080p/720p recording system that uses a hard disk as a storage device. The recorder unit and associated accessories are specifically designed for operation in a mobile environment.

The HDVR system, used in conjunction with the cameras, records up to four channels of full-motion video and audio data to a hard disk. The firmware-driven menu system provides a simple method for configuring the unit's operation as well as searching for and viewing previously recorded AV records.

Product Description

The HDVR unit consists of the following major components:

Standard Components and Features

- Extruded aluminum case (the case is anodized in black).
- Front and rear panels.
- Mother Board.
- Power cables.
- Power input 2 amp fuses (2).
- Tamper proof and lockable security enclosure.
- Panel lock with (2) keys for locking the security enclosure.
- Hard disk or Solid State Disk (customer supplied).
- Removable SD card, Class 10, minimum (customer supplied).

Optional Components and Features

- GPS speed and location data overlay.
- Extension cable for easy connection and installation.

Product Main Features

- Embedded operating system, assuring reliability and system integrity.
- Records up to four channels of full-motion color video with corresponding audio tracks.
- H.264 High Profile video compression.
- Total Record resource up to 120 1080P frame/second.
- Lockable security enclosure.
- Front panel USB2 port for recording to a flash card as an optional storage device.
- Ignition sense that provides DVR power-on in recording mode when the bus is started.
- Power-off delay record when the bus is shut-down with operator-selected delay times.

Video And Audio

- H.264 High Profile video compression, real time recording 1080p30, 720p30 and 540p30 for each channel. Frame rate adjustable for each channel.
- Audio compression:16bit 48KHz AAC codec. This codec offers high compression with high quality audio.
- 1080P resolution for each channel, which means each channel support 1920x1080 @30fps.
- Support 4 channel real time 1080P video and 4 channel audio recording.
- Real time live HD video and audio through WiFi, support Windows, Android and iOS
- Recorded HD video and audio real time playback over WiFi

GPS Time Synchronization & Time Zone

- Synchronize the DVR system time with GPS automatically
- Support All Time Zones Worldwide
- Support DST (Daylight Saving Time)

Power Management

- Reliable power management, wide voltage: +8V~+32VDC; The power input is protected against short positive transient (1500 watts peak pulse power capability with a 10x1000 us waveform); The power input is protected against negative voltage. Applicable for vehicles with +12V or +24V battery.
- The recorder provides each camera with stable +12V DC power; DVR can detect the short cut on power circuit.
- Can use ignition to control the power.
- DVR can monitor battery voltage after Ignition off, and auto into sleep mode when voltage is below specified level.

Recording mode

- Continuous record.
- Support schedule recording.
- Support alarm recording.

Speed and Vehicle status recording

- Record vehicle speed and car id with audio and video.
- Support 5 sensors, can be connected to speed, ignition, brake, return, right turn, left turn light etc.
- Over-speed alarm and trigger recording with separated files

G-Sensor

- X, Y, Z axis accelerometer
- Recorded G-Sensor Values can provide reference of data analyzing when accident happened
- Combined Recording can be triggered when G-Sensor values go beyond threshold

Hard Disk

- Support hard disk within 2TByte.

Note: As the inside height of the hard disk case is 10.3mm, you should choose the hard disk whose height is less than 9.5mm to fit into the case.

SD card

- Support SDHC card within 32GByte.
- Support SDXC card more than 64GByte (Maxim 2048GByte)
- Support hot-plug when the DVR system is not recording or remote-operation(remote copying or playing back)

Note: If you remove the SD card while recording or operating (remote copying or playing back), it might cause the damage of the files on SD card. While recording, the yellow light on the front panel will be on. So please stop recording or operating until the yellow light is off if you need to remove the SD card.


Multiple player supported

You may use manufacturer's PC Playback Software or any of the following third party media player to play back the record file.

- VLC media player (version1.0.0 or above);
- Storm player (Version 2009 or above);
- Winamp (Version 5.531 or above).

2. Product Figures

2.1 Front Panel



1: USB Host Port: Can be used as a secondary recording device, such as a flash memory card. This port cannot be used as a direct access link to a PC, however.

2: SD Card Slot

3: Stop Button: For stop recording

4: LANC Port: For connection to an Event button and status indicator Network Port (RJ45).

5: Status Lights (1: Power; 2: Run; 3: Alarm; 4: Record; 5: System)

6: Lock and power switch for DVR

7: hard disk case

8: LAN port (RJ45)

Get to know the status of DVR system by the indication of LED lights:


SYSTEM (Yellow)	Status/Description
On	When all of 4 channels are recording
Blinking	Blinking every 2 seconds, LED indicator off times indicate the missing number of cameras channels. For example, if it blinks 3 times per time, there are 3 cameras missing in total.
Off	No camera existing or no recording on.

PWR (Green)	RUN (Green)	Status/Description
Always On	Blinking	DVR is on & running
Blinking with RUN by turns	Blinking with PWR by turns	Ignition is not enabled and DVR is OFF.
Blinking together with RUN	Blinking together with PWR	Ignition sense is not enabled & DVR is running. Unit will turn OFF when "Delay Time" setting is reached.
Blinking every 3 seconds	Off	Use the key to turn off the DVR.

ALARM (Red)	Status/Description
On	Alarm input when BEEP is set as "ON". Audible alarm (beep) when enabled.
Off	No alarm.

REC(Red)	Description
On	Reading/Writing data from/to the hard disk or SD Card.
Off	Not Reading/Writing – inactive.

2.2 Rear panel



- 1: Power, Ground and ACC input.
- 2: 1x speed sensor, 3x sensors inputs, 1x RS232 port(for GPS) and 1x 5V DC output
- 3: AV input 1(including audio input 1, video input 1 and power output for camera 1)
- 4: AV input 2(including audio input 1, video input 1 and power output for camera 2)
- 5: AV input 3(including audio input 1, video input 1 and power output for camera 3)
- 6: AV input 5(including audio input 1, video input 1 and power output for camera 4)
- 7: AV input 6(including audio input 1, video input 1 and power output for camera 5)
- 8: AV input 7(including audio input 1, video input 1 and power output for camera 6)
- 9: AV input 8(including audio input 1, video input 1 and power output for camera 7)
- 10: AV input 4(including audio input 1, video input 1 and power output for camera 8)
- 11: Wifi antenna connector (Main)
- 12: Wifi antenna connector (Auxiliary)


The sockets on rear panel are of Molex Micro-Fit 3.0 (Model No.: Molex 0430450200). The definition of all sockets are given as below:

							
ACC	PWD	485A	TXD	USB-	5.0V	SNR2	SPEED
							
GND		485B	GPS	USB+	GND	SNR3	SNR1


3. Initial Set Up

3.1 Tamper-proof Case Mounting


- 1) Use a power drill and screws supplied to fix the bottom cover of the tamper-proof case in the right place inside the vehicle.



- 2) Put the DVR system inside the bottom cover, and load a hard disk.




- 3) Close with the top cover and lock it with keys supplied.




3.2 Power Connection

3.2.1. Use Ignition Switch to Turn On/Off DVR System



3.2.2. Turn On / Off DVR System Automatically




NOTE


1. The DVR uses DC power input, please be very careful when connecting to the “+” and “-” of the power supply.
2. Wide voltage range of 8V-32V for the DVR. The DVR may be damaged if the voltage comes too high. And the DVR may not work if the voltage comes too low.
3. Power of the DVR should be supplied by the car battery.
4. Power consumption of the DVR can be 60W when the engine starts. All the cables for connecting from power to the DVR should be thick enough for current over 5 Amperes.
5. To protect the battery from being damaged of short circuit, the fuse should be placed very closed to the “+” pole of car battery.

3.3 Camera Connection


Connect the camera with HDVR.





3.4 Sensor Harness Connection



GPS Connection (Option)



3.5 Event Button and Cable Connection (Option)



4. Connect the HDVR to a PC with network

4.1 Download and install the VLC player into your computer

User will need to install a VLC player to play back the video from HDVR. User can download the VLC player in <ftp://ezview.3322.org/DVR/HDVR/vlc-2.0.1-win32.exe>. Then please install the VLC player. After the installation, the VLC plug in will be available for your internet browser. It supports IE, Chrome and Firefox.

4.2 Connect the HDVR with network.

To connect the DVR via network, you can use network cable or WiFi to do it.

1) Connect the DVR via network cable

you can use a network cable connect to the DVR directly, please set your PC or notebook to use dynamic IP address, the HDVR's AP will assign a new IP address for your notebook.

2) Connect the DVR via Wifi:

If you use notebook with WiFi, you can scan and find an AP with name of "HDVR_****", just connect it.

Please set your notebook to use dynamic IP address, the HDVR's AP will assign a new IP address for your notebook.


4.3 Use a web browser to access DVR for live view or setting.

Please enter "hdvr.cfg" or "192.168.10.254" in the address bar of your web browser, the browser will notice you to use the VLC plug-in, check the "yes". Then you will view 4 images in quad mode.

1) For live view page, please click the button Cam1, Cam2, Cam3 and Cam4 for each camera's HD image (1080p/720p).

2) If you want to do some setting, please click the "SETTINGS" page title.

3) If the corresponding camera is recording, the red dot of CAMx will blink.



5. Basic Operation and Menu System

5.1 Hard Disk Formatting

For a brand new hard disk, you may need to format it before it can be used for DVR. To format it before using:

- 1) Put the hard disk into the hard disk case. Then put the hard disk case into the DVR and turn on the DVR.
- 2) Click "SETTINGS" and choose "Storage" in the "System" menu;

LIVE
SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Storage Management:
Memory Disk Status:
 Disk OK
 Total Memory: 62351 Mb
 Free Memory: 49599 Mb

Format

Storage Policy Settings:
 Memory Auto Overwrite: ☒

Apply

Help>>

Memory Disk Contents:
 Current folder to list: /

[Back](#)
[Up](#)

Name	Size	Action
Video	-	View
log.txt	0.22M	View

- a) Click "Format" to format the hard disk.
- b) Formatting storage media will result in loss of all data on the disk, backup your important files before formatting.
- c) The format process will take some time, please wait. You will see the capacity of hard disk after formatting.
- d) The oldest video files will be deleted automatically when the storage media gets full if "Memory Auto Overwrite" is checked.
- e) Alarm record files under the "Alarm" directory can only be deleted manually.
- f) "Memory Disk Contents" will list all the folders and files on the storage media in chronological order. Clicking "View" to download any designated file or explore the details in the folder

5.2 Set up recording

Click “Record Details” in the “DVR” menu to set up your recording.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Record Stream Settings:

	CAM1	CAM2	CAM3	CAM4
Resolution:	1920X1080 ▾	1920X1080 ▾	1920X1080 ▾	1920X1080 ▾
Bitrate(Kbps):	2000 ▾	2000 ▾	2000 ▾	2000 ▾
Frame Rate(1~30):	30 ▾	30 ▾	30 ▾	30 ▾
File Length(Minutes):	5 ▾	5 ▾	5 ▾	5 ▾
Record with Audio:	Yes ▾	Yes ▾	Yes ▾	Yes ▾
Record Mode:	Auto ▾	Auto ▾	Auto ▾	Auto ▾
Size(MBytes/hour):	675	675	675	675
Camera Status:	OK	OK	OK	OK
Record Status:	Recording	Recording	Recording	Recording
Stop All	Stop	Stop	Stop	Stop

Record File Encryption:

Using Encryption: ☐

Total Memory:62351 MBytes
Estimated Recording Time:23Hours

Apply

Help>>

- Each camera supports up to 1080p30, bitrate varies from 100Kbps to 8000Kbps. Default setting is 1080p30 with bitrate of 3000Kbps. 1200Kbps is recommended for 720p25. DVR uses intelligent bitrate control to save media space when doing H.264 image compression. If no obvious moving in scope, the bitrate will be reduced to 50%(75% for 1080p) of the set value automatically. For example, if one camera is set to 720p25 at 1200Kbps, the actual running bitrate could be 600Kbps when no obvious movement.
- Three levels of resolution supported for record: 1080p(1920x1080), 720p(1280x720) and 540p(960x540). If you want record more time with same SD card, you can select 720p or 540p for recording, use lower frame rate and lower bitrate with acceptable video quality.
- SD card with speed of Class 10 is recommended for high bitrate setting.
- Estimated recording time with the storage media being used will be shown up under the configuration box. The DVR allows for the customized settings for resolution, bitrate and frame rate on each individual camera. Note: The estimated recording time depends on the complexity and strength of movement.
- The file length can be optional from 1 min to 4 hours. The size for a single file should not be over 2GB with limitation of FAT32. That means the file size will be limited as 2GB or less to avoid file system error, even it does not reach the set record time (when high bitrate and/or long file length is set).
- Support 3 record modes: Manual/Auto/Off. Default is Auto.
Manual: Send commands from the page, ie. Mouse click on Start button.
Auto: DVR will start recording automatically after it is turned on.
Off: Any camera set with "Off", it will not start to record anyway.
- Support 3 record modes: Manual/Auto/Off. Default is Auto.
- Click Start/Stop to start or stop record on each individual camera. Click "Apply" to have the setting change(s) take effect. choose "RECORD" to enter its sub-menu;
- The record file can be encrypted. You may just check the "Using Encryption" to enable this feature. The encrypted file can only be played-back on AVPlayer provided by the manufacturer.

5.3 Setup your cameras

Click “Camera Setting” in the DVR menu to setup the cameras.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Camera Selection:

CAM1 BBBBA

2015-04-02 15:23:28.61



☒ CAM1

☐ CAM2

☐ CAM3

☐ CAM4

Camera Settings:

Brightness(0-100):

50

Contrast...(0-100):

50

Hue.....(0-100):

50

Saturation(0-100):

50

Audio Volume(0-100):

100

Camera Title:

CAM1

Video Lost Beep:

☒ Enable

Power Line Frequency:

☒ Disable ☒ 50 Hz ☐ 60 Hz

Flip:

☒ Vertical ☒ Horizontal

Auto Black-and-White:

☒ Enable

Apply

Help>>

1. Click CAMx to adjust each camera's brightness, contrast, audio volume, and other settings.
2. Max 12 characters are limited for each camera title.
3. Camera image can be flipped in direction of horizontal or vertical.
4. When “Auto Black-and-White” is enabled, it would switch from color mode to Black&White mode, or from Black&White mode to color mode automatically according to the camera light sensor device.

5.4 Setup alarms

Click “Alarm Details” to set up alarm actions.

	LIVE	SETTINGS		
DVR Record Details Record Schedule Camera Settings				
Alarms Alarm Details Motion Detection				
Mobile Power Motor GPS G-Sensor				
Network WiFi Network Network Settings				
System Date & Time Upgrade Reset Storage User Management				
Alarm Detail Settings:				
Trigger Level/Mode:	Alarm1 High ▼	Alarm2 High ▼	Alarm3 High ▼	Event Button Event Button ▼
Alarm Record:				1234
	☐ CAM1	☐ CAM2	☐ CAM3	☐ CAM4
Alarm OSD:	s1	s2	s3	SOS
Alarm Buzzer:	Off ▼	Off ▼	Off ▼	Off ▼
Alarm Record Settings:				
Pre-record Time:	20 ▼ Seconds			
Post-record Time:	60 ▼ Seconds			
Apply				
Help>>				

1. Alarm setting includes 3 external triggers and 1 event button.
2. External triggers can be set with high level active or low level active.
3. Event button can be used to start/stop recording, or trigger an alarm recording.
4. Combined Recording can be triggered when any alarm happens.
5. The image burn in characters can be edited in Alarm OSD menu.
6. Pre-record and Post-record time can be set for alarm triggered record file.
7. Alarm record files will not be deleted even disk gets full and Overwrite option is ON.

5.5 Setup Motion Detection

Click “Motion Detection” to set up Motion Detection alarm.

LIVE
SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time


Upgrade

Reset

Storage

User Management

Motion Zone Settings:



Enable All
Disable All

Click on individual motion regions to enable or disable. Regions are enabled when fully transparent.

☒ CAM1
 ☐ CAM2
 ☐ CAM3
 ☐ CAM4

Motion Details Settings:

Enable Adaptive Bitrate:	☒
Record when motion detection triggered:	☐
Alarm Buzzer:	☐
Sensitivity(0-100):	80
Percent of enabled area required to trigger (0-100):	50

Apply
Help>>

1. Up to 12 motion detection areas can be activated for each camera.
2. Each camera needs to be configed individual.

5.6 Setup power

Click "Power" in the "Mobile" menu to setup the power supply.

LIVE
SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Power Settings:

Ignition Level:	High ▼
Power Off Delay:	30
	Seconds
Power On At(HH:MM):	00 : 00
Power Off At(HH:MM):	00 : 00

Apply
Help>>

1. Default ignition level is HIGH, while LOW for few cars with main switch on negative pole.
2. Power Off Delay is used to set how long the DVR keeps working after ignition is off.
3. "Power On At" and "Power Off At" is used for scheduling Power On/Off. To enable this function, keep the yellow ignition wire connected with red power wire.

5.7 Setup vehicle parameters

Click “Motor” in the “Mobile” menu to setup vehicle parameters.

	LIVE	SETTINGS
DVR Record Details Record Schedule Camera Settings		
Alarms Alarm Details Motion Detection		
Mobile Power Motor GPS G-Sensor		
Network WiFi Network Network Settings		
System Date & Time Upgrade Reset Storage User Management		
	Motor Settings: License ID: BBBBBA Obtain Speed : From GPS(If Any) Speed Unit: KMH Speed Limit(KMH/MPH): 0 Overspeed Record: ☐ CAM1 ☐ CAM2 ☐ CAM3 ☐ CAM4 Overspeed OSD: Overspeed Buzzer: Off Idling too long Alarm(Minutes): Disable Apply Help>>	

1. Speed obtains from GPS (if existing).
2. The item "Speed Limit" is used to set the speed alarm threshold.
3. Combined Recording can be triggered when over speed.
4. The image burn in characters can be edited and applied when over speed.

5.8 Setup GPS parameters

Click “GPS” in the “Mobile” menu to setup the GPS parameters.

	LIVE	SETTINGS
DVR Record Details Record Schedule Camera Settings		
Alarms Alarm Details Motion Detection		
Mobile Power Motor GPS G-Sensor		
Network WiFi Network Network Settings		
System Date & Time Upgrade Reset Storage User Management		
	GPS Status: GPS Status: GPS NOT FOUND GPS Settings: GPS OSD : On GPS Baudrate: 9600 Sync with GPS Time : ☒ Apply Help>>	

1. GPS Status:

GPS NOT FOUND: No GPS detected.

GPS DATA: GPS is found but data stream error (baudrate or protocol error).

GPS GPRMC: GPS GPRMC means correct but inactive GPRMC frames.

(GPS searching in processing, or GPS signal is weak or lost)

2. GPS OSD gives the option if longitude/latitude data to be burned in video image.
3. Sync with GPS Time gives the option to synchronize the DVR system time with GPS time.
4. DVR system time will be synchronized with GPS time every hour if sync option enabled, and only minutes and seconds will be synchronized. If you want to set date and hour, please reference "Date and Time" menu.

5.9 Setup G-Sensor parameters

Click "G-Sensor" in the "Mobile" menu to setup G-Sensor Menu.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

G-Sensor Settings:

	Axis X	Axis Y	Axis Z
Instant Value(g):	0.015	0.003	-0.977
Initial Offset(g):	0	0	-1
Alarm Threshold(g):	0.25	0.25	0.25
Alarm OSD:	x	y	z
Alarm Record:	☐ CAM1	☐ CAM2	☐ CAM3 ☐ CAM4
Alarm Buzzer:	Off ▼	Off ▼	Off ▼

Apply

Help>>

1. G-Sensor Instant Value can give the X/Y/Z axis accelerometer values instantly.
2. For Earth gravity effect, it will get about 1.0g on Z axis when DVR is placed on a horizontal platform.
3. Initial values should be set to the X/Y/Z axis values when the vehicle is still, and DVR is installed on desired position.
4. Alarm Threshold can be set to the absolute differential value between initial value and acceptable maximum value, if the absolute difference is over the threshold, it will trigger according axis alarm.
5. Combined Recording can be triggered when G-Sensor Alarm happened.
6. Recorded G-Sensor Values can provide reference of data analyzing when accident happened.

5.10 Setup schedule record

Click “Record Schedule” in the “DVR” menu to setup schedule record.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Record Schedule Settings

Camera:

☒ All ☐ CAM1 ☐ CAM2 ☐ CAM3 ☐ CAM4

Schedule:

	HH:MM		HH:MM
1.From	00 : 00	To	00 : 00
2.From	00 : 00	To	00 : 00
3.From	00 : 00	To	00 : 00

Clear

Apply

Help>>

1. The record schedule allows for 3 time plans per day.
2. Each camera can be scheduled individual, or click "All" to apply the same record schedule to all cameras.

5.11 Network setting

Click "WiFi network" in the "Network" menu to set up the network.

The screenshot shows the 'Network' settings page for a DVR. The left sidebar lists various settings categories: DVR, Alarms, Mobile, Network, and System. The 'Network' category is selected, and the 'WiFi Network' option is highlighted. The main content area is titled 'Wireless Network:' and contains two sections: 'AP Mode WiFi Settings:' and 'Client Mode WiFi Settings:'. Under 'AP Mode', there are checkboxes for 'Enable WIFI AP:', 'Enable DHCP:', and 'Hide SSID:'. Below these are input fields for 'Local SSID:' (containing 'HDVR_0000AA'), 'Channel:' (a dropdown menu showing '11'), 'Security:' (a dropdown menu showing 'None'), 'Password(8-63chars):' (an empty text field), and 'Country Region:' (a dropdown menu showing '0 (ch 1-11)'). Under 'Client Mode', there is a checkbox for 'Enable WIFI Client:', a 'Remote SSID:' field with a red 'X' icon, and a 'Security:' dropdown menu showing 'OPEN'. At the bottom of the main area are two buttons: 'Apply' and 'Help>>'. The top of the interface has tabs for 'LIVE' and 'SETTINGS'.

1. The WiFi of DVR can work in both WiFi AP and WiFi Client mode:
 - I. AP Mode
 - WiFi AP can be turned ON or Off with checkbox.
 - Local SSID can be renamed, ie. Vehicle Plate Number.
 - WiFi Channels should correspond with the Country Region.
 - Encryption mode should be selected when a WiFi password needed.
 - II. Client Mode
 - WiFi Client can be turned ON or Off with checkbox.
 - Use "Wireless Scan" to show the available remote WiFi AP list.
 - Click the remote WiFi AP which the DVR want to connected.
 - Enter the password as mentioned to connect.
 - Default IP mode is DHCP, Static IP address mode is also available.
2. Click "Apply" button when all of the settings completed and the WiFi will restart and force new settings take effect.

5.13 Set up date and time.

Click "Date & Time" in the "System" menu to setup date and time.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

Date & Time Settings:

Date Format:

yyyy-mm-dd

Camera Time:

2015-04-02 15:32:18

Set Mode:

Keep Current Settings

Time Zone:

(GMT+08:00) Beijing, Chongqing, Hong Kong, Urumqi

DST Setting:

Disable

Apply

Help>>

1. Manual Setting and Sync with PC Time are the two ways for adjusting time.
2. Intelligent Device (PC, Pad or Phone) connected to DVR can sync it's time to DVR system time by way of "Sync with PC time".
3. The item "Time Zone" is used to select the according time zone in your country.
4. The item "DST Setting" now is only useful for three countries: USA/Australia/New Zealand.

5.14 Upgrade the firmware

Click “Upgrade” in the “System” menu to upgrade the firmware of HDVR or Cameras.


LIVE SETTINGS	
DVR Record Details Record Schedule Camera Settings	Current versions: DVR Kernel Version: DVR App Version: DVR Mcu Version: DVR Web Version: Camera1 Version: Camera2 Version: Camera3 Version: Camera4 Version:
Alarms Alarm Details Motion Detection	
Mobile Power Motor GPS G-Sensor	
Network WiFi Network Network Settings	
System Date & Time Upgrade Reset Storage User Management	Export the config file from your dvr: Export
Please select a file(*.tar) to update your dvr or import a config(*.cfg) into your dvr: Location: 选择文件 未选择任何文件	
Upload Help>>	

1. System Version includes:

DVR Kernel Version	DVR App Version	MCU FW version
Web Menu version	Camera FW version	
2. Upgrade file should be ended with .tar.
3. After Upgrade completed, web will notice refreshing web page or waiting DVR restart.
4. Restart browser or clear web cache if necessary.

5.15 Reset the HDVR

Click “Reset” in the “System” menu to Reset your HDVR.



The HDVR can be reset to “Factory Setting” for all setting. You can also reboot the HDVR in this menu.

5.16 User Management

Click “User Management” in the “System” menu to set the user authority for your HDVR.

Admin has all authorities to configure or change settings. Other levels of user can only watch the live video, and review the record files.

LIVE

SETTINGS

DVR

Record Details

Record Schedule

Camera Settings

Alarms

Alarm Details

Motion Detection

Mobile

Power

Motor

GPS

G-Sensor

Network

WiFi Network

Network Settings

System

Date & Time

Upgrade

Reset

Storage

User Management

User Management

Current User: **Admin** **Logout**

Reset Password

Username: Admin ▼

New Password:

New Password Again:

Apply

6. Specification

Model		HDVR
System	Operating System	Linux 2.6
	Start up Time	<20 seconds (From power on to recording)
	Operator Interface	English / Simplified Chinese/Russian
	Storage	2.5" Hard Disk(up to 2TB), SSD(up to 2TB) or SD Card (up to 128GB)
	Video System	H.264 Main/High Profile, HD 1080p30/720p30/540p30 Recording for each channel
	Voltage Input / Output	Input: 8 V ~ 32 V DC, Output: 12V/1.5A (4 channels)
Video	Video Input	Maximum 8 x 1080p/720p camera inputs
	Video output	Note book/iPhone/iPad/Android Pad/Android Phone
	Preview	1 image / 4 images (Switch for 8 images)
	Standard Stream	ISO 14496-10
	Recording Resolution	Selectable (1920x1080, 1280x720, 960x540)
	Recording	Supports normal, schedule, alarm recording and continuous
	Video Compression	H.264 (High profile up to level 4.1)
	Max fps (total)	240fps@1080p for 8 channels model
Audio	Audio Input	Build in Camera
	Audio compression	AAC (16bit, 48KHz)
Interface I/O	LAN	1(RJ-45) 10M / 100M Ethernet port
	USB	Supports USB 2.0 for U-Disk recording
	Serial	RS-232×1
Network	WiFi	Build in 802.11b/g/n AP, speed up to 300Mbps
	Protocol	TCP / IP
Alarm & Sensor	Inputs	3 Alarm input, 1 speed, 1 ignition, 1 Panic button, G-Sensor
	Outputs	1 Beeper, Alarm LED, Email
	Multi-mode	Activation by video loss, maximum permissible speed, Collision, SD space, Video Motion, etc..
Power Supply	Ignition key	Recording starts when ignition is on, stops with delay time when ignition is off.
	Power Consumption	Average 2.0W (without SD/SSD/HDD and without providing power for the cameras)
Physical Characters	Dimension	143.3mm x 133.0mm x 30.2mm
	Weight	1.08kgs
Others	Backup	By WiFi (300Mbps, Actual download speed up to 150Mbps)
	Clock	Internal, permanent calendar, Time sync from GPS (if available)
	GPS	GPS/GLONASS module external
	Function Dual Streaming	Allows you to configure the frame rate of different transmission frame rate recording and bandwidth control
	Self-protection	Protection against overload, short circuit and reverse polarity
	Reset	Option to return to factory default setting

	SD memory	Support SD card x 1 (support SDXC, up to 128GB)
	LED's	Indicates Power, RUN, Alarm, Media Access, Recording status, network
	Method of writing and reading of data	Overwrite ON/OFF selectable
	Synchronization time	GPS Time Synch / NTP (Network Time Protocol) Time Synch via networking
Environment	Operating Temperature	-30 ~ 60°C
	Relative humidity	5% - 95%
	Vibration resistance	< 3 Grms
	Resistance to mechanical shock	< 1200 Grms
Embedded Software	Config. FPS per channel	allows (1~30fps)
	ID records vehicle license plate	allows
	USB	Record
	Rename channels	allows
	Watermark	fixed
	Schedule	Settings hour, minute, 3 time plans per day
	Image Playback	Includes date and time, latitude and longitude, vehicle speed, and vehicle ID plate and name or channel number
	Playback Speed	Speed forward 1x ~ 16x

7. List of Standard Accessories

Item	Description	Quantity
1	HD Video Recorder	1 pc
2	Tamperproof & Lock Case	1 pc
3	Lock case key	2 pcs
4	WiFi Antenna	2 pcs
5	Signal cables	1 pc
6	Power cable	1 pc
7	Fuse box	1 pc
8	3A fuse	2 pcs
9	User's Manual	1 pc

Options:

Item	Description	Quantity
1	External GPS Receiver	1 pc
2	Event Button & Cable	1 pc
3	Extension Cable (3m, 6.2m, 10m Option)	1 pc for one camera, 2 pcs for two cameras, 3 pcs for three cameras 4 pcs for four cameras 5 pc for five cameras, 6 pcs for six cameras, 7 pcs for seven cameras 8 pcs for eight cameras
4	Hard Disk	1pc
5	Hard Disk Reader	1pc
6	Anti-vibration case	1pc

8. Trouble Shooting.

1. Q : After connecting the DVR power, no WiFi AP SSID available, 5 and No.6 indicators lights on panel flashing alternately.

A: The No.5 and No.6 LED indicator light is "Power" and "Run". If the 2 indicators lights are flashing alternatively, the DVR missed the ignition signal, please check if the yellow line of the input power lines has connected with the power positive level, or if it's the same as the setting of the effective electrical level in menu settings. (The factory default settings set the high level effective, that is, it is effective when the yellow ignition signal line is connecting with the power positive level.)

2. Q: As hard disk's capacity limited, how to make the videos' time expand to meet the requirements of the customers?

A: Reduce the video frame rate, resolution and bit rate, please see 5.2.

3. Q: What is a high level, what is low level?

A: Generally, there are two electrical levels in the car, the power and the ground. Automotive power voltage with 12V and 24V, we generally call it high level, not the specific voltage value. Ground of Vehicle is the reference level, accurately is battery negative electrode. We generally call it low level. For cars with negative switch control (the main switch cut off the connection of the battery cathode and car chassis ground), the chassis ground connects to the battery anode through a certain resistance, the chassis ground is not a reference ground anymore. Please see the Appendix in the back, including the potential analysis diagram against cars with negative switch control.

4. Q: Respectively, what's the voltage reference range of the high and low level in the DVR?

A: The voltage range of low level is DC 0V~3V, the high level is DC6V~32V.

5. Q: SD cards or hard drives are OK, but the video recording doesn't work, what should I do?

A: Please make sure if the default setting of Record Mode is changed from "Automatic" to "Off", and whether to modify the DVR to scheduled record mode and the current time is not within the time period you set.

6. Q: Do internal real time clock of the DVR maintained by batteries? If so, how long will it last?

A: Rechargeable batteries are used for DVR internal real time clock. If the battery is fully charged and DVR is completely disconnected from the power supply, internal real time clock can probably last for 1 month.

If a GPS is existing, Sync with GPS Time gives the option to synchronize the DVR system time with GPS time.

7. Q: what do the 6 indicator lights representative on the panel of the DVR?

A: Please reference the description in 2.1

8. Q: what kind of player software should use to play back video slots in SD card on the PC? Why some of them don't play normally?

A: The DVR recording files is a standard AVI format, video stream compression standard is senior H. 264.

1. DVR has its own player software, including many special additional feature, such as playing continuously, fast forward playing, and other quickly locating recording and playing.

2. The recorded files also support general players. Such as VLC (version 1.0.0 and above, free open source software, can download from the internet), Media Player Classic(version 2009 Build: 3.9. above), or Storm Audio.

9. Q: How to upgrade the DVR program?

A: Please reference the instructions of 5.11

10. Q: Do your DVRs have RS485 control PTZ functions?

A: The DVR will not support PTZ directly. The traditional RS485 is not supported in the High Definition Video System anymore. The PTZ implementation mode is like the IP Camera, our new HD camera can support PTZ or ePTZ in the future. Please contact our sales for more information.

11. Q: what is “Power OFF Delay”?

A: Users who need to install DVR often want the DVR to record the images inside and outside the car for a while after the driver turn the engine off. That is, DVR cannot be turned off after engine is shutdown, it should be off after record continuously for the specified period of time. This time is called “Power OFF Delay” time, such as 30 seconds. You can set the time you need on "Car Settings – Power Off Delay ".


When the users who need “Power OFF Delay” function, the positive level of the DVR and the ground should be connected directly (through the fuse) to the cathode and anode of the car battery, at the same time attach car ignition signal line to the ACC of the car.

Of course, the time of “Power OFF Delay” cannot be set too long, because after the engine shutdown, mobile DVR entirely depend on the power of the car battery to work, we should prevent the vehicle can't start correctly next time if the mobile DVR drained the energy of the car battery.

12. Q: What does the indicator light mean on the wire control L25?

A: The indicator light on the wire control is double color light, red and green. See the following form for their state.

State of green light	meaning	State of green light	meaning
One slow flash every three seconds	System start	Slow flash every three seconds	Communication of wire control is not normal
One flash every second	System is normal but no record	One flash every second	No memory device
lighting	System recording normal	lighting	No definition
One flash every 0.5 seconds	No definition	One flash every 0.5 seconds	System alarm indicator (the same as buzzer)



FCC Statement

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter.