

SAR TEST REPORT

Reference No. : WTD26D06155087W011
FCC ID : 2AEPIBLACKC2
Applicant : COLOMBIANA DE COMERCIO S.A.
Address : Car. 43E No 8-71, Medellin, Colombia
Manufacturer : Mobiwire Mobiles (Ningbo) Co.,Ltd
Address : No. 518, Changting East Road, Yuelin Street, Fenghua District,
Ningbo City, Zhejiang Province, China
Product : Smart Phone
Model(s) : Black C2
Brand Name : Kalley
Standards : FCC 47 CFR Part2(2.1093)
IEEE Std C95.1: 2019
IEC/IEEE 62209-1528:2020
& Published RF Exposure KDB Procedures
Date of Receipt sample : 2026-06-04
Date of Test : 2026-06-04 to 2026-07-13
Date of Issue : 2026-07-17
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Frank Yin

Frank Yin / Project Engineer

Approved by:

Deval Qin

Deval Qin / Designated Reviewer

Waltek Testing Group Co., Ltd.

<http://www.waltek.com.cn>

Page 1 of 232

2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	2
3 REVISION HISTORY	3
4 GENERAL INFORMATION	4
4.1 GENERAL DESCRIPTION OF E.U.T.	4
4.2 DETAILS OF E.U.T.	4
4.3 TEST FACILITY	7
5 SUMMARY OF TEST RESULTS	8
6 EQUIPMENT USED DURING TEST	9
6.1 EQUIPMENT LIST	9
7 SAR INTRODUCTION	10
7.1 INTRODUCTION	10
7.2 SAR DEFINITION	10
8 SAR MEASUREMENT SETUP	11
9 EXPOSURE LIMIT	20
10 SYSTEM AND LIQUID VALIDATION	21
10.1 SYSTEM VALIDATION	21
10.2 LIQUID VALIDATION	24
11 TYPE A MEASUREMENT UNCERTAINTY	33
12 OUTPUT POWER VERIFICATION	36
12.1 TEST CONDITION	36
12.2 TEST PROCEDURES	36
12.3 TEST RESULT	37
13 EXPOSURE CONDITIONS CONSIDERATION	79
13.1 EUT ANTENNA LOCATION	79
13.2 TEST POSITION CONSIDERATION	79
13.3 RF EXPOSURE	80
14 SAR TEST RESULTS	82
14.1 TEST CONDITION	82
14.2 GENERALLY TEST PROCEDURES	82
14.3 SAR SUMMARY TEST RESULT	83
15 SAR MEASUREMENT REFERENCE	110
15.1 REFERENCES	110
15.2 MAXIMUM SAR MEASUREMENT PLOTS	111
16 CALIBRATION REPORTS-PROBE AND DIPOLE	135
17 SAR SYSTEM PHOTOS	229
18 SETUP PHOTOS	230
19 EUT PHOTOS	232

3 Revision History

Test Report No.	Date of Receipt Sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD26D06155087W011	2026-06-04	2026-06-04 to 2026-07-13	2026-07-17	Original	-	Valid

4 General Information

4.1 General Description of E.U.T.

Product:	Smart Phone
Model(s):	Black C2
Model Description:	N/A
Test Sample No.:	1-1/1
Bluetooth Version:	V5.2
Wi-Fi Specification:	2.4G-802.11b/g/n HT20/n HT40 5G-802.11a/ n(HT20/40)/ac(VHT20/40/80)
GSM Band(s):	GSM 850/1900MHz
GPRS/EGPRS Class:	12
WCDMA Band(s):	FDD Band II/IV/V
LTE Band(s):	FDD Band 2/4/5/7/13
GPS:	Support
Hardware Version:	V00
Software Version:	Kalley_BLACK_C2_V01_20260520_FCC

4.2 Details of E.U.T.

Operation Frequency:	BLE: 2402~2480MHz Bluetooth: 2402~2480MHz 2.4G Wi-Fi: 802.11b/g/n HT20: 2412~2462MHz 802.11n HT40: 2422~2452MHz 5G Wi-Fi: 802.11a/n(HT20)/ac (VHT20): U-NII-1: 5180-5240MHz, U-NII-2A: 5260-5320MHz(DFS), U-NII-2C: 5500-5700MHz(DFS), U-NII-3: 5745-5825MHz 802.11n(HT40)/ac (VHT40): U-NII-1: 5190-5230MHz, U-NII-2A: 5270-5310MHz(DFS), U-NII-2C: 5510-5670MHz(DFS), U-NII-3: 5755-5795MHz 802.11ac (VHT80): U-NII-1: 5210MHz, U-NII-2A: 5290MHz(DFS), U-NII-2C: 5530-5610MHz(DFS), U-NII-3: 5775MHz NFC: 13.56MHz GSM/GPRS/EDGE 850: 824~849MHz GSM/GPRS/EDGE 1900: 1850~1910MHz WCDMA Band II: 1850~1910MHz WCDMA Band IV:1710~1755MHz WCDMA Band V: 824~849MHz LTE Band 2: 1850~1910MHz LTE Band 4: 1710~1755MHz
----------------------	--

	LTE Band 5: 824~849MHz LTE Band 7: 2500~2570MHz LTE Band 13: 777~787MHz
Max. RF output power:	LE 1M: -2.91dBm, LE 2M: -2.98dBm Bluetooth: 8.54dBm 2.4G Wi-Fi: 22.50dBm 5G Wi-Fi: U-NII-1: 12.11dBm U-NII-2A: 11.84dBm U-NII-2C: 12.11dBm U-NII-3: 11.96dBm NFC: -41.18dBm EIRP GSM 850: 32.83dBm GSM 1900: 29.23dBm WCDMA Band II: 22.77dBm WCDMA Band IV: 23.42dBm WCDMA Band V: 23.23dBm LTE Band 2: 22.58dBm LTE Band 4: 21.34dBm LTE Band 5: 24.31dBm LTE Band 7: 22.01dBm LTE Band 13: 24.34dBm
Max.SAR:	0.885W/kg 1g Head Tissue 1.044W/kg 1g Body Tissue 1.014W/kg 1g Hotspot
Max Simultaneous SAR	1.369W/kg
Type of Modulation:	BLE: GFSK Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK 2.4G Wi-Fi: DSSS, OFDM 5G Wi-Fi: OFDM NFC: ASK GSM,GPRS: GMSK EDGE: GMSK, 8PSK WCDMA: BPSK LTE: QPSK, 16QAM
Antenna installation	BLE/Bluetooth/2.4G Wi-Fi/5G Wi-Fi: FPC Antenna NFC: FPC Antenna GSM/WCDMA/LTE: FPC Antenna
Antenna Gain:	BLE/Bluetooth/2.4G Wi-Fi: -0.1dBi 5G Wi-Fi: U-NII-1: -1.02dBi U-NII-2A: -1.21dBi U-NII-2C: -0.43dBi U-NII-3: -1.63dBi NFC: 0dBi GSM 850: -3.70dBi GSM 1900: 0.23dBi WCDMA Band II: 0.23dBi WCDMA Band IV: 0.05dBi WCDMA Band V: -3.70dBi LTE Band 2: 0.23dBi

LTE Band 4: 0.05dBi
LTE Band 5: -3.70dBi
LTE Band 7: -1.59dBi
LTE Band 13: -5.24dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings: Battery: DC 3.87V, 5900mAh, 22.833Wh

Adapter: Model: 805A-018B-1A

Input: 100-240V~, 50/60Hz, 0.5A

Output: 5.0V===3.0A, 9.0V===2.0A, 12.0V===1.5A MAX

4.3 Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

5 Summary of Test Results

The maximum results of Specific Absorption Rate (SAR) have found during testing are as follows:

Frequency Band	Head SAR	Body-worn (10mm Gap)	Hotspot (10mm Gap)	SAR _{1g} Limit (W/kg)
	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	Maximum SAR _{1g} (W/kg)	
GSM 850	0.885	0.326	0.298	1.6
GSM 1900	0.464	0.672	0.659	1.6
WCDMA BAND II	0.593	0.920	0.910	1.6
WCDMA BAND IV	0.581	1.044	1.010	1.6
WCDMA BAND V	0.867	0.301	0.306	1.6
LTE Band 2	0.629	1.028	1.014	1.6
LTE Band 4	0.486	0.936	0.906	1.6
LTE Band 5	0.400	0.411	0.429	1.6
LTE Band 7	0.852	0.752	0.987	1.6
LTE Band 13	0.234	0.225	0.318	1.6
WLAN 2.4GHz	0.509	0.259	0.357	1.6
WLAN 5GHz	0.375	0.224	0.240	1.6
Bluetooth	0.498	0.220	0.253	1.6
Simultaneous Transmission	1.369	1.303	1.255	1.6

Remark:

The device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg) specified in FCC 47 CFR Part 2.1093 and IEEE Std C95.1: 2019, and had been tested in accordance with the measurement methods and procedure specified in KDB 865664 D01 v01r04, KDB 865664 D02 v01r02 and KDB 941225 D06.

6 Equipment Used during Test

6.1 Equipment List

Name of Equipment	Manufacturer	Type/Model	Serial Number	Calibration Date	Calibration Due
6 AXIS ROBOT	KUKA	KR6 R900 SIXX	502635	N/A	N/A
SATIMO Test Software	MVG	OPENSAR	OPENSAR V 4 02 27	N/A	N/A
PHANTOM TABLE	MVG	N/A	SAR_1215_01	N/A	N/A
SAM PHANTOM	MVG	SAM118	SN 11/15 SAM118	N/A	N/A
MultiMeter	Keithley	MiltiMeter 2000	4073942	2026-02-25	2027-02-24
S-Parameter Network Analyzer	Agilent	8753E	JP38160684	2025-09-15	2026-09-14
Universal Radio Communication Tester	ROHDE&SCHWARZ	CMU200	114798	2025-07-04 2026-07-01	2026-07-03 2027-06-30
Wideband Radio Communication Tester	ROHDE&SCHWARZ	CMW500	127818	2025-07-04 2026-07-01	2026-07-03 2027-06-30
E-Field Probe	MVG	SSE2	2523-EPGO-417	2025-07-25	2026-07-24
DIPOLE 750	MVG	SID750	SN 09/15 DIP 0G750-357	2023-08-08	2026-08-07
DIPOLE 835	MVG	SID835	SN 09/15 DIP 0G835-358	2023-08-08	2026-08-07
DIPOLE 1800	MVG	SID1800	SN 09/15 DIP 1G800-360	2023-08-08	2026-08-07
DIPOLE 1900	MVG	SID1900	SN 09/15 DIP 1G900-361	2023-08-08	2026-08-07
DIPOLE 2450	MVG	SID2450	SN 09/15 DIP 2G450-363	2023-08-08	2026-08-07
DIPOLE 2600	MVG	SID2600	SN 16/15 DIP 2G600-376	2023-08-08	2026-08-07
Limesar Dielectric Probe	MVG	SCLMP	SN 11/15 OCPG 69	2026-02-24	2027-02-23
Power Amplifier	BONN	BLWA 0830 -160/100/40D	128740	2025-07-04 2026-07-01	2026-07-03 2027-06-30
Signal Generator	R&S	SMB100A	105942	2025-07-04 2026-07-01	2026-07-03 2027-06-30
Power Meter	R&S	NRP2	102031	2025-07-04 2026-07-01	2026-07-03 2027-06-30
Power Meter	R&S	NRVD	102284	2025-07-04 2026-07-01	2026-07-03 2027-06-30
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340009	2025-07-04 2026-07-01	2026-07-03 2027-06-30
USB Wideband Power Sensor	Malaysia Keysight	U2021XA	MY54340010	2025-07-04 2026-07-01	2026-07-03 2027-06-30

7 SAR Introduction

7.1 Introduction

This measurement report shows compliance of the EUT with IEEE Std C95.1: 2019 and FCC 47 CFR Part2 (2.1093). The test procedures, as described in IEC/IEEE 62209-1528: 2020 Standard for Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)

7.2 SAR Definition

- ☐ SAR : Specific Absorption Rate
- ☐ The SAR characterize the absorption of energy by a quantity of tissue
- ☐ This is related to a increase of the temperature of these tissues during a time period.

$$DAS = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dV} \right)$$

$$DAS = \frac{\sigma E^2}{\rho}$$

$$DAS = c_h \left. \frac{dT}{dt} \right|_{t=0}$$

SAR definition

$$SAR = \frac{\sigma E^2}{\rho}$$

- ☐ SAR : Specific Absorption Rate

- σ : Liquid conductivity

$$\circ \epsilon_r = \epsilon' - j\epsilon'' \text{ (complex permittivity of liquid)}$$

$$\circ \sigma = \frac{\epsilon'' \omega}{\epsilon_0}$$

- ρ : Liquid density


$$\circ \rho = 1000 \text{ g/L} = 1000 \text{ Kg/m}^3$$

where:

σ = conductivity of the tissue (S/m)
 ρ = mass density of the tissue (kg/m³)
 E = rms electric field strength (V/m)

8 SAR Measurement Setup

SAR bench sub-systems





Scanning System (robot)

- ✘ It must be able to scan all the volume of the phantom to evaluate the tridimensional distribution of SAR.
- ✘ Must be able to set the probe orthogonal of the surface of the phantom ($\pm 30^\circ$).
- ✘ Detects stresses on the probe and stop itself if necessary to keep the integrity of the probe.




SAM Phantom (Specific Anthropomorphic Mannequin)

- ✦ The probe scanning of the E-Field is done in the 2 half of the normalized head.
- ✦ The normalized shape of the phantom corresponds to the dimensions of 90% of an adult head size.
- ✦ The materials for the phantom should not affect the radiation of the device under test (DUT)
 - Permittivity < 5
- ✦ The head is filled with tissue simulating liquid.
- ✦ The hand holding the DUT does not have to be modeled.



Bi-section sagittale du fantôme avec périmètre étendu (montrée sur le côté comme lors des essais de DAS de l'appareil)



The OPENSAR system for performing compliance tests consist of the following items:

1. A standard high precision 6-axis robot (KUKA) with controller and software.
2. KUKA Control Panel (KCP).
3. A dosimetric probe, i.e., an isotropic E-field probe optimized and calibrated for usage in tissue simulating liquid. The probe is equipped with an optical surface detector system.
4. The functions of the PC plug-in card are to perform the time critical task such as signal filtering, surveillance of the robot operation fast movement interrupts.
5. A computer operating Windows 7.
6. OPENSAR software.
7. Remote control with teaches pendant and additional circuitry for robot safety such as warning lamps, etc.
8. The SAM phantom enabling testing left-hand right-hand and body usage.
9. The Position device for handheld EUT.
10. Tissue simulating liquid mixed according to the given recipes (see Application Note).
11. System validation dipoles to validate the proper functioning of the system.

Data Evaluation

The OPENSAR software automatically executes the following procedure to calculate the field units from the microvolt readings at the probe connector. The parameters used in the valuation are stored in the configuration modules of the software:

Probe Parameters	- Sensitivity	Norm _i
	- Conversion factor	ConvFi
	- Diode compression point Dcpi	
Device Parameter	- Frequency	f
	- Crest factor	cf
Media Parametrs	- Conductivity	σ
	- Density	ρ

These parameters must be set correctly in the software. They can either be found in the component documents or be imported into the software from the configuration files issued for the OPENSAR components.

The first step of the evaluation is a linearization of the filtered input signal to account for the compression characteristics of the detector diode. The compensation depends on the input signal, the diode type and the DC-transmission factor from the diode to the evaluation electronics. If the exciting field is pulsed, the crest factor of the signal must be known to correctly compensate for peak power. The formula for each channel can be given as

$$V_i = U_i + U_i^2 \cdot \frac{cf}{dcp_i}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

U_i = Input signal of channel i ($i = x, y, z$)

cf = Crest factor of exciting field (DASY parameter)

dcp_i = Diode compression point (DASY parameter)

From the compensated input signals the primary field data for each channel can be evaluated:

$$\text{E-field probes: } E_i = \sqrt{\frac{V_i}{\text{Norm}_i \cdot \text{ConvF}}}$$

$$\text{H-field probes: } H_i = \sqrt{V_i} \cdot \frac{a_{i0} + a_{i1}f + a_{i2}f^2}{f}$$

Where V_i = Compensated signal of channel i ($i = x, y, z$)

Norm_i = Sensor sensitivity of channel i ($i = x, y, z$)
μV/(V/m)² for E0field Probes

ConvF = Sensitivity enhancement in solution

a_{ij} = Sensor sensitivity factors for H-field probes

$$\begin{aligned}
 f &= \text{Carrier frequency (GHz)} \\
 E_i &= \text{Electric field strength of channel } i \text{ in V/m} \\
 H_i &= \text{Magnetic field strength of channel } i \text{ in A/m}
 \end{aligned}$$

The RSS value of the field components gives the total field strength (Hermitian magnitude):

$$E_{\text{tot}} = \sqrt{E_x^2 + E_y^2 + E_z^2}$$

The primary field data are used to calculate the derived field units.

$$SAR = E_{\text{tot}}^2 \cdot \frac{\sigma}{\rho \cdot 1000}$$

$$\begin{aligned}
 \text{where } SAR &= \text{local specific absorption rate in mW/g} \\
 E_{\text{tot}} &= \text{total field strength in V/m} \\
 \sigma &= \text{conductivity in [mho/m] or [siemens/m]} \\
 \rho &= \text{equivalent tissue density in g/cm}^3
 \end{aligned}$$

Note that the density is normally set to 1 (or 1.06), to account for actual brain density rather than the density of the simulation liquid.

The power flow density is calculated assuming the excitation field as a free space field.

$$P_{\text{pwe}} = \frac{E_{\text{tot}}^2}{3770} \quad \text{or} \quad P_{\text{pwe}} = H_{\text{tot}}^2 \cdot 37.7$$

$$\begin{aligned}
 \text{where } P_{\text{pwe}} &= \text{Equivalent power density of a plane wave in mW/cm}^2 \\
 E_{\text{tot}} &= \text{total electric field strength in V/m} \\
 H_{\text{tot}} &= \text{total magnetic field strength in A/m}
 \end{aligned}$$

SAR Evaluation – Peak Spatial - Average

The procedure for assessing the peak spatial-average SAR value consists of the following steps

- **Power Reference Measurement**

The reference and drift jobs are useful jobs for monitoring the power drift of the device under test in the batch process. Both jobs measure the field at a specified reference position, at a selectable distance from the phantom surface. The reference position can be either the selected section's grid reference point or a user point in this section. The reference job projects the selected point onto the phantom surface, orients the probe perpendicularly to the surface, and approaches the surface using the selected detection method.

- **Area Scan**

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a finer measurement around the hot spot. The sophisticated interpolation routines implemented in OPENSAR software can find the maximum locations even in relatively coarse grids. The scan area is defined by an editable grid. This grid is anchored at the grid reference point of the selected section in the phantom. When the area scan's property sheet is brought-up, grid was at to 15 mm by 15 mm and can be edited by a user.

- **Zoom Scan**

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 g and 10 g of simulated tissue. The default zoom scan measures 5 x 5 x 7 points within a cube whose base faces are centered around the maximum found in a preceding area scan job within the same procedure. If the preceding Area Scan job indicates more than one maximum, the number of Zoom Scans has to be enlarged accordingly (The default number inserted is 1).

- **Power Drift measurement**

The drift job measures the field at the same location as the most recent reference job within the same procedure, and with the same settings. The drift measurement gives the field difference in dB from the reading conducted within the last reference measurement. Several drift measurements are possible for one reference measurement. This allows a user to monitor the power drift of the device under test within a batch process. In the properties of the Drift job, the user can specify a limit for the drift and have OPENSAR software stop the measurements if this limit is exceeded.

SAR Evaluation – Peak SAR

The procedure for spatial peak SAR evaluation has been implemented according to the IEEE1528 standard. It can be conducted for 1 g and 10 g. The OPENSAR system allows evaluations that combine measured data and robot positions, such as:

- maximum search
- extrapolation
- boundary correction
- peak search for averaged SAR

During a maximum search, global and local maximum searches are automatically performed in 2-D after each Area Scan measurement with at least 6 measurement points. It is based on the evaluation of the local SAR gradient calculated by the Quadratic Shepard's method. The algorithm will find the global maximum and all local maxima within -2 dB of the global maxima for all SAR distributions.

Extrapolation

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. Several measurements at different distances are necessary for the extrapolation. They are used in the Cube Scan to obtain SAR values between the lowest measurement points and the inner phantom surface. The routine uses the fourth order least square polynomial method for extrapolation. For a grid using 5x5x7 measurement points with 5mm resolution amounting to 343 measurement points, the uncertainty of the extrapolation routines is less than 1% for 1 g and 10 g cubes.

Definition of Reference Points

Ear Reference Point

Figure 6.2 shows the front, back and side views of the SAM Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERPs are 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 6.1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 6.1). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 6.1 Close-up side view of ERP's



Figure 6.2 Front, back and side view of SAM

Device Reference Points

Two imaginary lines on the device need to be established: the vertical centerline and the horizontal line. The test device is placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Fig. 6.3). The “test device reference point” is then located at the same level as the center of the ear reference point. The test device is positioned so that the “vertical centerline” is bisecting the front surface of the device at it's top and bottom edges, positioning the “ear reference point” on the outer surface of both the left and right head phantoms on the ear reference point [5].




Figure 6.3 Handset Vertical Center & Horizontal Line Reference Points

Test Configuration – Positioning for Cheek / Touch

1. Position the device close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure below), such that the plane defined by the vertical center line and the horizontal line of the device is approximately parallel to the sagittal plane of the phantom




Figure 7.1 Front, Side and Top View of Cheek/Touch Position

2. Translate the device towards the phantom along the line passing through RE and LE until the device touches the ear.
3. While maintaining the device in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to MB-NF including the line MB (called the reference plane).
4. Rotate the device around the vertical centerline until the device (horizontal line) is symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE and maintaining the device contact with the ear, rotate the device about the line NF until any point on the device is in contact with a phantom point below the ear (cheek). See Figure below.




Figure 7.2 Side view w/ relevant markings

Test Configuration – Positioning for Ear / 15° Tilt

With the test device aligned in the Cheek/Touch Position”:

1. While maintaining the orientation of the device, retract the device parallel to the reference plane far enough to enable a rotation of the device by 15 degrees.
2. Rotate the device around the horizontal line by 15 degrees.
3. While maintaining the orientation of the device, move the device parallel to the reference plane until any part of the device touches the head. (In this position, point A is located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact is at any location other than the pinna, the angle of the device shall be reduced. The tilted position is obtained when any part of the device is in contact with the ear as well as a second part of the device is in contact with the head (see Figure below).





Figure 7.3 Front, Side and Top View of Ear/15° Tilt Position

Test Position – Body Configurations

Body Worn Position

- (a) To position the device parallel to the phantom surface with either keypad up or down.
- (b) To adjust the device parallel to the flat phantom.
- (c) To adjust the distance between the device surface and the flat phantom to 1.0 cm or holster surface and the flat phantom to 0 cm.



9 Exposure limit

In order for users to be aware of the body-worn operating requirements for meeting RF exposure compliance, operating instructions and cautions statements are included in the user's manual.

Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 8.1 Human Exposure Limits

	UNCONTROLLED ENVIRONMENT General Population (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT Professional Population (W/kg) or (mW/g)
SPATIAL PEAK SAR ¹ Brain	1.60	8.00
SPATIAL AVERAGE SAR ² Whole Body	0.08	0.40
SPATIAL PEAK SAR ³ Hands, Feet, Ankles, Wrists	4.00	20.00


¹ The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

² The Spatial Average value of the SAR averaged over the whole body.

³ The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

10 System and liquid validation

10.1 System validation



Verification Setup Block Diagram



Dipole Antenna Setup Photo

The system performance check verifies that the system operates within its specifications. System and operator errors can be detected and corrected. It is recommended that the system performance check be performed prior to any usage of the system in order to guarantee reproducible results. The system performance check uses normal SAR measurements in a simplified setup with a well characterized source. This setup was selected to give a high sensitivity to all parameters that might fail or vary over time. The system check does not intend to replace the calibration of the components, but indicates situations where the system uncertainty is exceeded due to drift or failure.

In the simplified setup for system evaluation, the DUT is replaced by a calibrated dipole and the power source is replaced by a continuous wave that comes from a signal generator. The calibrated dipole must be placed beneath the flat phantom section of the SAM twin phantom with the correct distance holder. The distance holder should touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The equipment setup is shown below:

1. Signal Generator
2. Amplifier
3. Directional Coupler
4. Power Meter
5. Calibrated Dipole

The output power on dipole port must be calibrated to 30 dBm (1000 mW) before dipole is connected.

Numerical reference SAR values (W/kg) for reference dipole and flat phantom

Frequency (MHz)	1g SAR	10g SAR	Local SAR at surface(above feed-point)	Local SAR at surface(y = 2 cm offset from feedpoint)
300	3.02	2.04	4.40	2.10
450	4.92	3.28	7.20	3.20
750	8.49	5.55	12.6	4.59
835	9.56	6.22	14.1	4.90
900	10.9	6.99	16.4	5.40
1450	29.0	16.0	50.2	6.50
1800	38.4	20.1	69.5	6.80
1900	39.7	20.5	72.1	6.60
2000	41.1	21.1	74.6	6.50
2450	52.4	24.0	104	7.70
2600	55.3	24.6	113	8.29
3000	63.8	25.7	140	9.50

Table 1: system validation (1g)

Measurement Date	Frequency (MHz)	Liquid Type (head/body)	1W Target SAR1g (W/kg)	Measured SAR1g (W/kg)	1W Normalized SAR1g (W/kg)	Desired Tolerance (%)	Actual Tolerance (%)
2026-06-22	750	head	8.78	0.931	9.31	±10	6.04
2026-06-23	835	head	9.57	0.927	9.27	±10	-3.13
2026-06-15	1800	head	38.73	4.122	41.22	±10	6.43
2026-06-16	1900	head	39.51	4.139	41.39	±10	4.76
2026-07-13	2450	head	54.33	5.540	55.40	±10	1.97
2026-06-17	2600	head	56.23	5.438	54.38	±10	-3.29

Remark: 1. system check input power: 100mW.

2. Referring to IEEE 1528:2013, Section 8.2, The system check shall be performed at a test frequency that is within ±10% or ±100 MHz of the compliance test mid-band frequency, so the 1750 MHz system verification is made of 1800MHz Dipole.

10.2 liquid validation

The dielectric parameters were checked prior to assessment using the HP85070C dielectric probe kit. The dielectric parameters measured are reported in each correspondent section.

KDB 865664 recommended Tissue Dielectric Parameters

The head and body tissue parameters given in this below table should be used to measure the SAR of transmitters operating in 100 MHz to 6 GHz frequency range. The tissue dielectric parameters of the tissue medium at the test frequency should be within the tolerance required in this document. The dielectric parameters should be linearly interpolated between the closest pair of target frequencies to determine the applicable dielectric parameters corresponding to the device test frequency.

The head tissue dielectric parameters recommended by IEEE Std 1528-2013 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness variations in a human head. Other head and body tissue parameters that have not been specified in 1528 are derived from tissue dielectric parameters computed from the 4-Cole-Cole equations described above and extrapolated according to the head parameters specified in 1528.

Target Frequency	Head Tissue		Body Tissue	
MHz	ϵ_r	σ (S/m)	ϵ_r	σ (S/m)
150	52.3	0.76	61.9	0.80
300	45.3	0.87	58.2	0.92
450	43.5	0.87	56.7	0.94
750	41.9	0.89	55.5	0.96
835	41.5	0.90	55.2	0.97
900	41.5	0.97	55.0	1.05
915	41.5	0.98	55.0	1.06
1450	40.5	1.20	54.0	1.30
1610	40.3	1.29	53.8	1.40
1800-2000	40.0	1.40	53.3	1.52
2450	39.2	1.80	52.7	1.95
2600	39.0	1.96	52.5	2.16
3000	38.5	2.40	52.0	2.73
5800	35.3	5.27	48.2	6.00

Tissue Dielectric Parameters for Head and Body Phantoms

The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 in P1528 have been incorporated in the following table. These head parameters are derived from planar layer models simulating the highest expected SAR for the dielectric properties and tissue thickness Power drifts in a human head. Other head and body tissue parameters that have not been specified in P1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations described in Reference [12] and extrapolated according to the head parameters specified in P1528.

Table 2: Recommended Dielectric Performance of Tissue

Recommended Dielectric Performance of Tissue						
Head/Body						
Ingredients (% by weight)	Frequency (MHz)					
	750	835	1800	1900	2450	2600
Water	40.52	41.45	55.2	54.9	62.7	54.8
Salt (Nacl)	1.61	1.45	0.3	0.18	0.5	0.1
Sugar	57.67	56.0	0.0	0.0	0.0	0.0
HEC	0.1	1.0	0.0	0.0	0.0	0.0
Bactericide	0.1	0.1	0.0	0.0	0.0	0.0
Triton x-100	0.0	0.0	0.0	0.0	36.8	0.0
DGBE	0.0	0.0	44.5	44.92	0.0	45.1

Table 3: Dielectric Performance of Head Tissue Simulating Liquid


Temperature: 23.5°C , Relative humidity: 23.9%				
Frequency(MHz)	Measured Date	Description	Dielectric Parameters	
			ϵ_r	$\sigma(\text{s/m})$
750	2026-06-22	Target Value $\pm 5\%$ window	41.90 39.81 — 44.00	0.89 0.85 — 0.93
		Measurement Value	41.75	0.90
835	2026-06-23	Target Value $\pm 5\%$ window	41.50 39.43 — 43.58	0.90 0.86 — 0.95
		Measurement Value	41.50	0.90
1800	2026-06-15	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	38.61	1.34
1900	2026-06-16	Target Value $\pm 5\%$ window	40.00 38.00 — 42.00	1.40 1.33 — 1.47
		Measurement Value	38.97	1.35
2450	2026-07-13	Target Value $\pm 5\%$ window	39.2 37.24 — 41.16	1.80 1.71 — 1.89
		Measurement Value	39.23	1.79
2600	2026-06-17	Target Value $\pm 5\%$ window	39.0 37.05 — 40.95	1.96 1.87 — 2.05
		Measurement Value	39.09	1.89

System Verification Plots


Product Description: Dipole

Model: SID750


Test Date: 2026-06-22






Product Description: Dipole
Model: SID835
Test Date: 2026-06-23






Product Description: Dipole
Model: SID1800
Test Date: 2026-06-15




Product Description: Dipole
Model: SID1900
Test Date: 2026-06-16

Medium(liquid type)	HL1900
Frequency (MHz)	1900.000
Relative permittivity (real part)	38.97
Conductivity (S/m)	1.35
Input power	100mW
Crest factor	1.0
E-Field Probe	2523-EPGO-417
Conversion Factor	2.82
Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Variation (%)	-3.22
SAR 10g (W/kg)	2.137236
SAR 1g (W/kg)	4.139088
SURFACE SAR	VOLUME SAR
	
	

Product Description: Dipole
Model: SID2450
Test Date: 2026-07-13

Medium(liquid type)	HL2450
Frequency (MHz)	2450.000
Relative permittivity (real part)	39.23
Conductivity (S/m)	1.79
Input power	100mW
Crest factor	1.0
E-Field Probe	2523-EPGO-417
Conversion Factor	3.02
Area Scan	dx=8mm dy=8mm
Zoom Scan	dx=5mm dy=5mm dz=4mm
Variation (%)	2.47
SAR 10g (W/kg)	2.710059
SAR 1g (W/kg)	5.539560
SURFACE SAR	VOLUME SAR
	
	

Product Description: Dipole
Model: SID2600
Test Date: 2026-06-17



11 Type a Measurement Uncertainty

The component of uncertainty may generally be categorized according to the methods used to evaluate them. The evaluation of uncertainty by the statistical analysis of a series of observations is termed a Type A evaluation of uncertainty. The evaluation of uncertainty by means other than the statistical analysis of a series of observation is termed a Type B evaluation of uncertainty. Each component of uncertainty, however evaluated, is represented by an estimated standard deviation, termed standard uncertainty, which is determined by the positive square root of the estimated variance

A Type A evaluation of standard uncertainty may be based on any valid statistical method for treating data. This includes calculating the standard deviation of the mean of a series of independent observations; using the method of least squares to fit a curve to the data in order to estimate the parameter of the curve and their standard deviations; or carrying out an analysis of variance in order to identify and quantify random effects in certain kinds of measurement.

A type B evaluation of standard uncertainty is typically based on scientific judgment using all of the relevant information available. These may include previous measurement data, experience and specification, data provided in calibration reports and uncertainties assigned to reference data taken from handbooks. Broadly speaking, the uncertainty is either obtained from an outdoor source or obtained from an assumed distribution, such as the normal distribution, rectangular or triangular distributions indicated in Table below :

Uncertainty Distribution	Normal	Rectangle	Triangular	U Shape
Multi-plying Factor(a)	$1/k(b)$	$1 / \sqrt{3}$	$1 / \sqrt{6}$	$1 / \sqrt{2}$

(a) standard uncertainty is determined as the product of the multiplying factor and the estimated range of variations in the measured quantity

(b) k is the coverage factor

Standard Uncertainty for Assumed Distribution

The combined standard uncertainty of the measurement result represents the estimated standard deviation of the result. It is obtained by combining the individual standard uncertainties of both Type A and Type -sum- by taking the positive square root of the estimated variances.

Expanded uncertainty is a measure of uncertainty that defines an interval about the measurement result within which the measured value is confidently believed to lie. It is obtained by multiplying the combined standard uncertainty by a coverage factor. Typically, the coverage factor ranges from 2 to 3. Using a coverage factor allows the true value of a measured quantity to be specified with a defined probability within the specified uncertainty range. For purpose of this document, a coverage factor two is used, which corresponds to confidence interval of about 95 %.

The COMOSAR Uncertainty Budget is show in below table:

UNCERTAINTY FOR SYSTEM PERFORMANCE CHECK								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+- %)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{Cp})^{1/2}$	$(1_{Cp})^{1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{1/2}$	$(Cp)^{1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	0.00	N	1	1	1	0.00	0.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algorithms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Dipole								
Deviation of experimental source from numerical source	4.00	N	1	1	1	4.00	4.00	∞
Input power and SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
Dipole axis to liquid Distance	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.21	10.12	
Expanded Uncertainty (95% Confidence interval)		k				19.91	19.73	

UNCERTAINTY EVALUATION FOR HANDSET SAR TEST								
a	c	d	e= f(d,k)	f	g	h= c*f/e	i= c*g/e	k
Uncertainty Component	Tol (+-%)	Prob. Dist.	Div.	Ci (1g)	Ci (10g)	1g Ui (+-%)	10g Ui (+-%)	Vi
Measurement System								
Probe calibration	5.8	N	1	1	1	5.80	5.80	∞
Axial Isotropy	3.5	R	$\sqrt{3}$	$(1_{Cp})^{\wedge 1/2}$	$(1_{Cp})^{\wedge 1/2}$	1.43	1.43	∞
Hemispherical Isotropy	5.9	R	$\sqrt{3}$	$(Cp)^{\wedge 1/2}$	$(Cp)^{\wedge 1/2}$	2.41	2.41	∞
Boundary effect	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Linearity	4.7	R	$\sqrt{3}$	1	1	2.71	2.71	∞
System detection limits	1.0	R	$\sqrt{3}$	1	1	0.58	0.58	∞
Modulation response	3.00	N	1	1	1	3.00	3.00	∞
Readout Electronics	0.50	N	1	1	1	0.50	0.50	∞
Reponse Time	0.0	R	$\sqrt{3}$	1	1	0.00	0.00	∞
Integration Time	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
RF ambient Conditions - Noise	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
RF ambient Conditions - Reflections	3.0	R	$\sqrt{3}$	1	1	1.73	1.73	∞
Probe positioner Mechanical Tolerance	1.4	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Probe positioning with respect to Phantom Shell	1.40	R	$\sqrt{3}$	1	1	0.81	0.81	∞
Extrapolation, interpolation and integration Algoritms for Max. SAR Evaluation	2.3	R	$\sqrt{3}$	1	1	1.33	1.33	∞
Test sample Related								
Test sample positioning	2.60	N	1	1	1	2.60	2.60	N-1
Device Holder Uncertainty	3.00	N	1	1	1	3.00	3.00	N-1
Output power Variation - SAR drift measurement	5.00	R	$\sqrt{3}$	1	1	2.89	2.89	∞
SAR scaling	2.00	R	$\sqrt{3}$	1	1	1.15	1.15	∞
Phantom and Tissue Parameters								
Phantom Uncertainty (Shape and thickness tolerances)	4.00	R	$\sqrt{3}$	1	1	2.31	2.31	∞
Uncertainty in SAR correction for deviation (in permittivity and conductivity)	2.00	N	1	1	1	2.00	1.68	∞
Liquid conductivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid conductivity - measurement uncertainty	4.00	N	1	0.23	0.26	0.92	1.04	M
Liquid permittivity (temperature uncertainty)	2.50	N	1	0.78	0.71	1.95	1.77	∞
Liquid permittivity - measurement uncertainty	5.00	N	1	0.23	0.26	1.15	1.30	M
Combined Standard Uncertainty		RSS				10.63	10.54	
Expanded Uncertainty (95% Confidence interval)		k				20.73	20.56	

12 Output Power Verification

12.1 Test Condition

1. Conducted Measurement
EUT was set for low, mid, high channel with modulated mode and highest RF output power. The base station simulator was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ± 1.5 dB.
3. Environmental Conditions

Temperature	25.3°C
Relative Humidity	59.2%
Atmospheric Pressure	1015mbar

12.2 Test Procedures

Smart Phone radio output power measurement

1. The transmitter output port was connected to base station emulator.
2. Establish communication link between emulator and EUT and set EUT to operate at maximum output power all the time.
3. Select lowest, middle, and highest channels for each band and different possible test mode.
4. Measure the conducted peak burst power and conducted average burst power from EUT antenna port.

Other radio output power measurement:

The output power was measured using power meter at low, mid, and hi channels.

Source-based Time Averaged Burst Power Calculation:

For TDMA, the following duty cycle factor was used to calculate the source-based time average power

Number of Time slot	1	2	3	4
Duty Cycle	1:8	1:4	1:2.66	1:2
Duty cycle factor	-9.03 dB	-6.02 dB	-4.26 dB	-3.01 dB
Crest Factor	8	4	2.66	2

Remark: *Time slot duty cycle factor = $10 * \log(\text{Time Slot Duty Cycle})$*

Source based time averaged power = Maximum burst averaged power (1 Uplink) – 9.03 dB

Source based time averaged power = Maximum burst averaged power (2 Uplink) – 6.02 dB

Source based time averaged power = Maximum burst averaged power (3 Uplink) – 4.26 dB

Source based time averaged power = Maximum burst averaged power (4 Uplink) – 3.01 dB

12.3 Test Result

Summary of Power Reduction:

1. Device is support Receiver ON/OFF. There are Bluetooth & Wi-Fi & GSM850/1900W&CDMA B5 <E B5/7/13 support Receiver OFF. There are WCDMA B2/4 & LTE B2/4 support Receiver ON reduced power.

Receiver OFF	Receiver ON
Power Level P1	Power Level P2

Note:

The power management for SAR compliance at different exposure conditions (head, hotspot).

The device will invoke corresponding work scenarios power level base on frequency bands/antennas.

Refer to the KDB388624 D02 Pre-Approval Guidance List v18r03.

Power Level P1:

Burst Average Power (dBm)								
Band	GSM 850				GSM 1900			
Channel	128	190	251	Tune up Power tolerant	512	661	810	Tune up Power tolerant
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice	32.61	32.78	32.83	32.9±1	29.23	29.23	29.19	29.3±1
GPRS 1 slots	32.51	32.73	32.81	32.9±1	27.49	28.37	29.18	29.2±1
GPRS 2 slots	30.54	30.81	30.81	30.9±1	25.47	26.40	27.21	27.3±1
GPRS 3 slots	29.94	30.24	30.29	30.3±1	23.57	24.38	25.24	25.3±1
GPRS 4 slots	27.92	28.20	28.32	28.4±1	21.46	22.37	23.14	23.2±1
EGPRS 1 slots	27.38	27.51	27.60	27.6±1	24.69	25.42	25.97	26.0±1
EGPRS 2 slots	26.34	26.59	26.65	26.7±1	23.65	24.48	24.94	25.0±1
EGPRS 3 slots	24.30	24.55	24.50	24.6±1	21.56	22.36	22.81	22.9±1
EGPRS 4 slots	22.29	22.56	22.59	22.6±1	19.51	20.41	20.89	20.9±1
Remark : GPRS, CS1 coding scheme. EGPRS, MCS5 coding scheme. Multi 1 Slot , Support Max 4 downlink, 1 uplink , 5 working link Multi 2 Slots , Support Max 4 downlink, 2 uplink , 5 working link Multi 3 Slots , Support Max 4 downlink, 3 uplink , 5 working link Multi 4 Slots , Support Max 4 downlink, 4 uplink , 5 working link								

Source Based time Average Power (dBm)								
Band	GSM 850				GSM 1900			
Channel	128	190	251	Time Average factor	512	661	810	Time Average factor
Frequency (MHz)	824.2	836.6	848.8	/	1850.2	1880	1909.8	/
GSM Voice	23.58	23.75	23.80	-9.03	20.20	20.20	20.16	-9.03
GPRS 1 slots	23.48	23.70	23.78	-9.03	18.46	19.34	20.15	-9.03
GPRS 2 slots	24.52	24.79	24.79	-6.02	19.45	20.38	21.19	-6.02
GPRS 3 slots	25.68	25.98	26.03	-4.26	19.31	20.12	20.98	-4.26
GPRS 4 slots	24.91	25.19	25.31	-3.01	18.45	19.36	20.13	-3.01
EGPRS 1 slots	18.35	18.48	18.57	-9.03	15.66	16.39	16.94	-9.03
EGPRS 2 slots	20.32	20.57	20.63	-6.02	17.63	18.46	18.92	-6.02
EGPRS 3 slots	20.04	20.29	20.24	-4.26	17.30	18.10	18.55	-4.26
EGPRS 4 slots	19.28	19.55	19.58	-3.01	16.50	17.40	17.88	-3.01
Remark : Time average factor = 1 uplink , $10 \cdot \log(1/8) = -9.03\text{dB}$, 2 uplink , $10 \cdot \log(2/8) = -6.02\text{dB}$, 3 uplink , $10 \cdot \log(3/8) = -4.26\text{dB}$, 4 uplink , $10 \cdot \log(4/8) = -3.01\text{dB}$ Source based time average power = Burst Average power + Time Average factor								

Note: DUT was set in GPRS(3Tx slots) for GSM 850, and GPRS(2Tx slots) for GSM 1900 due to the Maximum source-base time average output power for body SAR.

WCDMA - Average Power (dBm)								
Band	WCDMA Band II				WCDMA Band V			
Channel	9262	9400	9538	Tune up Power tolerant	4132	4183	4233	Tune up Power tolerant
Frequency (MHz)	1852.4	1880	1907.6	/	826.4	836.6	846.6	/
RMC 12.2k	22.62	22.68	22.77	22.8±1	23.23	23.21	23.13	23.3±1
HSDPA Subtest-1	21.58	21.61	21.73	21.8±1	22.22	22.21	22.08	22.3±1
HSDPA Subtest-2	21.45	21.38	21.54	21.6±1	22.11	22.00	21.89	22.2±1
HSDPA Subtest-3	20.83	20.77	21.02	20.9±1	21.47	21.49	21.29	21.5±1
HSDPA Subtest-4	20.59	20.59	20.88	20.9±1	21.23	21.35	21.12	21.4±1
HSUPA Subtest-1	21.07	21.13	21.24	21.3±1	21.69	21.69	21.62	21.7±1
HSUPA Subtest-2	20.90	20.91	21.08	21.1±1	21.49	21.50	21.50	21.5±1
HSUPA Subtest-3	21.40	21.40	21.49	21.5±1	22.41	22.40	22.41	22.5±1
HSUPA Subtest-4	20.28	20.34	20.46	20.5±1	20.99	20.88	20.90	21.0±1
HSUPA Subtest-5	21.41	21.36	21.55	21.6±1	22.53	22.41	22.32	22.6±1

WCDMA - Average Power (dBm)				
Band	WCDMA Band IV			
Channel	1312	1413	1513	Tune up Power tolerant
Frequency (MHz)	1712.4	1732.6	1752.6	/
RMC 12.2k	23.42	23.31	23.19	23.5±1
HSDPA Subtest-1	22.37	22.21	22.17	22.4±1
HSDPA Subtest-2	22.22	21.96	22.02	22.3±1
HSDPA Subtest-3	21.67	21.41	21.38	21.7±1
HSDPA Subtest-4	21.53	21.23	21.26	21.6±1
HSUPA Subtest-1	21.91	21.79	21.67	22.0±1
HSUPA Subtest-2	21.71	21.56	21.51	21.8±1
HSUPA Subtest-3	22.14	21.93	21.94	22.2±1
HSUPA Subtest-4	21.04	20.82	20.92	21.1±1
HSUPA Subtest-5	22.04	21.86	22.01	22.1±1

Power Level P2:

WCDMA - Average Power (dBm)								
Band	WCDMA Band II				WCDMA Band IV			
Channel	9262	9400	9538	Tune up Power tolerant	1312	1413	1513	Tune up Power tolerant
Frequency (MHz)	1852.4	1880	1907.6	/	1712.4	1732.6	1752.6	/
RMC 12.2k	20.62	20.78	20.71	20.8±1	21.53	21.34	21.22	21.6±1
HSDPA Subtest-1	18.05	17.83	17.46	18.1±1	18.16	17.74	18.36	18.2±1
HSDPA Subtest-2	17.88	17.59	17.30	17.9±1	17.95	17.54	18.26	18.3±1
HSDPA Subtest-3	17.26	16.96	16.72	17.3±1	17.32	17.02	17.70	17.8±1
HSDPA Subtest-4	17.15	16.85	16.59	17.2±1	17.20	16.85	17.50	17.5±1
HSUPA Subtest-1	19.65	17.52	17.63	19.7±1	17.87	18.56	18.33	18.6±1
HSUPA Subtest-2	19.46	17.29	17.49	19.5±1	17.77	18.43	18.14	18.5±1
HSUPA Subtest-3	19.85	17.68	17.87	19.9±1	18.16	18.81	18.57	18.9±1
HSUPA Subtest-4	18.75	16.65	16.84	18.8±1	17.08	17.76	17.51	17.8±1
HSUPA Subtest-5	19.77	17.68	17.93	19.8±1	18.23	18.80	18.65	18.8±1

LTE Power Reduction

The following tests were conducted according to the test requirements outlined in section 6.2 of the 3GPP TS36.101 specification.

The allowed Maximum Power Reduction (MPR) for the maximum output power due to higher order modulation and transmit bandwidth configuration (resource blocks) is specified in Table 6.2.3-1 of the 3GPP TS36.101.

Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 3

Modulation	Channel bandwidth / Transmission bandwidth (RB)						MPR (dB)
	1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2

The allowed A-MPR values specified below in Table 6.2.4.-1 of 3GPP TS36.101 are in addition to the allowed MPR requirements. All the measurements below were performed with A-MPR disabled, by using Network Signalling Value of "NS_01".

Table 6.2.4-1: Additional Maximum Power Reduction (A-MPR)

Network Signalling value	Requirements (sub-clause)	E-UTRA Band	Channel bandwidth (MHz)	Resources Blocks (N_{RB})	A-MPR (dB)
NS_01	6.6.2.1.1	Table 5.5-1	1.4, 3, 5, 10, 15, 20	Table 5.6-1	NA
NS_03	6.6.2.2.1	2, 4, 10, 23, 25, 35, 36	3	>5	≤ 1
			5	>6	≤ 1
			10	>6	≤ 1
			15	>8	≤ 1
			20	>10	≤ 1
NS_04	6.6.2.2.2	41	5	>6	≤ 1
			10, 15, 20	See Table 6.2.4-4	
NS_05	6.6.3.3.1	1	10, 15, 20	≥ 50	≤ 1
NS_06	6.6.2.2.3	12, 13, 14, 17	1.4, 3, 5, 10	Table 5.6-1	n/a
NS_07	6.6.2.2.3 6.6.3.3.2	13	10	Table 6.2.4-2	Table 6.2.4-2
NS_08	6.6.3.3.3	19	10, 15	> 44	≤ 3
NS_09	6.6.3.3.4	21	10, 15	> 40	≤ 1
				> 55	≤ 2
NS_10		20	15, 20	Table 6.2.4-3	Table 6.2.4-3
NS_11	6.6.2.2.1	23 ¹	1.4, 3, 5, 10	Table 6.2.4-5	Table 6.2.4-5
--					
NS_32	-	-	-	-	-

Note 1: Applies to the lower block of Band 23, i.e. a carrier placed in the 2000-2010 MHz region.

Power Level P1:**LTE Band 2:**

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	18607	1850.7	QPSK	1	0	22.1	22.2±1	/
				1	2	22.17	22.2±1	/
				1	5	22.05	22.2±1	/
				3	0	22.12	22.2±1	/
				3	1	22.19	22.2±1	/
				3	2	22.12	22.2±1	/
				6	0	21.14	21.2±1	1.0
			16QAM	1	0	21.17	21.3±1	1.0
				1	2	21.29	21.3±1	1.0
				1	5	21.15	21.3±1	1.0
				3	0	21.16	21.3±1	1.0
				3	1	21.23	21.3±1	1.0
				3	2	21.19	21.3±1	1.0
				6	0	20.26	20.3±1	1.0
	18900	1880	QPSK	1	0	22.21	22.4±1	/
				1	2	22.29	22.4±1	/
				1	5	22.2	22.4±1	/
				3	0	22.23	22.4±1	/
				3	1	22.31	22.4±1	/
				3	2	22.23	22.4±1	/
				6	0	21.25	21.3±1	1.0
			16QAM	1	0	21.53	21.7±1	1.0
				1	2	21.61	21.7±1	1.0
				1	5	21.55	21.7±1	1.0
				3	0	21.41	21.7±1	1.0
				3	1	21.45	21.7±1	1.0
				3	2	21.43	21.7±1	1.0
				6	0	20.14	20.2±1	1.0
	19193	1909.3	QPSK	1	0	22.29	22.5±1	/
				1	2	22.4	22.5±1	/
				1	5	22.27	22.5±1	/
				3	0	22.29	22.5±1	/
				3	1	22.42	22.5±1	/
				3	2	22.38	22.5±1	/
				6	0	21.4	21.5±1	1.0
			16QAM	1	0	21.31	21.6±1	1.0
				1	2	21.36	21.6±1	1.0
				1	5	21.33	21.6±1	1.0
				3	0	21.47	21.6±1	1.0
				3	1	21.56	21.6±1	1.0
				3	2	21.5	21.6±1	1.0
				6	0	20.54	20.6±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	18615	1851.5	QPSK	1	0	22.17	22.3±1	/
				1	8	22.29	22.3±1	/
				1	14	22.04	22.3±1	/
				6	0	21.14	21.2±1	1.0
				6	4	21.15	21.2±1	1.0
				6	9	21.09	21.2±1	1.0
				15	0	21.11	21.2±1	1.0
			16QAM	1	0	21.05	21.2±1	1.0
				1	8	21.14	21.2±1	1.0
				1	14	20.99	21.2±1	1.0
				6	0	20.26	20.3±1	1.0
				6	4	20.22	20.3±1	1.0
				6	9	20.2	20.3±1	1.0
				15	0	20.16	20.3±1	1.0
	18900	1880	QPSK	1	0	22.25	22.4±1	/
				1	8	22.4	22.4±1	/
				1	14	22.25	22.4±1	/
				6	0	21.26	21.3±1	1.0
				6	4	21.28	21.3±1	1.0
				6	9	21.2	21.3±1	1.0
				15	0	21.24	21.3±1	1.0
			16QAM	1	0	21.54	21.8±1	1.0
				1	8	21.72	21.8±1	1.0
				1	14	21.59	21.8±1	1.0
				6	0	20.31	20.4±1	1.0
				6	4	20.37	20.4±1	1.0
				6	9	20.3	20.4±1	1.0
				15	0	20.27	20.4±1	1.0
	19185	1908.5	QPSK	1	0	22.33	22.5±1	/
				1	8	22.48	22.5±1	/
				1	14	22.35	22.5±1	/
				6	0	21.43	21.5±1	1.0
				6	4	21.44	21.5±1	1.0
				6	9	21.37	21.5±1	1.0
				15	0	21.36	21.5±1	1.0
			16QAM	1	0	21.32	21.5±1	1.0
				1	8	21.49	21.5±1	1.0
				1	14	21.31	21.5±1	1.0
				6	0	20.44	20.5±1	1.0
				6	4	20.43	20.5±1	1.0
				6	9	20.4	20.5±1	1.0
				15	0	20.33	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	18625	1852.5	QPSK	1	0	22	22.3±1	/
				1	12	22.21	22.3±1	/
				1	24	21.94	22.3±1	/
				12	0	21.07	21.2±1	1.0
				12	6	21.13	21.2±1	1.0
				12	11	21.1	21.2±1	1.0
				25	0	21.09	21.2±1	1.0
			16QAM	1	0	21.2	21.4±1	1.0
				1	12	21.39	21.4±1	1.0
				1	24	21.23	21.4±1	1.0
				12	0	20.22	20.3±1	1.0
				12	6	20.21	20.3±1	1.0
				12	11	20.18	20.3±1	1.0
				25	0	20.14	20.3±1	1.0
	18900	1880	QPSK	1	0	22.12	22.4±1	/
				1	12	22.38	22.4±1	/
				1	24	22.15	22.4±1	/
				12	0	21.24	21.3±1	1.0
				12	6	21.28	21.3±1	1.0
				12	11	21.23	21.3±1	1.0
				25	0	21.21	21.3±1	1.0
			16QAM	1	0	21.66	21.9±1	1.0
				1	12	21.87	21.9±1	1.0
				1	24	21.64	21.9±1	1.0
				12	0	20.36	20.4±1	1.0
				12	6	20.39	20.4±1	1.0
				12	11	20.3	20.4±1	1.0
				25	0	20.28	20.4±1	1.0
	19175	1907.5	QPSK	1	0	22.31	22.6±1	/
				1	12	22.58	22.6±1	/
				1	24	22.33	22.6±1	/
				12	0	21.38	21.5±1	1.0
				12	6	21.45	21.5±1	1.0
				12	11	21.29	21.5±1	1.0
				25	0	21.38	21.5±1	1.0
			16QAM	1	0	21.31	21.7±1	1.0
				1	12	21.61	21.7±1	1.0
				1	24	21.37	21.7±1	1.0
				12	0	20.44	20.5±1	1.0
				12	6	20.45	20.5±1	1.0
				12	11	20.31	20.5±1	1.0
				25	0	20.32	20.5±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	18650	1855	QPSK	1	0	22.17	22.3±1	/
				1	24	22.21	22.3±1	/
				1	49	22.1	22.3±1	/
				25	0	21.17	21.2±1	1.0
				25	12	21.2	21.2±1	1.0
				25	24	21.19	21.2±1	1.0
				50	0	21.19	21.2±1	1.0
			16QAM	1	0	21.06	21.2±1	1.0
				1	24	21.15	21.2±1	1.0
				1	49	21.01	21.2±1	1.0
				25	0	20.23	20.3±1	1.0
				25	12	20.24	20.3±1	1.0
				25	24	20.26	20.3±1	1.0
				50	0	20.21	20.3±1	1.0
	18900	1880	QPSK	1	0	22.24	22.4±1	/
				1	24	22.4	22.4±1	/
				1	49	22.29	22.4±1	/
				25	0	21.36	21.4±1	1.0
				25	12	21.34	21.4±1	1.0
				25	24	21.32	21.4±1	1.0
				50	0	21.34	21.4±1	1.0
			16QAM	1	0	21.52	21.7±1	1.0
				1	24	21.7	21.7±1	1.0
				1	49	21.6	21.7±1	1.0
				25	0	20.36	20.4±1	1.0
				25	12	20.34	20.4±1	1.0
				25	24	20.36	20.4±1	1.0
				50	0	20.33	20.4±1	1.0
	19150	1905	QPSK	1	0	22.31	22.5±1	/
				1	24	22.45	22.5±1	/
				1	49	22.35	22.5±1	/
				25	0	21.42	21.5±1	1.0
				25	12	21.39	21.5±1	1.0
				25	24	21.29	21.5±1	1.0
				50	0	21.34	21.5±1	1.0
			16QAM	1	0	21.33	21.5±1	1.0
				1	24	21.45	21.5±1	1.0
				1	49	21.35	21.5±1	1.0
				25	0	20.51	20.6±1	1.0
				25	12	20.53	20.6±1	1.0
				25	24	20.39	20.6±1	1.0
				50	0	20.37	20.6±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	18675	1857.5	QPSK	1	0	22.02	22.3±1	/
				1	37	22.24	22.3±1	/
				1	74	21.98	22.3±1	/
				36	0	21.16	21.2±1	1.0
				36	16	21.17	21.2±1	1.0
				36	35	21.11	21.2±1	1.0
				75	0	21.14	21.2±1	1.0
			16QAM	1	0	20.94	21.2±1	1.0
				1	37	21.16	21.2±1	1.0
				1	74	20.92	21.2±1	1.0
				36	0	20.13	20.2±1	1.0
				36	16	20.16	20.2±1	1.0
				36	35	20.16	20.2±1	1.0
				75	0	20.18	20.2±1	1.0
	18900	1880	QPSK	1	0	22.13	22.5±1	/
				1	37	22.41	22.5±1	/
				1	74	22.15	22.5±1	/
				36	0	21.31	21.4±1	1.0
				36	16	21.35	21.4±1	1.0
				36	35	21.27	21.4±1	1.0
				75	0	21.34	21.4±1	1.0
			16QAM	1	0	21.46	21.8±1	1.0
				1	37	21.73	21.8±1	1.0
				1	74	21.52	21.8±1	1.0
				36	0	20.28	20.4±1	1.0
				36	16	20.33	20.4±1	1.0
				36	35	20.33	20.4±1	1.0
				75	0	20.29	20.4±1	1.0
	19125	1902.5	QPSK	1	0	22.23	22.6±1	/
				1	37	22.53	22.6±1	/
				1	74	22.28	22.6±1	/
				36	0	21.44	21.5±1	1.0
				36	16	21.5	21.5±1	1.0
				36	35	21.39	21.5±1	1.0
				75	0	21.44	21.5±1	1.0
			16QAM	1	0	21.69	21.8±1	1.0
				1	37	21.79	21.8±1	1.0
				1	74	21.58	21.8±1	1.0
				36	0	20.35	20.4±1	1.0
				36	16	20.39	20.4±1	1.0
				36	35	20.31	20.4±1	1.0
				75	0	20.33	20.4±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	18700	1860	QPSK	1	0	21.8	22.2±1	/
				1	49	22.17	22.2±1	/
				1	99	21.75	22.2±1	/
				50	0	21.08	21.2±1	1.0
				50	24	21.15	21.2±1	1.0
				50	49	21.19	21.2±1	1.0
				100	0	21.09	21.2±1	1.0
			16QAM	1	0	21.4	21.7±1	1.0
				1	49	21.69	21.7±1	1.0
				1	99	21.34	21.7±1	1.0
				50	0	20.13	20.3±1	1.0
				50	24	20.16	20.3±1	1.0
				50	49	20.24	20.3±1	1.0
				100	0	20.15	20.3±1	1.0
	18900	1880	QPSK	1	0	21.89	22.4±1	/
				1	49	22.31	22.4±1	/
				1	99	21.98	22.4±1	/
				50	0	21.24	21.3±1	1.0
				50	24	21.27	21.3±1	1.0
				50	49	21.18	21.3±1	1.0
				100	0	21.23	21.3±1	1.0
			16QAM	1	0	21.35	21.8±1	1.0
				1	49	21.73	21.8±1	1.0
				1	99	21.45	21.8±1	1.0
				50	0	20.26	20.4±1	1.0
				50	24	20.31	20.4±1	1.0
				50	49	20.21	20.4±1	1.0
				100	0	20.24	20.4±1	1.0
	19100	1900	QPSK	1	0	22.07	22.5±1	/
				1	49	22.44	22.5±1	/
				1	99	22.09	22.5±1	/
				50	0	21.33	21.4±1	1.0
				50	24	21.4	21.4±1	1.0
				50	49	21.2	21.4±1	1.0
				100	0	21.27	21.4±1	1.0
			16QAM	1	0	21.56	21.9±1	1.0
				1	49	21.81	21.9±1	1.0
				1	99	21.46	21.9±1	1.0
				50	0	20.36	20.4±1	1.0
				50	24	20.38	20.4±1	1.0
				50	49	20.23	20.4±1	1.0
				100	0	20.3	20.4±1	1.0

LTE Band 4:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	19957	1710.7	QPSK	1	0	21.18	21.3±1	/
				1	2	21.23	21.3±1	/
				1	5	21.15	21.3±1	/
				3	0	21.22	21.3±1	/
				3	1	21.25	21.3±1	/
				3	2	21.17	21.3±1	/
				6	0	20.20	20.2±1	1.0
			16QAM	1	0	20.17	20.3±1	1.0
				1	2	20.27	20.3±1	1.0
				1	5	20.20	20.3±1	1.0
				3	0	20.14	20.3±1	1.0
				3	1	20.27	20.3±1	1.0
				3	2	20.16	20.3±1	1.0
				6	0	19.37	19.4±1	1.0
	20175	1732.5	QPSK	1	0	21.02	21.2±1	/
				1	2	21.14	21.2±1	/
				1	5	21.05	21.2±1	/
				3	0	21.13	21.2±1	/
				3	1	21.16	21.2±1	/
				3	2	21.11	21.2±1	/
				6	0	20.09	20.1±1	1.0
			16QAM	1	0	20.42	20.5±1	1.0
				1	2	20.47	20.5±1	1.0
				1	5	20.35	20.5±1	1.0
				3	0	20.30	20.5±1	1.0
				3	1	20.30	20.5±1	1.0
				3	2	20.31	20.5±1	1.0
				6	0	19.03	19.1±1	1.0
	20393	1754.3	QPSK	1	0	20.95	21.1±1	/
				1	2	21.03	21.1±1	/
				1	5	20.90	21.1±1	/
				3	0	20.89	21.1±1	/
				3	1	21.00	21.1±1	/
				3	2	20.99	21.1±1	/
				6	0	19.98	20.0±1	1.0
			16QAM	1	0	19.99	20.3±1	1.0
				1	2	20.01	20.3±1	1.0
				1	5	19.93	20.3±1	1.0
				3	0	20.14	20.3±1	1.0
				3	1	20.21	20.3±1	1.0
				3	2	20.16	20.3±1	1.0
				6	0	19.17	19.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	19965	1711.5	QPSK	1	0	21.21	21.4±1	/
				1	8	21.34	21.4±1	/
				1	14	21.12	21.4±1	/
				6	0	20.16	20.3±1	1.0
				6	4	20.24	20.3±1	1.0
				6	9	20.15	20.3±1	1.0
				15	0	20.17	20.3±1	1.0
			16QAM	1	0	20.03	20.2±1	1.0
				1	8	20.16	20.2±1	1.0
				1	14	20.06	20.2±1	1.0
				8	0	19.31	19.4±1	1.0
				8	4	19.27	19.4±1	1.0
				8	9	19.26	19.4±1	1.0
				15	0	19.21	19.4±1	1.0
	20175	1732.5	QPSK	1	0	21.13	21.3±1	/
				1	8	21.28	21.3±1	/
				1	14	21.09	21.3±1	/
				6	0	20.09	20.2±1	1.0
				6	4	20.13	20.2±1	1.0
				6	9	20.03	20.2±1	1.0
				15	0	20.08	20.2±1	1.0
			16QAM	1	0	20.44	20.6±1	1.0
				1	8	20.57	20.6±1	1.0
				1	14	20.41	20.6±1	1.0
				6	0	19.14	19.3±1	1.0
				6	4	19.25	19.3±1	1.0
				6	9	19.14	19.3±1	1.0
				15	0	19.09	19.3±1	1.0
	20385	1753.5	QPSK	1	0	20.95	21.2±1	/
				1	8	21.13	21.2±1	/
				1	14	20.87	21.2±1	/
				6	0	20.01	20.1±1	1.0
				6	4	20.00	20.1±1	1.0
				6	9	19.98	20.1±1	1.0
				15	0	19.93	20.1±1	1.0
			16QAM	1	0	19.94	20.1±1	1.0
				1	8	20.04	20.1±1	1.0
				1	14	19.88	20.1±1	1.0
				8	0	19.03	19.1±1	1.0
				8	4	19.03	19.1±1	1.0
				8	9	19.00	19.1±1	1.0
				15	0	18.87	19.1±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	19975	1712.5	QPSK	1	0	20.99	21.3±1	/
				1	49	21.29	21.3±1	/
				1	99	21.04	21.3±1	/
				12	0	20.14	20.2±1	1.0
				12	24	20.13	20.2±1	1.0
				12	49	20.14	20.2±1	1.0
				25	0	20.20	20.2±1	1.0
			16QAM	1	0	20.27	20.5±1	1.0
				1	49	20.44	20.5±1	1.0
				1	99	20.25	20.5±1	1.0
				12	0	19.17	19.3±1	1.0
				12	24	19.25	19.3±1	1.0
				12	49	19.20	19.3±1	1.0
				25	0	19.16	19.3±1	1.0
	20175	1732.5	QPSK	1	0	20.94	21.3±1	/
				1	49	21.27	21.3±1	/
				1	99	21.00	21.3±1	/
				12	0	20.07	20.1±1	1.0
				12	24	20.07	20.1±1	1.0
				12	49	20.10	20.1±1	1.0
				25	0	20.09	20.1±1	1.0
			16QAM	1	0	20.55	20.8±1	1.0
				1	49	20.75	20.8±1	1.0
				1	99	20.53	20.8±1	1.0
				12	0	19.18	19.3±1	1.0
				12	24	19.23	19.3±1	1.0
				12	49	19.24	19.3±1	1.0
				25	0	19.19	19.3±1	1.0
	20375	1752.5	QPSK	1	0	20.94	21.2±1	/
				1	49	21.13	21.2±1	/
				1	99	20.92	21.2±1	/
				12	0	20.00	20.1±1	1.0
				12	24	20.06	20.1±1	1.0
				12	49	19.92	20.1±1	1.0
				25	0	20.00	20.1±1	1.0
			16QAM	1	0	20.03	20.2±1	1.0
				1	49	20.15	20.2±1	1.0
				1	99	19.99	20.2±1	1.0
				12	0	18.97	19.1±1	1.0
				12	24	19.02	19.1±1	1.0
				12	49	19.03	19.1±1	1.0
				25	0	18.87	19.1±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20000	1715	QPSK	1	0	21.24	21.3±1	/
				1	49	21.24	21.3±1	/
				1	99	21.12	21.3±1	/
				25	0	20.23	20.3±1	1.0
				25	24	20.17	20.3±1	1.0
				25	49	20.19	20.3±1	1.0
				50	0	20.24	20.3±1	1.0
			16QAM	1	0	20.03	20.2±1	1.0
				1	49	20.15	20.2±1	1.0
				1	99	20.03	20.2±1	1.0
				25	0	19.25	19.3±1	1.0
				25	24	19.18	19.3±1	1.0
				25	49	19.24	19.3±1	1.0
				50	0	19.25	19.3±1	1.0
	20175	1732.5	QPSK	1	0	21.07	21.3±1	/
				1	49	21.22	21.3±1	/
				1	99	21.13	21.3±1	/
				25	0	20.05	20.2±1	1.0
				25	24	20.18	20.2±1	1.0
				25	49	20.18	20.2±1	1.0
				50	0	20.18	20.2±1	1.0
			16QAM	1	0	20.38	20.5±1	1.0
				1	49	20.49	20.5±1	1.0
				1	99	20.39	20.5±1	1.0
				25	0	19.15	19.3±1	1.0
				25	24	19.24	19.3±1	1.0
				25	49	19.19	19.3±1	1.0
				50	0	19.17	19.3±1	1.0
	20350	1750	QPSK	1	0	21.07	21.1±1	/
				1	49	21.04	21.1±1	/
				1	99	20.94	21.1±1	/
				25	0	20.07	20.1±1	1.0
				25	24	20.05	20.1±1	1.0
				25	49	20.01	20.1±1	1.0
				50	0	20.04	20.1±1	1.0
			16QAM	1	0	20.05	20.1±1	1.0
				1	49	19.99	20.1±1	1.0
				1	99	19.88	20.1±1	1.0
				25	0	19.18	19.2±1	1.0
				25	24	19.12	19.2±1	1.0
				25	49	19.07	19.2±1	1.0
				50	0	19.04	19.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20025	1717.5	QPSK	1	0	21.02	21.4±1	/
				1	49	21.32	21.4±1	/
				1	99	21.04	21.4±1	/
				36	0	20.17	20.3±1	1.0
				36	24	20.25	20.3±1	1.0
				36	49	20.23	20.3±1	1.0
				75	0	20.20	20.3±1	1.0
			16QAM	1	0	19.89	20.1±1	1.0
				1	49	20.07	20.1±1	1.0
				1	99	19.90	20.1±1	1.0
				36	0	19.14	20.1±1	1.0
				36	24	19.12	20.1±1	1.0
				36	49	19.20	20.1±1	1.0
				75	0	19.21	20.1±1	1.0
	20175	1732.5	QPSK	1	0	21.03	21.3±1	/
				1	49	21.26	21.3±1	/
				1	99	21.01	21.3±1	/
				36	0	20.11	20.2±1	1.0
				36	24	20.15	20.2±1	1.0
				36	49	20.07	20.2±1	1.0
				75	0	20.16	20.2±1	1.0
			16QAM	1	0	20.36	20.6±1	1.0
				1	49	20.56	20.6±1	1.0
				1	99	20.35	20.6±1	1.0
				36	0	19.10	19.3±1	1.0
				36	24	19.21	19.3±1	1.0
				36	49	19.17	19.3±1	1.0
				75	0	19.20	19.3±1	1.0
	20325	1747.5	QPSK	1	0	20.97	21.3±1	/
				1	49	21.30	21.3±1	/
				1	99	20.86	21.3±1	/
				36	0	20.20	20.2±1	1.0
				36	24	20.19	20.2±1	1.0
				36	49	20.11	20.2±1	1.0
				75	0	20.15	20.2±1	1.0
			16QAM	1	0	20.28	20.6±1	1.0
				1	49	20.51	20.6±1	1.0
				1	99	20.22	20.6±1	1.0
				36	0	19.03	19.1±1	1.0
				36	24	19.08	19.1±1	1.0
				36	49	19.05	19.1±1	1.0
				75	0	19.05	19.1±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20050	1720	QPSK	1	0	20.79	21.2±1	/
				1	49	21.11	21.2±1	/
				1	99	20.81	21.2±1	/
				50	0	20.04	20.2±1	1.0
				50	24	20.16	20.2±1	1.0
				50	49	20.09	20.2±1	1.0
				100	0	20.12	20.2±1	1.0
			16QAM	1	0	20.30	20.8±1	1.0
				1	49	20.73	20.8±1	1.0
				1	99	20.36	20.8±1	1.0
				50	0	19.11	19.3±1	1.0
				50	24	19.24	19.3±1	1.0
				50	49	19.17	19.3±1	1.0
				100	0	19.18	19.3±1	1.0
	20175	1732.5	QPSK	1	0	20.69	21.2±1	/
				1	49	21.15	21.2±1	/
				1	99	20.80	21.2±1	/
				50	0	20.09	20.2±1	1.0
				50	24	20.16	20.2±1	1.0
				50	49	20.10	20.2±1	1.0
				100	0	20.12	20.2±1	1.0
			16QAM	1	0	20.23	20.6±1	1.0
				1	49	20.58	20.6±1	1.0
				1	99	20.22	20.6±1	1.0
				50	0	19.13	19.2±1	1.0
				50	24	19.19	19.2±1	1.0
				50	49	19.10	19.2±1	1.0
				100	0	19.15	19.2±1	1.0
	20300	1745	QPSK	1	0	20.79	21.1±1	/
				1	49	21.10	21.1±1	/
				1	99	20.69	21.1±1	/
				50	0	20.08	20.1±1	1.0
				50	24	20.05	20.1±1	1.0
				50	49	20.03	20.1±1	1.0
				100	0	20.02	20.1±1	1.0
			16QAM	1	0	20.21	20.5±1	1.0
				1	49	20.43	20.5±1	1.0
				1	99	20.06	20.5±1	1.0
				50	0	18.97	19.1±1	1.0
				50	24	19.09	19.1±1	1.0
				50	49	18.98	19.1±1	1.0
				100	0	19.08	19.1±1	1.0

LTE Band 5:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	20407	824.7	QPSK	1	0	24.1	24.2±1	/
				1	2	24.2	24.2±1	/
				1	5	24.09	24.2±1	/
				3	0	24.12	24.2±1	/
				3	1	24.13	24.2±1	/
				3	2	24.08	24.2±1	/
				6	0	23.15	23.2±1	1.0
			16QAM	1	0	23.11	23.3±1	1.0
				1	2	23.22	23.3±1	1.0
				1	5	23.11	23.3±1	1.0
				3	0	23.1	23.3±1	1.0
				3	1	23.15	23.3±1	1.0
				3	2	23.08	23.3±1	1.0
				6	0	22.26	22.3±1	1.0
	20525	836.5	QPSK	1	0	24.07	24.2±1	/
				1	2	24.17	24.2±1	/
				1	5	24.04	24.2±1	/
				3	0	24.1	24.2±1	/
				3	1	24.14	24.2±1	/
				3	2	24.09	24.2±1	/
				6	0	23.17	23.2±1	1.0
			16QAM	1	0	23.39	23.5±1	1.0
				1	2	23.45	23.5±1	1.0
				1	5	23.33	23.5±1	1.0
				3	0	23.26	23.5±1	1.0
				3	1	23.28	23.5±1	1.0
				3	2	23.25	23.5±1	1.0
				6	0	22.03	22.1±1	1.0
	20634	848.3	QPSK	1	0	23.91	24.1±1	/
				1	2	24.07	24.1±1	/
				1	5	23.92	24.1±1	/
				3	0	24.01	24.1±1	/
				3	1	24.07	24.1±1	/
				3	2	24.01	24.1±1	/
				6	0	23.13	23.2±1	1.0
			16QAM	1	0	22.95	23.2±1	1.0
				1	2	23.02	23.2±1	1.0
				1	5	22.96	23.2±1	1.0
				3	0	23.18	23.2±1	1.0
				3	1	23.27	23.2±1	1.0
				3	2	23.18	23.2±1	1.0
				6	0	22.25	22.3±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	20415	825.5	QPSK	1	0	24.22	24.3±1	/
				1	8	24.27	24.3±1	/
				1	14	24.11	24.3±1	/
				6	0	23.18	23.2±1	1.0
				6	4	23.2	23.2±1	1.0
				6	9	23.14	23.2±1	1.0
				15	0	23.12	23.2±1	1.0
			16QAM	1	0	23.02	23.2±1	1.0
				1	8	23.12	23.2±1	1.0
				1	14	23.01	23.2±1	1.0
				8	0	22.24	22.3±1	1.0
				8	4	22.25	22.3±1	1.0
				8	9	22.22	22.3±1	1.0
				15	0	22.13	22.3±1	1.0
	20525	836.5	QPSK	1	0	24.15	24.3±1	/
				1	8	24.3	24.3±1	/
				1	14	24.11	24.3±1	/
				6	0	23.19	23.2±1	1.0
				6	4	23.2	23.2±1	1.0
				6	9	23.14	23.2±1	1.0
				15	0	23.12	23.2±1	1.0
			16QAM	1	0	23.43	23.6±1	1.0
				1	8	23.56	23.6±1	1.0
				1	14	23.41	23.6±1	1.0
				6	0	22.2	22.3±1	1.0
				6	4	22.22	22.3±1	1.0
				6	9	22.18	22.3±1	1.0
				15	0	22.12	22.3±1	1.0
	20635	847.5	QPSK	1	0	24.06	24.1±1	/
				1	8	24.1	24.1±1	/
				1	14	24.03	24.1±1	/
				6	0	23.13	23.2±1	1.0
				6	4	23.18	23.2±1	1.0
				6	9	23.12	23.2±1	1.0
				15	0	23.1	23.2±1	1.0
			16QAM	1	0	23.08	23.2±1	1.0
				1	8	23.17	23.2±1	1.0
				1	14	22.97	23.2±1	1.0
				8	0	22.1	22.2±1	1.0
				8	4	22.17	22.2±1	1.0
				8	9	22.12	22.2±1	1.0
				15	0	22.02	22.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20425	826.5	QPSK	1	0	24.01	24.3±1	/
				1	49	24.22	24.3±1	/
				1	99	23.98	24.3±1	/
				12	0	23.11	23.2±1	1.0
				12	24	23.18	23.2±1	1.0
				12	49	23.13	23.2±1	1.0
				25	0	23.12	23.2±1	1.0
			16QAM	1	0	23.18	23.5±1	1.0
				1	49	23.44	23.5±1	1.0
				1	99	23.15	23.5±1	1.0
				12	0	22.11	22.2±1	1.0
				12	24	22.2	22.2±1	1.0
				12	49	22.16	22.2±1	1.0
				25	0	22.12	22.2±1	1.0
	20525	836.5	QPSK	1	0	24.06	24.3±1	/
				1	49	24.28	24.3±1	/
				1	99	24	24.3±1	/
				12	0	23.18	23.2±1	1.0
				12	24	23.15	23.2±1	1.0
				12	49	23.13	23.2±1	1.0
				25	0	23.12	23.2±1	1.0
			16QAM	1	0	23.52	23.8±1	1.0
				1	49	23.73	23.8±1	1.0
				1	99	23.5	23.8±1	1.0
				12	0	22.22	22.3±1	1.0
				12	24	22.28	22.3±1	1.0
				12	49	22.22	22.3±1	1.0
				25	0	22.19	22.3±1	1.0
	20625	846.5	QPSK	1	0	24.03	24.3±1	/
				1	49	24.26	24.3±1	/
				1	99	24	24.3±1	/
				12	0	23.08	23.2±1	1.0
				12	24	23.15	23.2±1	1.0
				12	49	23.1	23.2±1	1.0
				25	0	23.1	23.2±1	1.0
			16QAM	1	0	23.05	23.3±1	1.0
				1	49	23.28	23.3±1	1.0
				1	99	23.03	23.3±1	1.0
				12	0	22.11	22.2±1	1.0
				12	24	22.17	22.2±1	1.0
				12	49	22.13	22.2±1	1.0
				25	0	22.02	22.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20450	829	QPSK	1	0	24.21	24.4±1	/
				1	49	24.31	24.4±1	/
				1	99	24.22	24.4±1	/
				25	0	23.14	23.2±1	1.0
				25	24	23.19	23.2±1	1.0
				25	49	23.17	23.2±1	1.0
				50	0	23.2	23.2±1	1.0
			16QAM	1	0	23.05	23.2±1	1.0
				1	49	23.12	23.2±1	1.0
				1	99	23.03	23.2±1	1.0
				25	0	22.18	22.2±1	1.0
				25	24	22.18	22.2±1	1.0
				25	49	22.19	22.2±1	1.0
				50	0	22.14	22.2±1	1.0
	20525	836.5	QPSK	1	0	24.16	24.3±1	/
				1	49	24.24	24.3±1	/
				1	99	24.14	24.3±1	/
				25	0	23.18	23.3±1	1.0
				25	24	23.2	23.3±1	1.0
				25	49	23.21	23.3±1	1.0
				50	0	23.17	23.3±1	1.0
			16QAM	1	0	23.42	23.6±1	1.0
				1	49	23.53	23.6±1	1.0
				1	99	23.47	23.6±1	1.0
				25	0	22.21	22.3±1	1.0
				25	24	22.24	22.3±1	1.0
				25	49	22.21	22.3±1	1.0
				50	0	22.21	22.3±1	1.0
	20600	844	QPSK	1	0	24.08	24.2±1	/
				1	49	24.14	24.2±1	/
				1	99	24.07	24.2±1	/
				25	0	23.16	23.2±1	1.0
				25	24	23.16	23.2±1	1.0
				25	49	23.15	23.2±1	1.0
				50	0	23.16	23.2±1	1.0
			16QAM	1	0	23.12	23.2±1	1.0
				1	49	23.18	23.2±1	1.0
				1	99	23.04	23.2±1	1.0
				25	0	22.24	22.3±1	1.0
				25	24	22.27	22.3±1	1.0
				25	49	22.19	22.3±1	1.0
				50	0	22.19	22.3±1	1.0

LTE Band 7:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	20775	2502.5	QPSK	1	0	21.58	21.9±1	/
				1	49	21.84	21.9±1	/
				1	99	21.62	21.9±1	/
				12	0	20.67	20.8±1	1.0
				12	24	20.80	20.8±1	1.0
				12	49	20.73	20.8±1	1.0
				25	0	20.73	20.8±1	1.0
			16QAM	1	0	20.59	21.0±1	1.0
				1	49	20.91	21.0±1	1.0
				1	99	20.66	21.0±1	1.0
				12	0	19.66	19.8±1	1.0
				12	24	19.77	19.8±1	1.0
				12	49	19.72	19.8±1	1.0
				25	0	19.59	19.8±1	1.0
	21100	2535	QPSK	1	0	21.74	22.0±1	/
				1	49	21.96	22.0±1	/
				1	99	21.69	22.0±1	/
				12	0	20.59	20.8±1	1.0
				12	24	20.70	20.8±1	1.0
				12	49	20.74	20.8±1	1.0
				25	0	20.69	20.8±1	1.0
			16QAM	1	0	20.69	21.0±1	1.0
				1	49	20.97	21.0±1	1.0
				1	99	20.72	21.0±1	1.0
				12	0	19.70	19.8±1	1.0
				12	24	19.76	19.8±1	1.0
				12	49	19.73	19.8±1	1.0
				25	0	19.59	19.8±1	1.0
	21425	2567.5	QPSK	1	0	21.70	22.0±1	/
				1	49	22.00	22.0±1	/
				1	99	21.66	22.0±1	/
				12	0	20.82	21.9±1	1.0
				12	24	20.88	21.9±1	1.0
				12	49	20.73	21.9±1	1.0
				25	0	20.79	21.9±1	1.0
			16QAM	1	0	21.14	21.4±1	1.0
				1	49	21.33	21.4±1	1.0
				1	99	21.13	21.4±1	1.0
				12	0	19.78	19.9±1	1.0
				12	24	19.88	19.9±1	1.0
				12	49	19.87	19.9±1	1.0
				25	0	19.72	19.9±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20800	2505	QPSK	1	0	21.85	21.9±1	/
				1	49	21.85	21.9±1	/
				1	99	21.84	21.9±1	/
				25	0	20.67	20.8±1	1.0
				25	24	20.75	20.8±1	1.0
				25	49	20.78	20.8±1	1.0
				50	0	20.66	20.8±1	1.0
			16QAM	1	0	20.50	20.6±1	1.0
				1	49	20.58	20.6±1	1.0
				1	99	20.56	20.6±1	1.0
				25	0	19.71	19.8±1	1.0
				25	24	19.76	19.8±1	1.0
				25	49	19.74	19.8±1	1.0
				50	0	19.70	19.8±1	1.0
	21100	2535	QPSK	1	0	21.84	21.9±1	/
				1	49	21.82	21.9±1	/
				1	99	21.80	21.9±1	/
				25	0	20.75	20.8±1	1.0
				25	24	20.75	20.8±1	1.0
				25	49	20.79	20.8±1	1.0
				50	0	20.72	20.8±1	1.0
			16QAM	1	0	21.04	21.1±1	1.0
				1	49	21.07	21.1±1	1.0
				1	99	20.95	21.1±1	1.0
				25	0	19.78	19.8±1	1.0
				25	24	19.77	19.8±1	1.0
				25	49	19.73	19.8±1	1.0
				50	0	19.76	19.8±1	1.0
	21400	2565	QPSK	1	0	21.78	21.9±1	/
				1	49	21.84	21.9±1	/
				1	99	21.78	21.9±1	/
				25	0	20.81	20.9±1	1.0
				25	24	20.83	20.9±1	1.0
				25	49	20.74	20.9±1	1.0
				50	0	20.75	20.9±1	1.0
			16QAM	1	0	20.66	20.8±1	1.0
				1	49	20.76	20.8±1	1.0
				1	99	20.74	20.8±1	1.0
				25	0	19.84	19.9±1	1.0
				25	24	19.85	19.9±1	1.0
				25	49	19.83	19.9±1	1.0
				50	0	19.69	19.9±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20825	2507.5	QPSK	1	0	21.67	21.9±1	/
				1	49	21.84	21.9±1	/
				1	99	21.60	21.9±1	/
				36	0	20.84	20.9±1	1.0
				36	24	20.79	20.9±1	1.0
				36	49	20.87	20.9±1	1.0
				75	0	20.78	20.9±1	1.0
			16QAM	1	0	20.41	20.7±1	1.0
				1	49	20.65	20.7±1	1.0
				1	99	20.35	20.7±1	1.0
				36	0	19.58	19.9±1	1.0
				36	24	19.69	19.9±1	1.0
				36	49	19.82	19.9±1	1.0
				75	0	19.71	19.9±1	1.0
	21100	2535	QPSK	1	0	21.68	22.0±1	/
				1	49	21.96	22.0±1	/
				1	99	21.61	22.0±1	/
				36	0	20.79	20.8±1	1.0
				36	24	20.78	20.8±1	1.0
				36	49	20.75	20.8±1	1.0
				75	0	20.77	20.8±1	1.0
			16QAM	1	0	20.94	21.2±1	1.0
				1	49	21.13	21.2±1	1.0
				1	99	20.76	21.2±1	1.0
				36	0	19.73	19.8±1	1.0
				36	24	19.78	19.8±1	1.0
				36	49	19.76	19.8±1	1.0
				75	0	19.78	19.8±1	1.0
	21375	2562.5	QPSK	1	0	21.80	21.9±1	/
				1	49	21.88	21.9±1	/
				1	99	21.70	21.9±1	/
				36	0	20.84	20.9±1	1.0
				36	24	20.86	20.9±1	1.0
				36	49	20.84	20.9±1	1.0
				75	0	20.88	20.9±1	1.0
			16QAM	1	0	21.01	21.2±1	1.0
				1	49	21.13	21.2±1	1.0
				1	99	20.86	21.2±1	1.0
				36	0	19.74	19.8±1	1.0
				36	24	19.72	19.8±1	1.0
				36	49	19.73	19.8±1	1.0
				75	0	19.72	19.8±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20850	2510	QPSK	1	0	21.35	21.9±1	/
				1	49	21.83	21.9±1	/
				1	99	21.35	21.9±1	/
				50	0	20.59	20.8±1	1.0
				50	24	20.73	20.8±1	1.0
				50	49	20.61	20.8±1	1.0
				100	0	20.55	20.8±1	1.0
			16QAM	1	0	20.81	21.2±1	1.0
				1	49	21.19	21.2±1	1.0
				1	99	20.89	21.2±1	1.0
				50	0	19.54	19.7±1	1.0
				50	24	19.64	19.7±1	1.0
				50	49	19.66	19.7±1	1.0
				100	0	19.57	19.7±1	1.0
	21100	2535	QPSK	1	0	21.47	21.8±1	/
				1	49	21.77	21.8±1	/
				1	99	21.39	21.8±1	/
				50	0	20.60	20.7±1	1.0
				50	24	20.69	20.7±1	1.0
				50	49	20.69	20.7±1	1.0
				100	0	20.62	20.7±1	1.0
			16QAM	1	0	20.84	21.3±1	1.0
				1	49	21.21	21.3±1	1.0
				1	99	20.77	21.3±1	1.0
				50	0	19.64	19.8±1	1.0
				50	24	19.75	19.8±1	1.0
				50	49	19.61	19.8±1	1.0
				100	0	19.70	19.8±1	1.0
	21350	2560	QPSK	1	0	21.69	22.1±1	/
				1	49	22.01	22.1±1	/
				1	99	21.48	22.1±1	/
				50	0	20.65	20.8±1	1.0
				50	24	20.75	20.8±1	1.0
				50	49	20.63	20.8±1	1.0
				100	0	20.65	20.8±1	1.0
			16QAM	1	0	20.84	21.1±1	1.0
				1	49	21.02	21.1±1	1.0
				1	99	20.77	21.1±1	1.0
				50	0	19.68	19.7±1	1.0
				50	24	19.67	19.7±1	1.0
				50	49	19.59	19.7±1	1.0
				100	0	19.62	19.7±1	1.0

LTE Band 13:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	23205	779.5	QPSK	1	0	23.96	24.3±1	/
				1	49	24.26	24.3±1	/
				1	99	23.98	24.3±1	/
				12	0	23.03	23.1±1	1.0
				12	24	23.08	23.1±1	1.0
				12	49	23.04	23.1±1	1.0
				25	0	23.03	23.1±1	1.0
			16QAM	1	0	23.01	23.3±1	1.0
				1	49	23.22	23.3±1	1.0
				1	99	23.03	23.3±1	1.0
				12	0	22.08	22.2±1	1.0
				12	24	22.13	22.2±1	1.0
				12	49	22.05	22.2±1	1.0
				25	0	21.99	22.2±1	1.0
	23230	782.0	QPSK	1	0	24.07	24.4±1	/
				1	49	24.33	24.4±1	/
				1	99	24.09	24.4±1	/
				12	0	23.04	23.2±1	1.0
				12	24	23.12	23.2±1	1.0
				12	49	23.03	23.2±1	1.0
				25	0	23.05	23.2±1	1.0
			16QAM	1	0	23.06	23.3±1	1.0
				1	49	23.29	23.3±1	1.0
				1	99	23.08	23.3±1	1.0
				12	0	22.06	22.2±1	1.0
				12	24	22.14	22.2±1	1.0
				12	49	22.08	22.2±1	1.0
				25	0	22.06	22.2±1	1.0
	23255	784.5	QPSK	1	0	24.01	24.3±1	/
				1	49	24.25	24.3±1	/
				1	99	23.94	24.3±1	/
				12	0	23.1	23.1±1	1.0
				12	24	23.1	23.1±1	1.0
				12	49	22.98	23.1±1	1.0
				25	0	23.01	23.1±1	1.0
			16QAM	1	0	23.38	23.7±1	1.0
				1	49	23.61	23.7±1	1.0
				1	99	23.4	23.7±1	1.0
				12	0	22.1	22.2±1	1.0
				12	24	22.16	22.2±1	1.0
				12	49	22.1	22.2±1	1.0
				25	0	22.08	22.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	23230	782.0	QPSK	1	0	24.19	24.4±1	/
				1	49	24.34	24.4±1	/
				1	99	24.12	24.4±1	/
				25	0	23.01	23.1±1	1.0
				25	24	23.04	23.1±1	1.0
				25	49	23.01	23.1±1	1.0
				50	0	23.06	23.1±1	1.0
			16QAM	1	0	22.9	23.0±1	1.0
				1	49	22.92	23.0±1	1.0
				1	99	22.88	23.0±1	1.0
				25	0	22.03	23.0±1	1.0
				25	24	22.08	23.0±1	1.0
				25	49	22.02	23.0±1	1.0
				50	0	22.03	23.0±1	1.0

LE Measurement Result

Mode	Channel number	Frequency (MHz)	Output Power(dBm)	Tune up limited(dBm)
LE 1M	0	2402	-3.73	-3.0±1
	19	2440	-2.91	-2.0±1
	39	2480	-4.04	-4.0±1
LE 2M	1	2404	-3.73	-3.0±1
	19	2440	-2.98	-2.0±1
	38	2478	-3.73	-3.0±1

Bluetooth Measurement Result

Mode	Frequency (MHz)	Output Power(dBm)	Tune up limited(dBm)
GFSK	2402	8.54	8.6±1
	2441	6.77	6.8±1
	2480	6.52	6.6±1
$\pi/4$ DQPSK	2402	7.71	7.8±1
	2441	5.94	6.0±1
	2480	5.70	5.7±1
8DPSK	2402	7.71	7.8±1
	2441	5.91	6.0±1
	2480	5.76	5.8±1

NFC Measurement Result

Frequency(MHz)	E-Field Strength (dBuV/m)	Measurement Distance (m)	EIRP (dBm)	Tune up limited(dBm)
13.56	53.98	3	-41.18	-41.2±1

2.4G Wi-Fi Measurement Result

Channel number	Frequency (MHz)	Output Power(dBm)	Tune up limited(dBm)
TX 11b	2412	20.25	20.3±1
	2437	20.81	20.9±1
	2462	20.09	20.1±1
TX 11g	2412	22.08	22.1±1
	2437	22.50	22.6±1
	2462	21.53	21.6±1
TX 11n HT20	2412	21.42	21.5±1
	2437	22.14	22.2±1
	2462	21.19	21.2±1
TX 11n HT40	2422	21.84	21.9±1
	2437	21.90	22.0±1
	2452	21.38	21.4±1

Note: 5G Wi-Fi Power tested results please refer to the test report WTX26X06180335W.

Power Level P2:**LTE Band 2:**

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	18607	1850.7	QPSK	1	0	20.41	20.6±1	/
				1	2	20.51	20.6±1	/
				1	5	20.46	20.6±1	/
				3	0	20.27	20.6±1	/
				3	1	20.34	20.6±1	/
				3	2	20.54	20.6±1	/
				6	0	19.32	19.5±1	1.0
			16QAM	1	0	19.34	19.7±1	1.0
				1	2	19.47	19.7±1	1.0
				1	5	19.60	19.7±1	1.0
				3	0	19.48	19.7±1	1.0
				3	1	19.65	19.7±1	1.0
				3	2	19.46	19.7±1	1.0
				6	0	18.30	18.5±1	1.0
	18900	1880	QPSK	1	0	20.59	20.6±1	/
				1	2	20.48	20.6±1	/
				1	5	20.21	20.6±1	/
				3	0	20.46	20.6±1	/
				3	1	20.51	20.6±1	/
				3	2	20.34	20.6±1	/
				6	0	19.26	19.5±1	1.0
			16QAM	1	0	20.00	20.0±1	1.0
				1	2	19.83	20.0±1	1.0
				1	5	19.67	20.0±1	1.0
				3	0	19.58	20.0±1	1.0
				3	1	19.81	20.0±1	1.0
				3	2	19.47	20.0±1	1.0
				6	0	18.57	19.0±1	1.0
	19193	1909.3	QPSK	1	0	20.76	20.8±1	/
				1	2	20.73	20.8±1	/
				1	5	20.76	20.8±1	/
				3	0	20.40	20.8±1	/
				3	1	20.80	20.8±1	/
				3	2	20.45	20.8±1	/
				6	0	19.64	20.0±1	1.0
			16QAM	1	0	19.42	20.0±1	1.0
				1	2	19.49	20.0±1	1.0
				1	5	19.35	20.0±1	1.0
				3	0	19.85	20.0±1	1.0
				3	1	19.63	20.0±1	1.0
				3	2	19.60	20.0±1	1.0
				6	0	18.76	19.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	18615	1851.5	QPSK	1	0	20.61	20.8±1	/
				1	8	20.71	20.8±1	/
				1	14	20.11	20.8±1	/
				6	0	19.29	20.0±1	1.0
				6	4	19.64	20.0±1	1.0
				6	9	19.16	20.0±1	1.0
				15	0	19.31	20.0±1	1.0
			16QAM	1	0	19.41	20.0±1	1.0
				1	8	19.34	20.0±1	1.0
				1	14	19.23	20.0±1	1.0
				6	0	18.69	19.0±1	1.0
				6	4	18.43	19.0±1	1.0
				6	9	18.50	19.0±1	1.0
				15	0	18.24	19.0±1	1.0
	18900	1880	QPSK	1	0	20.71	20.8±1	/
				1	8	20.45	20.8±1	/
				1	14	20.45	20.8±1	/
				6	0	19.70	20.0±1	1.0
				6	4	19.51	20.0±1	1.0
				6	9	19.45	20.0±1	1.0
				15	0	19.47	20.0±1	1.0
			16QAM	1	0	19.82	20.1±1	1.0
				1	8	19.87	20.1±1	1.0
				1	14	20.02	20.1±1	1.0
				6	0	18.74	19.0±1	1.0
				6	4	18.44	19.0±1	1.0
				6	9	18.45	19.0±1	1.0
				15	0	18.35	19.0±1	1.0
	19185	1908.5	QPSK	1	0	20.72	20.8±1	/
				1	8	20.70	20.8±1	/
				1	14	20.62	20.8±1	/
				6	0	19.62	20.0±1	1.0
				6	4	19.72	20.0±1	1.0
				6	9	19.55	20.0±1	1.0
				15	0	19.50	20.0±1	1.0
			16QAM	1	0	19.75	20.0±1	1.0
				1	8	19.70	20.0±1	1.0
				1	14	19.60	20.0±1	1.0
				6	0	18.84	19.0±1	1.0
				6	4	18.72	19.0±1	1.0
				6	9	18.56	19.0±1	1.0
				15	0	18.72	19.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	18625	1852.5	QPSK	1	0	20.13	20.7±1	/
				1	12	20.69	20.7±1	/
				1	24	20.18	20.7±1	/
				12	0	19.49	20.0±1	1.0
				12	6	19.52	20.0±1	1.0
				12	11	19.18	20.0±1	1.0
				25	0	19.51	20.0±1	1.0
			16QAM	1	0	19.32	20.0±1	1.0
				1	12	19.76	20.0±1	1.0
				1	24	19.41	20.0±1	1.0
				12	0	18.64	19.0±1	1.0
				12	6	18.39	19.0±1	1.0
				12	11	18.22	19.0±1	1.0
				25	0	18.20	19.0±1	1.0
	18900	1880	QPSK	1	0	20.59	20.9±1	/
				1	12	20.83	20.9±1	/
				1	24	20.55	20.9±1	/
				12	0	19.51	20.0±1	1.0
				12	6	19.72	20.0±1	1.0
				12	11	19.23	20.0±1	1.0
				25	0	19.29	20.0±1	1.0
			16QAM	1	0	19.90	20.0±1	1.0
				1	12	20.28	20.3±1	1.0
				1	24	20.07	20.3±1	1.0
				12	0	18.54	19.0±1	1.0
				12	6	18.74	19.0±1	1.0
				12	11	18.69	19.0±1	1.0
				25	0	18.51	19.0±1	1.0
	19175	1907.5	QPSK	1	0	20.57	20.8±1	/
				1	12	20.71	20.8±1	/
				1	24	20.67	20.8±1	/
				12	0	19.52	20.0±1	1.0
				12	6	19.70	20.0±1	1.0
				12	11	19.35	20.0±1	1.0
				25	0	19.51	20.0±1	1.0
			16QAM	1	0	19.61	20.0±1	1.0
				1	12	19.99	20.0±1	1.0
				1	24	19.65	20.0±1	1.0
				12	0	18.76	19.0±1	1.0
				12	6	18.57	19.0±1	1.0
				12	11	18.35	19.0±1	1.0
				25	0	18.63	19.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	18650	1855	QPSK	1	0	20.23	20.4±1	/
				1	24	20.38	20.4±1	/
				1	49	20.26	20.4±1	/
				25	0	19.23	20.0±1	1.0
				25	12	19.30	20.0±1	1.0
				25	24	19.66	20.0±1	1.0
				50	0	19.64	20.0±1	1.0
			16QAM	1	0	19.34	19.5±1	1.0
				1	24	19.33	19.5±1	1.0
				1	49	19.02	19.5±1	1.0
				25	0	18.44	19.0±1	1.0
				25	12	18.68	19.0±1	1.0
				25	24	18.35	19.0±1	1.0
				50	0	18.33	19.4±1	1.0
	18900	1880	QPSK	1	0	20.67	20.8±1	/
				1	24	20.75	20.8±1	/
				1	49	20.58	20.8±1	/
				25	0	19.79	20.0±1	1.0
				25	12	19.70	20.0±1	1.0
				25	24	19.42	20.0±1	1.0
				50	0	19.50	20.0±1	1.0
			16QAM	1	0	19.88	20.2±1	1.0
				1	24	20.19	20.2±1	1.0
				1	49	19.84	20.2±1	1.0
				25	0	18.49	19.0±1	1.0
				25	12	18.65	19.0±1	1.0
				25	24	18.62	19.0±1	1.0
				50	0	18.58	19.0±1	1.0
	19150	1905	QPSK	1	0	20.32	20.8±1	/
				1	24	20.60	20.8±1	/
				1	49	20.77	20.8±1	/
				25	0	19.82	20.0±1	1.0
				25	12	19.70	20.0±1	1.0
				25	24	19.53	20.0±1	1.0
				50	0	19.83	20.0±1	1.0
			16QAM	1	0	19.38	20.0±1	1.0
				1	24	19.73	20.0±1	1.0
				1	49	19.48	20.0±1	1.0
				25	0	18.86	19.0±1	1.0
				25	12	18.75	19.0±1	1.0
				25	24	18.87	19.0±1	1.0
				50	0	18.87	19.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	18675	1857.5	QPSK	1	0	20.09	20.7±1	/
				1	37	20.67	20.7±1	/
				1	74	20.05	20.7±1	/
				36	0	19.41	19.7±1	1.0
				36	16	19.33	19.7±1	1.0
				36	35	19.50	19.7±1	1.0
				75	0	19.61	19.7±1	1.0
			16QAM	1	0	19.34	19.5±1	1.0
				1	37	19.46	19.5±1	1.0
				1	74	19.34	19.5±1	1.0
				36	0	18.28	18.6±1	1.0
				36	16	18.57	18.6±1	1.0
				36	35	18.60	18.6±1	1.0
				75	0	18.34	18.6±1	1.0
	18900	1880	QPSK	1	0	20.38	20.7±1	/
				1	37	20.64	20.7±1	/
				1	74	20.53	20.7±1	/
				36	0	19.49	19.7±1	1.0
				36	16	19.61	19.7±1	1.0
				36	35	19.57	19.7±1	1.0
				75	0	19.61	19.7±1	1.0
			16QAM	1	0	19.67	20.0±1	1.0
				1	37	19.99	20.0±1	1.0
				1	74	19.68	20.0±1	1.0
				36	0	18.38	18.5±1	1.0
				36	16	18.49	18.5±1	1.0
				36	35	18.38	18.5±1	1.0
				75	0	18.36	18.5±1	1.0
	19125	1902.5	QPSK	1	0	20.49	20.8±1	/
				1	37	20.80	20.8±1	/
				1	74	20.76	20.8±1	/
				36	0	19.50	19.8±1	1.0
				36	16	19.75	19.8±1	1.0
				36	35	19.42	19.8±1	1.0
				75	0	19.65	19.8±1	1.0
			16QAM	1	0	19.98	20.1±1	1.0
				1	37	20.08	20.1±1	1.0
				1	74	20.01	20.1±1	1.0
				36	0	18.74	18.8±1	1.0
				36	16	18.51	18.8±1	1.0
				36	35	18.42	18.8±1	1.0
				75	0	18.36	18.8±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	18700	1860	QPSK	1	0	19.92	20.4±1	/
				1	49	20.32	20.4±1	/
				1	99	20.23	20.4±1	/
				50	0	19.57	19.6±1	1.0
				50	24	19.57	19.6±1	1.0
				50	49	19.23	19.6±1	1.0
				100	0	19.09	19.6±1	1.0
			16QAM	1	0	19.57	20.0±1	1.0
				1	49	19.99	20.0±1	1.0
				1	99	19.63	20.0±1	1.0
				50	0	18.59	18.6±1	1.0
				50	24	18.59	18.6±1	1.0
				50	49	18.37	18.6±1	1.0
				100	0	18.44	18.6±1	1.0
	18900	1880	QPSK	1	0	20.11	20.8±1	/
				1	49	20.71	20.8±1	/
				1	99	20.21	20.8±1	/
				50	0	19.29	19.6±1	1.0
				50	24	19.42	19.6±1	1.0
				50	49	19.49	19.6±1	1.0
				100	0	19.58	19.6±1	1.0
			16QAM	1	0	19.44	20.3±1	1.0
				1	49	20.21	20.3±1	1.0
				1	99	19.86	20.3±1	1.0
				50	0	18.66	18.7±1	1.0
				50	24	18.58	18.7±1	1.0
				50	49	18.30	18.7±1	1.0
				100	0	18.67	18.7±1	1.0
	19100	1900	QPSK	1	0	20.40	20.9±1	/
				1	49	20.85	20.9±1	/
				1	99	20.28	20.9±1	/
				50	0	19.35	19.5±1	1.0
				50	24	19.45	19.5±1	1.0
				50	49	19.24	19.5±1	1.0
				100	0	19.40	19.5±1	1.0
			16QAM	1	0	19.73	20.0±1	1.0
				1	49	19.92	20.0±1	1.0
				1	99	19.51	20.0±1	1.0
				50	0	18.60	18.7±1	1.0
				50	24	18.74	18.7±1	1.0
				50	49	18.62	18.7±1	1.0
				100	0	18.34	18.7±1	1.0

LTE Band 4:

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
1.4MHz	19957	1710.7	QPSK	1	0	18.78	19.2±1	/
				1	2	19.00	19.2±1	/
				1	5	19.02	19.2±1	/
				3	0	19.16	19.2±1	/
				3	1	18.96	19.2±1	/
				3	2	19.12	19.2±1	/
				6	0	19.03	19.2±1	1.0
			16QAM	1	0	19.18	19.2±1	1.0
				1	2	19.20	19.2±1	1.0
				1	5	19.16	19.2±1	1.0
				3	0	19.12	19.2±1	1.0
				3	1	19.12	19.2±1	1.0
				3	2	19.06	19.2±1	1.0
				6	0	19.04	19.2±1	1.0
	20175	1732.5	QPSK	1	0	18.99	19.2±1	/
				1	2	18.97	19.2±1	/
				1	5	18.71	19.2±1	/
				3	0	18.83	19.2±1	/
				3	1	19.13	19.2±1	/
				3	2	19.04	19.2±1	/
				6	0	18.85	19.2±1	1.0
			16QAM	1	0	19.27	19.5±1	1.0
				1	2	19.46	19.5±1	1.0
				1	5	19.35	19.5±1	1.0
				3	0	19.13	19.5±1	1.0
				3	1	19.21	19.5±1	1.0
				3	2	19.09	19.5±1	1.0
				6	0	18.91	19.5±1	1.0
	20393	1754.3	QPSK	1	0	18.60	19.0±1	/
				1	2	18.80	19.0±1	/
				1	5	18.41	19.0±1	/
				3	0	18.69	19.0±1	/
				3	1	18.80	19.0±1	/
				3	2	18.77	19.0±1	/
				6	0	18.83	19.0±1	1.0
			16QAM	1	0	18.74	19.0±1	1.0
				1	2	18.87	19.0±1	1.0
				1	5	18.79	19.0±1	1.0
				3	0	18.99	19.0±1	1.0
				3	1	18.94	19.0±1	1.0
				3	2	18.90	19.0±1	1.0
				6	0	18.88	19.0±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
3MHz	19965	1711.5	QPSK	1	0	18.86	19.2±1	/
				1	8	19.16	19.2±1	/
				1	14	18.94	19.2±1	/
				6	0	19.04	19.2±1	1.0
				6	4	19.10	19.2±1	1.0
				6	9	18.83	19.2±1	1.0
				15	0	18.91	19.2±1	1.0
			16QAM	1	0	19.04	19.1±1	1.0
				1	8	18.98	19.1±1	1.0
				1	14	18.92	19.1±1	1.0
				8	0	19.05	19.1±1	1.0
				8	4	19.06	19.1±1	1.0
				8	9	19.05	19.1±1	1.0
				15	0	18.95	19.1±1	1.0
	20175	1732.5	QPSK	1	0	18.87	19.1±1	/
				1	8	19.07	19.1±1	/
				1	14	18.94	19.1±1	/
				6	0	18.78	19.1±1	1.0
				6	4	18.96	19.1±1	1.0
				6	9	18.87	19.1±1	1.0
				15	0	18.80	19.1±1	1.0
			16QAM	1	0	19.34	19.5±1	1.0
				1	8	19.40	19.5±1	1.0
				1	14	19.41	19.5±1	1.0
				6	0	19.05	19.5±1	1.0
				6	4	19.15	19.5±1	1.0
				6	9	18.97	19.5±1	1.0
				15	0	18.88	19.5±1	1.0
	20385	1753.5	QPSK	1	0	18.89	19.0±1	/
				1	8	18.96	19.0±1	/
				1	14	18.59	19.0±1	/
				6	0	18.78	19.0±1	1.0
				6	4	18.78	19.0±1	1.0
				6	9	18.72	19.0±1	1.0
				15	0	18.86	19.0±1	1.0
			16QAM	1	0	19.01	19.1±1	1.0
				1	8	18.87	19.1±1	1.0
				1	14	18.85	19.1±1	1.0
				8	0	18.77	19.1±1	1.0
				8	4	18.90	19.1±1	1.0
				8	9	18.79	19.1±1	1.0
				15	0	18.90	19.1±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
5MHz	19975	1712.5	QPSK	1	0	18.78	19.2±1	/
				1	49	19.18	19.2±1	/
				1	99	18.86	19.2±1	/
				12	0	19.01	19.2±1	1.0
				12	24	18.99	19.2±1	1.0
				12	49	18.85	19.2±1	1.0
				25	0	18.86	19.2±1	1.0
			16QAM	1	0	19.13	19.4±1	1.0
				1	49	19.35	19.4±1	1.0
				1	99	19.07	19.4±1	1.0
				12	0	18.93	19.4±1	1.0
				12	24	19.14	19.4±1	1.0
				12	49	19.10	19.4±1	1.0
				25	0	18.96	19.4±1	1.0
	20175	1732.5	QPSK	1	0	18.94	19.3±1	/
				1	49	19.23	19.3±1	/
				1	99	18.78	19.3±1	/
				12	0	18.98	19.3±1	1.0
				12	24	18.90	19.3±1	1.0
				12	49	18.95	19.3±1	1.0
				25	0	18.88	19.3±1	1.0
			16QAM	1	0	19.36	19.6±1	1.0
				1	49	19.59	19.6±1	1.0
				1	99	19.31	19.6±1	1.0
				12	0	19.11	19.6±1	1.0
				12	24	19.05	19.6±1	1.0
				12	49	18.99	19.6±1	1.0
				25	0	18.98	19.6±1	1.0
	20375	1752.5	QPSK	1	0	18.84	19.1±1	/
				1	49	19.06	19.1±1	/
				1	99	18.80	19.1±1	/
				12	0	18.66	19.1±1	1.0
				12	24	18.91	19.1±1	1.0
				12	49	18.89	19.1±1	1.0
				25	0	18.79	19.1±1	1.0
			16QAM	1	0	18.93	19.1±1	1.0
				1	49	19.01	19.1±1	1.0
				1	99	18.99	19.1±1	1.0
				12	0	18.78	19.1±1	1.0
				12	24	18.80	19.1±1	1.0
				12	49	18.92	19.1±1	1.0
				25	0	18.88	19.1±1	1.0


BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
10MHz	20000	1715	QPSK	1	0	19.07	19.2±1	/
				1	49	19.01	19.2±1	/
				1	99	18.98	19.2±1	/
				25	0	18.88	19.2±1	1.0
				25	24	19.08	19.2±1	1.0
				25	49	19.06	19.2±1	1.0
				50	0	19.11	19.2±1	1.0
			16QAM	1	0	18.96	19.1±1	1.0
				1	49	19.05	19.1±1	1.0
				1	99	19.01	19.1±1	1.0
				25	0	19.08	19.1±1	1.0
				25	24	18.95	19.1±1	1.0
				25	49	19.04	19.1±1	1.0
				50	0	19.07	19.1±1	1.0
	20175	1732.5	QPSK	1	0	18.86	19.0±1	/
				1	49	18.84	19.0±1	/
				1	99	18.99	19.0±1	/
				25	0	18.98	19.0±1	1.0
				25	24	18.88	19.0±1	1.0
				25	49	18.93	19.0±1	1.0
				50	0	18.89	19.0±1	1.0
			16QAM	1	0	19.36	19.4±1	1.0
				1	49	19.38	19.4±1	1.0
				1	99	19.19	19.4±1	1.0
				25	0	18.96	19.4±1	1.0
				25	24	19.05	19.4±1	1.0
				25	49	18.92	19.4±1	1.0
				50	0	19.10	19.4±1	1.0
	20350	1750	QPSK	1	0	18.92	19.0±1	/
				1	49	18.80	19.0±1	/
				1	99	18.73	19.0±1	/
				25	0	18.77	19.0±1	1.0
				25	24	18.82	19.0±1	1.0
				25	49	18.73	19.0±1	1.0
				50	0	18.77	19.0±1	1.0
			16QAM	1	0	18.93	19.2±1	1.0
				1	49	18.95	19.2±1	1.0
				1	99	18.69	19.2±1	1.0
				25	0	19.12	19.2±1	1.0
				25	24	18.95	19.2±1	1.0
				25	49	19.05	19.2±1	1.0
				50	0	18.86	19.2±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
15MHz	20025	1717.5	QPSK	1	0	18.80	19.2±1	/
				1	49	19.14	19.2±1	/
				1	99	18.86	19.2±1	/
				36	0	18.86	19.2±1	1.0
				36	24	19.11	19.2±1	1.0
				36	49	18.99	19.2±1	1.0
				75	0	18.98	19.2±1	1.0
			16QAM	1	0	18.83	19.2±1	1.0
				1	49	19.01	19.2±1	1.0
				1	99	18.73	19.2±1	1.0
				36	0	19.03	19.2±1	1.0
				36	24	19.01	19.2±1	1.0
				36	49	18.96	19.2±1	1.0
				75	0	19.11	19.2±1	1.0
	20175	1732.5	QPSK	1	0	18.80	19.2±1	/
				1	49	19.19	19.2±1	/
				1	99	18.87	19.2±1	/
				36	0	18.83	19.2±1	1.0
				36	24	18.92	19.2±1	1.0
				36	49	18.90	19.2±1	1.0
				75	0	18.82	19.2±1	1.0
			16QAM	1	0	19.10	19.4±1	1.0
				1	49	19.33	19.4±1	1.0
				1	99	19.08	19.4±1	1.0
				36	0	18.91	19.4±1	1.0
				36	24	18.90	19.4±1	1.0
				36	49	18.86	19.4±1	1.0
				75	0	18.89	19.4±1	1.0
	20325	1747.5	QPSK	1	0	18.77	19.1±1	/
				1	49	19.02	19.1±1	/
				1	99	18.62	19.1±1	/
				36	0	18.82	19.1±1	1.0
				36	24	18.81	19.1±1	1.0
				36	49	18.79	19.1±1	1.0
				75	0	18.84	19.1±1	1.0
			16QAM	1	0	19.28	19.4±1	1.0
				1	49	19.38	19.4±1	1.0
				1	99	19.10	19.4±1	1.0
				36	0	18.96	19.4±1	1.0
				36	24	18.93	19.4±1	1.0
				36	49	18.70	19.4±1	1.0
				75	0	18.79	19.4±1	1.0

BW(MHz)	Ch	Freq(MHz)	Mode	UL RB Allocation	UL RB Offset	Average Power (dbm)	Tune up limited(dBm)	MPR (dB)
20MHz	20050	1720	QPSK	1	0	18.62	19.1±1	/
				1	49	19.10	19.1±1	/
				1	99	18.59	19.1±1	/
				50	0	18.78	19.1±1	1.0
				50	24	19.06	19.1±1	1.0
				50	49	18.96	19.1±1	1.0
				100	0	18.84	19.1±1	1.0
			16QAM	1	0	19.25	19.6±1	1.0
				1	49	19.56	19.6±1	1.0
				1	99	19.15	19.6±1	1.0
				50	0	18.87	19.6±1	1.0
				50	24	18.96	19.6±1	1.0
				50	49	18.87	19.6±1	1.0
				100	0	19.08	19.6±1	1.0
	20175	1732.5	QPSK	1	0	18.70	19.0±1	/
				1	49	18.91	19.0±1	/
				1	99	18.62	19.0±1	/
				50	0	18.92	19.0±1	1.0
				50	24	18.94	19.0±1	1.0
				50	49	18.99	19.0±1	1.0
				100	0	18.93	19.0±1	1.0
			16QAM	1	0	19.11	19.5±1	1.0
				1	49	19.44	19.5±1	1.0
				1	99	19.24	19.5±1	1.0
				50	0	19.05	19.5±1	1.0
				50	24	18.95	19.5±1	1.0
				50	49	19.02	19.5±1	1.0
				100	0	19.05	19.5±1	1.0
	20300	1745	QPSK	1	0	18.73	19.0±1	/
				1	49	18.97	19.0±1	/
				1	99	18.44	19.0±1	/
				50	0	18.87	19.0±1	1.0
				50	24	18.89	19.0±1	1.0
				50	49	18.84	19.0±1	1.0
				100	0	18.92	19.0±1	1.0
			16QAM	1	0	19.03	19.5±1	1.0
				1	49	19.45	19.5±1	1.0
				1	99	19.04	19.5±1	1.0
				50	0	18.77	19.5±1	1.0
				50	24	18.96	19.5±1	1.0
				50	49	18.80	19.5±1	1.0
				100	0	18.99	19.5±1	1.0

13 Exposure Conditions Consideration

13.1 EUT antenna location



13.2 Test position consideration

Distance of EUT antenna-to-edge/surface(mm)						
Antennas	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
GSM: B5 WCDMA: B5 LTE: B5/13/28	<25	<25	<25	18	<25	165
GSM: B2 WCDMA: B2/4 LTE: B2/4/7	<25	<25	<25	<25	159	<25
BT/WIFI	<25	<25	67	<25	<25	152
Test distance: 10mm						
Antennas	Back Side	Front Side	Left Edge	Right Edge	Top Edge	Bottom Edge
GSM: B5 WCDMA: B5 LTE: B5/13/28	YES	YES	YES	YES	YES	NO
GSM: B2 WCDMA: B2/4 LTE: B2/4/7	YES	YES	YES	YES	NO	YES
BT/WIFI	YES	YES	NO	YES	YES	NO

Note:

1. Head/Body SAR/Hotspot mode assessments are required.
2. Referring to KDB 941225 D06v02r01, when the overall device length and width are $\geq 9\text{cm} * 5\text{cm}$, the test distance is 10mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.
3. Per KDB 447498 D01v06, for handsets the test separation distance is determined by the smallest distance between the outer surface of the device and the user, which is 0 mm for head SAR, 10 mm for body SAR.

13.3 RF Exposure

Standard Requirement:

1. According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$\left[\frac{(\text{max. power of channel, including tune-up tolerance, mW})}{(\text{min. test separation distance, mm})} \right] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16} \text{ where}$$

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation¹⁷
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{Exclusion Thresholds} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

Test Distance (5mm)

Mode	MAX Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Exclusion Thresholds	Limit
BLE	-2.91	-2.0±1	-1.0	0.79	0.248	3
Bluetooth	8.54	8.6±1	9.6	9.12	2.827	3
2.4G Wi-Fi	22.50	22.6±1	23.6	229.09	71.525	3

Test Distance (10mm)

Mode	MAX Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Exclusion Thresholds	Limit
BLE	-2.91	-2.0±1	-1.0	0.79	0.124	3
Bluetooth	8.54	8.6±1	9.6	9.12	1.413	3
2.4G Wi-Fi	22.50	22.6±1	23.6	229.09	35.762	3

2. According to the KDB 447498 D01 V06, 4.3.1 c), for frequencies below 100 MHz, the following may be considered for SAR test exclusion (also illustrated in Appendix C):

Appendix C

SAR Test Exclusion Thresholds for < 100 MHz and < 200 mm

Approximate SAR test exclusion power thresholds at selected frequencies and test separation distances are illustrated in the following table. The equation and threshold in 4.3.1 must be applied to determine SAR test exclusion.

MHz	< 50	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	mm
100	237	474	481	487	494	501	507	514	521	527	534	541	547	554	561	567	mW
50	308	617	625	634	643	651	660	669	677	686	695	703	712	721	729	738	
10	474	948	961	975	988	1001	1015	1028	1041	1055	1068	1081	1095	1108	1121	1135	
1	711	1422	1442	1462	1482	1502	1522	1542	1562	1582	1602	1622	1642	1662	1682	1702	
0.1	948	1896	1923	1949	1976	2003	2029	2056	2083	2109	2136	2163	2189	2216	2243	2269	
0.05	1019	2039	2067	2096	2125	2153	2182	2211	2239	2268	2297	2325	2354	2383	2411	2440	
0.01	1185	2370	2403	2437	2470	2503	2537	2570	2603	2637	2670	2703	2737	2770	2803	2837	

- 1) For test separation distances > 50 mm and < 200 mm, the power threshold at the corresponding test separation distance at 100 MHz in step b) is multiplied by $[1 + \log(100/f(\text{MHz}))]$
- 2) For test separation distances ≤ 50 mm, the power threshold determined by the equation in c) 1) for 50 mm and 100 MHz is multiplied by $\frac{1}{2}$
- 3) SAR measurement procedures are not established below 100 MHz.

Test Distance (5mm)

Mode	MAX Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Exclusion Thresholds (mW)	Limit (mW)
NFC	-41.18	-41.2±1	-40.2	0.000095	0.000002	308

The exclusion thresholds of NFC is $0.000002 < 308$, so the RF exposure evaluation is not required.

14 SAR Test Results

14.1 Test Condition

1. SAR Measurement
The distance between the EUT and the antenna of the emulator is more than 50 cm and the output power radiated from the emulator antenna is at least 30 dB less than the output power of EUT.
2. Environmental Conditions

Temperature	23.5°C
Relative Humidity	53.9%
Atmospheric Pressure	1007mbar

14.2 Generally Test Procedures

1. Establish communication link between EUT and base station emulation by air link.
2. Place the EUT in the selected test position. (Cheek, tilt or flat)
3. Perform SAR testing at middle or highest output power channel under the selected test mode. If the measured 1-g SAR is ≤ 0.8 W/kg, then testing for the other channel will not be performed.
4. When SAR is < 0.8 W/kg, no repeated SAR measurement is required

For WCDMA test:

1. KDB941225 D01-Body SAR is not required for HSDPA when the average output of each RF channel with HSDPA active is less than 0.25dB higher than measured without HSDPA using 12.2kbps RMC or the maximum SAR for 12.2kbps RMC $< 75\%$ of the SAR limit.
2. KDB941225 D01-Body SAR is not required for handset with HSPA capabilities when the maximum average output of each RF channel with HSUPA/HSDPA active is less than 0.25dB higher than that measure without HSUPA/HSDPA using 12.2kbps RMC AND THE maximum SAR for 12.2kbps RMC is $< 75\%$ of the SAR limit

For LTE test:

1. According to FCC KDB 941225 D05v02r05:
 - a. Per Section 5.2.1, SAR is required for QPSK 1 RB Allocation for the largest bandwidth
 - i. The required channel and offset combination with the highest maximum output power is required for SAR.
 - ii. When the reported SAR is ≤ 0.8 W/kg, testing of the remaining RB offset configurations and required test channels is not required. Otherwise, SAR is required for the remaining required test channels using the RB offset configuration with highest output power for that channel.
 - iii. When the reported SAR for a required test channel is > 1.45 W/kg, SAR is required for all RB offset configurations for that channel.
 - b. Per Section 5.2.2, SAR is required for 50% RB allocation using the largest bandwidth following the same procedures outlined in Section 5.2.1.
 - c. Per Section 5.2.3, QPSK SAR is not required for the 100% allocation when the highest maximum output power for the 100% allocation is less than the highest maximum output power of the 1 RB and 50% RB allocations and the reported SAR for the 1 RB and 50% RB allocations is < 0.8 W/kg.
 - d. Per Section 5.2.4 and 5.3, SAR tests for higher order modulations and lower bandwidths configurations are not required when the conducted power of the required test configurations determined by Sections 5.2.1 through 5.2.3 is less than or equal to $\frac{1}{2}$ dB higher than the equivalent configuration using QPSK modulation and when the QPSK SAR for those configurations is < 1.45 W/kg.
 - e. A-MPR was disabled for all SAR tests by setting NS=01 on the base station simulator. SAR tests were performed with the same number of RB and RB offsets transmitting on all TTI frames (maximum TTI).

14.3 SAR Summary Test Result

Table 4: SAR Values of GSM 850MHz Band (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	251	848.8	Voice call	33.9	32.83	1.279	0.649	0.830	--
	Tilt	251	848.8	Voice call	33.9	32.83	1.279	0.625	0.800	--
	Cheek	128	824.2	Voice call	33.9	32.61	1.346	0.608	0.818	--
	Cheek	190	836.6	Voice call	33.9	32.78	1.294	0.613	0.793	--
	Tilt	128	824.2	Voice call	33.9	32.61	1.346	0.576	0.775	--
	Tilt	190	836.6	Voice call	33.9	32.78	1.294	0.589	0.762	--
Left Head	Cheek	251	848.8	Voice call	33.9	32.83	1.279	0.692	0.885	1
	Tilt	251	848.8	Voice call	33.9	32.83	1.279	0.657	0.841	--
	Cheek	128	824.2	Voice call	33.9	32.61	1.346	0.651	0.876	--
	Cheek	190	836.6	Voice call	33.9	32.78	1.294	0.674	0.872	--
	Tilt	128	824.2	Voice call	33.9	32.61	1.346	0.608	0.818	--
	Tilt	190	836.6	Voice call	33.9	32.78	1.294	0.635	0.822	--
Right Head	Cheek	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.566	0.714	--
	Tilt	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.538	0.679	--
Left Head	Cheek	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.685	0.864	--
	Tilt	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.652	0.823	--
	Cheek	128	824.2	GPRS 3 slots	31.3	29.94	1.368	0.635	0.869	--
	Cheek	190	836.6	GPRS 3 slots	31.3	30.24	1.276	0.663	0.846	--
	Tilt	128	824.2	GPRS 3 slots	31.3	29.94	1.368	0.608	0.832	--
	Tilt	190	836.6	GPRS 3 slots	31.3	30.24	1.276	0.637	0.813	--

Table 5: SAR Values of GSM 850MHz Band (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Body-worn (10mm Separation)	Front Side	251	848.8	Voice call	33.9	32.83	1.279	0.230	0.294	--
	Back Side	251	848.8	Voice call	33.9	32.83	1.279	0.255	0.326	2
Hotspot (10mm Separation)	Front Side	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.211	0.266	--
	Back Side	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.236	0.298	--
	Left Edge	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.156	0.197	--
	Right Edge	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.054	0.068	--
	Top Edge	251	848.8	GPRS 3 slots	31.3	30.29	1.262	0.135	0.170	--

Table 6: SAR Values of GSM 1900MHz Band (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	512	1850.2	Voice call	30.3	29.23	1.279	0.363	0.464	3
	Tilt	512	1850.2	Voice call	30.3	29.23	1.279	0.345	0.441	--
Left Head	Cheek	512	1850.2	Voice call	30.3	29.23	1.279	0.295	0.377	--
	Tilt	512	1850.2	Voice call	30.3	29.23	1.279	0.272	0.348	--
Right Head	Cheek	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.322	0.414	--
	Tilt	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.295	0.379	--
Left Head	Cheek	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.239	0.307	--
	Tilt	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.225	0.289	--
Body-worn (10mm Separation)	Front Side	512	1850.2	Voice call	30.3	29.23	1.279	0.265	0.339	--
	Back Side	512	1850.2	Voice call	30.3	29.23	1.279	0.525	0.672	4
Hotspot (10mm Separation)	Front Side	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.248	0.319	--
	Back Side	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.513	0.659	--
	Left Edge	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.188	0.242	--
	Right Edge	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.062	0.080	--
	Bottom Edge	810	1909.8	GPRS 2 slots	28.3	27.21	1.285	0.211	0.271	--

Table 7: SAR Values of WCDMA BAND II

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head (P2)	Cheek	9400	1880	RMC 12.2kbps	21.8	20.78	1.265	0.469	0.593	5
	Tilt	9400	1880	RMC 12.2kbps	21.8	20.78	1.265	0.434	0.549	--
Left Head (P2)	Cheek	9400	1880	RMC 12.2kbps	21.8	20.78	1.265	0.339	0.429	--
	Tilt	9400	1880	RMC 12.2kbps	21.8	20.78	1.265	0.312	0.395	--
Body-worn (10mm Separation) (P1)	Front Side	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.387	0.491	--
	Back Side	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.726	0.920	6
	Back Side	9262	1852.4	RMC 12.2kbps	23.8	22.62	1.312	0.695	0.912	--
	Back Side	9400	1880	RMC 12.2kbps	23.8	22.68	1.294	0.701	0.907	--
Hotspot (10mm Separation) (P1)	Front Side	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.365	0.463	--
	Back Side	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.718	0.910	--
	Left Edge	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.319	0.404	--
	Right Edge	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.146	0.185	--
	Bottom Edge	9538	1907.6	RMC 12.2kbps	23.8	22.77	1.268	0.459	0.582	--
	Back Side	9262	1852.4	RMC 12.2kbps	23.8	22.62	1.312	0.672	0.882	--
	Back Side	9400	1880	RMC 12.2kbps	23.8	22.68	1.294	0.685	0.887	--

Table 8: SAR Values of WCDMA BAND IV

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power(dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head (P2)	Cheek	1312	1712.4	RMC 12.2kbps	22.6	21.53	1.279	0.454	0.581	7
	Tilt	1312	1712.4	RMC 12.2kbps	22.6	21.53	1.279	0.425	0.544	--
Left Head (P2)	Cheek	1312	1712.4	RMC 12.2kbps	22.6	21.53	1.279	0.388	0.496	--
	Tilt	1312	1712.4	RMC 12.2kbps	22.6	21.53	1.279	0.355	0.454	--
Body-worn (10mm Separation) (P1)	Front Side	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.493	0.632	--
	Back Side	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.814	1.044	8
	Back Side	1413	1732.6	RMC 12.2kbps	24.5	23.31	1.315	0.787	1.035	--
	Back Side	1513	1752.6	RMC 12.2kbps	24.5	23.19	1.352	0.764	1.033	--
Hotspot (10mm Separation) (P1)	Front Side	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.481	0.617	--
	Back Side	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.788	1.010	--
	Left Edge	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.422	0.541	--
	Right Edge	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.185	0.237	--
	Bottom Edge	1312	1712.4	RMC 12.2kbps	24.5	23.42	1.282	0.734	0.941	--
	Back Side	1413	1732.6	RMC 12.2kbps	24.5	23.31	1.315	0.765	1.006	--
	Back Side	1513	1752.6	RMC 12.2kbps	24.5	23.19	1.352	0.742	1.003	--
	Bottom Edge	1413	1732.6	RMC 12.2kbps	24.5	23.31	1.315	0.709	0.932	--
	Bottom Edge	1513	1752.6	RMC 12.2kbps	24.5	23.19	1.352	0.687	0.929	--

Table 9: SAR Values of WCDMA BAND V (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power(dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.619	0.792	--
	Tilt	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.595	0.761	--
Left Head	Cheek	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.678	0.867	9
	Tilt	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.655	0.838	--
	Cheek	4183	836.6	RMC 12.2kbps	24.3	23.21	1.285	0.665	0.855	--
	Cheek	4233	846.6	RMC 12.2kbps	24.3	23.13	1.309	0.642	0.840	--
	Tilt	4183	836.6	RMC 12.2kbps	24.3	23.21	1.285	0.646	0.830	--
	Tilt	4233	846.6	RMC 12.2kbps	24.3	23.13	1.309	0.621	0.813	--
Body-worn (10mm Separation)	Front Side	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.196	0.251	--
	Back Side	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.235	0.301	--
Hotspot (10mm Separation)	Front Side	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.187	0.239	--
	Back Side	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.212	0.271	--
	Left Edge	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.228	0.292	--
	Right Edge	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.049	0.063	--
	Top Edge	4132	826.4	RMC 12.2kbps	24.3	23.23	1.279	0.239	0.306	10

Table 10: SAR Values of LTE BAND 2, 5MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Body-worn (10mm Separation) (P1)	Front Side	19175	1907.5	23.6	22.58	0	1.265	0.538	0.680	--
		Back Side	19175	1907.5	23.6	22.58	0	1.265	0.813	1.028	12
		Back Side	18625	1852.5	23.3	22.21	0	1.285	0.771	0.991	--
		Back Side	18900	1880	23.4	22.38	0	1.265	0.786	0.994	--
	Hotspot (10mm Separation) (P1)	Front Side	19175	1907.5	23.6	22.58	0	1.265	0.514	0.650	--
		Back Side	19175	1907.5	23.6	22.58	0	1.265	0.802	1.014	--
		Left Edge	19175	1907.5	23.6	22.58	0	1.265	0.365	0.462	--
		Right Edge	19175	1907.5	23.6	22.58	0	1.265	0.136	0.172	--
		Bottom Edge	19175	1907.5	23.6	22.58	0	1.265	0.483	0.611	--
		Back Side	18625	1852.5	23.3	22.21	0	1.285	0.758	0.974	--
		Back Side	18900	1880	23.4	22.38	0	1.265	0.761	0.962	--
50%RB #0	Body-worn (10mm Separation) (P1)	Front Side	19175	1907.5	23.6	22.58	1	1.265	0.516	0.653	--
		Back Side	19175	1907.5	23.6	22.58	1	1.265	0.783	0.990	--
		Back Side	18625	1852.5	23.3	22.21	1	1.285	0.744	0.956	--
		Back Side	18900	1880	23.4	22.38	1	1.265	0.757	0.957	--
	Hotspot (10mm Separation) (P1)	Front Side	19175	1907.5	23.6	22.58	1	1.265	0.471	0.596	--
		Back Side	19175	1907.5	23.6	22.58	1	1.265	0.766	0.969	--
		Left Edge	19175	1907.5	23.6	22.58	1	1.265	0.338	0.427	--
		Right Edge	19175	1907.5	23.6	22.58	1	1.265	0.125	0.158	--
		Bottom Edge	19175	1907.5	23.6	22.58	1	1.265	0.462	0.584	--
		Back Side	18625	1852.5	23.3	22.21	1	1.285	0.737	0.947	--
		Back Side	18900	1880	23.4	22.38	1	1.265	0.752	0.951	--

Table 11: SAR Values of LTE BAND 2, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head (P2)	Cheek	19100	1900	21.9	20.85	0	1.274	0.494	0.629	11
		Tilt	19100	1900	21.9	20.85	0	1.274	0.466	0.593	--
	Left Head (P2)	Cheek	19100	1900	21.9	20.85	0	1.274	0.427	0.544	--
		Tilt	19100	1900	21.9	20.85	0	1.274	0.407	0.518	--
	Body-worn (10mm Separation) (P1)	Front Side	19100	1900	23.5	22.44	0	1.276	0.485	0.619	--
		Back Side	19100	1900	23.5	22.44	0	1.276	0.758	0.968	--
		Back Side	18700	1860	23.2	22.17	0	1.268	0.706	0.895	--
		Back Side	18900	1880	23.4	22.31	0	1.285	0.723	0.929	--
	Hotspot (10mm Separation) (P1)	Front Side	19100	1900	23.5	22.44	0	1.276	0.465	0.594	--
		Back Side	19100	1900	23.5	22.44	0	1.276	0.732	0.934	--
		Left Edge	19100	1900	23.5	22.44	0	1.276	0.317	0.405	--
		Right Edge	19100	1900	23.5	22.44	0	1.276	0.116	0.148	--
		Bottom Edge	19100	1900	23.5	22.44	0	1.276	0.439	0.560	--
		Back Side	18700	1860	23.2	22.17	0	1.268	0.701	0.889	--
		Back Side	18900	1880	23.4	22.31	0	1.285	0.715	0.919	--
50% RB #0	Right Head (P2)	Cheek	19100	1900	21.9	20.85	0	1.274	0.453	0.577	--
		Tilt	19100	1900	21.9	20.85	0	1.274	0.406	0.517	--
	Left Head (P2)	Cheek	19100	1900	21.9	20.85	0	1.274	0.392	0.499	--
		Tilt	19100	1900	21.9	20.85	0	1.274	0.349	0.444	--
	Body-worn (10mm Separation) (P1)	Front Side	19100	1900	23.5	22.44	1	1.276	0.461	0.588	--
		Back Side	19100	1900	23.5	22.44	1	1.276	0.735	0.938	--
		Back Side	18700	1860	23.2	22.17	1	1.268	0.682	0.865	--
		Back Side	18900	1880	23.4	22.31	1	1.285	0.704	0.905	--
	Hotspot (10mm Separation) (P1)	Front Side	19100	1900	23.5	22.44	1	1.276	0.453	0.578	--
		Back Side	19100	1900	23.5	22.44	1	1.276	0.714	0.911	--
		Left Edge	19100	1900	23.5	22.44	1	1.276	0.303	0.387	--
		Right Edge	19100	1900	23.5	22.44	1	1.276	0.109	0.139	--
		Bottom Edge	19100	1900	23.5	22.44	1	1.276	0.425	0.542	--
		Back Side	18700	1860	23.2	22.17	1	1.268	0.669	0.848	--
		Back Side	18900	1880	23.4	22.31	1	1.285	0.682	0.877	--

Table 12: SAR Values of LTE BAND 4, 5MHz, 16QAM

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head (P2)	Cheek	20175	1732.5	20.6	19.59	0	1.262	0.385	0.486	13
		Tilt	20175	1732.5	20.6	19.59	0	1.262	0.294	0.371	--
	Left Head (P2)	Cheek	20175	1732.5	20.6	19.59	0	1.262	0.362	0.457	--
		Tilt	20175	1732.5	20.6	19.59	0	1.262	0.247	0.312	--
50%RB #0	Right Head (P2)	Cheek	20175	1732.5	20.6	19.59	1	1.262	0.209	0.264	--
		Tilt	20175	1732.5	20.6	19.59	1	1.262	0.134	0.169	--
	Left Head (P2)	Cheek	20175	1732.5	20.6	19.59	1	1.262	0.249	0.314	--
		Tilt	20175	1732.5	20.6	19.59	1	1.262	0.108	0.136	--

Table 13: SAR Values of LTE BAND 4, 3MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Body-worn (10mm Separation) (P1)	Front Side	19965	1711.5	22.4	21.34	0	1.276	0.444	0.567	--
		Back Side	19965	1711.5	22.4	21.34	0	1.276	0.733	0.936	14
		Back Side	20175	1732.5	22.3	21.28	0	1.265	0.589	0.745	--
		Back Side	20385	1753.5	22.2	21.13	0	1.279	0.657	0.841	--
	Hotspot (10mm Separation) (P1)	Front Side	19965	1711.5	22.4	21.34	0	1.276	0.432	0.551	--
		Back Side	19965	1711.5	22.4	21.34	0	1.276	0.710	0.906	--
		Left Edge	19965	1711.5	22.4	21.34	0	1.276	0.364	0.465	--
		Right Edge	19965	1711.5	22.4	21.34	0	1.276	0.154	0.197	--
		Bottom Edge	19965	1711.5	22.4	21.34	0	1.276	0.494	0.631	--
		Back Side	20175	1732.5	22.3	21.28	0	1.265	0.594	0.751	--
		Back Side	20385	1753.5	22.2	21.13	0	1.279	0.632	0.809	--
50% RB #0	Body-worn (10mm Separation) (P1)	Front Side	19965	1711.5	22.4	21.34	1	1.276	0.408	0.521	--
		Back Side	19965	1711.5	22.4	21.34	1	1.276	0.683	0.872	--
		Back Side	20175	1732.5	22.3	21.28	1	1.265	0.606	0.766	--
		Back Side	20385	1753.5	22.2	21.13	1	1.279	0.587	0.751	--
	Hotspot (10mm Separation) (P1)	Front Side	19965	1711.5	22.4	21.34	1	1.276	0.389	0.497	--
		Back Side	19965	1711.5	22.4	21.34	1	1.276	0.674	0.860	--
		Left Edge	19965	1711.5	22.4	21.34	1	1.276	0.372	0.475	--
		Right Edge	19965	1711.5	22.4	21.34	1	1.276	0.104	0.133	--
		Bottom Edge	19965	1711.5	22.4	21.34	1	1.276	0.408	0.521	--
		Back Side	20175	1732.5	22.3	21.28	1	1.265	0.602	0.761	--
		Back Side	20385	1753.5	22.2	21.13	1	1.279	0.590	0.755	--

Table 14: SAR Values of LTE BAND 4, 20MHz, 16QAM

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head (P2)	Cheek	20050	1720	20.6	19.56	0	1.271	0.348	0.442	--
		Tilt	20050	1720	20.6	19.56	0	1.271	0.218	0.277	--
	Left Head (P2)	Cheek	20050	1720	20.6	19.56	0	1.271	0.317	0.403	--
		Tilt	20050	1720	20.6	19.56	0	1.271	0.195	0.248	--
50%RB #0	Right Head (P2)	Cheek	20050	1720	20.6	19.56	1	1.271	0.371	0.471	--
		Tilt	20050	1720	20.6	19.56	1	1.271	0.262	0.333	--
	Left Head (P2)	Cheek	20050	1720	20.6	19.56	1	1.271	0.321	0.408	--
		Tilt	20050	1720	20.6	19.56	1	1.271	0.204	0.259	--

Table 15: SAR Values of LTE BAND 4, 20MHz, QPSK

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Body-worn (10mm Separation) (P1)	Front Side	20175	1732.5	22.2	21.15	0	1.274	0.354	0.451	--
		Back Side	20175	1732.5	22.2	21.15	0	1.274	0.676	0.861	--
		Back Side	20050	1720	22.2	21.11	0	1.285	0.568	0.730	--
		Back Side	20300	1745	22.1	21.10	0	1.259	0.509	0.641	--
	Hotspot (10mm Separation) (P1)	Front Side	20175	1732.5	22.2	21.15	0	1.274	0.439	0.559	--
		Back Side	20175	1732.5	22.2	21.15	0	1.274	0.701	0.893	--
		Left Edge	20175	1732.5	22.2	21.15	0	1.274	0.351	0.447	--
		Right Edge	20175	1732.5	22.2	21.15	0	1.274	0.163	0.208	--
		Bottom Edge	20175	1732.5	22.2	21.15	0	1.274	0.427	0.544	--
		Back Side	20050	1720	22.2	21.11	0	1.285	0.518	0.666	--
		Back Side	20300	1745	22.1	21.10	0	1.259	0.645	0.812	--
50% RB #0	Body-worn (10mm Separation) (P1)	Front Side	20175	1732.5	22.2	21.15	1	1.274	0.401	0.511	--
		Back Side	20175	1732.5	22.2	21.15	1	1.274	0.643	0.819	--
		Back Side	20050	1720	22.2	21.11	1	1.285	0.504	0.648	--
		Back Side	20300	1745	22.1	21.10	1	1.259	0.498	0.627	--
	Hotspot (10mm Separation) (P1)	Front Side	20175	1732.5	22.2	21.15	1	1.274	0.378	0.481	--
		Back Side	20175	1732.5	22.2	21.15	1	1.274	0.683	0.870	--
		Left Edge	20175	1732.5	22.2	21.15	1	1.274	0.318	0.405	--
		Right Edge	20175	1732.5	22.2	21.15	1	1.274	0.124	0.158	--
		Bottom Edge	20175	1732.5	22.2	21.15	1	1.274	0.372	0.474	--
		Back Side	20050	1720	22.2	21.11	1	1.285	0.614	0.789	--
		Back Side	20300	1745	22.1	21.10	1	1.259	0.574	0.723	--

Table 16: SAR Values of LTE BAND 5, 10MHz, QPSK (P1)

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	20450	829	25.4	24.31	0	1.285	0.279	0.359	--
		Tilt	20450	829	25.4	24.31	0	1.285	0.253	0.325	--
	Left Head	Cheek	20450	829	25.4	24.31	0	1.285	0.311	0.400	15
		Tilt	20450	829	25.4	24.31	0	1.285	0.296	0.380	--
	Body-worn (10mm Separation)	Front Side	20450	829	25.4	24.31	0	1.285	0.137	0.176	--
		Back Side	20450	829	25.4	24.31	0	1.285	0.32	0.411	--
	Hotspot (10mm Separation)	Front Side	20450	829	25.4	24.31	0	1.285	0.132	0.170	--
		Back Side	20450	829	25.4	24.31	0	1.285	0.315	0.405	--
		Left Edge	20450	829	25.4	24.31	0	1.285	0.195	0.251	--
		Right Edge	20450	829	25.4	24.31	0	1.285	0.307	0.395	--
		Top Edge	20450	829	25.4	24.31	0	1.285	0.334	0.429	16
50%RB #0	Right Head	Cheek	20450	829	25.4	24.31	1	1.285	0.255	0.328	--
		Tilt	20450	829	25.4	24.31	1	1.285	0.232	0.298	--
	Left Head	Cheek	20450	829	25.4	24.31	1	1.285	0.297	0.382	--
		Tilt	20450	829	25.4	24.31	1	1.285	0.274	0.352	--
	Body-worn (10mm Separation)	Front Side	20450	829	25.4	24.31	1	1.285	0.131	0.168	--
		Back Side	20450	829	25.4	24.31	1	1.285	0.305	0.392	--
	Hotspot (10mm Separation)	Front Side	20450	829	25.4	24.31	1	1.285	0.122	0.157	--
		Back Side	20450	829	25.4	24.31	1	1.285	0.286	0.368	--
		Left Edge	20450	829	25.4	24.31	1	1.285	0.186	0.239	--
		Right Edge	20450	829	25.4	24.31	1	1.285	0.289	0.371	--
		Top Edge	20450	829	25.4	24.31	1	1.285	0.312	0.401	--

Table 17: SAR Values of LTE BAND 7, 20MHz, QPSK (P1)

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	21350	2560	23.1	22.01	0	1.285	0.617	0.793	--
		Tilt	21350	2560	23.1	22.01	0	1.285	0.592	0.761	--
	Left Head	Cheek	21350	2560	23.1	22.01	0	1.285	0.663	0.852	17
		Tilt	21350	2560	23.1	22.01	0	1.285	0.648	0.833	--
		Cheek	20850	2510	22.9	21.83	0	1.279	0.645	0.825	--
		Cheek	21100	2535	22.8	21.77	0	1.268	0.64	0.811	--
		Tilt	20850	2510	22.9	21.83	0	1.279	0.636	0.814	--
		Tilt	21100	2535	22.8	21.77	0	1.268	0.629	0.797	--
	Body-worn (10mm Separation)	Front Side	21350	2560	23.1	22.01	0	1.285	0.427	0.549	--
		Back Side	21350	2560	23.1	22.01	0	1.285	0.585	0.752	--
	Hotspot (10mm Separation)	Front Side	21350	2560	23.1	22.01	0	1.285	0.422	0.542	--
		Back Side	21350	2560	23.1	22.01	0	1.285	0.576	0.740	--
		Left Edge	21350	2560	23.1	22.01	0	1.285	0.176	0.226	--
		Right Edge	21350	2560	23.1	22.01	0	1.285	0.161	0.207	--
		Bottom Edge	21350	2560	23.1	22.01	0	1.285	0.768	0.987	18
		Bottom Edge	20850	2510	22.9	21.83	0	1.279	0.751	0.961	--
		Bottom Edge	21100	2535	22.8	21.77	0	1.268	0.743	0.942	--

Table 18: SAR Values of LTE BAND 7, 20MHz, QPSK (P1)

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
50%RB #0	Right Head	Cheek	21350	2560	23.1	22.01	1	1.285	0.595	0.765	--
		Tilt	21350	2560	23.1	22.01	1	1.285	0.578	0.743	--
	Left Head	Cheek	21350	2560	23.1	22.01	1	1.285	0.647	0.832	--
		Tilt	21350	2560	23.1	22.01	1	1.285	0.634	0.815	--
		Cheek	20850	2510	22.9	21.83	1	1.279	0.636	0.814	--
		Cheek	21100	2535	22.8	21.77	1	1.268	0.623	0.790	--
		Tilt	20850	2510	22.9	21.83	1	1.279	0.619	0.792	--
		Tilt	21100	2535	22.8	21.77	1	1.268	0.612	0.776	--
	Body-worn (10mm Separation)	Front Side	21350	2560	23.1	22.01	1	1.285	0.415	0.533	--
		Back Side	21350	2560	23.1	22.01	1	1.285	0.573	0.736	--
	Hotspot (10mm Separation)	Front Side	21350	2560	23.1	22.01	1	1.285	0.406	0.522	--
		Back Side	21350	2560	23.1	22.01	1	1.285	0.551	0.708	--
		Left Edge	21350	2560	23.1	22.01	1	1.285	0.171	0.220	--
		Right Edge	21350	2560	23.1	22.01	1	1.285	0.145	0.186	--
		Bottom Edge	21350	2560	23.1	22.01	1	1.285	0.752	0.967	--
		Bottom Edge	20850	2510	22.9	21.83	1	1.279	0.743	0.951	--
		Bottom Edge	21100	2535	22.8	21.77	1	1.268	0.726	0.920	--

Table 19: SAR Values of LTE BAND 13, 10MHz, QPSK (P1)

Test Mode	Test Positions		Channel		Power(dBm)		MPR (dB)	SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
			CH.	MHz	Maximum Turn-up Power (dBm)	Measured output power (dBm)		Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
1RB #49	Right Head	Cheek	23230	782.0	25.4	24.34	0	1.276	0.154	0.197	--
		Tilt	23230	782.0	25.4	24.34	0	1.276	0.139	0.177	--
	Left Head	Cheek	23230	782.0	25.4	24.34	0	1.276	0.183	0.234	19
		Tilt	23230	782.0	25.4	24.34	0	1.276	0.165	0.211	--
	Body-worn (10mm Separation)	Front Side	23230	782.0	25.4	24.34	0	1.276	0.079	0.101	--
		Back Side	23230	782.0	25.4	24.34	0	1.276	0.176	0.225	--
	Hotspot (10mm Separation)	Front Side	23230	782.0	25.4	24.34	0	1.276	0.072	0.092	--
		Back Side	23230	782.0	25.4	24.34	0	1.276	0.166	0.212	--
		Left Edge	23230	782.0	25.4	24.34	0	1.276	0.172	0.220	--
		Right Edge	23230	782.0	25.4	24.34		1.276	0.249	0.318	20
		Top Edge	23230	782.0	25.4	24.34	0	1.276	0.180	0.230	--
50%RB #0	Right Head	Cheek	23230	782.0	25.4	24.34	1	1.276	0.147	0.188	--
		Tilt	23230	782.0	25.4	24.34	1	1.276	0.131	0.167	--
	Left Head	Cheek	23230	782.0	25.4	24.34	1	1.276	0.168	0.214	--
		Tilt	23230	782.0	25.4	24.34	1	1.276	0.160	0.204	--
	Body-worn (10mm Separation)	Front Side	23230	782.0	25.4	24.34	1	1.276	0.064	0.082	--
		Back Side	23230	782.0	25.4	24.34	1	1.276	0.158	0.202	--
	Hotspot (10mm Separation)	Front Side	23230	782.0	25.4	24.34	1	1.276	0.063	0.080	--
		Back Side	23230	782.0	25.4	24.34	1	1.276	0.162	0.207	--
		Left Edge	23230	782.0	25.4	24.34	1	1.276	0.157	0.200	--
		Right Edge	23230	782.0	25.4	24.34		1.276	0.232	0.296	--
		Top Edge	23230	782.0	25.4	24.34	1	1.276	0.166	0.212	--

Table 20: SAR Values of 2.4G Wi-Fi (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power (dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	6	2437	802.11g	23.6	22.5	1.288	0.395	0.509	21
	Tilt	6	2437	802.11g	23.6	22.5	1.288	0.372	0.479	--
Left Head	Cheek	6	2437	802.11g	23.6	22.5	1.288	0.376	0.484	--
	Tilt	6	2437	802.11g	23.6	22.5	1.288	0.344	0.443	--
Body-worn (10mm Separation)	Front Side	6	2437	802.11g	23.6	22.5	1.288	0.168	0.216	--
	Back Side	6	2437	802.11g	23.6	22.5	1.288	0.201	0.259	--
Hotspot (10mm Separation)	Front Side	6	2437	802.11g	23.6	22.5	1.288	0.155	0.200	--
	Back Side	6	2437	802.11g	23.6	22.5	1.288	0.187	0.241	--
	Right Edge	6	2437	802.11g	23.6	22.5	1.288	0.277	0.357	22
	Top Edge	6	2437	802.11g	23.6	22.5	1.288	0.085	0.110	--

Table 21: SAR Values of Bluetooth (P1)

Test Positions		Channel		Test Mode	Power(dBm)		SAR 1g(W/Kg), Limit(1.6W/kg)			Plot No.
		CH.	MHz		Maximum Turn-up Power (dBm)	Measured output power (dBm)	Scaling Factor	Measured SAR 1g(W/kg)	Scaled SAR 1g(W/kg)	
Right Head	Cheek	0	2402	GFSK	9.6	8.54	1.276	0.390	0.498	23
	Tilt	0	2402	GFSK	9.6	8.54	1.276	0.359	0.458	--
Left Head	Cheek	0	2402	GFSK	9.6	8.54	1.276	0.365	0.466	--
	Tilt	0	2402	GFSK	9.6	8.54	1.276	0.342	0.437	--
Body-worn (10mm Separation)	Front Side	0	2402	GFSK	9.6	8.54	1.276	0.135	0.172	--
	Back Side	0	2402	GFSK	9.6	8.54	1.276	0.172	0.220	--
Hotspot (10mm Separation)	Front Side	0	2402	GFSK	9.6	8.54	1.276	0.124	0.158	--
	Back Side	0	2402	GFSK	9.6	8.54	1.276	0.159	0.203	--
	Right Edge	0	2402	GFSK	9.6	8.54	1.276	0.198	0.253	24
	Top Edge	0	2402	GFSK	9.6	8.54	1.276	0.063	0.080	--

Note:

1. According to KDB 648474-D04 Handset SAR v01r03 section 1.5, the diagonal dimension of this device is > 16.0 cm, but the hotspot mode 1-g reported SAR is 1.044 W/kg < 1.2 W/kg, so the 10-g extremity SAR is required.
2. 5G Wi-Fi SAR tested results please refer to the test report WTX26X06180335W.

Measurement variability consideration

According to KDB 865664 D01v01r04 section 2.8.1, repeated measurements are required following the procedures as below:

Repeated measurement is not required when the original highest measured SAR is $< 0.80 \text{ W/kg}$; steps 2) through 4) do not apply.

When the original highest measured SAR is $\geq 0.80 \text{ W/kg}$, repeat that measurement once.

Perform a second repeated measurement only if the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 or when the original or repeated measurement is $\geq 1.45 \text{ W/kg}$ (~ 10% from the 1-g SAR limit).

Perform a third repeated measurement only if the original, first or second repeated measurement is $\geq 1.5 \text{ W/kg}$ and the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 .

Repeated SAR

Body SAR Test								
Band	Mode	Test Position Body	Frequency	SAR1g (W/kg)	Repeated SAR		Ratio	
			MHz		1	2	1	2
WCDMA BAND IV	RMC 12.2kbps	Back Side	1712.4	0.814	0.809	/	1.006	/
LTE BAND 2	QPSK 1RB 5MHz	Back Side	1907.5	0.813	0.810	/	1.004	/

Hotspot SAR Test								
Band	Mode	Test Position Body	Frequency	SAR1g (W/kg)	Repeated SAR		Ratio	
			MHz		1	2	1	2
LTE BAND 2	QPSK 1RB 5MHz	Back Side	1907.5	0.802	0.796	/	1.008	/

Simultaneous Transmission SAR Analysis.**List of Mode for Simultaneous Multi-band Transmission:**

No.	Configurations	Head SAR	Body-worn SAR	Hotspot SAR
1	GSM(Voice) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
2	GPRS (Data) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
3	GSM(Voice) + WLAN 5GHz(Data)	Yes	Yes	Yes
4	GPRS (Data) + WLAN 5GHz(Data)	Yes	Yes	Yes
5	GSM(Voice) + Bluetooth(Data)	Yes	Yes	Yes
6	GPRS (Data) + Bluetooth(Data)	Yes	Yes	Yes
7	WCDMA (Voice) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
8	WCDMA (Data) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
9	WCDMA (Voice) + WLAN 5GHz(Data)	Yes	Yes	Yes
10	WCDMA (Data) + WLAN 5GHz(Data)	Yes	Yes	Yes
11	WCDMA (Voice) + Bluetooth(Data)	Yes	Yes	Yes
12	WCDMA (Data) + Bluetooth(Data)	Yes	Yes	Yes
13	LTE (Data) + WLAN 2.4GHz(Data)	Yes	Yes	Yes
14	LTE (Data) + WLAN 5GHz(Data)	Yes	Yes	Yes
15	LTE (Data) + Bluetooth(Data)	Yes	Yes	Yes

Remark:

1. GSM/ WCDMA/LTE share the same antenna, and cannot transmit simultaneously.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. According to the KDB 447498 D01 v06, when standalone SAR test exclusion applies to an antenna that transmits simultaneously with other antennas, the standalone SAR must be estimated according to following to determine simultaneous transmission SAR test exclusion:

$$(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm}) \cdot [\sqrt{f(\text{GHz})}/x]$$
W/kg for test separation distances ≤ 50 mm;
where $x = 7.5$ for 1-g SAR, and $x = 18.75$ for 10-g SAR.
For simultaneous transmission analysis, Bluetooth SAR is estimated per KDB 447498 D01 v06 as below:
4. The maximum SAR summation is calculated based on the same configuration and test position

Head SAR Simultaneous**WWAN and 2.4G Wi-Fi**

Position	WWAN (maximum)		2.4G Wi-Fi	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850(Voice call)	0.830	0.509	1.339
Right Tilt	GSM850(Voice call)	0.800	0.479	1.279
Left Cheek	GSM850(Voice call)	0.885	0.484	1.369
Left Tilt	GSM850(Voice call)	0.841	0.443	1.284
Right Cheek	WCDMA BAND V	0.792	0.509	1.301
Right Tilt	WCDMA BAND V	0.761	0.479	1.240
Left Cheek	WCDMA BAND V	0.867	0.484	1.351
Left Tilt	WCDMA BAND V	0.838	0.443	1.281
Right Cheek	LTE BAND 7(1RB)	0.793	0.509	1.302
Right Tilt	LTE BAND 7(1RB)	0.761	0.479	1.240
Left Cheek	LTE BAND 7(1RB)	0.852	0.484	1.336
Left Tilt	LTE BAND 7(1RB)	0.833	0.443	1.276

WWAN and 5G Wi-Fi

Position	WWAN (maximum)		5G Wi-Fi	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850(Voice call)	0.830	0.193	1.023
Right Tilt	GSM850(Voice call)	0.800	0.202	1.002
Left Cheek	GSM850(Voice call)	0.885	0.375	1.260
Left Tilt	GSM850(Voice call)	0.841	0.358	1.199
Right Cheek	WCDMA BAND V	0.792	0.193	0.985
Right Tilt	WCDMA BAND V	0.761	0.202	0.963
Left Cheek	WCDMA BAND V	0.867	0.375	1.242
Left Tilt	WCDMA BAND V	0.838	0.358	1.196
Right Cheek	LTE BAND 7(1RB)	0.793	0.193	0.986
Right Tilt	LTE BAND 7(1RB)	0.761	0.202	0.963
Left Cheek	LTE BAND 7(1RB)	0.852	0.375	1.227
Left Tilt	LTE BAND 7(1RB)	0.833	0.358	1.191

WWAN and BT

Position	WWAN (maximum)		BT	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Right Cheek	GSM850(Voice call)	0.830	0.498	1.328
Right Tilt	GSM850(Voice call)	0.800	0.458	1.258
Left Cheek	GSM850(Voice call)	0.885	0.466	1.351
Left Tilt	GSM850(Voice call)	0.841	0.437	1.278
Right Cheek	WCDMA BAND V	0.792	0.498	1.290
Right Tilt	WCDMA BAND V	0.761	0.458	1.219
Left Cheek	WCDMA BAND V	0.867	0.466	1.333
Left Tilt	WCDMA BAND V	0.838	0.437	1.275
Right Cheek	LTE BAND 7(1RB)	0.793	0.498	1.291
Right Tilt	LTE BAND 7(1RB)	0.761	0.458	1.219
Left Cheek	LTE BAND 7(1RB)	0.852	0.466	1.318
Left Tilt	LTE BAND 7(1RB)	0.833	0.437	1.270

Body-worn SAR Simultaneous**WWAN and 2.4G Wi-Fi**

Position	WWAN (maximum)		2.4G Wi-Fi (10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(Voice call)	0.339	0.216	0.555
Back	GSM1900(Voice call)	0.672	0.259	0.931
Front	WCDMA BAND IV	0.632	0.216	0.848
Back	WCDMA BAND IV	1.044	0.259	1.303
Front	LTE BAND 2(1RB)	0.68	0.216	0.896
Back	LTE BAND 2(1RB)	1.028	0.259	1.287

WWAN and 5G Wi-Fi

Position	WWAN (maximum)		5G Wi-Fi (10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(Voice call)	0.339	0.224	0.563
Back	GSM1900(Voice call)	0.672	0.072	0.744
Front	WCDMA BAND IV	0.632	0.224	0.856
Back	WCDMA BAND IV	1.044	0.072	1.116
Front	LTE BAND 2(1RB)	0.68	0.224	0.904
Back	LTE BAND 2(1RB)	1.028	0.072	1.100

WWAN and BT

Position	WWAN (maximum)		BT(10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(Voice call)	0.339	0.172	0.511
Back	GSM1900(Voice call)	0.672	0.220	0.892
Front	WCDMA BAND IV	0.632	0.172	0.804
Back	WCDMA BAND IV	1.044	0.220	1.264
Front	LTE BAND 2(1RB)	0.68	0.172	0.852
Back	LTE BAND 2(1RB)	1.028	0.220	1.248

Hotspot SAR Simultaneous**WWAN and 2.4G Wi-Fi**

Position	WWAN (maximum)		2.4G Wi-Fi (10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(GPRS 2 slots)	0.672	0.200	0.872
Back	GSM1900(GPRS 2 slots)	0.319	0.241	0.560
Left	GSM1900(GPRS 2 slots)	0.659	-	0.659
Right	GSM1900(GPRS 2 slots)	0.242	0.357	0.599
Top	GSM850(GPRS 3 slots)	0.170	0.110	0.280
Bottom	GSM1900(GPRS 2 slots)	0.271	-	0.271
Front	WCDMA BAND IV	0.617	0.200	0.817
Back	WCDMA BAND IV	1.010	0.241	1.251
Left	WCDMA BAND IV	0.541	-	0.541
Right	WCDMA BAND IV	0.237	0.357	0.594
Top	WCDMA BAND V	0.306	0.110	0.416
Bottom	WCDMA BAND IV	0.941	-	0.941
Front	LTE BAND 1(1RB)	0.650	0.200	0.850
Back	LTE BAND 2(1RB)	1.014	0.241	1.255
Left	LTE BAND 2(1RB)	0.465	-	0.465
Right	LTE BAND 5(1RB)	0.395	0.357	0.752
Top	LTE BAND 5(1RB)	0.429	0.110	0.539
Bottom	LTE BAND 7(1RB)	0.987	-	0.987

WWAN and 5G Wi-Fi

Position	WWAN (maximum)		5G Wi-Fi (10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(GPRS 2 slots)	0.672	0.072	0.744
Back	GSM1900(GPRS 2 slots)	0.319	0.224	0.543
Left	GSM1900(GPRS 2 slots)	0.659	-	0.659
Right	GSM1900(GPRS 2 slots)	0.242	0.240	0.482
Top	GSM850(GPRS 3 slots)	0.170	0.061	0.231
Bottom	GSM1900(GPRS 2 slots)	0.271	-	0.271
Front	WCDMA BAND IV	0.617	0.072	0.689
Back	WCDMA BAND IV	1.010	0.224	1.234
Left	WCDMA BAND IV	0.541	-	0.541
Right	WCDMA BAND IV	0.237	0.240	0.477
Top	WCDMA BAND V	0.306	0.061	0.367
Bottom	WCDMA BAND IV	0.941	-	0.941
Front	LTE BAND 1(1RB)	0.650	0.072	0.722
Back	LTE BAND 2(1RB)	1.014	0.224	1.238
Left	LTE BAND 2(1RB)	0.465	-	0.465
Right	LTE BAND 5(1RB)	0.395	0.240	0.635
Top	LTE BAND 5(1RB)	0.429	0.061	0.490
Bottom	LTE BAND 7(1RB)	0.987	-	0.987

WWAN and BT

Position	WWAN (maximum)		BT (10mm)	Summed SAR (W/kg)
	Band	Scaled SAR (W/kg)	Scaled SAR (W/kg)	
Front	GSM1900(GPRS 2 slots)	0.672	0.158	0.830
Back	GSM1900(GPRS 2 slots)	0.319	0.203	0.522
Left	GSM1900(GPRS 2 slots)	0.659	-	0.659
Right	GSM1900(GPRS 2 slots)	0.242	0.253	0.495
Top	GSM850(GPRS 3 slots)	0.170	0.080	0.250
Bottom	GSM1900(GPRS 2 slots)	0.271	-	0.271
Front	WCDMA BAND IV	0.617	0.158	0.775
Back	WCDMA BAND IV	1.010	0.203	1.213
Left	WCDMA BAND IV	0.541	-	0.541
Right	WCDMA BAND IV	0.237	0.253	0.490
Top	WCDMA BAND V	0.306	0.080	0.386
Bottom	WCDMA BAND IV	0.941	-	0.941
Front	LTE BAND 1(1RB)	0.650	0.158	0.808
Back	LTE BAND 2(1RB)	1.014	0.203	1.217
Left	LTE BAND 2(1RB)	0.465	-	0.465
Right	LTE BAND 5(1RB)	0.395	0.253	0.648
Top	LTE BAND 5(1RB)	0.429	0.080	0.509
Bottom	LTE BAND 7(1RB)	0.987	-	0.987


15 SAR Measurement Reference

15.1 References


1. FCC 47 CFR Part 2 “Frequency Allocations and Radio Treaty Matters; General Rules and Regulations”
2. IEEE Std. C95.1:2019, “IEEE Standard for Safety Levels with Respect to Human Exposure to Electric, Magnetic, and Electromagnetic Fields, 0 Hz to 300 GHz”, 2019
3. IEC/IEEE 62209-1528:2020, Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices –Part 1528: Human models, instrumentation, and procedures (Frequency range of 4 MHz to 10 GHz)
4. FCC KDB 447498 D01 v06, “Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies”, Oct 23th, 2015
5. FCC KDB 941225 D01 v03r01, “3G SAR Measurement Procedures”, Oct 23th, 2015
6. FCC KDB 941225 D05 v02r05, “SAR Evaluation Considerations for LTE Devices”, Dec 16th, 2015
7. FCC KDB 941225 D06 v02r01, “SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities”, Oct 23th, 2015
8. FCC KDB865664 D01 v01r04, “SAR Measurement Requirements 100MHz to 6GHz”, Aug 7th, 2015
9. FCC KDB865664 D02 v01r02, “RF Exposure Compliance Reporting and Documentation Considerations ”, Oct 23th, 2015
10. FCC KDB648474 D04 v01r03, “SAR Evaluation Considerations for Wireless Handsets”, Oct 23th, 2015
11. FCC KDB 248227 D01 v02r02, SAR Guidance for IEEE 802.11 (Wi-Fi) Transmitters, Oct 23th, 2015.

15.2Maximum SAR measurement Plots


Plot 1: GPRS 850, High channel (Left Head Cheek)
Product Description:Smart Phone
Test Date: 2026-06-23




Plot 2: GPRS850, High channel (Body-worn /Hotspot, Back Side)
Product Description:Smart Phone
Test Date: 2026-06-23




Plot 3: GSM 1900, Low channel (Right Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-16




Plot 4: GSM 1900, Low channel (Body-worn /Hotspot, Back Side)
Product Description: Smart Phone
Test Date: 2026-06-16




Plot 5: WCDMA BAND II, Middle channel (Right Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-16




Plot 6: WCDMA BAND II, High channel (Body-worn /Hotspot, Back Side)
Product Description: Smart Phone
Test Date: 2026-06-16



Plot 7: WCDMA BAND IV, Low channel (Right Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-15




Plot 8: WCDMA BAND IV, Low channel (Body-worn/Hotspot, Back Side)
Product Description: Smart Phone
Test Date: 2026-06-15




Plot 9: WCDMA BAND V, Low channel (Left Head Cheek)

Product Description: Smart Phone


Test Date: 2026-01-25



Plot 10: WCDMA BAND V, Low channel (Body-worn/Hotspot, Top Edge)
Product Description: Smart Phone
Test Date: 2026-01-25




Plot 11:LTE BAND 2, High channel (Right Head Cheek)
Product Description:Smart Phone
Test Date: 2026-06-16




Plot 12:LTE BAND 2, High channel (Body-worn /Hotspot, Back Side)

Product Description:Smart Phone
Test Date: 2026-06-16




Plot 13:LTE BAND 4, Middle channel (Right Head Cheek)


Product Description: Smart Phone
Test Date: 2026-06-15




Plot 14: LTE BAND 4, Low channel (Body-worn/ Hotspot, Back Side)
Product Description: Smart Phone
Test Date: 2026-06-15




Plot 15:LTE BAND 5, Low channel (Left Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-23



Plot 16: LTE BAND 5, Low channel (Body-worn/ Hotspot, Top Edge)
Product Description: Smart Phone
Test Date: 2026-06-23




Plot 17:LTE BAND 7, High channel (Left Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-17




Plot 18: LTE BAND 7, High channel (Body-worn/ Hotspot, Bottom Edge)

Product Description: Smart Phone


Test Date: 2026-06-17




Plot 19:LTE BAND 13, Low channel (Left Head Cheek)
Product Description: Smart Phone
Test Date: 2026-06-22




Plot 20: LTE BAND 13, Low channel (Body-worn/ Hotspot, Right Edge)
Product Description: Smart Phone
Test Date: 2026-06-22




Plot 21:2.4G Wi-Fi, Middle channel (Right Head Cheek)
Product Description: Smart Phone
Test Date: 2026-07-13



Plot 22: 2.4G Wi-Fi, Middle channel (Body-worn/ Hotspot, Right Edge)
Product Description: Smart Phone
Test Date: 2026-07-13




Plot 23: Bluetooth, Low channel (Right Head Cheek)
Product Description: Smart Phone
Test Date: 2026-07-13



Plot 24: Bluetooth, Low channel (Body-worn/ Hotspot, Right Edge)

Product Description: Smart Phone

Test Date: 2026-07-13



16 Calibration Reports-Probe and Dipole



COMOSAR E-Field Probe Calibration Report

Ref : ACR.304.21.27.BES.B

WALTEK TESTING GROUP CO., LTD
NO,77, HOUJIE SECTION, GUANTAI ROAD, HOUJIE TOWN
DONGGUAN GUANGDONG 518105, CHINA
MVG COMOSAR DOSIMETRIC E-FIELD PROBE
SERIAL NO.: 2523-EPGO-417

Calibrated at MVG

Z.I. de la pointe du diable

Technopôle Brest Iroise – 295 avenue Alexis de Rochon

29280 PLOUZANE - FRANCE

Calibration date: 07/25/2025



Accreditations #2-6789
Scope available on www.cofrac.fr

The use of the Cofrac brand and the accreditation references is prohibited from any reproduction.

Summary:

This document presents the method and results from an accredited COMOSAR Dosimetric E-Field Probe calibration performed at MVG, using the CALIPROBE test bench, for use with a MVG COMOSAR system only. The test results covered by accreditation are traceable to the International System of Units (SI).

Page: 1/10



COMOSAR E-FIELD PROBE CALIBRATION REPORT

Ref: ACR.304.21.27.BES.B

	Name	Function	Date	Signature
Prepared by :	Cyrille ONNEE	Measurement Responsible	7/25/2025	
Checked & approved by:	Jérôme Luc	Technical Manager	7/25/2025	
Authorized by:	Yann Toutain	Laboratory Director	7/25/2025	

Yann
Toutain ID

Signature
numérique de
Yann Toutain ID
Date : 2025.07.25
09:52:33 +01'00'

	Customer Name
Distribution :	WALTEK TESTING GROUP CO., LTD

Issue	Name	Date	Modifications
A	Cyrille ONNEE	7/25/2025	Initial release



TABLE OF CONTENTS

1 Device Under Test 4

2 Product Description 4

2.1 General Information 4

3 Measurement Method 4

3.1 Sensitivity 4

3.2 Linearity 5

3.3 Isotropy 5

3.4 Boundary Effect 5

4 Measurement Uncertainty 6

5 Calibration Results..... 6

5.1 Calibration in air 6

5.2 Calibration in liquid 7

6 Verification Results 8

7 List of Equipment 9