

Test Report

Verified code: 102948

Report No.: E20220216738902-1

Customer: Huizhou Desay SV Automotive Co., Ltd.

Address: 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone,
Huizhou, Guangdong, P.R. China

Sample Name: Multimedia Player Assembly

Sample Model: TR3392/40

Receive Sample Date: Feb.28,2022

Test Date: Mar.03,2022 ~ Jul.12,2022

Reference Document: CFR 47, FCC Part 15 Subpart C
RADIO FREQUENCY DEVICES:Subpart C—Intentional Radiators

Test Result: Pass

Prepared by: *Wen Wen*

Reviewed by:

Jiang Tao

Approved by:

Xiao Liang

GUANGZHOU GRG METROLOGY & TEST CO., LTD

Issued Date: 2022-07-27

GUANGZHOU GRG METROLOGY & TEST CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1.	TEST RESULT SUMMARY	6
2.	GENERAL DESCRIPTION OF EUT.....	7
2.1	APPLICANT	7
2.2	MANUFACTURER.....	7
2.3	FACTORY	7
2.4	BASIC DESCRIPTION OF EQUIPMENT UNDER TEST	7
2.5	TEST OPERATION MODE	8
2.6	MODEL DIFFERENCE DESCRIPTIONS.....	8
2.7	LOCAL SUPPORTIVE	9
2.8	CONFIGURATION OF SYSTEM UNDER TEST	9
2.9	DUTY CYCLE.....	10
3.	LABORATORY AND ACCREDITATIONS	12
3.1	LABORATORY	12
3.2	ACCREDITATIONS	12
3.3	MEASUREMENT UNCERTAINTY	13
4.	LIST OF USED TEST EQUIPMENT AT GRGT	14
5.	TEST RESULTS	15
5.1	EUT TEST CONDITIONS	15
5.2	20dB BANDWIDTH.....	17
5.2.1	LIMITS.....	17
5.2.2	TEST PROCEDURES	17
5.2.3	TEST SETUP	17
5.2.4	TEST RESULTS	17
5.3	CARRIER FREQUENCIES SEPARATED.....	23
5.3.1	LIMITS.....	23
5.3.2	TEST PROCEDURES	23
5.3.3	TEST SETUP	23
5.3.4	TEST RESULTS	23
5.4	HOPPING CHANNEL NUMBER.....	26
5.4.1	LIMITS.....	26
5.4.2	TEST PROCEDURES	26
5.4.3	TEST SETUP	26
5.4.4	TEST RESULTS	26
5.5	DWELL TIME	29
5.5.1	LIMITS.....	29
5.5.2	TEST PROCEDURES	29
5.5.3	TEST SETUP	29
5.5.4	TEST RESULTS	30
5.6	MAXIMUM PEAK OUTPUT POWER	36
5.6.1	LIMITS.....	36
5.6.2	TEST PROCEDURES	36

5.6.3	TEST SETUP	36
5.6.4	TEST RESULTS	37
5.7	CONDUCTED BAND EDGES AND SPURIOUS EMISSIONS	38
5.7.1	LIMITS.....	38
5.7.2	TEST PROCEDURES	38
5.7.3	TEST SETUP	38
5.7.4	TEST RESULTS	39
5.8	RADIATED SPURIOUS EMISSIONS	59
5.8.1	LIMITS.....	59
5.8.2	TEST PROCEDURES	59
5.8.3	TEST SETUP	63
5.8.4	DATA SAMPLE	64
5.8.5	TEST RESULTS	65
5.9	RESTRICTED BANDS OF OPERATION.....	87
5.9.1	LIMITS.....	87
5.9.2	TEST PROCEDURES	88
5.9.3	TEST SETUP	88
5.9.4	TEST RESULTS	89
APPENDIX A. PHOTOGRAPH OF THE TEST CONNECTION DIAGRAM		101
APPENDIX B. PHOTOGRAPH OF THE EUT		101

----- The following blanks -----

REPORT ISSUED HISTORY

Report Version	Report No.	Description	Compile Date
1.0	E20220216738902-1	Original Issue	2022-07-13

----- The following blanks -----

1. TEST RESULT SUMMARY

Standard	Item	Limit / Severity	Result
FCC 47 CFR Part 15 Subpart C (15.247) ANSI C63.10-2013 KDB 558074 D01 15.247 measurement guidance v05r02	Antenna Requirement	Section 15.203	PASS
	20dB Bandwidth	Section 15.247(a)(1)	PASS
	Carrier Frequencies Separated	Section 15.247(a)(1)	PASS
	Hopping Channel Number	Section 15.247(a)(1)(iii)	PASS
	Dwell Time	Section 15.247(a)(1)(iii)	PASS
	Maximum Peak Output Power	Section 15.247(b)(1)	PASS
	Conducted Emission	Section 15.207	N/A ¹
	Conducted band edges and Spurious Emission	Section 15.247(d)	PASS
	Radiated Spurious Emission	Section 15.247(d) &15.205 &15.209	PASS
	Restricted bands of operation	Section 15.247(d) &15.205 &15.209	PASS

Note:1. The EUT is power by battery, not applicable.

The EUT antenna is PCB Printed antenna. Max Antenna gain is 2dBi ,which accordance 15.203 is considered sufficient to comply with the provisions of this section.

----- The following blanks -----

2. GENERAL DESCRIPTION OF EUT

2.1 APPLICANT

Name: Huizhou Desay SV Automotive Co., Ltd.
Address: 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou, Guangdong, P.R. China

2.2 MANUFACTURER

Name: Huizhou Desay SV Automotive Co., Ltd.
Address: 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou, Guangdong, P.R. China

2.3 FACTORY

Name: Huizhou Desay SV Automotive Co., Ltd.
Address: 103, Hechang 5th Road West, Zhongkai National Hi-tech Industrial Development Zone, Huizhou, Guangdong, P.R. China

2.4 BASIC DESCRIPTION OF EQUIPMENT UNDER TEST

Equipment: Multimedia Player Assembly
Model No.: TR3392/40
Adding Model: TR3371/40, TR3361/40, TR3382/40
Models difference: Refer to section 2.6

Trade Name:



FCC ID: 2AEQTNV101140

Power supply: DC 12V

Frequency Range: 2402MHz~2480MHz

Transmit Power: GFSK: 10.97dBm
 $\pi/4$ -DQPSK: 9.26dBm
8DPSK: 9.55dBm

Type of Modulation: FHSS (GFSK for 1Mbps, $\pi/4$ -DQPSK for 2Mbps, 8DPSK for 3Mbps)

Antenna Specification: PCB Printed antenna with 2dBi gain (Max)

Temperature Range: -40°C ~ 85°C

Hardware Version: HW001

Software Version: S018A02XPS11001

Sample No: E20220216738902-0001, E20220216738902-0002, E20220216738902-0003



Note: The model TR3392/40 is the most functions and PCB boards, after evaluated for the model TR3392/40 all test items had tested. For model TR3382/40 Radiated Spurious Emission(30MHz -18GHz) had tested, as this model is the most complex circuit board for other models which has no DAB port and individual DAB module adapter board.



2.5 TEST OPERATION MODE

Mode No.	Description of the modes
1	Bluetooth(BT) fixed frequency transmitting

2.6 MODEL DIFFERENCE DESCRIPTIONS

The sample (product name:Multimedia Player Assembly, model:TR3392/40) and its additional model TR3371/40, TR3361/40 and TR3382/40 are different from appearance design, AM, FM radio antenna port, DAB interface and DAB function. In addition, PCB board, RAM and storage capacity are the same.


Product name	Model	Wirelessfunction	other differences	
		DAB port	PCB	Appearance
Multimedia Player Assembly	TR3392/40 (Base)	Contains DAB interface and DAB functions	TR3392/40 has one more small PCB board than TR3382/40. The function of the small PCB board is DAB, and the radio function moved from the main board	
	TR3371/40 (Variant)	Contains DAB interface and DAB functions	Same as TR3392/40	 Mounting bracket is different from TR3392/40

	TR3361/40 (Variant)	Not contains DAB interface and DAB functions	Same as TR3382/40	 Mounting bracket, radio antenna location is different from TR3392/40
	TR3382/40 (Variant)	Not contains DAB interface and DAB functions	TR3382/40 has one less PCB board than TR3392/40, does not support DAB, and the radio module is integrated on the motherboard	 Mounting bracket, radio antenna location is different from TR3392/40

2.7 LOCAL SUPPORTIVE

Name of Equipment	Manufacturer	Model	Serial Number	Note
Battery	BOSCH	L2-400	D8J16H288-0610	/
Cable				
DC cable(No.1)	/	/	/	UnShielded, 1.60m

2.8 CONFIGURATION OF SYSTEM UNDER TEST



Test software:


Software version	Test level
ADB	Default

2.9 DUTY CYCLE


EUT Name	Multimedia Player Assembly	Model	TR3392/40
Environmental Conditions	23.5°C/48%RH	Test Voltage	DC 12V
Tested By	Lu Wei	Tested Date	2022-03-04

TestMode	Antenna	Frequency [MHz]	ON Time [ms]	Period [ms]	DC [%]	T [s]
DH5	Ant1	2441	2.87	6.21	46.22	0.00287
2DH5	Ant1	2441	2.87	6.21	46.22	0.00287
3DH5	Ant1	2441	2.87	6.21	46.22	0.00287


DH5_2441MHz



2DH5_2441MHz



3DH5_2441MHz



3. LABORATORY AND ACCREDITATIONS

3.1 LABORATORY

The tests & measurements refer to this report were performed by Shenzhen EMC Laboratory of Guangzhou GRG Metrology & Test Co., Ltd.

Add : No.1301 Guangang Road Xinlan Community, Guanlan Street, Longhua District
Shenzhen, 518110, People's Republic of China

P.C. : 518110

Tel : 0755-61180008

Fax : 0755-61180008

3.2 ACCREDITATIONS

Our laboratories are accredited and approved by the following approval agencies according to ISO/IEC 17025:2017.

USA A2LA (Certificate #2861.01)

The measuring facility of laboratories has been authorized or registered by the following approval agencies.

Canada ISED (Company Number: 24897, CAB identifier: CN0069)

USA FCC (Registration Number: 759402, Designation Number: CN1198)

Copies of granted accreditation certificates are available for downloading from our web site,
<http://www.grgtest.com>

----- The following blanks -----

3.3 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement		Frequency	Uncertainty
Radiated Emission	Horizontal	9kHz~30MHz	4.46dB
		30MHz~200MHz	4.30dB
		200MHz~1000MHz	4.50dB
		1GHz~18GHz	5.60dB
		18GHz~26.5GHz	3.65dB
	Vertical	9kHz~30MHz	4.46dB
		30MHz~200MHz	4.40dB
		200MHz~1000MHz	4.50dB
		1GHz~18GHz	5.60dB
		18GHz~26.5GHz	3.65dB

Measurement	Uncertainty
RF frequency	6.0×10^{-6}
RF power conducted	0.78 dB
Occupied channel bandwidth	0.4 dB
Unwanted emission, conducted	0.68 dB
Humidity	6 %
Temperature	2 °C

This uncertainty represents an expanded uncertainty factor of $k=2$.

----- The following blanks -----

4. LIST OF USED TEST EQUIPMENT AT GRGT

Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Hopping Channel Number				
Spectrum Analyzer	R&S	FSV30	104381	2022-12-10
Dwell Time				
Spectrum Analyzer	R&S	FSV30	104381	2022-12-10
Radiated Spurious Emission&Restricted bands of operation				
Test S/W	EZ	CCS-03A1	/	/
Loop Antenna	TESEQ	HLA6121	52599	2023-04-02
Test Receiver	R&S	ESR7	102444	2022-09-21
Preamplifier	EMEC	EM330	I00426	2023-03-05
Bi-log Antenna	Schwarzbeck	VULB9160	VULB9160-3401	2022-10-27
Spectrum Analyzer	Agilent	N9020B	MY57120179	2022-08-08
Horn Antenna	Schwarzbeck	BBHA9120D (1201)	02143	2022-10-22
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	BBHA 9170-497	2022-10-16
Amplifier	Tonscend	TAP01018048	AP20E8060075	2023-05-05
Amplifier	Tonscend	TAP184050	AP20E806071	2023-05-05
Test S/W	Tonscend	JS36-RE/2.5.1.5		
20 dB Bandwidth				
Spectrum Analyzer	R&S	FSV30	104381	2022-12-10
Maximum Peak Output Power				
Pulse power sensor	Anritsu	MA2411B	1126150	2023-03-01
Power meter	Anritsu	ML2495A	1204003	2023-02-28
Conducted band edges and Spurious Emission				
Spectrum Analyzer	R&S	FSV30	104381	2022-12-10
Carrier Frequencies Separated				
Spectrum Analyzer	R&S	FSV30	104381	2022-12-10

Note: The calibration interval of the above test instruments is 12 months.

5. TEST RESULTS

5.1 EUT TEST CONDITIONS

Type of antenna: PCB Printed

Test frequencies: According to the 15.31(m) Measurements on intentional radiators or receivers, other than TV broadcast receivers, shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table:

Frequency range over which device operates	Number of frequencies	Location in the range of operation
1 MHz or less	1	Middle
1 to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top 1 near middle and 1 near bottom

EUT channels and frequencies list:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2416	28	2430
1	2403	15	2417	29	2431
2	2404	16	2418	30	2432
3	2405	17	2419	31	2433
4	2406	18	2420	32	2434
5	2407	19	2421	33	2435
6	2408	20	2422	34	2436
7	2409	21	2423	35	2437
8	2410	22	2424	36	2438
9	2411	23	2425	37	2439
10	2412	24	2426	38	2440
11	2413	25	2427	39	2441
12	2414	26	2428	40	2442
13	2415	27	2429	41	2443

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
42	2444	55	2457	68	2470
43	2445	56	2458	69	2471
44	2446	57	2459	70	2472
45	2447	58	2460	71	2473
46	2448	59	2461	72	2474
47	2449	60	2462	73	2475
48	2450	61	2463	74	2476
49	2451	62	2464	75	2477
50	2452	63	2465	76	2478
51	2453	64	2466	77	2479
52	2454	65	2467	78	2480
53	2455	66	2468		
54	2456	67	2469		

Test frequency is the lowest channel: 0 frequency(2402MHz), middle channel: 39 frequency (2441MHz) and highest channel: 78 frequency(2480MHz)

----- The following blanks -----

5.2 20dB BANDWIDTH


5.2.1 LIMITS

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.2.2 TEST PROCEDURES

- 1) Remove the antenna from the EUT, and then connect a low loss RF cable from antenna port to the spectrum analyzer.
- 2) Set the spectrum analyzer as RBW=30 kHz, VBW=100 kHz, Span=3MHz, Sweep = auto. Allow the trace to stabilize, record 20dB bandwidth value
- 3) Repeat until all the test channels are investigated.

5.2.3 TEST SETUP



5.2.4 TEST RESULTS

Environment: 23.5°C/48%RH/101.0kPa
Tested By: Lu Wei


Voltage: DC 12V
Date: 2022-03-04

Test mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
DH5	Lowest	2402	0.945
	Middle	2441	0.951
	Highest	2480	0.948
Test mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
2DH5	Lowest	2402	1.347
	Middle	2441	1.350
	Highest	2480	1.350
Test mode	Channel	Frequency (MHz)	20 dB Bandwidth (MHz)
3DH5	Lowest	2402	1.308
	Middle	2441	1.323
	Highest	2480	1.323


Result plot as follows:

DH5


Lowest Channel



Middle Channel




Highest Channel




2DH5


Lowest Channel




Middle Channel




Highest Channel




3DH5
Lowest Channel



Middle Channel



Highest Channel



----- The following blanks -----

5.3 CARRIER FREQUENCIES SEPARATED


5.3.1 LIMITS

1) Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.3.2 TEST PROCEDURES

- 1) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2) Set center frequency of spectrum analyzer = middle of hopping channel.
- 3) Set the spectrum analyzer as RBW=30kHz, VBW=30kHz, Sweep = auto
- 4) Use the marker-delta function to mark hopping channel carrier frequencies and record the channel separation.

5.3.3 TEST SETUP



5.3.4 TEST RESULTS

Environment: 23.5°C/48%RH/101.0kPa
 Tested By: Lu Wei

Voltage: DC 12V
 Date: 2022-03-04

DH5

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.006	634	> Two-thirds of the 20 dB Bandwidth	Pass

2DH5

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.000	900	> Two-thirds of the 20 dB Bandwidth	Pass


3DH5

Channel Separation (MHz)	Two-thirds of the 20 dB Bandwidth (kHz)	Channel Separation Limit	Result
1.006	882	> Two-thirds of the 20 dB Bandwidth	Pass

Result plot as follows:


DH5

Measurement of Channel Separation




2DH5

Measurement of Channel Separation



3DH5
Measurement of Channel Separation



----- The following blanks -----

5.4 HOPPING CHANNEL NUMBER

5.4.1 LIMITS

Regulation 15.247 (a) (1)(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

5.4.2 TEST PROCEDURES

- 1) Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
- 2) Set the spectrum analyzer as RBW=100kHz, VBW=300kHz.
- 3) Set the spectrum analyzer: start frequency = 2400MHz. stop frequency = 2483.5MHz. Submit the test result graph.

5.4.3 TEST SETUP



5.4.4 TEST RESULTS


Environment: 23.5°C/48%RH/101.0kPa
Tested By: Lu Wei

Voltage: DC 12V
Date: 2022-03-04

Result (No. of CH)	Limit (No. of CH)	Result
79	≥15	PASS


GFSK

2.400 GHz – 2.4835 GHz




$\pi/4$ -DQPSK

2.400 GHz – 2.4835 GHz



2.400 GHz – 2.4835 GHz



----- The following blanks -----

5.5 DWELL TIME

5.5.1 LIMITS

Regulation 15.247(a)(1)(iii) Frequency hopping systems in the 2400-2483.5MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.5.2 TEST PROCEDURES

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the spectrum.
- 2) Set spectrum analyzer span = 0. centered on a hopping channel;
- 3) Set RBW = 1MHz and VBW = 3MHz. Sweep = as necessary to capture the entire dwell time per hopping channel. Detector Function = Peak. Trace = Max hold;
- 4) Use the marker-delta function to determine the dwell time. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.). Repeat this test for each variation.
- 5) DH1 Packet permit maximum $1600 / 79 / 2 = 10.12$ hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $10.12 \times 31.6 = 320$ within 31.6 seconds
- 6) DH3 Packet permit maximum $1600 / 79 / 4 = 5.06$ hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $5.06 \times 31.6 = 160$ within 31.6 seconds
- 7) DH5 Packet permit maximum $1600 / 79 / 6 = 3.37$ hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times $3.37 \times 31.6 = 106.6$ within 31.6 seconds

5.5.3 TEST SETUP



5.5.4 TEST RESULTS

Environment: 23.5°C/48%RH/101.0kPa
Tested By: Lu Wei

Voltage: DC 12V
Date: 2022-03-04

The test period: $T = 0.4 \text{ Second/Channel} \times 79 \text{ Channel} = 31.6 \text{ s}$

GFSK: Middle Channel (2.441GHz)

DH1	time slot=	0.38	(ms)*	$(1600/(2*79))$	*	31.6	=	122	ms
DH3	time slot=	1.63	(ms)*	$(1600/(4*79))$	*	31.6	=	261	ms
DH5	time slot=	2.87	(ms)*	$(1600/(6*79))$	*	31.6	=	306	ms

$\pi/4$ -DQPSK: Middle Channel (2.441GHz)

2DH1	time slot=	0.39	(ms)*	$(1600/(2*79))$	*	31.6	=	125	ms
2DH3	time slot=	1.63	(ms)*	$(1600/(4*79))$	*	31.6	=	261	ms
2DH5	time slot=	2.87	(ms)*	$(1600/(6*79))$	*	31.6	=	306	ms

8DPSK: Middle Channel (2.441GHz)


3DH1	time slot=	0.39	(ms)*	$(1600/(2*79))$	*	31.6	=	125	ms
3DH3	time slot=	1.63	(ms)*	$(1600/(4*79))$	*	31.6	=	261	ms
3DH5	time slot=	2.87	(ms)*	$(1600/(6*79))$	*	31.6	=	306	ms

The results are not greater than 0.4 seconds.


----- The following blanks -----

Please refer the graph as below:


GFSK
Middle Frequency (2.441GHz)
DH1




DH3




DH5




$\pi/4$ -DQPSK
Middle Frequency (2.441GHz)
2DH1




Mid Frequency (2.441GHz)
2DH3




2DH5




8DPSK
Middle Frequency (2.441GHz)
3DH1



3DH3



3DH5



----- The following blanks -----

5.6 MAXIMUM PEAK OUTPUT POWER


5.6.1 LIMITS

Regulation 15.247 (b)(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.6.2 TEST PROCEDURES

- 1) Remove the antenna from the EUT and then connect a low RF cable from the antenna port to the power meter and enable the EUT transmit continuously.
- 2) Keep the EUT in transmitting at lowest, middle and highest channel individually. Record the max value.

5.6.3 TEST SETUP



----- The following blanks -----

5.6.4 TEST RESULTS

Environment: 23.5°C/48%RH/101.0kPa
Tested By: Lu Wei

Voltage: DC 12V
Date: 2022-03-04

DH5

Test Channel	Fundamental Frequency (GHz)	Max Output Power(dBm)	Limit (dBm)	Peak/Average	Pass/Fail
Lowest	2.402	9.05	20.97	Peak	Pass
Middle	2.441	10.90			Pass
Highest	2.480	10.97			Pass

2DH5

Test Channel	Fundamental Frequency (GHz)	Max Output Power(dBm)	Limit (dBm)	Peak/Average	Pass/Fail
Lowest	2.402	7.84	20.97	Peak	Pass
Middle	2.441	9.26			Pass
Highest	2.480	9.12			Pass

3DH5

Test Channel	Fundamental Frequency (GHz)	Max Output Power(dBm)	Limit (dBm)	Peak/Average	Pass/Fail
Lowest	2.402	8.14	20.97	Peak	Pass
Middle	2.441	9.55			Pass
Highest	2.480	9.40			Pass

5.7 CONDUCTED BAND EDGES AND SPURIOUS EMISSIONS

5.7.1 LIMITS


In any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

5.7.2 TEST PROCEDURES

Test procedures follow KDB 558074 D01 15.247 measurement guidance v05r02.

- 1) Remove the antenna from the EUT and then connect a low attenuation cable from the antenna port to the spectrum.
- 2) Set the spectrum analyzer: RBW =100KHz; VBW =300KHz, Frequency range = 30MHz to 26.5GHz; Sweep = auto; Detector Function = Peak. Trace = Max, hold.
- 3) Measure and record the results in the test report.
- 4) The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5.7.3 TEST SETUP



5.7.4 TEST RESULTS

Environment: 23.5°C/48%RH/101.0kPa
Tested By: Lu Wei



Voltage: DC 12V
Date: 2022-03-04

Test result plot as follows:



Band Edges

DH5


CH Low (2.35GHz ~2.405GHz)





CH High (2.47GHz ~ 2.55GHz)





2DH5
CH Low (2.35GHz ~2.405GHz)





CH High (2.47GHz ~ 2.55GHz)




3DH5
CH Low (2.35GHz ~2.405GHz)




CH High (2.47GHz ~ 2.55GHz)






Spurious Emissions
DH5
CH Low







CH Mid





CH High





2DH5
CH Low

