


TEST REPORT

Application No.: SZEM2006004911CR
Applicant: UAB Teltonika Networks
Address of Applicant: K. Barsausko st. 66 Kaunas LT-51436 Lithuania
Manufacturer: UAB Teltonika Networks
Address of Manufacturer: K. Barsausko st. 66 Kaunas LT-51436 Lithuania
Factory: UAB Teltonika EMS
Address of Factory: Liepkalnio st. 132A, LT-02121, Vilnius, Lithuania
Equipment Under Test (EUT):
EUT Name: LTE Router
Model No.: RUT955
Trade Mark: Teltonika
FCC ID: 2AET4RUT955AF
Standard(s) : 47 CFR Part 15, Subpart C 15.247
 (only for Conducted Emissions at AC Power Line, Radiated Emissions which fall in the restricted bands and Radiated Spurious Emissions)
Date of Receipt: 2020-06-10
Date of Test: 2020-06-13 to 2020-08-15
Date of Issue: 2020-11-05

Test Result:	Pass*
---------------------	--------------

* In the configuration tested, the EUT complied with the standards specified above.



Keny Xu
 EMC Laboratory Manager



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
 Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
 Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
 中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

Revision Record				
Version	Chapter	Date	Modifier	Remark
01		2020-11-05		Original

Authorized for issue by:			
			
		Harry Wu /Project Engineer	
			
		Eric Fu /Reviewer	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Inspection & Testing Services Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

2 Test Summary

Radio Spectrum Matter Part				
Item	Standard	Method	Requirement	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

Remark:

Model No.: RUT955

This test report (Ref. No.: SZEM200600491102) is only valid with the original test report (Ref. No.: SZEM200600490902).

Compared with the original report, this report just changed the information of factory.

According to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for all the model RUT955, with only differences as changed the information of applicant, manufacturer, factory and LTE module from EC25-AF to EC25-G which are pin to pin compatible

Considering to the difference, pre-scan were performed on the sample in this report to find the items which can be influential to the result in the original test report for fully retest.

Therefore in this report Conducted Emissions at AC Power Line, Radiated Emissions which fall in the restricted bands and Radiated Spurious Emission were fully retested on model RUT955 and shown the data in this report, other tests please refer to original report SZEM200600490902).

3 Contents

	Page
1 COVER PAGE	1
2 TEST SUMMARY	3
3 CONTENTS	4
4 GENERAL INFORMATION	5
4.1 DETAILS OF E.U.T.	5
4.2 DESCRIPTION OF SUPPORT UNITS	5
4.3 DETAILS OF SAMPLE SETTING.....	5
4.4 MEASUREMENT UNCERTAINTY	6
4.5 TEST LOCATION.....	7
4.6 TEST FACILITY.....	7
4.7 DEVIATION FROM STANDARDS.....	7
4.8 ABNORMALITIES FROM STANDARD CONDITIONS	7
5 EQUIPMENT LIST	8
6 RADIO SPECTRUM MATTER TEST RESULTS	10
6.1 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....	10
6.1.1 E.U.T. Operation	10
6.1.2 Test Setup Diagram	10
6.1.3 Measurement Procedure and Data.....	11
6.2 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	14
6.2.1 E.U.T. Operation	14
6.2.2 Test Setup Diagram	14
6.2.3 Measurement Procedure and Data.....	15
6.3 RADIATED SPURIOUS EMISSIONS	48
6.3.1 E.U.T. Operation	49
6.3.2 Test Setup Diagram	49
6.3.3 Measurement Procedure and Data.....	50
7 PHOTOGRAPHS.....	77
7.1 TEST SETUP.....	77
7.2 EUT CONSTRUCTIONAL DETAILS (EUT PHOTOS).....	77

4 General Information

4.1 Details of E.U.T.

Power Supply:	DC 9-30V AC/DC Adapter Mode: SJ-09010033 Input: AC100-240V, 50/60Hz, 0.8A Output: DC 9.0V, 1.0A
Cable:	DC Cable: 2m, Unshielded Network Cable: 1.5m, Unshielded Wifi Antenna: 3m, Unshielded GPS Antenna: 3m, Unshielded
Operation Frequency:	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
Modulation Type:	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
Number of Channels:	802.11b/g/n(HT20):11 802.11n(HT40):7
Channel Spacing:	5MHz
Antenna Type:	RP-SMA Connector
Antenna Gain:	Antenna 1 & 2: 5dBi
S/N:	1107172849
Hardware version:	17
Firmware version:	RUT9xx_R_AA.BB.CC

4.2 Description of Support Units

The EUT has been tested as an independent unit.

4.3 Details of Sample setting.

RF software:	art2_ver_2_28_7BIN_[RUT95x]
Software Power setting:	Tx Power: Target

4.4 Measurement Uncertainty

No.	Item	Measurement Uncertainty
1	Conduction emission	$\pm 3.0\text{dB}$ (150kHz to 30MHz)
2	Radiated Spurious emission test	$\pm 4.5\text{dB}$ (Below 1GHz)
		$\pm 4.8\text{dB}$ (Above 1GHz)
3	Temperature test	$\pm 1^{\circ}\text{C}$
4	Humidity test	$\pm 3\%$
5	Supply voltages	$\pm 1\%$



4.5 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

4.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **A2LA (Certificate No. 3816.01)**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

- **VCCI**

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd. have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

- **FCC –Designation Number: CN1178**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1178. Test Firm Registration Number: 406779.

- **Innovation, Science and Economic Development Canada**

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

4.7 Deviation from Standards

None

4.8 Abnormalities from Standard Conditions

None



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

5 Equipment List

Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Shielding Room	ZhongYu Electron	GB-88	SEM001-06	2019-06-13	2022-06-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM024-01	2019-07-09	2020-07-10
				2020-07-10	2021-07-09
LISN	Rohde & Schwarz	ENV216	SEM007-01	2019-09-24	2020-09-23
LISN	ETS-LINDGREN	3816/2	SEM007-02	2020-04-01	2021-03-31
EMI Test Receiver	Rohde & Schwarz	ESCI	SEM004-02	2020-03-24	2021-03-23

Radiated Emissions which fall in the restricted bands					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019-07-09	2020-07-10
				2020-07-10	2021-07-09
EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2017-08-15	2020-08-14
				2020-08-14	2023-08-13

Radiated Spurious Emissions					
Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019-07-09	2020-07-10
				2020-07-10	2021-07-09



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Horn Antenna	Schwarzbeck	BBHA 9170	SEM003-15	2017-10-17	2020-10-16
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23
Pre-amplifier	Rohde & Schwarz	CH14-H052	SEM005-17	2020-04-01	2021-03-31
Pre-amplifier	Compliance Directions Systems Inc.	PAP-2640-50	SEM005-08	2020-04-01	2021-03-31
DC Power Supply	Zhao Xin	KXN-6020D	SEM011-08	2019-09-24	2020-09-23
Active Loop Antenna	ETS-Lindgren	6502	SEM003-08	2020-08-14	2023-08-13

Radiated Emissions

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
3m Semi-Anechoic Chamber	AUDIX	N/A	SEM001-02	2018-03-13	2021-03-12
Measurement Software	AUDIX	e3 V8.2014-6-27	N/A	N/A	N/A
Coaxial Cable	SGS	N/A	SEM026-01	2019-07-09 2020-07-10	2020-07-10 2021-07-09
EXA Spectrum Analyzer	AgilentTechnologies Inc	N9010A	SEM004-12	2020-04-09	2021-04-08
Horn Antenna	Rohde & Schwarz	HF907	SEM003-07	2018-04-13	2021-04-12
Pre-Amplifier	Compliance Directions Systems Inc.	PAP-0126	SEM004-11	2019-09-24	2020-09-23

General used equipment

Equipment	Manufacturer	Model No	Inventory No	Cal Date	Cal Due Date
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-03	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Shanghai Meteorological Industry Factory	ZJ1-2B	SEM002-04	2019-09-26	2020-09-25
Humidity/ Temperature Indicator	Mingle	N/A	SEM002-08	2019-09-26	2020-09-25
Barometer	Changchun Meteorological Industry Factory	DYM3	SEM002-01	2020-04-07	2021-04-06



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6 Radio Spectrum Matter Test Results

6.1 Conducted Emissions at AC Power Line (150kHz-30MHz)

Test Requirement 47 CFR Part 15, Subpart C 15.207

Test Method: ANSI C63.10 (2013) Section 6.2

Limit:

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


6.1.1 E.U.T. Operation

Operating Environment:

Temperature: 25 °C Humidity: 51 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

6.1.2 Test Setup Diagram




6.1.3 Measurement Procedure and Data

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50μH + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.
- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

Mode:a; Line:Live Line



Site : Shielding Room

Condition: Line

Job No. : 04911CR


Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1573	0.01	9.59	16.72	26.32	55.60	-29.28	Average
2	0.1573	0.01	9.59	43.72	53.32	65.60	-12.28	QP
3	0.4837	0.06	9.59	22.39	32.04	46.27	-14.23	Average
4	0.4837	0.06	9.59	42.95	52.60	56.27	-3.67	QP
5	0.5128	0.06	9.59	25.63	35.28	46.00	-10.72	Average
6	0.5128	0.06	9.59	42.52	52.17	56.00	-3.83	QP
7	1.3029	0.12	9.60	16.06	25.78	46.00	-20.22	Average
8	1.3029	0.12	9.60	33.93	43.65	56.00	-12.35	QP
9	2.8390	0.16	9.66	14.44	24.26	46.00	-21.74	Average
10	2.8390	0.16	9.66	30.44	40.26	56.00	-15.74	QP
11	5.0848	0.17	9.67	16.60	26.44	50.00	-23.56	Average
12	5.0848	0.17	9.67	29.06	38.90	60.00	-21.10	QP



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Mode:a; Line:Neutral Line



Site : Shielding Room

Condition: Neutral

Job No. : 04911CR

Test mode: a

	Freq	Cable Loss	LISN Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB	dBuV	dBuV	dBuV	dB	
1	0.1685	0.01	9.55	25.63	35.19	55.03	-19.84	Average
2	0.1685	0.01	9.55	41.96	51.52	65.03	-13.51	QP
3	0.3100	0.04	9.54	1.11	10.69	49.97	-39.28	Average
4	0.3100	0.04	9.54	32.28	41.86	59.97	-18.11	QP
5	0.5020	0.06	9.54	26.83	36.43	46.00	-9.57	Average
6	0.5020	0.06	9.54	38.12	47.72	56.00	-8.28	QP
7	1.7716	0.15	9.56	15.50	25.21	46.00	-20.79	Average
8	1.7716	0.15	9.56	28.52	38.23	56.00	-17.77	QP
9	4.7969	0.17	9.62	13.44	23.23	46.00	-22.77	Average
10	4.7969	0.17	9.62	25.45	35.24	56.00	-20.76	QP
11	27.1270	0.27	10.58	9.10	19.95	50.00	-30.05	Average
12	27.1270	0.27	10.58	20.74	31.59	60.00	-28.41	QP



6.2 Radiated Emissions which fall in the restricted bands

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.10.5

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.


6.2.1 E.U.T. Operation

Operating Environment:

Temperature: 22.5 °C Humidity: 48.8 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

6.2.2 Test Setup Diagram



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

6.2.3 Measurement Procedure and Data


- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Antenna 1 & 2 were tested for Modulation: 802.11b,802.11g. Only the worst case was recorded in the report.
Antenna 1, 2 & 1+2, were tested for Modulation: 802.11n. Only the worst case was recorded in the report.

Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2360.976	4.30	28.47	40.96	68.00	59.81	74.00	-14.19	peak
2	2390.000	4.34	28.52	40.97	65.87	57.76	74.00	-16.24	peak
3 *	2412.000	4.38	28.56	40.98	104.02	95.98	74.00	21.98	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2360.019	4.30	28.47	40.96	57.93	49.74	54.00	-4.26	Average
2	2390.000	4.34	28.52	40.97	57.30	49.19	54.00	-4.81	Average
3 *	2412.000	4.38	28.56	40.98	101.84	93.80	54.00	39.80	Average



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2361.454	4.30	28.47	40.96	68.82	60.63	74.00	-13.37	Peak
2	2390.000	4.34	28.52	40.97	66.51	58.40	74.00	-15.60	Peak
3 *	2412.000	4.38	28.56	40.98	96.84	88.80	74.00	14.80	Peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11B

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2386.461	4.34	28.51	40.97	57.28	49.16	54.00	-4.84	Average
2	2390.000	4.34	28.52	40.97	57.22	49.11	54.00	-4.89	Average
3 *	2412.000	4.38	28.56	40.98	94.94	86.90	54.00	32.90	Average



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	104.06	96.16	74.00	22.16	peak
2 2483.500	4.49	28.67	41.01	67.18	59.33	74.00	-14.67	peak
3 2499.848	4.52	28.70	41.02	68.47	60.67	74.00	-13.33	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	102.17	94.27	54.00	40.27	Average
2 2483.500	4.49	28.67	41.01	57.58	49.73	54.00	-4.27	Average
3 2499.848	4.52	28.70	41.02	57.53	49.73	54.00	-4.27	Average



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	96.61	88.71	74.00	14.71	Peak
2 2483.500	4.49	28.67	41.01	66.83	58.98	74.00	-15.02	Peak
3 2495.761	4.51	28.69	41.02	68.36	60.54	74.00	-13.46	Peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	94.89	86.99	54.00	32.99	Average
2 2483.500	4.49	28.67	41.01	57.41	49.56	54.00	-4.44	Average
3 2487.104	4.50	28.68	41.01	57.58	49.75	54.00	-4.25	Average



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
Freq		Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2370.200	4.31	28.48	40.96	68.93	60.76	74.00	-13.24	peak
2	2390.000	4.34	28.52	40.97	65.94	57.83	74.00	-16.17	peak
3 *	2412.000	4.38	28.56	40.98	106.48	98.44	74.00	24.44	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2360.019	4.30	28.47	40.96	58.13	49.94	54.00	-4.06 Average
2	2390.000	4.34	28.52	40.97	57.44	49.33	54.00	-4.67 Average
3 *	2412.000	4.38	28.56	40.98	99.03	90.99	54.00	36.99 Average



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2383.803	4.33	28.51	40.97	68.45	60.32	74.00	-13.68 Peak
2	2390.000	4.34	28.52	40.97	66.69	58.58	74.00	-15.42 Peak
3 *	2412.000	4.38	28.56	40.98	101.63	93.59	74.00	19.59 Peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2388.274	4.34	28.52	40.97	57.30	49.19	54.00	-4.81	Average
2	2390.000	4.34	28.52	40.97	57.19	49.08	54.00	-4.92	Average
3 *	2412.000	4.38	28.56	40.98	94.73	86.69	54.00	32.69	Average



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	106.90	99.00	74.00	25.00	peak
2 2483.500	4.49	28.67	41.01	66.92	59.07	74.00	-14.93	peak
3 2491.177	4.51	28.69	41.01	68.36	60.55	74.00	-13.45	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2462.000	4.46	28.64	41.00	99.77	91.87	54.00	37.87 Average
2 2483.500	4.49	28.67	41.01	57.65	49.80	54.00	-4.20 Average
3 2483.940	4.49	28.67	41.01	57.73	49.88	54.00	-4.12 Average



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	100.68	92.78	74.00	18.78	Peak
2 2483.500	4.49	28.67	41.01	66.57	58.72	74.00	-15.28	Peak
3 2492.234	4.51	28.69	41.01	68.48	60.67	74.00	-13.33	Peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	94.29	86.39	54.00	32.39	Average
2 2483.500	4.49	28.67	41.01	57.44	49.59	54.00	-4.41	Average
3 2496.417	4.51	28.69	41.02	57.61	49.79	54.00	-4.21	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2333.635	4.25	28.42	40.95	68.44	60.16	74.00	-13.84	peak
2	2390.000	4.34	28.52	40.97	66.65	58.54	74.00	-15.46	peak
3 *	2412.000	4.38	28.56	40.98	101.26	93.22	74.00	19.22	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2359.900	4.30	28.47	40.96	58.24	50.05	54.00	-3.95 Average
2	2390.000	4.34	28.52	40.97	57.20	49.09	54.00	-4.91 Average
3 *	2412.000	4.38	28.56	40.98	93.95	85.91	54.00	31.91 Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2328.794	4.24	28.41	40.95	68.58	60.28	74.00	-13.72	Peak
2	2390.000	4.34	28.52	40.97	65.64	57.53	74.00	-16.47	Peak
3 *	2412.000	4.38	28.56	40.98	96.55	88.51	74.00	14.51	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 Band edge
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2389.484	4.34	28.52	40.97	57.25	49.14	54.00	-4.86	Average
2	2390.000	4.34	28.52	40.97	57.22	49.11	54.00	-4.89	Average
3 *	2412.000	4.38	28.56	40.98	89.98	81.94	54.00	27.94	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	101.77	93.87	74.00	19.87	peak
2 2483.500	4.49	28.67	41.01	66.00	58.15	74.00	-15.85	peak
3 2493.342	4.51	28.69	41.01	68.40	60.59	74.00	-13.41	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	94.55	86.65	54.00	32.65	Average
2 2483.500	4.49	28.67	41.01	57.52	49.67	54.00	-4.33	Average
3 2489.014	4.50	28.68	41.01	57.59	49.76	54.00	-4.24	Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	96.71	88.81	74.00	14.81	Peak
2 2483.500	4.49	28.67	41.01	66.56	58.71	74.00	-15.29	Peak
3 2492.939	4.51	28.69	41.01	68.96	61.15	74.00	-12.85	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 Band edge
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2462.000	4.46	28.64	41.00	90.12	82.22	54.00	28.22	Average
2 2483.500	4.49	28.67	41.01	57.41	49.56	54.00	-4.44	Average
3 2491.177	4.51	28.69	41.01	57.49	49.68	54.00	-4.32	Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2349.427	4.28	28.45	40.96	68.44	60.21	74.00	-13.79 peak
2	2390.000	4.34	28.52	40.97	66.16	58.05	74.00	-15.95 peak
3 *	2422.000	4.40	28.57	40.99	98.43	90.41	74.00	16.41 peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2360.093	4.30	28.47	40.96	58.21	50.02	54.00	-3.98	Average
2	2390.000	4.34	28.52	40.97	57.43	49.32	54.00	-4.68	Average
3 *	2422.000	4.40	28.57	40.99	91.57	83.55	54.00	29.55	Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	2350.018	4.28	28.45	40.96	68.25	60.02	74.00	-13.98	Peak
2	2390.000	4.34	28.52	40.97	67.01	58.90	74.00	-15.10	Peak
3 *	2422.000	4.40	28.57	40.99	92.88	84.86	74.00	10.86	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2422 Band edge
Note : 2.4G WIFI 11N40

		Cable	Ant	Preamp	Read	Limit	Over	
	Freq	Loss	Factor	Factor	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dB	
1	2386.972	4.34	28.51	40.97	57.34	49.22	54.00	-4.78 Average
2	2390.000	4.34	28.52	40.97	57.21	49.10	54.00	-4.90 Average
3 *	2422.000	4.40	28.57	40.99	86.03	78.01	54.00	24.01 Average



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2452.000	4.44	28.62	41.00	98.54	90.60	74.00	16.60	peak
2 2483.500	4.49	28.67	41.01	66.23	58.38	74.00	-15.62	peak
3 2485.699	4.50	28.68	41.01	68.87	61.04	74.00	-12.96	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read	Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1 * 2452.000	4.44	28.62	41.00	91.17	83.23	54.00	29.23 Average
2 2483.500	4.49	28.67	41.01	57.71	49.86	54.00	-4.14 Average
3 2483.865	4.49	28.67	41.01	57.73	49.88	54.00	-4.12 Average



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2452.000	4.44	28.62	41.00	93.26	85.32	74.00	11.32	Peak
2 2483.500	4.49	28.67	41.01	66.75	58.90	74.00	-15.10	Peak
3 2492.344	4.51	28.69	41.01	68.29	60.48	74.00	-13.52	Peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2



Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2452 Band edge
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1 * 2452.000	4.44	28.62	41.00	86.78	78.84	54.00	24.84	Average
2 2483.500	4.49	28.67	41.01	57.42	49.57	54.00	-4.43	Average
3 2492.627	4.51	28.69	41.01	57.51	49.70	54.00	-4.30	Average



6.3 Radiated Spurious Emissions

Test Requirement 47 CFR Part 15, Subpart C 15.209 & 15.247(d)

Test Method: ANSI C63.10 (2013) Section 6.4,6.5,6.6

Measurement Distance: 3m

Limit:

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch, EMC Laboratory.

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Shenzhen, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgsgroup.com.cn
中国·深圳·科技园中区M-10栋一号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com


6.3.1 E.U.T. Operation

Operating Environment:

Temperature: 25.2 °C Humidity: 59 % RH Atmospheric Pressure: 1005 mbar

Test mode a:TX mode_Keep the EUT in continuously transmitting mode with all modulation types. All data rates for each modulation type have been tested and found the data rate @ 1Mbps is the worst case of IEEE 802.11b; data rate @ 6Mbps is the worst case of IEEE 802.11g; data rate @ 6.5Mbps is the worst case of IEEE 802.11n(HT20); data rate @ 13.5Mbps is the worst case of IEEE 802.11n(HT40). Only the data of worst case is recorded in the report.

6.3.2 Test Setup Diagram



6.3.3 Measurement Procedure and Data

- a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.


Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

Below 1GHz

Worst case:

Mode:a; Polarization:Horizontal



Condition: 3m HORIZONTAL


Job No. : 04911CR

Test Mode: a

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	83.23	1.10	12.37	27.65	43.17	28.99	40.00	-11.01	QP
2	89.90	1.10	13.09	27.65	42.36	28.90	43.50	-14.60	QP
3	137.42	1.29	13.63	27.42	43.03	30.53	43.50	-12.97	QP
4	195.14	1.39	16.36	27.18	41.28	31.85	43.50	-11.65	QP
5 pp	212.27	1.47	16.94	27.13	41.61	32.89	43.50	-10.61	QP
6	267.55	1.76	18.98	26.97	38.90	32.67	46.00	-13.33	QP



Mode:a; Polarization:Vertical



Condition: 3m VERTICAL

Job No. : 04911CR

Test Mode: a

	Freq	Cable	Ant	Preamp	Read	Limit	Over	
	MHz	Loss	Factor	Factor	Level	Level	Line	Limit Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB
1	44.12	0.69	16.05	27.70	44.68	33.72	40.00	-6.28 QP
2 pp	49.88	0.80	14.24	27.69	49.29	36.64	40.00	-3.36 QP
3	52.95	0.80	13.89	27.69	49.04	36.04	40.00	-3.96 QP
4	90.86	1.11	13.18	27.65	47.24	33.88	43.50	-9.62 QP
5	129.01	1.27	13.38	27.47	50.30	37.48	43.50	-6.02 QP
6	154.28	1.33	15.01	27.34	45.42	34.42	43.50	-9.08 QP




Above 1GHz

Antenna 1 & 2 were tested for Modulation: 802.11b,802.11g. Only the worst case was recorded in the report.

Antenna 1, 2 & 1+2, were tested for Modulation: 802.11n. Only the worst case was recorded in the report.

Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	45.78	35.21	74.00	-38.79	peak
2	4469.214	6.73	33.60	42.53	47.79	45.59	74.00	-28.41	peak
3	4824.000	7.12	34.19	42.78	45.98	44.51	74.00	-29.49	peak
4	6995.172	8.54	36.49	41.69	47.05	50.39	74.00	-23.61	peak
5	7236.000	8.77	36.40	41.56	46.25	49.86	74.00	-24.14	peak
6	9648.000	10.79	37.53	38.51	41.11	50.92	74.00	-23.08	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11B

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1653.550	3.39	26.48	40.60	45.70	34.97	74.00	-39.03 peak
2	4482.150	6.74	33.60	42.54	47.41	45.21	74.00	-28.79 peak
3	4824.000	7.12	34.19	42.78	46.04	44.57	74.00	-29.43 peak
4	6914.763	8.50	36.27	41.73	46.29	49.33	74.00	-24.67 peak
5	7236.000	8.77	36.40	41.56	46.22	49.83	74.00	-24.17 peak
6	9648.000	10.79	37.53	38.51	42.01	51.82	74.00	-22.18 peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:middle, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1682.477	3.42	26.60	40.62	46.54	35.94	74.00	-38.06	peak
2	4392.376	6.66	33.60	42.47	47.38	45.17	74.00	-28.83	peak
3	4874.000	7.17	34.28	42.82	46.30	44.93	74.00	-29.07	peak
4	6621.375	8.34	35.45	41.88	47.41	49.32	74.00	-24.68	peak
5	7311.000	8.84	36.37	41.53	46.12	49.80	74.00	-24.20	peak
6	9748.000	10.76	37.55	38.37	42.23	52.17	74.00	-21.83	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:middle, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1565.191	3.32	26.10	40.55	45.96	34.83	74.00	-39.17	peak
2	4304.400	6.58	33.60	42.40	47.13	44.91	74.00	-29.09	peak
3	4874.000	7.17	34.28	42.82	44.65	43.28	74.00	-30.72	peak
4	6934.778	8.51	36.32	41.72	46.36	49.47	74.00	-24.53	peak
5	7311.000	8.84	36.37	41.53	46.13	49.81	74.00	-24.19	peak
6	9748.000	10.76	37.55	38.37	41.22	51.16	74.00	-22.84	peak



Mode:a; Polarization:Horizontal; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.40	26.52	40.61	46.15	35.46	74.00	-38.54	peak
2	4242.641	6.52	33.60	42.35	48.08	45.85	74.00	-28.15	peak
3	4924.000	7.22	34.37	42.85	45.46	44.20	74.00	-29.80	peak
4	6776.265	8.43	35.89	41.80	47.30	49.82	74.00	-24.18	peak
5	7386.000	8.91	36.34	41.49	44.76	48.52	74.00	-25.48	peak
6	9848.000	10.73	37.57	38.22	41.20	51.28	74.00	-22.72	peak



Mode:a; Polarization:Vertical; Modulation:802.11b; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11B

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1629.825	3.37	26.38	40.59	46.60	35.76	74.00	-38.24	peak
2	4316.859	6.59	33.60	42.41	47.56	45.34	74.00	-28.66	peak
3	4924.000	7.22	34.37	42.85	44.52	43.26	74.00	-30.74	peak
4	6995.172	8.54	36.49	41.69	45.45	48.79	74.00	-25.21	peak
5	7386.000	8.91	36.34	41.49	46.59	50.35	74.00	-23.65	peak
6	9848.000	10.73	37.57	38.22	40.39	50.47	74.00	-23.53	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1473.013	3.22	25.69	40.49	46.15	34.57	74.00	-39.43	peak
2	4443.453	6.71	33.60	42.51	48.12	45.92	74.00	-28.08	peak
3	4824.000	7.12	34.19	42.78	46.09	44.62	74.00	-29.38	peak
4	6698.373	8.39	35.67	41.84	47.55	49.77	74.00	-24.23	peak
5	7236.000	8.77	36.40	41.56	44.62	48.23	74.00	-25.77	peak
6	9648.000	10.79	37.53	38.51	41.70	51.51	74.00	-22.49	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:Low, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1634.543	3.38	26.40	40.59	45.62	34.81	74.00	-39.19	peak
2	4304.400	6.58	33.60	42.40	48.35	46.13	74.00	-27.87	peak
3	4824.000	7.12	34.19	42.78	47.21	45.74	74.00	-28.26	peak
4	6835.278	8.46	36.05	41.77	46.64	49.38	74.00	-24.62	peak
5	7236.000	8.77	36.40	41.56	44.23	47.84	74.00	-26.16	peak
6	9648.000	10.79	37.53	38.51	41.60	51.41	74.00	-22.59	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:middle, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.62	40.62	45.38	34.80	74.00	-39.20	peak
2	4430.628	6.70	33.60	42.50	47.63	45.43	74.00	-28.57	peak
3	4874.000	7.17	34.28	42.82	44.46	43.09	74.00	-30.91	peak
4	6340.436	8.27	34.98	42.04	47.72	48.93	74.00	-25.07	peak
5	7311.000	8.84	36.37	41.53	45.35	49.03	74.00	-24.97	peak
6	9748.000	10.76	37.55	38.37	40.96	50.90	74.00	-23.10	peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:middle, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11G

		Cable	Ant	Preamp	Read		Limit	Over	
	Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1611.091	3.36	26.30	40.58	45.53	34.61	74.00	-39.39	peak
2	4417.841	6.68	33.60	42.49	47.60	45.39	74.00	-28.61	peak
3	4874.000	7.17	34.28	42.82	44.64	43.27	74.00	-30.73	peak
4	6995.172	8.54	36.49	41.69	46.23	49.57	74.00	-24.43	peak
5	7311.000	8.84	36.37	41.53	46.40	50.08	74.00	-23.92	peak
6	9748.000	10.76	37.55	38.37	40.05	49.99	74.00	-24.01	peak



Mode:a; Polarization:Horizontal; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	45.25	34.71	74.00	-39.29 peak
2	4316.859	6.59	33.60	42.41	47.44	45.22	74.00	-28.78 peak
3	4924.000	7.22	34.37	42.85	44.80	43.54	74.00	-30.46 peak
4	6564.209	8.31	35.29	41.92	47.86	49.54	74.00	-24.46 peak
5	7386.000	8.91	36.34	41.49	45.95	49.71	74.00	-24.29 peak
6	9848.000	10.73	37.57	38.22	41.08	51.16	74.00	-22.84 peak



Mode:a; Polarization:Vertical; Modulation:802.11g; bandwidth:20MHz; Channel:High, Antenna 1




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11G

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1366.374	3.05	25.25	40.41	46.97	34.86	74.00	-39.14	peak
2	4456.315	6.72	33.60	42.52	47.53	45.33	74.00	-28.67	peak
3	4924.000	7.22	34.37	42.85	45.35	44.09	74.00	-29.91	peak
4	6855.063	8.47	36.10	41.76	46.88	49.69	74.00	-24.31	peak
5	7386.000	8.91	36.34	41.49	46.37	50.13	74.00	-23.87	peak
6	9848.000	10.73	37.57	38.22	41.17	51.25	74.00	-22.75	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N20

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1606.441	3.35	26.28	40.57	46.05	35.11	74.00	-38.89 peak
2	4086.182	6.37	33.60	42.23	47.42	45.16	74.00	-28.84 peak
3	4824.000	7.12	34.19	42.78	45.51	44.04	74.00	-29.96 peak
4	6995.172	8.54	36.49	41.69	46.47	49.81	74.00	-24.19 peak
5	7236.000	8.77	36.40	41.56	44.73	48.34	74.00	-25.66 peak
6	9648.000	10.79	37.53	38.51	41.29	51.10	74.00	-22.90 peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2412 TX RSE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	45.25	34.68	74.00	-39.32	peak
2	4417.841	6.68	33.60	42.49	48.44	46.23	74.00	-27.77	peak
3	4824.000	7.12	34.19	42.78	45.58	44.11	74.00	-29.89	peak
4	6776.265	8.43	35.89	41.80	46.71	49.23	74.00	-24.77	peak
5	7236.000	8.77	36.40	41.56	44.04	47.65	74.00	-26.35	peak
6	9648.000	10.79	37.53	38.51	42.23	52.04	74.00	-21.96	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:middle, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1692.231	3.42	26.64	40.63	45.41	34.84	74.00	-39.16	peak
2	4329.354	6.60	33.60	42.42	46.95	44.73	74.00	-29.27	peak
3	4874.000	7.17	34.28	42.82	45.04	43.67	74.00	-30.33	peak
4	6756.708	8.42	35.83	41.81	47.08	49.52	74.00	-24.48	peak
5	7311.000	8.84	36.37	41.53	45.57	49.25	74.00	-24.75	peak
6	9748.000	10.76	37.55	38.37	40.00	49.94	74.00	-24.06	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:middle, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1653.550	3.39	26.48	40.60	45.38	34.65	74.00	-39.35	peak
2	4279.589	6.56	33.60	42.38	47.94	45.72	74.00	-28.28	peak
3	4874.000	7.17	34.28	42.82	45.18	43.81	74.00	-30.19	peak
4	6995.172	8.54	36.49	41.69	45.46	48.80	74.00	-25.20	peak
5	7311.000	8.84	36.37	41.53	46.05	49.73	74.00	-24.27	peak
6	9748.000	10.76	37.55	38.37	41.89	51.83	74.00	-22.17	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1560.673	3.31	26.08	40.55	46.10	34.94	74.00	-39.06	peak
2	4430.628	6.70	33.60	42.50	47.43	45.23	74.00	-28.77	peak
3	4924.000	7.22	34.37	42.85	44.97	43.71	74.00	-30.29	peak
4	6954.852	8.52	36.38	41.71	46.08	49.27	74.00	-24.73	peak
5	7386.000	8.91	36.34	41.49	45.32	49.08	74.00	-24.92	peak
6	9848.000	10.73	37.57	38.22	41.63	51.71	74.00	-22.29	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:20MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2462 TX RSE
Note : 2.4G WIFI 11N20

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1687.347	3.42	26.62	40.62	45.48	34.90	74.00	-39.10	peak
2	4316.859	6.59	33.60	42.41	47.78	45.56	74.00	-28.44	peak
3	4924.000	7.22	34.37	42.85	44.84	43.58	74.00	-30.42	peak
4	6995.172	8.54	36.49	41.69	45.87	49.21	74.00	-24.79	peak
5	7386.000	8.91	36.34	41.49	45.26	49.02	74.00	-24.98	peak
6	9848.000	10.73	37.57	38.22	41.01	51.09	74.00	-22.91	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2422 TX RSE
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1639.274	3.38	26.42	40.59	46.02	35.23	74.00	-38.77 peak
2	4354.454	6.63	33.60	42.44	46.89	44.68	74.00	-29.32 peak
3	4844.000	7.14	34.23	42.79	46.40	44.98	74.00	-29.02 peak
4	6995.172	8.54	36.49	41.69	46.09	49.43	74.00	-24.57 peak
5	7266.000	8.79	36.39	41.55	44.67	48.30	74.00	-25.70 peak
6	9688.000	10.78	37.54	38.45	41.56	51.43	74.00	-22.57 peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:Low, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2422 TX RSE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1634.543	3.38	26.40	40.59	47.52	36.71	74.00	-37.29	peak
2	4242.641	6.52	33.60	42.35	47.66	45.43	74.00	-28.57	peak
3	4844.000	7.14	34.23	42.79	44.86	43.44	74.00	-30.56	peak
4	6526.373	8.29	35.18	41.94	47.97	49.50	74.00	-24.50	peak
5	7266.000	8.79	36.39	41.55	45.65	49.28	74.00	-24.72	peak
6	9688.000	10.78	37.54	38.45	41.68	51.55	74.00	-22.45	peak



Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:middle, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1663.137	3.40	26.52	40.61	45.76	35.07	74.00	-38.93	peak
2	4469.214	6.73	33.60	42.53	47.29	45.09	74.00	-28.91	peak
3	4874.000	7.17	34.28	42.82	44.89	43.52	74.00	-30.48	peak
4	6934.778	8.51	36.32	41.72	46.84	49.95	74.00	-24.05	peak
5	7311.000	8.84	36.37	41.53	45.33	49.01	74.00	-24.99	peak
6	9748.000	10.76	37.55	38.37	42.07	52.01	74.00	-21.99	peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:middle, Antenna 1+2




Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2437 TX RSE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1702.042	3.43	26.68	40.63	45.51	34.99	74.00	-39.01	peak
2	4456.315	6.72	33.60	42.52	47.09	44.89	74.00	-29.11	peak
3	4874.000	7.17	34.28	42.82	45.13	43.76	74.00	-30.24	peak
4	6995.172	8.54	36.49	41.69	47.42	50.76	74.00	-23.24	peak
5	7311.000	8.84	36.37	41.53	45.47	49.15	74.00	-24.85	peak
6	9748.000	10.76	37.55	38.37	41.62	51.56	74.00	-22.44	peak



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com/en/Terms-and-Conditions/Terms-e-Documents.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.
Attention: To check the authenticity of testing / inspection report and certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Mode:a; Polarization:Horizontal; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2




Site : chamber
Condition: 3m HORIZONTAL
Job No : 04911CR/04912CR
Mode : 2452 TX RSE
Note : 2.4G WIFI 11N40

	Cable	Ant	Preamp	Read		Limit	Over	
Freq	Loss	Factor	Factor	Level	Level	Line	Limit	Remark
MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1658.337	3.40	26.50	40.61	45.84	35.13	74.00	-38.87 peak
2	4181.768	6.46	33.60	42.31	47.22	44.97	74.00	-29.03 peak
3	4904.000	7.20	34.33	42.84	46.83	45.52	74.00	-28.48 peak
4	6914.763	8.50	36.27	41.73	46.41	49.45	74.00	-24.55 peak
5	7356.000	8.88	36.36	41.50	44.75	48.49	74.00	-25.51 peak
6	9808.000	10.75	37.56	38.28	41.80	51.83	74.00	-22.17 peak



Mode:a; Polarization:Vertical; Modulation:802.11n; bandwidth:40MHz; Channel:High, Antenna 1+2



Site : chamber
Condition: 3m VERTICAL
Job No : 04911CR/04912CR
Mode : 2452 TX RSE
Note : 2.4G WIFI 11N40

	Freq	Cable Loss	Ant Factor	Preamp Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dB/m	dB	dBuV	dBuV/m	dBuV/m	dB	
1	1697.129	3.43	26.66	40.63	44.87	34.33	74.00	-39.67	peak
2	4379.699	6.65	33.60	42.46	47.78	45.57	74.00	-28.43	peak
3	4904.000	7.20	34.33	42.84	45.99	44.68	74.00	-29.32	peak
4	6934.778	8.51	36.32	41.72	46.37	49.48	74.00	-24.52	peak
5	7356.000	8.88	36.36	41.50	45.51	49.25	74.00	-24.75	peak
6	9808.000	10.75	37.56	38.28	41.15	51.18	74.00	-22.82	peak



7 Photographs

7.1 Test Setup

Please refer to setup photos.

7.2 EUT Constructional Details (EUT Photos)

Please Refer to external and internal photos for details.

- End of the Report -