FCC RF Test Report

APPLICANT	:	Polebridge Port Hole Limited Liability Company
EQUIPMENT	:	Tablet
MODEL NAME	:	PR53DC
FCC ID	:	2AETH-1210
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	(NII) Unlicensed National Information Infrastructure

The testing was completed on Apr. 12, 2016. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Product Feature of Equipment Under Test 5
1.3 Product Specification of Equipment Under Test 5
1.4 Modification of EUT 5
1.5 Testing Location 6
1.6 Applicable Standards 6

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**

2.1 Carrier Frequency and Channel 7
2.2 Pre-Scanned RF Power 8
2.3 Test Mode 8
2.4 Connection Diagram of Test System 9
2.5 Support Unit used in test configuration and system 10
2.6 EUT Operation Test Setup 10
2.7 Measurement Results Explanation Example 10

3 TEST RESULT **11**

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 11
3.2 Maximum Conducted Output Power Measurement 14
3.3 Power Spectral Density Measurement 15
3.4 Unwanted Emissions Measurement 17
3.5 AC Conducted Emission Measurement 21
3.6 Frequency Stability Measurement 25
3.7 Automatically Discontinue Transmission 26
3.8 Antenna Requirements 28

4 LIST OF MEASURING EQUIPMENT **29**

5 UNCERTAINTY OF EVALUATION **30**

APPENDIX A. CONDUCTED TEST RESULTS

APPENDIX B. RADIATED SPURIOUS EMISSION

APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS

APPENDIX D. DUTY CYCLE PLOTS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5D3034-01E	Rev. 01	Initial issue of report	Apr. 26, 2016

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	≤ -17, -27 dBm/MHz &15.209(a)	Pass	Under limit 0.63 dB at 5714.280 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 16.90 dB at 2.694 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Polebridge Port Hole Limited Liability Company
Three Sugar Creek Center, Suite 100
Sugar Land, Texas, 77478

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Tablet
Model Name	PR53DC
FCC ID	2AETH-1210
EUT supports Radios application	WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth v4.1 EDR/LE

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	802.11a : 15.72 dBm / 0.0373 W 802.11n HT20 : 15.52 dBm / 0.0356 W 802.11n HT40 : 15.80 dBm / 0.0380 W
99% Occupied Bandwidth	802.11a : 17.65 MHz 802.11n HT20 : 18.40 MHz 802.11n HT40 : 36.50 MHz
Antenna Type	Fixed Internal Antenna with gain 1.60 dBi
Type of Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH02-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH12-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.6 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	**159**	**5795**
	151	**5755**	161	5805
	153	5765	165	5825
	157	5785		

Note: The above Frequency and Channel in boldface were 802.11n HT40.

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test in the following tables.

5GHz 802.11a mode								
Data Rate (MHz)	6M bps	9M bps	12M bps	18M bps	24M bps	36M bps	48M bps	54M bps
Average Power (dBm)	15.72	15.52	15.54	15.53	15.48	15.51	15.54	15.52

5GHz 802.11n HT20 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Average Power (dBm)	15.52	15.49	15.51	15.46	15.50	15.49	15.50	15.51

5GHz 802.11n HT40 mode								
Data Rate (MHz)	MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
Average Power (dBm)	15.80	15.78	15.76	15.73	15.69	15.74	15.67	15.70

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

AC Conducted Emission	Mode 1 : WLAN (5GHz) Link + Bluetooth Link + USB Cable (Charging from Adapter) + Camrea (Rear) + Earphone

Ch. #		Band IV：5725-5850 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159

2.4 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
5.	Micro SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, “ADB” installed in the notebook make the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.

2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth



Maximum 99% Occupied Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02. Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

1. The testing follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02.
   - Measure the duty cycle.
   - Set span to encompass the entire emission bandwidth (EBW) of the signal.
   - Set RBW = 300 kHz.
   - Set VBW ≥ 1 MHz.
   - Number of points in sweep ≥ 2 Span / RBW.
   - Sweep time = auto.
   - Detector = RMS
   - Trace average at least 100 traces in power averaging mode.
   - Add 10 log(500kHz/RBW) to the test result.
   - Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/300kHz)



3.4 Unwanted Emissions Measurement

This section as specified in FCC Part 15.407(b) is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement. The unwanted emissions shall comply with 15.407(b)(1) to (6), and restricted bands per FCC Part15.205.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5725-5850 MHz band: all emissions within the frequency range from the band edge to 10 MHz above or below the band edge shall not exceed an EIRP of -17 dBm/MHz (78.3dBμV/m); for frequencies 10 MHz or greater above or below the band edge, emissions shall not exceed an EIRP of -27 dBm/MHz (68.3dBμV/m).

(2) Unwanted spurious emissions fallen in restricted bands per FCC Part15.205 shall comply with the general field strength limits set forth in § 15.209 as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E=\frac{1000000\sqrt{30P}}{3}$$ μV/m, where P is the eirp (Watts)

EIRP (dBm)	Field Strength at 3m (dBμV/m)
-17	78.3
- 27	68.3

(3) KDB 789033 D02 General UNII Test Procedures New Rules v01r02 G)2)c) As specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r02. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz

   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.

6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B and Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



AMN = Artificial mains network (LISN)
AE = Associated equipment
EUT = Equipment under test
ISN = Impedance stabilization network

3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	23~24℃
Test Engineer :	Derreck Chen	**Relative Humidity :**	50~52%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	WLAN (5GHz) Link + Bluetooth Link + USB Cable (Charging from Adapter) + Camrea (Rear) + Earphone		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	36.9	Off	L1	19.6	27.9	64.8
0.438000	28.3	Off	L1	19.6	28.8	57.1
0.526000	35.3	Off	L1	19.6	20.7	56.0
1.230000	34.0	Off	L1	19.6	22.0	56.0
1.662000	35.0	Off	L1	19.6	21.0	56.0
2.646000	38.9	Off	L1	19.6	17.1	56.0
2.838000	38.2	Off	L1	19.6	17.8	56.0
22.942000	26.6	Off	L1	19.9	33.4	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	25.6	Off	L1	19.6	29.2	54.8
0.438000	19.4	Off	L1	19.6	27.7	47.1
0.526000	22.9	Off	L1	19.6	23.1	46.0
1.230000	22.8	Off	L1	19.6	23.2	46.0
1.662000	23.3	Off	L1	19.6	22.7	46.0
2.646000	26.0	Off	L1	19.6	20.0	46.0
2.838000	25.3	Off	L1	19.6	20.7	46.0
22.942000	19.3	Off	L1	19.9	30.7	50.0

Test Mode :	Mode 1	**Temperature :**	23~24℃
Test Engineer :	Derreck Chen	**Relative Humidity :**	50~52%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	WLAN (5GHz) Link + Bluetooth Link + USB Cable (Charging from Adapter) + Camrea (Rear) + Earphone		



Final Result : QuasiPeak

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	37.0	Off	N	19.6	27.8	64.8
0.342000	32.6	Off	N	19.6	26.6	59.2
0.414000	35.3	Off	N	19.6	22.3	57.6
0.518000	31.7	Off	N	19.6	24.3	56.0
2.694000	38.9	Off	N	19.6	17.1	56.0
19.742000	34.6	Off	N	19.9	25.4	60.0
21.110000	35.6	Off	N	20.0	24.4	60.0
23.238000	35.0	Off	N	20.0	25.0	60.0

Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	25.5	Off	N	19.6	29.3	54.8
0.342000	22.6	Off	N	19.6	26.6	49.2
0.414000	24.3	Off	N	19.6	23.3	47.6
0.518000	19.9	Off	N	19.6	26.1	46.0
2.694000	29.1	Off	N	19.6	16.9	46.0
19.742000	21.1	Off	N	19.9	28.9	50.0
21.110000	22.7	Off	N	20.0	27.3	50.0
23.238000	22.4	Off	N	20.0	27.6	50.0

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.

3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

EUT is verified this characteristic during the function check of normal sample associated with an access point:

A. Information start: make EUT supply information to the access point.

B. Information stop: stop supplying information to the access point.

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving.

C. Information start: make EUT supply information to the access point again.

The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

5745MHz



Note : The control / signalling information during the period B is precluded.

3.8 Antenna Requirements

3.8.1 Standard Applicable

According to FCC 47 CFR Section 15.407(a)(1)(2) ,if transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
DC Power Supply	TOPWARD	3303D	740889	N/A	May. 27, 2015	Apr. 08, 2016 ~ Apr. 12, 2016	May. 26, 2016	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz	Jul. 29, 2015	Apr. 08, 2016 ~ Apr. 12, 2016	Jul. 28, 2016	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz	Jul. 29, 2015	Apr. 08, 2016 ~ Apr. 12, 2016	Jul. 28, 2016	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz~40GHz	Jun. 18, 2015	Apr. 08, 2016 ~ Apr. 12, 2016	Jun. 17, 2016	Conducted (TH02-HY)
Temperature Chamber	ESPEC	SU-241	92003713	-30℃ ~95℃	Jun. 15, 2015	Apr. 08, 2016 ~ Apr. 12, 2016	Jun. 14, 2016	Conducted (TH02-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Mar. 21, 2016	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 26, 2015	Mar. 21, 2016	Aug. 25, 2016	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2015	Mar. 21, 2016	Dec. 01, 2016	Conduction (CO05-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Sep. 02, 2015	Mar. 31, 2016~ Apr. 01, 2016	Sep. 01, 2016	Radiation (03CH12-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHZ	Sep. 24, 2015	Mar. 31, 2016~ Apr. 01, 2016	Sep. 23, 2016	Radiation (03CH12-HY)
Bilog Antenna	TESEQ	CBL 6111D	37059	30MHz~1GHz	Dec. 29, 2015	Mar. 31, 2016~ Apr. 01, 2016	Dec. 28, 2016	Radiation (03CH12-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100390	20Hz~26.5GHz	Dec. 21, 2015	Mar. 31, 2016~ Apr. 01, 2016	Dec. 20, 2016	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Nov. 02, 2015	Mar. 31, 2016~ Apr. 01, 2016	Nov. 01, 2016	Radiation (03CH12-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 02, 2015	Mar. 31, 2016~ Apr. 01, 2016	Nov. 01, 2016	Radiation (03CH12-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Nov. 20, 2015	Mar. 31, 2016~ Apr. 01, 2016	Nov. 19, 2016	Radiation (03CH12-HY)
Preamplifier	MITEQ	AMF-7D-00101800-30-10P	1815698	1GHz~18GHz	Dec. 14, 2015	Mar. 31, 2016~ Apr. 01, 2016	Dec. 13, 2016	Radiation (03CH12-HY)
Preamplifier	Agilent	8449B	3008A02375	1GHz~26.5GHz	Jan. 05, 2016	Mar. 31, 2016~ Apr. 01, 2016	Jan. 04, 2017	Radiation (03CH12-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Mar. 31, 2016~ Apr. 01, 2016	N/A	Radiation (03CH12-HY)
Turn Table	EMEC	TT2000	N/A	0-360 degre	N/A	Mar. 31, 2016~ Apr. 01, 2016	N/A	Radiation (03CH12-HY)
Preamplifier	MITEQ	JS44-18004000-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Mar. 31, 2016~ Apr. 01, 2016	Jun. 01, 2016	Radiation (03CH12-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.26**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.4**

Appendix A. Conducted Test Results

Test Engineer:	Anan Wu and Derek Hsu	Temperature:	21~25	°C
Test Date:	2016/04/08 ~ 2016/04/12	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	17.65	29.5	15.76	0.5	Pass
11a	6Mbps	1	157	5785	17.45	28	15.16	0.5	Pass
11a	6Mbps	1	165	5825	17.45	30.3	15.12	0.5	Pass
HT20	MCS 0	1	149	5745	18.4	30.1	15.96	0.5	Pass
HT20	MCS 0	1	157	5785	18.3	27.5	15.12	0.5	Pass
HT20	MCS 0	1	165	5825	18.3	32.2	15.16	0.5	Pass
HT40	MCS 0	1	151	5755	36.2	41	35.04	0.5	Pass
HT40	MCS 0	1	159	5795	36.5	67.6	35.2	0.5	Pass

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.21	15.15	30.00	1.60		Pass
11a	6Mbps	1	157	5785	0.21	15.72	30.00	1.60		Pass
11a	6Mbps	1	165	5825	0.21	15.41	30.00	1.60		Pass
HT20	MCS 0	1	149	5745	0.22	15.10	30.00	1.60		Pass
HT20	MCS 0	1	157	5785	0.22	15.52	30.00	1.60		Pass
HT20	MCS 0	1	165	5825	0.22	15.43	30.00	1.60		Pass
HT40	MCS 0	1	151	5755	0.40	12.70	30.00	1.60		Pass
HT40	MCS 0	1	159	5795	0.40	15.80	30.00	1.60		Pass

Report Number : FR5D3034-01E

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.21	2.22	1.93	30.00	1.60	Pass
11a	6Mbps	1	157	5785	0.21	2.22	2.38	30.00	1.60	Pass
11a	6Mbps	1	165	5825	0.21	2.22	2.33	30.00	1.60	Pass
HT20	MCS 0	1	149	5745	0.22	2.22	1.84	30.00	1.60	Pass
HT20	MCS 0	1	157	5785	0.22	2.22	2.13	30.00	1.60	Pass
HT20	MCS 0	1	165	5825	0.22	2.22	1.87	30.00	1.60	Pass
HT40	MCS 0	1	151	5755	0.40	2.22	-4.39	30.00	1.60	Pass
HT40	MCS 0	1	159	5795	0.40	2.22	-1.17	30.00	1.60	Pass

Report Number : FR5D3034-01E

TEST RESULTS DATA
Frequency Stability

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stablility (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6M bps	1	149	5745	5745.000	0.000	0.00	25	3.4	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	25	4.2	
11a	6M bps	1	149	5745	5745.025	0.025	4.35	25	3.8	
11a	6M bps	1	149	5745	5745.050	0.050	8.70	0	3.8	
11a	6M bps	1	149	5745	5745.000	0.000	0.00	35	3.8	

Appendix B. Radiated Spurious Emission

Test Engineer :	Ricky Su, Nick Yu, and Citta Ke	Temperature :	21~23℃
		Relative Humidity :	51~53%

Band 4 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5712.2	60.2	-13.8	74	50.23	32.29	11.84	34.16	181	155	P	H
		5725	76.1	-2.2	78.3	66.11	32.31	11.84	34.16	181	155	P	H
		5714.12	48.22	-5.78	54	38.25	32.29	11.84	34.16	181	155	A	H
	*	5745	109.26	-	-	99.22	32.34	11.86	34.16	181	155	P	H
	*	5745	99.41	-	-	89.37	32.34	11.86	34.16	181	155	A	H
													H
													H
													H
		5696.44	58.37	-15.63	74	48.44	32.27	11.82	34.16	104	231	P	V
		5724.28	68.55	-9.75	78.3	58.56	32.31	11.84	34.16	104	231	P	V
		5714.76	46.9	-7.1	54	36.93	32.29	11.84	34.16	104	231	A	V
	*	5745	106.71	-	-	96.67	32.34	11.86	34.16	104	231	P	V
	*	5745	96.46	-	-	86.42	32.34	11.86	34.16	104	231	A	V
													V
													V
													V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		5705.56	58.99	-15.01	74	49.02	32.29	11.84	34.16	205	113	P	H
		5716.28	59.34	-18.96	78.3	49.37	32.29	11.84	34.16	205	113	P	H
		5705	47.4	-6.6	54	37.43	32.29	11.84	34.16	205	113	A	H
	*	5785	109.18	-	-	99.08	32.39	11.88	34.17	205	113	P	H
	*	5785	98.64	-	-	88.54	32.39	11.88	34.17	205	113	A	H
		5852.88	59.81	-18.49	78.3	49.47	32.48	12.03	34.17	205	113	P	H
		5864.96	58.85	-15.15	74	48.35	32.51	12.17	34.18	205	113	P	H
		5865.12	47.79	-6.21	54	37.29	32.51	12.17	34.18	205	113	A	H
		5705	57.82	-16.18	74	47.85	32.29	11.84	34.16	100	231	P	V
		5719.8	57.73	-20.57	78.3	47.74	32.31	11.84	34.16	100	231	P	V
		5705	46.39	-7.61	54	36.42	32.29	11.84	34.16	100	231	A	V
	*	5785	107.36	-	-	97.26	32.39	11.88	34.17	100	231	P	V
	*	5785	97.01	-	-	86.91	32.39	11.88	34.17	100	231	A	V
		5854.96	58.42	-19.88	78.3	48.06	32.51	12.03	34.18	100	231	P	V
		5863.68	58.42	-15.58	74	47.92	32.51	12.17	34.18	100	231	P	V
		5865.12	47.24	-6.76	54	36.74	32.51	12.17	34.18	100	231	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
	*	5825	109.58	-	-	99.26	32.46	12.03	34.17	205	113	P	H
	*	5825	99.29	-	-	88.97	32.46	12.03	34.17	205	113	A	H
		5857.6	61.11	-17.19	78.3	50.75	32.51	12.03	34.18	205	113	P	H
		5887.84	60.1	-13.9	74	49.55	32.56	12.17	34.18	205	113	P	H
		5861.28	48.31	-5.69	54	37.81	32.51	12.17	34.18	205	113	A	H
													H
													H
802.11a													H
CH 165	*	5825	107.15	-	-	96.83	32.46	12.03	34.17	100	231	P	V
5825MHz	*	5825	97.02	-	-	86.7	32.46	12.03	34.17	100	231	A	V
		5853.44	59.76	-18.54	78.3	49.42	32.48	12.03	34.17	100	231	P	V
		5887.52	59.37	-14.63	74	48.82	32.56	12.17	34.18	100	231	P	V
		5863.28	47.66	-6.34	54	37.16	32.51	12.17	34.18	100	231	A	V
													V
													V
													V
													V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	53.18	-20.82	74	52.45	40.11	18.4	57.78	300	147	P	H
		11490	43.12	-10.88	54	42.39	40.11	18.4	57.78	300	147	A	H
		17235	54.55	-19.45	74	46.9	41.65	23.14	57.14	100	52	P	H
		17235	44.63	-9.37	54	36.98	41.65	23.14	57.14	100	52	A	H
		11490	51.76	-22.24	74	51.03	40.11	18.4	57.78	268	43	P	V
		11490	41.62	-12.38	54	40.89	40.11	18.4	57.78	268	43	A	V
		17238	57.15	-16.85	74	49.5	41.65	23.14	57.14	100	121	P	V
		17238	47.06	-6.94	54	39.41	41.65	23.14	57.14	100	121	A	V
802.11a CH 157 5785MHz		11570	52.36	-21.64	74	51.72	39.95	18.49	57.8	300	127	P	H
		11570	42.3	-11.7	54	41.66	39.95	18.49	57.8	300	127	A	H
		17355	53.19	-20.81	74	45.48	42.02	23.25	57.56	312	99	P	H
		17355	42.98	-11.02	54	35.27	42.02	23.25	57.56	312	99	A	H
		11570	49.83	-24.17	74	49.19	39.95	18.49	57.8	400	0	P	V
		17355	53.23	-20.77	74	45.52	42.02	23.25	57.56	100	68	P	V
		17355	43.13	-10.87	54	35.42	42.02	23.25	57.56	100	68	A	V
													V
802.11a CH 165 5825MHz		11650	52.54	-21.46	74	51.96	39.8	18.58	57.8	300	126	P	H
		11650	42.46	-11.54	54	41.88	39.8	18.58	57.8	300	126	A	H
		17475	50.78	-23.22	74	43.01	42.39	23.36	57.98	266	102	P	H
		17475	40.66	-13.34	54	32.89	42.39	23.36	57.98	266	102	A	H
		11650	51.88	-22.12	74	51.3	39.8	18.58	57.8	100	77	P	V
		11650	41.66	-12.34	54	41.08	39.8	18.58	57.8	100	77	A	V
		17475	53.16	-20.84	74	45.39	42.39	23.36	57.98	100	180	P	V
		17475	42.89	-11.11	54	35.12	42.39	23.36	57.98	100	180	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5713.48	61.62	-12.38	74	51.65	32.29	11.84	34.16	181	154	P	H
		5724.84	74.79	-3.51	78.3	64.8	32.31	11.84	34.16	181	154	P	H
		5714.68	48.27	-5.73	54	38.3	32.29	11.84	34.16	181	154	A	H
	*	5745	109.16	-	-	99.12	32.34	11.86	34.16	181	154	P	H
	*	5745	99.09	-	-	89.05	32.34	11.86	34.16	181	154	A	H
													H
802.11n													H
HT20													H
CH 149		5714.84	62.21	-11.79	74	52.24	32.29	11.84	34.16	104	230	P	V
5745MHz		5723.88	71.16	-7.14	78.3	61.17	32.31	11.84	34.16	104	230	P	V
		5714.76	47.2	-6.8	54	37.23	32.29	11.84	34.16	104	230	A	V
	*	5745	106.33	-	-	96.29	32.34	11.86	34.16	104	230	P	V
	*	5745	96.38	-	-	86.34	32.34	11.86	34.16	104	230	A	V
													V
													V
													V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 157 5785MHz		5708.12	59.54	-14.46	74	49.57	32.29	11.84	34.16	189	137	P	H
		5722.76	58.71	-19.59	78.3	48.72	32.31	11.84	34.16	189	137	P	H
		5704.92	47.56	-6.44	54	37.59	32.29	11.84	34.16	189	137	A	H
	*	5785	108.67	-	-	98.57	32.39	11.88	34.17	189	137	P	H
	*	5785	98.88	-	-	88.78	32.39	11.88	34.17	189	137	A	H
		5851.2	59.2	-19.1	78.3	48.86	32.48	12.03	34.17	189	137	P	H
		5862.4	59.66	-14.34	74	49.16	32.51	12.17	34.18	189	137	P	H
		5865.04	47.73	-6.27	54	37.23	32.51	12.17	34.18	189	137	A	H
		5689	58.44	-15.56	74	48.51	32.27	11.82	34.16	100	233	P	V
		5715.24	58.72	-19.58	78.3	48.75	32.29	11.84	34.16	100	233	P	V
		5705.08	46.45	-7.55	54	36.48	32.29	11.84	34.16	100	233	A	V
	*	5785	106.67	-	-	96.57	32.39	11.88	34.17	100	233	P	V
	*	5785	96.65	-	-	86.55	32.39	11.88	34.17	100	233	A	V
		5857.52	59.03	-19.27	78.3	48.67	32.51	12.03	34.18	100	233	P	V
		5860.72	58.61	-15.39	74	48.11	32.51	12.17	34.18	100	233	P	V
		5865.04	47.22	-6.78	54	36.72	32.51	12.17	34.18	100	233	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz	*	5825	108.95	-	-	98.63	32.46	12.03	34.17	192	134	P	H
	*	5825	98.92	-	-	88.6	32.46	12.03	34.17	192	134	A	H
		5850	61.19	-12.81	74	50.85	32.48	12.03	34.17	192	134	P	H
		5876.08	59.39	-14.61	74	48.87	32.53	12.17	34.18	192	134	P	H
		5862.08	48.07	-5.93	54	37.57	32.51	12.17	34.18	192	134	A	H
													H
													H
													H
	*	5825	106.58	-	-	96.26	32.46	12.03	34.17	100	232	P	V
	*	5825	96.92	-	-	86.6	32.46	12.03	34.17	100	232	A	V
		5851.68	60.38	-17.92	78.3	50.04	32.48	12.03	34.17	100	232	P	V
		5884.8	59.42	-14.58	74	48.9	32.53	12.17	34.18	100	232	P	V
		5862.32	47.71	-6.29	54	37.21	32.51	12.17	34.18	100	232	A	V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	52.91	-21.09	74	52.18	40.11	18.4	57.78	311	259	P	H
		11490	42.82	-11.18	54	42.09	40.11	18.4	57.78	311	259	A	H
		17235	55.34	-18.66	74	47.69	41.65	23.14	57.14	293	48	P	H
		17235	45.15	-8.85	54	37.5	41.65	23.14	57.14	293	48	A	H
		11490	51.68	-22.32	74	50.95	40.11	18.4	57.78	100	133	P	V
		11490	41.36	-12.64	54	40.63	40.11	18.4	57.78	100	133	A	V
		17232	56.3	-17.7	74	48.65	41.65	23.14	57.14	100	100	P	V
		17232	46.15	-7.85	54	38.5	41.65	23.14	57.14	100	100	A	V
802.11n HT20 CH 157 5785MHz		11570	52.19	-21.81	74	51.55	39.95	18.49	57.8	366	293	P	H
		11570	41.97	-12.03	54	41.33	39.95	18.49	57.8	366	293	A	H
		17355	53.67	-20.33	74	45.96	42.02	23.25	57.56	333	68	P	H
		17355	43.72	-10.28	54	36.01	42.02	23.25	57.56	333	68	A	H
		11570	51.54	-22.46	74	50.9	39.95	18.49	57.8	100	96	P	V
		11570	41.52	-12.48	54	40.88	39.95	18.49	57.8	100	96	A	V
		17355	53.64	-20.36	74	45.93	42.02	23.25	57.56	100	150	P	V
		17355	43.42	-10.58	54	35.71	42.02	23.25	57.56	100	150	A	V
802.11n HT20 CH 165 5825MHz		11650	53.02	-20.98	74	52.44	39.8	18.58	57.8	300	300	P	H
		11650	41.91	-12.09	54	41.33	39.8	18.58	57.8	300	300	A	H
		17475	51.25	-22.75	74	43.48	42.39	23.36	57.98	200	247	P	H
		17475	40.1	-13.9	54	32.33	42.39	23.36	57.98	200	247	A	H
		11650	50.16	-23.84	74	49.58	39.8	18.58	57.8	100	0	P	V
		17475	52.73	-21.27	74	44.96	42.39	23.36	57.98	100	87	P	V
		17475	41.65	-12.35	54	33.88	42.39	23.36	57.98	100	87	A	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5714.28	67.67	-0.63	68.3	57.7	32.29	11.84	34.16	209	113	P	H
		5721.64	74.18	-4.12	78.3	64.19	32.31	11.84	34.16	209	113	P	H
	*	5755	103.17	-	-	93.12	32.36	11.86	34.17	209	113	P	H
		5755	93.01	-	-	82.96	32.36	11.86	34.17	209	113	A	H
		5858.16	57.83	-20.47	78.3	47.47	32.51	12.03	34.18	209	113	P	H
		5886.48	58.32	-9.98	68.3	47.8	32.53	12.17	34.18	209	113	P	H
802.11n													H
HT40													H
CH 151		5712.04	64.54	-3.76	68.3	54.57	32.29	11.84	34.16	100	230	P	V
5755MHz		5725	69.18	-9.12	78.3	59.19	32.31	11.84	34.16	100	230	P	V
	*	5755	101.14	-	-	91.09	32.36	11.86	34.17	100	230	P	V
		5755	90.61	-	-	80.56	32.36	11.86	34.17	100	230	A	V
		5856.88	58.11	-20.19	78.3	47.75	32.51	12.03	34.18	100	230	P	V
		5886.88	58.14	-10.16	68.3	47.62	32.53	12.17	34.18	100	230	P	V
													V
													V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5713.4	58.63	-15.37	74	48.66	32.29	11.84	34.16	200	113	P	H
		5723.96	59.08	-19.22	78.3	49.09	32.31	11.84	34.16	200	113	P	H
		5714.44	47.16	-6.84	54	37.19	32.29	11.84	34.16	200	113	A	H
	*	5795	105.63	-	-	95.51	32.41	11.88	34.17	200	113	P	H
	*	5795	95.25	-	-	85.13	32.41	11.88	34.17	200	113	A	H
		5850.16	59.31	-18.99	78.3	48.97	32.48	12.03	34.17	200	113	P	H
		5860.24	59.62	-14.38	74	49.12	32.51	12.17	34.18	200	113	P	H
		5862.4	48.12	-5.88	54	37.62	32.51	12.17	34.18	200	113	A	H
		5696.76	57.63	-16.37	74	47.7	32.27	11.82	34.16	100	231	P	V
		5722.04	58.16	-20.14	78.3	48.17	32.31	11.84	34.16	100	231	P	V
		5711.16	46.38	-7.62	54	36.41	32.29	11.84	34.16	100	231	A	V
	*	5795	103.96	-	-	93.84	32.41	11.88	34.17	100	231	P	V
	*	5795	93.44	-	-	83.32	32.41	11.88	34.17	100	231	A	V
		5856.8	58.7	-19.6	78.3	48.34	32.51	12.03	34.18	100	231	P	V
		5883.52	59.1	-14.9	74	48.58	32.53	12.17	34.18	100	231	P	V
		5863.6	47.66	-6.34	54	37.16	32.51	12.17	34.18	100	231	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	48.29	-25.71	74	47.54	40.1	18.45	57.8	100	0	P	H
		17268	49.24	-19.06	68.3	41.58	41.75	23.17	57.26	100	0	P	H
													H
													H
		11510	47.59	-26.41	74	46.84	40.1	18.45	57.8	100	0	P	V
		17268	49.9	-18.4	68.3	42.24	41.75	23.17	57.26	100	0	P	V
													V
													V
802.11n HT40 CH 159 5795MHz		11590	49.01	-24.99	74	48.36	39.91	18.54	57.8	100	0	P	H
		17388	50.82	-23.18	74	43.08	42.13	23.29	57.68	100	124	P	H
		17388	40.98	-13.02	54	33.24	42.13	23.29	57.68	100	124	A	H
													H
		11590	49.21	-24.79	74	48.56	39.91	18.54	57.8	100	0	P	V
		17388	52.05	-21.95	74	44.31	42.13	23.29	57.68	100	235	P	V
		17388	42.29	-11.71	54	34.55	42.13	23.29	57.68	100	235	A	V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
5GHz 802.11n HT40 LF		81.84	31.74	-8.26	40	49.31	13.81	1.06	32.44	124	60	P	H
		143.13	31.74	-11.76	43.5	44.72	17.69	1.75	32.42	-	-	P	H
		285.69	33.84	-12.16	46	44.63	19.22	2.25	32.26	-	-	P	H
		500.2	34.88	-11.12	46	40.09	24	3.19	32.4	-	-	P	H
		557.6	32.22	-13.78	46	36.68	24.64	3.3	32.4	-	-	P	H
		982.5	33.55	-20.45	54	30.57	29.91	3.92	30.85	-	-	P	H
													H
													H
													H
													H
													H
													H
		82.92	35.73	-4.27	40	53.08	14.03	1.06	32.44	-	-	P	V
		201.18	40.46	-3.04	43.5	55.34	15.83	1.7	32.41	112	210	P	V
		214.95	39.14	-4.36	43.5	53.77	16.05	1.7	32.38	-	-	P	V
		304.9	30.11	-15.89	46	40.37	19.64	2.34	32.24	-	-	P	V
		740.3	29.08	-16.92	46	30.08	27.36	3.97	32.33	-	-	P	V
		935.6	33.04	-12.96	46	29.77	29.92	4.6	31.25	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Radiated Spurious Emission Plots

Test Engineer :	Ricky Su, Nick Yu, and Citta Ke	**Temperature :**	21~23℃
		Relative Humidity :	51~53%

Note symbol

-L	**Low channel location**
-R	**High channel location**

Band 4 - 5725~5850MHz

WIFI 802.11a (Fundamental @ 3m)

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Fundamental @ 3m)

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Fundamental @ 3m)

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5

WIFI	Band 4 5725~5850MHz Fundamental @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Vertical
Peak/ Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 9

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz - L	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 10

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 11

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 12

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz - L	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH157 5785MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 13

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:0.300KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 14

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH151 5755MHz -	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5
Peak	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 15 Power : 14.5

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz - L	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11n HT40 CH159 5795MHz - R	
1	Horizontal	Vertical
Peak	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16
Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 HORIZONTAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B (AVG) 3m HORN_9120D_1328 VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Preject : 5D3034-01 Mode : 16

Band 4 - 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 9	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 9

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 10	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 10

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 11	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 11

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH149 5745MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 12	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 12

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH157 5785MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 13	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 13

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT20 CH165 5825MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 14	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 14

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH151 5755MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 15	 Site : 03CH12-HY Condition : FCC PART 15E_BAND4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 15

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11n HT40 CH159 5795MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 16	 Site : 03CH12-HY Condition : FCC CLASS-B_BAND 4 3m HORN_9120D_1328 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 16

Emission below 1GHz

5GHz WIFI 802.11n HT40 (LF)

WIFI	5GHz 5725~5850MHz	
ANT	802.11n HT40 LF	
1	Horizontal	Vertical
QP / Peak	 Site : 03CH12-HY Condition : FCC CLASS-B 3m BILOG_6111D_37059 HORIZONTAL Detector : Peak Preject : 5D3034-01 Mode : 18	 Site : 03CH12-HY Condition : FCC CLASS-B 3m BILOG_6111D_37059 VERTICAL Detector : Peak Preject : 5D3034-01 Mode : 18

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
802.11a	95.33	4080.00	0.25	300Hz
802.11n HT20	95.00	3800.00	0.26	300Hz
802.11n HT40	91.13	1850.00	0.54	1kHz

802.11a



Date: 28.MAR.2016 14:50:45

802.11n HT20



Date: 28.MAR.2016 15:21:20

802.11n HT40



Date: 28.MAR.2016 15:25:44