




FCC RADIO TEST REPORT

FCC ID : 2AEUP-5DYFA2
Equipment : Video Doorbell
Brand Name : ring 
Model Name : 5DFYA2
Applicant : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Manufacturer : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Jul. 04, 2025 and testing was performed from Jul. 23, 2025 to Aug. 22, 2025. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.



Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	6
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup	9
2.5 Measurement Results Explanation Example.....	9
3 Test Result	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	11
3.3 Power Spectral Density Measurement	12
3.4 Conducted Band Edges and Spurious Emission Measurement	13
3.5 Radiated Band Edges and Spurious Emission Measurement	14
3.6 AC Conducted Emission Measurement.....	18
3.7 Antenna Requirements.....	20
4 List of Measuring Equipment.....	21
5 Measurement Uncertainty	23
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission	
Appendix D. Radiated Spurious Emission Plots	
Appendix E. Duty Cycle Plots	
Appendix F. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR550659-01C	01	Initial issue of report	Sep. 20, 2025

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)(3)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203 15.247(b)	Antenna Requirement	Pass	-

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Hannah Yang



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth-LE, LoRa, Wi-Fi 2.4GHz 802.11b/g/n/ac/ax, and Wi-Fi 5GHz 802.11a/n/ac/ax and 24GHz Radar.		
Antenna Type LoRa: IFA Antenna		
Antenna information		
902 MHz ~ 928 MHz	Peak Gain (dBi)	0.5

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.



1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No.
	TH05-HY, CO07-HY, 03CH13-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.


2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
902 – 928 MHz	0	902.5	16	915.3
	1	903.3	17	916.1
	2	904.1	18	916.9
	3	904.9	19	917.7
	4	905.7	20	918.5
	5	906.5	21	919.3
	6	907.3	22	920.1
	7	908.1	23	920.9
	8	908.9	24	921.7
	9	909.7	25	922.5
	10	910.5	26	923.3
	11	911.3	27	924.1
	12	912.1	28	924.9
	13	912.9	29	925.7
	14	913.7	30	926.5
	15	914.5		

2.2 Test Mode

Summary table of Test Cases		
Test Item	Feature	LoRa
Conducted Test Cases	LoRa 500 KHz DTS	Mode 1: CH00 Tx_902.50 MHz
		Mode 2: CH15 Tx_914.50 MHz
		Mode 3: CH30 Tx_926.50 MHz
AC Conducted Emission	Mode 1: Lora TX + Power from plug in adapter	
Remark: The detailed Radiated test modes are shown in Appendix C.		

2.3 Connection Diagram of Test System





2.4 EUT Operation Test Setup

The RF test items, utility “J-Link RTT viewer V8.10e” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

Section 15.247(b)(3) For systems using digital modulation in the 902-928 MHz, the limit for peak output power is 1 watt.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.3 Method AVGPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated test above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Aug. 29, 2024	Aug. 04, 2025 ~ Aug. 13, 2025	Aug. 28, 2025	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9K~30M	Mar. 05, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Mar. 04, 2026	Radiation (03CH13-HY)
Amplifier	SONOMA	310N	187282	9kHz~1GHz	Dec. 12, 2024	Aug. 04, 2025 ~ Aug. 13, 2025	Dec. 11, 2025	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00800N1D01N-06	40103 & 07	30MHz~1GHz	Apr. 13, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Apr. 12, 2026	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz~18GHz	Aug. 15, 2024	Aug. 04, 2025 ~ Aug. 13, 2025	Aug. 14, 2025	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 14, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	May 13, 2026	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Jan. 11, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Jan. 10, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30MHz~18GHz	Feb. 06, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102E	508408-2E	30MHz~40GHz	Jun. 16, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Jun. 15, 2026	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/4	30MHz~18GHz	Feb. 06, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Feb. 05, 2026	Radiation (03CH13-HY)
Notch Filter	Wainwright	WLK4-1000-15 30-8000-40SS	SN12	1.53GHz Low Pass Filter	Sep. 11, 2024	Aug. 04, 2025 ~ Aug. 13, 2025	Sep. 10, 2025	Radiation (03CH13-HY)
Notch Filter	Wainwright	WHKX12-900-1000-15000-60 SS	SN11	1GHz High Pass Filter	Mar. 12, 2025	Aug. 04, 2025 ~ Aug. 13, 2025	Mar. 11, 2026	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP215159	N/A	Sep. 10, 2024	Aug. 04, 2025 ~ Aug. 13, 2025	Sep. 09, 2025	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Aug. 04, 2025 ~ Aug. 13, 2025	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Aug. 04, 2025 ~ Aug. 13, 2025	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Aug. 04, 2025 ~ Aug. 13, 2025	N/A	Radiation (03CH13-HY)
Software	Audix	N/A	RK-001124	N/A	N/A	Aug. 04, 2025 ~ Aug. 13, 2025	N/A	Radiation (03CH13-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 01, 2024	Aug. 01, 2025 ~ Aug. 22, 2025	Oct. 31, 2025	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	13I00030SNO 31 (NO:182)	9kHz~6GHz	Jan. 09, 2025	Aug. 01, 2025 ~ Aug. 22, 2025	Jan. 08, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101467	10HZ~44GHZ	Jan. 14, 2025	Aug. 01, 2025 ~ Aug. 22, 2025	Jan. 13, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Aug. 01, 2025 ~ Aug. 22, 2025	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_version_240513	N/A	Conducted Other Test Item	N/A	Aug. 01, 2025 ~ Aug. 22, 2025	N/A	Conducted (TH05-HY)

**FCC RADIO TEST REPORT****Report No. : FR550659-01C**

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Jul. 23, 2025	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 23, 2025	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 23, 2024	Jul. 23, 2025	Oct. 22, 2025	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 03, 2025	Jul. 23, 2025	Mar. 02, 2026	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 24, 2025	Jul. 23, 2025	Mar. 23, 2026	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 26, 2025	Jul. 23, 2025	Mar. 25, 2026	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 23, 2024	Jul. 23, 2025	Sep. 22, 2025	Conduction (CO07-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.80 dB
---	---------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu	Temperature:	23~25	°C
Test Date:	2025/8/1~2025/8/22	Relative Humidity:	54~58	%

<SF7>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Lora DTS 500Kbps	SF7	1	0	902.5	0.499	0.594	0.50	Pass
Lora DTS 500Kbps	SF7	1	15	914.5	0.527	0.617	0.50	Pass
Lora DTS 500Kbps	SF7	1	30	926.5	0.529	0.615	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Lora DTS 500Kbps	SF7	1	0	902.5	24.10	27.00	0.50	24.60	36.00	Pass
Lora DTS 500Kbps	SF7	1	15	914.5	23.70	27.00	0.50	24.20	36.00	Pass
Lora DTS 500Kbps	SF7	1	30	926.5	24.80	30.00	0.50	25.30	36.00	Pass

TEST RESULTS DATA
Average Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Average PSD (dBm /3kHz)	DG (dBi)	Average PSD Limit (dBm /3kHz)	Pass/Fail
Lora DTS 500Kbps	SF7	1	0	902.5	23.98	5.85	0.50	8.00	Pass
Lora DTS 500Kbps	SF7	1	15	914.5	23.54	4.08	0.50	8.00	Pass
Lora DTS 500Kbps	SF7	1	30	926.5	24.90	5.07	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<SF8>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Lora DTS 500Kbps	SF8	1	0	902.5	0.517	0.604	0.50	Pass
Lora DTS 500Kbps	SF8	1	15	914.5	0.532	0.629	0.50	Pass
Lora DTS 500Kbps	SF8	1	30	926.5	0.532	0.630	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Lora DTS 500Kbps	SF8	1	0	902.5	24.20	27.00	0.50	24.70	36.00	Pass
Lora DTS 500Kbps	SF8	1	15	914.5	23.70	27.00	0.50	24.20	36.00	Pass
Lora DTS 500Kbps	SF8	1	30	926.5	24.80	30.00	0.50	25.30	36.00	Pass

TEST RESULTS DATA
Average Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Average PSD (dBm /3kHz)	DG (dBi)	Average PSD Limit (dBm /3kHz)	Pass/Fail
Lora DTS 500Kbps	SF8	1	0	902.5	24.01	5.06	0.50	8.00	Pass
Lora DTS 500Kbps	SF8	1	15	914.5	23.57	4.21	0.50	8.00	Pass
Lora DTS 500Kbps	SF8	1	30	926.5	24.91	5.35	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<SF9>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Lora DTS 500Kbps	SF9	1	0	902.5	0.527	0.622	0.50	Pass
Lora DTS 500Kbps	SF9	1	15	914.5	0.538	0.635	0.50	Pass
Lora DTS 500Kbps	SF9	1	30	926.5	0.535	0.633	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Lora DTS 500Kbps	SF9	1	0	902.5	24.20	27.00	0.50	24.70	36.00	Pass
Lora DTS 500Kbps	SF9	1	15	914.5	24.80	27.00	0.50	25.30	36.00	Pass
Lora DTS 500Kbps	SF9	1	30	926.5	24.80	30.00	0.50	25.30	36.00	Pass

TEST RESULTS DATA
Average Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Average PSD (dBm /3kHz)	DG (dBi)	Average PSD Limit (dBm /3kHz)	Pass/Fail
Lora DTS 500Kbps	SF9	1	0	902.5	24.03	5.65	0.50	8.00	Pass
Lora DTS 500Kbps	SF9	1	15	914.5	24.70	5.29	0.50	8.00	Pass
Lora DTS 500Kbps	SF9	1	30	926.5	24.89	5.39	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<SF10>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Lora DTS 500Kbps	SF10	1	0	902.5	0.532	0.627	0.50	Pass
Lora DTS 500Kbps	SF10	1	15	914.5	0.539	0.637	0.50	Pass
Lora DTS 500Kbps	SF10	1	30	926.5	0.539	0.637	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Lora DTS 500Kbps	SF10	1	0	902.5	24.60	27.00	0.50	25.10	36.00	Pass
Lora DTS 500Kbps	SF10	1	15	914.5	24.70	27.00	0.50	25.20	36.00	Pass
Lora DTS 500Kbps	SF10	1	30	926.5	24.80	30.00	0.50	25.30	36.00	Pass

TEST RESULTS DATA
Average Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Average PSD (dBm /3kHz)	DG (dBi)	Average PSD Limit (dBm /3kHz)	Pass/Fail
Lora DTS 500Kbps	SF10	1	0	902.5	24.53	4.60	0.50	8.00	Pass
Lora DTS 500Kbps	SF10	1	15	914.5	24.61	4.73	0.50	8.00	Pass
Lora DTS 500Kbps	SF10	1	30	926.5	24.80	4.98	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

<SF11>

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
Lora DTS 500Kbps	SF11	1	0	902.5	0.536	0.628	0.50	Pass
Lora DTS 500Kbps	SF11	1	15	914.5	0.542	0.640	0.50	Pass
Lora DTS 500Kbps	SF11	1	30	926.5	0.540	0.638	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
Lora DTS 500Kbps	SF11	1	0	902.5	24.70	27.00	0.50	25.20	36.00	Pass
Lora DTS 500Kbps	SF11	1	15	914.5	24.70	27.00	0.50	25.20	36.00	Pass
Lora DTS 500Kbps	SF11	1	30	926.5	24.80	30.00	0.50	25.30	36.00	Pass




TEST RESULTS DATA
Average Power Density

Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Average PSD (dBm /3kHz)	DG (dBi)	Average PSD Limit (dBm /3kHz)	Pass/Fail
Lora DTS 500Kbps	SF11	1	0	902.5	24.52	5.43	0.50	8.00	Pass
Lora DTS 500Kbps	SF11	1	15	914.5	24.61	5.03	0.50	8.00	Pass
Lora DTS 500Kbps	SF11	1	30	926.5	24.80	6.25	0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

**99% Occupied Bandwidth**

<SF7>


99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 15****99% Occupied Bandwidth Plot on Channel 30**




Power Spectral Density (dBm/3kHz)

<SF7>


Power Density (dBm/3kHz) Plot Channel 0



Power Density (dBm/3kHz) Plot Channel 15






Power Density (dBm/3kHz) Plot Channel 30



**Band Edge and Conducted Spurious Emission**


<SF7>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~10GHz Plot**




Channel 15

100kHz PSD reference Level Plot




Spurious Emission 30MHz~10GHz Plot






Channel 30


100kHz PSD reference Level Plot



Plot on Channel 30






Spurious Emission 30MHz~10GHz Plot





**99% Occupied Bandwidth**

<SF8>


99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 15****99% Occupied Bandwidth Plot on Channel 30**




Power Spectral Density (dBm/3kHz)

<SF8>


Power Density (dBm/3kHz) Plot Channel 0



Power Density (dBm/3kHz) Plot Channel 15






Power Density (dBm/3kHz) Plot Channel 30



**Band Edge and Conducted Spurious Emission**


<SF8>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~10GHz Plot**




Channel 15

100kHz PSD reference Level Plot




Spurious Emission 30MHz~10GHz Plot






Channel 30


100kHz PSD reference Level Plot



Plot on Channel 30






Spurious Emission 30MHz~10GHz Plot






**6dB Bandwidth**

<SF9>

6 dB Bandwidth Plot on Channel 0**6 dB Bandwidth Plot on Channel 15****6 dB Bandwidth Plot on Channel 30**




**99% Occupied Bandwidth**

<SF9>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 15****99% Occupied Bandwidth Plot on Channel 30**




**Power Spectral Density (dBm/3kHz)**

<SF9>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 15****Power Density (dBm/3kHz) Plot Channel 30**

**Band Edge and Conducted Spurious Emission**


<SF9>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~10GHz Plot**




Channel 15

100kHz PSD reference Level Plot




Spurious Emission 30MHz~10GHz Plot






Channel 30


100kHz PSD reference Level Plot



Plot on Channel 30






Spurious Emission 30MHz~10GHz Plot






**6dB Bandwidth**

<SF10>

6 dB Bandwidth Plot on Channel 0**6 dB Bandwidth Plot on Channel 15****6 dB Bandwidth Plot on Channel 30**




**99% Occupied Bandwidth**

<SF10>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 15****99% Occupied Bandwidth Plot on Channel 30**




**Power Spectral Density (dBm/3kHz)**

<SF10>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 15****Power Density (dBm/3kHz) Plot Channel 30**

**Band Edge and Conducted Spurious Emission**


<SF10>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~10GHz Plot**




Channel 15

100kHz PSD reference Level Plot




Spurious Emission 30MHz~10GHz Plot






Channel 30


100kHz PSD reference Level Plot



Plot on Channel 30



Spurious Emission 30MHz~10GHz Plot







6dB Bandwidth

<SF11>


6 dB Bandwidth Plot on Channel 0



6 dB Bandwidth Plot on Channel 15






6 dB Bandwidth Plot on Channel 30






**99% Occupied Bandwidth**

<SF11>

99% Occupied Bandwidth Plot on Channel 0**99% Occupied Bandwidth Plot on Channel 15****99% Occupied Bandwidth Plot on Channel 30**




**Power Spectral Density (dBm/3kHz)**

<SF11>

Power Density (dBm/3kHz) Plot Channel 0**Power Density (dBm/3kHz) Plot Channel 15****Power Density (dBm/3kHz) Plot Channel 30**

**Band Edge and Conducted Spurious Emission**


<SF11>

Channel 0**100kHz PSD reference Level Plot****Plot on Channel 0****Spurious Emission 30MHz~10GHz Plot**




Channel 15

100kHz PSD reference Level Plot




Spurious Emission 30MHz~10GHz Plot






Channel 30


100kHz PSD reference Level Plot



Plot on Channel 30



Spurious Emission 30MHz~10GHz Plot






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	23.1~25.6℃
		Relative Humidity :	42.3~48.7%

EUT Information

Report NO : 550659-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Line

Full Spectrum



Final Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.152250	---	24.48	55.88	31.40	L1	FLO	20.0
0.152250	43.37	---	65.88	22.51	L1	FLO	20.0
0.183660	---	21.89	54.32	32.43	L1	FLO	20.0
0.183660	41.61	---	64.32	22.71	L1	FLO	20.0
0.209490	---	20.94	53.23	32.29	L1	FLO	20.0
0.209490	40.79	---	63.23	22.44	L1	FLO	20.0
0.231900	---	19.43	52.38	32.95	L1	FLO	20.0
0.231900	38.11	---	62.38	24.27	L1	FLO	20.0
0.258540	---	18.79	51.48	32.69	L1	FLO	20.0
0.258540	37.10	---	61.48	24.38	L1	FLO	20.0
0.285720	---	17.51	50.65	33.14	L1	FLO	20.0
0.285720	34.26	---	60.65	26.39	L1	FLO	20.0
0.314970	---	16.52	49.84	33.32	L1	FLO	20.0
0.314970	32.09	---	59.84	27.75	L1	FLO	20.0
0.442500	---	15.48	47.02	31.54	L1	FLO	20.0
0.442500	24.33	---	57.02	32.69	L1	FLO	20.0
0.469230	---	20.81	46.53	25.72	L1	FLO	20.0
0.469230	34.03	---	56.53	22.50	L1	FLO	20.0
0.493350	---	16.05	46.11	30.06	L1	FLO	20.0

0.493350	26.47	---	56.11	29.64	L1	FLO	20.0
13.132500	---	26.47	50.00	23.53	L1	FLO	20.5
13.132500	31.21	---	60.00	28.79	L1	FLO	20.5
21.579000	---	24.84	50.00	25.16	L1	FLO	20.9
21.579000	30.39	---	60.00	29.61	L1	FLO	20.9

EUT Information

Report NO : 550659-01
Test Mode : Mode 1
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	PE	Corr. (dB)
0.152250	---	24.84	55.88	31.04	N	FLO	20.0
0.152250	43.52	---	65.88	22.36	N	FLO	20.0
0.166290	---	23.81	55.14	31.33	N	FLO	20.0
0.166290	43.38	---	65.14	21.76	N	FLO	20.0
0.178890	---	21.60	54.54	32.94	N	FLO	20.0
0.178890	40.69	---	64.54	23.85	N	FLO	20.0
0.201750	---	20.23	53.54	33.31	N	FLO	20.0
0.201750	37.75	---	63.54	25.79	N	FLO	20.0
0.211830	---	21.05	53.13	32.08	N	FLO	20.0
0.211830	40.56	---	63.13	22.57	N	FLO	20.0
0.226500	---	18.88	52.58	33.70	N	FLO	20.0
0.226500	35.04	---	62.58	27.54	N	FLO	20.0
0.229380	---	19.14	52.47	33.33	N	FLO	20.0
0.229380	35.56	---	62.47	26.91	N	FLO	20.0
0.242250	---	18.81	52.02	33.21	N	FLO	20.0
0.242250	36.48	---	62.02	25.54	N	FLO	20.0
0.257190	---	19.00	51.52	32.52	N	FLO	20.0
0.257190	36.74	---	61.52	24.78	N	FLO	20.0
0.291570	---	17.40	50.48	33.08	N	FLO	20.0

0.291570	33.12	---	60.48	27.36	N	FLO	20.0
0.444030	---	17.82	46.99	29.17	N	FLO	20.0
0.444030	26.68	---	56.99	30.31	N	FLO	20.0
0.468330	---	24.83	46.54	21.71	N	FLO	20.0
0.468330	38.42	---	56.54	18.12	N	FLO	20.0
0.493530	---	18.79	46.11	27.32	N	FLO	20.0
0.493530	30.09	---	56.11	26.02	N	FLO	20.0
13.031250	---	24.11	50.00	25.89	N	FLO	20.5
13.031250	28.83	---	60.00	31.17	N	FLO	20.5
21.493500	---	24.83	50.00	25.17	N	FLO	20.9
21.493500	29.78	---	60.00	30.22	N	FLO	20.9



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Rain Lee, Jacky Hong and White Hou	Temperature :	20~26°C
		Relative Humidity :	40~65%

Note symbol

-L	Low channel location
-R	High channel location

**C1. Radiated Spurious Emission Test Modes**

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	902-928	0	Lora DTS 500KHz	0	902.5	SF7		
Mode 2	902-928	0	Lora DTS 500KHz	15	914.5	SF7		
Mode 3	902-928	0	Lora DTS 500KHz	30	926.5	SF7		
Mode 4	902-928	0	Lora DTS 500KHz	0	902.5	SF8		
Mode 5	902-928	0	Lora DTS 500KHz	15	914.5	SF8		
Mode 6	902-928	0	Lora DTS 500KHz	30	926.5	SF8		
Mode 7	902-928	0	Lora DTS 500KHz	0	902.5	SF9		
Mode 8	902-928	0	Lora DTS 500KHz	15	914.5	SF9		
Mode 9	902-928	0	Lora DTS 500KHz	30	926.5	SF9		
Mode 10	902-928	0	Lora DTS 500KHz	0	902.5	SF10		
Mode 11	902-928	0	Lora DTS 500KHz	15	914.5	SF10		



Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 12	902-928	0	Lora DTS 500KHz	30	926.5	SF10		
Mode 13	902-928	0	Lora DTS 500KHz	0	902.5	SF11		
Mode 14	902-928	0	Lora DTS 500KHz	15	914.5	SF11		
Mode 15	902-928	0	Lora DTS 500KHz	30	926.5	SF11		

**C2. Summary of each worse mode**

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Data Rate	Remark
1	Lora DTS 500KHz	00	2707.5	50.51	54	-3.49	H	Avg.	Pass	SF7	Harmonic
	Lora DTS 500KHz	00	30.97	33.97	40	-6.03	V	Peak.	Pass	SF7	LF
2	Lora DTS 500KHz	15	2743.5	50.24	54	-3.76	H	Avg.	Pass	SF7	Harmonic
	Lora DTS 500KHz	15	32.91	33.12	40	-6.88	V	Peak.	Pass	SF7	LF
3	Lora DTS 500KHz	30	2779.5	46.06	54	-7.94	H	Avg.	Pass	SF7	Harmonic
	Lora DTS 500KHz	30	31.94	33.66	40	-6.34	V	Peak.	Pass	SF7	LF
4	Lora DTS 500KHz	00	2707.5	50.24	54	-3.76	H	Avg.	Pass	SF8	Harmonic
	Lora DTS 500KHz	00	30.97	33.76	40	-6.24	V	Peak.	Pass	SF8	LF
5	Lora DTS 500KHz	15	2743.5	49.38	54	-4.62	H	Avg.	Pass	SF8	Harmonic
	Lora DTS 500KHz	15	30.97	33.1	40	-6.9	H	Peak.	Pass	SF8	LF



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Data Rate	Remark
6	Lora DTS 500KHz	30	2779.5	45.05	54	-8.95	H	Avg.	Pass	SF8	Harmonic
	Lora DTS 500KHz	30	967.02	47.91	54	-6.09	V	Peak.	Pass	SF8	LF
7	Lora DTS 500KHz	00	2707.5	49.39	54	-4.61	H	Avg.	Pass	SF9	Harmonic
	Lora DTS 500KHz	00	560.59	39.12	46	-6.88	V	Peak.	Pass	SF9	LF
8	Lora DTS 500KHz	15	2743.5	46.82	54	-7.18	H	Avg.	Pass	SF9	Harmonic
	Lora DTS 500KHz	15	554.77	39.73	46	-6.27	V	Peak.	Pass	SF9	LF
9	Lora DTS 500KHz	30	2779.5	45.47	54	-8.53	H	Avg.	Pass	SF9	Harmonic
	Lora DTS 500KHz	30	564.47	39.15	46	-6.85	V	Peak.	Pass	SF9	LF
10	Lora DTS 500KHz	00	2707.5	50.61	54	-3.39	H	Avg.	Pass	SF10	Harmonic
	Lora DTS 500KHz	00	983.51	47.75	54	-6.25	V	Peak.	Pass	SF10	LF



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Data Rate	Remark
11	Lora DTS 500KHz	15	2743.5	47.46	54	-6.54	H	Avg.	Pass	SF10	Harmonic
	Lora DTS 500KHz	15	999.03	47.3	54	-6.7	V	Peak.	Pass	SF10	LF
12	Lora DTS 500KHz	30	2779.5	46.27	54	-7.73	H	Avg.	Pass	SF10	Harmonic
	Lora DTS 500KHz	30	563.5	39.85	46	-6.15	H	Peak.	Pass	SF10	LF
13	Lora DTS 500KHz	00	2707.5	50.92	54	-3.08	H	Avg.	Pass	SF11	Harmonic
	Lora DTS 500KHz	00	1000	47.52	54	-6.48	V	Peak.	Pass	SF11	LF
14	Lora DTS 500KHz	15	2743.5	48.32	54	-5.68	H	Avg.	Pass	SF11	Harmonic
	Lora DTS 500KHz	15	30.97	33.28	40	-6.72	V	Peak.	Pass	SF11	LF
15	Lora DTS 500KHz	30	2779.5	45.53	54	-8.47	H	Avg.	Pass	SF11	Harmonic
	Lora DTS 500KHz	30	656.62	39.9	46	-6.1	V	Peak.	Pass	SF11	LF



Mode	1																																																																																																																																																																																																																																																																																																								
	Harmonic																																																																																																																																																																																																																																																																																																								
	902-928_Lora DTS 500KHz _CH00_ 902.5MHz																																																																																																																																																																																																																																																																																																								
ANT	0																																																																																																																																																																																																																																																																																																								
Pol.	Horizontal	Vertical																																																																																																																																																																																																																																																																																																							
Peak	Level (dBuV/m) Date: 2025-08-08 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2707.50</td><td>52.82</td><td>74.00</td><td>-21.18</td><td>74.74</td><td>28.20</td><td>7.27</td><td>57.57</td><td>0.18</td><td>168</td><td>212</td><td>Peak</td></tr><tr><td>2</td><td>2707.50</td><td>50.51</td><td>54.00</td><td>-3.49</td><td>72.43</td><td>28.20</td><td>7.27</td><td>57.57</td><td>0.18</td><td>168</td><td>212</td><td>Average</td></tr><tr><td>3</td><td>3610.00</td><td>37.60</td><td>74.00</td><td>-36.40</td><td>57.75</td><td>29.66</td><td>8.42</td><td>58.65</td><td>0.42</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>4512.50</td><td>38.91</td><td>74.00</td><td>-35.09</td><td>56.63</td><td>31.00</td><td>9.41</td><td>59.07</td><td>0.14</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>5415.00</td><td>47.31</td><td>74.00</td><td>-26.69</td><td>60.70</td><td>33.10</td><td>10.42</td><td>56.95</td><td>0.04</td><td>221</td><td>147</td><td>Peak</td></tr><tr><td>6</td><td>5415.00</td><td>40.40</td><td>54.00</td><td>-13.60</td><td>53.79</td><td>33.10</td><td>10.42</td><td>56.95</td><td>0.04</td><td>221</td><td>147</td><td>Average</td></tr><tr><td>7</td><td>8122.50</td><td>50.84</td><td>74.00</td><td>-23.16</td><td>58.00</td><td>37.06</td><td>12.89</td><td>57.25</td><td>0.14</td><td>192</td><td>278</td><td>Peak</td></tr><tr><td>8</td><td>8122.50</td><td>41.75</td><td>54.00</td><td>-12.25</td><td>48.91</td><td>37.06</td><td>12.89</td><td>57.25</td><td>0.14</td><td>192</td><td>278</td><td>Average</td></tr><tr><td>9</td><td>9025.00</td><td>45.12</td><td>74.00</td><td>-28.88</td><td>50.23</td><td>38.00</td><td>13.61</td><td>56.73</td><td>0.01</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	2707.50	52.82	74.00	-21.18	74.74	28.20	7.27	57.57	0.18	168	212	Peak	2	2707.50	50.51	54.00	-3.49	72.43	28.20	7.27	57.57	0.18	168	212	Average	3	3610.00	37.60	74.00	-36.40	57.75	29.66	8.42	58.65	0.42	--	--	Peak	4	4512.50	38.91	74.00	-35.09	56.63	31.00	9.41	59.07	0.14	--	--	Peak	5	5415.00	47.31	74.00	-26.69	60.70	33.10	10.42	56.95	0.04	221	147	Peak	6	5415.00	40.40	54.00	-13.60	53.79	33.10	10.42	56.95	0.04	221	147	Average	7	8122.50	50.84	74.00	-23.16	58.00	37.06	12.89	57.25	0.14	192	278	Peak	8	8122.50	41.75	54.00	-12.25	48.91	37.06	12.89	57.25	0.14	192	278	Average	9	9025.00	45.12	74.00	-28.88	50.23	38.00	13.61	56.73	0.01	--	--	Peak	Level (dBuV/m) Date: 2025-08-08 Site : 03CH13-HY Condition: PEAK_74 3m HORN_91280_1326 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2707.50</td><td>52.14</td><td>74.00</td><td>-21.86</td><td>74.06</td><td>28.20</td><td>7.27</td><td>57.57</td><td>0.18</td><td>100</td><td>340</td><td>Peak</td></tr><tr><td>2</td><td>2707.50</td><td>49.67</td><td>54.00</td><td>-4.33</td><td>71.59</td><td>28.20</td><td>7.27</td><td>57.57</td><td>0.18</td><td>100</td><td>340</td><td>Average</td></tr><tr><td>3</td><td>3610.00</td><td>37.34</td><td>74.00</td><td>-36.66</td><td>57.49</td><td>29.66</td><td>8.42</td><td>58.65</td><td>0.42</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>4512.50</td><td>39.14</td><td>74.00</td><td>-34.86</td><td>56.86</td><td>31.00</td><td>9.41</td><td>59.07</td><td>0.14</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>5</td><td>5415.00</td><td>45.63</td><td>74.00</td><td>-28.37</td><td>59.02</td><td>33.10</td><td>10.42</td><td>56.95</td><td>0.04</td><td>205</td><td>228</td><td>Peak</td></tr><tr><td>6</td><td>5415.00</td><td>38.79</td><td>54.00</td><td>-15.21</td><td>52.18</td><td>33.10</td><td>10.42</td><td>56.95</td><td>0.04</td><td>205</td><td>228</td><td>Average</td></tr><tr><td>7</td><td>8122.50</td><td>48.74</td><td>74.00</td><td>-25.26</td><td>55.90</td><td>37.06</td><td>12.89</td><td>57.25</td><td>0.14</td><td>330</td><td>54</td><td>Peak</td></tr><tr><td>8</td><td>8122.50</td><td>40.04</td><td>54.00</td><td>-13.96</td><td>47.20</td><td>37.06</td><td>12.89</td><td>57.25</td><td>0.14</td><td>330</td><td>54</td><td>Average</td></tr><tr><td>9</td><td>9025.00</td><td>45.35</td><td>74.00</td><td>-28.65</td><td>50.46</td><td>38.00</td><td>13.61</td><td>56.73</td><td>0.01</td><td>--</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor				MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg	1	2707.50	52.14	74.00	-21.86	74.06	28.20	7.27	57.57	0.18	100	340	Peak	2	2707.50	49.67	54.00	-4.33	71.59	28.20	7.27	57.57	0.18	100	340	Average	3	3610.00	37.34	74.00	-36.66	57.49	29.66	8.42	58.65	0.42	--	--	Peak	4	4512.50	39.14	74.00	-34.86	56.86	31.00	9.41	59.07	0.14	--	--	Peak	5	5415.00	45.63	74.00	-28.37	59.02	33.10	10.42	56.95	0.04	205	228	Peak	6	5415.00	38.79	54.00	-15.21	52.18	33.10	10.42	56.95	0.04	205	228	Average	7	8122.50	48.74	74.00	-25.26	55.90	37.06	12.89	57.25	0.14	330	54	Peak	8	8122.50	40.04	54.00	-13.96	47.20	37.06	12.89	57.25	0.14	330	54	Average	9	9025.00	45.35	74.00	-28.65	50.46	38.00	13.61	56.73	0.01	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																																																																																																																																																																																			
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																																
1	2707.50	52.82	74.00	-21.18	74.74	28.20	7.27	57.57	0.18	168	212	Peak																																																																																																																																																																																																																																																																																													
2	2707.50	50.51	54.00	-3.49	72.43	28.20	7.27	57.57	0.18	168	212	Average																																																																																																																																																																																																																																																																																													
3	3610.00	37.60	74.00	-36.40	57.75	29.66	8.42	58.65	0.42	--	--	Peak																																																																																																																																																																																																																																																																																													
4	4512.50	38.91	74.00	-35.09	56.63	31.00	9.41	59.07	0.14	--	--	Peak																																																																																																																																																																																																																																																																																													
5	5415.00	47.31	74.00	-26.69	60.70	33.10	10.42	56.95	0.04	221	147	Peak																																																																																																																																																																																																																																																																																													
6	5415.00	40.40	54.00	-13.60	53.79	33.10	10.42	56.95	0.04	221	147	Average																																																																																																																																																																																																																																																																																													
7	8122.50	50.84	74.00	-23.16	58.00	37.06	12.89	57.25	0.14	192	278	Peak																																																																																																																																																																																																																																																																																													
8	8122.50	41.75	54.00	-12.25	48.91	37.06	12.89	57.25	0.14	192	278	Average																																																																																																																																																																																																																																																																																													
9	9025.00	45.12	74.00	-28.88	50.23	38.00	13.61	56.73	0.01	--	--	Peak																																																																																																																																																																																																																																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																																																																																																																																																																																																																																			
MHz	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	dB	cm	deg																																																																																																																																																																																																																																																																																															
1	2707.50	52.14	74.00	-21.86	74.06	28.20	7.27	57.57	0.18	100	340	Peak																																																																																																																																																																																																																																																																																													
2	2707.50	49.67	54.00	-4.33	71.59	28.20	7.27	57.57	0.18	100	340	Average																																																																																																																																																																																																																																																																																													
3	3610.00	37.34	74.00	-36.66	57.49	29.66	8.42	58.65	0.42	--	--	Peak																																																																																																																																																																																																																																																																																													
4	4512.50	39.14	74.00	-34.86	56.86	31.00	9.41	59.07	0.14	--	--	Peak																																																																																																																																																																																																																																																																																													
5	5415.00	45.63	74.00	-28.37	59.02	33.10	10.42	56.95	0.04	205	228	Peak																																																																																																																																																																																																																																																																																													
6	5415.00	38.79	54.00	-15.21	52.18	33.10	10.42	56.95	0.04	205	228	Average																																																																																																																																																																																																																																																																																													
7	8122.50	48.74	74.00	-25.26	55.90	37.06	12.89	57.25	0.14	330	54	Peak																																																																																																																																																																																																																																																																																													
8	8122.50	40.04	54.00	-13.96	47.20	37.06	12.89	57.25	0.14	330	54	Average																																																																																																																																																																																																																																																																																													
9	9025.00	45.35	74.00	-28.65	50.46	38.00	13.61	56.73	0.01	--	--	Peak																																																																																																																																																																																																																																																																																													



Mode	1																																																																																																																																																																																																																	
	LF																																																																																																																																																																																																																	
	902-928_Lora DTS 500KHz _CH00_ 902.5MHz																																																																																																																																																																																																																	
ANT	0																																																																																																																																																																																																																	
Pol.	Horizontal					Vertical																																																																																																																																																																																																												
QPI Peak	Level (dBuV/m) Date: 2025-08-12 Site : 03CH13-HY Condition: QP 3m BILOG_40103 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>34.85</td><td>32.32</td><td>40.00</td><td>-7.68</td><td>31.47</td><td>22.06</td><td>0.82</td><td>32.00</td><td>0.12 -- -- Peak</td></tr><tr><td>2</td><td>159.98</td><td>31.08</td><td>43.50</td><td>-12.42</td><td>34.81</td><td>16.51</td><td>1.68</td><td>31.89</td><td>0.11 -- -- Peak</td></tr><tr><td>3</td><td>259.89</td><td>30.85</td><td>46.00</td><td>-15.15</td><td>30.37</td><td>20.10</td><td>2.13</td><td>31.74</td><td>0.12 -- -- Peak</td></tr><tr><td>4</td><td>406.36</td><td>34.11</td><td>46.00</td><td>-11.89</td><td>31.28</td><td>21.89</td><td>2.66</td><td>31.68</td><td>0.08 -- -- Peak</td></tr><tr><td>5</td><td>502.39</td><td>36.15</td><td>46.00</td><td>-9.85</td><td>31.00</td><td>23.98</td><td>2.96</td><td>31.80</td><td>0.11 -- -- Peak</td></tr><tr><td>6</td><td>902.50</td><td>116.12</td><td>-----</td><td>-----</td><td>104.00</td><td>29.01</td><td>3.98</td><td>31.07</td><td>0.19 100 153 Peak</td></tr><tr><td>7</td><td>966.05</td><td>45.45</td><td>54.00</td><td>-8.55</td><td>30.68</td><td>31.05</td><td>4.10</td><td>30.51</td><td>0.21 -- -- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	34.85	32.32	40.00	-7.68	31.47	22.06	0.82	32.00	0.12 -- -- Peak	2	159.98	31.08	43.50	-12.42	34.81	16.51	1.68	31.89	0.11 -- -- Peak	3	259.89	30.85	46.00	-15.15	30.37	20.10	2.13	31.74	0.12 -- -- Peak	4	406.36	34.11	46.00	-11.89	31.28	21.89	2.66	31.68	0.08 -- -- Peak	5	502.39	36.15	46.00	-9.85	31.00	23.98	2.96	31.80	0.11 -- -- Peak	6	902.50	116.12	-----	-----	104.00	29.01	3.98	31.07	0.19 100 153 Peak	7	966.05	45.45	54.00	-8.55	30.68	31.05	4.10	30.51	0.21 -- -- Peak	Level (dBuV/m) Date: 2025-08-12 Site : 03CH13-HY Condition: QP 3m BILOG_40103 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>30.97</td><td>33.97</td><td>40.00</td><td>-6.03</td><td>31.11</td><td>24.18</td><td>0.78</td><td>32.00</td><td>0.05 -- -- Peak</td></tr><tr><td>2</td><td>146.40</td><td>31.85</td><td>43.50</td><td>-11.65</td><td>34.73</td><td>17.50</td><td>1.61</td><td>31.92</td><td>0.08 -- -- Peak</td></tr><tr><td>3</td><td>261.83</td><td>30.67</td><td>46.00</td><td>-15.33</td><td>30.09</td><td>20.19</td><td>2.14</td><td>31.74</td><td>0.12 -- -- Peak</td></tr><tr><td>4</td><td>419.94</td><td>34.28</td><td>46.00</td><td>-11.72</td><td>30.90</td><td>22.40</td><td>2.70</td><td>31.69</td><td>0.09 -- -- Peak</td></tr><tr><td>5</td><td>505.30</td><td>35.83</td><td>46.00</td><td>-10.17</td><td>30.64</td><td>24.00</td><td>2.97</td><td>31.79</td><td>0.11 -- -- Peak</td></tr><tr><td>6</td><td>902.50</td><td>124.41</td><td>-----</td><td>-----</td><td>112.37</td><td>29.01</td><td>3.98</td><td>31.07</td><td>0.19 114 307 Peak</td></tr><tr><td>7</td><td>993.21</td><td>47.62</td><td>54.00</td><td>-6.38</td><td>33.04</td><td>30.51</td><td>4.16</td><td>30.22</td><td>0.23 -- -- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	30.97	33.97	40.00	-6.03	31.11	24.18	0.78	32.00	0.05 -- -- Peak	2	146.40	31.85	43.50	-11.65	34.73	17.50	1.61	31.92	0.08 -- -- Peak	3	261.83	30.67	46.00	-15.33	30.09	20.19	2.14	31.74	0.12 -- -- Peak	4	419.94	34.28	46.00	-11.72	30.90	22.40	2.70	31.69	0.09 -- -- Peak	5	505.30	35.83	46.00	-10.17	30.64	24.00	2.97	31.79	0.11 -- -- Peak	6	902.50	124.41	-----	-----	112.37	29.01	3.98	31.07	0.19 114 307 Peak	7	993.21	47.62	54.00	-6.38	33.04	30.51	4.16	30.22	0.23 -- -- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																								
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																									
1	34.85	32.32	40.00	-7.68	31.47	22.06	0.82	32.00	0.12 -- -- Peak																																																																																																																																																																																																									
2	159.98	31.08	43.50	-12.42	34.81	16.51	1.68	31.89	0.11 -- -- Peak																																																																																																																																																																																																									
3	259.89	30.85	46.00	-15.15	30.37	20.10	2.13	31.74	0.12 -- -- Peak																																																																																																																																																																																																									
4	406.36	34.11	46.00	-11.89	31.28	21.89	2.66	31.68	0.08 -- -- Peak																																																																																																																																																																																																									
5	502.39	36.15	46.00	-9.85	31.00	23.98	2.96	31.80	0.11 -- -- Peak																																																																																																																																																																																																									
6	902.50	116.12	-----	-----	104.00	29.01	3.98	31.07	0.19 100 153 Peak																																																																																																																																																																																																									
7	966.05	45.45	54.00	-8.55	30.68	31.05	4.10	30.51	0.21 -- -- Peak																																																																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																																									
1	30.97	33.97	40.00	-6.03	31.11	24.18	0.78	32.00	0.05 -- -- Peak																																																																																																																																																																																																									
2	146.40	31.85	43.50	-11.65	34.73	17.50	1.61	31.92	0.08 -- -- Peak																																																																																																																																																																																																									
3	261.83	30.67	46.00	-15.33	30.09	20.19	2.14	31.74	0.12 -- -- Peak																																																																																																																																																																																																									
4	419.94	34.28	46.00	-11.72	30.90	22.40	2.70	31.69	0.09 -- -- Peak																																																																																																																																																																																																									
5	505.30	35.83	46.00	-10.17	30.64	24.00	2.97	31.79	0.11 -- -- Peak																																																																																																																																																																																																									
6	902.50	124.41	-----	-----	112.37	29.01	3.98	31.07	0.19 114 307 Peak																																																																																																																																																																																																									
7	993.21	47.62	54.00	-6.38	33.04	30.51	4.16	30.22	0.23 -- -- Peak																																																																																																																																																																																																									

Remark: The unwanted signal falls within the non-restricted band and meet the requirements of 15.247 (d).