


RF Exposure Evaluation Report

APPLICANT : Ring LLC
EQUIPMENT : Environmental Alert Device
BRAND NAME : ring
MODEL NAME : 7ACEAB
FCC ID : 2AEUP-7ACEAB
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Nov. 13, 2025 and completed on Nov. 13, 2025. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.



Approved by: Hank Huang

Sporton International Inc. (Shenzhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	5
4. RF EXPOSURE LIMIT INTRODUCTION	6
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	7
5.1. Standalone Power Density Calculation	7



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA5N0519	Rev. 01	Initial issue of report.	Dec. 16, 2025



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	Ring LLC
Address	12515 Cerise Ave, Hawthorne, CA 90250, USA

Manufacturer	
Company Name	Ring LLC
Address	12515 Cerise Ave, Hawthorne, CA 90250, USA

2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Environmental Alert Device
Brand Name	ring
Model Name	7ACEAB
FCC ID	2AEUP-7ACEAB
Wireless Technology and Frequency Range	Bluetooth: 2402 MHz ~ 2480 MHz LoRa: 902 MHz ~ 928 MHz
Mode	Bluetooth LE LoRa / FSK
Antenna Gain	Bluetooth: 3.58 dBi LoRa: 1.45 dBi
Antenna Type	Bluetooth: Metal IFA antenna LoRa: Metal IFA antenna
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Comments and Explanations:
1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF output tune up power among production units

<Bluetooth>

Mode	Maximum power(dBm)
Bluetooth LE	10.0

<LoRa>

Mode	Maximum Power (dBm)
LoRa	21.0

4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna

5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
Bluetooth	2402.0	3.58	10.00	13.580	22.803	0.0045	1.000
LoRa	902.0	1.45	21.00	22.450	175.792	0.0350	0.601

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. According to the EUT characteristic, Bluetooth and LoRa cannot transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----