



FCC RF Test Report

APPLICANT : Ring LLC
EQUIPMENT : Environmental Alert Device
BRAND NAME : ring
MODEL NAME : 7ACEAB
FCC ID : 2AEUP-7ACEAB
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 07, 2025 ~ Dec. 16, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Test Software.....	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	8
2.4 EUT Operation Test Setup	9
2.5 Measurement Results Explanation Example.....	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	19
3.3 Power Spectral Density Measurement	20
3.4 Conducted Band Edges and Spurious Emission Measurement	29
3.5 Radiated Band Edges and Spurious Emission Measurement	38
3.6 Antenna Requirements	42
4 LIST OF MEASURING EQUIPMENT.....	43
5 UNCERTAINTY OF EVALUATION.....	44
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX D. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5N0519B	Rev. 01	Initial issue of report	Dec. 16, 2025
FR5N0519B	Rev. 02	Updated test plots for 6dB Bandwidth This report is an updated version, replacing the report issued on Dec. 16, 2025.	Dec. 22, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Report Only	-
3.2	15.247(b)(3)	Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 30\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 11.75 dB at 8230.500 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Applicable	1
3.6	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Remark1: Powered by a button battery only.

Conformity Assessment Condition:

- The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
- The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Ring LLC

12515 Cerise Ave, Hawthorne, CA 90250, USA

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Environmental Alert Device
Brand Name	ring
Model Name	7ACEAB
FCC ID	2AEUP-7ACEAB
SN Code	N/A
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	902 MHz ~ 928 MHz
Number of Channels	31
Bandwidth / Spread Factor	500kHz / 7, 8, 9, 10, 11
Maximum Output Power to Antenna	LoRa DTS SF7 : 19.70 dBm (0.0933 W) LoRa DTS SF8 : 19.60 dBm (0.0912 W) LoRa DTS SF9 : 19.60 dBm (0.0912 W) LoRa DTS SF10 : 19.60 dBm (0.0912 W) LoRa DTS SF11 : 19.80 dBm (0.0955 W)
99% Occupied Bandwidth	LoRa DTS SF7 : 0.51 MHz LoRa DTS SF11 : 0.53 MHz
Antenna Type / Gain	Metal IFA antenna with gain 1.45 dBi
Type of Modulation	LoRa

Note: For SF7/8/9/10/11 mode, the bandwidth and modulation are the same, only the data rate is different, so the whole testing has assessed SF7/11 mode by referring to the higher conducted power.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.



1.5 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH03-SZ	CN1256	421272

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2020

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
902-928 MHz	1	902.5	17	915.3
	2	903.3	18	916.1
	3	904.1	19	916.9
	4	904.9	20	917.7
	5	905.7	21	918.5
	6	906.5	22	919.3
	7	907.3	23	920.1
	8	908.1	24	920.9
	9	908.9	25	921.7
	10	909.7	26	922.5
	11	910.5	27	923.3
	12	911.3	28	924.1
	13	912.1	29	924.9
	14	912.9	30	925.7
	15	913.7	31	926.5
	16	914.5	-	-

Note: The above EUT's information was declared by manufacturer.


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Modulation
	Lora 500kHz DTS
Conducted TCs	Mode 1: LoRa Tx CH01_902.5 MHz
	Mode 2: LoRa Tx CH16_914.5 MHz
	Mode 3: LoRa Tx CH31_926.5 MHz
Radiated TCs	Mode 1: LoRa Tx CH01_902.5 MHz
	Mode 2: LoRa Tx CH16_914.5 MHz
	Mode 3: LoRa Tx CH31_926.5 MHz

2.3 Connection Diagram of Test System





2.4 EUT Operation Test Setup

For LoRa function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 0.3 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.3 + 20 = 20.3 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.8.1 for 6dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. Detector = Peak. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


For SF7:

6 dB Bandwidth Plot on 902.5 MHz



Date: 7.OCT.2025 16:00:12


6 dB Bandwidth Plot on 914.5 MHz



Date: 7.OCT.2025 16:04:36



6 dB Bandwidth Plot on 926.5 MHz




Date: 7.OCT.2025 16:08:17




For SF11:

6 dB Bandwidth Plot on 902.5MHz




6 dB Bandwidth Plot on 914.5 MHz





6 dB Bandwidth Plot on 926.5 MHz



Date: 7.OCT.2025 16:36:00




3.1.6 Test Result of 99% Occupied Bandwidth


Please refer to Appendix A.

For SF7:

99% Bandwidth Plot on 902.5 MHz




99% Occupied Bandwidth Plot on 914.5 MHz





99% Occupied Bandwidth Plot on 926.5 MHz




Date: 1.DEC.2025 16:26:47




For SF11:

99% Bandwidth Plot on 902.5MHz



Date: 1.DEC.2025 16:30:24


99% Bandwidth Plot on 914.5 MHz



Date: 1.DEC.2025 16:33:22



99% Bandwidth Plot on 926.5 MHz



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 902-928MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.5 Method AVGPSD-2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = power averaging (rms), Sweep time = auto couple. Use the peak marker function to determine the maximum power level.
6. Employ trace averaging (rms) mode over a minimum of 100 traces.
7. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
8. Measure and record the results in the test report.
9. Add $[10 \log (1 / D)]$, where D is the duty cycle.
10. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

For SF7:

PSD 100kHz Plot on 902.5 MHz




PSD 100kHz Plot on 914.5 MHz






PSD 100kHz Plot on 926.5 MHz




Date: 7.OCT.2025 16:08:48

For SF11:


PSD 100kHz Plot on 902.5 MHz



PSD 100kHz Plot on 914.5 MHz



PSD 100kHz Plot on 926.5 MHz




Date: 7.OCT.2025 16:37:20


3.3.7 Test Result of Power Spectral Density Plots (3kHz)

For SF7:

PSD 3kHz Plot on 902.5 MHz




PSD 3kHz Plot on 914.5 MHz





PSD 3kHz Plot on 926.5 MHz




Date: 7.OCT.2025 16:09:20




For SF11:

PSD 3kHz Plot on 902.5 MHz



Date: 7.OCT.2025 16:22:16


PSD 3kHz Plot on 914.5 MHz



Date: 7.OCT.2025 16:32:35



PSD 3kHz Plot on 926.5 MHz



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 11.11.3
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz when the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup






3.4.5 Test Result of Conducted Band Edges Plots

For SF7:


Low Band Edge Plot on 902.5 MHz



Date: 7.OCT.2025 16:03:11

Note: F1= 902MHz

High Band Edge Plot on 926.5 MHz




Date: 7.OCT.2025 16:11:11

Note: F1= 928MHz


For SF11:

Low Band Edge Plot on 902.5 MHz



Note: F1= 902MHz

High Band Edge Plot on 926.5 MHz




Note: F1= 928MHz




3.4.6 Test Result of Conducted Spurious Emission Plots

For SF7:

Conducted Spurious Emission Plot on 902.5 MHz




Conducted Spurious Emission Plot on 902.5 MHz






Conducted Spurious Emission Plot on 914.5 MHz



Date: 7.OCT.2025 16:06:13


Conducted Spurious Emission Plot on 914.5 MHz



Date: 7.OCT.2025 16:06:45




Conducted Spurious Emission Plot on 926.5 MHz



Date: 7.OCT.2025 16:09:46

Conducted Spurious Emission Plot on 926.5 MHz




Date: 7.OCT.2025 16:10:18




For SF11:

Conducted Spurious Emission Plot on 902.5 MHz




Conducted Spurious Emission Plot on 902.5 MHz






Conducted Spurious Emission Plot on 914.5 MHz



Date: 7.OCT.2025 16:33:10


Conducted Spurious Emission Plot on 914.5 MHz



Date: 7.OCT.2025 16:33:38




Conducted Spurious Emission Plot on 926.5 MHz



Date: 7.OCT.2025 16:38:35

Conducted Spurious Emission Plot on 926.5 MHz



Date: 7.OCT.2025 16:39:07

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B&C.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B&C.

3.5.8 Duty cycle

Please refer to Appendix D.



3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Oct. 07, 2025~ Dec. 01, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 25, 2024	Oct. 07, 2025~ Dec. 01, 2025	Dec. 24, 2025	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 14, 2024	Oct. 07, 2025~ Dec. 01, 2025	Oct. 13, 2025	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 13, 2025		Oct. 12, 2026	Conducted (TH01-SZ)
Attenuator	Woken Tech	WK0602-10	4	10dB	Jan. 13, 2025	Oct. 07, 2025~ Dec. 01, 2025	Jan. 12, 2026	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY544500 83	20Hz~8.4GHz	Apr. 02, 2025	Nov. 08, 2025~ Dec. 16, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
EXA Signal Analyzer	KEYSIGHT	N9010B	MY590711 91	10KHz-44GHz	Apr. 02, 2025	Nov. 08, 2025~ Dec. 16, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Nov. 08, 2025~ Dec. 16, 2025	Dec. 27, 2025	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz-2GHz	Aug. 19, 2025	Nov. 08, 2025~ Dec. 16, 2025	Aug. 18, 2026	Radiation (03CH03-SZ)
Double Ridge Guide Antenna	ETS-Lindgren	Burgeon-3117	00240107	1GHz~18GHz	Jul. 13, 2025	Nov. 08, 2025~ Dec. 16, 2025	Jul. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-H G	1871923	18GHz~40GHz	Jul. 03, 2025	Nov. 08, 2025~ Dec. 16, 2025	Jul. 02, 2026	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03, 2025	Nov. 08, 2025~ Dec. 16, 2025	Apr. 02, 2027	Radiation (03CH03-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz ~3000MHz	Apr. 02, 2025	Nov. 08, 2025~ Dec. 16, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101 800-30-10P-R	1943528	1GHz~18GHz	Oct. 13, 2025	Nov. 08, 2025~ Dec. 16, 2025	Oct. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	Keysight	83017A	MY532703 57	500MHz~26.5G Hz	Apr. 02, 2025	Nov. 08, 2025~ Dec. 16, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002 729	N/A	Oct. 17, 2025	Nov. 08, 2025~ Dec. 16, 2025	Oct. 16, 2026	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 08, 2025~ Dec. 16, 2025	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 08, 2025~ Dec. 16, 2025	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Conducted Power Spectral Density	± 1.32 dB
Frequency	± 1.3 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

----- THE END -----



Appendix A. Conducted Test Results

LoRa-DTS-Spreading Factor 7

Test Engineer:	Sam Zheng	Temperature:	20~26	°C
Test Date:	2025/10/07~2025/12/1	Relative Humidity:	40~51	%

TEST RESULTS DATA						
6dB and 99% Occupied Bandwidth						
Mod.	Channel	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
SF7	1	902.5MHz	0.48	0.60	0.50	Pass
SF7	16	914.5MHz	0.51	0.63	0.50	Pass
SF7	31	926.5MHz	0.51	0.62	0.50	Pass

TEST RESULTS DATA										
Average Power Table										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF7	1	902.5MHz	0.24	19.70	22.00	30.00	1.45	21.15	36.00	Pass
SF7	16	914.5MHz	0.24	19.60	22.00	30.00	1.45	21.05	36.00	Pass
SF7	31	926.5MHz	0.24	19.60	22.00	30.00	1.45	21.05	36.00	Pass

TEST RESULTS DATA							
Power Density							
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	AVG PSD (dBm /3kHz)	DG (dBi)	AVG PSD Limit (dBm /3kHz)	Pass/Fail
SF7	1	902.5MHz	0.24	3.49	1.45	8.00	Pass
SF7	16	914.5MHz	0.24	0.87	1.45	8.00	Pass
SF7	31	926.5MHz	0.24	0.78	1.45	8.00	Pass

LoRa-DTS-Spreading Factor 8

Test Engineer:	Sam Zheng	Temperature:	20~26	°C
Test Date:	2025/10/07~2025/12/1	Relative Humidity:	40~51	%

TEST RESULTS DATA Average Power Table										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF8	1	902.5MHz	0.15	19.60	22.00	30.00	1.45	21.05	36.00	Pass
SF8	16	914.5MHz	0.15	19.50	22.00	30.00	1.45	20.95	36.00	Pass
SF8	31	926.5MHz	0.15	19.50	22.00	30.00	1.45	20.95	36.00	Pass

LoRa-DTS-Spreading Factor 9

Test Engineer:	Sam Zheng	Temperature:	20~26	°C
Test Date:	2025/10/07~2025/12/1	Relative Humidity:	40~51	%

TEST RESULTS DATA Average Power Table										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF9	1	902.5MHz	0.08	19.60	22.00	30.00	1.45	21.05	36.00	Pass
SF9	16	914.5MHz	0.08	19.50	22.00	30.00	1.45	20.95	36.00	Pass
SF9	31	926.5MHz	0.08	19.40	22.00	30.00	1.45	20.85	36.00	Pass

LoRa-DTS-Spreading Factor 10

Test Engineer:	Sam Zheng	Temperature:	20~26	°C
Test Date:	2025/10/07~2025/11/10	Relative Humidity:	40~51	%

TEST RESULTS DATA Average Power Table										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF10	1	902.5MHz	0.05	19.60	22.00	30.00	1.45	21.05	36.00	Pass
SF10	16	914.5MHz	0.05	19.50	22.00	30.00	1.45	20.95	36.00	Pass
SF10	31	926.5MHz	0.05	19.50	22.00	30.00	1.45	20.95	36.00	Pass

LoRa-DTS-Spreading Factor 11

Test Engineer:	Sam Zheng	Temperature:	20~26	°C
Test Date:	2025/10/07~2025/12/1	Relative Humidity:	40~51	%

TEST RESULTS DATA						
6dB and 99% Occupied Bandwidth						
Mod.	Channel	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
SF11	1	902.5Mhz	0.52	0.64	0.50	Pass
SF11	16	914.5Mhz	0.53	0.65	0.50	Pass
SF11	31	926.5MHz	0.52	0.65	0.50	Pass

TEST RESULTS DATA										
Average Power Table										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF11	1	902.5Mhz	0.00	19.80	22.00	30.00	1.45	21.25	36.00	Pass
SF11	16	914.5MHz	0.00	19.70	22.00	30.00	1.45	21.15	36.00	Pass
SF11	31	926.5MHz	0.00	19.60	22.00	30.00	1.45	21.05	36.00	Pass

TEST RESULTS DATA							
Power Density							
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	AVG PSD (dBm /3kHz)	DG (dBi)	AVG PSD Limit (dBm /3kHz)	Pass/Fail
SF11	1	902.5Mhz	0.00	1.92	1.45	8.00	Pass
SF11	16	914.5MHz	0.00	-0.08	1.45	8.00	Pass
SF11	31	926.5MHz	0.00	0.11	1.45	8.00	Pass



Appendix B. Radiated Spurious Emission

LoRa DTS SF=7(Harmonic @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
902.5MHz		1805	41.34	-39.26	80.6	61.97	30.63	6.64	57.9	-	-	P	H
		2707.5	47.67	-26.33	74	64.62	32.28	8.61	57.84	215	221	P	H
		2707.5	36.68	-17.32	54	53.63	32.28	8.61	57.84	215	221	A	H
		3610	43.4	-30.6	74	58.81	32.93	9.66	58	-	-	P	H
		8122.5	50.17	-23.83	74	61.66	35.84	11.93	59.26	124	245	P	H
		8122.5	40.88	-13.12	54	52.37	35.84	11.93	59.26	124	245	A	H
		1805	49.47	-30.3	79.77	70.1	30.63	6.64	57.9	-	-	P	V
		2707.5	46.7	-27.3	74	63.65	32.28	8.61	57.84	251	224	P	V
		2707.5	35.68	-18.32	54	52.63	32.28	8.61	57.84	251	224	A	V
		3610	43.69	-30.31	74	59.1	32.93	9.66	58	-	-	P	V
		8122.5	49.17	-24.83	74	60.66	35.84	11.93	59.26	124	263	P	V
		8122.5	40.13	-13.87	54	51.62	35.84	11.93	59.26	124	263	A	V
914.5MHz		1829	43.23	-37.22	80.45	63.64	30.77	6.72	57.9	-	-	P	H
		2743.5	47.65	-26.35	74	64.63	32.25	8.62	57.85	132	224	P	H
		2743.5	36.64	-17.36	54	53.62	32.25	8.62	57.85	132	224	A	H
		3658	42.57	-31.43	74	57.93	33	9.64	58	-	-	P	H
		8230.5	50.38	-23.62	74	61.66	35.8	12.03	59.11	124	215	P	H
		8230.5	41.35	-12.65	54	52.63	35.8	12.03	59.11	124	215	A	H
		1829	51.71	-28.03	79.74	72.12	30.77	6.72	57.9	-	-	P	V
		2743.5	46.67	-27.33	74	63.65	32.25	8.62	57.85	224	325	P	V
		2743.5	35.64	-18.36	54	52.62	32.25	8.62	57.85	224	325	A	V
		3658	42.97	-31.03	74	58.33	33	9.64	58	-	-	P	V
		8230.5	49.18	-24.82	74	60.46	35.8	12.03	59.11	132	52	P	V
		8230.5	40.37	-13.63	54	51.65	35.8	12.03	59.11	132	52	A	V
926.5MHz		1853	49.61	-28.8	78.41	69.81	30.9	6.8	57.9	-	-	P	H
		2779.5	46.64	-27.36	74	63.65	32.22	8.63	57.86	125	325	P	H
		2779.5	36.23	-17.77	54	53.24	32.22	8.63	57.86	125	325	A	H
		3706	43.26	-30.74	74	58.55	33.1	9.61	58	-	-	P	H
		8338.5	50.53	-23.47	74	61.66	35.8	12.06	58.99	255	304	P	H



		8338.5	41.44	-12.56	54	52.57	35.8	12.06	58.99	255	304	A	H
		1853	57.35	-20.4	77.75	77.55	30.9	6.8	57.9	-	-	P	V
		2779.5	46.64	-27.36	74	63.65	32.22	8.63	57.86	132	241	P	V
		2779.5	35.62	-18.38	54	52.63	32.22	8.63	57.86	132	241	A	V
		3706	42.89	-31.11	74	58.18	33.1	9.61	58	-	-	P	V
		8338.5	49.5	-24.5	74	60.63	35.8	12.06	58.99	125	325	P	V
		8338.5	40.53	-13.47	54	51.66	35.8	12.06	58.99	125	325	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

LoRa DTS SF=11(Harmonic @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		1805	43.37	-36.34	79.71	64	30.63	6.64	57.9	-	-	P	H
		2707.5	47.71	-26.29	74	64.66	32.28	8.61	57.84	132	256	P	H
		2707.5	36.68	-17.32	54	53.63	32.28	8.61	57.84	132	256	A	H
		3610	42.83	-31.17	74	58.24	32.93	9.66	58	-	-	P	H
		8122.5	50.17	-23.83	74	61.66	35.84	11.93	59.26	245	214	P	H
		8122.5	41.14	-12.86	54	52.63	35.84	11.93	59.26	245	214	A	H
		1805	50.92	-28.47	79.39	71.55	30.63	6.64	57.9	-	-	P	V
		2707.5	46.71	-27.29	74	63.66	32.28	8.61	57.84	214	251	P	V
		2707.5	35.68	-18.32	54	52.63	32.28	8.61	57.84	214	251	A	V
		3610	43.25	-30.75	74	58.66	32.93	9.66	58	-	-	P	V
		8122.5	49.17	-24.83	74	60.66	35.84	11.93	59.26	132	52	P	V
		8122.5	40.14	-13.86	54	51.63	35.84	11.93	59.26	132	52	A	V
914.5MHz		1829	48.22	-31.38	79.6	68.63	30.77	6.72	57.9	-	-	P	H
		2743.5	47.67	-26.33	74	64.65	32.25	8.62	57.85	225	324	P	H
		2743.5	36.64	-17.36	54	53.62	32.25	8.62	57.85	225	324	A	H
		3658	43.08	-30.92	74	58.44	33	9.64	58	-	-	P	H
		8230.5	50.05	-23.95	74	61.33	35.8	12.03	59.11	124	125	P	H
		8230.5	42.25	-11.75	54	53.53	35.8	12.03	59.11	124	125	A	H
		1829	55.42	-23.94	79.36	75.83	30.77	6.72	57.9	-	-	P	V
		2743.5	46.67	-27.33	74	63.65	32.25	8.62	57.85	124	200	P	V



		2743.5	35.65	-18.35	54	52.63	32.25	8.62	57.85	124	200	A	V
		3658	42.39	-31.61	74	57.75	33	9.64	58	-	-	P	V
		8230.5	49.37	-24.63	74	60.65	35.8	12.03	59.11	124	52	P	V
		8230.5	40.34	-13.66	54	51.62	35.8	12.03	59.11	124	52	A	V
926.5MHz		1853	46.84	-33.07	79.91	67.04	30.9	6.8	57.9	-	-	P	H
		2779.5	47.31	-26.69	74	64.32	32.22	8.63	57.86	122	241	P	H
		2779.5	34.95	-19.05	54	51.96	32.22	8.63	57.86	122	241	A	H
		3706	43.29	-30.71	74	58.58	33.1	9.61	58	-	-	P	H
		8338.5	50.2	-23.8	74	61.33	35.8	12.06	58.99	124	210	P	H
		8338.5	41.56	-12.44	54	52.69	35.8	12.06	58.99	124	210	A	H
		1853	54.17	-24.31	78.48	74.37	30.9	6.8	57.9	-	-	P	V
		2779.5	46.23	-27.77	74	63.24	32.22	8.63	57.86	125	324	P	V
		2779.5	34.25	-19.75	54	51.26	32.22	8.63	57.86	125	324	A	V
		3706	42.68	-31.32	74	57.97	33.1	9.61	58	-	-	P	V
		8338.5	49.53	-24.47	74	60.66	35.8	12.06	58.99	124	236	P	V
		8338.5	40.94	-13.06	54	52.07	35.8	12.06	58.99	124	236	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



<30Mhz-1G>

LoRa DTS SF=7(LF @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		125.06	21.4	-22.1	43.5	35.58	16.38	1.14	31.7	-	-	P	H
		272.5	24.36	-21.64	46	35.37	18.83	1.72	31.56	-	-	P	H
	*	902.5	110.6	----	----	109.3	29.14	3.16	31	-	-	P	H
		126.03	21.1	-22.4	43.5	35.26	16.39	1.15	31.7	-	-	P	V
		280.26	24.5	-21.5	46	35.37	18.93	1.74	31.54	-	-	P	V
	*	902.5	109.77	----	----	108.47	29.14	3.16	31	-	-	P	V
914.5MHz		135.73	21.58	-21.92	43.5	36.22	18.01	2.25	34.9	-	-	P	H
		278.32	23.65	-22.35	46	36.59	18.68	3.12	34.74	-	-	P	H
	*	914.5	110.45	----	----	110.66	29.34	4.45	34	-	-	P	H
		137.67	20.77	-22.73	43.5	35.28	18.13	2.26	34.9	-	-	P	V
		282.2	23.79	-22.21	46	36.59	18.8	3.14	34.74	-	-	P	V
	*	914.5	109.74	----	----	109.95	29.34	4.45	34	-	-	P	V
926.5MHz		129.91	21.5	-22	43.5	35.58	16.46	1.16	31.7	-	-	P	H
		250.19	23.86	-22.14	46	35.28	18.53	1.65	31.6	-	-	P	H
	*	926.5	108.41	----	----	106.32	29.84	3.2	30.95	-	-	P	H
		135.73	20.83	-22.67	43.5	34.77	16.57	1.19	31.7	-	-	P	V
		285.11	24.28	-21.72	46	35.06	18.99	1.76	31.53	-	-	P	V
	*	926.5	107.75	----	----	105.66	29.84	3.2	30.95	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



LoRa DTS SF=11(LF @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		131.85	21.84	-21.66	43.5	35.87	16.5	1.17	31.7	-	-	P	H
		282.2	25.05	-20.95	46	35.88	18.96	1.75	31.54	-	-	P	H
	*	902.5	109.71	----	----	108.41	29.14	3.16	31	-	-	P	H
		127	21.92	-21.58	43.5	36.06	16.41	1.15	31.7	-	-	P	V
		253.1	24.6	-21.4	46	35.96	18.57	1.66	31.59	-	-	P	V
	*	902.5	109.39	----	----	108.09	29.14	3.16	31	-	-	P	V
914.5MHz		137.67	21.54	-21.96	43.5	36.05	18.13	2.26	34.9	-	-	P	H
		283.17	23.19	-22.81	46	35.96	18.83	3.14	34.74	-	-	P	H
	*	914.5	109.6	----	----	109.81	29.34	4.45	34	-	-	P	H
		136.7	21.63	-21.87	43.5	36.21	18.07	2.25	34.9	-	-	P	V
		284.14	22.93	-23.07	46	35.65	18.86	3.15	34.73	-	-	P	V
	*	914.5	109.39	----	----	109.6	29.34	4.45	34	-	-	P	V
926.5MHz		130.88	21.32	-22.18	43.5	35.37	16.48	1.17	31.7	-	-	P	H
		285.11	24.79	-21.21	46	35.57	18.99	1.76	31.53	-	-	P	H
	*	926.5	109.91	----	----	107.82	29.84	3.2	30.95	-	-	P	H
		127.97	21.43	-22.07	43.5	35.54	16.43	1.16	31.7	-	-	P	V
		258.92	24.64	-21.36	46	35.89	18.65	1.68	31.58	-	-	P	V
	*	926.5	108.48	----	----	106.39	29.84	3.2	30.95	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Appendix C. Radiated Spurious Emission Plots



LoRa 500KHz DTS SF=7 (Harmonic @ 3m)

LoRa	Harmonic @ 3m																																																																																																																																																	
ANT	LoRa 500KHz DTS SF=7 CH01 902.5 MHz																																																																																																																																																	
	Horizontal	Vertical																																																																																																																																																
Peak	Data: 1 Level (dBuV/m) Frequency (MHz) <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1805.00</td><td>41.34</td><td>61.97</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td></tr><tr><td>2</td><td>2707.50</td><td>47.67</td><td>-26.33</td><td>74.00</td><td>64.62</td><td>32.28</td><td>8.61 57.84 215 221 Peak</td></tr><tr><td>3</td><td>2707.50</td><td>36.68</td><td>-17.32</td><td>54.00</td><td>53.63</td><td>32.28</td><td>8.61 57.84 215 221 Average</td></tr><tr><td>4</td><td>3610.00</td><td>43.40</td><td>-30.60</td><td>74.00</td><td>58.81</td><td>32.93</td><td>9.66 58.00 --- Peak</td></tr><tr><td>5</td><td>8122.50</td><td>50.17</td><td>-23.83</td><td>74.00</td><td>61.66</td><td>35.84</td><td>11.93 59.26 124 245 Peak</td></tr><tr><td>6</td><td>8122.50</td><td>40.88</td><td>-13.12</td><td>54.00</td><td>52.37</td><td>35.84</td><td>11.93 59.26 124 245 Average</td></tr></table>	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg	1	1805.00	41.34	61.97	30.63	6.64	57.90	---	2	2707.50	47.67	-26.33	74.00	64.62	32.28	8.61 57.84 215 221 Peak	3	2707.50	36.68	-17.32	54.00	53.63	32.28	8.61 57.84 215 221 Average	4	3610.00	43.40	-30.60	74.00	58.81	32.93	9.66 58.00 --- Peak	5	8122.50	50.17	-23.83	74.00	61.66	35.84	11.93 59.26 124 245 Peak	6	8122.50	40.88	-13.12	54.00	52.37	35.84	11.93 59.26 124 245 Average	Data: 2 Level (dBuV/m) Frequency (MHz) <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1805.00</td><td>49.47</td><td>70.10</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td></tr><tr><td>2</td><td>2707.50</td><td>46.70</td><td>-27.30</td><td>74.00</td><td>63.65</td><td>32.28</td><td>8.61 57.84 251 224 Peak</td></tr><tr><td>3</td><td>2707.50</td><td>35.68</td><td>-18.32</td><td>54.00</td><td>52.63</td><td>32.28</td><td>8.61 57.84 251 224 Average</td></tr><tr><td>4</td><td>3610.00</td><td>43.69</td><td>-30.31</td><td>74.00</td><td>59.10</td><td>32.93</td><td>9.66 58.00 --- Peak</td></tr><tr><td>5</td><td>8122.50</td><td>49.17</td><td>-24.83</td><td>74.00</td><td>60.66</td><td>35.84</td><td>11.93 59.26 124 263 Peak</td></tr><tr><td>6</td><td>8122.50</td><td>40.13</td><td>-13.87</td><td>54.00</td><td>51.62</td><td>35.84</td><td>11.93 59.26 124 263 Average</td></tr></table>	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg	1	1805.00	49.47	70.10	30.63	6.64	57.90	---	2	2707.50	46.70	-27.30	74.00	63.65	32.28	8.61 57.84 251 224 Peak	3	2707.50	35.68	-18.32	54.00	52.63	32.28	8.61 57.84 251 224 Average	4	3610.00	43.69	-30.31	74.00	59.10	32.93	9.66 58.00 --- Peak	5	8122.50	49.17	-24.83	74.00	60.66	35.84	11.93 59.26 124 263 Peak	6	8122.50	40.13	-13.87	54.00	51.62	35.84	11.93 59.26 124 263 Average
	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																										
Freq	Level	Line	Level	Factor	Loss	Factor																																																																																																																																												
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																																																																																																											
1	1805.00	41.34	61.97	30.63	6.64	57.90	---																																																																																																																																											
2	2707.50	47.67	-26.33	74.00	64.62	32.28	8.61 57.84 215 221 Peak																																																																																																																																											
3	2707.50	36.68	-17.32	54.00	53.63	32.28	8.61 57.84 215 221 Average																																																																																																																																											
4	3610.00	43.40	-30.60	74.00	58.81	32.93	9.66 58.00 --- Peak																																																																																																																																											
5	8122.50	50.17	-23.83	74.00	61.66	35.84	11.93 59.26 124 245 Peak																																																																																																																																											
6	8122.50	40.88	-13.12	54.00	52.37	35.84	11.93 59.26 124 245 Average																																																																																																																																											
Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																											
Freq	Level	Line	Level	Factor	Loss	Factor																																																																																																																																												
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																																																																																																											
1	1805.00	49.47	70.10	30.63	6.64	57.90	---																																																																																																																																											
2	2707.50	46.70	-27.30	74.00	63.65	32.28	8.61 57.84 251 224 Peak																																																																																																																																											
3	2707.50	35.68	-18.32	54.00	52.63	32.28	8.61 57.84 251 224 Average																																																																																																																																											
4	3610.00	43.69	-30.31	74.00	59.10	32.93	9.66 58.00 --- Peak																																																																																																																																											
5	8122.50	49.17	-24.83	74.00	60.66	35.84	11.93 59.26 124 263 Peak																																																																																																																																											
6	8122.50	40.13	-13.87	54.00	51.62	35.84	11.93 59.26 124 263 Average																																																																																																																																											





LoRa	Harmonic @ 3m																																																																																																																																																																																																				
ANT	LoRa 500KHz DTS SF=7 CH16 914.5 MHz																																																																																																																																																																																																				
	Horizontal																																																																																																																																																																																																				
	Vertical																																																																																																																																																																																																				
Peak	Date: 1 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>1829.00</td><td>43.23</td><td>-----</td><td>63.64</td><td>30.77</td><td>6.72</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2743.50</td><td>47.65</td><td>-26.35</td><td>74.00</td><td>64.63</td><td>32.25</td><td>8.62</td><td>57.85</td><td>132</td><td>224</td><td>Peak</td></tr><tr><td>3</td><td>2743.50</td><td>36.64</td><td>-17.36</td><td>54.00</td><td>53.62</td><td>32.25</td><td>8.62</td><td>57.85</td><td>132</td><td>224</td><td>Average</td></tr><tr><td>4</td><td>3658.00</td><td>42.57</td><td>-31.43</td><td>74.00</td><td>57.93</td><td>33.00</td><td>9.64</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8230.50</td><td>50.30</td><td>-23.62</td><td>74.00</td><td>61.66</td><td>35.80</td><td>12.03</td><td>59.11</td><td>124</td><td>215</td><td>Peak</td></tr><tr><td>6</td><td>8230.50</td><td>41.35</td><td>-12.65</td><td>54.00</td><td>52.63</td><td>35.80</td><td>12.03</td><td>59.11</td><td>124</td><td>215</td><td>Average</td></tr></table> Date: 2 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>1829.00</td><td>51.71</td><td>-----</td><td>72.12</td><td>30.77</td><td>6.72</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2743.50</td><td>46.67</td><td>-27.33</td><td>74.00</td><td>63.65</td><td>32.25</td><td>8.62</td><td>57.85</td><td>224</td><td>325</td><td>Peak</td></tr><tr><td>3</td><td>2743.50</td><td>35.64</td><td>-18.36</td><td>54.00</td><td>52.62</td><td>32.25</td><td>8.62</td><td>57.85</td><td>224</td><td>325</td><td>Average</td></tr><tr><td>4</td><td>3658.00</td><td>42.97</td><td>-31.03</td><td>74.00</td><td>58.33</td><td>33.00</td><td>9.64</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8230.50</td><td>49.18</td><td>-24.82</td><td>74.00</td><td>60.46</td><td>35.80</td><td>12.03</td><td>59.11</td><td>132</td><td>52</td><td>Peak</td></tr><tr><td>6</td><td>8230.50</td><td>40.37</td><td>-13.63</td><td>54.00</td><td>51.65</td><td>35.80</td><td>12.03</td><td>59.11</td><td>132</td><td>52</td><td>Average</td></tr></table>												Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	1	1829.00	43.23	-----	63.64	30.77	6.72	57.90	---	---	Peak	2	2743.50	47.65	-26.35	74.00	64.63	32.25	8.62	57.85	132	224	Peak	3	2743.50	36.64	-17.36	54.00	53.62	32.25	8.62	57.85	132	224	Average	4	3658.00	42.57	-31.43	74.00	57.93	33.00	9.64	58.00	---	---	Peak	5	8230.50	50.30	-23.62	74.00	61.66	35.80	12.03	59.11	124	215	Peak	6	8230.50	41.35	-12.65	54.00	52.63	35.80	12.03	59.11	124	215	Average		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	1	1829.00	51.71	-----	72.12	30.77	6.72	57.90	---	---	Peak	2	2743.50	46.67	-27.33	74.00	63.65	32.25	8.62	57.85	224	325	Peak	3	2743.50	35.64	-18.36	54.00	52.62	32.25	8.62	57.85	224	325	Average	4	3658.00	42.97	-31.03	74.00	58.33	33.00	9.64	58.00	---	---	Peak	5	8230.50	49.18	-24.82	74.00	60.46	35.80	12.03	59.11	132	52	Peak	6	8230.50	40.37	-13.63	54.00	51.65	35.80	12.03	59.11	132	52	Average
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																													
	Freq	Level	Line	Level	Factor	Loss																																																																																																																																																																																															
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm																																																																																																																																																																																														
	1	1829.00	43.23	-----	63.64	30.77	6.72	57.90	---	---	Peak																																																																																																																																																																																										
	2	2743.50	47.65	-26.35	74.00	64.63	32.25	8.62	57.85	132	224	Peak																																																																																																																																																																																									
	3	2743.50	36.64	-17.36	54.00	53.62	32.25	8.62	57.85	132	224	Average																																																																																																																																																																																									
4	3658.00	42.57	-31.43	74.00	57.93	33.00	9.64	58.00	---	---	Peak																																																																																																																																																																																										
5	8230.50	50.30	-23.62	74.00	61.66	35.80	12.03	59.11	124	215	Peak																																																																																																																																																																																										
6	8230.50	41.35	-12.65	54.00	52.63	35.80	12.03	59.11	124	215	Average																																																																																																																																																																																										
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																														
Freq	Level	Line	Level	Factor	Loss																																																																																																																																																																																																
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm																																																																																																																																																																																															
1	1829.00	51.71	-----	72.12	30.77	6.72	57.90	---	---	Peak																																																																																																																																																																																											
2	2743.50	46.67	-27.33	74.00	63.65	32.25	8.62	57.85	224	325	Peak																																																																																																																																																																																										
3	2743.50	35.64	-18.36	54.00	52.62	32.25	8.62	57.85	224	325	Average																																																																																																																																																																																										
4	3658.00	42.97	-31.03	74.00	58.33	33.00	9.64	58.00	---	---	Peak																																																																																																																																																																																										
5	8230.50	49.18	-24.82	74.00	60.46	35.80	12.03	59.11	132	52	Peak																																																																																																																																																																																										
6	8230.50	40.37	-13.63	54.00	51.65	35.80	12.03	59.11	132	52	Average																																																																																																																																																																																										





LoRa	Harmonic @ 3m																																																																																																																																																																																																					
ANT	LoRa 500KHz DTS SF=7 CH31 926.5 MHz																																																																																																																																																																																																					
	Horizontal					Vertical																																																																																																																																																																																																
Peak	Date: 1  Level (dBuV/m) Frequency (MHz) <table><tr><th>Peak</th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1853.00</td><td>49.61</td><td>-----</td><td>-----</td><td>69.81</td><td>30.90</td><td>6.80</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2779.50</td><td>46.64</td><td>-27.36</td><td>74.00</td><td>63.65</td><td>32.22</td><td>8.63</td><td>57.86</td><td>125</td><td>325</td><td>Peak</td></tr><tr><td>3</td><td>2779.50</td><td>36.23</td><td>-17.77</td><td>54.00</td><td>53.24</td><td>32.22</td><td>8.63</td><td>57.86</td><td>125</td><td>325</td><td>Average</td></tr><tr><td>4</td><td>3786.00</td><td>43.26</td><td>-30.74</td><td>74.00</td><td>58.55</td><td>33.10</td><td>9.61</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8338.50</td><td>58.53</td><td>-23.47</td><td>74.00</td><td>61.66</td><td>35.80</td><td>12.06</td><td>58.99</td><td>255</td><td>304</td><td>Peak</td></tr><tr><td>6</td><td>8338.50</td><td>41.44</td><td>-12.56</td><td>54.00</td><td>52.57</td><td>35.80</td><td>12.06</td><td>58.99</td><td>255</td><td>304</td><td>Average</td></tr></table>					Peak	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	1	1853.00	49.61	-----	-----	69.81	30.90	6.80	57.90	---	---	Peak	2	2779.50	46.64	-27.36	74.00	63.65	32.22	8.63	57.86	125	325	Peak	3	2779.50	36.23	-17.77	54.00	53.24	32.22	8.63	57.86	125	325	Average	4	3786.00	43.26	-30.74	74.00	58.55	33.10	9.61	58.00	---	---	Peak	5	8338.50	58.53	-23.47	74.00	61.66	35.80	12.06	58.99	255	304	Peak	6	8338.50	41.44	-12.56	54.00	52.57	35.80	12.06	58.99	255	304	Average	Date: 2  Level (dBuV/m) Frequency (MHz) <table><tr><th>Peak</th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1853.00</td><td>57.35</td><td>-----</td><td>-----</td><td>77.55</td><td>30.90</td><td>6.80</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2779.50</td><td>46.64</td><td>-27.36</td><td>74.00</td><td>63.65</td><td>32.22</td><td>8.63</td><td>57.86</td><td>132</td><td>241</td><td>Peak</td></tr><tr><td>3</td><td>2779.50</td><td>35.62</td><td>-18.38</td><td>54.00</td><td>52.63</td><td>32.22</td><td>8.63</td><td>57.86</td><td>132</td><td>241</td><td>Average</td></tr><tr><td>4</td><td>3786.00</td><td>42.89</td><td>-31.11</td><td>74.00</td><td>58.18</td><td>33.10</td><td>9.61</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8338.50</td><td>49.50</td><td>-24.50</td><td>74.00</td><td>68.63</td><td>35.80</td><td>12.06</td><td>58.99</td><td>125</td><td>325</td><td>Peak</td></tr><tr><td>6</td><td>8338.50</td><td>40.53</td><td>-13.47</td><td>54.00</td><td>51.66</td><td>35.80</td><td>12.06</td><td>58.99</td><td>125</td><td>325</td><td>Average</td></tr></table>					Peak	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg	1	1853.00	57.35	-----	-----	77.55	30.90	6.80	57.90	---	---	Peak	2	2779.50	46.64	-27.36	74.00	63.65	32.22	8.63	57.86	132	241	Peak	3	2779.50	35.62	-18.38	54.00	52.63	32.22	8.63	57.86	132	241	Average	4	3786.00	42.89	-31.11	74.00	58.18	33.10	9.61	58.00	---	---	Peak	5	8338.50	49.50	-24.50	74.00	68.63	35.80	12.06	58.99	125	325	Peak	6	8338.50	40.53	-13.47	54.00	51.66	35.80	12.06	58.99	125	325	Average
	Peak	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																											
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																																																																																											
	1	1853.00	49.61	-----	-----	69.81	30.90	6.80	57.90	---	---	Peak																																																																																																																																																																																										
	2	2779.50	46.64	-27.36	74.00	63.65	32.22	8.63	57.86	125	325	Peak																																																																																																																																																																																										
	3	2779.50	36.23	-17.77	54.00	53.24	32.22	8.63	57.86	125	325	Average																																																																																																																																																																																										
	4	3786.00	43.26	-30.74	74.00	58.55	33.10	9.61	58.00	---	---	Peak																																																																																																																																																																																										
5	8338.50	58.53	-23.47	74.00	61.66	35.80	12.06	58.99	255	304	Peak																																																																																																																																																																																											
6	8338.50	41.44	-12.56	54.00	52.57	35.80	12.06	58.99	255	304	Average																																																																																																																																																																																											
Peak	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																												
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																																																																																												
1	1853.00	57.35	-----	-----	77.55	30.90	6.80	57.90	---	---	Peak																																																																																																																																																																																											
2	2779.50	46.64	-27.36	74.00	63.65	32.22	8.63	57.86	132	241	Peak																																																																																																																																																																																											
3	2779.50	35.62	-18.38	54.00	52.63	32.22	8.63	57.86	132	241	Average																																																																																																																																																																																											
4	3786.00	42.89	-31.11	74.00	58.18	33.10	9.61	58.00	---	---	Peak																																																																																																																																																																																											
5	8338.50	49.50	-24.50	74.00	68.63	35.80	12.06	58.99	125	325	Peak																																																																																																																																																																																											
6	8338.50	40.53	-13.47	54.00	51.66	35.80	12.06	58.99	125	325	Average																																																																																																																																																																																											





LoRa 500KHz DTS SF=11 (Harmonic @ 3m)

LoRa	Harmonic @ 3m																																																																																																																																																																			
ANT	LoRa 500KHz DTS SF=11 CH01 902.5 MHz																																																																																																																																																																			
	Horizontal	Vertical																																																																																																																																																																		
Peak	Data: 1 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1805.00</td><td>43.37</td><td>74.00</td><td>64.00</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td></tr><tr><td>2</td><td>2707.50</td><td>47.71</td><td>74.00</td><td>64.66</td><td>32.28</td><td>8.61</td><td>57.84</td><td>132</td></tr><tr><td>3</td><td>2707.50</td><td>36.68</td><td>74.00</td><td>53.63</td><td>32.28</td><td>8.61</td><td>57.84</td><td>132</td></tr><tr><td>4</td><td>3610.00</td><td>42.83</td><td>74.00</td><td>58.24</td><td>32.93</td><td>9.66</td><td>58.00</td><td>---</td></tr><tr><td>5</td><td>8122.50</td><td>50.17</td><td>74.00</td><td>61.66</td><td>35.84</td><td>11.93</td><td>59.26</td><td>245</td></tr><tr><td>6</td><td>8122.50</td><td>41.14</td><td>74.00</td><td>52.63</td><td>35.84</td><td>11.93</td><td>59.26</td><td>245</td></tr></table>		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level	Factor	Loss				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	1805.00	43.37	74.00	64.00	30.63	6.64	57.90	---	2	2707.50	47.71	74.00	64.66	32.28	8.61	57.84	132	3	2707.50	36.68	74.00	53.63	32.28	8.61	57.84	132	4	3610.00	42.83	74.00	58.24	32.93	9.66	58.00	---	5	8122.50	50.17	74.00	61.66	35.84	11.93	59.26	245	6	8122.50	41.14	74.00	52.63	35.84	11.93	59.26	245	Data: 2 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1805.00</td><td>50.92</td><td>74.00</td><td>71.55</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td></tr><tr><td>2</td><td>2707.50</td><td>46.71</td><td>74.00</td><td>63.66</td><td>32.28</td><td>8.61</td><td>57.84</td><td>214</td></tr><tr><td>3</td><td>2707.50</td><td>35.68</td><td>74.00</td><td>52.63</td><td>32.28</td><td>8.61</td><td>57.84</td><td>214</td></tr><tr><td>4</td><td>3610.00</td><td>43.25</td><td>74.00</td><td>58.66</td><td>32.93</td><td>9.66</td><td>58.00</td><td>---</td></tr><tr><td>5</td><td>8122.50</td><td>49.17</td><td>74.00</td><td>60.66</td><td>35.84</td><td>11.93</td><td>59.26</td><td>132</td></tr><tr><td>6</td><td>8122.50</td><td>40.14</td><td>74.00</td><td>51.63</td><td>35.84</td><td>11.93</td><td>59.26</td><td>132</td></tr></table>		Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level	Factor	Loss				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	1805.00	50.92	74.00	71.55	30.63	6.64	57.90	---	2	2707.50	46.71	74.00	63.66	32.28	8.61	57.84	214	3	2707.50	35.68	74.00	52.63	32.28	8.61	57.84	214	4	3610.00	43.25	74.00	58.66	32.93	9.66	58.00	---	5	8122.50	49.17	74.00	60.66	35.84	11.93	59.26	132	6	8122.50	40.14	74.00	51.63	35.84	11.93	59.26	132
	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																												
	Freq	Level	Line	Level	Factor	Loss																																																																																																																																																														
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																												
1	1805.00	43.37	74.00	64.00	30.63	6.64	57.90	---																																																																																																																																																												
2	2707.50	47.71	74.00	64.66	32.28	8.61	57.84	132																																																																																																																																																												
3	2707.50	36.68	74.00	53.63	32.28	8.61	57.84	132																																																																																																																																																												
4	3610.00	42.83	74.00	58.24	32.93	9.66	58.00	---																																																																																																																																																												
5	8122.50	50.17	74.00	61.66	35.84	11.93	59.26	245																																																																																																																																																												
6	8122.50	41.14	74.00	52.63	35.84	11.93	59.26	245																																																																																																																																																												
	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																												
	Freq	Level	Line	Level	Factor	Loss																																																																																																																																																														
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																												
1	1805.00	50.92	74.00	71.55	30.63	6.64	57.90	---																																																																																																																																																												
2	2707.50	46.71	74.00	63.66	32.28	8.61	57.84	214																																																																																																																																																												
3	2707.50	35.68	74.00	52.63	32.28	8.61	57.84	214																																																																																																																																																												
4	3610.00	43.25	74.00	58.66	32.93	9.66	58.00	---																																																																																																																																																												
5	8122.50	49.17	74.00	60.66	35.84	11.93	59.26	132																																																																																																																																																												
6	8122.50	40.14	74.00	51.63	35.84	11.93	59.26	132																																																																																																																																																												



LoRa	Harmonic @ 3m																																																																																																																																																															
ANT	LoRa 500KHz DTS SF=11 CH16 914.5 MHz																																																																																																																																																															
	Horizontal																																																																																																																																																															
	Vertical																																																																																																																																																															
Peak	Date: 1  <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>1829.00</td><td>48.22</td><td>-----</td><td>68.63</td><td>30.77</td><td>6.72</td><td>57.90 --- --- Peak</td></tr><tr><td>2</td><td>2743.50</td><td>47.67</td><td>-26.33</td><td>74.00</td><td>64.65</td><td>32.25</td><td>8.62 57.85 225 324 Peak</td></tr><tr><td>3</td><td>2743.50</td><td>36.64</td><td>-17.36</td><td>54.00</td><td>53.62</td><td>32.25</td><td>8.62 57.85 225 324 Average</td></tr><tr><td>4</td><td>3658.00</td><td>43.08</td><td>-38.92</td><td>74.00</td><td>58.44</td><td>33.00</td><td>9.64 58.00 --- --- Peak</td></tr><tr><td>5</td><td>8238.50</td><td>50.05</td><td>-23.95</td><td>74.00</td><td>61.33</td><td>35.80</td><td>12.03 59.11 124 125 Peak</td></tr><tr><td>6</td><td>8238.50</td><td>42.25</td><td>-11.75</td><td>54.00</td><td>53.53</td><td>35.80</td><td>12.03 59.11 124 125 Average</td></tr></table>											Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	deg	1	1829.00	48.22	-----	68.63	30.77	6.72	57.90 --- --- Peak	2	2743.50	47.67	-26.33	74.00	64.65	32.25	8.62 57.85 225 324 Peak	3	2743.50	36.64	-17.36	54.00	53.62	32.25	8.62 57.85 225 324 Average	4	3658.00	43.08	-38.92	74.00	58.44	33.00	9.64 58.00 --- --- Peak	5	8238.50	50.05	-23.95	74.00	61.33	35.80	12.03 59.11 124 125 Peak	6	8238.50	42.25	-11.75	54.00	53.53	35.80	12.03 59.11 124 125 Average	Date: 2  <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>1829.00</td><td>55.42</td><td>-----</td><td>75.83</td><td>30.77</td><td>6.72</td><td>57.90 --- --- Peak</td></tr><tr><td>2</td><td>2743.50</td><td>46.67</td><td>-27.33</td><td>74.00</td><td>63.65</td><td>32.25</td><td>8.62 57.85 124 208 Peak</td></tr><tr><td>3</td><td>2743.50</td><td>35.65</td><td>-18.35</td><td>54.00</td><td>52.63</td><td>32.25</td><td>8.62 57.85 124 208 Average</td></tr><tr><td>4</td><td>3658.00</td><td>42.39</td><td>-31.61</td><td>74.00</td><td>57.75</td><td>33.00</td><td>9.64 58.00 --- --- Peak</td></tr><tr><td>5</td><td>8238.50</td><td>49.37</td><td>-24.63</td><td>74.00</td><td>60.65</td><td>35.80</td><td>12.03 59.11 124 52 Peak</td></tr><tr><td>6</td><td>8238.50</td><td>40.34</td><td>-13.66</td><td>54.00</td><td>51.62</td><td>35.80</td><td>12.03 59.11 124 52 Average</td></tr></table>											Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	deg	1	1829.00	55.42	-----	75.83	30.77	6.72	57.90 --- --- Peak	2	2743.50	46.67	-27.33	74.00	63.65	32.25	8.62 57.85 124 208 Peak	3	2743.50	35.65	-18.35	54.00	52.63	32.25	8.62 57.85 124 208 Average	4	3658.00	42.39	-31.61	74.00	57.75	33.00	9.64 58.00 --- --- Peak	5	8238.50	49.37	-24.63	74.00	60.65	35.80	12.03 59.11 124 52 Peak	6	8238.50	40.34	-13.66	54.00	51.62	35.80	12.03 59.11 124 52 Average
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																								
	Freq	Level	Line	Level	Factor	Loss																																																																																																																																																										
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	deg																																																																																																																																																									
	1	1829.00	48.22	-----	68.63	30.77	6.72	57.90 --- --- Peak																																																																																																																																																								
	2	2743.50	47.67	-26.33	74.00	64.65	32.25	8.62 57.85 225 324 Peak																																																																																																																																																								
	3	2743.50	36.64	-17.36	54.00	53.62	32.25	8.62 57.85 225 324 Average																																																																																																																																																								
4	3658.00	43.08	-38.92	74.00	58.44	33.00	9.64 58.00 --- --- Peak																																																																																																																																																									
5	8238.50	50.05	-23.95	74.00	61.33	35.80	12.03 59.11 124 125 Peak																																																																																																																																																									
6	8238.50	42.25	-11.75	54.00	53.53	35.80	12.03 59.11 124 125 Average																																																																																																																																																									
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																									
Freq	Level	Line	Level	Factor	Loss																																																																																																																																																											
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	deg																																																																																																																																																										
1	1829.00	55.42	-----	75.83	30.77	6.72	57.90 --- --- Peak																																																																																																																																																									
2	2743.50	46.67	-27.33	74.00	63.65	32.25	8.62 57.85 124 208 Peak																																																																																																																																																									
3	2743.50	35.65	-18.35	54.00	52.63	32.25	8.62 57.85 124 208 Average																																																																																																																																																									
4	3658.00	42.39	-31.61	74.00	57.75	33.00	9.64 58.00 --- --- Peak																																																																																																																																																									
5	8238.50	49.37	-24.63	74.00	60.65	35.80	12.03 59.11 124 52 Peak																																																																																																																																																									
6	8238.50	40.34	-13.66	54.00	51.62	35.80	12.03 59.11 124 52 Average																																																																																																																																																									





LoRa	Harmonic @ 3m																																																																																																																																																																																																	
ANT	LoRa 500KHz DTS SF=11 CH31 926.5 MHz																																																																																																																																																																																																	
	Horizontal						Vertical																																																																																																																																																																																											
Peak	Date: 1  <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1853.00</td><td>46.84</td><td>-----</td><td>67.04</td><td>30.90</td><td>6.80</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2779.50</td><td>47.31</td><td>-26.69</td><td>74.00</td><td>64.32</td><td>32.22</td><td>8.63</td><td>57.86</td><td>122</td><td>241 Peak</td></tr><tr><td>3</td><td>2779.50</td><td>34.95</td><td>-19.05</td><td>54.00</td><td>51.96</td><td>32.22</td><td>8.63</td><td>57.86</td><td>122</td><td>241 Average</td></tr><tr><td>4</td><td>3706.00</td><td>43.29</td><td>-30.71</td><td>74.00</td><td>58.58</td><td>33.10</td><td>9.61</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8338.50</td><td>50.20</td><td>-23.80</td><td>74.00</td><td>61.33</td><td>35.00</td><td>12.06</td><td>58.99</td><td>124</td><td>210 Peak</td></tr><tr><td>6</td><td>8338.50</td><td>41.56</td><td>-12.44</td><td>54.00</td><td>52.69</td><td>35.00</td><td>12.06</td><td>58.99</td><td>124</td><td>210 Average</td></tr></table>							Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	1853.00	46.84	-----	67.04	30.90	6.80	57.90	---	---	Peak	2	2779.50	47.31	-26.69	74.00	64.32	32.22	8.63	57.86	122	241 Peak	3	2779.50	34.95	-19.05	54.00	51.96	32.22	8.63	57.86	122	241 Average	4	3706.00	43.29	-30.71	74.00	58.58	33.10	9.61	58.00	---	---	Peak	5	8338.50	50.20	-23.80	74.00	61.33	35.00	12.06	58.99	124	210 Peak	6	8338.50	41.56	-12.44	54.00	52.69	35.00	12.06	58.99	124	210 Average	Date: 2  <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>1853.00</td><td>54.17</td><td>-----</td><td>74.37</td><td>30.90</td><td>6.80</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2779.50</td><td>46.23</td><td>-27.77</td><td>74.00</td><td>63.24</td><td>32.22</td><td>8.63</td><td>57.86</td><td>125</td><td>324 Peak</td></tr><tr><td>3</td><td>2779.50</td><td>34.25</td><td>-19.75</td><td>54.00</td><td>51.26</td><td>32.22</td><td>8.63</td><td>57.86</td><td>125</td><td>324 Average</td></tr><tr><td>4</td><td>3706.00</td><td>42.68</td><td>-31.32</td><td>74.00</td><td>57.97</td><td>33.10</td><td>9.61</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8338.50</td><td>49.53</td><td>-24.47</td><td>74.00</td><td>60.66</td><td>35.00</td><td>12.06</td><td>58.99</td><td>124</td><td>236 Peak</td></tr><tr><td>6</td><td>8338.50</td><td>40.94</td><td>-13.06</td><td>54.00</td><td>52.07</td><td>35.00</td><td>12.06</td><td>58.99</td><td>124</td><td>236 Average</td></tr></table>							Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	1853.00	54.17	-----	74.37	30.90	6.80	57.90	---	---	Peak	2	2779.50	46.23	-27.77	74.00	63.24	32.22	8.63	57.86	125	324 Peak	3	2779.50	34.25	-19.75	54.00	51.26	32.22	8.63	57.86	125	324 Average	4	3706.00	42.68	-31.32	74.00	57.97	33.10	9.61	58.00	---	---	Peak	5	8338.50	49.53	-24.47	74.00	60.66	35.00	12.06	58.99	124	236 Peak	6	8338.50	40.94	-13.06	54.00	52.07	35.00	12.06	58.99	124	236 Average
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																										
	Freq	Level	Line	Level Factor	Loss Factor																																																																																																																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																																										
	1	1853.00	46.84	-----	67.04	30.90	6.80	57.90	---	---	Peak																																																																																																																																																																																							
	2	2779.50	47.31	-26.69	74.00	64.32	32.22	8.63	57.86	122	241 Peak																																																																																																																																																																																							
	3	2779.50	34.95	-19.05	54.00	51.96	32.22	8.63	57.86	122	241 Average																																																																																																																																																																																							
4	3706.00	43.29	-30.71	74.00	58.58	33.10	9.61	58.00	---	---	Peak																																																																																																																																																																																							
5	8338.50	50.20	-23.80	74.00	61.33	35.00	12.06	58.99	124	210 Peak																																																																																																																																																																																								
6	8338.50	41.56	-12.44	54.00	52.69	35.00	12.06	58.99	124	210 Average																																																																																																																																																																																								
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																											
Freq	Level	Line	Level Factor	Loss Factor																																																																																																																																																																																														
MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																																											
1	1853.00	54.17	-----	74.37	30.90	6.80	57.90	---	---	Peak																																																																																																																																																																																								
2	2779.50	46.23	-27.77	74.00	63.24	32.22	8.63	57.86	125	324 Peak																																																																																																																																																																																								
3	2779.50	34.25	-19.75	54.00	51.26	32.22	8.63	57.86	125	324 Average																																																																																																																																																																																								
4	3706.00	42.68	-31.32	74.00	57.97	33.10	9.61	58.00	---	---	Peak																																																																																																																																																																																							
5	8338.50	49.53	-24.47	74.00	60.66	35.00	12.06	58.99	124	236 Peak																																																																																																																																																																																								
6	8338.50	40.94	-13.06	54.00	52.07	35.00	12.06	58.99	124	236 Average																																																																																																																																																																																								



<30Mhz-1G>
LoRa 500KHz DTS SF=7 (LF @ 3m)

LoRa	LF @ 3m																																																																																																																																																					
ANT	LoRa 500KHz DTS SF=7 CH01 902.5MHz																																																																																																																																																					
	Horizontal										Vertical																																																																																																																																											
Peak	Data: 1 Level (dBuV/m) PAR: MC_LORA <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>125.86</td><td>21.48</td><td>-22.10</td><td>43.58</td><td>35.58</td><td>16.38</td><td>1.14</td><td>31.70</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>272.58</td><td>24.36</td><td>-21.64</td><td>46.00</td><td>35.37</td><td>18.83</td><td>1.72</td><td>31.56</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>902.58</td><td>110.68</td><td>-----</td><td>-----</td><td>109.38</td><td>29.14</td><td>3.16</td><td>31.80</td><td>---</td><td>Peak</td></tr></table>																					Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	125.86	21.48	-22.10	43.58	35.58	16.38	1.14	31.70	---	Peak	2	272.58	24.36	-21.64	46.00	35.37	18.83	1.72	31.56	---	Peak	3	902.58	110.68	-----	-----	109.38	29.14	3.16	31.80	---	Peak	Data: 2 Level (dBuV/m) PAR: MC_LORA <table><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>126.83</td><td>21.10</td><td>-22.48</td><td>43.58</td><td>35.26</td><td>16.39</td><td>1.15</td><td>31.70</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>288.26</td><td>24.58</td><td>-21.58</td><td>46.00</td><td>35.37</td><td>18.93</td><td>1.74</td><td>31.54</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>902.58</td><td>109.77</td><td>-----</td><td>-----</td><td>108.47</td><td>29.14</td><td>3.16</td><td>31.80</td><td>---</td><td>Peak</td></tr></table>																					Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg		1	126.83	21.10	-22.48	43.58	35.26	16.39	1.15	31.70	---	Peak	2	288.26	24.58	-21.58	46.00	35.37	18.93	1.74	31.54	---	Peak	3	902.58	109.77	-----	-----	108.47	29.14	3.16	31.80	---	Peak
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																											
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																																												
	1	125.86	21.48	-22.10	43.58	35.58	16.38	1.14	31.70	---	Peak																																																																																																																																											
2	272.58	24.36	-21.64	46.00	35.37	18.83	1.72	31.56	---	Peak																																																																																																																																												
3	902.58	110.68	-----	-----	109.38	29.14	3.16	31.80	---	Peak																																																																																																																																												
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																												
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	dB	cm	deg																																																																																																																																													
1	126.83	21.10	-22.48	43.58	35.26	16.39	1.15	31.70	---	Peak																																																																																																																																												
2	288.26	24.58	-21.58	46.00	35.37	18.93	1.74	31.54	---	Peak																																																																																																																																												
3	902.58	109.77	-----	-----	108.47	29.14	3.16	31.80	---	Peak																																																																																																																																												



LoRa	LF @ 3m																																																																																																	
ANT	LoRa 500KHz DTS SF=7 CH16 914.5MHz																																																																																																	
	Horizontal	Vertical																																																																																																
Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>135.730</td><td>21.58</td><td>-21.92</td><td>43.50</td><td>36.22</td><td>18.01</td><td>2.25 34.90 --- --- Peak</td></tr><tr><td>2</td><td>278.320</td><td>23.65</td><td>-22.35</td><td>46.00</td><td>36.59</td><td>18.68</td><td>3.12 34.74 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>110.45</td><td>---</td><td>---</td><td>110.66</td><td>29.34</td><td>4.45 34.00 --- --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	1	135.730	21.58	-21.92	43.50	36.22	18.01	2.25 34.90 --- --- Peak	2	278.320	23.65	-22.35	46.00	36.59	18.68	3.12 34.74 --- --- Peak	3	914.500	110.45	---	---	110.66	29.34	4.45 34.00 --- --- Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th></tr><tr><td>1</td><td>137.670</td><td>20.77</td><td>-22.73</td><td>43.50</td><td>35.28</td><td>18.13</td><td>2.26 34.90 --- --- Peak</td></tr><tr><td>2</td><td>282.200</td><td>23.79</td><td>-22.21</td><td>46.00</td><td>36.59</td><td>18.80</td><td>3.14 34.74 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>109.74</td><td>---</td><td>---</td><td>109.95</td><td>29.34</td><td>4.45 34.00 --- --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	1	137.670	20.77	-22.73	43.50	35.28	18.13	2.26 34.90 --- --- Peak	2	282.200	23.79	-22.21	46.00	36.59	18.80	3.14 34.74 --- --- Peak	3	914.500	109.74	---	---	109.95	29.34	4.45 34.00 --- --- Peak
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																											
	Freq	Level	Line	Level	Factor	Loss	Factor																																																																																											
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB																																																																																											
1	135.730	21.58	-21.92	43.50	36.22	18.01	2.25 34.90 --- --- Peak																																																																																											
2	278.320	23.65	-22.35	46.00	36.59	18.68	3.12 34.74 --- --- Peak																																																																																											
3	914.500	110.45	---	---	110.66	29.34	4.45 34.00 --- --- Peak																																																																																											
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																											
	Freq	Level	Line	Level	Factor	Loss	Factor																																																																																											
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB																																																																																											
1	137.670	20.77	-22.73	43.50	35.28	18.13	2.26 34.90 --- --- Peak																																																																																											
2	282.200	23.79	-22.21	46.00	36.59	18.80	3.14 34.74 --- --- Peak																																																																																											
3	914.500	109.74	---	---	109.95	29.34	4.45 34.00 --- --- Peak																																																																																											





LoRa	LF @ 3m																																																																																																																																				
ANT	LoRa 500KHz DTS SF=7 CH31 926.5 MHz																																																																																																																																				
	Horizontal																																																																																																																																				
	Vertical																																																																																																																																				
Peak	Data: 1 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>129.91</td><td>21.58</td><td>-22.80</td><td>43.58</td><td>35.58</td><td>16.46</td><td>1.16</td><td>31.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>258.19</td><td>23.86</td><td>-22.14</td><td>46.00</td><td>35.28</td><td>18.53</td><td>1.65</td><td>31.60</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>926.58</td><td>108.41</td><td>-----</td><td>-----</td><td>106.32</td><td>29.84</td><td>3.20</td><td>38.95</td><td>---</td><td>---</td><td>Peak</td></tr></table> Data: 2 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>135.73</td><td>20.83</td><td>-22.67</td><td>43.58</td><td>34.77</td><td>16.57</td><td>1.19</td><td>31.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>285.11</td><td>24.28</td><td>-21.72</td><td>46.00</td><td>35.86</td><td>18.99</td><td>1.76</td><td>31.53</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>926.58</td><td>107.75</td><td>-----</td><td>-----</td><td>105.66</td><td>29.84</td><td>3.20</td><td>38.95</td><td>---</td><td>---</td><td>Peak</td></tr></table>												Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Level Factor	Loss Factor			MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	129.91	21.58	-22.80	43.58	35.58	16.46	1.16	31.70	---	---	Peak	2	258.19	23.86	-22.14	46.00	35.28	18.53	1.65	31.60	---	---	Peak	3	926.58	108.41	-----	-----	106.32	29.84	3.20	38.95	---	---	Peak		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Limit	Line	Level Factor	Loss Factor			MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	135.73	20.83	-22.67	43.58	34.77	16.57	1.19	31.70	---	---	Peak	2	285.11	24.28	-21.72	46.00	35.86	18.99	1.76	31.53	---	---	Peak	3	926.58	107.75	-----	-----	105.66	29.84	3.20	38.95	---	---	Peak
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																													
	Freq	Level	Limit	Line	Level Factor	Loss Factor																																																																																																																															
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																												
1	129.91	21.58	-22.80	43.58	35.58	16.46	1.16	31.70	---	---	Peak																																																																																																																										
2	258.19	23.86	-22.14	46.00	35.28	18.53	1.65	31.60	---	---	Peak																																																																																																																										
3	926.58	108.41	-----	-----	106.32	29.84	3.20	38.95	---	---	Peak																																																																																																																										
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																														
Freq	Level	Limit	Line	Level Factor	Loss Factor																																																																																																																																
MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																													
1	135.73	20.83	-22.67	43.58	34.77	16.57	1.19	31.70	---	---	Peak																																																																																																																										
2	285.11	24.28	-21.72	46.00	35.86	18.99	1.76	31.53	---	---	Peak																																																																																																																										
3	926.58	107.75	-----	-----	105.66	29.84	3.20	38.95	---	---	Peak																																																																																																																										





LoRa 500KHz DTS SF=11 (LF @ 3m)

LoRa	LF @ 3m																																																																																																	
ANT	LoRa 500KHz DTS SF=11 CH01 902.5 MHz																																																																																																	
	Horizontal	Vertical																																																																																																
Peak	Data: 1 Level (dBuV/m) Frequency (MHz) PAR: 0.00, LORA <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>131.85</td><td>21.84</td><td>-21.66</td><td>43.58</td><td>35.87</td><td>16.50</td><td>1.17 31.70 --- --- Peak</td></tr><tr><td>2</td><td>282.28</td><td>25.05</td><td>-20.95</td><td>46.00</td><td>35.88</td><td>18.96</td><td>1.75 31.54 --- --- Peak</td></tr><tr><td>3</td><td>902.50</td><td>109.71</td><td>-----</td><td>108.41</td><td>29.14</td><td>3.16</td><td>31.00 --- --- Peak</td></tr></table>	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg	1	131.85	21.84	-21.66	43.58	35.87	16.50	1.17 31.70 --- --- Peak	2	282.28	25.05	-20.95	46.00	35.88	18.96	1.75 31.54 --- --- Peak	3	902.50	109.71	-----	108.41	29.14	3.16	31.00 --- --- Peak	Data: 2 Level (dBuV/m) Frequency (MHz) PAR: 0.00, LORA <table><tr><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>127.00</td><td>21.92</td><td>-21.58</td><td>43.58</td><td>36.06</td><td>16.41</td><td>1.15 31.70 --- --- Peak</td></tr><tr><td>2</td><td>253.10</td><td>24.60</td><td>-21.40</td><td>46.00</td><td>35.96</td><td>18.57</td><td>1.66 31.59 --- --- Peak</td></tr><tr><td>3</td><td>902.50</td><td>109.39</td><td>-----</td><td>108.09</td><td>29.14</td><td>3.16</td><td>31.00 --- --- Peak</td></tr></table>	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level	Factor	Loss	Factor		MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg	1	127.00	21.92	-21.58	43.58	36.06	16.41	1.15 31.70 --- --- Peak	2	253.10	24.60	-21.40	46.00	35.96	18.57	1.66 31.59 --- --- Peak	3	902.50	109.39	-----	108.09	29.14	3.16	31.00 --- --- Peak
Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																											
Freq	Level	Line	Level	Factor	Loss	Factor																																																																																												
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																																																											
1	131.85	21.84	-21.66	43.58	35.87	16.50	1.17 31.70 --- --- Peak																																																																																											
2	282.28	25.05	-20.95	46.00	35.88	18.96	1.75 31.54 --- --- Peak																																																																																											
3	902.50	109.71	-----	108.41	29.14	3.16	31.00 --- --- Peak																																																																																											
Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																											
Freq	Level	Line	Level	Factor	Loss	Factor																																																																																												
MHz	dBuV/m	dB	dBuV/m	dB	dB	cm	deg																																																																																											
1	127.00	21.92	-21.58	43.58	36.06	16.41	1.15 31.70 --- --- Peak																																																																																											
2	253.10	24.60	-21.40	46.00	35.96	18.57	1.66 31.59 --- --- Peak																																																																																											
3	902.50	109.39	-----	108.09	29.14	3.16	31.00 --- --- Peak																																																																																											



LoRa	LF @ 3m																																																																																																	
ANT	LoRa 500KHz DTS SF=11 CH16 914.5 MHz																																																																																																	
	Horizontal	Vertical																																																																																																
Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>137.670</td><td>21.54</td><td>-21.96</td><td>43.50</td><td>36.05</td><td>18.13</td><td>2.26 34.90 --- --- Peak</td></tr><tr><td>2</td><td>283.170</td><td>23.19</td><td>-22.81</td><td>46.00</td><td>35.96</td><td>18.83</td><td>3.14 34.74 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>109.60</td><td>---</td><td>---</td><td>109.81</td><td>29.34</td><td>4.45 34.00 --- --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	deg	1	137.670	21.54	-21.96	43.50	36.05	18.13	2.26 34.90 --- --- Peak	2	283.170	23.19	-22.81	46.00	35.96	18.83	3.14 34.74 --- --- Peak	3	914.500	109.60	---	---	109.81	29.34	4.45 34.00 --- --- Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>136.700</td><td>21.63</td><td>-21.87</td><td>43.50</td><td>36.21</td><td>18.07</td><td>2.25 34.90 --- --- Peak</td></tr><tr><td>2</td><td>284.140</td><td>22.93</td><td>-23.07</td><td>46.00</td><td>35.65</td><td>18.86</td><td>3.15 34.73 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>109.39</td><td>---</td><td>---</td><td>109.60</td><td>29.34</td><td>4.45 34.00 --- --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	deg	1	136.700	21.63	-21.87	43.50	36.21	18.07	2.25 34.90 --- --- Peak	2	284.140	22.93	-23.07	46.00	35.65	18.86	3.15 34.73 --- --- Peak	3	914.500	109.39	---	---	109.60	29.34	4.45 34.00 --- --- Peak
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																											
	Freq	Level	Line	Level Factor	Loss Factor																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	deg																																																																																											
1	137.670	21.54	-21.96	43.50	36.05	18.13	2.26 34.90 --- --- Peak																																																																																											
2	283.170	23.19	-22.81	46.00	35.96	18.83	3.14 34.74 --- --- Peak																																																																																											
3	914.500	109.60	---	---	109.81	29.34	4.45 34.00 --- --- Peak																																																																																											
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																											
	Freq	Level	Line	Level Factor	Loss Factor																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	deg																																																																																											
1	136.700	21.63	-21.87	43.50	36.21	18.07	2.25 34.90 --- --- Peak																																																																																											
2	284.140	22.93	-23.07	46.00	35.65	18.86	3.15 34.73 --- --- Peak																																																																																											
3	914.500	109.39	---	---	109.60	29.34	4.45 34.00 --- --- Peak																																																																																											




LoRa	LF @ 3m																																																																																																											
ANT	LoRa 500KHz DTS SF=11 CH31 926.5 MHz																																																																																																											
	Horizontal	Vertical																																																																																																										
Peak	Date: 1 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>138.88</td><td>21.32</td><td>-22.18</td><td>43.58</td><td>35.37</td><td>16.48</td><td>1.17</td><td>31.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>285.11</td><td>24.79</td><td>-21.21</td><td>46.00</td><td>35.57</td><td>18.99</td><td>1.76</td><td>31.53</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>926.50</td><td>109.91</td><td>-----</td><td>107.82</td><td>29.84</td><td>3.20</td><td>38.95</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	1	138.88	21.32	-22.18	43.58	35.37	16.48	1.17	31.70	---	---	Peak	2	285.11	24.79	-21.21	46.00	35.57	18.99	1.76	31.53	---	---	Peak	3	926.50	109.91	-----	107.82	29.84	3.20	38.95	---	---	---	Peak	Date: 2 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>127.97</td><td>21.43</td><td>-22.07</td><td>43.58</td><td>35.54</td><td>16.43</td><td>1.16</td><td>31.70</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>258.92</td><td>24.64</td><td>-21.36</td><td>46.00</td><td>35.89</td><td>18.65</td><td>1.68</td><td>31.58</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>926.50</td><td>108.48</td><td>-----</td><td>106.39</td><td>29.84</td><td>3.20</td><td>38.95</td><td>---</td><td>---</td><td>---</td><td>Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg	1	127.97	21.43	-22.07	43.58	35.54	16.43	1.16	31.70	---	---	Peak	2	258.92	24.64	-21.36	46.00	35.89	18.65	1.68	31.58	---	---	Peak	3	926.50	108.48	-----	106.39	29.84	3.20	38.95	---	---	---	Peak
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																				
1	138.88	21.32	-22.18	43.58	35.37	16.48	1.17	31.70	---	---	Peak																																																																																																	
2	285.11	24.79	-21.21	46.00	35.57	18.99	1.76	31.53	---	---	Peak																																																																																																	
3	926.50	109.91	-----	107.82	29.84	3.20	38.95	---	---	---	Peak																																																																																																	
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																					
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																				
1	127.97	21.43	-22.07	43.58	35.54	16.43	1.16	31.70	---	---	Peak																																																																																																	
2	258.92	24.64	-21.36	46.00	35.89	18.65	1.68	31.58	---	---	Peak																																																																																																	
3	926.50	108.48	-----	106.39	29.84	3.20	38.95	---	---	---	Peak																																																																																																	



Appendix D. Duty Cycle Plots


Band	Duty Cycle (%)	VBW Setting (Hz)	Duty Factor (dB)
LoRa(DTS)SF7	94.56	100	0.24
LoRa(DTS)SF8	96.55	-	0.15
LoRa(DTS)SF9	98.13	-	0.08
LoRa(DTS)SF10	98.77	-	0.05
LoRa(DTS)SF11	100	10	0

LoRa(DTS)SF 7






LoRa(DTS)SF 8




LoRa(DTS)SF 9





LoRa(DTS)SF 10



LoRa(DTS)SF 11

