



FCC RF Test Report

APPLICANT : Ring LLC
EQUIPMENT : Environmental Alert Device
BRAND NAME : ring
MODEL NAME : 7AFYA6
FCC ID : 2AEUP-7AFYA6
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 02, 2025 ~ Dec. 15, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant	5
1.2 Product Feature of Equipment Under Test.....	5
1.3 Product Specification of Equipment Under Test.....	5
1.4 Modification of EUT	5
1.5 Testing Location	6
1.6 Test Software.....	6
1.7 Applicable Standards.....	6
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	7
2.1 Carrier Frequency Channel	7
2.2 Test Mode.....	8
2.3 Connection Diagram of Test System.....	9
2.4 EUT Operation Test Setup	9
2.5 Measurement Results Explanation Example.....	9
3 TEST RESULT	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	19
3.3 Power Spectral Density Measurement	20
3.4 Conducted Band Edges and Spurious Emission Measurement	29
3.5 Radiated Spurious Emission Measurement	38
3.6 AC Conducted Emission Measurement.....	42
3.7 Antenna Requirements.....	44
4 LIST OF MEASURING EQUIPMENT.....	45
5 UNCERTAINTY OF EVALUATION.....	46
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT	
APPENDIX C. RADIATED SPURIOUS EMISSION	
APPENDIX D. RADIATED SPURIOUS EMISSION PLOTS	
APPENDIX E. DUTY CYCLE PLOTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5N0309B	Rev. 01	Initial issue of report	Dec. 16, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Output Power	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm/3kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	$\leq 30\text{dBc}$	Pass	-
3.5	15.247(d)	Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 13.50 dB at 8122.50 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 20.48 dB at 0.444750 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Ring LLC

12515 Cerise Ave, Hawthorne, CA 90250, USA

1.2 Product Feature of Equipment Under Test

Product Feature	
Equipment	Environmental Alert Device
Brand Name	ring
Model Name	7AFYA6
FCC ID	2AEUP-7AFYA6
SN Code	N/A
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.3 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	902 MHz ~ 928 MHz
Number of Channels	31
Bandwidth / Spread Factor	500kHz / 7, 8, 9, 10, 11
Maximum Output Power to Antenna	LoRa DTS SF7 : 20.40 dBm (0.1096 W) LoRa DTS SF8 : 20.10 dBm (0.1023 W) LoRa DTS SF9 : 20.00 dBm (0.1000 W) LoRa DTS SF10 : 20.10 dBm (0.1023 W) LoRa DTS SF11 : 20.40 dBm (0.1096 W)
99% Occupied Bandwidth	LoRa DTS SF7 : 0.53 MHz LoRa DTS SF11 : 0.52 MHz
Antenna Type / Gain	PCB IFA antenna with gain 0.41 dBi
Type of Modulation	LoRa

Note: For SF7/8/9/10/11 mode, the bandwidth and modulation are the same, only the data rate is different, so the whole testing has assessed SF7/11 mode by referring to the higher conducted power.

1.4 Modification of EUT

No modifications are made to the EUT during all test items.

1.5 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH03-SZ CO02-SZ	CN1256	421272

1.6 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24
2.	CO02-SZ	R&S	EMC32	10.60.20

1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2020

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
902-928 MHz	1	902.5	17	915.3
	2	903.3	18	916.1
	3	904.1	19	916.9
	4	904.9	20	917.7
	5	905.7	21	918.5
	6	906.5	22	919.3
	7	907.3	23	920.1
	8	908.1	24	920.9
	9	908.9	25	921.7
	10	909.7	26	922.5
	11	910.5	27	923.3
	12	911.3	28	924.1
	13	912.1	29	924.9
	14	912.9	30	925.7
	15	913.7	31	926.5
	16	914.5	-	-

Note: The above EUT's information was declared by manufacturer.


2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Modulation
	Lora 500kHz DTS
Conducted TCs	Mode 1: LoRa Tx CH01_902.5 MHz Mode 2: LoRa Tx CH16_914.5 MHz Mode 3: LoRa Tx CH31_926.5 MHz
Radiated TCs	Mode 1: LoRa Tx CH01_902.5 MHz Mode 2: LoRa Tx CH16_914.5 MHz Mode 3: LoRa Tx CH31_926.5 MHz
AC Conducted Emission	Mode 1: Lora Tx + USB charging from adapter

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

For LoRa function, the engineering test program was provided and enabled to make EUT continuous transmit.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 0.3 dB and 20dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 0.3 + 20 = 20.3 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 11.8.1 for 6dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth (VBW) $\geq 3 \times \text{RBW}$. Detector = Peak. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) = 1%~5% of OBW and set the Video bandwidth (VBW) approximately three times the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup






3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.


For SF7:

6 dB Bandwidth Plot on 902.5 MHz



Date: 2.OCT.2025 13:40:33


6 dB Bandwidth Plot on 914.5 MHz



Date: 2.OCT.2025 14:15:13



6 dB Bandwidth Plot on 926.5 MHz




Date: 2.OCT.2025 14:39:04




For SF11:

6 dB Bandwidth Plot on 902.5MHz



Date: 2.OCT.2025 15:29:52


6 dB Bandwidth Plot on 914.5 MHz



Date: 2.OCT.2025 15:50:06



6 dB Bandwidth Plot on 926.5 MHz



Date: 2.OCT.2025 16:02:03




3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.


For SF7:

99% Bandwidth Plot on 902.5 MHz



Date: 1.DEC.2025 13:46:49


99% Occupied Bandwidth Plot on 914.5 MHz



Date: 1.DEC.2025 13:48:33



99% Occupied Bandwidth Plot on 926.5 MHz




Date: 1.DEC.2025 13:50:06




For SF11:

99% Bandwidth Plot on 902.5MHz



Date: 1.DEC.2025 13:53:24


99% Bandwidth Plot on 914.5 MHz



Date: 1.DEC.2025 13:52:22



99% Bandwidth Plot on 926.5 MHz



Date: 1.DEC.2025 13:51:27

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 902-928MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2020 clause 11.10.5 Method AVGPDS-2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = power averaging (rms), Sweep time = auto couple. Use the peak marker function to determine the maximum power level.
6. Employ trace averaging (rms) mode over a minimum of 100 traces.
7. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
8. Measure and record the results in the test report.
9. Add $[10 \log (1 / D)]$, where D is the duty cycle.
10. The Measured power density (dBm)/ 100kHz is a reference level and used as 30dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Please refer to Appendix A.




3.3.6 Test Result of Power Spectral Density Plots (100kHz)

For SF7:

PSD 100kHz Plot on 902.5 MHz




PSD 100kHz Plot on 914.5 MHz





PSD 100kHz Plot on 926.5 MHz




Date: 2.OCT.2025 14:40:36




For SF11:

PSD 100kHz Plot on 902.5 MHz




PSD 100kHz Plot on 914.5 MHz





PSD 100kHz Plot on 926.5 MHz




Date: 2.OCT.2025 16:03:59




3.3.7 Test Result of Power Spectral Density Plots (3kHz)

For SF7:

PSD 3kHz Plot on 902.5 MHz




PSD 3kHz Plot on 914.5 MHz





PSD 3kHz Plot on 926.5 MHz




Date: 2.OCT.2025 15:02:39




For SF11:

PSD 3kHz Plot on 902.5 MHz



Date: 2.OCT.2025 15:37:41


PSD 3kHz Plot on 914.5 MHz



Date: 2.OCT.2025 15:51:23



PSD 3kHz Plot on 926.5 MHz



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.


3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2020 clause 11.11.3
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 30 dB relative to the maximum in-band peak PSD level in 100 kHz when the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

For SF7:


Low Band Edge Plot on 902.5 MHz



Date: 9.OCT.2025 11:11:51

Note: F1= 902MHz

High Band Edge Plot on 926.5 MHz




Date: 2.OCT.2025 14:42:24

Note: F1= 928MHz




For SF11:

Low Band Edge Plot on 902.5 MHz



Note: F1= 902MHz

High Band Edge Plot on 926.5 MHz




Note: F1= 928MHz




3.4.6 Test Result of Conducted Spurious Emission Plots

For SF7:

Conducted Spurious Emission Plot on 902.5 MHz




Conducted Spurious Emission Plot on 902.5 MHz






Conducted Spurious Emission Plot on 914.5 MHz



Date: 2.OCT.2025 15:14:31


Conducted Spurious Emission Plot on 914.5 MHz



Date: 2.OCT.2025 15:13:40




Conducted Spurious Emission Plot on 926.5 MHz



Date: 2.OCT.2025 14:46:09

Conducted Spurious Emission Plot on 926.5 MHz




Date: 2.OCT.2025 14:45:27




For SF11:

Conducted Spurious Emission Plot on 902.5 MHz




Conducted Spurious Emission Plot on 902.5 MHz






Conducted Spurious Emission Plot on 914.5 MHz




Conducted Spurious Emission Plot on 914.5 MHz






Conducted Spurious Emission Plot on 926.5 MHz



Conducted Spurious Emission Plot on 926.5 MHz



3.5 Radiated Spurious Emission Measurement

3.5.1 Limit of Radiated Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C&D.

3.5.7 Duty cycle

Please refer to Appendix E.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Oct. 02, 2025~Dec. 01, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 25, 2024	Oct. 02, 2025~Dec. 01, 2025	Dec. 24, 2025	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 14, 2024	Oct. 02, 2025~Dec. 01, 2025	Oct. 13, 2025	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 13, 2025		Oct. 12, 2026	Conducted (TH01-SZ)
Attenuatore	Woken Tech	WK0602-10	4	10dB	Jan. 13, 2025	Oct. 02, 2025~Dec. 01, 2025	Jan. 12, 2026	Conducted (TH01-SZ)
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 02, 2025	Nov. 13, 2025~Dec. 03, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
EXA Signal Analyzer	KEYSIGHT	N9010B	MY59071191	10KHz~44GHz	Apr. 02, 2025	Nov. 13, 2025~Dec. 03, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Nov. 13, 2025~Dec. 03, 2025	Dec. 27, 2025	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 19, 2025	Nov. 13, 2025~Dec. 03, 2025	Aug. 18, 2026	Radiation (03CH03-SZ)
Double Ridge Guide Antenna	ETS-Lindgren	Burgeon-3117	00240107	1GHz~18GHz	Jul. 13, 2025	Nov. 13, 2025~Dec. 03, 2025	Jul. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Nov. 13, 2025~Dec. 03, 2025	Jul. 02, 2026	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz~40GHz	Apr. 03, 2025	Nov. 13, 2025~Dec. 03, 2025	Apr. 02, 2027	Radiation (03CH03-SZ)
Amplifier	EM Electronics	EM330	060756	0.01Hz~3000MHz	Apr. 02, 2025	Nov. 13, 2025~Dec. 03, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	AMF-7D-00101800-30-10P-R	1943528	1GHz~18GHz	Oct. 13, 2025	Nov. 13, 2025~Dec. 03, 2025	Oct. 12, 2026	Radiation (03CH03-SZ)
HF Amplifier	Keysight	83017A	MY53270357	500MHz~26.5GHz	Apr. 02, 2025	Nov. 13, 2025~Dec. 03, 2025	Apr. 01, 2026	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Oct. 17, 2025	Nov. 13, 2025~Dec. 03, 2025	Oct. 16, 2026	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 13, 2025~Dec. 03, 2025	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 13, 2025~Dec. 03, 2025	NCR	Radiation (03CH03-SZ)
EMI Receiver	R&S	ESR7	102297	9kHz~7GHz;	Jul. 02, 2025	Dec. 15, 2025	Jul. 01, 2026	Conduction (CO02-SZ)
AC LISN	R&S	ENV216	101499	9kHz~30MHz	Jul. 03, 2025	Dec. 15, 2025	Jul. 02, 2026	Conduction (CO02-SZ)
AC Power Source	CHROMA	61601	616010002470	100Vac~250Vac	Dec. 25, 2024	Dec. 15, 2025	Dec. 24, 2025	Conduction (CO02-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	± 1.34 dB
Occupied Channel Bandwidth	± 0.012 MHz
Conducted Power	± 1.34 dB
Conducted Power Spectral Density	± 1.32 dB
Frequency	± 1.3 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.5dB
---	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.9dB
---	-------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0dB
---	-------

----- THE END -----



Appendix A. Conducted Test Results

LoRa-DTS-Spreading Factor 7

Test Engineer:	Liu Qiu Qiu	Temperature:	20~26	°C
Test Date:	2025/10/2~2025/12/1	Relative Humidity:	40~51	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Channel	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
SF7	1	902.5MHz	0.49	0.61	0.50	Pass
SF7	16	914.5MHz	0.53	0.62	0.50	Pass
SF7	31	926.5MHz	0.52	0.64	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF7	1	902.5MHz	0.26	20.40	22.00	30.00	0.41	20.81	36.00	Pass
SF7	16	914.5MHz	0.26	20.20	22.00	30.00	0.41	20.61	36.00	Pass
SF7	31	926.5MHz	0.26	20.10	22.00	30.00	0.41	20.51	36.00	Pass

TEST RESULTS DATA
Power Density

Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	AVG PSD (dBm /3kHz)	DG (dBi)	AVG PSD Limit (dBm /3kHz)	Pass/Fail
SF7	1	902.5MHz	0.26	2.20	0.41	8.00	Pass
SF7	16	914.5MHz	0.26	0.59	0.41	8.00	Pass
SF7	31	926.5MHz	0.26	-0.04	0.41	8.00	Pass

LoRa-DTS-Spreading Factor 8

<u>TEST RESULTS DATA</u> <u>Average Power Table</u>										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF8	1	902.5MHz	0.14	20.10	22.00	30.00	0.41	20.51	36.00	Pass
SF8	16	914.5MHz	0.14	19.90	22.00	30.00	0.41	20.31	36.00	Pass
SF8	31	926.5MHz	0.14	19.80	22.00	30.00	0.41	20.21	36.00	Pass

LoRa-DTS-Spreading Factor 9

<u>TEST RESULTS DATA</u> <u>Average Power Table</u>										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF9	1	902.5MHz	0.08	20.00	22.00	30.00	0.41	20.41	36.00	Pass
SF9	16	914.5MHz	0.08	19.90	22.00	30.00	0.41	20.31	36.00	Pass
SF9	31	926.5MHz	0.08	19.80	22.00	30.00	0.41	20.21	36.00	Pass

LoRa-DTS-Spreading Factor 10

<u>TEST RESULTS DATA</u> <u>Average Power Table</u>										
Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF10	1	902.5MHz	0.03	20.10	22.00	30.00	0.41	20.51	36.00	Pass
SF10	16	914.5MHz	0.03	19.90	22.00	30.00	0.41	20.31	36.00	Pass
SF10	31	926.5MHz	0.03	19.80	22.00	30.00	0.41	20.21	36.00	Pass

LoRa-DTS-Spreading Factor 11**TEST RESULTS DATA****6dB and 99% Occupied Bandwidth**

Mod.	Channel	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
SF11	1	902.5Mhz	0.52	0.64	0.50	Pass
SF11	16	914.5Mhz	0.52	0.65	0.50	Pass
SF11	31	926.5MHz	0.52	0.65	0.50	Pass

TEST RESULTS DATA**Average Power Table**

Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
SF11	1	902.5Mhz	0.00	20.40	22.00	30.00	0.41	20.81	36.00	Pass
SF11	16	914.5MHz	0.00	20.30	22.00	30.00	0.41	20.71	36.00	Pass
SF11	31	926.5MHz	0.00	20.10	22.00	30.00	0.41	20.51	36.00	Pass

TEST RESULTS DATA**Power Density**


Mod.	Channel	Freq. (MHz)	Duty Factor (dB)	AVG PSD (dBm /3kHz)	DG (dBi)	AVG PSD Limit (dBm /3kHz)	Pass/Fail
SF11	1	902.5Mhz	0.00	0.80	0.41	8.00	Pass
SF11	16	914.5MHz	0.00	-0.68	0.41	8.00	Pass
SF11	31	926.5MHz	0.00	-0.40	0.41	8.00	Pass



Appendix B. AC Conducted Emission Test Results

Test Engineer :	XuRuibin	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Line


Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.163500	34.83	---	65.28	30.45	L1	OFF	19.8
0.163500	---	27.98	55.28	27.30	L1	OFF	19.8
0.209760	31.28	---	63.22	31.94	L1	OFF	19.7
0.209760	---	24.64	53.22	28.58	L1	OFF	19.7
0.444750	29.27	---	56.97	27.70	L1	OFF	19.7
0.444750	---	26.50	46.97	20.48	L1	OFF	19.7
0.587940	30.38	---	56.00	25.62	L1	OFF	19.7
0.587940	---	24.98	46.00	21.02	L1	OFF	19.7
5.126640	25.17	---	60.00	34.83	L1	OFF	19.9
5.126640	---	24.45	50.00	25.55	L1	OFF	19.9
19.218750	28.88	---	60.00	31.12	L1	OFF	20.2
19.218750	---	25.25	50.00	24.75	L1	OFF	20.2

Test Engineer :	XuRuibin	Temperature :	22~24°C
		Relative Humidity :	44~50%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.159000	35.63	---	65.52	29.89	N	OFF	19.8
0.159000	---	28.65	55.52	26.87	N	OFF	19.8
0.235500	32.29	---	62.25	29.96	N	OFF	19.7
0.235500	---	24.72	52.25	27.53	N	OFF	19.7
0.444300	29.92	---	56.98	27.06	N	OFF	19.7
0.444300	---	24.65	46.98	22.33	N	OFF	19.7
0.579750	30.07	---	56.00	25.93	N	OFF	19.7
0.579750	---	24.32	46.00	21.68	N	OFF	19.7
5.127360	25.25	---	60.00	34.75	N	OFF	19.8
5.127360	---	24.36	50.00	25.64	N	OFF	19.8
18.984750	30.05	---	60.00	29.95	N	OFF	20.3
18.984750	---	25.59	50.00	24.41	N	OFF	20.3



Appendix C. Radiated Spurious Emission

lor a DTS SF=7(Harmonic @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	Line (dBμV/m)	Level (dBμV)	Factor (dB/m)	Loss (dB)	Factor (dB)	Pos (cm)	Pos (deg)	Avg. (P/A)	(H/V)
902.5MHz		1805	49.7	-37.33	87.03	70.33	30.63	6.64	57.9	-	-	P	H
		2707.5	47.07	-26.93	74	64.02	32.28	8.61	57.84	124	-	P	H
		2707.5	35.71	-18.29	54	52.66	32.28	8.61	57.84	124	198	A	H
		3610	42.19	-31.81	74	57.6	32.93	9.66	58	-	-	P	H
		8122.5	49.78	-24.22	74	61.27	35.84	11.93	59.26	124	345	P	H
		8122.5	39.48	-14.52	54	50.97	35.84	11.93	59.26	124	345	P	H
		1805	48.91	-31.99	80.9	69.54	30.63	6.64	57.9	-	-	P	V
		2707.5	45.32	-28.68	74	62.27	32.28	8.61	57.84	278	62	P	V
		2707.5	33.48	-20.52	54	50.43	32.28	8.61	57.84	278	62	A	V
		3610	43.2	-30.8	74	58.61	32.93	9.66	58	-	-	P	V
		8122.5	49.17	-24.83	74	60.66	35.84	11.93	59.26	132	220	P	V
		8122.5	38.14	-15.86	54	49.63	35.84	11.93	59.26	132	220	P	V
914.5MHz		1829	48.02	-39.38	87.4	68.43	30.77	6.72	57.9	-	-	P	H
		2743.5	46.48	-27.52	74	63.46	32.25	8.62	57.85	132	256	P	H
		2743.5	34.67	-19.33	54	51.65	32.25	8.62	57.85	132	256	A	H
		3658	44	-30	74	59.36	33	9.64	58	-	-	P	H
		8230.5	49.68	-24.32	74	60.96	35.8	12.03	59.11	132	241	P	H
		8230.5	40.34	-13.66	54	51.62	35.8	12.03	59.11	132	241	P	H
		1829	44.52	-36.33	80.85	64.93	30.77	6.72	57.9	-	-	P	V
		2743.5	45.68	-28.32	74	62.66	32.25	8.62	57.85	123	224	P	V
		2743.5	34.64	-19.36	54	51.62	32.25	8.62	57.85	123	224	A	V
		3658	41.51	-32.49	74	56.87	33	9.64	58	-	-	P	V
		8230.5	49.37	-24.63	74	60.65	35.8	12.03	59.11	124	323	P	V
		8230.5	38.34	-15.66	54	49.62	35.8	12.03	59.11	124	323	P	V
926.5MHz		1853	44.22	-40.78	85	64.42	30.9	6.8	57.9	-	-	P	H
		2779.5	46.95	-27.05	74	63.96	32.22	8.63	57.86	346	215	P	H
		2779.5	34.61	-19.39	54	51.62	32.22	8.63	57.86	346	215	A	H
		3706	42.74	-31.26	74	58.03	33.1	9.61	58	-	-	P	H



		8338.5	49.83	-24.17	74	60.96	35.8	12.06	58.99	132	126	P	H
		8338.5	39.53	-14.47	54	50.66	35.8	12.06	58.99	132	126	P	H
		1853	44.39	-33.50	77.89	64.59	30.9	6.8	57.9	-	-	P	V
		2779.5	45.34	-28.66	74	62.35	32.22	8.63	57.86	123	262	P	V
		2779.5	34.61	-19.39	54	51.62	32.22	8.63	57.86	123	262	A	V
		3706	42.77	-31.23	74	58.06	33.1	9.61	58	-	-	P	V
		8338.5	48.53	-25.47	74	59.66	35.8	12.06	58.99	132	326	P	V
		8338.5	38.5	-15.5	54	49.63	35.8	12.06	58.99	132	326	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Iora DTS SF= 11(Harmonic @ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		1805	44.96	-42.43	87.39	65.59	30.63	6.64	57.9	-	-	P	H
		2707.5	47.02	-26.98	74	63.97	32.28	8.61	57.84	124	221	P	H
		2707.5	36.01	-17.99	54	52.96	32.28	8.61	57.84	124	221	A	H
		3610	42.49	-31.51	74	57.9	32.93	9.66	58	-	-	P	H
		8122.5	49.47	-24.53	74	60.96	35.84	11.93	59.26	132	224	P	H
		8122.5	40.5	-13.5	54	51.99	35.84	11.93	59.26	132	224	P	H
		1805	43.5	-37.42	80.92	64.13	30.63	6.64	57.9	-	-	P	V
		2707.5	45.98	-28.02	74	62.93	32.28	8.61	57.84	124	226	P	V
		2707.5	34.67	-19.33	54	51.62	32.28	8.61	57.84	124	226	A	V
		3610	42.36	-31.64	74	57.77	32.93	9.66	58	-	-	P	V
		8122.5	49.16	-24.84	74	60.65	35.84	11.93	59.26	241	59	P	V
		8122.5	39.78	-14.22	54	51.27	35.84	11.93	59.26	241	59	P	V
914.5MHz		1829	47.26	-40.13	87.39	67.67	30.77	6.72	57.9	-	-	P	H
		2743.5	46.64	-27.36	74	63.62	32.25	8.62	57.85	256	324	P	H
		2743.5	34.98	-19.02	54	51.96	32.25	8.62	57.85	256	324	A	H
		3658	42.26	-31.74	74	57.62	33	9.64	58	-	-	P	H
		8230.5	50.07	-23.93	74	61.35	35.8	12.03	59.11	124	223	P	H
		8230.5	39.37	-14.63	54	50.65	35.8	12.03	59.11	124	223	P	H
		1829	46.03	-34.55	80.58	66.44	30.77	6.72	57.9	-	-	A	V



		2743.5	45.67	-28.33	74	62.65	32.25	8.62	57.85	124	225	P	V
		2743.5	34.64	-19.36	54	51.62	32.25	8.62	57.85	124	225	A	V
		3658	41.64	-32.36	74	57	33	9.64	58	-	-	P	V
		8230.5	49.38	-24.62	74	60.66	35.8	12.03	59.11	198	76	P	V
		8230.5	38.34	-15.66	54	49.62	35.8	12.03	59.11	198	76	P	V
926.5MHz		1853	42.2	-43.86	86.06	62.4	30.9	6.8	57.9	-	-	P	H
		2779.5	46.64	-27.36	74	63.65	32.22	8.63	57.86	124	230	P	H
		2779.5	34.62	-19.38	54	51.63	32.22	8.63	57.86	124	230	A	H
		3706	42.01	-31.99	74	57.3	33.1	9.61	58	-	-	P	H
		8338.5	50.14	-23.86	74	61.27	35.8	12.06	58.99	124	198	P	H
		8338.5	39.83	-14.17	54	50.96	35.8	12.06	58.99	124	198	P	H
		1853	43.53	-33.52	77.05	63.73	30.9	6.8	57.9	-	-	P	V
		2779.5	45.61	-28.39	74	62.62	32.22	8.63	57.86	124	125	P	V
		2779.5	34.05	-19.95	54	51.06	32.22	8.63	57.86	124	125	A	V
		3706	42.57	-31.43	74	57.86	33.1	9.61	58	-	-	P	V
		8338.5	49.53	-24.47	74	60.66	35.8	12.06	58.99	224	114	P	V
		8338.5	39.5	-14.5	54	50.63	35.8	12.06	58.99	224	114	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



< 30M-1G>

Iora DTS SF=7 (LF@ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		136.7	16.95	-26.55	43.5	30.87	16.58	1.2	31.7	-	-	P	H
		280.26	21.01	-24.99	46	31.88	18.93	1.74	31.54	-	-	P	H
	*	870.99	40.05	-46.98	87.03	38.37	29	3.1	30.42	-	-	P	H
		902.5	117.03	---	---	115.73	29.14	3.16	31	-	-	P	H
		935.01	43.42	-43.61	87.03	41.05	30.09	3.21	30.93	-	-	P	H
		127	18.89	-24.61	43.5	33.03	16.41	1.15	31.7	-	-	P	V
		258.92	20.96	-25.04	46	32.21	18.65	1.68	31.58	-	-	P	V
	*	902.5	110.9	---	---	109.6	29.14	3.16	31	-	-	P	V
		935.01	40.18	-40.72	80.9	37.81	30.09	3.21	30.93	-	-	P	V
914.5MHz		134.76	22.45	-21.05	43.5	37.15	17.96	2.24	34.9	-	-	P	H
		279.29	23.4	-22.6	46	36.3	18.71	3.13	34.74	-	-	P	H
	*	914.5	117.4	---	---	117.61	29.34	4.45	34	-	-	P	H
		137.67	22.3	-21.2	43.5	36.81	18.13	2.26	34.9	-	-	P	V
		285.11	23.55	-22.45	46	36.23	18.9	3.15	34.73	-	-	P	V
	*	914.5	110.85	---	---	111.06	29.34	4.45	34	-	-	P	V
926.5MHz		131.85	17.63	-25.87	43.5	31.66	16.5	1.17	31.7	-	-	P	H
		262.8	20.52	-25.48	46	31.7	18.7	1.69	31.57	-	-	P	H
	*	894.27	43.66	-41.34	85	42.34	29.06	3.15	30.89	-	-	P	H
		926.5	115	---	---	112.91	29.84	3.2	30.95	-	-	P	H
		958.29	39.98	-39.98	85	37.16	30.48	3.24	30.9	-	-	P	H
		127	17.16	-26.34	43.5	31.3	16.41	1.15	31.7	-	-	P	V
		260.86	21.29	-24.71	46	32.52	18.67	1.68	31.58	-	-	P	V
	*	894.27	39.17	-38.72	77.89	37.85	29.06	3.15	30.89	-	-	P	V
		926.5	107.89	---	---	105.8	29.84	3.2	30.95	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												





lor a DTS SF=11(LF@ 3m)

	Note	Frequency	Level	Margin	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
902.5MHz		127.97	17.22	-26.28	43.5	31.33	16.43	1.16	31.7	-	-	P	H
		281.23	20.52	-25.48	46	31.38	18.94	1.74	31.54	-	-	P	H
	*	870.02	40.1	-47.29	87.39	38.41	29	3.09	30.4	-	-	P	H
		902.5	117.39	---	---	116.09	29.14	3.16	31	-	-	P	H
		934.04	44.37	-43.02	87.39	42.03	30.06	3.21	30.93	-	-	P	H
		126.03	17.13	-26.37	43.5	31.29	16.39	1.15	31.7	-	-	P	V
		285.11	20.58	-25.42	46	31.36	18.99	1.76	31.53	-	-	P	V
	*	902.5	110.92	---	---	109.62	29.14	3.16	31	-	-	P	V
		934.04	37.89	-43.03	80.92	35.55	30.06	3.21	30.93	-	-	P	V
914.5MHz		134.76	21.91	-21.59	43.5	36.61	17.96	2.24	34.9	-	-	P	H
		281.23	22.81	-23.19	46	35.64	18.77	3.14	34.74	-	-	P	H
	*	914.5	117.39	---	---	117.6	29.34	4.45	34	-	-	P	H
		134.76	22.11	-21.39	43.5	36.81	17.96	2.24	34.9	-	-	P	V
		284.14	23.1	-22.9	46	35.82	18.86	3.15	34.73	-	-	P	V
	*	914.5	110.58	---	---	110.79	29.34	4.45	34	-	-	P	V
926.5MHz		123.12	16.95	-26.55	43.5	31.18	16.34	1.13	31.7	-	-	P	H
		274.44	20.05	-25.95	46	31.03	18.85	1.72	31.55	-	-	P	H
	*	894.27	44.59	-41.47	86.06	43.27	29.06	3.15	30.89	-	-	P	H
		926.5	116.06	---	---	113.97	29.84	3.2	30.95	-	-	P	H
		958.29	39.95	-46.11	86.06	37.13	30.48	3.24	30.9	-	-	P	H
		127.97	17.35	-26.15	43.5	31.46	16.43	1.16	31.7	-	-	P	V
		240.49	20.61	-25.39	46	32.8	17.8	1.61	31.6	-	-	P	V
	*	894.27	37.83	-39.22	77.05	36.51	29.06	3.15	30.89	-	-	P	V
		926.5	107.05	---	---	104.96	29.84	3.2	30.95	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Appendix D. Radiated Spurious Emission Plots

LoRa 500KHz DTS SF=7 (Harmonic @ 3m)

LoRa	Harmonic @ 3m																																																																																																																																																																																													
ANT	LoRa 500KHz DTS SF=7 CH01 902.5MHz																																																																																																																																																																																													
	Horizontal	Vertical																																																																																																																																																																																												
Peak	Data: 1 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>1805.00</td><td>49.78</td><td>---</td><td>---</td><td>70.33</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2787.50</td><td>47.07</td><td>-26.93</td><td>74.00</td><td>64.02</td><td>32.28</td><td>8.61</td><td>57.84</td><td>124</td><td>198</td><td>Peak</td></tr><tr><td>3</td><td>2787.50</td><td>35.71</td><td>-18.29</td><td>54.00</td><td>52.66</td><td>32.28</td><td>8.61</td><td>57.84</td><td>124</td><td>198</td><td>Average</td></tr><tr><td>4</td><td>3610.00</td><td>42.19</td><td>-31.81</td><td>74.00</td><td>57.60</td><td>32.93</td><td>9.66</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8122.50</td><td>49.78</td><td>-24.22</td><td>74.00</td><td>61.27</td><td>35.84</td><td>11.93</td><td>59.26</td><td>124</td><td>345</td><td>Peak</td></tr><tr><td>6</td><td>8122.50</td><td>39.48</td><td>-14.52</td><td>54.00</td><td>50.97</td><td>35.84</td><td>11.93</td><td>59.26</td><td>124</td><td>345</td><td>Average</td></tr></tbody></table>		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg		1	1805.00	49.78	---	---	70.33	30.63	6.64	57.90	---	---	Peak	2	2787.50	47.07	-26.93	74.00	64.02	32.28	8.61	57.84	124	198	Peak	3	2787.50	35.71	-18.29	54.00	52.66	32.28	8.61	57.84	124	198	Average	4	3610.00	42.19	-31.81	74.00	57.60	32.93	9.66	58.00	---	---	Peak	5	8122.50	49.78	-24.22	74.00	61.27	35.84	11.93	59.26	124	345	Peak	6	8122.50	39.48	-14.52	54.00	50.97	35.84	11.93	59.26	124	345	Average	Data: 2 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1</td><td>1805.00</td><td>48.91</td><td>---</td><td>---</td><td>69.54</td><td>30.63</td><td>6.64</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2787.50</td><td>45.32</td><td>-28.68</td><td>74.00</td><td>62.27</td><td>32.28</td><td>8.61</td><td>57.84</td><td>278</td><td>62</td><td>Peak</td></tr><tr><td>3</td><td>2787.50</td><td>33.48</td><td>-20.52</td><td>54.00</td><td>50.43</td><td>32.28</td><td>8.61</td><td>57.84</td><td>278</td><td>62</td><td>Average</td></tr><tr><td>4</td><td>3610.00</td><td>43.20</td><td>-30.80</td><td>74.00</td><td>58.61</td><td>32.93</td><td>9.66</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8122.50</td><td>49.17</td><td>-24.83</td><td>74.00</td><td>60.66</td><td>35.84</td><td>11.93</td><td>59.26</td><td>132</td><td>220</td><td>Peak</td></tr><tr><td>6</td><td>8122.50</td><td>38.14</td><td>-15.86</td><td>54.00</td><td>49.63</td><td>35.84</td><td>11.93</td><td>59.26</td><td>132</td><td>220</td><td>Average</td></tr></tbody></table>		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg		1	1805.00	48.91	---	---	69.54	30.63	6.64	57.90	---	---	Peak	2	2787.50	45.32	-28.68	74.00	62.27	32.28	8.61	57.84	278	62	Peak	3	2787.50	33.48	-20.52	54.00	50.43	32.28	8.61	57.84	278	62	Average	4	3610.00	43.20	-30.80	74.00	58.61	32.93	9.66	58.00	---	---	Peak	5	8122.50	49.17	-24.83	74.00	60.66	35.84	11.93	59.26	132	220	Peak	6	8122.50	38.14	-15.86	54.00	49.63	35.84	11.93	59.26	132	220	Average
		Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																			
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																																																																					
1	1805.00	49.78	---	---	70.33	30.63	6.64	57.90	---	---	Peak																																																																																																																																																																																			
2	2787.50	47.07	-26.93	74.00	64.02	32.28	8.61	57.84	124	198	Peak																																																																																																																																																																																			
3	2787.50	35.71	-18.29	54.00	52.66	32.28	8.61	57.84	124	198	Average																																																																																																																																																																																			
4	3610.00	42.19	-31.81	74.00	57.60	32.93	9.66	58.00	---	---	Peak																																																																																																																																																																																			
5	8122.50	49.78	-24.22	74.00	61.27	35.84	11.93	59.26	124	345	Peak																																																																																																																																																																																			
6	8122.50	39.48	-14.52	54.00	50.97	35.84	11.93	59.26	124	345	Average																																																																																																																																																																																			
	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																				
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																																																																																					
1	1805.00	48.91	---	---	69.54	30.63	6.64	57.90	---	---	Peak																																																																																																																																																																																			
2	2787.50	45.32	-28.68	74.00	62.27	32.28	8.61	57.84	278	62	Peak																																																																																																																																																																																			
3	2787.50	33.48	-20.52	54.00	50.43	32.28	8.61	57.84	278	62	Average																																																																																																																																																																																			
4	3610.00	43.20	-30.80	74.00	58.61	32.93	9.66	58.00	---	---	Peak																																																																																																																																																																																			
5	8122.50	49.17	-24.83	74.00	60.66	35.84	11.93	59.26	132	220	Peak																																																																																																																																																																																			
6	8122.50	38.14	-15.86	54.00	49.63	35.84	11.93	59.26	132	220	Average																																																																																																																																																																																			



LoRa	Harmonic @ 3m																																																																																																																																																																																																						
ANT	LoRa 500KHz DTS SF=7 CH16 914.5MHz																																																																																																																																																																																																						
	Horizontal																																																																																																																																																																																																						
	Vertical																																																																																																																																																																																																						
Peak	Date: 1 Level (dBuV/m) <table><tr><th></th><th>Freq</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th colspan="2">Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>1829.00</td><td>48.02</td><td>---</td><td>---</td><td>68.43</td><td>30.77</td><td>6.72</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2743.50</td><td>46.48</td><td>-27.52</td><td>74.00</td><td>63.46</td><td>32.25</td><td>8.62</td><td>57.85</td><td>132</td><td>256</td><td>Peak</td></tr><tr><td>3</td><td>2743.50</td><td>34.67</td><td>-19.33</td><td>54.00</td><td>51.65</td><td>32.25</td><td>8.62</td><td>57.85</td><td>132</td><td>256</td><td>Average</td></tr><tr><td>4</td><td>3658.00</td><td>44.00</td><td>-30.00</td><td>74.00</td><td>59.36</td><td>33.00</td><td>9.64</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8230.50</td><td>49.68</td><td>-24.32</td><td>74.00</td><td>60.96</td><td>35.00</td><td>12.03</td><td>59.11</td><td>132</td><td>241</td><td>Peak</td></tr><tr><td>6</td><td>8230.50</td><td>40.34</td><td>-13.66</td><td>54.00</td><td>51.62</td><td>35.00</td><td>12.03</td><td>59.11</td><td>132</td><td>241</td><td>Average</td></tr></table> Date: 2 Level (dBuV/m) <table><tr><th></th><th>Freq</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th colspan="2">Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>1829.00</td><td>44.52</td><td>---</td><td>---</td><td>64.93</td><td>30.77</td><td>6.72</td><td>57.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>2743.50</td><td>45.58</td><td>-28.32</td><td>74.00</td><td>62.66</td><td>32.25</td><td>8.62</td><td>57.85</td><td>123</td><td>224</td><td>Peak</td></tr><tr><td>3</td><td>2743.50</td><td>34.64</td><td>-19.36</td><td>54.00</td><td>51.62</td><td>32.25</td><td>8.62</td><td>57.85</td><td>123</td><td>224</td><td>Average</td></tr><tr><td>4</td><td>3658.00</td><td>41.51</td><td>-32.49</td><td>74.00</td><td>56.87</td><td>33.00</td><td>9.64</td><td>58.00</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>8230.50</td><td>49.37</td><td>-24.63</td><td>74.00</td><td>60.65</td><td>35.00</td><td>12.03</td><td>59.11</td><td>124</td><td>323</td><td>Peak</td></tr><tr><td>6</td><td>8230.50</td><td>38.34</td><td>-15.66</td><td>54.00</td><td>49.62</td><td>35.00</td><td>12.03</td><td>59.11</td><td>124</td><td>323</td><td>Average</td></tr></table>												Freq	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark			MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	cm	deg		1	1829.00	48.02	---	---	68.43	30.77	6.72	57.90	---	---	Peak	2	2743.50	46.48	-27.52	74.00	63.46	32.25	8.62	57.85	132	256	Peak	3	2743.50	34.67	-19.33	54.00	51.65	32.25	8.62	57.85	132	256	Average	4	3658.00	44.00	-30.00	74.00	59.36	33.00	9.64	58.00	---	---	Peak	5	8230.50	49.68	-24.32	74.00	60.96	35.00	12.03	59.11	132	241	Peak	6	8230.50	40.34	-13.66	54.00	51.62	35.00	12.03	59.11	132	241	Average		Freq	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark			MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	cm	deg		1	1829.00	44.52	---	---	64.93	30.77	6.72	57.90	---	---	Peak	2	2743.50	45.58	-28.32	74.00	62.66	32.25	8.62	57.85	123	224	Peak	3	2743.50	34.64	-19.36	54.00	51.62	32.25	8.62	57.85	123	224	Average	4	3658.00	41.51	-32.49	74.00	56.87	33.00	9.64	58.00	---	---	Peak	5	8230.50	49.37	-24.63	74.00	60.65	35.00	12.03	59.11	124	323	Peak	6	8230.50	38.34	-15.66	54.00	49.62	35.00	12.03	59.11	124	323	Average
		Freq	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																													
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																																													
	1	1829.00	48.02	---	---	68.43	30.77	6.72	57.90	---	---	Peak																																																																																																																																																																																											
	2	2743.50	46.48	-27.52	74.00	63.46	32.25	8.62	57.85	132	256	Peak																																																																																																																																																																																											
	3	2743.50	34.67	-19.33	54.00	51.65	32.25	8.62	57.85	132	256	Average																																																																																																																																																																																											
	4	3658.00	44.00	-30.00	74.00	59.36	33.00	9.64	58.00	---	---	Peak																																																																																																																																																																																											
	5	8230.50	49.68	-24.32	74.00	60.96	35.00	12.03	59.11	132	241	Peak																																																																																																																																																																																											
	6	8230.50	40.34	-13.66	54.00	51.62	35.00	12.03	59.11	132	241	Average																																																																																																																																																																																											
		Freq	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																																																																																													
	MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB/m	dB	cm	deg																																																																																																																																																																																														
1	1829.00	44.52	---	---	64.93	30.77	6.72	57.90	---	---	Peak																																																																																																																																																																																												
2	2743.50	45.58	-28.32	74.00	62.66	32.25	8.62	57.85	123	224	Peak																																																																																																																																																																																												
3	2743.50	34.64	-19.36	54.00	51.62	32.25	8.62	57.85	123	224	Average																																																																																																																																																																																												
4	3658.00	41.51	-32.49	74.00	56.87	33.00	9.64	58.00	---	---	Peak																																																																																																																																																																																												
5	8230.50	49.37	-24.63	74.00	60.65	35.00	12.03	59.11	124	323	Peak																																																																																																																																																																																												
6	8230.50	38.34	-15.66	54.00	49.62	35.00	12.03	59.11	124	323	Average																																																																																																																																																																																												



LoRa	Harmonic @ 3m													
ANT	LoRa 500KHz DTS SF=7 CH31 926.5MHz													
	Horizontal													
	Vertical													
Peak	Date: 1 Level (dBuV/m) <													



LoRa 500KHz DTS SF=11 (Harmonic @ 3m)

LoRa	Band Harmonic @ 3m									
ANT	LoRa 500KHz DTS SF=11 CH01 902.5MHz									
	Horizontal									
	Vertical									
Peak	<									



LoRa	Harmonic @ 3m									
ANT	LoRa 500KHz DTS SF=11 CH16 914.5MHz									
	Horizontal					Vertical				
Peak	Date: 1 Level (dBuV/m) </									



LoRa	Harmonic @ 3m											
ANT	LoRa 500KHz DTS SF=11 CH31 926.5MHz											
	Horizontal											
	Vertical											
Peak	Date: 1 Level (dBuV/m) <											





<30M-1G>



LoRa 500KHz DTS SF=7 (LF @ 3m)

LoRa	LF @ 3m																																																																																																																																									
ANT	LoRa 500KHz DTS SF=7 CH01 902.5 MHz																																																																																																																																									
	Horizontal	Vertical																																																																																																																																								
Peak	Date: 1 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>136.70</td><td>16.95</td><td>-26.55</td><td>43.50</td><td>30.87</td><td>16.50</td><td>1.20</td><td>31.70</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>280.26</td><td>21.01</td><td>-24.99</td><td>46.00</td><td>31.08</td><td>18.93</td><td>1.74</td><td>31.54</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>870.99</td><td>40.05</td><td>---</td><td>---</td><td>38.37</td><td>29.00</td><td>3.10</td><td>30.42</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>902.50</td><td>117.03</td><td>---</td><td>---</td><td>115.73</td><td>29.14</td><td>3.16</td><td>31.00</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>935.01</td><td>43.42</td><td>---</td><td>---</td><td>41.05</td><td>30.09</td><td>3.21</td><td>30.93</td><td>---</td><td>Peak</td></tr></tbody></table>		Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	136.70	16.95	-26.55	43.50	30.87	16.50	1.20	31.70	---	Peak	2	280.26	21.01	-24.99	46.00	31.08	18.93	1.74	31.54	---	Peak	3	870.99	40.05	---	---	38.37	29.00	3.10	30.42	---	Peak	4	902.50	117.03	---	---	115.73	29.14	3.16	31.00	---	Peak	5	935.01	43.42	---	---	41.05	30.09	3.21	30.93	---	Peak	Date: 2 <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>127.00</td><td>18.89</td><td>-24.61</td><td>43.50</td><td>33.03</td><td>16.41</td><td>1.15</td><td>31.70</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>256.92</td><td>20.96</td><td>-25.04</td><td>46.00</td><td>32.21</td><td>18.65</td><td>1.60</td><td>31.58</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>902.50</td><td>110.90</td><td>---</td><td>---</td><td>109.60</td><td>29.14</td><td>3.16</td><td>31.00</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>935.01</td><td>40.18</td><td>---</td><td>---</td><td>37.81</td><td>30.09</td><td>3.21</td><td>30.93</td><td>---</td><td>Peak</td></tr></tbody></table>		Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg	1	127.00	18.89	-24.61	43.50	33.03	16.41	1.15	31.70	---	Peak	2	256.92	20.96	-25.04	46.00	32.21	18.65	1.60	31.58	---	Peak	3	902.50	110.90	---	---	109.60	29.14	3.16	31.00	---	Peak	4	935.01	40.18	---	---	37.81	30.09	3.21	30.93	---	Peak
	Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																		
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																																																																																																		
1	136.70	16.95	-26.55	43.50	30.87	16.50	1.20	31.70	---	Peak																																																																																																																																
2	280.26	21.01	-24.99	46.00	31.08	18.93	1.74	31.54	---	Peak																																																																																																																																
3	870.99	40.05	---	---	38.37	29.00	3.10	30.42	---	Peak																																																																																																																																
4	902.50	117.03	---	---	115.73	29.14	3.16	31.00	---	Peak																																																																																																																																
5	935.01	43.42	---	---	41.05	30.09	3.21	30.93	---	Peak																																																																																																																																
	Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																																		
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	dB	cm	deg																																																																																																																																	
1	127.00	18.89	-24.61	43.50	33.03	16.41	1.15	31.70	---	Peak																																																																																																																																
2	256.92	20.96	-25.04	46.00	32.21	18.65	1.60	31.58	---	Peak																																																																																																																																
3	902.50	110.90	---	---	109.60	29.14	3.16	31.00	---	Peak																																																																																																																																
4	935.01	40.18	---	---	37.81	30.09	3.21	30.93	---	Peak																																																																																																																																



LoRa	LF @ 3m																																																																																																									
ANT	LoRa 500KHz DTS SF=7 CH16 914.5 MHz																																																																																																									
	Horizontal					Vertical																																																																																																				
Peak																																																																																																										
	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>1</th><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>134.768</td><td>22.45</td><td>-21.85</td><td>43.58</td><td>37.15</td><td>17.96</td><td>2.24 34.90 --- --- Peak</td></tr><tr><td>2</td><td>279.298</td><td>23.48</td><td>-22.68</td><td>46.08</td><td>36.38</td><td>18.71</td><td>3.13 34.74 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>117.48</td><td>---</td><td>---</td><td>117.61</td><td>29.34</td><td>4.45 34.88 --- --- Peak</td></tr></table>						Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	1	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	1	134.768	22.45	-21.85	43.58	37.15	17.96	2.24 34.90 --- --- Peak	2	279.298	23.48	-22.68	46.08	36.38	18.71	3.13 34.74 --- --- Peak	3	914.500	117.48	---	---	117.61	29.34	4.45 34.88 --- --- Peak	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>1</th><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th></tr><tr><td>1</td><td>137.678</td><td>22.38</td><td>-21.28</td><td>43.58</td><td>36.81</td><td>18.13</td><td>2.26 34.98 --- --- Peak</td></tr><tr><td>2</td><td>285.118</td><td>23.55</td><td>-22.45</td><td>46.88</td><td>36.23</td><td>18.98</td><td>3.15 34.73 --- --- Peak</td></tr><tr><td>3</td><td>914.500</td><td>118.85</td><td>---</td><td>---</td><td>111.86</td><td>29.34</td><td>4.45 34.88 --- --- Peak</td></tr></table>						Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	1	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	1	137.678	22.38	-21.28	43.58	36.81	18.13	2.26 34.98 --- --- Peak	2	285.118	23.55	-22.45	46.88	36.23	18.98	3.15 34.73 --- --- Peak	3	914.500	118.85	---	---	111.86	29.34	4.45 34.88 --- --- Peak
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																		
	1	Freq	Level	Line	Level Factor	Loss Factor																																																																																																				
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm																																																																																																			
1	134.768	22.45	-21.85	43.58	37.15	17.96	2.24 34.90 --- --- Peak																																																																																																			
2	279.298	23.48	-22.68	46.08	36.38	18.71	3.13 34.74 --- --- Peak																																																																																																			
3	914.500	117.48	---	---	117.61	29.34	4.45 34.88 --- --- Peak																																																																																																			
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																			
1	Freq	Level	Line	Level Factor	Loss Factor																																																																																																					
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm																																																																																																			
1	137.678	22.38	-21.28	43.58	36.81	18.13	2.26 34.98 --- --- Peak																																																																																																			
2	285.118	23.55	-22.45	46.88	36.23	18.98	3.15 34.73 --- --- Peak																																																																																																			
3	914.500	118.85	---	---	111.86	29.34	4.45 34.88 --- --- Peak																																																																																																			





LoRa	LF @ 3m																																																																																																																																			
ANT	LoRa 500KHz DTS SF=7 CH31 926.5 MHz																																																																																																																																			
	Horizontal	Vertical																																																																																																																																		
Peak	Date: 1 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>131.85</td><td>17.63</td><td>-25.87</td><td>43.50</td><td>31.66</td><td>16.50</td><td>1.17</td><td>31.70</td><td>--- Peak</td></tr><tr><td>2</td><td>262.80</td><td>20.52</td><td>-25.48</td><td>46.00</td><td>31.70</td><td>18.70</td><td>1.69</td><td>31.57</td><td>--- Peak</td></tr><tr><td>3</td><td>894.27</td><td>43.66</td><td>---</td><td>42.34</td><td>29.86</td><td>3.15</td><td>30.89</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>926.50</td><td>115.00</td><td>---</td><td>112.91</td><td>29.84</td><td>3.20</td><td>30.95</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>958.29</td><td>39.98</td><td>---</td><td>37.16</td><td>30.48</td><td>3.24</td><td>30.90</td><td>---</td><td>Peak</td></tr></table>		Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	131.85	17.63	-25.87	43.50	31.66	16.50	1.17	31.70	--- Peak	2	262.80	20.52	-25.48	46.00	31.70	18.70	1.69	31.57	--- Peak	3	894.27	43.66	---	42.34	29.86	3.15	30.89	---	Peak	4	926.50	115.00	---	112.91	29.84	3.20	30.95	---	Peak	5	958.29	39.98	---	37.16	30.48	3.24	30.90	---	Peak	Date: 2 <table><tr><th></th><th>Freq</th><th>Level</th><th>Over Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>127.00</td><td>17.16</td><td>-26.34</td><td>43.50</td><td>31.30</td><td>16.41</td><td>1.15</td><td>31.70</td><td>--- Peak</td></tr><tr><td>2</td><td>260.86</td><td>21.29</td><td>-24.71</td><td>46.00</td><td>32.52</td><td>18.67</td><td>1.68</td><td>31.58</td><td>--- Peak</td></tr><tr><td>3</td><td>894.27</td><td>---</td><td>---</td><td>46.00</td><td>37.85</td><td>29.86</td><td>3.15</td><td>30.89</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>926.50</td><td>---</td><td>---</td><td>46.00</td><td>105.00</td><td>29.84</td><td>3.20</td><td>30.95</td><td>---</td><td>Peak</td></tr></table>		Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark		MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	1	127.00	17.16	-26.34	43.50	31.30	16.41	1.15	31.70	--- Peak	2	260.86	21.29	-24.71	46.00	32.52	18.67	1.68	31.58	--- Peak	3	894.27	---	---	46.00	37.85	29.86	3.15	30.89	---	Peak	4	926.50	---	---	46.00	105.00	29.84	3.20	30.95	---	Peak
	Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																												
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																											
1	131.85	17.63	-25.87	43.50	31.66	16.50	1.17	31.70	--- Peak																																																																																																																											
2	262.80	20.52	-25.48	46.00	31.70	18.70	1.69	31.57	--- Peak																																																																																																																											
3	894.27	43.66	---	42.34	29.86	3.15	30.89	---	Peak																																																																																																																											
4	926.50	115.00	---	112.91	29.84	3.20	30.95	---	Peak																																																																																																																											
5	958.29	39.98	---	37.16	30.48	3.24	30.90	---	Peak																																																																																																																											
	Freq	Level	Over Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																												
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg																																																																																																																											
1	127.00	17.16	-26.34	43.50	31.30	16.41	1.15	31.70	--- Peak																																																																																																																											
2	260.86	21.29	-24.71	46.00	32.52	18.67	1.68	31.58	--- Peak																																																																																																																											
3	894.27	---	---	46.00	37.85	29.86	3.15	30.89	---	Peak																																																																																																																										
4	926.50	---	---	46.00	105.00	29.84	3.20	30.95	---	Peak																																																																																																																										



LoRa 500KHz DTS SF=11 (LF @ 3m)

LoRa	LF @ 3m																																																																																																																																			
ANT	LoRa 500KHz DTS SF=11 CH01 902.5 MHz																																																																																																																																			
	Horizontal	Vertical																																																																																																																																		
Peak	Date: 1 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>127.97</td><td>17.22</td><td>-26.28</td><td>43.50</td><td>31.33</td><td>16.43</td><td>1.16</td><td>31.70</td><td>--- Peak</td></tr><tr><td>2</td><td>281.23</td><td>20.52</td><td>-25.48</td><td>46.00</td><td>31.38</td><td>18.96</td><td>1.74</td><td>31.54</td><td>--- Peak</td></tr><tr><td>3</td><td>879.82</td><td>40.10</td><td>---</td><td>---</td><td>38.41</td><td>29.00</td><td>3.09</td><td>30.40</td><td>--- Peak</td></tr><tr><td>4</td><td>902.50</td><td>117.39</td><td>---</td><td>---</td><td>116.09</td><td>29.14</td><td>3.16</td><td>31.00</td><td>--- Peak</td></tr><tr><td>5</td><td>934.04</td><td>44.37</td><td>---</td><td>---</td><td>42.03</td><td>30.06</td><td>3.21</td><td>30.93</td><td>--- Peak</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg		1	127.97	17.22	-26.28	43.50	31.33	16.43	1.16	31.70	--- Peak	2	281.23	20.52	-25.48	46.00	31.38	18.96	1.74	31.54	--- Peak	3	879.82	40.10	---	---	38.41	29.00	3.09	30.40	--- Peak	4	902.50	117.39	---	---	116.09	29.14	3.16	31.00	--- Peak	5	934.04	44.37	---	---	42.03	30.06	3.21	30.93	--- Peak	Date: 2 <table><tr><th>Freq</th><th>Level</th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable</th><th>Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dBuV</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>126.83</td><td>17.13</td><td>-26.37</td><td>43.50</td><td>31.29</td><td>16.39</td><td>1.15</td><td>31.70</td><td>--- Peak</td></tr><tr><td>2</td><td>285.11</td><td>20.58</td><td>-25.42</td><td>46.00</td><td>31.36</td><td>18.99</td><td>1.76</td><td>31.53</td><td>--- Peak</td></tr><tr><td>3</td><td>902.50</td><td>110.92</td><td>---</td><td>---</td><td>109.62</td><td>29.14</td><td>3.16</td><td>31.00</td><td>--- Peak</td></tr><tr><td>4</td><td>934.04</td><td>37.89</td><td>---</td><td>---</td><td>35.55</td><td>30.06</td><td>3.21</td><td>30.93</td><td>--- Peak</td></tr></table>	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg		1	126.83	17.13	-26.37	43.50	31.29	16.39	1.15	31.70	--- Peak	2	285.11	20.58	-25.42	46.00	31.36	18.99	1.76	31.53	--- Peak	3	902.50	110.92	---	---	109.62	29.14	3.16	31.00	--- Peak	4	934.04	37.89	---	---	35.55	30.06	3.21	30.93	--- Peak
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																												
1	127.97	17.22	-26.28	43.50	31.33	16.43	1.16	31.70	--- Peak																																																																																																																											
2	281.23	20.52	-25.48	46.00	31.38	18.96	1.74	31.54	--- Peak																																																																																																																											
3	879.82	40.10	---	---	38.41	29.00	3.09	30.40	--- Peak																																																																																																																											
4	902.50	117.39	---	---	116.09	29.14	3.16	31.00	--- Peak																																																																																																																											
5	934.04	44.37	---	---	42.03	30.06	3.21	30.93	--- Peak																																																																																																																											
Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark																																																																																																																											
MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	cm	deg																																																																																																																												
1	126.83	17.13	-26.37	43.50	31.29	16.39	1.15	31.70	--- Peak																																																																																																																											
2	285.11	20.58	-25.42	46.00	31.36	18.99	1.76	31.53	--- Peak																																																																																																																											
3	902.50	110.92	---	---	109.62	29.14	3.16	31.00	--- Peak																																																																																																																											
4	934.04	37.89	---	---	35.55	30.06	3.21	30.93	--- Peak																																																																																																																											



LoRa	LF @ 3m																																																																						
ANT	LoRa 500KHz DTS SF=11 CH16 914.5 MHz																																																																						
	Horizontal																																																																						
Peak																																																																							
	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>134.768</td><td>21.91</td><td>-21.59</td><td>43.58</td><td>36.61</td><td>17.96</td><td>2.24</td><td>34.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>281.230</td><td>22.81</td><td>-23.19</td><td>46.00</td><td>35.64</td><td>18.77</td><td>3.14</td><td>34.74</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>914.500</td><td>117.39</td><td>---</td><td>---</td><td>117.68</td><td>29.34</td><td>4.45</td><td>34.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>												Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	134.768	21.91	-21.59	43.58	36.61	17.96	2.24	34.90	---	---	Peak	2	281.230	22.81	-23.19	46.00	35.64	18.77	3.14	34.74	---	---	Peak	3	914.500	117.39	---	---	117.68	29.34	4.45	34.00	---	---	Peak
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																															
	Freq	Level	Line	Level Factor	Loss Factor																																																																		
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																															
	1	134.768	21.91	-21.59	43.58	36.61	17.96	2.24	34.90	---	---	Peak																																																											
	2	281.230	22.81	-23.19	46.00	35.64	18.77	3.14	34.74	---	---	Peak																																																											
	3	914.500	117.39	---	---	117.68	29.34	4.45	34.00	---	---	Peak																																																											
	Vertical																																																																						
Peak																																																																							
	<table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dB</th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>134.768</td><td>22.11</td><td>-21.39</td><td>43.58</td><td>36.81</td><td>17.96</td><td>2.24</td><td>34.90</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>284.148</td><td>23.10</td><td>-22.90</td><td>46.00</td><td>35.82</td><td>18.86</td><td>3.15</td><td>34.73</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>914.500</td><td>118.58</td><td>---</td><td>---</td><td>118.79</td><td>29.34</td><td>4.45</td><td>34.00</td><td>---</td><td>---</td><td>Peak</td></tr></table>												Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg	1	134.768	22.11	-21.39	43.58	36.81	17.96	2.24	34.90	---	---	Peak	2	284.148	23.10	-22.90	46.00	35.82	18.86	3.15	34.73	---	---	Peak	3	914.500	118.58	---	---	118.79	29.34	4.45	34.00	---	---	Peak
		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																															
	Freq	Level	Line	Level Factor	Loss Factor																																																																		
	MHz	dBuV/m	dB	dBuV/m	dB/m	dB	cm	deg																																																															
	1	134.768	22.11	-21.39	43.58	36.81	17.96	2.24	34.90	---	---	Peak																																																											
	2	284.148	23.10	-22.90	46.00	35.82	18.86	3.15	34.73	---	---	Peak																																																											
	3	914.500	118.58	---	---	118.79	29.34	4.45	34.00	---	---	Peak																																																											




LoRa	LF @ 3m																																																																																																																									
ANT	LoRa 500KHz DTS SF=11 CH31 926.5 MHz																																																																																																																									
	Horizontal	Vertical																																																																																																																								
Peak	Date: 1 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th></th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>123.12</td><td>16.95</td><td>-26.55</td><td>43.50</td><td>31.18</td><td>16.34</td><td>1.13 31.70 --- Peak</td></tr><tr><td>2</td><td>274.44</td><td>20.05</td><td>-25.95</td><td>46.00</td><td>31.03</td><td>18.85</td><td>1.72 31.55 --- Peak</td></tr><tr><td>3</td><td>894.27</td><td>44.59</td><td>---</td><td>---</td><td>43.27</td><td>29.06</td><td>3.15 30.89 --- Peak</td></tr><tr><td>4</td><td>926.50</td><td>116.06</td><td>---</td><td>---</td><td>113.97</td><td>29.84</td><td>3.20 30.95 --- Peak</td></tr><tr><td>5</td><td>958.29</td><td>39.95</td><td>---</td><td>---</td><td>37.13</td><td>30.48</td><td>3.24 30.90 --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m		dBuV/m	dB/m	dB	cm	deg	1	123.12	16.95	-26.55	43.50	31.18	16.34	1.13 31.70 --- Peak	2	274.44	20.05	-25.95	46.00	31.03	18.85	1.72 31.55 --- Peak	3	894.27	44.59	---	---	43.27	29.06	3.15 30.89 --- Peak	4	926.50	116.06	---	---	113.97	29.84	3.20 30.95 --- Peak	5	958.29	39.95	---	---	37.13	30.48	3.24 30.90 --- Peak	Date: 2 <table><tr><th></th><th>Over</th><th>Limit</th><th>ReadAntenna</th><th>Cable Preamp</th><th>A/Pos</th><th>T/Pos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Level Factor</th><th>Loss Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th></th><th>dBuV/m</th><th>dB/m</th><th>dB</th><th>dB</th><th>deg</th></tr><tr><td>1</td><td>127.97</td><td>17.35</td><td>-26.15</td><td>43.50</td><td>31.46</td><td>16.43</td><td>1.16 31.70 --- Peak</td></tr><tr><td>2</td><td>240.49</td><td>20.61</td><td>-25.39</td><td>46.00</td><td>32.80</td><td>17.80</td><td>1.61 31.60 --- Peak</td></tr><tr><td>3</td><td>894.27</td><td>37.83</td><td>---</td><td>---</td><td>36.51</td><td>29.06</td><td>3.15 30.89 --- Peak</td></tr><tr><td>4</td><td>926.50</td><td>107.05</td><td>---</td><td>---</td><td>104.96</td><td>29.84</td><td>3.20 30.95 --- Peak</td></tr></table>		Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark	Freq	Level	Line	Level Factor	Loss Factor				MHz	dBuV/m		dBuV/m	dB/m	dB	dB	deg	1	127.97	17.35	-26.15	43.50	31.46	16.43	1.16 31.70 --- Peak	2	240.49	20.61	-25.39	46.00	32.80	17.80	1.61 31.60 --- Peak	3	894.27	37.83	---	---	36.51	29.06	3.15 30.89 --- Peak	4	926.50	107.05	---	---	104.96	29.84	3.20 30.95 --- Peak
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																			
Freq	Level	Line	Level Factor	Loss Factor																																																																																																																						
MHz	dBuV/m		dBuV/m	dB/m	dB	cm	deg																																																																																																																			
1	123.12	16.95	-26.55	43.50	31.18	16.34	1.13 31.70 --- Peak																																																																																																																			
2	274.44	20.05	-25.95	46.00	31.03	18.85	1.72 31.55 --- Peak																																																																																																																			
3	894.27	44.59	---	---	43.27	29.06	3.15 30.89 --- Peak																																																																																																																			
4	926.50	116.06	---	---	113.97	29.84	3.20 30.95 --- Peak																																																																																																																			
5	958.29	39.95	---	---	37.13	30.48	3.24 30.90 --- Peak																																																																																																																			
	Over	Limit	ReadAntenna	Cable Preamp	A/Pos	T/Pos	Remark																																																																																																																			
Freq	Level	Line	Level Factor	Loss Factor																																																																																																																						
MHz	dBuV/m		dBuV/m	dB/m	dB	dB	deg																																																																																																																			
1	127.97	17.35	-26.15	43.50	31.46	16.43	1.16 31.70 --- Peak																																																																																																																			
2	240.49	20.61	-25.39	46.00	32.80	17.80	1.61 31.60 --- Peak																																																																																																																			
3	894.27	37.83	---	---	36.51	29.06	3.15 30.89 --- Peak																																																																																																																			
4	926.50	107.05	---	---	104.96	29.84	3.20 30.95 --- Peak																																																																																																																			


Appendix E. Duty Cycle Plots

Band	Duty Cycle (%)	VBW Setting (Hz)	Duty Factor (dB)
LoRa(DTS)SF7	94.25	100	0.26
LoRa(DTS)SF8	96.83	-	0.14
LoRa(DTS)SF9	98.29	-	0.08
LoRa(DTS)SF10	99.29	-	0.03
LoRa(DTS)SF11	100	10	0


LoRa(DTS)SF 7




LoRa(DTS)SF 8



LoRa(DTS)SF 9



LoRa(DTS)SF 10



LoRa(DTS)SF 11

