



FCC RADIO TEST REPORT

FCC ID : 2AEUPBHADP031
Equipment : Video Doorbell
Brand Name : ring
Model Name : 5DFYA4
Applicant : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Manufacturer : Ring LLC
12515 Cerise Ave, Hawthorne, CA 90250, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Oct. 23, 2025 and testing was performed from Oct. 31, 2025 to Feb. 04, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Modification of EUT	5
1.3 Testing Location	5
1.4 Applicable Standards.....	6
2 Test Configuration of Equipment Under Test	7
2.1 Carrier Frequency and Channel	7
2.2 Test Mode.....	7
2.3 Connection Diagram of Test System.....	8
2.4 Support Unit used in test configuration and system	8
2.5 EUT Operation Test Setup	8
2.6 Measurement Results Explanation Example.....	9
3 Test Result	10
3.1 6dB and 99% Bandwidth Measurement	10
3.2 Output Power Measurement.....	11
3.3 Power Spectral Density Measurement	12
3.4 Conducted Band Edges and Spurious Emission Measurement	13
3.5 Radiated Band Edges and Spurious Emission Measurement	14
3.6 AC Conducted Emission Measurement.....	17
3.7 Antenna Requirements.....	19
4 List of Measuring Equipment.....	20
5 Measurement Uncertainty	22
Appendix A. Conducted Test Results	
Appendix B. AC Conducted Emission Test Result	
Appendix C. Radiated Spurious Emission Test Result	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR5O1416-01A	01	Initial issue of report	Feb. 09, 2026

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Pass	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	-
3.6	15.207	AC Conducted Emission	Pass	-
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Keven Cheng

Report Producer: Shiori Chen

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
General Specs Bluetooth-LE and Wi-Fi 2.4GHz 802.11b/g/n.		
Antenna Type WLAN: <Ant. 1>: IFA Antenna		
Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	4.3

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

The test location is accredited based on TAF code 1190 and 3786 designated by NCC (National Communication Commission).

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)

FCC designation No.: TW1190 and TW3786

Note:

1. The test site complies with ANSI C63.4 2014 requirement.
2. The AC Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.



1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC Part 15 Subpart C §15.247
- ♦ ANSI C63.10-2020 + Cor.1-2023

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the tests are performed according to the manufacturer-defined usage pattern (Y-axis: longitudinal).
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		


2.2 Test Mode

The final test modes include the worst data rates for each modulation shown in the table below.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1 WLAN (2.4GHz) Link + Power from plug in adapter
Remark: - The detailed Radiated test modes are shown in Appendix C. - For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
2.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2m DC O/P: Shielded, 1.8m
3.	Notebook	Lenovo	IdeaPad Gaming 3 15IHU6	PD9AX201NG	N/A	Unshielded, 1.8m
4.	Mobile Phone	SAMSUNG	SM-A256E/DSN	A3LSMA730F	N/A	N/A
5.	Adapter	Ring	6PCEA3	N/A	N/A	AC I/P: Unshielded, 2.0m DC O/P: Shielded, 1.5m

2.5 EUT Operation Test Setup

The RF test items, utility “Compliance Tool.1.0.1.64” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 1% to 5% of the OBW but not less than 100 kHz. Set the Video bandwidth VBW $\geq 3 * RBW$. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth, and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = No faster than coupled (auto) time, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-”.


8. Use the following spectrum analyzer settings:
- (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
- For average measurement:
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site **v01r01**, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C.

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.7.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9kHz~30MHz	Dec. 18, 2024	Oct. 31, 2025~ Nov. 25, 2025	Dec. 17, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Dec. 17, 2024	Oct. 31, 2025~ Nov. 25, 2025	Dec. 16, 2025	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 13, 2025	Oct. 31, 2025~ Nov. 25, 2025	Jul. 12, 2026	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18E N	1GHz~18GHz	May. 20, 2025	Oct. 31, 2025~ Nov. 25, 2025	May. 19, 2026	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	1225	18GHz~40GHz	Jul. 02, 2025	Oct. 31, 2025~ Nov. 25, 2025	Jul. 01, 2026	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 26, 2025	Oct. 31, 2025~ Nov. 25, 2025	Sep. 25, 2026	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060872	18-40GHz	Nov. 29, 2024	Oct. 31, 2025~ Nov. 25, 2025	Nov. 28, 2025	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY62170278	10Hz~44GHz	Sep. 22, 2025	Oct. 31, 2025~ Nov. 25, 2025	Sep. 21, 2026	Radiation (03CH22-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290045	20Hz~8.4GHz	Apr. 21, 2025	Oct. 31, 2025~ Nov. 25, 2025	Apr. 20, 2026	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Dec. 24, 2024	Oct. 31, 2025~ Nov. 25, 2025	Dec. 23, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Oct. 31, 2025~ Nov. 25, 2025	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Oct. 31, 2025~ Nov. 25, 2025	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Oct. 31, 2025~ Nov. 25, 2025	N/A	Radiation (03CH22-HY)
Software	Audix	E3	RK-002347	N/A	N/A	Oct. 31, 2025~ Nov. 25, 2025	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 05, 2025	Oct. 31, 2025~ Nov. 25, 2025	Mar. 04, 2026	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER/EMC I	SUCOFLEX 102/EMCI01Y- KM-KM-500/E MCI01Y-KM-K M-9000	804611/2,240 914, 25043351,25 043350	30MHz~40GHz	May 19, 2025	Oct. 31, 2025~ Nov. 25, 2025	May 18, 2026	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP224371	N/A	Jun. 16, 2025	Nov. 05, 2025~ Feb. 04, 2026	Jun. 15, 2026	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17I00015SNO 37 (NO:167)	10MHz~6GHz	Nov. 14, 2025	Nov. 05, 2025~ Feb. 04, 2026	Nov. 13, 2026	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 29, 2025	Nov. 05, 2025~ Feb. 04, 2026	Aug. 28, 2026	Conducted (TH05-HY)
Switch Control Mainframe	E-Instument	ETF-1405-0	EC1900157 (BOX6)	N/A	Feb. 10, 2025	Nov. 05, 2025~ Feb. 04, 2026	Feb. 09, 2026	Conducted (TH05-HY)
Software	Sporton	BTWIFI_Final_ version_24051 3	N/A	Conducted Other Test Item	N/A	Nov. 05, 2025 Feb. 04, 2026	N/A	Conducted (TH05-HY)

**FCC RADIO TEST REPORT****Report No.: FR501416-01A**

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Nov. 13, 2025	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	N/A	Dec. 10, 2024	Nov. 13, 2025	Dec. 09, 2025	Conduction (CO05-HY)
Hygrometer	TECPEL	DTM-303A	TP210031	N/A	Jun. 26, 2025	Nov. 13, 2025	Jun. 25, 2026	Conduction (CO05-HY)
Two-Line V-Network	Rohde & Schwarz	ENV216	100081	N/A	Jul. 25, 2025	Nov. 13, 2025	Jul. 24, 2026	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Nov. 13, 2025	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 29, 2025	Nov. 13, 2025	Jul. 28, 2026	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	MQT24082501	N/A	Oct. 14, 2025	Nov. 13, 2025	Oct. 13, 2026	Conduction (CO05-HY)

5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.7 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.3 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.0 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.7 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Joseph Hu	Temperature:	21~25	°C
Test Date:	2025/11/5~2026/02/04	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band Single Antenna										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant1	Ant2	Ant1	Ant2		
11b	1Mbps	1	1	2412	12.51	-	7.08	-	0.50	Pass
11b	1Mbps	1	6	2437	12.56	-	7.06	-	0.50	Pass
11b	1Mbps	1	11	2462	12.56	-	7.08	-	0.50	Pass
11b	1Mbps	1	12	2467	12.67	-	7.08	-	0.50	Pass
11b	1Mbps	1	13	2472	12.73	-	7.08	-	0.50	Pass
11g	6Mbps	1	1	2412	15.95	-	15.90	-	0.50	Pass
11g	6Mbps	1	2	2417	17.04	-	15.78	-	0.50	Pass
11g	6Mbps	1	6	2437	17.25	-	15.88	-	0.50	Pass
11g	6Mbps	1	9	2452	17.02	-	15.83	-	0.50	Pass
11g	6Mbps	1	10	2457	16.94	-	15.86	-	0.50	Pass
11g	6Mbps	1	11	2462	16.94	-	15.93	-	0.50	Pass
11g	6Mbps	1	12	2467	16.94	-	15.85	-	0.50	Pass
11g	6Mbps	1	13	2472	17.09	-	15.74	-	0.50	Pass
HT20	MCS0	1	1	2412	17.96	-	16.76	-	0.50	Pass
HT20	MCS0	1	2	2417	18.01	-	16.89	-	0.50	Pass
HT20	MCS0	1	6	2437	18.33	-	16.96	-	0.50	Pass
HT20	MCS0	1	9	2452	17.99	-	17.03	-	0.50	Pass
HT20	MCS0	1	10	2457	17.99	-	16.78	-	0.50	Pass
HT20	MCS0	1	11	2462	17.97	-	16.78	-	0.50	Pass
HT20	MCS0	1	12	2467	17.95	-	16.93	-	0.50	Pass
HT20	MCS0	1	13	2472	18.05	-	16.42	-	0.50	Pass

TEST RESULTS DATA
Average Output Power

2.4GHz Band Single Antenna																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant1	Ant2	SUM	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	17.52	-		30.00	-	4.30	-	21.82	-	36.00	-	Pass
11b	1Mbps	1	6	2437	18.40	-		30.00	-	4.30	-	22.70	-	36.00	-	Pass
11b	1Mbps	1	11	2462	16.89	-		30.00	-	4.30	-	21.19	-	36.00	-	Pass
11b	1Mbps	1	12	2467	13.13	-		30.00	-	4.30	-	17.43	-	36.00	-	Pass
11b	1Mbps	1	13	2472	10.81	-		30.00	-	4.30	-	15.11	-	36.00	-	Pass
11g	6Mbps	1	1	2412	14.81	-		30.00	-	4.30	-	19.11	-	36.00	-	Pass
11g	6Mbps	1	2	2417	16.64	-		30.00	-	4.30	-	20.94	-	36.00	-	Pass
11g	6Mbps	1	6	2437	18.35	-		30.00	-	4.30	-	22.65	-	36.00	-	Pass
11g	6Mbps	1	9	2452	16.62	-		30.00	-	4.30	-	20.92	-	36.00	-	Pass
11g	6Mbps	1	10	2457	15.23	-		30.00	-	4.30	-	19.53	-	36.00	-	Pass
11g	6Mbps	1	11	2462	14.23	-		30.00	-	4.30	-	18.53	-	36.00	-	Pass
11g	6Mbps	1	12	2467	12.12	-		30.00	-	4.30	-	16.42	-	36.00	-	Pass
11g	6Mbps	1	13	2472	2.02	-		30.00	-	4.30	-	6.32	-	36.00	-	Pass
HT20	MCS0	1	1	2412	14.57	-		30.00	-	4.30	-	18.87	-	36.00	-	Pass
HT20	MCS0	1	2	2417	15.93	-		30.00	-	4.30	-	20.23	-	36.00	-	Pass
HT20	MCS0	1	6	2437	18.43	-		30.00	-	4.30	-	22.73	-	36.00	-	Pass
HT20	MCS0	1	9	2452	16.15	-		30.00	-	4.30	-	20.45	-	36.00	-	Pass
HT20	MCS0	1	10	2457	15.23	-		30.00	-	4.30	-	19.53	-	36.00	-	Pass
HT20	MCS0	1	11	2462	13.76	-		30.00	-	4.30	-	18.06	-	36.00	-	Pass
HT20	MCS0	1	12	2467	11.47	-		30.00	-	4.30	-	15.77	-	36.00	-	Pass
HT20	MCS0	1	13	2472	-8.26	-		30.00	-	4.30	-	-3.96	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

TEST RESULTS DATA
Peak Power Spectral Density


2.4GHz Band Single Antenna												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant1	Ant2	Worse + 3.01	Ant1	Ant2	Ant1	Ant2	
11b	1Mbps	1	1	2412	-4.03	-		4.30	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-2.31	-		4.30	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-4.45	-		4.30	-	8.00	-	Pass
11b	1Mbps	1	12	2467	-8.10	-		4.30	-	8.00	-	Pass
11b	1Mbps	1	13	2472	-11.20	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-10.49	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	2	2417	-7.88	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-7.19	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	9	2452	-9.39	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	10	2457	-10.63	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-11.32	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	12	2467	-12.85	-		4.30	-	8.00	-	Pass
11g	6Mbps	1	13	2472	-23.91	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-11.69	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	2	2417	-10.01	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-7.09	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	9	2452	-8.86	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	10	2457	-10.52	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-12.02	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	12	2467	-14.18	-		4.30	-	8.00	-	Pass
HT20	MCS0	1	13	2472	-32.85	-		4.30	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.




6dB and 99% Occupied Bandwidth

<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.


<802.11g>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11gN20>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




Power Spectral Density(dBm/3kHz)

<802.11b>




<802.11g>





<802.11gN20>







**Band Edges and Spurious Emission**

Number of TX = 1, Ant. 1 (Measured)

Test Mode : 802.11b

Test Channel : 01


100kHz PSD reference Level**Channel 01 Plot****Spurious Emission 30MHz~1GHz****Spurious Emission 1GHz~26.5GHz**



Test Mode : 802.11b


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 12


100kHz PSD reference Level




Channel 12 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11b

Test Channel : 13


100kHz PSD reference Level




Channel 13 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11g


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 12


100kHz PSD reference Level




Channel 12 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11g

Test Channel : 13


100kHz PSD reference Level




Channel 13 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 01


100kHz PSD reference Level




Channel 01 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Test Mode : 802.11gN20


Test Channel : 06

100kHz PSD reference Level




Channel 06 Plot

Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 11


100kHz PSD reference Level




Channel 11 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 12


100kHz PSD reference Level




Channel 12 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz







Test Mode : 802.11gN20

Test Channel : 13


100kHz PSD reference Level




Channel 13 Plot



Spurious Emission 30MHz~1GHz



Spurious Emission 1GHz~26.5GHz






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26℃
		Relative Humidity :	45~55%

EUT Information

Report NO : 5O1416-01
 Test Mode : Mode 2
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum


**Final Result**

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.77	55.88	27.11	L1	OFF	19.8
0.152250	33.44	---	65.88	32.44	L1	OFF	19.8
0.204000	---	25.37	53.45	28.08	L1	OFF	19.8
0.204000	29.06	---	63.45	34.39	L1	OFF	19.8
0.399750	---	25.42	47.86	22.44	L1	OFF	19.8
0.399750	28.16	---	57.86	29.70	L1	OFF	19.8
0.424500	---	27.38	47.36	19.98	L1	OFF	19.8
0.424500	31.04	---	57.36	26.32	L1	OFF	19.8
4.830000	---	25.49	46.00	20.51	L1	OFF	20.1
4.830000	26.63	---	56.00	29.37	L1	OFF	20.1
7.833750	---	25.91	50.00	24.09	L1	OFF	20.3
7.833750	27.32	---	60.00	32.68	L1	OFF	20.3

EUT Information

Report NO : 5O1416-01
Test Mode : Mode 2
Test Voltage : 120Vac/60Hz
Phase : Neutral

Full Spectrum



Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	28.59	55.88	27.29	N	OFF	19.8
0.152250	34.29	---	65.88	31.59	N	OFF	19.8
0.168000	---	26.63	55.06	28.43	N	OFF	19.8
0.168000	33.16	---	65.06	31.90	N	OFF	19.8
0.388500	---	23.95	48.10	24.15	N	OFF	19.8
0.388500	27.00	---	58.10	31.10	N	OFF	19.8
0.435750	---	25.14	47.14	22.00	N	OFF	19.8
0.435750	31.21	---	57.14	25.93	N	OFF	19.8
0.809250	---	23.16	46.00	22.84	N	OFF	19.9
0.809250	24.57	---	56.00	31.43	N	OFF	19.9
6.551250	---	25.79	50.00	24.21	N	OFF	20.2
6.551250	26.91	---	60.00	33.09	N	OFF	20.2



Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Ken Kuo 、 York Huang	Temperature :	20.9~23.4°C
		Relative Humidity :	59.4~63.1%

Note symbol

-L	Low channel location
-R	High channel location



C1. Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 5	2400-2483.5	1	802.11b	01	2412	1Mbps	-	-
Mode 6	2400-2483.5	1	802.11b	06	2437	1Mbps	-	-
Mode 7	2400-2483.5	1	802.11b	11	2462	1Mbps	-	-
Mode 8	2400-2483.5	1	802.11b	12	2467	1Mbps	-	-
Mode 9	2400-2483.5	1	802.11b	13	2472	1Mbps	-	-
Mode 10	2400-2483.5	1	802.11g	01	2412	6Mbps	-	-
Mode 11	2400-2483.5	1	802.11g	06	2437	6Mbps	-	-
Mode 12	2400-2483.5	1	802.11g	11	2462	6Mbps	-	-
Mode 13	2400-2483.5	1	802.11g	12	2467	6Mbps	-	-
Mode 14	2400-2483.5	1	802.11g	13	2472	6Mbps	-	-
Mode 15	2400-2483.5	1	802.11n HT20	01	2412	MCS0	-	-
Mode 16	2400-2483.5	1	802.11n HT20	06	2437	MCS0	-	-
Mode 17	2400-2483.5	1	802.11n HT20	11	2462	MCS0	-	-
Mode 18	2400-2483.5	1	802.11n HT20	12	2467	MCS0	-	-
Mode 19	2400-2483.5	1	802.11n HT20	13	2472	MCS0	-	-
Mode 20	2400-2483.5	1	802.11g	02	2417	6Mbps	-	-
Mode 21	2400-2483.5	1	802.11g	09	2452	6Mbps	-	-
Mode 22	2400-2483.5	1	802.11g	10	2457	6Mbps	-	-
Mode 23	2400-2483.5	1	802.11n HT20	02	2417	MCS0	-	-
Mode 24	2400-2483.5	1	802.11n HT20	09	2452	MCS0	-	-
Mode 25	2400-2483.5	1	802.11n HT20	10	2457	MCS0	-	-
Mode 26	2400-2483.5	1	802.11g	02	2417	6Mbps	-	LF
Mode 27	2400-2483.5	1	802.11g	02	2417	6Mbps	-	SHF



C2. Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
5	802.11b	01	2389.17	50.46	54.00	-3.54	V	Avg.	Pass	-	Band Edge
	802.11b	01	4824.00	45.06	74.00	-28.94	V	Peak	Pass	-	Harmonic
6	802.11b	06	2363.09	39.52	54.00	-14.48	V	Avg.	Pass	-	Band Edge
	802.11b	06	7311.00	39.87	54.00	-14.13	V	Avg.	Pass	-	Harmonic
7	802.11b	11	2484.76	50.30	54.00	-3.70	V	Avg.	Pass	-	Band Edge
	802.11b	11	7386.00	39.98	54.00	-14.02	V	Avg.	Pass	-	Harmonic
8	802.11b	12	2484.15	50.74	54.00	-3.26	V	Avg.	Pass	-	Band Edge
	802.11b	12	7401.00	40.31	54.00	-13.69	H	Avg.	Pass	-	Harmonic
9	802.11b	13	2483.77	50.17	54.00	-3.83	V	Avg.	Pass	-	Band Edge
	802.11b	13	7416.00	39.56	54.00	-14.44	V	Avg.	Pass	-	Harmonic
10	802.11g	01	2389.95	50.08	54.00	-3.92	V	Avg.	Pass	-	Band Edge
10	802.11g	01	4824.00	45.15	74.00	-28.85	H	Peak	Pass	-	Harmonic
11	802.11g	06	2483.68	45.39	54.00	-8.61	H	Avg.	Pass	-	Band Edge
11	802.11g	06	7311.00	39.93	54.00	-14.07	H	Avg.	Pass	-	Harmonic
12	802.11g	11	2483.55	50.48	54.00	-3.52	V	Avg.	Pass	-	Band Edge
12	802.11g	11	7386.00	39.70	54.00	-14.30	H	Avg.	Pass	-	Harmonic
13	802.11g	12	2483.51	49.69	54.00	-4.31	V	Avg.	Pass	-	Band Edge
13	802.11g	12	7401.00	40.16	54.00	-13.84	H	Avg.	Pass	-	Harmonic
14	802.11g	13	2483.55	48.99	54.00	-5.01	V	Avg.	Pass	-	Band Edge
14	802.11g	13	7416.00	40.08	54.00	-13.92	V	Avg.	Pass	-	Harmonic
15	802.11n HT20	01	2389.69	50.35	54.00	-3.65	V	Avg.	Pass	-	Band Edge
15	802.11n HT20	01	4824.00	45.57	74.00	-28.43	V	Peak	Pass	-	Harmonic
16	802.11n HT20	06	2484.00	47.89	54.00	-6.11	V	Avg.	Pass	-	Band Edge
16	802.11n HT20	06	7311.00	39.76	54.00	-14.24	H	Avg.	Pass	-	Harmonic
17	802.11n HT20	11	2483.51	50.15	54.00	-3.85	V	Avg.	Pass	-	Band Edge
17	802.11n HT20	11	7386.00	40.04	54.00	-13.96	H	Avg.	Pass	-	Harmonic



Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	RU	Remark
18	802.11n HT20	12	2483.51	50.31	54.00	-3.69	V	Avg.	Pass	-	Band Edge
18	802.11n HT20	12	7401.00	40.29	54.00	-13.71	H	Avg.	Pass	-	Harmonic
19	802.11n HT20	13	2483.55	46.53	54.00	-7.47	V	Avg.	Pass	-	Band Edge
19	802.11n HT20	13	7416.00	39.74	54.00	-14.26	V	Avg.	Pass	-	Harmonic
20	802.11g	02	2389.72	50.89	54.00	-3.11	V	Avg.	Pass	-	Band Edge
20	802.11g	02	7251.00	40.05	54.00	-13.95	H	Avg.	Pass	-	Harmonic
21	802.11g	09	2483.68	50.60	54.00	-3.40	V	Avg.	Pass	-	Band Edge
21	802.11g	09	7356.00	40.09	54.00	-13.91	H	Avg.	Pass	-	Harmonic
22	802.11g	10	2484.35	50.42	54.00	-3.58	V	Avg.	Pass	-	Band Edge
22	802.11g	10	7371.00	39.65	54.00	-14.35	H	Avg.	Pass	-	Harmonic
23	802.11n HT20	02	2389.61	50.86	54.00	-3.14	V	Avg.	Pass	-	Band Edge
23	802.11n HT20	02	7251.00	39.81	54.00	-14.19	H	Avg.	Pass	-	Harmonic
24	802.11n HT20	09	2483.58	49.86	54.00	-4.14	V	Avg.	Pass	-	Band Edge
24	802.11n HT20	09	7356.00	39.82	54.00	-14.18	V	Avg.	Pass	-	Harmonic
25	802.11n HT20	10	2483.75	50.09	54.00	-3.91	V	Avg.	Pass	-	Band Edge
25	802.11n HT20	10	7371.00	39.64	54.00	-14.36	H	Avg.	Pass	-	Harmonic
26	LF	02	480.08	41.07	46.00	-4.93	H	QP	Pass	-	LF
27	SHF	02	24857.39	40.67	74.00	-33.33	H	Peak	Pass	-	SHF



Mode	5																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH01_2412MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.95</td><td>54.78</td><td>74.00</td><td>-19.22</td><td>43.26</td><td>26.60</td><td>8.06</td><td>32.58</td><td>9.44</td><td>354</td><td>16 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.95	54.78	74.00	-19.22	43.26	26.60	8.06	32.58	9.44	354	16 Peak	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>106.99</td><td>-----</td><td>-----</td><td>95.25</td><td>26.80</td><td>8.09</td><td>32.59</td><td>9.44</td><td>354</td><td>16 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	106.99	-----	-----	95.25	26.80	8.09	32.59	9.44	354	16 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2389.95	54.78	74.00	-19.22	43.26	26.60	8.06	32.58	9.44	354	16 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2412.00	106.99	-----	-----	95.25	26.80	8.09	32.59	9.44	354	16 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2389.17</td><td>48.75</td><td>54.00</td><td>-5.25</td><td>37.22</td><td>26.61</td><td>8.06</td><td>32.58</td><td>9.44</td><td>354</td><td>16 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.17	48.75	54.00	-5.25	37.22	26.61	8.06	32.58	9.44	354	16 Average	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2412.00</td><td>103.67</td><td>-----</td><td>-----</td><td>91.93</td><td>26.80</td><td>8.09</td><td>32.59</td><td>9.44</td><td>354</td><td>16 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	103.67	-----	-----	91.93	26.80	8.09	32.59	9.44	354	16 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2389.17	48.75	54.00	-5.25	37.22	26.61	8.06	32.58	9.44	354	16 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2412.00	103.67	-----	-----	91.93	26.80	8.09	32.59	9.44	354	16 Average																																																																																							



Mode	5																																																																																							
	Band Edge																																																																																							
	2400-2483.5_802.11b_CH01_2412MHz																																																																																							
ANT	1																																																																																							
Pol.	Vertical						Fundamental																																																																																	
Peak	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto						Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto																																																																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.17	55.38	74.00	-18.62	43.85	26.61	8.06	32.58	9.44	100	360	Peak		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	110.13	-----	-----	98.39	26.80	8.09	32.59	9.44	100	360	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2389.17	55.38	74.00	-18.62	43.85	26.61	8.06	32.58	9.44	100	360	Peak																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2412.00	110.13	-----	-----	98.39	26.80	8.09	32.59	9.44	100	360	Peak																																																																												
Avg	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto						Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto																																																																																	
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2389.17	50.46	54.00	-3.54	38.93	26.61	8.06	32.58	9.44	100	360	Average		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2412.00	106.60	-----	-----	94.86	26.80	8.09	32.59	9.44	100	360	Average
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2389.17	50.46	54.00	-3.54	38.93	26.61	8.06	32.58	9.44	100	360	Average																																																																												
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	2412.00	106.60	-----	-----	94.86	26.80	8.09	32.59	9.44	100	360	Average																																																																												



Mode	5																																																																																							
	Harmonic																																																																																							
	2400-2483.5_802.11b_CH01_2412MHz																																																																																							
ANT	1																																																																																							
Pol.	Horizontal	Vertical																																																																																						
Peak Avg	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>44.86</td><td>74.00</td><td>-29.14</td><td>33.31</td><td>32.20</td><td>11.53</td><td>33.55</td><td>1.37</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	44.86	74.00	-29.14	33.31	32.20	11.53	33.55	1.37	--	Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4824.00</td><td>45.06</td><td>74.00</td><td>-28.94</td><td>33.51</td><td>32.20</td><td>11.53</td><td>33.55</td><td>1.37</td><td>--</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4824.00	45.06	74.00	-28.94	33.51	32.20	11.53	33.55	1.37	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	4824.00	44.86	74.00	-29.14	33.31	32.20	11.53	33.55	1.37	--	Peak																																																																													
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																														
1	4824.00	45.06	74.00	-28.94	33.51	32.20	11.53	33.55	1.37	--	Peak																																																																													



Mode	5	
	Harmonic	
	2400-2483.5_802.11b_CH01_2412MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL



Mode	6																																																																																																
	Band Edge - L																																																																																																
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																
ANT	1																																																																																																
Pol.	Horizontal						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2322.07</td><td>50.25</td><td>74.00</td><td>-23.75</td><td>38.49</td><td>26.90</td><td>7.96</td><td>32.53</td><td>9.43</td><td>379</td><td>22 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2322.07	50.25	74.00	-23.75	38.49	26.90	7.96	32.53	9.43	379	22 Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>110.91</td><td>-----</td><td>-----</td><td>99.26</td><td>26.68</td><td>8.13</td><td>32.61</td><td>9.45</td><td>379</td><td>22 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	110.91	-----	-----	99.26	26.68	8.13	32.61	9.45	379	22 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2322.07	50.25	74.00	-23.75	38.49	26.90	7.96	32.53	9.43	379	22 Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	110.91	-----	-----	99.26	26.68	8.13	32.61	9.45	379	22 Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2361.44</td><td>38.89</td><td>54.00</td><td>-15.11</td><td>27.10</td><td>26.90</td><td>8.02</td><td>32.56</td><td>9.43</td><td>379</td><td>22 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2361.44	38.89	54.00	-15.11	27.10	26.90	8.02	32.56	9.43	379	22 Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>107.56</td><td>-----</td><td>-----</td><td>95.94</td><td>26.66</td><td>8.12</td><td>32.61</td><td>9.45</td><td>379</td><td>22 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	107.56	-----	-----	95.94	26.66	8.12	32.61	9.45	379	22 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2361.44	38.89	54.00	-15.11	27.10	26.90	8.02	32.56	9.43	379	22 Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	107.56	-----	-----	95.94	26.66	8.12	32.61	9.45	379	22 Average																																																																																						



Mode	6										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Horizontal						Fundamental				
Peak	<										



Mode	6																																																																																																
	Band Edge - L																																																																																																
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																
ANT	1																																																																																																
Pol.	Vertical						Fundamental																																																																																										
Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2368.67</td><td>50.05</td><td>74.00</td><td>-23.95</td><td>38.24</td><td>26.90</td><td>8.03</td><td>32.56</td><td>9.44</td><td>275</td><td>18 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2368.67	50.05	74.00	-23.95	38.24	26.90	8.03	32.56	9.44	275	18 Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>111.87</td><td>-----</td><td>-----</td><td>100.22</td><td>26.68</td><td>8.13</td><td>32.61</td><td>9.45</td><td>275</td><td>18 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	111.87	-----	-----	100.22	26.68	8.13	32.61	9.45	275	18 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2368.67	50.05	74.00	-23.95	38.24	26.90	8.03	32.56	9.44	275	18 Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	111.87	-----	-----	100.22	26.68	8.13	32.61	9.45	275	18 Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2363.09</td><td>39.52</td><td>54.00</td><td>-14.48</td><td>27.73</td><td>26.90</td><td>8.02</td><td>32.56</td><td>9.43</td><td>275</td><td>18 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2363.09	39.52	54.00	-14.48	27.73	26.90	8.02	32.56	9.43	275	18 Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2437.00</td><td>108.58</td><td>-----</td><td>-----</td><td>96.93</td><td>26.68</td><td>8.13</td><td>32.61</td><td>9.45</td><td>275</td><td>18 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2437.00	108.58	-----	-----	96.93	26.68	8.13	32.61	9.45	275	18 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																							
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2363.09	39.52	54.00	-14.48	27.73	26.90	8.02	32.56	9.43	275	18 Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																							
1	2437.00	108.58	-----	-----	96.93	26.68	8.13	32.61	9.45	275	18 Average																																																																																						



Mode	6										
	Band Edge - R										
	2400-2483.5_802.11b_CH06_2437MHz										
ANT	1										
Pol.	Vertical										Fundamental
Peak	</										



Mode	6																																																																																																																																																						
	Harmonic																																																																																																																																																						
	2400-2483.5_802.11b_CH06_2437MHz																																																																																																																																																						
ANT	1																																																																																																																																																						
Pol.	Horizontal						Vertical																																																																																																																																																
Peak Avg																																																																																																																																																							
	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>45.66</td><td>74.00</td><td>-28.34</td><td></td><td>34.05</td><td>32.30</td><td>11.60</td><td>33.55</td><td>1.26</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>49.52</td><td>74.00</td><td>-24.48</td><td></td><td>33.07</td><td>37.20</td><td>14.28</td><td>36.03</td><td>1.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7311.00</td><td>39.76</td><td>54.00</td><td>-14.24</td><td></td><td>23.31</td><td>37.20</td><td>14.28</td><td>36.03</td><td>1.00</td><td>--</td><td>--</td><td>Average</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	4874.00	45.66	74.00	-28.34		34.05	32.30	11.60	33.55	1.26	--	--	Peak	2	7311.00	49.52	74.00	-24.48		33.07	37.20	14.28	36.03	1.00	--	--	Peak	3	7311.00	39.76	54.00	-14.24		23.31	37.20	14.28	36.03	1.00	--	--	Average	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Line</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr><tr><td>1</td><td>4874.00</td><td>45.29</td><td>74.00</td><td>-28.71</td><td></td><td>33.68</td><td>32.30</td><td>11.60</td><td>33.55</td><td>1.26</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7311.00</td><td>49.79</td><td>74.00</td><td>-24.21</td><td></td><td>33.34</td><td>37.20</td><td>14.28</td><td>36.03</td><td>1.00</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7311.00</td><td>39.87</td><td>54.00</td><td>-14.13</td><td></td><td>23.42</td><td>37.20</td><td>14.28</td><td>36.03</td><td>1.00</td><td>--</td><td>--</td><td>Average</td></tr></table>							Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark		MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg		1	4874.00	45.29	74.00	-28.71		33.68	32.30	11.60	33.55	1.26	--	--	Peak	2	7311.00	49.79	74.00	-24.21		33.34	37.20	14.28	36.03	1.00	--	--	Peak	3	7311.00	39.87	54.00	-14.13		23.42	37.20	14.28	36.03	1.00	--	--
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																											
1	4874.00	45.66	74.00	-28.34		34.05	32.30	11.60	33.55	1.26	--	--	Peak																																																																																																																																										
2	7311.00	49.52	74.00	-24.48		33.07	37.20	14.28	36.03	1.00	--	--	Peak																																																																																																																																										
3	7311.00	39.76	54.00	-14.24		23.31	37.20	14.28	36.03	1.00	--	--	Average																																																																																																																																										
	Freq	Level	Limit	Line	Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																										
	MHz	dBuV/m	dBuV/m	dB		dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																											
1	4874.00	45.29	74.00	-28.71		33.68	32.30	11.60	33.55	1.26	--	--	Peak																																																																																																																																										
2	7311.00	49.79	74.00	-24.21		33.34	37.20	14.28	36.03	1.00	--	--	Peak																																																																																																																																										
3	7311.00	39.87	54.00	-14.13		23.42	37.20	14.28	36.03	1.00	--	--	Average																																																																																																																																										



Mode	6	
	Harmonic	
	2400-2483.5_802.11b_CH06_2437MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL



Mode	7																																																																																			
	Band Edge																																																																																			
	2400-2483.5_802.11b_CH11_2462MHz																																																																																			
ANT	1																																																																																			
Pol.	Horizontal						Fundamental																																																																													
Peak	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 2484.91</td><td>54.23</td><td>74.00</td><td>-19.77</td><td>42.48</td><td>26.75</td><td>8.18</td><td>32.64</td><td>9.46</td><td>291</td><td>38</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.91	54.23	74.00	-19.77	42.48	26.75	8.18	32.64	9.46	291	38	Peak	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 2462.00</td><td>109.10</td><td>-----</td><td>-----</td><td>97.43</td><td>26.68</td><td>8.15</td><td>32.62</td><td>9.46</td><td>291</td><td>38</td><td>Peak</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	109.10	-----	-----	97.43	26.68	8.15	32.62	9.46	291	38	Peak
	Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.91	54.23	74.00	-19.77	42.48	26.75	8.18	32.64	9.46	291	38	Peak																																																																									
Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	109.10	-----	-----	97.43	26.68	8.15	32.62	9.46	291	38	Peak																																																																									
Avg	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 2484.72</td><td>47.15</td><td>54.00</td><td>-6.85</td><td>35.40</td><td>26.75</td><td>8.18</td><td>32.64</td><td>9.46</td><td>291</td><td>38</td><td>Average</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2484.72	47.15	54.00	-6.85	35.40	26.75	8.18	32.64	9.46	291	38	Average	Level (dBuV/m) Date: 2025-10-31 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th>Freq</th><th>Level</th><th>Limit</th><th>Line Margin</th><th>Read Level Factor</th><th>Ant Level Factor</th><th>Cable Loss Factor</th><th>Preamp Factor</th><th>Aux Factor</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th><th></th></tr></thead><tbody><tr><td>1 2462.00</td><td>105.76</td><td>-----</td><td>-----</td><td>94.09</td><td>26.68</td><td>8.15</td><td>32.62</td><td>9.46</td><td>291</td><td>38</td><td>Average</td></tr></tbody></table>						Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg		1 2462.00	105.76	-----	-----	94.09	26.68	8.15	32.62	9.46	291	38	Average
	Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2484.72	47.15	54.00	-6.85	35.40	26.75	8.18	32.64	9.46	291	38	Average																																																																									
Freq	Level	Limit	Line Margin	Read Level Factor	Ant Level Factor	Cable Loss Factor	Preamp Factor	Aux Factor	APos	TPos	Remark																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																										
1 2462.00	105.76	-----	-----	94.09	26.68	8.15	32.62	9.46	291	38	Average																																																																									



Mode	7																																																																																																		
	Band Edge																																																																																																		
	2400-2483.5_802.11b_CH11_2462MHz																																																																																																		
ANT	1																																																																																																		
Pol.	Vertical						Fundamental																																																																																												
Peak	Level (dBuV/m) Date: 2025-10-31 PEAK_BE_74						Level (dBuV/m) Date: 2025-10-31 PEAK_74																																																																																												
	Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2485.10</td><td>55.91</td><td>74.00</td><td>-18.09</td><td>44.16</td><td>26.75</td><td>8.18</td><td>32.64</td><td>9.46</td><td>300</td><td>354</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2485.10	55.91	74.00	-18.09	44.16	26.75	8.18	32.64	9.46	300	354	Peak	Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>110.03</td><td>-----</td><td>-----</td><td>98.36</td><td>26.68</td><td>8.15</td><td>32.62</td><td>9.46</td><td>300</td><td>354</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	110.03	-----	-----	98.36	26.68	8.15	32.62	9.46	300	354
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2485.10	55.91	74.00	-18.09	44.16	26.75	8.18	32.64	9.46	300	354	Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2462.00	110.03	-----	-----	98.36	26.68	8.15	32.62	9.46	300	354	Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-10-31 AVG_BE_54						Level (dBuV/m) Date: 2025-10-31 AVG_54																																																																																												
	Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.76</td><td>50.30</td><td>54.00</td><td>-3.70</td><td>38.55</td><td>26.75</td><td>8.18</td><td>32.64</td><td>9.46</td><td>300</td><td>354</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.76	50.30	54.00	-3.70	38.55	26.75	8.18	32.64	9.46	300	354	Average	Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2462.00</td><td>106.69</td><td>-----</td><td>-----</td><td>95.02</td><td>26.68</td><td>8.15</td><td>32.62</td><td>9.46</td><td>300</td><td>354</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2462.00	106.69	-----	-----	95.02	26.68	8.15	32.62	9.46	300	354
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2484.76	50.30	54.00	-3.70	38.55	26.75	8.18	32.64	9.46	300	354	Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																											
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																									
1	2462.00	106.69	-----	-----	95.02	26.68	8.15	32.62	9.46	300	354	Average																																																																																							

7

Mode

Harmonic

2400-2483.5_802.11b_CH11_2462MHz

ANT

1

Pol.

Horizontal

Vertical

Peak

Avg

Level (dBuV/m)

Date: 2025-10-31

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

3000

6000

9000

12000

15000

18000

PEAK_74

AVG_54

1

2

Site : 03CH22-HY

Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL

	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	4924.00	46.39	74.00	-27.61	34.61	32.50	11.67	33.54	1.15	--	--	Peak
2	7386.00	49.67	74.00	-24.33	33.32	37.13	14.28	36.09	1.03	--	--	Peak
3	7386.00	39.75	54.00	-14.25	23.40	37.13	14.28	36.09	1.03	--	--	Average

Level (dBuV/m)

Date: 2025-10-31

140

122.5

105.0

87.5

70.0

52.5

35.0

17.5

0

3000

6000

9000

12000

15000

18000

PEAK_74

AVG_54

1

2

Site : 03CH22-HY

Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL

	Freq	Level	Limit	Line Margin	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	
1	4924.00	45.53	74.00	-28.47	33.75	32.50	11.67	33.54	1.15	--	--	Peak
2	7386.00	49.96	74.00	-24.04	33.61	37.13	14.28	36.09	1.03	--	--	Peak
3	7386.00	39.98	54.00	-14.02	23.63	37.13	14.28	36.09	1.03	--	--	Average



Mode	7	
	Harmonic	
	2400-2483.5_802.11b_CH11_2462MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL



Mode	8																																																																																	
	Band Edge																																																																																	
	2400-2483.5_802.11b_CH12_2467MHz																																																																																	
ANT	1																																																																																	
Pol.	Horizontal					Fundamental																																																																												
Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 2483.93</td><td>55.60</td><td>74.00</td><td>-18.40</td><td>43.86</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 2483.93	55.60	74.00	-18.40	43.86	26.74	8.18	32.64	9.46	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 2467.00</td><td>104.31</td><td>-----</td><td>-----</td><td>92.70</td><td>26.62</td><td>8.16</td><td>32.63</td><td>9.46</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 2467.00	104.31	-----	-----	92.70	26.62	8.16	32.63	9.46
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																																										
1 2483.93	55.60	74.00	-18.40	43.86	26.74	8.18	32.64	9.46																																																																										
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																																										
1 2467.00	104.31	-----	-----	92.70	26.62	8.16	32.63	9.46																																																																										
Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 2484.15</td><td>49.02</td><td>54.00</td><td>-4.98</td><td>37.28</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 2484.15	49.02	54.00	-4.98	37.28	26.74	8.18	32.64	9.46	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th></tr><tr><td>1 2467.00</td><td>100.92</td><td>-----</td><td>-----</td><td>89.29</td><td>26.64</td><td>8.16</td><td>32.63</td><td>9.46</td></tr></table>					Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	1 2467.00	100.92	-----	-----	89.29	26.64	8.16	32.63	9.46
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																																										
1 2484.15	49.02	54.00	-4.98	37.28	26.74	8.18	32.64	9.46																																																																										
Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																										
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB																																																																										
1 2467.00	100.92	-----	-----	89.29	26.64	8.16	32.63	9.46																																																																										



Mode	8																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH12_2467MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.62</td><td>56.78</td><td>74.00</td><td>-17.22</td><td>45.04</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>300</td><td>0 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2483.62	56.78	74.00	-17.22	45.04	26.74	8.18	32.64	9.46	300	0 Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2467.00</td><td>105.48</td><td>-----</td><td>-----</td><td>93.87</td><td>26.62</td><td>8.16</td><td>32.63</td><td>9.46</td><td>300</td><td>0 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2467.00	105.48	-----	-----	93.87	26.62	8.16	32.63	9.46	300	0 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2483.62	56.78	74.00	-17.22	45.04	26.74	8.18	32.64	9.46	300	0 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2467.00	105.48	-----	-----	93.87	26.62	8.16	32.63	9.46	300	0 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.15</td><td>50.74</td><td>54.00</td><td>-3.26</td><td>39.00</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>300</td><td>0 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2484.15	50.74	54.00	-3.26	39.00	26.74	8.18	32.64	9.46	300	0 Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2467.00</td><td>102.14</td><td>-----</td><td>-----</td><td>90.53</td><td>26.62</td><td>8.16</td><td>32.63</td><td>9.46</td><td>300</td><td>0 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	2467.00	102.14	-----	-----	90.53	26.62	8.16	32.63	9.46	300	0 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2484.15	50.74	54.00	-3.26	39.00	26.74	8.18	32.64	9.46	300	0 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																								
1	2467.00	102.14	-----	-----	90.53	26.62	8.16	32.63	9.46	300	0 Average																																																																																							







Mode	8																																																																																																																																																
	Harmonic																																																																																																																																																
	2400-2483.5_802.11b_CH12_2467MHz																																																																																																																																																
ANT	1																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th rowspan="2">Freq</th><th rowspan="2">Level</th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th rowspan="2">APos</th><th rowspan="2">TPos</th><th rowspan="2">Remark</th></tr><tr><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4934.00</td><td>46.75</td><td>74.00</td><td>-27.25</td><td>34.94</td><td>32.54</td><td>11.68</td><td>33.54</td><td>1.13</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>7401.00</td><td>50.30</td><td>74.00</td><td>-23.70</td><td>33.98</td><td>37.10</td><td>14.28</td><td>36.10</td><td>1.04</td><td>--</td><td>-- Peak</td></tr><tr><td>3</td><td>7401.00</td><td>40.31</td><td>54.00</td><td>-13.69</td><td>23.99</td><td>37.10</td><td>14.28</td><td>36.10</td><td>1.04</td><td>--</td><td>-- Average</td></tr></table>						Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4934.00	46.75	74.00	-27.25	34.94	32.54	11.68	33.54	1.13	--	-- Peak	2	7401.00	50.30	74.00	-23.70	33.98	37.10	14.28	36.10	1.04	--	-- Peak	3	7401.00	40.31	54.00	-13.69	23.99	37.10	14.28	36.10	1.04	--	-- Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th rowspan="2">Freq</th><th rowspan="2">Level</th><th colspan="2">Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th rowspan="2">APos</th><th rowspan="2">TPos</th><th rowspan="2">Remark</th></tr><tr><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4934.00</td><td>45.70</td><td>74.00</td><td>-28.30</td><td>33.89</td><td>32.54</td><td>11.68</td><td>33.54</td><td>1.13</td><td>--</td><td>-- Peak</td></tr><tr><td>2</td><td>7401.00</td><td>49.77</td><td>74.00</td><td>-24.23</td><td>33.45</td><td>37.10</td><td>14.28</td><td>36.10</td><td>1.04</td><td>--</td><td>-- Peak</td></tr><tr><td>3</td><td>7401.00</td><td>39.93</td><td>54.00</td><td>-14.07</td><td>23.61</td><td>37.10</td><td>14.28</td><td>36.10</td><td>1.04</td><td>--</td><td>-- Average</td></tr></table>					Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4934.00	45.70	74.00	-28.30	33.89	32.54	11.68	33.54	1.13	--	-- Peak	2	7401.00	49.77	74.00	-24.23	33.45	37.10	14.28	36.10	1.04	--	-- Peak	3	7401.00	39.93	54.00	-14.07	23.61	37.10	14.28	36.10	1.04	--	-- Average
	Freq	Level	Limit		Read	Ant			Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																			
			Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1	4934.00	46.75	74.00	-27.25	34.94	32.54	11.68	33.54	1.13	--	-- Peak																																																																																																																																						
2	7401.00	50.30	74.00	-23.70	33.98	37.10	14.28	36.10	1.04	--	-- Peak																																																																																																																																						
3	7401.00	40.31	54.00	-13.69	23.99	37.10	14.28	36.10	1.04	--	-- Average																																																																																																																																						
Freq	Level	Limit		Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																						
		Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																						
1	4934.00	45.70	74.00	-28.30	33.89	32.54	11.68	33.54	1.13	--	-- Peak																																																																																																																																						
2	7401.00	49.77	74.00	-24.23	33.45	37.10	14.28	36.10	1.04	--	-- Peak																																																																																																																																						
3	7401.00	39.93	54.00	-14.07	23.61	37.10	14.28	36.10	1.04	--	-- Average																																																																																																																																						



Mode	8	
	Harmonic	
	2400-2483.5_802.11b_CH12_2467MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL



Mode	9																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH13_2472MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Horizontal						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-11-01  Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.96</td><td>54.51</td><td>74.00</td><td>-19.49</td><td>42.77</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>362</td><td>25 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	2483.96	54.51	74.00	-19.49	42.77	26.74	8.18	32.64	9.46	362	25 Peak	Level (dBuV/m) Date: 2025-11-01  Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2472.00</td><td>101.38</td><td>-----</td><td>-----</td><td>89.76</td><td>26.62</td><td>8.17</td><td>32.63</td><td>9.46</td><td>362</td><td>25 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	2472.00	101.38	-----	-----	89.76	26.62	8.17	32.63	9.46	362	25 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																								
1	2483.96	54.51	74.00	-19.49	42.77	26.74	8.18	32.64	9.46	362	25 Peak																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																								
1	2472.00	101.38	-----	-----	89.76	26.62	8.17	32.63	9.46	362	25 Peak																																																																																							
Avg	Level (dBuV/m) Date: 2025-11-01  Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.89</td><td>48.20</td><td>54.00</td><td>-5.80</td><td>36.46</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>362</td><td>25 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	2483.89	48.20	54.00	-5.80	36.46	26.74	8.18	32.64	9.46	362	25 Average	Level (dBuV/m) Date: 2025-11-01  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2472.00</td><td>98.04</td><td>-----</td><td>-----</td><td>86.42</td><td>26.62</td><td>8.17</td><td>32.63</td><td>9.46</td><td>362</td><td>25 Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg	1	2472.00	98.04	-----	-----	86.42	26.62	8.17	32.63	9.46	362	25 Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																								
1	2483.89	48.20	54.00	-5.80	36.46	26.74	8.18	32.64	9.46	362	25 Average																																																																																							
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																										
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	dB	cm	deg																																																																																								
1	2472.00	98.04	-----	-----	86.42	26.62	8.17	32.63	9.46	362	25 Average																																																																																							



Mode	9																																																																																																	
	Band Edge																																																																																																	
	2400-2483.5_802.11b_CH13_2472MHz																																																																																																	
ANT	1																																																																																																	
Pol.	Vertical						Fundamental																																																																																											
Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_BE_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2484.12</td><td>56.28</td><td>74.00</td><td>-17.72</td><td>44.54</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>299</td><td>0</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2484.12	56.28	74.00	-17.72	44.54	26.74	8.18	32.64	9.46	299	0	Peak	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2472.00</td><td>103.58</td><td>-----</td><td>-----</td><td>91.96</td><td>26.62</td><td>8.17</td><td>32.63</td><td>9.46</td><td>299</td><td>0</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2472.00	103.58	-----	-----	91.96	26.62	8.17	32.63	9.46	299	0	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2484.12	56.28	74.00	-17.72	44.54	26.74	8.18	32.64	9.46	299	0	Peak																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2472.00	103.58	-----	-----	91.96	26.62	8.17	32.63	9.46	299	0	Peak																																																																																						
Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_BE_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2483.77</td><td>50.17</td><td>54.00</td><td>-3.83</td><td>38.43</td><td>26.74</td><td>8.18</td><td>32.64</td><td>9.46</td><td>299</td><td>0</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2483.77	50.17	54.00	-3.83	38.43	26.74	8.18	32.64	9.46	299	0	Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2472.00</td><td>100.24</td><td>-----</td><td>-----</td><td>88.60</td><td>26.64</td><td>8.17</td><td>32.63</td><td>9.46</td><td>299</td><td>0</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg	1	2472.00	100.24	-----	-----	88.60	26.64	8.17	32.63	9.46	299	0	Average
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																								
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2483.77	50.17	54.00	-3.83	38.43	26.74	8.18	32.64	9.46	299	0	Average																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																									
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor	Factor																																																																																												
	MHz	dBuV/m	dBuV/m	dB	dB/m	dB	dB	cm	deg																																																																																									
1	2472.00	100.24	-----	-----	88.60	26.64	8.17	32.63	9.46	299	0	Average																																																																																						



Mode	9																																																																																																																																																																					
	Harmonic																																																																																																																																																																					
	2400-2483.5_802.11b_CH13_2472MHz																																																																																																																																																																					
ANT	1																																																																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																																																																															
Peak Avg	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th colspan="2">Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th colspan="2"></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4944.00</td><td>45.50</td><td>74.00</td><td>-28.50</td><td>33.66</td><td>32.58</td><td>11.69</td><td>33.54</td><td>1.11</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7416.00</td><td>49.34</td><td>74.00</td><td>-24.66</td><td>32.96</td><td>37.16</td><td>14.29</td><td>36.11</td><td>1.04</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7416.00</td><td>39.40</td><td>54.00</td><td>-14.60</td><td>23.02</td><td>37.16</td><td>14.29</td><td>36.11</td><td>1.04</td><td>--</td><td>--</td><td>Average</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq		Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4944.00	45.50	74.00	-28.50	33.66	32.58	11.69	33.54	1.11	--	--	Peak	2	7416.00	49.34	74.00	-24.66	32.96	37.16	14.29	36.11	1.04	--	--	Peak	3	7416.00	39.40	54.00	-14.60	23.02	37.16	14.29	36.11	1.04	--	--	Average	Level (dBuV/m) Date: 2025-11-01 Site : 03CH22-HY Condition: PEAK_74 3m DRH18-E_LE2C04A18EN_250520 VERTICAL <table><tr><th colspan="2"></th><th colspan="2">Limit</th><th colspan="2">Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th rowspan="2">Remark</th></tr><tr><th colspan="2">Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>Factor</th><th></th><th></th></tr><tr><th colspan="2"></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4944.00</td><td>46.03</td><td>74.00</td><td>-27.97</td><td>34.19</td><td>32.58</td><td>11.69</td><td>33.54</td><td>1.11</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>2</td><td>7416.00</td><td>49.48</td><td>74.00</td><td>-24.52</td><td>33.10</td><td>37.16</td><td>14.29</td><td>36.11</td><td>1.04</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>3</td><td>7416.00</td><td>39.56</td><td>54.00</td><td>-14.44</td><td>23.18</td><td>37.16</td><td>14.29</td><td>36.11</td><td>1.04</td><td>--</td><td>--</td><td>Average</td></tr></table>								Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq		Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	4944.00	46.03	74.00	-27.97	34.19	32.58	11.69	33.54	1.11	--	--	Peak	2	7416.00	49.48	74.00	-24.52	33.10	37.16	14.29	36.11	1.04	--	--	Peak	3	7416.00	39.56	54.00	-14.44	23.18	37.16	14.29	36.11	1.04	--	--	Average
			Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
	Freq		Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																																																																																																												
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																										
1	4944.00	45.50	74.00	-28.50	33.66	32.58	11.69	33.54	1.11	--	--	Peak																																																																																																																																																										
2	7416.00	49.34	74.00	-24.66	32.96	37.16	14.29	36.11	1.04	--	--	Peak																																																																																																																																																										
3	7416.00	39.40	54.00	-14.60	23.02	37.16	14.29	36.11	1.04	--	--	Average																																																																																																																																																										
		Limit		Read		Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																										
Freq		Level	Line Margin	Level	Factor	Loss	Factor	Factor	Factor																																																																																																																																																													
		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																										
1	4944.00	46.03	74.00	-27.97	34.19	32.58	11.69	33.54	1.11	--	--	Peak																																																																																																																																																										
2	7416.00	49.48	74.00	-24.52	33.10	37.16	14.29	36.11	1.04	--	--	Peak																																																																																																																																																										
3	7416.00	39.56	54.00	-14.44	23.18	37.16	14.29	36.11	1.04	--	--	Average																																																																																																																																																										



Mode	9	
	Harmonic	
	2400-2483.5_802.11b_CH13_2472MHz	
ANT	1	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 HORIZONTAL	Level (dBuV/m) Date: 2025-11-13 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_250520 VERTICAL