FCC Test Report

Report No.: AGC01576150502FE03

FCC ID	:	2AEUVBTR200
APPLICATION PURPOSE	:	Original Equipment
PRODUCT DESIGNATION	:	Home HD Bluetooth Receiver
BRAND NAME	:	KINIVO
MODEL NAME	:	BTR200
CLIENT	:	Kinivo Inc
DATE OF ISSUE	:	May 28,2015
STANDARD(S) **TEST PROCEDURE(S)**	:	FCC Part 15 Rules
REPORT VERSION	:	V1.0

Attestation of ***G***lobal ***C***ompliance (Shenzhen) Co., Ltd

CAUTION:
This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	/	May 28,2015	Valid	Original Report

TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY 4
2. GENERAL INFORMATION 5
2.1. PRODUCT DESCRIPTION 5
2.2. TABLE OF CARRIER FREQUENCYS 5
3. MEASUREMENT UNCERTAINTY 6
4. DESCRIPTION OF TEST MODES 6
5. SYSTEM TEST CONFIGURATION 7
5.1. CONFIGURATION OF EUT SYSTEM 7
5.2. EQUIPMENT USED IN EUT SYSTEM 7
5.3. SUMMARY OF TEST RESULTS 7
6. TEST FACILITY 8
7 ALL TEST EQUIPMENT LIST 8
8. RADIATED EMISSION 9
8.1TEST LIMIT 9
8.2. MEASUREMENT PROCEDURE 10
8.3. TEST SETUP 12
8.4. TEST RESULT(Worst modulation:GFSK) 14
9. BAND EDGE EMISSION 27
9.1. MEASUREMENT PROCEDURE 27
9.2 TEST SETUP 27
9.3 RADIATED TEST RESULT(Worst modulation:GFSK) 28
10. 20DB BANDWIDTH 32
10.1. MEASUREMENT PROCEDURE 32
10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) 32
10.3. LIMITS AND MEASUREMENT RESULTS 32
11. FCC LINE CONDUCTED EMISSION TEST 39
11.1. LIMITS OF LINE CONDUCTED EMISSION TEST 39
11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST 39
11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST 40
11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST 40
11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST 41
APPENDIX A: PHOTOGRAPHS OF TEST SETUP 43
APPENDIX B: PHOTOGRAPHS OF EUT 45

1. VERIFICATION OF CONFORMITY

Applicant	Kinivo Inc
Address	8573 154th Ave NE Redmond, WA 98052 United States
Manufacturer	LANYA ELECTRONIC CO., Ltd
Address	3/F, Building 6, Lijincheng Industrial Park, Gongyedong Road, Longhua Town, Baoan District, Shenzhen, China.
Product Designation	Home HD Bluetooth Receiver
Brand Name	KINIVO
Test Model	BTR200
Date of test	May 26,2015 to May 27,2015
Deviation	None
Condition of Test Sample	Normal
Report Template	AGCRT-US-BR/RF

We hereby certify that:

The above equipment was tested by Compliance Certification Service(Shenzhen) Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4 (2009) and the energy emitted by the sample EUT tested as described in this report is in compliance with radiated emission limits of FCC Rules Part 15.249.

Prepared By	Time Huang	May 28,2015
Checked By	Forrest Lei	May 28,2015
Authorized By	Solger Zhang	May 28,2015

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	3.36dBm(Max)
Bluetooth Version	V 3.0
Modulation	GFSK, π /4-DQPSK, 8DPSK
Number of channels	79
Hardware Version	BTR200
Software Version	BTR200
Antenna Designation	PCB Antenna (Met 15.203 Antenna requirement)
Antenna Gain	2dBi
Power Supply	DC5V by adapter Adapter Input :AC100~240V/50/60Hz
Note: The USB port only used for power supply and can't be used to transfer data with PC.	

2.2. TABLE OF CARRIER FREQUENCYS

Frequency Band	Channel Number	Frequency
2400~2483.5MHZ	0	2402MHZ
	1	2403MHZ
	:	:
	38	2440 MHZ
	39	2441 MHZ
	40	2442 MHZ
	:	:
	77	2479 MHZ
	78	2480 MHZ

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U，where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2，providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±3.18dB
2	All emissions,radiated	±3.91dB
3	Temperature	±0.5°C
4	Humidity	±2%

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
1	Low channel GFSK
2	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
9	High channel 8DPSK
10	Normal operation (BT)

Note:
1. Only the result of the worst case was recorded in the report, if no other cases.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.

5. SYSTEM TEST CONFIGURATION

5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

Item	Equipment	Model No.	ID or Specification	Remark
1	Home HD Bluetooth Receiver	KINIVO	BTR200	EUT
2	Control box	N/A	N/A	A.E
3	PC	Dell	INSPIRON	A.E

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249	Radiated Emission	Compliant
§15.249	Band Edges	Compliant
§15.207	Conduction Emission	Compliant
N/A	BANDWITH	Compliant

6. TEST FACILITY

Site	Compliance Certification Service(Shenzhen) Inc.
Location	No.10-1 Mingkeda Logistics Park, No.18 Huanguan South RD. Guan lan Town,Baoan Distr
FCC Registration No.	441872
Description	The test site is constructed and calibrated to meet the FCC requirements in documents ANSI C63.4:2009.

7 ALL TEST EQUIPMENT LIST

Radiated Emission Test Site 966(2)					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
PSA Series Spectrum Analyzer	Agilent	E4446A	US44300399	03/01/2015	03/01/2016
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2015	03/08/2016
Amplifier	MITEQ	AM-1604-3000	1123808	03/18/2015	03/17/2016
High Noise Amplifier	Agilent	8449B	3008A01838	03/18/2015	03/17/2016
Board-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170-497	07/10/2014	07/09/2015
Bilog Antenna	SCHAFFNER	CBL6143	5082	03/01/2015	03/01/2016
Horn Antenna	SCHWARZBECK	BBHA9120	D286	03/01/2015	03/01/2016
Loop Antenna	COM-POWER	AL-130	121044	09/27/2014	09/26/2015
Turn Table	N/A	N/A	N/A	N.C.R	N.C.R
Controller	Sunol Sciences	SC104V	022310-1	N.C.R	N.C.R
Controller	CT	N/A	N/A	N.C.R	N.C.R
Temp. / Humidity Meter	Anymetre	JR913	N/A	02/28/2015	02/27/2016
Antenna Tower	SUNOL	TLT2	N/A	N.C.R	N.C.R
Test S/W	FARAD	LZ-RF / CCS-SZ-3A2			

Conducted Emission Test Site					
Name of Equipment	**Manufacturer**	**Model Number**	**Serial Number**	**Last Calibration**	**Due Calibration**
EMI TEST RECEIVER	ROHDE&SCHWARZ	ESCI	100783	03/09/2015	03/08/2016
LISN(EUT)	ROHDE&SCHWARZ	ENV216	101543-WX	03/09/2015	03/08/2016
LISN	EMCO	3825/2	8901-1459	03/09/2015	03/08/2016
Temp. / Humidity Meter	VICTOR	HTC-1	N/A	03/04/2015	03/03/2016
Test S/W	FARAD	EZ-EMC/ CCS-3A1-CE			

8. RADIATED EMISSION

8.1TEST LIMIT

Standard FCC15.249

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency (MHz)	Distance Meters	Field Strengths Limit	
		μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	---
0.490 ~ 1.705	30	24000/F(kHz)	---
1.705 ~ 30	30	30	---
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	Other:74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Remark: (1) Emission level dB μ V = 20 log Emission level μ V/m

(2) The smaller limit shall apply at the cross point between two frequency bands.

(3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

8.2. MEASUREMENT PROCEDURE

1. Configure the EUT according to ANSI C63.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.

The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	1GHz~26.5GHz 1MHz/1MHz for Peak, 1MHz/10Hz for Average

Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP

8.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz



8.4. TEST RESULT(Worst modulation:GFSK)

RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

RADIATED EMISSION BELOW 1GHZ

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	17.24	11.51	28.75	40.00	-11.25	peak			
2		127.0000	9.65	13.03	22.68	43.50	-20.82	peak			
3		191.6667	17.43	11.61	29.04	43.50	-14.46	peak			
4		256.3333	14.82	14.09	28.91	46.00	-17.09	peak			
5		308.0667	9.27	15.95	25.22	46.00	-20.78	peak			
6		603.9167	1.72	23.74	25.46	46.00	-20.54	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-LOW CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Low Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	20.64	8.51	29.15	40.00	-10.85	peak			
2		88.2000	20.68	4.74	25.42	43.50	-18.08	peak			
3		131.8500	14.94	11.80	26.74	43.50	-16.76	peak			
4		169.0333	10.44	14.76	25.20	43.50	-18.30	peak			
5		261.1833	9.01	14.24	23.25	46.00	-22.75	peak			
6		594.2167	8.35	22.70	31.05	46.00	-14.95	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Middle Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	17.42	11.51	28.93	40.00	-11.07	peak			
2		149.6333	11.04	15.26	26.30	43.50	-17.20	peak			
3		199.7500	17.14	11.99	29.13	43.50	-14.37	peak			
4		256.3333	17.85	14.09	31.94	46.00	-14.06	peak			
5		563.5000	2.71	22.82	25.53	46.00	-20.47	peak			
6		886.8333	1.26	28.27	29.53	46.00	-16.47	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)- MIDDLE CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Middle Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	21.20	8.51	29.71	40.00	-10.29	peak			
2		65.5667	19.11	5.98	25.09	40.00	-14.91	peak			
3		131.8500	14.91	11.80	26.71	43.50	-16.79	peak			
4		169.0333	10.63	14.76	25.39	43.50	-18.11	peak			
5		256.3333	10.32	14.09	24.41	46.00	-21.59	peak			
6		594.2167	8.00	22.70	30.70	46.00	-15.30	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	17.40	11.51	28.91	40.00	-11.09	peak			
2		127.0000	9.39	13.03	22.42	43.50	-21.08	peak			
3		224.0000	11.50	12.91	24.41	46.00	-21.59	peak			
4		261.1833	17.02	14.24	31.26	46.00	-14.74	peak			
5		430.9333	4.73	20.01	24.74	46.00	-21.26	peak			
6		558.6500	5.15	22.70	27.85	46.00	-18.15	peak			

RESULT: PASS

RADIATED EMISSION TEST- (30MHZ-1GHZ)-HIGH CHANNEL -VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: High Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 22.8
Humidity: 54.1 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	39.7000	18.62	8.51	27.13	40.00	-12.87	peak			
2		65.5667	17.81	5.98	23.79	40.00	-16.21	peak			
3		131.8500	15.37	11.80	27.17	43.50	-16.33	peak			
4		169.0333	8.76	14.76	23.52	43.50	-19.98	peak			
5		256.3333	10.20	14.09	24.29	46.00	-21.71	peak			
6		594.2167	7.44	22.70	30.14	46.00	-15.86	peak			

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The “Factor” value can be calculated automatically by software of measurement system.

RADIATED EMISSION ABOVE 1GHZ

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL-HORIZONTAL



Site: site #1 | Polarization: *Horizontal* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- | Power: | Humidity: 60 %
EUT: Home HD Bluetooth Receiver | Distance: 3m
M/N: BTR200
Mode: Low Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	110.23	-9.68	100.55	114.00	-13.45	peak			
2		3650.000	52.86	-6.97	45.89	74.00	-28.11	peak			
3		4875.000	48.35	-2.13	46.22	74.00	-27.78	peak			
4	*	2402.000	100.06	-9.68	90.38	94.00	-3.62	AVG	150	224	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-LOW CHANNEL- VERTICAL



Site: site #1 | Polarization: *Vertical* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- | Power: | Humidity: 60 %
EUT: Home HD Bluetooth Receiver | Distance: 3m
M/N: BTR200
Mode: Low Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2402.000	110.16	-9.68	100.48	114.00	-13.52	peak			
2		4075.000	50.41	-4.55	45.86	74.00	-28.14	peak			
3		4925.000	48.02	-2.00	46.02	74.00	-27.98	peak			
4	*	2402.000	99.41	-9.68	89.73	94.00	-4.27	AVG	150	301	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Middle Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	109.29	-9.63	99.66	114.00	-14.34	peak			
2		3650.000	51.80	-6.97	44.83	74.00	-29.17	peak			
3		5141.667	47.69	-1.80	45.89	74.00	-28.11	peak			
4	*	2441.000	100.44	-9.63	90.81	94.00	-3.19	AVG	150	253	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-MIDDLE CHANNEL- VERTICAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Middle Channel TX
Note:

Polarization: *Vertical*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2441.000	109.23	-9.63	99.60	114.00	-14.40	peak			
2		3441.667	53.59	-7.94	45.65	74.00	-28.35	peak			
3		4425.000	48.87	-3.36	45.51	74.00	-28.49	peak			
4	*	2441.000	100.77	-9.63	91.14	94.00	-2.86	AVG	150	185	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL-HORIZONTAL



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)-
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: High Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance: 3m

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	108.37	-9.59	98.78	114.00	-15.22	peak			
2		3583.333	53.85	-7.38	46.47	74.00	-27.53	peak			
3		4825.000	49.34	-2.26	47.08	74.00	-26.92	peak			
4	*	2480.000	101.31	-9.59	91.72	94.00	-2.28	AVG	150	247	

RESULT: PASS

RADIATED EMISSION TEST- (ABOVE 1GHZ)-HIGH CHANNEL- VERTICAL



Site: site #1 | Polarization: *Vertical* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK)- | Power: | Humidity: 60 %
EUT: Home HD Bluetooth Receiver | Distance: 3m
M/N: BTR200
Mode: High Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2480.000	107.30	-9.59	97.71	114.00	-16.29	peak			
2		3983.333	50.09	-4.91	45.18	74.00	-28.82	peak			
3		5275.000	48.52	-1.81	46.71	74.00	-27.29	peak			
4	*	2480.000	101.22	-9.59	91.63	94.00	-2.37	AVG	150	164	

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.
The “Factor” value can be calculated automatically by software of measurement system.

Field strength of the fundamental signal

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	110.23	-9.68	100.55	114	-13.45	Horizontal
2402	110.16	-9.68	100.48	114	-13.52	Vertical
2441	109.29	-9.63	99.66	114	-14.34	Horizontal
2441	109.23	-9.63	99.60	114	-14.40	Vertical
2480	108.37	-9.59	98.78	114	-15.22	Horizontal
2480	107.30	-9.59	97.71	114	-16.29	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	100.06	-9.68	90.38	94	-3.62	Horizontal
2402	99.41	-9.68	89.73	94	-4.27	Vertical
2441	100.44	-9.63	90.81	94	-3.19	Horizontal
2441	100.77	-9.63	91.14	94	-2.86	Vertical
2480	101.31	-9.59	91.72	94	-2.28	Horizontal
2480	101.22	-9.59	91.63	94	-2.37	Vertical

9. BAND EDGE EMISSION

9.1. MEASUREMENT PROCEDURE

1The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.

2Max hold the trace of the setp 1,and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.

3Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO

(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1KHz) / Sweep=AUTO

9.2 TEST SETUP

RADIATED EMISSION TEST SETUP



CONDUCTED TEST SETUP



9.3 RADIATED TEST RESULT(Worst modulation:GFSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Low Channel TX
Note:

Polarization: *Horizontal*
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	.	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2294.642	30.84	10.20	41.04	74.00	-32.96	peak			
2		2390.000	29.62	10.31	39.93	74.00	-34.07	peak			
3	*	2402.000	89.91	10.32	100.23	74.00	26.23	peak			

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical



Site: site #1
Limit: FCC Class B 3M Radiation above 1GHZ(PK)
EUT: Home HD Bluetooth Receiver
M/N: BTR200
Mode: Low Channel TX
Note:

Polarization: ***Vertical***
Power:
Distance:

Temperature: 26
Humidity: 60 %

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1		2250.225	30.19	10.16	40.35	74.00	-33.65	peak			
2		2390.000	28.85	10.31	39.16	74.00	-34.84	peak			
3	*	2402.000	90.26	10.32	100.58	74.00	26.58	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal



Site: site #1 Polarization: ***Horizontal*** Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) Power: Humidity: 60 %
EUT: Home HD Bluetooth Receiver Distance:
M/N: BTR200
Mode: High Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	88.46	10.41	98.87	74.00	24.87	peak			
2		2483.500	28.75	10.41	39.16	74.00	-34.84	peak			
3		2490.833	30.30	10.42	40.72	74.00	-33.28	peak			

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



Site: site #1 | Polarization: *Vertical* | Temperature: 26
Limit: FCC Class B 3M Radiation above 1GHZ(PK) | Power: | Humidity: 60 %
EUT: Home HD Bluetooth Receiver | Distance:
M/N: BTR200
Mode: High Channel TX
Note:

No.	Mk.	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
1	*	2480.000	88.35	10.41	98.76	74.00	24.76	peak			
2		2483.500	30.37	10.41	40.78	74.00	-33.22	peak			
3		2492.777	30.70	10.42	41.12	74.00	-32.88	peak			

RESULT: PASS

Note: The other modes radiation emission have enough 20dB margin.

Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

10. 20DB BANDWIDTH

10.1. MEASUREMENT PROCEDURE

1. Connect EUT RF output port to the Spectrum Analyzer through an RF attenuator
2, Set the EUT Work on the top, the middle and the bottom operation frequency individually.
3. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel
   RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

10.2. TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)



10.3. LIMITS AND MEASUREMENT RESULTS

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	0.786	PASS
	Middle Channel	0.787	PASS
	High Channel	0.785	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.289	PASS
	Middle Channel	1.240	PASS
	High Channel	1.250	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESUL			
Applicable Limits	Measurement Result		
	Test Data (MHz)		Criteria
N/A	Low Channel	1.278	PASS
	Middle Channel	1.306	PASS
	High Channel	1.247	PASS

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



11. FCC LINE CONDUCTED EMISSION TEST

11.1. LIMITS OF LINE CONDUCTED EMISSION TEST

Frequency	Maximum RF Line Voltage	
	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	56	46
5MHz~30MHz	60	50

Note:
1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

11.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



11.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.4.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.
4. All support equipments received AC120V/60Hz power from a LISN, if any.
5. The EUT received DC charging voltage by adapter which received 120V/60Hzpower by a LISN..
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

11.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.

2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.

11.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

Line Conducted Emission Test Line 1-L



Site: Conduction | Phase: *L1* | Temperature: 24.3
Limit: FCC Class B Conduction(QP) | Power: | Humidity: 53.1 %
EUT:Home HD Bluetooth Receiver
M/N: BTR200
Mode: Normal Operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5540	28.94		21.48	10.35	39.29		31.83	56.00	46.00	-16.71	-14.17	P	
2	0.6940	27.78		14.37	10.35	38.13		24.72	56.00	46.00	-17.87	-21.28	P	
3	1.4980	19.39		11.78	10.38	29.77		22.16	56.00	46.00	-26.23	-23.84	P	
4	2.6660	19.25		11.17	10.47	29.72		21.64	56.00	46.00	-26.28	-24.36	P	
5	11.7299	17.79		1.37	10.13	27.92		11.50	60.00	50.00	-32.08	-38.50	P	
6	24.6780	16.29		-1.78	10.12	26.41		8.34	60.00	50.00	-33.59	-41.66	P	

Line Conducted Emission Test Line 2-N



Site: Conduction
Phase: N
Temperature: 24.3
Limit: FCC Class B Conduction(QP)
Power:
Humidity: 53.1 %
EUT:Home HD Bluetooth Receiver
M/N: BTR200
Mode: Normal Operation with charging
Note:

No.	Freq. (MHz)	Reading_Level (dBuV)			Correct Factor	Measurement (dBuV)			Limit (dBuV)		Margin (dB)		P/F	Comment
		Peak	QP	AVG	dB	Peak	QP	AVG	QP	AVG	QP	AVG		
1	0.5620	28.02		5.26	10.34	38.36		15.60	56.00	46.00	-17.64	-30.40	P	
2	0.6980	28.89		20.04	10.35	39.24		30.39	56.00	46.00	-16.76	-15.61	P	
3	1.5300	19.79		-0.02	10.37	30.16		10.35	56.00	46.00	-25.84	-35.65	P	
4	2.5820	18.34		-1.92	10.45	28.79		8.53	56.00	46.00	-27.21	-37.47	P	
5	3.6420	15.81		-2.86	10.49	26.30		7.63	56.00	46.00	-29.70	-38.37	P	
6	11.7299	12.93		-3.63	10.13	23.06		6.50	60.00	50.00	-36.94	-43.50	P	

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP

FCC RADIATED EMISSION TEST SETUP





APPENDIX B: PHOTOGRAPHS OF EUT

All VIEW OF EUT

TOP VIEW OF EUT

BOTTOM VIEW OF EUT

FRONT VIEW OF EUT

BACK VIEW OF EUT

LEFT VIEW OF EUT

RIGHT VIEW OF EUT

VIEW OF EUT(PORT)

ADAPTER OF EUT

OPEN VIEW OF EUT



INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



INTERNAL VIEW OF EUT-6



INTERNAL VIEW OF EUT-7



----END OF REPORT----