

FCC PART 15B, CLASS B TEST REPORT

For

Jovision Technology Co.,Ltd.

Floor11, Building D, In-hi tech Square, No.2008 Xinluo Street, Jinan, Shandong, China

FCC ID: 2AEW9JVS-HC801E

Report Type: Original Report	Product Type: HD Network Camera
Report Number: RSZ170904009-00A	
Report Date: 2017-09-27	
Reviewed By: RF Engineer	Simon Wang <i>Simon wang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the Federal Government. This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★". This report may contain data were produced under the subcontractor and shall be marked with an asterisk "△".

TABLE OF CONTENTS

GENERAL INFORMATION	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	3
OBJECTIVE	3
RELATED SUBMITTAL(S)/GRANT(S)	3
TEST METHODOLOGY	3
MEASUREMENT UNCERTAINTY	4
TEST FACILITY	4
SYSTEM TEST CONFIGURATION	5
DESCRIPTION OF TEST CONFIGURATION	5
EUT EXERCISE SOFTWARE	5
SPECIAL ACCESSORIES	5
EQUIPMENT MODIFICATIONS	5
SUPPORT EQUIPMENT LIST AND DETAILS	5
EXTERNAL I/O CABLE	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
TEST EQUIPMENT LIST	8
FCC §15.107 – AC LINE CONDUCTED EMISSIONS	9
APPLICABLE STANDARD	9
EUT SETUP	9
EMI TEST RECEIVER SETUP	9
TEST PROCEDURE	9
CORRECTED FACTOR & MARGIN CALCULATION	10
TEST RESULTS SUMMARY	10
TEST DATA	10
FCC §15.109 - RADIATED SPURIOUS EMISSIONS	13
APPLICABLE STANDARD	13
EUT SETUP	13
EMI TEST RECEIVER SETUP	14
TEST PROCEDURE	14
CORRECTED AMPLITUDE & MARGIN CALCULATION	14
TEST RESULTS SUMMARY	14
TEST DATA	15

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The JOVISION TECHNOLOGY CO.,LTD.'s product, model number: JVS-HC810E (FCC ID: 2AEW9JVS-HC801E) in this report is a HD Network Camera, which was measured approximately: 66 mm (L) × 66 mm (W) × 172 mm (H), rated with input voltage: DC 12V from adapter. The highest operating frequency is 2462MHz.

Adapter Information:

Model: SOY-1200200US

Input: AC 100-240V, 50/60Hz, 0.6A Max

Output: DC 12V, 2.0A

Notes: This series products model: JVS-HC810E and JVS-DC810, JVS-HC810C, JVS-DC810C, JVS-DC810E, JVS-FC810C, JVS-FC810E, JVS-TC810C, JVS-TC810E, JVS-NC810C, JVS-NC810E, HC810E, HC810C, DC810, DC810C, DC810E, FC810C, FC810E, TC810C, TC810E, NC810C, NC810E, JVS-V8A-EN, JVS-V8A, JVS-HV810A are identical; they have the same or similar appearance, structure, PCB, Material and function to the testing products. Model JVS-HC810E was selected for fully testing, the detailed information can be referred to the attached declaration which was stated and guaranteed by the applicant.

**All measurement and test data in this report was gathered from production sample serial number: 1702037 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2017-09-04.*

Objective

This test report is prepared on behalf of Jovision Technology Co.,Ltd. in accordance with Part 2-Subpart J, Part 15-Subparts A, B of the Federal Communication Commissions rules.

The objective of the manufacturer is to determine the compliance of the EUT with FCC Part 15 B.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DTS, submissions with FCC ID: 2AEW9JVS-HC801E

Test Methodology

All measurements contained in this report were conducted with ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		uncertainty
Conducted Emissions		±1.95dB
Emissions, radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

Bay Area Compliance Laboratories Corp. (Shenzhen) has been accredited to ISO/IEC 17025 by CNAS(Lab code: L2408). And accredited to ISO/IEC 17025 by NVLAP(Lab code: 200707-0), the FCC Designation No. CN5001 under the KDB 974614 D01.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Bay Area Compliance Laboratories Corp. (Shenzhen) was registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in a manufacturer testing fashion.

EUT operation mode: monitor and recording (monitor with computer and recording with EUT)

EUT Exercise Software

“SOOVVI Int'l” exercise software was used.

Special Accessories

No special accessory.

Equipment Modifications

No modification was made to the EUT tested.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	PC	Vostro 220s	127bp2x
DELL	LCD Monitor	E178WFPC	CN-OWY564-64180-7C4-2SQH
Microsoft	Keyboard	1406	0200706128743
Microsoft	Mouse	1405	0204608630856
BELKIN	Router	N+	N/A
Kingston	SD Card	N/A	N/A
ADATA	USB Disk	C008	N/A

External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Detachable USB Cable	1.5	Host PC	Mouse
Un-shielding Detachable K/B Cable	1.5	Host PC	Keyboard
Un-shielding Detachable VGA Cable	1.5	Host PC	LCD Monitor
Un-shielding Detachable RJ45 Cable	1.5	EUT	Router
Shielding Detachable Adapter Cable	1.0	EUT	Adapter
Un-shielding Detachable RJ45 Cable	1.5	Router	PC

Block Diagram of Test Setup

For conducted emission:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Results
§15.107	AC Line Conducted Emissions	Compliance
§15.109	Radiated Spurious Emissions	Compliance

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
AC Line Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2016-10-19	2017-10-19
Rohde & Schwarz	LISN 1	ENV216	3560.6650.12-101613-Yb	2016-12-07	2017-12-07
Com-Power	LISN 2	LI-200	12208	2016-12-07	2017-12-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2017-05-21	2017-11-19
Rohde & Schwarz	CE Test software	EMC 32	V8.53.0	NCR	NCR
N/A	Conducted Emission Cable	N/A	UF A210B-1-0720-504504	2017-05-12	2017-11-12
Radiated Emission Test					
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2017-04-24	2018-04-24
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-17	2017-12-16
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2017-02-14	2018-02-14
HP	Amplifier	HP8447E	1937A01046	2017-05-21	2017-11-19
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2016-12-07	2017-12-07
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	104PEA	218124002	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	1	2017-05-21	2017-11-19
Ducommun technologies	RF Cable	RG-214	2	2017-05-22	2017-11-22


* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.107 – AC LINE CONDUCTED EMISSIONS

Applicable Standard

According to FCC §15.107

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with per ANSI C63.4-2014. The related limit was specified in FCC Part 15.107 Class B.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the host PC was connected to the first LISN and the other relevant equipments were connected to the second LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Corrected factor is calculated by adding LISN/ISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Correction Factor} = \text{LISN VDF} + \text{Cable Loss} + \text{Transient Limiter Attenuation}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.107,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL., $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data


Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	101.0 kPa


The testing was performed by Jacob Kong on 2017-09-25.

EUT Operation Mode: monitor and recording

AC 120V/60 Hz, Line



Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.352750	40.9	20.2	58.9	18.0	QP
0.356690	38.5	20.2	58.8	20.3	QP
0.419790	39.1	20.2	57.5	18.4	QP
0.474770	47.2	20.2	56.4	9.2	QP
0.478890	46.8	20.2	56.4	9.6	QP
1.081950	35.1	20.1	56.0	20.9	QP
0.352750	32.8	20.2	48.9	16.1	Ave.
0.356690	31.7	20.2	48.8	17.1	Ave.
0.419790	31.9	20.2	47.5	15.6	Ave.
0.474770	38.4	20.2	46.4	8.0	Ave.
0.478890	38.6	20.2	46.4	7.8	Ave.
1.081950	28.8	20.1	46.0	17.2	Ave.

AC 120V/60 Hz, Neutral

Frequency (MHz)	Corrected Amplitude (dBμV)	Correction Factor (dB)	Limit (dBμV)	Margin (dB)	Detector (PK/Ave./QP)
0.348690	37.6	20.2	59.0	21.4	QP
0.352750	41.0	20.2	58.9	17.9	QP
0.427550	40.1	20.2	57.3	17.2	QP
0.471010	47.1	20.2	56.5	9.4	QP
0.474770	47.1	20.2	56.4	9.3	QP
1.057630	35.4	20.1	56.0	20.6	QP
0.348690	30.7	20.2	49.0	18.3	Ave.
0.352750	32.8	20.2	48.9	16.1	Ave.
0.427550	31.1	20.2	47.3	16.2	Ave.
0.471010	38.6	20.2	46.5	7.9	Ave.
0.474770	38.4	20.2	46.4	8.0	Ave.
1.057630	29.0	20.1	46.0	17.0	Ave.

Note:

- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude


FCC §15.109 - RADIATED SPURIOUS EMISSIONS

Applicable Standard


FCC §15.109

EUT Setup

Below 1GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters chamber test site, using the setup accordance with the ANSI C63.4-2014. The specification used was the FCC Part 15.109 Class B limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 12.31 GHz.

During the radiated emission test, the EMI test receiver was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All data was recorded in the Quasi-peak detector mode from 30 MHz to 1 GHz and PK detector modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the data in the following table, the EUT complied with the FCC §15.109 Class B,

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**

Temperature:	23 °C
Relative Humidity:	50 %
ATM Pressure:	100.0 kPa

The testing was performed by Jacob Kong on 2017-09-22.

EUT Operation Mode: monitor and recording

30MHz – 12.31GHz:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBuV/m)	FCC Part 15B	
	Reading (dBuV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H / V)			Limit (dBuV/m)	Margin (dB)
50.43	44.70	QP	315	1.1	V	-11.0	33.7	40	6.3
51.81	43.23	QP	227	1.0	V	-11.1	32.13	40	7.87
143.31	41.29	QP	321	1.1	V	-4.6	36.69	43.5	6.81
148.13	41.54	QP	289	1.0	V	-4.5	37.04	43.5	6.46
588.02	33.32	QP	225	1.0	V	3.8	37.12	46	8.88
637.46	29.00	QP	97	1.0	V	4.2	33.2	46	12.8
1008.16	61.12	PK	153	2.4	H	-8.60	52.52	74	21.48
1008.16	40.71	Ave.	153	2.4	H	-8.60	32.11	54	21.89
2345.16	44.34	PK	228	1.1	H	-0.74	43.60	74	30.40
2345.16	30.68	Ave.	228	1.1	H	-0.74	29.94	54	24.06
1012.02	57.28	PK	279	2.3	V	-8.60	48.68	74	25.32
1012.02	42.72	Ave.	279	2.3	V	-8.60	34.12	54	19.88
2289.34	45.73	PK	212	2.4	V	-0.74	44.99	74	29.01
2289.34	30.87	Ave.	212	2.4	V	-0.74	30.13	54	23.87

Note:

- 1) Correction Factor=Antenna factor (RX) + cable loss – amplifier factor
- 2) Corrected Amplitude = Correction Factor + Reading
- 3) Margin = Limit - Corrected Amplitude

******* END OF REPORT *******