



Product Service

---

**Choose certainty.  
Add value.**

# Report On

Specific Absorption Rate Testing of the  
DAQRI Smart Helmet

FCC ID: 2AEWMDQR001001

**COMMERCIAL-IN-CONFIDENCE**

Document 75937080 Report 05 Issue 1

March 2017



Product Service

TÜV SÜD Product Service, Octagon House, Concorde Way, Segensworth North,  
Fareham, Hampshire, United Kingdom, PO15 5RL  
Tel: +44 (0) 1489 558100. Website: [www.tuv-sud.co.uk](http://www.tuv-sud.co.uk)

COMMERCIAL-IN-CONFIDENCE

**REPORT ON**

Specific Absorption Rate Testing of the  
DAQRI Smart Helmet

Document 75937080 Report 05 Issue 1

March 2017

**PREPARED FOR**

DAQRI LLC  
1201 W. 5th St. Suite T-800  
Los Angeles  
California  
90017  
United States

**PREPARED BY**

**Stephen Dodd**  
SAR Engineer

**APPROVED BY**

**Nigel Grigsby**  
Authorised Signatory

**DATED**

31 March 2017



## CONTENTS

| Section        | Page No                                                  |
|----------------|----------------------------------------------------------|
| <b>1</b>       | <b>REPORT SUMMARY ..... 3</b>                            |
| 1.1            | Introduction ..... 4                                     |
| 1.2            | Brief Summary of Results ..... 5                         |
| 1.3            | Test Results Summary ..... 6                             |
| 1.4            | FCC Power Measurements ..... 17                          |
| <b>2</b>       | <b>TEST DETAILS ..... 20</b>                             |
| 2.1            | DASY5 Measurement System ..... 21                        |
| 2.2            | WLAN 2450 MHz Head SAR Test Results ..... 25             |
| 2.3            | WLAN 2450 MHz Body-Extremity SAR Test Results ..... 26   |
| 2.4            | WLAN U-NII-2A Head SAR Test Results ..... 27             |
| 2.5            | WLAN U-NII-2A Body-Extremity SAR Test Results ..... 28   |
| 2.6            | WLAN U-NII-2C Head SAR Test Results ..... 29             |
| 2.7            | WLAN U-NII-2C Body-Extremity SAR Test Results ..... 30   |
| 2.8            | WLAN U-NII-3 Head SAR Test Results ..... 31              |
| 2.9            | WLAN U-NII-3 Body-Extremity SAR Test Results ..... 32    |
| <b>3</b>       | <b>TEST EQUIPMENT USED ..... 33</b>                      |
| 3.1            | Test Equipment Used ..... 34                             |
| 3.2            | Test Software ..... 35                                   |
| 3.3            | Dielectric Properties of Simulant Liquids ..... 36       |
| 3.4            | Test Conditions ..... 37                                 |
| 3.5            | Measurement Uncertainty ..... 38                         |
| <b>4</b>       | <b>ACCREDITATION, DISCLAIMERS AND COPYRIGHT ..... 42</b> |
| 4.1            | Accreditation, Disclaimers and Copyright ..... 43        |
| <b>ANNEX A</b> | <b>Probe Calibration Reports ..... A.2</b>               |
| <b>ANNEX B</b> | <b>Dipole Calibration Reports ..... B.2</b>              |



Product Service

## **SECTION 1**

### **REPORT SUMMARY**

Specific Absorption Rate Testing of the  
DAQRI Smart Helmet



## 1.1 INTRODUCTION

The information contained in this report is intended to show verification of the Specific Absorption Rate Testing of the DAQRI Smart Helmet to the requirements of KDB 447498 D01 v06 General RF Exposure Guidance.

|                               |                                                                                                                                                                                                                                 |
|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Objective                     | To perform Specific Absorption Rate Testing to determine the Equipment Under Test's (EUT's) compliance with the requirements specified of KDB 447498 D01 v06 General RF Exposure Guidance, for the series of tests carried out. |
| Applicant                     | DAQRI LLC                                                                                                                                                                                                                       |
| Manufacturer                  | DAQRI International Ltd                                                                                                                                                                                                         |
| Model Number                  | DAQRI Smart Helmet                                                                                                                                                                                                              |
| Number of Samples Tested      | 1                                                                                                                                                                                                                               |
| Hardware Version              | DAQRI Thor DE                                                                                                                                                                                                                   |
| Software Version              | V16                                                                                                                                                                                                                             |
| Serial Number                 | Not Serialised - 75937080_TSR0061                                                                                                                                                                                               |
| Battery Cell Manufacturer     | GETAC TECHNOLOGY CORP                                                                                                                                                                                                           |
| Battery Model Number          | THR-00152                                                                                                                                                                                                                       |
| Test Specification/Issue/Date | KDB 447498 D01 v06 General RF Exposure Guidance                                                                                                                                                                                 |
| Start of Test                 | 20 March 2017                                                                                                                                                                                                                   |
| Finish of Test                | 23 March 2017                                                                                                                                                                                                                   |
| Related Document(s)           | FCC 47CFR 2.1093: 2015<br>KDB 865664 – D01 v01r04<br>KDB 865664 – D02 v01r02<br>IEEE 1528-2013<br>KDB 248227 – D01 v02r02                                                                                                       |
| Name of Engineer(s)           | Stephen Dodd                                                                                                                                                                                                                    |



Product Service

## 1.2 BRIEF SUMMARY OF RESULTS

The measurements shown in this report were made in accordance with the procedures specified KDB 447498 D01 v06 General RF Exposure Guidance.

The maximum 1g volume averaged stand -alone SAR found during this Assessment:

|                                                                                                                                                                                       |                        |                      |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------|
| Max 1g SAR (W/kg) Head                                                                                                                                                                | <b>0.20</b> (Measured) | <b>0.29</b> (Scaled) |
| The maximum 1g volume averaged SAR level measured for all the tests performed did not exceed the limits for General Population/Uncontrolled Exposure (W/kg) Partial Body of 1.6 W/kg. |                        |                      |

The maximum 10g volume averaged stand -alone SAR found during this Assessment:

|                                                                                                                                                                                        |                        |                      |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|----------------------|
| Max 10g SAR (W/kg) Body-Extremity                                                                                                                                                      | <b>0.31</b> (Measured) | <b>0.45</b> (Scaled) |
| The maximum 10g volume averaged SAR level measured for all the tests performed did not exceed the limits for General Population/Uncontrolled Exposure (W/kg) Partial Body of 4.0 W/kg. |                        |                      |

The maximum 1g volume averaged stand -alone Reported SAR found during this Assessment for each supported mode:

| Band                                                                                                                                                                                                                                         | Test Configuration | Max Reported SAR (W/kg) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|-------------------------|
| 2450 MHz                                                                                                                                                                                                                                     | Head               | 0.08                    |
| U-NII-2A                                                                                                                                                                                                                                     | Head               | 0.28                    |
| U-NII-2C                                                                                                                                                                                                                                     | Head               | 0.21                    |
| U-NII-3                                                                                                                                                                                                                                      | Head               | 0.29                    |
| The maximum 1g volume averaged SAR level measured for all the tests performed (including simultaneous transmission analysis results) did not exceed the limits for General Population/Uncontrolled Exposure (W/kg) Partial Body of 1.6 W/kg. |                    |                         |

The maximum 10g volume averaged stand -alone Reported SAR found during this Assessment for each supported mode:

| Band                                                                                                                                                                                                                                          | Test Configuration | Max Reported SAR (W/kg) |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|-------------------------|
| 2450 MHz                                                                                                                                                                                                                                      | Body-Extremity     | 0.26                    |
| U-NII-2A                                                                                                                                                                                                                                      | Body-Extremity     | 0.29                    |
| U-NII-2C                                                                                                                                                                                                                                      | Body-Extremity     | 0.33                    |
| U-NII-3                                                                                                                                                                                                                                       | Body-Extremity     | 0.45                    |
| The maximum 10g volume averaged SAR level measured for all the tests performed (including simultaneous transmission analysis results) did not exceed the limits for General Population/Uncontrolled Exposure (W/kg) Partial Body of 4.0 W/kg. |                    |                         |



Product Service

### 1.3 TEST RESULTS SUMMARY

#### 1.3.1 System Performance / Validation Check Results

Prior to formal testing being performed a System Check was performed in accordance with KDB 865664 and the results were compared against published data in Standard IEEE 1528-2003. The following results were obtained: -

##### System performance / Validation results

| Date       | Frequency (MHz) | Max 1g SAR (W/kg)* | Percentage Drift on Reference |
|------------|-----------------|--------------------|-------------------------------|
| 20/03/2017 | 5200 MHz        | 70.07              | -8.41                         |
| 20/03/2017 | 5500 MHz        | 83.20              | -0.12                         |
| 21/03/2017 | 5800 MHz        | 74.44              | 0.46                          |
| 21/03/2017 | 5200 MHz        | 64.89              | -9.62                         |
| 21/03/2017 | 5500 MHz        | 71.66              | -9.41                         |
| 21/03/2017 | 5500 MHz        | 71.66              | -9.41                         |
| 22/03/2017 | 5500 MHz        | 72.06              | -8.90                         |
| 22/03/2017 | 5800 MHz        | 67.28              | -9.20                         |
| 22/03/2017 | 2450 MHz        | 48.17              | -5.92                         |
| 23/03/2017 | 2450 MHz        | 53.74              | 2.56                          |

\*Normalised to a forward power of 1W



### 1.3.2 Results Summary Tables

#### 2.4 GHz DSSS Helmet Internal - Antenna A Power Setting 16: WLAN 2450 MHz 802.11b 20MHz 1Mbps Head Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1              | 2412            | 15.19                        | 16.50         | 0.06                   | 0.08                 | Figure 2           |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$<br>KDB248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 |                |                 |                              |               |                        |                      |                    |

#### 2.4 GHz DSSS Helmet Internal - Antenna B Power Setting 16: WLAN 2450 MHz 802.11b 20MHz 1Mbps Head Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1              | 2412            | 15.19                        | 16.50         | 0.02                   | 0.03                 | Figure 3           |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$<br>KDB248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 |                |                 |                              |               |                        |                      |                    |

#### 2.4 GHz DSSS Helmet External - Antenna A Power Setting 16: WLAN 2450 MHz 802.11b 20MHz 1Mbps Extremity-Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1              | 2412            | 15.19                        | 16.50         | 0.19                    | 0.26                  | Figure 4           |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$<br>KDB248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 |                |                 |                              |               |                         |                       |                    |



Product Service

2.4 GHz DSSS Helmet External - Antenna B Power Setting 16: 802.11b 20MHz 1Mbps  
Extremity Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1              | 2412            | 15.19                        | 16.50         | 0.18                    | 0.25                  | Figure 5           |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$<br>KDB248227 D01 v02 - Testing was not required for OFDM as per Section 5.2.2 |                |                 |                              |               |                         |                       |                    |

5 GHz Helmet Internal - Antenna A U-NII 2A Power Setting 16: 802.11n 40MHz HT0 Head  
Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 54             | 5270            | 15.12                        | 17.00         | 0.07                   | 0.11                 | Figure 6           |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |

5 GHz Helmet Internal - Antenna B U-NII 2A Power Setting 16: 802.11n 40MHz HT0 Head  
Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 54             | 5270            | 15.12                        | 17.00         | 0.19                   | 0.28                 | Figure 7           |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |



Product Service

5 GHz Helmet External - Antenna A U-NII 2A Power Setting 16: 802.11n 40MHz HT0 Extremity Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 54             | 5270            | 15.12                        | 17.00         | 0.19                    | 0.29                  | Figure 8           |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |

5 GHz Helmet External - Antenna B U-NII 2A Power Setting 16: 802.11n 40MHz HT0 Extremity Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 54             | 5270            | 15.12                        | 17.00         | 0.18                    | 0.27                  | Figure 9           |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |

5 GHz Helmet Internal - Antenna A U-NII 2C Power Setting 16: 802.11n 40MHz HT0 Head Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 118            | 5590            | 16.08                        | 17.50         | 0.07                   | 0.10                 | Figure 10          |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |



Product Service

5 GHz Helmet Internal - Antenna B U-NII 2C Power Setting 16: 802.11n 40MHz HT0 Head  
Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 118            | 5590            | 16.08                        | 17.50         | 0.15                   | 0.21                 | Figure 11          |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |

5 GHz Helmet External - Antenna A U-NII 2C Power Setting 16: 802.11n 40MHz HT0 Extremity  
Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 118            | 5590            | 16.08                        | 17.50         | 0.15                    | 0.21                  | Figure 12          |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |

5 GHz Helmet External - Antenna B U-NII 2C Power Setting 16: MHz 802.11n 40MHz HT0  
Extremity Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 118            | 5590            | 16.08                        | 17.50         | 0.23                    | 0.33                  | Figure 13          |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |



5 GHz Helmet Internal - Antenna A U-NII 3 Power Setting 17: 802.11ac 80MHz VHT0 Head  
Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 138            | 5690            | 16.34                        | 18.00         | 0.20                   | <b>0.29</b>          | Figure 14          |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |

5 GHz Helmet Internal - Antenna B U-NII 3 Power Setting 17: MHz 802.11ac 80MHz VHT0  
Head Specific Absorbtion Rate (Maximum SAR) 1g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 1g SAR (W/kg) | Scaled 1g SAR (W/kg) | Scan Figure Number |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|------------------------|----------------------|--------------------|
| 0mm Internal                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 138            | 5690            | 16.34                        | 18.00         | 0.19                   | 0.26                 | Figure 15          |
| Limit for General Population (Uncontrolled Exposure) 1.6 W/kg (1g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 0.8\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 0.6\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.4\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                        |                      |                    |

5 GHz Helmet External - Antenna A U-NII 3 Power Setting 17: 802.11ac 80MHz VHT0 Extremity  
Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 138            | 5690            | 16.34                        | 18.00         | 0.21                    | 0.31                  | Figure 16          |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |



### 5 GHz Helmet External - Antenna B U-NII 3 Power Setting 17: 802.11ac 80MHz VHT0 Extremity Specific Absorbtion Rate (Maximum SAR) 10g Results

| Test Position                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Channel Number | Frequency (MHz) | Measured Average Power (dBm) | Tune Up (dBm) | Measured 10g SAR (W/kg) | Scaled 10g SAR (W/kg) | Scan Figure Number |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|-----------------|------------------------------|---------------|-------------------------|-----------------------|--------------------|
| 1mm External                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 138            | 5690            | 16.34                        | 18.00         | 0.31                    | <b>0.45</b>           | Figure 17          |
| Limit for General Population (Uncontrolled Exposure) 4 W/kg (10g)<br>KDB 447498 D01 - Testing of other required channels within the operation mode of a frequency band is not required when the reported 1g SAR for mid-band or highest output power channel is:<br>$\leq 2.0\text{W/kg}$ when the transmission band is $\leq 100\text{MHz}$<br>$\leq 1.5\text{W/kg}$ when the transmission band is between 100MHz and 200MHz<br>$\leq 0.1\text{W/kg}$ when the transmission band is $\geq 200\text{MHz}$ |                |                 |                              |               |                         |                       |                    |

#### 1.3.3 Simultaneous Transmission

| Position                                                                                                                                                                                                                                                                                                            | 802.11b 20MHz 1Mbps 1g SAR (W/kg)     | 802.11b 20MHz 1Mbps 1g SAR (W/kg)      | $\Sigma$ 1g SAR (W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|----------------------------------------|------------------------|
| Head                                                                                                                                                                                                                                                                                                                | SISO A<br>CH 1<br>(Scaled SAR values) | SISO B<br>CH 1<br>(Scaled SAR values)) |                        |
| Internal                                                                                                                                                                                                                                                                                                            | 0.08                                  | 0.03                                   | 0.11                   |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                       |                                        |                        |

Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.

| Position                                                                                                                                                                                                                                                                                                            | 802.11b 20MHz 1Mbps 10g SAR (W/kg)    | 802.11b 20MHz 1Mbps Head 10g SAR (W/kg) | $\Sigma$ 10g SAR (W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------|-----------------------------------------|-------------------------|
| Extremity                                                                                                                                                                                                                                                                                                           | SISO A<br>CH 1<br>(Scaled SAR values) | SISO B<br>CH 1<br>(Scaled SAR values))  |                         |
| External                                                                                                                                                                                                                                                                                                            | 0.26                                  | 0.25                                    | 0.51                    |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                       |                                         |                         |

Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.



Product Service

| Position                                                                                                                                                                                                                                                                                                            | 802.11n 40MHz<br>HT0 1g SAR<br>(W/kg)  | 802.11n 40MHz<br>HT0 1g SAR<br>(W/kg)  | $\Sigma$ 1g SAR (W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|----------------------------------------|------------------------|
| Head                                                                                                                                                                                                                                                                                                                | SISO A<br>CH 54<br>(Scaled SAR values) | SISO B<br>CH 54<br>(Scaled SAR values) |                        |
| Internal                                                                                                                                                                                                                                                                                                            | 0.11                                   | 0.28                                   | 0.39                   |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                        |                                        |                        |

Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.

| Position                                                                                                                                                                                                                                                                                                            | 802.11n 40MHz<br>HT0 10g SAR<br>(W/kg) | 802.11n 40MHz<br>HT0 10g SAR<br>(W/kg) | $\Sigma$ 10g SAR<br>(W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|----------------------------------------|----------------------------|
| Extremity                                                                                                                                                                                                                                                                                                           | SISO A<br>CH 54<br>(Scaled SAR values) | SISO B<br>CH 54<br>(Scaled SAR values) |                            |
| External                                                                                                                                                                                                                                                                                                            | 0.29                                   | 0.27                                   | 0.56                       |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                        |                                        |                            |

Simultaneous SAR measurements were not required as the sum of the 10g SAR measurements did not exceed 4.0 W/kg.

| Position                                                                                                                                                                                                                                                                                                             | 802.11n 40MHz<br>HT0 1g SAR<br>(W/kg)   | 802.11n 40MHz<br>HT0 1g SAR<br>(W/kg)   | $\Sigma$ 1g SAR (W/kg) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------|------------------------|
| Head                                                                                                                                                                                                                                                                                                                 | SISO A<br>CH 118<br>(Scaled SAR values) | SISO B<br>CH 118<br>(Scaled SAR values) |                        |
| Internal                                                                                                                                                                                                                                                                                                             | 0.10                                    | 0.21                                    | 0.31                   |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion.. |                                         |                                         |                        |

Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.

| Position                                                                                                                                                                                                                                                                                                            | 802.11n 40MHz<br>HT0 10g SAR<br>(W/kg)  | 802.11n 40MHz<br>HT0 10g SAR<br>(W/kg)  | $\Sigma$ 10g SAR<br>(W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------|----------------------------|
| Extremity                                                                                                                                                                                                                                                                                                           | SISO A<br>CH 118<br>(Scaled SAR values) | SISO B<br>CH 118<br>(Scaled SAR values) |                            |
| External                                                                                                                                                                                                                                                                                                            | 0.21                                    | 0.33                                    | 0.54                       |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                         |                                         |                            |



Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.

| Position                                                                                                                                                                                                                                                                                                            | 802.11ac 80MHz<br>VHT0 1g SAR<br>(W/kg) | 802.11ac 80MHz<br>VHT0 1g SAR<br>(W/kg) | $\Sigma$ 1g SAR (W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|-----------------------------------------|------------------------|
| Head                                                                                                                                                                                                                                                                                                                | SISO A<br>CH 138<br>(Scaled SAR values) | SISO B<br>CH 138<br>(Scaled SAR values) |                        |
| Internal                                                                                                                                                                                                                                                                                                            | 0.29                                    | 0.26                                    | 0.55                   |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                         |                                         |                        |

Simultaneous SAR measurements were not required as the sum of the 1g SAR measurements did not exceed 1.6 W/kg.

| Position                                                                                                                                                                                                                                                                                                            | 802.11ac 80MHz<br>VHT0 10g SAR<br>(W/kg) | 802.11ac 80MHz<br>VHT0 10g SAR<br>(W/kg) | $\Sigma$ 10g SAR<br>(W/kg) |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|------------------------------------------|----------------------------|
| Extremity                                                                                                                                                                                                                                                                                                           | SISO A<br>CH 138<br>(Scaled SAR values)  | SISO B<br>CH 138<br>(Scaled SAR values)  |                            |
| External                                                                                                                                                                                                                                                                                                            | 0.31                                     | 0.45                                     | <b>0.76</b>                |
| The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently as per KDB 248227 D01 Section 6.5. The highest reported SAR for the 802.11 transmission modes in the frequency band was used for simultaneous transmission SAR test exclusion. |                                          |                                          |                            |

Simultaneous SAR measurements were not required as the sum of the 10g SAR measurements did not exceed 4.0 W/kg.

The antennas were spatially separated to the extent that the SAR distributions did not overlap, therefore were treated independently



#### 1.3.4 Standalone SAR Test Exclusion Considerations (KDB 447498 D01)

The 1g SAR Test exclusion thresholds for 100 MHz to 6 GHz *test separation distances*  $\leq 50$  mm are determined by:

$$\frac{[(\text{max power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]}{[\sqrt{f \text{ (GHz)}}] \leq 3.0, \text{ where}$$

- $f \text{ (GHz)}$  is the RF channel transmit frequency in GHz.
- Power and distance are rounded to the nearest mW and mm before calculation.
- The result is rounded to one decimal place for comparison.
- When the maximum test separation distance is  $< 5$  mm, a distance of 5 mm is applied.

| Band     | Frequency (MHz) | Power (dBm) | Power (mW) | Test Position | Distance (mm) | Threshold | Test Exclusion |
|----------|-----------------|-------------|------------|---------------|---------------|-----------|----------------|
| 2450 MHz | 2412            | 16.5        | 44.7       | Head          | <5            | 13.9      | No             |
| 2450 MHz | 2412            | 16.5        | 44.7       | Body          | <5            | 13.9      | No             |
| U-NII-1  | 5270            | 17.0        | 50.1       | Head          | <5            | 23.0      | No             |
| U-NII-1  | 5270            | 17.0        | 50.1       | Body          | <5            | 23.0      | No             |
| U-NII-2a | 5590            | 17.5        | 56.2       | Head          | <5            | 26.6      | No             |
| U-NII-2a | 5590            | 17.5        | 56.2       | Body          | <5            | 26.6      | No             |
| U-NII-3  | 5690            | 18.0        | 63.1       | Head          | <5            | 30.1      | No             |
| U-NII-3  | 5690            | 18.0        | 63.1       | Body          | <5            | 30.1      | No             |

#### 1.3.5 Technical Description

The equipment under test (EUT) was a DAQRI Smart Helmet. A full technical description can be found in the manufacturer's documentation.

#### 1.3.6 Test Configuration and Modes of Operation

To enable accurate SAR assessment of the device, the internal electronics (PCB and battery) were removed from the inside of the helmet. This was due the measurement system not being able to measure inside the helmet and the form-factor and the curved edges of the DUT.

The testing was performed with an integral battery supplied and manufactured by DAQRI.

WLAN testing was achieved using the devices internal software, customer supplied software and settings supplied by the customer. For each scan the device was configured into a continuous transmission test mode.

Worst case data rates used were 2.4 GHz DSSS -802.11.b 20 MHz 1Mbps, U-NIII-2A 802.11n 40 MHz MCS0, U-NIII-2C 802.11n 40 MHz MCS0, U-NIII-3 802.11ac 80 MHz MCS0.

For head SAR assessment the internal electronics / PCB and battery of the device were placed against an Elliptical phantom with a 0mm separation distance. The separation distance from the antenna to the phantom shell was 32mm. The phantom was filled with broad band simulant liquid. The dielectric properties were measured and found to be in accordance with the requirements for the dielectric properties specified in KDB 865665.

For body/extremity SAR assessment the internal electronics / PCB and battery of the device were placed against an Elliptical phantom with a 1mm separation distance to simulate the outer shell of the helmet. The separation distance from the antenna to the phantom shell was 5mm. The phantom was filled with broad band simulant liquid. The dielectric properties were



Product Service

measured and found to be in accordance with the requirements for the dielectric properties specified in KDB 865665

The Elliptical Phantom dimensions are 600 mm major axis and 400mm minor axis with a shell thickness of 2.00mm. The phantom was filled to a minimum depth of 150mm with the appropriate simulant liquid. The dielectric properties were in accordance with the requirements specified in KDB 865665.

Included in this report are descriptions of the test method; the equipment used and an analysis of the test uncertainties applicable and diagrams indicating the locations of maximum SAR for each test position along with photographs indicating the positioning of the handset against the body as appropriate.

#### **1.3.7 Deviations From Standard**

Power measurements on several channels were more than 2dB lower than the maximum tune-up limit, specified in KDB 447498 D01 General RF Exposure Guidance v06.

Although the power output of the DUT could not be permanently adjusted by the customer, for testing purposes the output power could be temporarily adjusted using the customer supplied software. The DUT power levels were increased to be within the tune-up limit tolerance for testing, hence giving an over-estimation of the SAR values which would be lower in real time use.



## 1.4 FCC POWER MEASUREMENTS

### 1.4.1 Method

Conducted power measurements were made using a power meter.

### 1.4.2 Conducted Power Measurements

#### WLAN 2450 MHz

| Mode                           | Frequency (MHz) | Duty Cycle (%) | Burst Average Power (dBm)<br>SISO A | Burst Average Power (dBm)<br>SISO B |
|--------------------------------|-----------------|----------------|-------------------------------------|-------------------------------------|
| 802.11b - 20 MHz - 1 Mbps DSSS | 2412            | 100            | <b>15.19</b>                        | <b>15.14</b>                        |
| 802.11b - 20 MHz - 1 Mbps DSSS | 2437            | 100            | 14.67                               | 14.63                               |
| 802.11b - 20 MHz - 1 Mbps DSSS | 2462            | 100            | 15.03                               | 15.02                               |
| 802.11b - 20 MHz - 6 Mbps OFDM | 2412            | 100            | <b>15.98</b>                        | <b>15.97</b>                        |
| 802.11b - 20 MHz - 6 Mbps OFDM | 2437            | 100            | 15.48                               | 15.43                               |
| 802.11b - 20 MHz - 6 Mbps OFDM | 2462            | 100            | 15.82                               | 15.79                               |

#### WLAN 5000 MHz

| Mode                      | Frequency (MHz) | Duty Cycle (%) | Burst Average Power (dBm)<br>SISO A | Burst Average Power (dBm)<br>SISO B |
|---------------------------|-----------------|----------------|-------------------------------------|-------------------------------------|
| 802.11a - 20 MHz - 6 Mbps | 5180            | 100            | 14.76                               | 14.37                               |
| 802.11a - 20 MHz - 6 Mbps | 5200            | 100            | 14.53                               | 14.27                               |
| 802.11a - 20 MHz - 6 Mbps | 5220            | 100            | 14.50                               | 14.08                               |
| 802.11a - 20 MHz - 6 Mbps | 5240            | 100            | 14.09                               | 14.23                               |
| 802.11a - 20 MHz - 6 Mbps | 5260            | 100            | 14.52                               | 14.71                               |
| 802.11a - 20 MHz - 6 Mbps | 5280            | 100            | 14.56                               | 14.67                               |
| 802.11a - 20 MHz - 6 Mbps | 5300            | 100            | 14.72                               | 14.69                               |
| 802.11a - 20 MHz - 6 Mbps | 5320            | 100            | 14.86                               | 14.72                               |
| 802.11a - 20 MHz - 6 Mbps | 5500            | 100            | 15.71                               | 15.62                               |
| 802.11a - 20 MHz - 6 Mbps | 5560            | 100            | 15.96                               | 16.02                               |
| 802.11a - 20 MHz - 6 Mbps | 5580            | 100            | 15.98                               | 15.91                               |
| 802.11a - 20 MHz - 6 Mbps | 5640            | 100            | 15.67                               | 15.48                               |
| 802.11a - 20 MHz - 6 Mbps | 5660            | 100            | 15.49                               | 15.44                               |
| 802.11a - 20 MHz - 6 Mbps | 5745            | 100            | 15.13                               | 15.42                               |



|                           |      |     |              |              |
|---------------------------|------|-----|--------------|--------------|
| 802.11a - 20 MHz - 6 Mbps | 5825 | 100 | 15.30        | 15.43        |
| 802.11a- 20 MHz-HT0       | 5180 | 100 | 14.76        | 14.37        |
| 802.11a- 20 MHz-HT0       | 5200 | 100 | 14.49        | 14.27        |
| 802.11a- 20 MHz-HT0       | 5220 | 100 | 14.53        | 14.08        |
| 802.11a- 20 MHz-HT0       | 5240 | 100 | 14.09        | 14.23        |
| 802.11a- 20 MHz-HT0       | 5260 | 100 | 14.41        | 14.69        |
| 802.11a- 20 MHz-HT0       | 5280 | 100 | 14.45        | 14.60        |
| 802.11a- 20 MHz-HT0       | 5300 | 100 | 14.55        | 14.57        |
| 802.11a- 20 MHz-HT0       | 5320 | 100 | 14.76        | 14.61        |
| 802.11a- 20 MHz-HT0       | 5500 | 100 | 15.43        | 15.52        |
| 802.11a- 20 MHz-HT0       | 5560 | 100 | 15.63        | 15.93        |
| 802.11a- 20 MHz-HT0       | 5580 | 100 | 15.63        | 15.76        |
| 802.11a- 20 MHz-HT0       | 5640 | 100 | 14.86        | 15.34        |
| 802.11a- 20 MHz-HT0       | 5660 | 100 | 15.46        | 15.04        |
| 802.11a- 20 MHz-HT0       | 5745 | 100 | 13.18        | 13.38        |
| 802.11a- 20 MHz-HT0       | 5825 | 100 | 13.33        | 13.39        |
| 802.11n- 40MHz-HT0        | 5190 | 100 | <b>14.75</b> | <b>15.08</b> |
| 802.11n- 40MHz-HT0        | 5230 | 100 | 14.47        | 14.73        |
| 802.11n- 40MHz-HT0        | 5270 | 100 | <b>15.12</b> | <b>15.27</b> |
| 802.11n- 40MHz-HT0        | 5310 | 100 | 12.94        | 13.72        |
| 802.11n- 40MHz-HT0        | 5510 | 100 | 12.69        | 14.19        |
| 802.11n- 40MHz-HT0        | 5550 | 100 | 15.93        | 15.95        |
| 802.11n- 40MHz-HT0        | 5590 | 100 | <b>16.08</b> | <b>15.98</b> |
| 802.11n- 40MHz-HT0        | 5630 | 100 | 15.62        | 15.74        |
| 802.11n- 40MHz-HT0        | 5670 | 100 | 15.42        | 15.81        |
| 802.11n- 40MHz-HT0        | 5710 | 100 | 15.28        | 15.65        |
| 802.11n- 40MHz-HT0        | 5755 | 100 | 13.27        | 13.30        |
| 802.11n- 40MHz-HT0        | 5795 | 100 | 13.02        | 12.78        |
| 802.11n-20MHz-VHT0        | 5180 | 100 | 14.93        | 14.38        |
| 802.11n-20MHz-VHT0        | 5200 | 100 | 14.61        | 14.33        |
| 802.11n-20MHz-VHT0        | 5220 | 100 | 14.63        | 14.03        |



|                     |      |     |              |              |
|---------------------|------|-----|--------------|--------------|
| 802.11n-20MHz-VHT0  | 5240 | 100 | 14.27        | 14.12        |
| 802.11n-20MHz-VHT0  | 5260 | 100 | 14.48        | 14.15        |
| 802.11n-20MHz-VHT0  | 5680 | 100 | 14.46        | 14.06        |
| 802.11n-20MHz-VHT0  | 5300 | 100 | 14.63        | 14.10        |
| 802.11n-20MHz-VHT0  | 5320 | 100 | 14.79        | 14.13        |
| 802.11n-20MHz-VHT0  | 5500 | 100 | 15.31        | 15.03        |
| 802.11n-20MHz-VHT0  | 5560 | 100 | 15.47        | 15.06        |
| 802.11n-20MHz-VHT0  | 5580 | 100 | 15.48        | 14.84        |
| 802.11n-20MHz-VHT0  | 5640 | 100 | 15.13        | 15.38        |
| 802.11ac-40MHz-VHT0 | 5190 | 100 | 15.1         | 15.09        |
| 802.11ac-40MHz-VHT0 | 5230 | 100 | 14.8         | 14.70        |
| 802.11ac-40MHz-VHT0 | 5270 | 100 | 15.22        | 15.36        |
| 802.11ac-40MHz-VHT0 | 5310 | 100 | 12.57        | 13.85        |
| 802.11ac-40MHz-VHT0 | 5510 | 100 | 12.98        | 14.03        |
| 802.11ac-40MHz-VHT0 | 5550 | 100 | 14.68        | 16.02        |
| 802.11ac-40MHz-VHT0 | 5590 | 100 | 12.16        | 15.71        |
| 802.11ac-40MHz-VHT0 | 5630 | 100 | 15.23        | 15.60        |
| 802.11ac-40MHz-VHT0 | 5670 | 100 | 14.74        | 15.75        |
| 802.11ac-40MHz-VHT0 | 5710 | 100 | 15.51        | 15.65        |
| 802.11ac-40MHz-VHT0 | 5755 | 100 | 13.36        | 13.27        |
| 802.11ac-40MHz-VHT0 | 5795 | 100 | 13.08        | 13.07        |
| 802.11ac-80MHz-VHT0 | 5210 | 100 | 12.77        | 12.88        |
| 802.11ac-80MHz-VHT0 | 5290 | 100 | 10.62        | 11.75        |
| 802.11ac-80MHz-VHT0 | 5530 | 100 | 12.17        | 12.24        |
| 802.11ac-80MHz-VHT0 | 5610 | 100 | 15.64        | 15.56        |
| 802.11ac-80MHz-VHT0 | 5690 | 100 | <b>16.34</b> | <b>16.61</b> |
| 802.11ac-80MHz-VHT0 | 5775 | 100 | 12.99        | 12.95        |



Product Service

## **SECTION 2**

### **TEST DETAILS**

Specific Absorption Rate Testing of the  
DAQRI Smart Helmet



## 2.1 DASY5 MEASUREMENT SYSTEM

### 2.1.1 System Description

The DASY5 system for performing compliance tests consists of the following items:




**Figure 1 System Description Diagram**

A standard high precision 6-axis robot (Stäubli TX=RX family) with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).

An isotropic field probe optimized and calibrated for the targeted measurement.

A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.

The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.

The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.

The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.

A computer running Win7 professional operating system and the DASY5 software.

Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.

The phantom, the device holder and other accessories according to the targeted measurement.

### 2.1.2 Probe Specification

The probes used by the DASY system are isotropic E-field probes, constructed with a symmetric design and a triangular core. The probes have built-in shielding against static charges and are contained within a PEEK enclosure material. These probes are specially designed and calibrated for use in liquids with high permittivities. The frequency range of the probes are from 6 MHz to 6 GHz.

### 2.1.3 Data Acquisition Electronics

The data acquisition electronics (DAE4 or DAE3) consist of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder with a control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information, as well as an optical uplink for commands and the clock.

The mechanical probe mounting device includes two different sensor systems for frontal and sideways probe contacts. They are used for mechanical surface detection and probe collision detection. The input impedance of both the DAE4 as well as of the DAE3 box is 200MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.

### 2.1.4 SAR Evaluation Description

The DASY5 software includes all numerical procedures necessary to evaluate the spatial peak SAR values.

Based on the IEEE 1528 standard, a new algorithm has been implemented. The spatial-peak SAR can be computed over any required mass.

The base for the evaluation is a "cube" measurement in a volume of 30mm<sup>3</sup> (7x7x7 points). The measured volume must include the 1 g and 10 g cubes with the highest averaged SAR values. For that purpose, the centre of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan. If the 10g cube or both cubes are not entirely inside the measured volumes, the system issues a warning regarding the evaluated spatial peak values within the Post processing engine (SEMCAD X). This means that if the measured volume is shifted, higher values might be possible. To get the correct values you can use a finer measurement grid for the area scan. In complicated field distributions, a large grid spacing for the area scan might miss some details and give an incorrectly interpolated peak location.

The entire evaluation of the spatial peak values is performed within the Post-processing engine (SEMCAD X). The system always gives the maximum values for the 1 g and 10 g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

1. extraction of the measured data (grid and values) from the Zoom Scan
2. calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
3. generation of a high-resolution mesh within the measured volume
4. interpolation of all measured values from the measurement grid to the high-resolution grid
5. extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
6. calculation of the averaged SAR within masses of 1 g and 10 g

### 2.1.5 Interpolation, Extrapolation and Detection of Maxima

The probe is calibrated at the centre of the dipole sensors which is located 1 to 2.7mm away from the probe tip. During measurements, the probe stops shortly above the phantom surface, depending on the probe and the surface detecting system. Both distances are included as parameters in the probe configuration file. The software always knows exactly how far away the measured point is from the surface. As the probe cannot directly measure at the surface, the values between the deepest measured point and the surface must be extrapolated.

In DASY5, the choice of the coordinate system defining the location of the measurement points has no influence on the uncertainty of the interpolation, Maxima Search and extrapolation routines. The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method [1]. Thereby, the interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The DASY5 routines construct a once-continuously differentiable function that interpolates the measurement values as follows:

For each measurement point a trivariate (3-D) / bivariate (2-D) quadratic is computed. It interpolates the measurement values at the data point and forms a least-square fit to neighbouring measurement values. The spatial location of the quadratic with respect to the measurement values is attenuated by an inverse distance weighting. This is performed since the calculated quadratic will fit measurement values at nearby points more accurate than at points located further away.

After the quadratics are calculated for at all measurement points, the interpolating function is calculated as a weighted average of the quadratics.

There are two control parameters that govern the behaviour of the interpolation method. One specifies the number of measurement points to be used in computing the least-square fits for the local quadratics. These measurement points are the ones nearest the input point for which the quadratic is being computed. The second parameter specifies the number of measurement points that will be used in calculating the weights for the quadratics to produce the final function. The input data points used there are the ones nearest the point at which the interpolation is desired. Appropriate defaults are chosen for each of the control parameters

The trivariate quadratics that have been previously computed for the 3-D interpolation and whose input data are at the closest distance from the phantom surface, are used in order to extrapolate the fields to the surface of the phantom.

In order to determine all the field maxima in 2-D (Area Scan) and 3-D (Zoom Scan), the measurement grid is refined by a default factor of 10 and the interpolation function is used to evaluate all field values between corresponding measurement points. Subsequently, a linear search is applied to find all the candidate maxima. In a last step, non physical maxima are removed and only those maxima which are within 2 dB of the global maximum value are retained.

In the Area Scan, the gradient of the interpolation function is evaluated to find all the extrema of the SAR distribution. The uncertainty on the locations of the extrema is less than 1/20 of the grid size. Only local maxima within 2 dB of the global maximum are searched and passed for the Zoom Scan measurement.

In the Zoom Scan, the interpolation function is used to extrapolate the Peak SAR from the lowest measurement points to the inner phantom surface (the extrapolation distance). The



uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5mm.

#### **2.1.6 Averaging and Determination of Spatial Peak SAR**

The interpolated data is used to average the SAR over the 1g and 10g cubes by spatially discretising the entire measured volume. The resolution of this spatial grid used to calculate the averaged SAR is 1mm or about 42875 interpolated points. The resulting volumes are defined as cubical volumes containing the appropriate tissue parameters that are centered at the location. The location is defined as the centre of the incremental volume (voxel).

The spatial-peak SAR must be evaluated in cubical volumes containing a mass that is within 5% of the required mass. The cubical volume centered at each location, as defined above, should be expanded in all directions until the desired value for the mass is reached, with no surface boundaries of the averaging volume extending beyond the outermost surface of the considered region. In addition, the cubical volume should not consist of more than 10% of air. If these conditions are not satisfied then the centre of the averaging volume is moved to the next location. Otherwise, the exact size of the final sampling cube is found using an inverse polynomial approximation algorithm, leading to results with improved accuracy. If one boundary of the averaging volume reaches the boundary of the measured volume during its expansion, it will not be evaluated at all. Reference is kept of all locations used and those not used for averaging the SAR. All average SAR values are finally assigned to the centered location in each valid averaging volume.

All locations included in an averaging volume are marked to indicate that they have been used at least once. If a location has been marked as used, but has never been assigned to the centre of a cube, the highest averaged SAR value of all other cubical volumes which have used this location for averaging is assigned to this location. Only those locations that are not part of any valid averaging volume should be marked as unused. For the case of an unused location, a new averaging volume must be constructed which will have the unused location centered at one surface of the cube. The remaining five surfaces are expanded evenly in all directions until the required mass is enclosed, regardless of the amount of included air. Of the six possible cubes with one surface centered on the unused location, the smallest cube is used, which still contains the required mass.

If the final cube containing the highest averaged SAR touches the surface of the measured volume, an appropriate warning is issued within the Post-processing engine.



## 2.2 WLAN 2450 MHz HEAD SAR TEST RESULTS




Figure 2: SAR Head Testing Results for the DAQRI Smart Helmet at 2412 MHz.



Figure 3: SAR Head Testing Results for the DAQRI Smart Helmet at 2412 MHz.



## 2.3 WLAN 2450 MHz BODY-EXTREMITY SAR TEST RESULTS




Figure 4: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 2412 MHz.




Figure 5: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 2412 MHz.



## 2.4 WLAN U-NII-2A HEAD SAR TEST RESULTS




Figure 6: SAR Head Testing Results for the DAQRI Smart Helmet at 5270 MHz.




Figure 7: SAR Head Testing Results for the DAQRI Smart Helmet at 5270 MHz.



## 2.5 WLAN U-NII-2A BODY-EXTREMITY SAR TEST RESULTS




Figure 8: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5270 MHz.




Figure 9: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5270 MHz.



## 2.6 WLAN U-NII-2C HEAD SAR TEST RESULTS




Figure 10: SAR Head Testing Results for the DAQRI Smart Helmet at 5590 MHz.




Figure 11: SAR Head Testing Results for the DAQRI Smart Helmet at 5590 MHz.



## 2.7 WLAN U-NII-2C BODY-EXTREMITY SAR TEST RESULTS




Figure 12: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5590 MHz.




Figure 13: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5590 MHz.



## 2.8 WLAN U-NII-3 HEAD SAR TEST RESULTS




Figure 14: SAR Head Testing Results for the DAQRI Smart Helmet at 5690 MHz.




Figure 15: SAR Head Testing Results for the DAQRI Smart Helmet at 5690 MHz.



## 2.9 WLAN U-NII-3 BODY-EXTREMITY SAR TEST RESULTS




Figure 16: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5690 MHz.




Figure 16: SAR Body-Extremity Testing Results for the DAQRI Smart Helmet at 5690 MHz.



Product Service

## **SECTION 3**

### **TEST EQUIPMENT USED**



### 3.1 TEST EQUIPMENT USED

The following test equipment was used at TÜV SÜD Product Service:

| Instrument Description                          | Manufacturer         | Model Type                             | TE Number | Cal Period (months) | Calibration Due Date |
|-------------------------------------------------|----------------------|----------------------------------------|-----------|---------------------|----------------------|
| 10MHz - 2.5GHz, 3W, Amplifier                   | Vectawave Technology | VTL5400                                | 51        | -                   | TU                   |
| Power Sensor                                    | Rohde & Schwarz      | NRV-Z1                                 | 60        | 12                  | 16-Jun-2017          |
| Signal Generator                                | Hewlett Packard      | ESG4000A                               | 61        | 12                  | 12-Jul-2017          |
| Attenuator (20dB, 10W)                          | Weinschel            | 37-20-34                               | 482       | 12                  | 26-Oct-2017          |
| Bi-directional Coupler                          | IndexSar Ltd         | 7401 (VDC0830-20)                      | 2414      | -                   | TU                   |
| Thermometer                                     | Digitron             | T208                                   | 64        | 12                  | 13-May-2017          |
| Hygrometer                                      | Rotronic             | I-1000                                 | 2784      | 12                  | 26-Apr-2017          |
| Power Sensor                                    | Rohde & Schwarz      | NRV- Z5                                | 2878      | 12                  | 16-Jun-2017          |
| Dual Channel Power Meter                        | Rohde & Schwarz      | NRVD                                   | 3259      | 12                  | 16-Jun-2017          |
| Data Acquisition Electronics                    | Speag                | DAE 4 - SD 000 D04 BM                  | 4689      | 12                  | 12-Dec-2017          |
| Measurement Server                              | Speag                | DASY 5 Measurement Server              | 4692      | -                   | TU                   |
| Body Phantom                                    | Speag                | ELI Phantom                            | 4699      | -                   | TU                   |
| Body Phantom                                    | Speag                | ELI Phantom                            | 4833      | -                   | TU                   |
| Dosimetric SAR Probe                            | Speag                | EX3DV4                                 | 4700      | 12                  | 16-Dec-2017          |
| Mounting Platform for TX90XL Robot and Phantoms | Speag                | MP6C-TX90XL Mounting Platform Extended | 4702      | -                   | TU                   |
| Robot                                           | Speag                | TX90 XLspeag Robot                     | 4704      | -                   | TU                   |
| 2450MHz Dipole                                  | Speag                | D2450V2                                | 3875      | 12                  | 14-Dec-2017          |
| 5000 MHz Dipole                                 | Speag                | D5000V2                                | 4796      | 12                  | 14-Dec-2017          |
| HBBL Fluid                                      | Speag                | Batch 2                                | N/A       | Weekly              | 06-Mar-2017          |
| MBBL Fluid                                      | Speag                | Batch 1                                | N/A       | Weekly              | 06-Mar-2017          |

TU = Traceability Unscheduled



Product Service

### 3.2 TEST SOFTWARE

The following software was used to control the TÜV SÜD Product Service DASY System.

| Instrument  | Version Number |
|-------------|----------------|
| DASY system | 52.8.8(1258)   |



Product Service

### 3.3 DIELECTRIC PROPERTIES OF SIMULANT LIQUIDS

The fluid properties of the simulant fluids used during routine SAR evaluation meet the dielectric properties required KDB 865665.

The dielectric properties of the tissue simulant liquids used for the SAR testing at TÜV SÜD Product Service are as follows:-

| Fluid Type and Frequency | Relative Permittivity Target | Relative Permittivity Measured | Conductivity Target | Conductivity Measured |
|--------------------------|------------------------------|--------------------------------|---------------------|-----------------------|
| 2450 MHz HBBL            | 39.20                        | 41.01                          | 1.80                | 1.86                  |
| 2450 MHz MBBL            | 52.70                        | 52.69                          | 1.95                | 2.02                  |
| 5200 MHz HBBL            | 35.99                        | 36.49                          | 4.66                | 4.64                  |
| 5200 MHz MBBL            | 49.01                        | 48.12                          | 5.30                | 5.38                  |
| 5500 MHz HBBL            | 35.64                        | 35.93                          | 4.96                | 4.98                  |
| 5500 MHz MBBL            | 48.61                        | 47.51                          | 5.65                | 5.80                  |
| 5800 MHz HBBL            | 35.30                        | 35.33                          | 5.27                | 5.34                  |
| 5800 MHz MBBL            | 48.20                        | 46.87                          | 6.00                | 6.25                  |



### 3.4 TEST CONDITIONS

#### 3.4.1 Test Laboratory Conditions

Ambient temperature: Within +15°C to +35°C.

The actual temperature during the testing ranged from 21.1°C to 22.7°C.

The actual humidity during the testing ranged from 33.0% to 40.9% RH.

#### 3.4.2 Test Fluid Temperature Range

| Frequency | Fluid | Min Temperature °C | Max Temperature °C |
|-----------|-------|--------------------|--------------------|
| 2450 MHz  | HBBL  | 20.9               | 20.9               |
| 2450 MHz  | MBBL  | 21.9               | 21.9               |
| 5200 MHz  | HBBL  | 21.6               | 21.6               |
| 5200 MHz  | MBBL  | 21.6               | 21.6               |
| 5500 MHz  | HBBL  | 21.6               | 21.6               |
| 5500 MHz  | MBBL  | 21.9               | 21.9               |
| 5800 MHz  | HBBL  | 21.9               | 21.9               |
| 5800 MHz  | MBBL  | 21.9               | 21.9               |

#### 3.4.3 SAR Drift

The maximum SAR Drift was recorded as 0.18 dB for head and 0.25 dB for body.



### 3.5 MEASUREMENT UNCERTAINTY

Head, Full SAR Measurements, 3 GHz to 6 GHz Using Probe EX3DV4 - SN3759

| Source of Uncertainty                | Uncertainty $\pm$ % | Probability distribution | Div  | $c_i$ (1g) | Standard Uncertainty $\pm$ % (1g) | $V_i$ ( $V_{eff}$ ) |
|--------------------------------------|---------------------|--------------------------|------|------------|-----------------------------------|---------------------|
| <b>Measurement System</b>            |                     |                          |      |            |                                   |                     |
| Probe calibration                    | 6.6                 | N                        | 1.00 | 1.00       | 6.6                               | Infinity            |
| Axial Isotropy                       | 4.7                 | R                        | 1.73 | 0.70       | 1.9                               | Infinity            |
| Hemispherical Isotropy               | 9.6                 | R                        | 1.73 | 0.70       | 3.9                               | Infinity            |
| Boundary effect                      | 2.0                 | R                        | 1.73 | 1.00       | 1.2                               | Infinity            |
| Linearity                            | 4.7                 | R                        | 1.73 | 1.00       | 2.7                               | Infinity            |
| System Detection limits              | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Modulation response                  | 2.4                 | R                        | 1.73 | 1.00       | 1.4                               | Infinity            |
| Readout electronics                  | 0.3                 | N                        | 1.00 | 1.00       | 0.3                               | Infinity            |
| Response time                        | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Integration time                     | 2.6                 | R                        | 1.73 | 1.00       | 1.5                               | Infinity            |
| RF ambient noise                     | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| RF ambient reflections               | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Probe positioner                     | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Probe positioning                    | 6.7                 | R                        | 1.73 | 1.00       | 3.9                               | Infinity            |
| Max SAR Evaluation                   | 4.0                 | R                        | 1.73 | 1.00       | 2.3                               | Infinity            |
| <b>Test sample related</b>           |                     |                          |      |            |                                   |                     |
| Device Positioning                   | 2.9                 | N                        | 1.00 | 1.00       | 2.9                               | 145                 |
| Device Holder                        | 3.6                 | N                        | 1.00 | 1.00       | 3.6                               | 5                   |
| Input Power and SAR Drift            | 5.0                 | R                        | 1.73 | 1.00       | 0.1                               | Infinity            |
| <b>Phantom and Setup</b>             |                     |                          |      |            |                                   |                     |
| Phantom uncertainty                  | 6.6                 | R                        | 1.73 | 1.00       | 3.8                               | Infinity            |
| SAR Correction                       | 1.9                 | R                        | 1.73 | 1.00       | 1.1                               | Infinity            |
| Liquid conductivity Meas.            | 2.5                 | R                        | 1.73 | 0.78       | 1.1                               | Infinity            |
| Liquid Permittivity Meas.            | 2.5                 | R                        | 1.73 | 0.23       | 0.3                               | Infinity            |
| Temp. Unc. Conductivity              | 3.4                 | R                        | 1.73 | 0.78       | 1.5                               | Infinity            |
| Temp. Unc. Permittivity              | 0.4                 | R                        | 1.73 | 0.23       | 0.1                               | Infinity            |
| <b>Combined Standard Uncertainty</b> |                     | <b>RSS</b>               |      |            | 11.9                              | 748                 |
| <b>Expanded Standard Uncertainty</b> |                     | <b>K=2</b>               |      |            | 23.9                              |                     |



## Head, Full SAR Measurements, 300 MHz to 3 GHz Using Probe EX3DV4 - SN3759

| Source of Uncertainty                | Uncertainty $\pm$ % | Probability distribution | Div  | $c_i$ (1g) | Standard Uncertainty $\pm$ % (1g) | $V_i$ ( $V_{eff}$ ) |
|--------------------------------------|---------------------|--------------------------|------|------------|-----------------------------------|---------------------|
| <b>Measurement System</b>            |                     |                          |      |            |                                   |                     |
| Probe calibration                    | 6.0                 | N                        | 1.00 | 1.00       | 6.0                               | Infinity            |
| Axial Isotropy                       | 4.7                 | R                        | 1.73 | 0.70       | 1.9                               | Infinity            |
| Hemispherical Isotropy               | 9.6                 | R                        | 1.73 | 0.70       | 3.9                               | Infinity            |
| Boundary effect                      | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Linearity                            | 4.7                 | R                        | 1.73 | 1.00       | 2.7                               | Infinity            |
| System Detection limits              | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Modulation response                  | 2.4                 | R                        | 1.73 | 1.00       | 1.4                               | Infinity            |
| Readout electronics                  | 0.3                 | N                        | 1.00 | 1.00       | 0.3                               | Infinity            |
| Response time                        | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Integration time                     | 2.6                 | R                        | 1.73 | 1.00       | 1.5                               | Infinity            |
| RF ambient noise                     | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| RF ambient reflections               | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Probe positioner                     | 0.4                 | R                        | 1.73 | 1.00       | 0.2                               | Infinity            |
| Probe positioning                    | 2.9                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Max SAR Evaluation                   | 2.0                 | R                        | 1.73 | 1.00       | 1.2                               | Infinity            |
| <b>Test sample related</b>           |                     |                          |      |            |                                   |                     |
| Device Positioning                   | 2.9                 | N                        | 1.00 | 1.00       | 2.9                               | 145                 |
| Device Holder                        | 3.6                 | N                        | 1.00 | 1.00       | 3.6                               | 5                   |
| Input Power and SAR Drift            | 5.0                 | R                        | 1.73 | 1.00       | 0.1                               | Infinity            |
| <b>Phantom and Setup</b>             |                     |                          |      |            |                                   |                     |
| Phantom uncertainty                  | 6.1                 | R                        | 1.73 | 1.00       | 3.5                               | Infinity            |
| SAR Correction                       | 1.9                 | R                        | 1.73 | 1.00       | 1.1                               | Infinity            |
| Liquid conductivity Meas.            | 2.5                 | R                        | 1.73 | 0.78       | 1.1                               | Infinity            |
| Liquid Permittivity Meas.            | 2.5                 | R                        | 1.73 | 0.23       | 0.3                               | Infinity            |
| Temp. Unc. Conductivity              | 3.4                 | R                        | 1.73 | 0.78       | 1.5                               | Infinity            |
| Temp. Unc. Permittivity              | 0.4                 | R                        | 1.73 | 0.23       | 0.1                               | Infinity            |
| <b>Combined Standard Uncertainty</b> |                     | <b>RSS</b>               |      |            | 10.8                              | 361                 |
| <b>Expanded Standard Uncertainty</b> |                     | <b>K=2</b>               |      |            | 21.5                              |                     |



Body, Full SAR Measurements, 300 MHz to 3 GHz Using Probe EX3DV4 - SN3759

| Source of Uncertainty                | Uncertainty $\pm$ % | Probability distribution | Div  | $c_i$ (1g) | Standard Uncertainty $\pm$ % (1g) | $V_i$ ( $V_{eff}$ ) |
|--------------------------------------|---------------------|--------------------------|------|------------|-----------------------------------|---------------------|
| <b>Measurement System</b>            |                     |                          |      |            |                                   |                     |
| Probe calibration                    | 6.0                 | N                        | 1.00 | 1.00       | 6.0                               | Infinity            |
| Axial Isotropy                       | 4.7                 | R                        | 1.73 | 0.70       | 1.9                               | Infinity            |
| Hemispherical Isotropy               | 9.6                 | R                        | 1.73 | 0.70       | 3.9                               | Infinity            |
| Boundary effect                      | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Linearity                            | 4.7                 | R                        | 1.73 | 1.00       | 2.7                               | Infinity            |
| System Detection limits              | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Modulation response                  | 2.4                 | R                        | 1.73 | 1.00       | 1.4                               | Infinity            |
| Readout electronics                  | 0.3                 | N                        | 1.00 | 1.00       | 0.3                               | Infinity            |
| Response time                        | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Integration time                     | 2.6                 | R                        | 1.73 | 1.00       | 1.5                               | Infinity            |
| RF ambient noise                     | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| RF ambient reflections               | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Probe positioner                     | 0.4                 | R                        | 1.73 | 1.00       | 0.2                               | Infinity            |
| Probe positioning                    | 2.9                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Max SAR Evaluation                   | 5.0                 | R                        | 1.73 | 1.00       | 1.2                               | Infinity            |
| <b>Test sample related</b>           |                     |                          |      |            |                                   |                     |
| Device Positioning                   | 2.9                 | N                        | 1.00 | 1.00       | 2.9                               | 145                 |
| Device Holder                        | 3.6                 | N                        | 1.00 | 1.00       | 3.6                               | 5                   |
| Input Power and SAR Drift            | 0.3                 | R                        | 1.73 | 1.00       | 0.1                               | Infinity            |
| <b>Phantom and Setup</b>             |                     |                          |      |            |                                   |                     |
| Phantom uncertainty                  | 6.1                 | R                        | 1.73 | 1.00       | 3.5                               | Infinity            |
| SAR Correction                       | 1.9                 | R                        | 1.73 | 1.00       | 1.1                               | Infinity            |
| Liquid conductivity Meas.            | 2.5                 | R                        | 1.73 | 0.78       | 1.1                               | Infinity            |
| Liquid Permittivity Meas.            | 2.5                 | R                        | 1.73 | 0.23       | 0.3                               | Infinity            |
| Temp. Unc. Conductivity              | 3.4                 | R                        | 1.73 | 0.78       | 1.5                               | Infinity            |
| Temp. Unc. Permittivity              | 0.4                 | R                        | 1.73 | 0.23       | 0.1                               | Infinity            |
| <b>Combined Standard Uncertainty</b> |                     | <b>RSS</b>               |      |            | 10.8                              | 361                 |
| <b>Expanded Standard Uncertainty</b> |                     | <b>K=2</b>               |      |            | 21.5                              |                     |



Body, Full SAR Measurements, 3 GHz to 6 GHz Using Probe EX3DV4 - SN3759

| Source of Uncertainty                | Uncertainty $\pm$ % | Probability distribution | Div  | $c_i$ (1g) | Standard Uncertainty $\pm$ % (1g) | $V_i$ ( $V_{eff}$ ) |
|--------------------------------------|---------------------|--------------------------|------|------------|-----------------------------------|---------------------|
| <b>Measurement System</b>            |                     |                          |      |            |                                   |                     |
| Probe calibration                    | 6.6                 | N                        | 1.00 | 1.00       | 6.6                               | Infinity            |
| Axial Isotropy                       | 4.7                 | R                        | 1.73 | 0.70       | 1.9                               | Infinity            |
| Hemispherical Isotropy               | 9.6                 | R                        | 1.73 | 0.70       | 3.9                               | Infinity            |
| Boundary effect                      | 2.0                 | R                        | 1.73 | 1.00       | 1.2                               | Infinity            |
| Linearity                            | 4.7                 | R                        | 1.73 | 1.00       | 2.7                               | Infinity            |
| System Detection limits              | 1.0                 | R                        | 1.73 | 1.00       | 0.6                               | Infinity            |
| Modulation response                  | 2.4                 | R                        | 1.73 | 1.00       | 1.4                               | Infinity            |
| Readout electronics                  | 0.3                 | N                        | 1.00 | 1.00       | 0.3                               | Infinity            |
| Response time                        | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Integration time                     | 2.6                 | R                        | 1.73 | 1.00       | 1.5                               | Infinity            |
| RF ambient noise                     | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| RF ambient reflections               | 3.0                 | R                        | 1.73 | 1.00       | 1.7                               | Infinity            |
| Probe positioner                     | 0.8                 | R                        | 1.73 | 1.00       | 0.5                               | Infinity            |
| Probe positioning                    | 6.7                 | R                        | 1.73 | 1.00       | 3.9                               | Infinity            |
| Max SAR Evaluation                   | 5.0                 | R                        | 1.73 | 1.00       | 2.3                               | Infinity            |
| <b>Test sample related</b>           |                     |                          |      |            |                                   |                     |
| Device Positioning                   | 2.9                 | N                        | 1.00 | 1.00       | 2.9                               | 145                 |
| Device Holder                        | 3.6                 | N                        | 1.00 | 1.00       | 3.6                               | 5                   |
| Input Power and SAR Drift            | 0.3                 | R                        | 1.73 | 1.00       | 0.1                               | Infinity            |
| <b>Phantom and Setup</b>             |                     |                          |      |            |                                   |                     |
| Phantom uncertainty                  | 6.6                 | R                        | 1.73 | 1.00       | 3.8                               | Infinity            |
| SAR Correction                       | 1.9                 | R                        | 1.73 | 1.00       | 1.1                               | Infinity            |
| Liquid conductivity Meas.            | 2.5                 | R                        | 1.73 | 0.78       | 1.1                               | Infinity            |
| Liquid Permittivity Meas.            | 2.5                 | R                        | 1.73 | 0.23       | 0.3                               | Infinity            |
| Temp. Unc. Conductivity              | 3.4                 | R                        | 1.73 | 0.78       | 1.5                               | Infinity            |
| Temp. Unc. Permittivity              | 0.4                 | R                        | 1.73 | 0.23       | 0.1                               | Infinity            |
| <b>Combined Standard Uncertainty</b> |                     | <b>RSS</b>               |      |            | 11.9                              | 748                 |
| <b>Expanded Standard Uncertainty</b> |                     | <b>K=2</b>               |      |            | 23.9                              |                     |



Product Service

## **SECTION 4**

### **ACCREDITATION, DISCLAIMERS AND COPYRIGHT**



#### 4.1 ACCREDITATION, DISCLAIMERS AND COPYRIGHT



This report relates only to the actual item/items tested.

Our UKAS Accreditation does not cover opinions and interpretations and any expressed are outside the scope of our UKAS Accreditation.

Results of tests not covered by our UKAS Accreditation Schedule are marked NUA (Not UKAS Accredited).

This report must not be reproduced, except in its entirety, without the written permission of TÜV SÜD Product Service

© 2017 TÜV SÜD Product Service



Product Service

## **ANNEX A**

### **PROBE CALIBRATION REPORT**



Product Service

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**Client **TüV SÜD UK**Certificate No: **EX3-3759\_Dec16****CALIBRATION CERTIFICATE**Object **EX3DV4 - SN:3759**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-12.v9, QA CAL-14.v4, QA CAL-23.v5,  
QA CAL-25.v6  
Calibration procedure for dosimetric E-field probes**

Calibration date: **December 16, 2016**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature ( $22 \pm 3$ )°C and humidity < 70%.

Calibration Equipment used (M&amp;TE critical for calibration)

| Primary Standards          | ID               | Cal Date (Certificate No.)        | Scheduled Calibration  |
|----------------------------|------------------|-----------------------------------|------------------------|
| Power meter NRP            | SN: 104778       | 06-Apr-16 (No. 217-02288/02289)   | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103244       | 06-Apr-16 (No. 217-02288)         | Apr-17                 |
| Power sensor NRP-Z91       | SN: 103245       | 06-Apr-16 (No. 217-02289)         | Apr-17                 |
| Reference 20 dB Attenuator | SN: S5277 (20x)  | 05-Apr-16 (No. 217-02293)         | Apr-17                 |
| Reference Probe ES3DV2     | SN: 3013         | 31-Dec-15 (No. ES3-3013_Dec15)    | Dec-16                 |
| DAE4                       | SN: 660          | 7-Dec-16 (No. DAE4-660_Dec16)     | Dec-17                 |
| Secondary Standards        | ID               | Check Date (in house)             | Scheduled Check        |
| Power meter E4419B         | SN: GB41293874   | 06-Apr-16 (in house check Jun-16) | In house check: Jun-18 |
| Power sensor E4412A        | SN: MY41498087   | 06-Apr-16 (in house check Jun-16) | In house check: Jun-18 |
| Power sensor E4412A        | SN: 000110210    | 06-Apr-16 (in house check Jun-16) | In house check: Jun-18 |
| RF generator HP 8648C      | SN: US3642U01700 | 04-Aug-99 (in house check Jun-16) | In house check: Jun-18 |
| Network Analyzer HP 8753E  | SN: US37390585   | 18-Oct-01 (in house check Oct-16) | In house check: Oct-17 |

|                                                                                                                 | Name          | Function              | Signature |
|-----------------------------------------------------------------------------------------------------------------|---------------|-----------------------|-----------|
| Calibrated by:                                                                                                  | Michael Weber | Laboratory Technician |           |
| Approved by:                                                                                                    | Katja Pokovic | Technical Manager     |           |
| This calibration certificate shall not be reproduced except in full without written approval of the laboratory. |               |                       |           |
| Issued: December 19, 2016                                                                                       |               |                       |           |

Certificate No: EX3-3759\_Dec16

Page 1 of 38



Product Service

**Calibration Laboratory of  
Schmid & Partner  
Engineering AG**  
Zeughausstrasse 43, 8004 Zurich, Switzerland



**S** Schweizerischer Kalibrierdienst  
**C** Service suisse d'étalonnage  
**S** Servizio svizzero di taratura  
**S** Swiss Calibration Service

Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108****Glossary:**

|                          |                                                                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| TSL                      | tissue simulating liquid                                                                                                                                |
| NORM <sub>x,y,z</sub>    | sensitivity in free space                                                                                                                               |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>                                                                                                              |
| DCP                      | diode compression point                                                                                                                                 |
| CF                       | crest factor (1/duty_cycle) of the RF signal                                                                                                            |
| A, B, C, D               | modulation dependent linearization parameters                                                                                                           |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis                                                                                                                    |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |
| Connector Angle          | information used in DASY system to align probe sensor X to the robot coordinate system                                                                  |

**Calibration is Performed According to the Following Standards:**

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

**Methods Applied and Interpretation of Parameters:**

- NORM<sub>x,y,z</sub>:** Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). NORM<sub>x,y,z</sub> are only intermediate values, i.e., the uncertainties of NORM<sub>x,y,z</sub> does not affect the  $E^2$ -field uncertainty inside TSL (see below ConvF).
- NORM(f)<sub>x,y,z</sub> = NORM<sub>x,y,z</sub> \* frequency\_response** (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP<sub>x,y,z</sub>:** DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR:** PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A<sub>x,y,z</sub>; B<sub>x,y,z</sub>; C<sub>x,y,z</sub>; D<sub>x,y,z</sub>; VR<sub>x,y,z</sub>:** A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters:** Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM<sub>x,y,z</sub> \* ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- Spherical isotropy (3D deviation from isotropy):** in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset:** The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle:** The angle is assessed using the information gained by determining the NORM<sub>x</sub> (no uncertainty required).



Product Service

EX3DV4 – SN:3759

December 16, 2016

# Probe EX3DV4

## SN:3759

Manufactured: March 16, 2010  
Calibrated: December 16, 2016

Calibrated for DASY/EASY Systems  
(Note: non-compatible with DASY2 system!)



EX3DV4- SN:3759

December 16, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3759

### Basic Calibration Parameters

|                                                           | Sensor X | Sensor Y | Sensor Z | Unc (k=2)     |
|-----------------------------------------------------------|----------|----------|----------|---------------|
| Norm ( $\mu\text{V}/(\text{V}/\text{m})^2$ ) <sup>A</sup> | 0.47     | 0.42     | 0.45     | $\pm 10.1 \%$ |
| DCP (mV) <sup>B</sup>                                     | 101.1    | 99.1     | 101.2    |               |

### Modulation Calibration Parameters

| UID | Communication System Name |   | A<br>dB | B<br>dB $\sqrt{\mu\text{V}}$ | C   | D<br>dB | VR<br>mV | Unc <sup>E</sup><br>(k=2) |
|-----|---------------------------|---|---------|------------------------------|-----|---------|----------|---------------------------|
| 0   | CW                        | X | 0.0     | 0.0                          | 1.0 | 0.00    | 149.0    | $\pm 3.5 \%$              |
|     |                           | Y | 0.0     | 0.0                          | 1.0 |         | 147.4    |                           |
|     |                           | Z | 0.0     | 0.0                          | 1.0 |         | 138.4    |                           |

Note: For details on UID parameters see Appendix.

### Sensor Model Parameters

|   | C1<br>fF | C2<br>fF | $\alpha$<br>$\text{V}^{-1}$ | T1<br>$\text{ms} \cdot \text{V}^{-2}$ | T2<br>$\text{ms} \cdot \text{V}^{-1}$ | T3<br>ms | T4<br>$\text{V}^{-2}$ | T5<br>$\text{V}^{-1}$ | T6    |
|---|----------|----------|-----------------------------|---------------------------------------|---------------------------------------|----------|-----------------------|-----------------------|-------|
| X | 45.34    | 339.8    | 35.83                       | 13.18                                 | 1.015                                 | 4.992    | 0.942                 | 0.363                 | 1.005 |
| Y | 51.23    | 384.3    | 35.89                       | 14.75                                 | 0.946                                 | 5.017    | 1.083                 | 0.33                  | 1.006 |
| Z | 48.36    | 361.1    | 35.6                        | 14.31                                 | 1.297                                 | 4.99     | 0.629                 | 0.453                 | 1.004 |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor  $k=2$ , which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of Norm X,Y,Z do not affect the  $E^2$ -field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter; uncertainty not required.

<sup>E</sup> Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.



EX3DV4- SN:3759

December 16, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3759

### Calibration Parameter Determined in Head Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 450                  | 43.5                               | 0.87                            | 10.95   | 10.95   | 10.95   | 0.15               | 1.30                    | ± 13.3 %  |
| 750                  | 41.9                               | 0.89                            | 10.45   | 10.45   | 10.45   | 0.28               | 1.01                    | ± 12.0 %  |
| 835                  | 41.5                               | 0.90                            | 10.04   | 10.04   | 10.04   | 0.16               | 1.40                    | ± 12.0 %  |
| 900                  | 41.5                               | 0.97                            | 9.94    | 9.94    | 9.94    | 0.24               | 0.97                    | ± 12.0 %  |
| 1640                 | 40.3                               | 1.29                            | 8.63    | 8.63    | 8.63    | 0.19               | 0.80                    | ± 12.0 %  |
| 1750                 | 40.1                               | 1.37                            | 8.58    | 8.58    | 8.58    | 0.18               | 0.96                    | ± 12.0 %  |
| 1900                 | 40.0                               | 1.40                            | 8.32    | 8.32    | 8.32    | 0.14               | 0.86                    | ± 12.0 %  |
| 2100                 | 39.8                               | 1.49                            | 8.45    | 8.45    | 8.45    | 0.23               | 0.84                    | ± 12.0 %  |
| 2300                 | 39.5                               | 1.67                            | 7.80    | 7.80    | 7.80    | 0.15               | 1.07                    | ± 12.0 %  |
| 2450                 | 39.2                               | 1.80                            | 7.42    | 7.42    | 7.42    | 0.23               | 0.86                    | ± 12.0 %  |
| 2600                 | 39.0                               | 1.96                            | 7.16    | 7.16    | 7.16    | 0.20               | 1.08                    | ± 12.0 %  |
| 5200                 | 36.0                               | 4.66                            | 5.68    | 5.68    | 5.68    | 0.30               | 1.80                    | ± 13.1 %  |
| 5300                 | 35.9                               | 4.76                            | 5.46    | 5.46    | 5.46    | 0.30               | 1.80                    | ± 13.1 %  |
| 5500                 | 35.6                               | 4.96                            | 5.05    | 5.05    | 5.05    | 0.35               | 1.80                    | ± 13.1 %  |
| 5600                 | 35.5                               | 5.07                            | 4.72    | 4.72    | 4.72    | 0.40               | 1.80                    | ± 13.1 %  |
| 5800                 | 35.3                               | 5.27                            | 5.02    | 5.02    | 5.02    | 0.40               | 1.80                    | ± 13.1 %  |

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



EX3DV4- SN:3759

December 16, 2016

## DASY/EASY - Parameters of Probe: EX3DV4 - SN:3759

### Calibration Parameter Determined in Body Tissue Simulating Media

| f (MHz) <sup>C</sup> | Relative Permittivity <sup>F</sup> | Conductivity (S/m) <sup>F</sup> | ConvF X | ConvF Y | ConvF Z | Alpha <sup>G</sup> | Depth <sup>G</sup> (mm) | Unc (k=2) |
|----------------------|------------------------------------|---------------------------------|---------|---------|---------|--------------------|-------------------------|-----------|
| 450                  | 56.7                               | 0.94                            | 11.67   | 11.67   | 11.67   | 0.05               | 1.20                    | ± 13.3 %  |
| 750                  | 55.5                               | 0.96                            | 10.25   | 10.25   | 10.25   | 0.31               | 0.85                    | ± 12.0 %  |
| 835                  | 55.2                               | 0.97                            | 9.85    | 9.85    | 9.85    | 0.16               | 1.31                    | ± 12.0 %  |
| 900                  | 55.0                               | 1.05                            | 9.83    | 9.83    | 9.83    | 0.29               | 0.86                    | ± 12.0 %  |
| 1640                 | 53.8                               | 1.40                            | 8.63    | 8.63    | 8.63    | 0.26               | 0.80                    | ± 12.0 %  |
| 1750                 | 53.4                               | 1.49                            | 8.16    | 8.16    | 8.16    | 0.27               | 0.86                    | ± 12.0 %  |
| 1900                 | 53.3                               | 1.52                            | 7.87    | 7.87    | 7.87    | 0.21               | 0.96                    | ± 12.0 %  |
| 2100                 | 53.2                               | 1.62                            | 8.26    | 8.26    | 8.26    | 0.16               | 1.04                    | ± 12.0 %  |
| 2300                 | 52.9                               | 1.81                            | 7.56    | 7.56    | 7.56    | 0.29               | 0.80                    | ± 12.0 %  |
| 2450                 | 52.7                               | 1.95                            | 7.49    | 7.49    | 7.49    | 0.11               | 0.99                    | ± 12.0 %  |
| 2600                 | 52.5                               | 2.16                            | 7.31    | 7.31    | 7.31    | 0.14               | 1.10                    | ± 12.0 %  |
| 5200                 | 49.0                               | 5.30                            | 5.00    | 5.00    | 5.00    | 0.35               | 1.90                    | ± 13.1 %  |
| 5300                 | 48.9                               | 5.42                            | 4.78    | 4.78    | 4.78    | 0.35               | 1.90                    | ± 13.1 %  |
| 5500                 | 48.6                               | 5.65                            | 4.27    | 4.27    | 4.27    | 0.40               | 1.90                    | ± 13.1 %  |
| 5600                 | 48.5                               | 5.77                            | 3.98    | 3.98    | 3.98    | 0.50               | 1.90                    | ± 13.1 %  |
| 5800                 | 48.2                               | 6.00                            | 4.20    | 4.20    | 4.20    | 0.50               | 1.90                    | ± 13.1 %  |

<sup>C</sup> Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Above 5 GHz frequency validity can be extended to ± 110 MHz.

<sup>F</sup> At frequencies below 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters ( $\epsilon$  and  $\sigma$ ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.


<sup>G</sup> Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.



EX3DV4— SN:3759

December 16, 2016




### Frequency Response of E-Field (TEM-Cell: ifi110 EXX, Waveguide: R22)

Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  ( $k=2$ )



EX3DV4— SN:3759

December 16, 2016



**Receiving Pattern ( $\phi$ ),  $\vartheta = 0^\circ$** **f=600 MHz,TEM****f=1800 MHz,R22****Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )**



EX3DV4- SN:3759

December 16, 2016

### Dynamic Range $f(\text{SAR}_{\text{head}})$ (TEM cell , $f_{\text{eval}} = 1900 \text{ MHz}$ )


Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )



EX3DV4- SN:3759



December 16, 2016

## Conversion Factor Assessment



## Deviation from Isotropy in Liquid

Error ( $\phi$ ,  $\theta$ ),  $f = 900 \text{ MHz}$



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  ( $k=2$ )



EX3DV4— SN:3759

December 16, 2016

**DASY/EASY - Parameters of Probe: EX3DV4 - SN:3759****Other Probe Parameters**

|                                               |            |
|-----------------------------------------------|------------|
| Sensor Arrangement                            | Triangular |
| Connector Angle (°)                           | -3         |
| Mechanical Surface Detection Mode             | enabled    |
| Optical Surface Detection Mode                | disabled   |
| Probe Overall Length                          | 337 mm     |
| Probe Body Diameter                           | 10 mm      |
| Tip Length                                    | 9 mm       |
| Tip Diameter                                  | 2.5 mm     |
| Probe Tip to Sensor X Calibration Point       | 1 mm       |
| Probe Tip to Sensor Y Calibration Point       | 1 mm       |
| Probe Tip to Sensor Z Calibration Point       | 1 mm       |
| Recommended Measurement Distance from Surface | 1.4 mm     |



EX3DV4- SN:3759

December 16, 2016

**Appendix: Modulation Calibration Parameters**

| UID           | Communication System Name                     |   | A<br>dB | B<br>dB $\sqrt{\mu V}$ | C     | D<br>dB | VR<br>mV | Max<br>Unc <sup>E</sup><br>(k=2) |
|---------------|-----------------------------------------------|---|---------|------------------------|-------|---------|----------|----------------------------------|
| 0             | CW                                            | X | 0.00    | 0.00                   | 1.00  | 0.00    | 149.0    | $\pm 3.5\%$                      |
|               |                                               | Y | 0.00    | 0.00                   | 1.00  |         | 147.4    |                                  |
|               |                                               | Z | 0.00    | 0.00                   | 1.00  |         | 138.4    |                                  |
| 10010-<br>CAA | SAR Validation (Square, 100ms, 10ms)          | X | 3.04    | 67.74                  | 11.79 | 10.00   | 20.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 3.27    | 68.79                  | 12.30 |         | 20.0     |                                  |
|               |                                               | Z | 3.42    | 68.76                  | 12.60 |         | 20.0     |                                  |
| 10011-<br>CAB | UMTS-FDD (WCDMA)                              | X | 0.99    | 66.30                  | 14.68 | 0.00    | 150.0    | $\pm 9.6\%$                      |
|               |                                               | Y | 1.02    | 66.67                  | 14.90 |         | 150.0    |                                  |
|               |                                               | Z | 0.99    | 66.23                  | 14.64 |         | 150.0    |                                  |
| 10012-<br>CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 1 Mbps)      | X | 1.17    | 63.37                  | 14.79 | 0.41    | 150.0    | $\pm 9.6\%$                      |
|               |                                               | Y | 1.18    | 63.58                  | 14.98 |         | 150.0    |                                  |
|               |                                               | Z | 1.18    | 63.40                  | 14.78 |         | 150.0    |                                  |
| 10013-<br>CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS-OFDM, 6 Mbps) | X | 4.83    | 66.46                  | 16.84 | 1.46    | 150.0    | $\pm 9.6\%$                      |
|               |                                               | Y | 4.90    | 66.50                  | 16.94 |         | 150.0    |                                  |
|               |                                               | Z | 4.87    | 66.45                  | 16.82 |         | 150.0    |                                  |
| 10021-<br>DAC | GSM-FDD (TDMA, GMSK)                          | X | 27.32   | 96.15                  | 23.00 | 9.39    | 50.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 113.48                 | 27.55 |         | 50.0     |                                  |
|               |                                               | Z | 18.13   | 91.34                  | 22.13 |         | 50.0     |                                  |
| 10023-<br>DAC | GPRS-FDD (TDMA, GMSK, TN 0)                   | X | 17.75   | 90.44                  | 21.39 | 9.57    | 50.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 64.93   | 107.78                 | 26.22 |         | 50.0     |                                  |
|               |                                               | Z | 13.93   | 87.63                  | 21.03 |         | 50.0     |                                  |
| 10024-<br>DAC | GPRS-FDD (TDMA, GMSK, TN 0-1)                 | X | 100.00  | 110.23                 | 24.91 | 6.56    | 60.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 111.43                 | 25.52 |         | 60.0     |                                  |
|               |                                               | Z | 66.71   | 106.54                 | 24.55 |         | 60.0     |                                  |
| 10025-<br>DAC | EDGE-FDD (TDMA, 8PSK, TN 0)                   | X | 4.69    | 70.97                  | 25.39 | 12.57   | 50.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 9.43    | 92.86                  | 36.24 |         | 50.0     |                                  |
|               |                                               | Z | 4.57    | 69.11                  | 24.07 |         | 50.0     |                                  |
| 10026-<br>DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1)                 | X | 8.47    | 87.67                  | 30.15 | 9.56    | 60.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 11.37   | 95.44                  | 33.46 |         | 60.0     |                                  |
|               |                                               | Z | 8.88    | 87.57                  | 29.82 |         | 60.0     |                                  |
| 10027-<br>DAC | GPRS-FDD (TDMA, GMSK, TN 0-1-2)               | X | 100.00  | 109.77                 | 23.94 | 4.80    | 80.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 111.14                 | 24.62 |         | 80.0     |                                  |
|               |                                               | Z | 100.00  | 110.40                 | 24.46 |         | 80.0     |                                  |
| 10028-<br>DAC | GPRS-FDD (TDMA, GMSK, TN 0-1-2-3)             | X | 100.00  | 110.50                 | 23.60 | 3.55    | 100.0    | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 111.94                 | 24.31 |         | 100.0    |                                  |
|               |                                               | Z | 100.00  | 110.79                 | 23.94 |         | 100.0    |                                  |
| 10029-<br>DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2)               | X | 5.65    | 79.24                  | 25.77 | 7.80    | 80.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 6.78    | 83.68                  | 27.89 |         | 80.0     |                                  |
|               |                                               | Z | 6.05    | 79.84                  | 25.79 |         | 80.0     |                                  |
| 10030-<br>CAA | IEEE 802.15.1 Bluetooth (GFSK, DH1)           | X | 100.00  | 108.40                 | 23.61 | 5.30    | 70.0     | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 109.85                 | 24.34 |         | 70.0     |                                  |
|               |                                               | Z | 39.21   | 99.31                  | 21.96 |         | 70.0     |                                  |
| 10031-<br>CAA | IEEE 802.15.1 Bluetooth (GFSK, DH3)           | X | 100.00  | 109.64                 | 22.00 | 1.88    | 100.0    | $\pm 9.6\%$                      |
|               |                                               | Y | 100.00  | 111.22                 | 22.73 |         | 100.0    |                                  |
|               |                                               | Z | 100.00  | 109.98                 | 22.33 |         | 100.0    |                                  |



EX3DV4- SN:3759

December 16, 2016

|           |                                                     |   |        |        |       |       |       |         |
|-----------|-----------------------------------------------------|---|--------|--------|-------|-------|-------|---------|
| 10032-CAA | IEEE 802.15.1 Bluetooth (GFSK, DH5)                 | X | 100.00 | 115.35 | 23.50 | 1.17  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 100.00 | 116.40 | 23.97 |       | 100.0 |         |
|           |                                                     | Z | 100.00 | 114.90 | 23.50 |       | 100.0 |         |
| 10033-CAA | IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH1)           | X | 5.50   | 80.43  | 20.01 | 5.30  | 70.0  | ± 9.6 % |
|           |                                                     | Y | 8.78   | 88.43  | 23.32 |       | 70.0  |         |
|           |                                                     | Z | 5.52   | 79.91  | 19.94 |       | 70.0  |         |
| 10034-CAA | IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH3)           | X | 2.26   | 72.05  | 15.71 | 1.88  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 2.75   | 75.11  | 17.48 |       | 100.0 |         |
|           |                                                     | Z | 2.35   | 72.23  | 15.94 |       | 100.0 |         |
| 10035-CAA | IEEE 802.15.1 Bluetooth (PI/4-DQPSK, DH5)           | X | 1.71   | 69.83  | 14.64 | 1.17  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 1.95   | 71.69  | 15.93 |       | 100.0 |         |
|           |                                                     | Z | 1.77   | 69.99  | 14.88 |       | 100.0 |         |
| 10036-CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH1)               | X | 6.42   | 82.93  | 20.96 | 5.30  | 70.0  | ± 9.6 % |
|           |                                                     | Y | 11.14  | 92.31  | 24.62 |       | 70.0  |         |
|           |                                                     | Z | 6.34   | 82.16  | 20.81 |       | 70.0  |         |
| 10037-CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH3)               | X | 2.14   | 71.45  | 15.43 | 1.88  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 2.61   | 74.51  | 17.21 |       | 100.0 |         |
|           |                                                     | Z | 2.24   | 71.69  | 15.69 |       | 100.0 |         |
| 10038-CAA | IEEE 802.15.1 Bluetooth (8-DPSK, DH5)               | X | 1.72   | 70.07  | 14.85 | 1.17  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 1.96   | 72.01  | 16.17 |       | 100.0 |         |
|           |                                                     | Z | 1.78   | 70.24  | 15.09 |       | 100.0 |         |
| 10039-CAB | CDMA2000 (1xRTT, RC1)                               | X | 1.67   | 70.78  | 15.04 | 0.00  | 150.0 | ± 9.6 % |
|           |                                                     | Y | 1.78   | 71.15  | 15.56 |       | 150.0 |         |
|           |                                                     | Z | 1.72   | 70.94  | 15.32 |       | 150.0 |         |
| 10042-CAB | IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Halfrate) | X | 22.45  | 92.22  | 20.50 | 7.78  | 50.0  | ± 9.6 % |
|           |                                                     | Y | 100.00 | 109.74 | 25.02 |       | 50.0  |         |
|           |                                                     | Z | 17.06  | 89.50  | 20.18 |       | 50.0  |         |
| 10044-CAA | IS-91/EIA/TIA-553 FDD (FDMA, FM)                    | X | 0.00   | 92.98  | 2.04  | 0.00  | 150.0 | ± 9.6 % |
|           |                                                     | Y | 0.00   | 94.50  | 2.19  |       | 150.0 |         |
|           |                                                     | Z | 0.00   | 94.03  | 3.01  |       | 150.0 |         |
| 10048-CAA | DECT (TDD, TDMA/FDM, GFSK, Full Slot, 24)           | X | 8.86   | 78.37  | 18.88 | 13.80 | 25.0  | ± 9.6 % |
|           |                                                     | Y | 12.87  | 84.32  | 21.06 |       | 25.0  |         |
|           |                                                     | Z | 8.56   | 78.04  | 19.28 |       | 25.0  |         |
| 10049-CAA | DECT (TDD, TDMA/FDM, GFSK, Double Slot, 12)         | X | 9.63   | 81.59  | 18.85 | 10.79 | 40.0  | ± 9.6 % |
|           |                                                     | Y | 15.92  | 88.85  | 21.37 |       | 40.0  |         |
|           |                                                     | Z | 9.22   | 81.13  | 19.17 |       | 40.0  |         |
| 10056-CAA | UMTS-TDD (TD-SCDMA, 1.28 Mcps)                      | X | 9.68   | 84.10  | 21.63 | 9.03  | 50.0  | ± 9.6 % |
|           |                                                     | Y | 14.40  | 91.26  | 24.48 |       | 50.0  |         |
|           |                                                     | Z | 8.89   | 82.35  | 21.22 |       | 50.0  |         |
| 10058-DAC | EDGE-FDD (TDMA, 8PSK, TN 0-1-2-3)                   | X | 4.44   | 74.95  | 23.28 | 6.55  | 100.0 | ± 9.6 % |
|           |                                                     | Y | 5.07   | 77.93  | 24.80 |       | 100.0 |         |
|           |                                                     | Z | 4.74   | 75.63  | 23.39 |       | 100.0 |         |
| 10059-CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 2 Mbps)            | X | 1.20   | 64.26  | 15.22 | 0.61  | 110.0 | ± 9.6 % |
|           |                                                     | Y | 1.22   | 64.64  | 15.52 |       | 110.0 |         |
|           |                                                     | Z | 1.22   | 64.34  | 15.22 |       | 110.0 |         |
| 10060-CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 5.5 Mbps)          | X | 3.05   | 83.81  | 21.08 | 1.30  | 110.0 | ± 9.6 % |
|           |                                                     | Y | 6.45   | 94.80  | 24.64 |       | 110.0 |         |
|           |                                                     | Z | 3.16   | 83.51  | 20.82 |       | 110.0 |         |



EX3DV4— SN:3759

December 16, 2016

|           |                                                |   |      |       |       |      |       |         |
|-----------|------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10061-CAB | IEEE 802.11b WiFi 2.4 GHz (DSSS, 11 Mbps)      | X | 2.26 | 74.64 | 19.29 | 2.04 | 110.0 | ± 9.6 % |
|           |                                                | Y | 2.80 | 78.34 | 20.99 |      | 110.0 |         |
|           |                                                | Z | 2.40 | 74.91 | 19.27 |      | 110.0 |         |
| 10062-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 6 Mbps)       | X | 4.64 | 66.51 | 16.35 | 0.49 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.71 | 66.52 | 16.41 |      | 100.0 |         |
|           |                                                | Z | 4.68 | 66.50 | 16.34 |      | 100.0 |         |
| 10063-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 9 Mbps)       | X | 4.65 | 66.58 | 16.42 | 0.72 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.72 | 66.60 | 16.50 |      | 100.0 |         |
|           |                                                | Z | 4.69 | 66.57 | 16.41 |      | 100.0 |         |
| 10064-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 12 Mbps)      | X | 4.93 | 66.82 | 16.63 | 0.86 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.02 | 66.89 | 16.73 |      | 100.0 |         |
|           |                                                | Z | 4.98 | 66.83 | 16.63 |      | 100.0 |         |
| 10065-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 18 Mbps)      | X | 4.80 | 66.69 | 16.70 | 1.21 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.89 | 66.77 | 16.81 |      | 100.0 |         |
|           |                                                | Z | 4.84 | 66.71 | 16.69 |      | 100.0 |         |
| 10066-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 24 Mbps)      | X | 4.81 | 66.69 | 16.83 | 1.46 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.90 | 66.80 | 16.97 |      | 100.0 |         |
|           |                                                | Z | 4.86 | 66.71 | 16.83 |      | 100.0 |         |
| 10067-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 36 Mbps)      | X | 5.10 | 66.85 | 17.25 | 2.04 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.19 | 66.91 | 17.37 |      | 100.0 |         |
|           |                                                | Z | 5.15 | 66.85 | 17.23 |      | 100.0 |         |
| 10068-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 48 Mbps)      | X | 5.14 | 66.87 | 17.43 | 2.55 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.25 | 67.04 | 17.62 |      | 100.0 |         |
|           |                                                | Z | 5.21 | 66.92 | 17.43 |      | 100.0 |         |
| 10069-CAB | IEEE 802.11a/h WiFi 5 GHz (OFDM, 54 Mbps)      | X | 5.22 | 66.88 | 17.62 | 2.67 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.33 | 67.01 | 17.80 |      | 100.0 |         |
|           |                                                | Z | 5.29 | 66.91 | 17.62 |      | 100.0 |         |
| 10071-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 9 Mbps)  | X | 4.92 | 66.52 | 17.10 | 1.99 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.99 | 66.58 | 17.23 |      | 100.0 |         |
|           |                                                | Z | 4.96 | 66.52 | 17.09 |      | 100.0 |         |
| 10072-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 12 Mbps) | X | 4.90 | 66.80 | 17.28 | 2.30 | 100.0 | ± 9.6 % |
|           |                                                | Y | 4.98 | 66.91 | 17.43 |      | 100.0 |         |
|           |                                                | Z | 4.95 | 66.83 | 17.27 |      | 100.0 |         |
| 10073-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 18 Mbps) | X | 4.96 | 66.95 | 17.56 | 2.83 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.04 | 67.07 | 17.74 |      | 100.0 |         |
|           |                                                | Z | 5.01 | 66.98 | 17.56 |      | 100.0 |         |
| 10074-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 24 Mbps) | X | 4.95 | 66.85 | 17.70 | 3.30 | 100.0 | ± 9.6 % |
|           |                                                | Y | 5.02 | 66.97 | 17.89 |      | 100.0 |         |
|           |                                                | Z | 5.01 | 66.89 | 17.70 |      | 100.0 |         |
| 10075-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 36 Mbps) | X | 4.99 | 66.96 | 17.98 | 3.82 | 90.0  | ± 9.6 % |
|           |                                                | Y | 5.08 | 67.14 | 18.22 |      | 90.0  |         |
|           |                                                | Z | 5.06 | 67.04 | 18.00 |      | 90.0  |         |
| 10076-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 48 Mbps) | X | 5.01 | 66.78 | 18.11 | 4.15 | 90.0  | ± 9.6 % |
|           |                                                | Y | 5.08 | 66.91 | 18.32 |      | 90.0  |         |
|           |                                                | Z | 5.08 | 66.85 | 18.11 |      | 90.0  |         |
| 10077-CAB | IEEE 802.11g WiFi 2.4 GHz (DSSS/OFDM, 54 Mbps) | X | 5.04 | 66.85 | 18.20 | 4.30 | 90.0  | ± 9.6 % |
|           |                                                | Y | 5.10 | 66.97 | 18.41 |      | 90.0  |         |
|           |                                                | Z | 5.10 | 66.92 | 18.20 |      | 90.0  |         |



EX3DV4- SN:3759

December 16, 2016

|           |                                                     |   |        |        |       |      |       |         |
|-----------|-----------------------------------------------------|---|--------|--------|-------|------|-------|---------|
| 10081-CAB | CDMA2000 (1xRTT, RC3)                               | X | 0.80   | 65.24  | 12.08 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 0.85   | 65.56  | 12.59 |      | 150.0 |         |
|           |                                                     | Z | 0.82   | 65.35  | 12.34 |      | 150.0 |         |
| 10082-CAB | IS-54 / IS-136 FDD (TDMA/FDM, PI/4-DQPSK, Fullrate) | X | 0.68   | 58.27  | 3.79  | 4.77 | 80.0  | ± 9.6 % |
|           |                                                     | Y | 0.86   | 60.00  | 4.99  |      | 80.0  |         |
|           |                                                     | Z | 0.80   | 58.87  | 4.46  |      | 80.0  |         |
| 10090-DAC | GPRS-FDD (TDMA, GMSK, TN 0-4)                       | X | 100.00 | 110.24 | 24.94 | 6.56 | 60.0  | ± 9.6 % |
|           |                                                     | Y | 100.00 | 111.45 | 25.55 |      | 60.0  |         |
|           |                                                     | Z | 61.75  | 105.66 | 24.37 |      | 60.0  |         |
| 10097-CAB | UMTS-FDD (HSDPA)                                    | X | 1.80   | 67.24  | 15.39 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 1.81   | 67.18  | 15.46 |      | 150.0 |         |
|           |                                                     | Z | 1.80   | 67.11  | 15.37 |      | 150.0 |         |
| 10098-CAB | UMTS-FDD (HSUPA, Subtest 2)                         | X | 1.76   | 67.18  | 15.35 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 1.78   | 67.13  | 15.43 |      | 150.0 |         |
|           |                                                     | Z | 1.76   | 67.04  | 15.33 |      | 150.0 |         |
| 10099-DAC | EDGE-FDD (TDMA, 8PSK, TN 0-4)                       | X | 8.51   | 87.74  | 30.17 | 9.56 | 60.0  | ± 9.6 % |
|           |                                                     | Y | 11.43  | 95.53  | 33.48 |      | 60.0  |         |
|           |                                                     | Z | 8.91   | 87.61  | 29.83 |      | 60.0  |         |
| 10100-CAC | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, QPSK)            | X | 3.05   | 69.78  | 16.46 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 3.13   | 70.04  | 16.53 |      | 150.0 |         |
|           |                                                     | Z | 3.07   | 69.82  | 16.43 |      | 150.0 |         |
| 10101-CAC | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)          | X | 3.21   | 67.25  | 15.78 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 3.26   | 67.38  | 15.84 |      | 150.0 |         |
|           |                                                     | Z | 3.23   | 67.28  | 15.77 |      | 150.0 |         |
| 10102-CAC | LTE-FDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)          | X | 3.31   | 67.26  | 15.89 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 3.37   | 67.35  | 15.94 |      | 150.0 |         |
|           |                                                     | Z | 3.34   | 67.28  | 15.89 |      | 150.0 |         |
| 10103-CAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, QPSK)            | X | 5.95   | 73.98  | 19.42 | 3.98 | 65.0  | ± 9.6 % |
|           |                                                     | Y | 6.46   | 75.28  | 20.05 |      | 65.0  |         |
|           |                                                     | Z | 5.88   | 73.30  | 19.04 |      | 65.0  |         |
| 10104-CAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 16-QAM)          | X | 6.15   | 72.74  | 19.68 | 3.98 | 65.0  | ± 9.6 % |
|           |                                                     | Y | 6.50   | 73.70  | 20.23 |      | 65.0  |         |
|           |                                                     | Z | 6.36   | 72.92  | 19.68 |      | 65.0  |         |
| 10105-CAC | LTE-TDD (SC-FDMA, 100% RB, 20 MHz, 64-QAM)          | X | 5.78   | 71.44  | 19.39 | 3.98 | 65.0  | ± 9.6 % |
|           |                                                     | Y | 6.20   | 72.69  | 20.09 |      | 65.0  |         |
|           |                                                     | Z | 6.26   | 72.53  | 19.82 |      | 65.0  |         |
| 10108-CAD | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, QPSK)            | X | 2.66   | 69.02  | 16.27 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 2.74   | 69.24  | 16.34 |      | 150.0 |         |
|           |                                                     | Z | 2.69   | 69.04  | 16.24 |      | 150.0 |         |
| 10109-CAD | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 16-QAM)          | X | 2.86   | 67.09  | 15.67 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 2.92   | 67.19  | 15.74 |      | 150.0 |         |
|           |                                                     | Z | 2.89   | 67.10  | 15.67 |      | 150.0 |         |
| 10110-CAD | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, QPSK)             | X | 2.15   | 68.08  | 15.82 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 2.23   | 68.29  | 15.94 |      | 150.0 |         |
|           |                                                     | Z | 2.18   | 68.07  | 15.80 |      | 150.0 |         |
| 10111-CAD | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 16-QAM)           | X | 2.58   | 67.97  | 15.95 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                     | Y | 2.63   | 67.86  | 15.99 |      | 150.0 |         |
|           |                                                     | Z | 2.60   | 67.91  | 15.97 |      | 150.0 |         |



EX3DV4- SN:3759

December 16, 2016

|           |                                                |   |      |       |       |      |       |         |
|-----------|------------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10112-CAD | LTE-FDD (SC-FDMA, 100% RB, 10 MHz, 64-QAM)     | X | 2.99 | 67.13 | 15.75 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 3.05 | 67.18 | 15.80 |      | 150.0 |         |
|           |                                                | Z | 3.01 | 67.13 | 15.74 |      | 150.0 |         |
| 10113-CAD | LTE-FDD (SC-FDMA, 100% RB, 5 MHz, 64-QAM)      | X | 2.73 | 68.15 | 16.11 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.78 | 68.00 | 16.13 |      | 150.0 |         |
|           |                                                | Z | 2.76 | 68.09 | 16.12 |      | 150.0 |         |
| 10114-CAB | IEEE 802.11n (HT Greenfield, 13.5 Mbps, BPSK)  | X | 5.12 | 67.14 | 16.40 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.16 | 67.11 | 16.38 |      | 150.0 |         |
|           |                                                | Z | 5.14 | 67.13 | 16.37 |      | 150.0 |         |
| 10115-CAB | IEEE 802.11n (HT Greenfield, 81 Mbps, 16-QAM)  | X | 5.39 | 67.23 | 16.45 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.47 | 67.32 | 16.49 |      | 150.0 |         |
|           |                                                | Z | 5.43 | 67.27 | 16.45 |      | 150.0 |         |
| 10116-CAB | IEEE 802.11n (HT Greenfield, 135 Mbps, 64-QAM) | X | 5.20 | 67.31 | 16.41 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.26 | 67.33 | 16.42 |      | 150.0 |         |
|           |                                                | Z | 5.23 | 67.32 | 16.39 |      | 150.0 |         |
| 10117-CAB | IEEE 802.11n (HT Mixed, 13.5 Mbps, BPSK)       | X | 5.08 | 66.99 | 16.34 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.13 | 67.01 | 16.35 |      | 150.0 |         |
|           |                                                | Z | 5.10 | 67.00 | 16.32 |      | 150.0 |         |
| 10118-CAB | IEEE 802.11n (HT Mixed, 81 Mbps, 16-QAM)       | X | 5.47 | 67.43 | 16.56 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.55 | 67.51 | 16.60 |      | 150.0 |         |
|           |                                                | Z | 5.51 | 67.48 | 16.56 |      | 150.0 |         |
| 10119-CAB | IEEE 802.11n (HT Mixed, 135 Mbps, 64-QAM)      | X | 5.19 | 67.27 | 16.40 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 5.23 | 67.26 | 16.40 |      | 150.0 |         |
|           |                                                | Z | 5.21 | 67.26 | 16.38 |      | 150.0 |         |
| 10140-CAC | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 16-QAM)     | X | 3.35 | 67.26 | 15.81 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 3.41 | 67.36 | 15.86 |      | 150.0 |         |
|           |                                                | Z | 3.37 | 67.28 | 15.80 |      | 150.0 |         |
| 10141-CAC | LTE-FDD (SC-FDMA, 100% RB, 15 MHz, 64-QAM)     | X | 3.47 | 67.39 | 16.00 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 3.53 | 67.45 | 16.03 |      | 150.0 |         |
|           |                                                | Z | 3.50 | 67.41 | 15.99 |      | 150.0 |         |
| 10142-CAD | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, QPSK)        | X | 1.92 | 68.04 | 15.43 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.00 | 68.21 | 15.62 |      | 150.0 |         |
|           |                                                | Z | 1.95 | 68.01 | 15.47 |      | 150.0 |         |
| 10143-CAD | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 16-QAM)      | X | 2.43 | 68.67 | 15.60 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.48 | 68.53 | 15.74 |      | 150.0 |         |
|           |                                                | Z | 2.46 | 68.63 | 15.70 |      | 150.0 |         |
| 10144-CAD | LTE-FDD (SC-FDMA, 100% RB, 3 MHz, 64-QAM)      | X | 2.19 | 66.27 | 13.92 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.28 | 66.45 | 14.25 |      | 150.0 |         |
|           |                                                | Z | 2.23 | 66.33 | 14.07 |      | 150.0 |         |
| 10145-CAD | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, QPSK)      | X | 1.16 | 64.50 | 11.31 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 1.29 | 65.42 | 12.29 |      | 150.0 |         |
|           |                                                | Z | 1.24 | 65.05 | 11.89 |      | 150.0 |         |
| 10146-CAD | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 16-QAM)    | X | 1.75 | 64.91 | 10.68 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.10 | 66.86 | 12.19 |      | 150.0 |         |
|           |                                                | Z | 1.85 | 65.40 | 11.22 |      | 150.0 |         |
| 10147-CAD | LTE-FDD (SC-FDMA, 100% RB, 1.4 MHz, 64-QAM)    | X | 1.99 | 66.41 | 11.55 | 0.00 | 150.0 | ± 9.6 % |
|           |                                                | Y | 2.48 | 68.95 | 13.31 |      | 150.0 |         |
|           |                                                | Z | 2.12 | 67.01 | 12.15 |      | 150.0 |         |



EX3DV4- SN:3759

December 16, 2016

|           |                                            |   |      |       |       |      |       |         |
|-----------|--------------------------------------------|---|------|-------|-------|------|-------|---------|
| 10149-CAC | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)  | X | 2.87 | 67.16 | 15.72 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.93 | 67.25 | 15.78 |      | 150.0 |         |
|           |                                            | Z | 2.90 | 67.17 | 15.71 |      | 150.0 |         |
| 10150-CAC | LTE-FDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)  | X | 3.00 | 67.19 | 15.79 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.05 | 67.23 | 15.84 |      | 150.0 |         |
|           |                                            | Z | 3.02 | 67.19 | 15.79 |      | 150.0 |         |
| 10151-CAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, QPSK)    | X | 6.19 | 76.09 | 20.32 | 3.98 | 65.0  | ± 9.6 % |
|           |                                            | Y | 6.72 | 77.39 | 20.98 |      | 65.0  |         |
|           |                                            | Z | 6.36 | 75.98 | 20.19 |      | 65.0  |         |
| 10152-CAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 16-QAM)  | X | 5.64 | 72.49 | 19.24 | 3.98 | 65.0  | ± 9.6 % |
|           |                                            | Y | 6.02 | 73.58 | 19.91 |      | 65.0  |         |
|           |                                            | Z | 5.85 | 72.65 | 19.26 |      | 65.0  |         |
| 10153-CAC | LTE-TDD (SC-FDMA, 50% RB, 20 MHz, 64-QAM)  | X | 6.03 | 73.53 | 20.06 | 3.98 | 65.0  | ± 9.6 % |
|           |                                            | Y | 6.38 | 74.47 | 20.65 |      | 65.0  |         |
|           |                                            | Z | 6.24 | 73.66 | 20.07 |      | 65.0  |         |
| 10154-CAD | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, QPSK)    | X | 2.20 | 68.51 | 16.09 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.28 | 68.70 | 16.20 |      | 150.0 |         |
|           |                                            | Z | 2.23 | 68.51 | 16.09 |      | 150.0 |         |
| 10155-CAD | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 16-QAM)  | X | 2.58 | 67.98 | 15.97 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.63 | 67.87 | 16.01 |      | 150.0 |         |
|           |                                            | Z | 2.61 | 67.92 | 15.98 |      | 150.0 |         |
| 10156-CAD | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, QPSK)     | X | 1.76 | 68.06 | 15.17 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 1.85 | 68.29 | 15.45 |      | 150.0 |         |
|           |                                            | Z | 1.80 | 68.08 | 15.26 |      | 150.0 |         |
| 10157-CAD | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 16-QAM)   | X | 2.02 | 66.77 | 13.91 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.12 | 66.99 | 14.30 |      | 150.0 |         |
|           |                                            | Z | 2.07 | 66.86 | 14.11 |      | 150.0 |         |
| 10158-CAD | LTE-FDD (SC-FDMA, 50% RB, 10 MHz, 64-QAM)  | X | 2.74 | 68.22 | 16.16 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.79 | 68.06 | 16.17 |      | 150.0 |         |
|           |                                            | Z | 2.77 | 68.16 | 16.17 |      | 150.0 |         |
| 10159-CAD | LTE-FDD (SC-FDMA, 50% RB, 5 MHz, 64-QAM)   | X | 2.12 | 67.25 | 14.20 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.23 | 67.45 | 14.59 |      | 150.0 |         |
|           |                                            | Z | 2.18 | 67.37 | 14.42 |      | 150.0 |         |
| 10160-CAC | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, QPSK)    | X | 2.69 | 68.25 | 16.09 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.75 | 68.31 | 16.13 |      | 150.0 |         |
|           |                                            | Z | 2.71 | 68.19 | 16.05 |      | 150.0 |         |
| 10161-CAC | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 16-QAM)  | X | 2.89 | 67.14 | 15.71 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 2.95 | 67.16 | 15.77 |      | 150.0 |         |
|           |                                            | Z | 2.92 | 67.13 | 15.72 |      | 150.0 |         |
| 10162-CAC | LTE-FDD (SC-FDMA, 50% RB, 15 MHz, 64-QAM)  | X | 3.00 | 67.31 | 15.83 | 0.00 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.06 | 67.29 | 15.87 |      | 150.0 |         |
|           |                                            | Z | 3.03 | 67.28 | 15.83 |      | 150.0 |         |
| 10166-CAD | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, QPSK)   | X | 3.52 | 69.26 | 18.89 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.63 | 69.41 | 18.97 |      | 150.0 |         |
|           |                                            | Z | 3.54 | 68.96 | 18.65 |      | 150.0 |         |
| 10167-CAD | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 16-QAM) | X | 4.34 | 72.30 | 19.40 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 4.53 | 72.61 | 19.56 |      | 150.0 |         |
|           |                                            | Z | 4.33 | 71.71 | 19.05 |      | 150.0 |         |



EX3DV4- SN:3759

December 16, 2016

|           |                                            |   |       |       |       |      |       |         |
|-----------|--------------------------------------------|---|-------|-------|-------|------|-------|---------|
| 10168-CAD | LTE-FDD (SC-FDMA, 50% RB, 1.4 MHz, 64-QAM) | X | 4.92  | 75.00 | 20.95 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 5.05  | 74.92 | 20.91 |      | 150.0 |         |
|           |                                            | Z | 4.86  | 74.20 | 20.52 |      | 150.0 |         |
| 10169-CAC | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, QPSK)      | X | 2.94  | 68.69 | 18.63 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.06  | 69.43 | 19.00 |      | 150.0 |         |
|           |                                            | Z | 2.97  | 68.51 | 18.42 |      | 150.0 |         |
| 10170-CAC | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)    | X | 4.15  | 75.29 | 21.28 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 4.43  | 76.35 | 21.68 |      | 150.0 |         |
|           |                                            | Z | 4.11  | 74.52 | 20.83 |      | 150.0 |         |
| 10171-AAC | LTE-FDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)    | X | 3.30  | 70.50 | 18.18 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.54  | 71.68 | 18.72 |      | 150.0 |         |
|           |                                            | Z | 3.31  | 70.02 | 17.86 |      | 150.0 |         |
| 10172-CAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, QPSK)      | X | 5.72  | 82.17 | 24.47 | 6.02 | 65.0  | ± 9.6 % |
|           |                                            | Y | 9.41  | 91.72 | 28.09 |      | 65.0  |         |
|           |                                            | Z | 7.05  | 84.62 | 25.03 |      | 65.0  |         |
| 10173-CAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 16-QAM)    | X | 10.09 | 89.06 | 25.03 | 6.02 | 65.0  | ± 9.6 % |
|           |                                            | Y | 16.80 | 97.79 | 27.98 |      | 65.0  |         |
|           |                                            | Z | 9.48  | 86.64 | 24.01 |      | 65.0  |         |
| 10174-CAC | LTE-TDD (SC-FDMA, 1 RB, 20 MHz, 64-QAM)    | X | 7.37  | 83.04 | 22.50 | 6.02 | 65.0  | ± 9.6 % |
|           |                                            | Y | 11.94 | 90.83 | 25.28 |      | 65.0  |         |
|           |                                            | Z | 6.31  | 79.38 | 21.04 |      | 65.0  |         |
| 10175-CAD | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, QPSK)      | X | 2.90  | 68.35 | 18.36 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.02  | 69.11 | 18.74 |      | 150.0 |         |
|           |                                            | Z | 2.93  | 68.17 | 18.15 |      | 150.0 |         |
| 10176-CAD | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 16-QAM)    | X | 4.15  | 75.31 | 21.29 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 4.43  | 76.38 | 21.69 |      | 150.0 |         |
|           |                                            | Z | 4.12  | 74.55 | 20.84 |      | 150.0 |         |
| 10177-CAF | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, QPSK)       | X | 2.92  | 68.51 | 18.47 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.05  | 69.27 | 18.84 |      | 150.0 |         |
|           |                                            | Z | 2.95  | 68.34 | 18.26 |      | 150.0 |         |
| 10178-CAD | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 16-QAM)     | X | 4.11  | 75.05 | 21.16 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 4.38  | 76.11 | 21.55 |      | 150.0 |         |
|           |                                            | Z | 4.07  | 74.28 | 20.70 |      | 150.0 |         |
| 10179-CAD | LTE-FDD (SC-FDMA, 1 RB, 10 MHz, 64-QAM)    | X | 3.67  | 72.68 | 19.56 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.93  | 73.84 | 20.04 |      | 150.0 |         |
|           |                                            | Z | 3.66  | 72.05 | 19.16 |      | 150.0 |         |
| 10180-CAD | LTE-FDD (SC-FDMA, 1 RB, 5 MHz, 64-QAM)     | X | 3.29  | 70.43 | 18.13 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.53  | 71.60 | 18.66 |      | 150.0 |         |
|           |                                            | Z | 3.30  | 69.94 | 17.80 |      | 150.0 |         |
| 10181-CAC | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, QPSK)      | X | 2.92  | 68.49 | 18.46 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.04  | 69.25 | 18.83 |      | 150.0 |         |
|           |                                            | Z | 2.95  | 68.32 | 18.25 |      | 150.0 |         |
| 10182-CAC | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 16-QAM)    | X | 4.10  | 75.03 | 21.14 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 4.37  | 76.08 | 21.54 |      | 150.0 |         |
|           |                                            | Z | 4.06  | 74.26 | 20.69 |      | 150.0 |         |
| 10183-AAB | LTE-FDD (SC-FDMA, 1 RB, 15 MHz, 64-QAM)    | X | 3.29  | 70.40 | 18.12 | 3.01 | 150.0 | ± 9.6 % |
|           |                                            | Y | 3.52  | 71.58 | 18.65 |      | 150.0 |         |
|           |                                            | Z | 3.30  | 69.92 | 17.79 |      | 150.0 |         |