

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	SHENZHEN HUBSAN INTELLIGENT Co.,LTD.
Address	:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen,China.
Equipment under Test	:	Spy Hawk with GPS
Model No	:	H301S
Trade Mark	:	HUBSAN
FCC ID	:	2AEXY301SRX
Manufacturer	:	DONGGUAN TENGSHENG INDUSTRIAL CO.,LTD.
Address	:	A22# Luyi Street, Tianxin Village, Tangxia Town, Dong guan, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City,
Guangdong Province, China, 523808

Tel: +86-0769-22891499 [Http://www.dgddt.com](http://www.dgddt.com)

REPORT

TABLE OF CONTENTS

	Test report declares.....	4
1.	Summary of test results	4
2.	General test information.....	5
2.1.	Description of EUT	5
2.2.	Accessories of EUT	5
2.3.	Assistant equipment used for test.....	5
2.4.	Block diagram of EUT configuration for test	5
2.5.	Test environment conditions	6
2.6.	Test laboratory.....	6
2.7.	Measurement uncertainty	6
3.	Equipment used during test	7
4.	20dB Bandwidth.....	8
4.1.	Block diagram of test setup	8
4.2.	Limits	8
4.3.	Test Procedure.....	8
4.4.	Test Result.....	8
4.5.	Original test data	9
5.	Radiated emission	11
5.1.	Block diagram of test setup	11
5.2.	Limit	12
5.3.	Test Procedure.....	13
5.4.	Test result	14
6.	Band Edge Compliance (radiated method)	18
6.1.	Block diagram of test setup	18
6.2.	Limit	18
6.3.	Test Procedure.....	18
6.4.	Test result	18
7.	Power Line Conducted Emission	23
7.1.	Block diagram of test setup	23
7.2.	Power Line Conducted Emission Limits(Class B).....	23
7.3.	Test Procedure.....	23
7.4.	Test Result.....	24
8.	Antenna Requirements	25
8.1.	Limit.....	25
8.2.	Result.....	25
9.	Test setup photograph	26
10.	Photos of the EUT	27

TEST REPORT DECLARE

Applicant	:	SHENZHEN HUBSAN INTELLIGENT Co.,LTD.
Address	:	13th Floor, Bldg 1C, Shenzhen Software Industry Base, Xuefu Road, Nanshan District, Shenzhen,China.
Equipment under Test	:	Spy Hawk with GPS
Model No	:	H301S
Trade Mark	:	HUBSAN
Manufacturer	:	DONGGUAN TENGSHENG INDUSTRIAL CO.,LTD.
Address	:	A22# Luyi Street, Tianxin Village, Tangxia Town, Dong guan, China

Test Standard Used:

FCC Rules and Regulations Part 15 Subpart C: 2015

Test procedure used:

ANSI C63.10:2013, ANSI C63.4:2014

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-R16Q0627-1E2		
Date of Test:	Jun.27, 2016~Jul.03, 2016	Date of Report:	Jul.03, 2016

Prepared By:


Leo Liu/Engineer

Approved By:


Ke Jia Feng/EMC Manager

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. Summary of test results

Description of Test Item	Standard	Results
20dB Bandwidth	FCC Part 15: 15.215 ANSI C63.10 :2013 ANSI C63.4:2014	PASS
Radiated Emission	FCC Part 15: 15.209 FCC Part 15: 15.249(d) ANSI C63.10 :2013 ANSI C63.4:2014	PASS
Band Edge Compliance	FCC Part 15: 15.249(d) ANSI C63.10 :2013 ANSI C63.4:2014	PASS
Power Line Conducted Emissions	FCC Part 15: 15.207 ANSI C63.10 :2013 ANSI C63.4:2014	N/A
Note: N/A is an abbreviation for Not Applicable.		

2. General test information

2.1. Description of EUT

EUT* Name	:	Spy Hawk with GPS
Model Number	:	H301S
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 7.4V from battery
Operation frequency	:	5735MHz -5865 MHz
Channel	:	27
Modulation	:	FM
Data rate	:	N/A
Antenna Type	:	Integrated antenna, maximum PK gain: 0dBi
Date of Receipt	:	Jun.27, 2016
Sample Type	:	Series production

Note: EUT is the ab. of equipment under test.

2.2. Accessories of EUT

Description of Accessories	Manufacturer	Model number or Type	Serial No.	Other
/	/	/	/	/

2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN
/	/	/	/	/

2.4. Block diagram of EUT configuration for test



Used to control EUT work in Continuous TX mode by key, and select test channel, wireless mode as blow table.

Note: Full battery is used during all test.

Tested mode, information	
Mode	Frequency (MHz)
Tx Mode	5735
	5795
	5865

2.5. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25°C
Humidity range:	40-75%
Pressure range:	86-106kPa

2.6. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong

Province, China, 523808 Tel: +86-0769-22891499 <http://www.dgddt.com>

FCC Registration Number: 270092

2.7. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	±1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz ≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Dwell Time	±0.6%
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz ≤ f < 8GHz)
	1.66dB(8GHz ≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10 ⁻⁸
Temperature	±0.4°C
Humidity	±2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	±3.14 dB (Antenna Polarize: V)
	±3.16 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-18GHz)	±4.14dB(1-6GHz)
	±4.46dB (6GHz-18Gz)
Uncertainty for Power line conduction emission test	2.44dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test					
Spectrum analyzer	R&S	FSU26	1166.1660.26	2015/10/24	1 Year
Attenuator	Mini-Circuits	BW-S10W2	101109	2015/08/18	1 Year
RF Cable	Micable	C10-01-01-1	100309	2015/08/18	1 Year
Radiated Emission Test					
EMI Test Receiver	R&S	ESU8	100316	2015/10/24	1Year
Spectrum analyzer	R&S	FSU26	1166.1660.26	2015/10/24	1Year
Spectrum analyzer	Agilent	E4447A	MY50180031	2015/09/22	1Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2016/05/30	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	2015/10/24	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	2015/10/31	1 Year
Horn Antenna	EMCO	3116	00060095	2015/10/30	1 Year
Pre-amplifier	A.H.	PAM-0118	360	2015/08/18	1 Year
Pre-amplifier	A.H.	PAM-1840VH	562	2015/08/18	1 Year
RF Cable	HUBSER	CP-X2	W11.03	2015/10/24	1Year
RF Cable	HUBSER	CP-X1	W12.02	2015/10/24	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	2015/10/24	1 Year
Test software	Audix	E3	V 6.11111b	/	/
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	2015/10/24	1 Year
LISN 1	R&S	ENV216	101109	2015/10/24	1 Year
LISN 2	R&S	ESH2-Z5	100309	2015/10/24	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	2015-10-24	1 Year
CE Cable 1	HUBSER	ESU8/RF2	W10.01	2015/10/24	1 Year
Test software	Audix	E3	V 6.11111b	/	/

4. 20dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in § 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.



4.3. Test Procedure


- (1) Configure EUT and assistant system according clause 2.4 and 4.2.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (3) Configure EUT work in test mode as stated in clause 2.4.
- (4) The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 kHz RBW and 300 kHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.4. Test Result

Mode	Freq (MHz)	20dB bandwidth Result (MHz)	99% bandwidth Result (MHz)	Limit (MHz)	Margin (MHz)	Conclusion
Tx mode	5735	6.38	/	/	/	PASS
	5795	6.09	/	/	/	PASS
	5865	6.15	/	/	/	PASS
Test Date : Jul. 29, 2016				Test Engineer: Toby Ren		

4.5. Original test data







5. Radiated emission

5.1. Block diagram of test setup


In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for below 1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

5.2. Limit

5.2. 1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

5.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0

Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)
------------	---	---

Note: (1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz. Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\text{Log}(30m/3m)$$

8.3.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

5.3. Test Procedure

(1) EUT was placed on a non-metallic table, 150 cm above the ground plane inside a semi-anechoic chamber.

(2) Setup EUT and assistant system according clause 2.4 and 8.2

(3) Test antenna was located 1m/3m from the EUT on an adjustable mast, and the antenna used as below table:

Test frequency range	Test antenna used
9KHz-30MHz	Active Loop antenna
30MHz-1GHz	Trilog Broadband Antenna
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)
18GHz-40GHz	Horn Antenna(18GHz-40GHz)

According ANSI C63.10:2013f clause 6.4.4.2 and 6.5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(4) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

- (5) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.
- (6) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz, 110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.
- (7) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

- (8) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).
- (9) X axis, Y axis, Z axis are tested, and worse setup X axis is reported.

5.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9 KHz to 25GHz were comply with FCC 15.209 limit.

Note1: According exploratory test no any obvious emission were detected from 9KHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.


Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz.

Note3: For emissions above 1GHz. If peak results comply with AV limit, AV Result is deemed to comply with AV limit.

Radiated Emission test (below 1GHz)**TR-4-E-009 Radiated Emission Test Result**

Test Site	: DDT 3m Chamber	D:\2016 Report Data\re.EM6
Test Date	: 2016-06-29	Tested By : Toby
EUT	: Spy Hawk with GPS	Model Number : H301S
Power Supply	: DC 7.4V from battery	Test Mode : TX Mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	Antenna/Distance : 2015 VULB9163/3m/VERTICAL
Memo	:	

Data: 30



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	32.41	10.90	11.44	3.69	26.03	40.00	-13.97	QP	VERTICAL
2	98.14	4.78	11.85	4.28	20.91	43.50	-22.59	QP	VERTICAL
3	146.89	11.50	7.44	4.58	23.52	43.50	-19.98	QP	VERTICAL
4	195.82	12.86	10.13	4.88	27.87	43.50	-15.63	QP	VERTICAL
5	397.63	6.41	15.65	5.79	27.85	46.00	-18.15	QP	VERTICAL
6	492.47	5.71	17.20	6.14	29.05	46.00	-16.95	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.


2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\re.EM6**
Test Date : 2016-06-29 **Tested By** : Toby
EUT : Spy Hawk with GPS **Model Number** : H301S
Power Supply : DC 7.4V from battery **Test Mode** : TX Mode
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2015 VULB9163/3m/HORIZONTAL
Memo :

Data: 31



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	97.80	11.49	11.83	4.28	27.60	43.50	-15.90	QP	HORIZONTAL
2	146.89	21.89	7.44	4.58	33.91	43.50	-9.59	QP	HORIZONTAL
3	171.39	19.51	8.54	4.73	32.78	43.50	-10.72	QP	HORIZONTAL
4	195.82	25.76	10.13	4.88	40.77	43.50	-2.73	QP	HORIZONTAL
5	340.78	16.21	14.70	5.55	36.46	46.00	-9.54	QP	HORIZONTAL
6	393.47	14.06	15.57	5.77	35.40	46.00	-10.60	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Detector type	Polarization
Tx mode 5735MHz									
5735.00	75.07	34.84	29.22	9.41	90.10	94.00	-3.90	Average	VERTICAL
5735.00	83.78	34.84	29.22	9.41	98.81	114.00	-15.19	Peak	VERTICAL
11470.00	36.06	36.76	34.49	13.58	51.91	54.00	-2.09	Average	VERTICAL
11470.00	51.66	36.76	34.49	13.58	67.51	74.00	-6.49	Peak	VERTICAL
17205.00	21.69	43.53	36.80	18.55	46.97	54.00	-7.03	Average	VERTICAL
17205.00	39.47	43.53	36.80	18.55	64.75	74.00	-9.25	Peak	VERTICAL
5735.00	75.15	34.84	29.22	9.41	90.18	94.00	-3.82	Average	HORIZONTAL
5735.00	83.58	34.84	29.22	9.41	98.61	114.00	-15.39	Peak	HORIZONTAL
11470.00	33.01	36.76	34.49	13.58	48.86	54.00	-5.14	Average	HORIZONTAL
11470.00	45.15	36.76	34.49	13.58	61.00	74.00	-13.00	Peak	HORIZONTAL

Tx mode 5795MHz									
5795.00	74.27	34.88	29.21	9.48	89.42	94.00	-4.58	Average	VERTICAL
5795.00	82.06	34.88	29.21	9.48	97.21	114.00	-16.79	Peak	VERTICAL
11590.00	36.03	36.86	34.58	13.70	52.01	54.00	-1.99	Average	VERTICAL
11590.00	48.26	36.86	34.58	13.70	64.24	74.00	-9.76	Peak	VERTICAL

5795.00	75.99	34.88	29.21	9.48	91.14	94.00	-2.86	Average	HORIZONTAL
5795.00	84.03	34.88	29.21	9.48	99.18	114.00	-14.82	Peak	HORIZONTAL
11590.00	33.59	36.86	34.58	13.70	49.57	54.00	-4.43	Average	HORIZONTAL
11590.00	43.59	36.86	34.58	13.70	59.57	74.00	-14.43	Peak	HORIZONTAL
16419.00	20.87	44.57	35.92	17.43	46.95	54.00	-7.05	Average	HORIZONTAL
16419.00	35.47	44.57	35.92	17.43	61.55	74.00	-12.45	Peak	HORIZONTAL

Tx mode 5865MHz									
5865.00	75.02	34.92	29.20	9.56	90.30	94.00	-3.70	Average	VERTICAL
5865.00	83.25	34.92	29.20	9.56	98.53	114.00	-15.47	Peak	VERTICAL
11730.00	35.74	37.12	34.66	13.88	52.08	54.00	-1.92	Average	VERTICAL
11730.00	47.27	37.12	34.66	13.88	63.61	74.00	-10.39	Peak	VERTICAL
17595.00	20.00	43.33	37.31	18.93	44.95	54.00	-9.05	Average	VERTICAL
17595.00	36.68	43.33	37.31	18.93	61.63	74.00	-12.37	Peak	VERTICAL
5865.00	75.09	34.92	29.20	9.56	90.37	94.00	-3.63	Average	HORIZONTAL
5865.00	83.69	34.92	29.20	9.56	98.97	114.00	-15.03	Peak	HORIZONTAL
11730.00	32.99	37.12	34.66	13.88	49.33	54.00	-4.67	Average	HORIZONTAL
11730.00	42.59	37.12	34.66	13.88	58.93	74.00	-15.07	Peak	HORIZONTAL
17595.00	19.89	43.33	37.31	18.93	44.84	54.00	-9.16	Average	HORIZONTAL
17595.00	35.84	43.33	37.31	18.93	60.79	74.00	-13.21	Peak	HORIZONTAL

Result: Pass

Test Date : Jul. 02, 2016

Test Engineer : Toby Ren

Note1: Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


Result: Pass.

Note2: RBW is set at 1MHz, VBW is set at 3MHz peak detector for Peak ; RMS detector for Average

For fundamental frequency, RBW is set at 7MHz, VBW is set at 7MHz , peak detector for Peak ; RMS detector for Average

6. Band Edge Compliance (radiated method)

6.1. Block diagram of test setup



6.2. Limit

All restriction band should comply with 15.209, other emission should be at least 20dB below the fundamental.

6.3. Test Procedure

Same with clause 4.4 except change investigated frequency range from 5700MHz to 5760MHz and 5850MHz to 5900MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.


6.4. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\re.EM6**
Test Date : 2016-07-02 **Tested By** : Toby
EUT : Spy Hawk with GPS **Model Number** : H301S
Power Supply : DC 7.4V from battery **Test Mode** : TX 5735 MHz
Condition : Temp:24.5'C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2015 HF907/3m/VERTICAL
Memo :

Data: 35



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	5704.02	37.91	34.83	29.22	9.39	52.91	74.00	-21.09	Peak	VERTICAL
2	5725.00	35.90	34.84	29.22	9.41	50.93	74.00	-23.07	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\re.EM6**
Test Date : 2016-07-02 **Tested By** : Toby
EUT : Spy Hawk with GPS **Model Number** : H301S
Power Supply : DC 7.4V from battery **Test Mode** : TX 5735 MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2015 HF907/3m/HORIZONTAL
Memo :

Data: 34



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	5705.52	37.16	34.83	29.22	9.39	52.16	74.00	-21.84	Peak	HORIZONTAL
2	5725.00	35.59	34.84	29.22	9.41	50.62	74.00	-23.38	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\re.EM6**
Test Date : 2016-07-02 **Tested By** : Toby
EUT : Spy Hawk with GPS **Model Number** : H301S
Power Supply : DC 7.4V from battery **Test Mode** : TX 5865 MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2015 HF907/3m/VERTICAL
Memo :

Data: 37



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	5875.00	35.26	34.93	29.20	9.56	50.55	74.00	-23.45	Peak	VERTICAL
2	5894.15	37.36	34.94	29.20	9.57	52.67	74.00	-21.33	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.


2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site : DDT 3m Chamber **D:\2016 Report Data\re.EM6**
Test Date : 2016-07-02 **Tested By** : Toby
EUT : Spy Hawk with GPS **Model Number** : H301S
Power Supply : DC 7.4V from battery **Test Mode** : TX 5865 MHz
Condition : Temp:24.5°C,Humi:55%,
 Press:100.1kPa **Antenna/Distance** : 2015 HF907/3m/HORIZONTAL
Memo :

Data: 36



Item (Mark)	Freq (MHz)	Read Level (dBμV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBμV/m)	Limit Line (dBμV/m)	Over Limit (dB)	Detector	Polarization
1	5875.00	34.61	34.93	29.20	9.56	49.90	74.00	-24.10	Peak	HORIZONTAL
2	5897.60	37.89	34.94	29.20	9.59	53.22	74.00	-20.78	Peak	HORIZONTAL


Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

7. Power Line Conducted Emission

7.1. Block diagram of test setup



7.2. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

7.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

Configuration EUT to simulate typical usage as described in clause 2.4 and test equipment as described in clause 10.2 of this report.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

The test mode(s) described in clause 2.4 were scanned during the preliminary test.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

7.4. Test Result

Not Applicable

8. Antenna Requirements

8.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Result

The antennas used for this product are Integrated antenna and that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is only 0dBi.