

1

2

3

4

5

6

7

8

9

0

KEYPAD

User Manual

PRODUCT DESCRIPTION

1

2

3

4

5

6

7

8

9

0

UNLOCK

LOCK

DEFAULT ACTIONS:

• UNLOCK:

Enter passcode + to unlock

• LOCK:

Press to lock.

IN THE BOX

1

2

3

4

5

6

7

8

9

0

Keypad x 1

0

0

Mounting Plate x 1

Drill Bit x 1

Anchor x 4

Screw x 4

AAA Battery x 2

TOOLS YOU MAY NEED

Drill

Hammer

Pencil

INSTALLATION - KEYPAD

• Pull out the battery cover at the bottom.

• Insert the batteries. See battery orientation at the back of the keypad.

INSTALLATION OPTION 1: WITH DOUBLE-SIDED TAPE

• Place the battery cover back.

• 1. Remove the backing of the adhesive at the back of the mounting plate. Stick the mounting plate to the place where you wish to install the keypad.

• 2. Mount the bottom of the keypad to the mounting plate, press the keypad against the mounting plate.

INSTALLATION OPTION 2: WITH SCREWS

• 1. Place the mounting plate on the wall at the position where you wish to install. Use a pen to mark the two holes on the wall.

• 2. Use the provided drill bit to drill two holes at the marked spots.

• 3. Insert the plastic anchors into the two holes, use a hammer to gently tap them in until they are flush with the wall.

• Place the mounting plate over the two screw holes, use the provided screws to secure the mounting plate against the wall.

• Mount the bottom of the keypad to the mounting plate, press the keypad against the mounting plate.

GETTING STARTED

(1) Follow the Installation Guide to install the Keypad.

(2) Download "Tuya Smart" from Google Play or App Store. Or scan the QR code below to download.

Download on the App Store

GET IT ON Google Play

(3) Log in to Tuya Smart or create a new account.

(4) Make sure to have set up the Smart Lock before adding the Keypad.

Notice: Please follow the steps if you failed to add the Keypad in the App.

(1) Open the battery cover of the Keypad,

(2) Press and hold both the unlock, lock key and close the battery cover.

(3) Keypad is reset successfully when you hear a beep and release the keys.

• Step 1

Tap + to add.

• Step 2

Tap "Auto Scan".

• Step 3

Wait for the Keypad to show up and tap Next.

• Step 4

Wait for the connection to complete.

• Step 5

Tap Done when the Keypad is added successfully.

• Step 6

Tap the Keypad icon in the App.

• Step 7

Wait for the Keypad to connect and tap "Bind a lock first".

• Step 8

Tap "Add" to add.

• Step 9

Select the Smart Lock you wish to bind and tap "Start Binding".

• Step 10

Binding in progress...

• Step 11

Tap the "<" icon to return to the previous menu.

• Step 12

Tap the key icon to set up a password.

• Step 13

Tap "+" to add a password.

• Step 14

Choose a password type and follow the steps on the App to create a password.

工艺说明：说明书，FP0211-TY，英文，4C印刷，105双铜，折叠尺寸：45\*110mm，风琴折，过光油，无铅

|                                                                                             |  |  |  |                         |                 |                     |            |
|---------------------------------------------------------------------------------------------|--|--|--|-------------------------|-----------------|---------------------|------------|
| <div><div>BOSMA</div><div>Guangzhou BOSMA Technology Co., Ltd.<br/>广州博冠智能科技有限公司</div></div> |  |  |  | MODEL NO.<br>机型         | FP0211-TY       | MATERIAL<br>材料      | 105G双铜     |
|                                                                                             |  |  |  | NAME<br>名称              | 说明书             | OUTPUT DATE<br>完稿时间 | 2021.09.09 |
|                                                                                             |  |  |  | MATERIAL NO.<br>物料号     | 3.03.03.4902.00 | VERSION<br>版本       | VA         |
| APPROVED<br>批准                                                                              |  |  |  | MATERIAL NO.<br>物料号     |                 | UNIT<br>单位          | 毫米         |
| CHECKED<br>审核                                                                               |  |  |  | DESIGNED<br>设计          | 冯惠琪             | TYPE/FACES<br>字体    | pt         |
|                                                                                             |  |  |  | SIZE<br>图幅              | A3              | SCALE<br>比例         | 1:1        |
|                                                                                             |  |  |  | SHEET OF<br>第 1 页 共 1 页 |                 |                     |            |

## FCC Statement

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.