

# Standalone SAR test exclusion considerations

October 5, 2015

- Device category = ☐ Portable device ☒ Mobile device
- Transmitting mode = ☒ Single Transmitting ☐ Simultaneous Transmitting
- Max. transmitting frequency = 2480 MHz
- Min. test separation distance = 200 mm
- Max. Antenna Gain = 4.38 dBi
- Max. power with turn-up tolerance = 10.00 dBm = 10.0 mW ( Typical Power = Max. 10.00 dBm )

Note.

KDB 447498 D01 clause 4.3.1 Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separation distances > 50 mm

[ Threshold at 50 mm + ( test separation distance - 50 mm ) X 10 ] mW

= [ 0.08 + ( 200mm - 50mm X 10 ) ] = 1500.1

Note. The calculation result was rounded to one decimal place for comparison.

→ SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

## Maximum Permissible Exposure(MPE) evaluation for mobile device

$$S = P G / ( 4 R^2 \pi ) , \text{ mW/cm}^2$$

$$= 0.005454 \text{ mW/cm}^2$$

S = Maximum power density

P = Maximum power with turn-up tolerance

G = Numeric power gain of the antenna

R = Distance from transmitting antenna

**Conclusion: The exposure condition of this device is compliant with FCC rules.**

The limit for maximum permissible exposure = 1.000000 mW/cm<sup>2</sup>