



MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance D01

FCC Part 2 §2.1091

1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is ≤ 1.0 . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density

3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density



Compliance Certification Services (Shenzhen) Inc.

Report No: C170824Z02-RP1 _MPE

FCC ID: 2AF5PMD1600

Date of Issue: October 18, 2017

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance, $d=0.2\text{m}$, as well as the maximum gain of the used antenna as follow table, the RF power density can be obtained.

Frequency Band	Antenna type and antenna number	Maximum antenna gain
2.4GHz	Antenna 0, Internal Antenna	2dBi
	Antenna 1, Internal Antenna	2dBi
5GHz	Antenna 2, Internal Antenna	3dBi
	Antenna 3, Internal Antenna	3dBi
	Antenna 4, Internal Antenna	3dBi

4. Estimation Result

4.1 Conducted Power Results

2.4GHz WIFI

IEEE 802.11 b						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Average Conducted Output Power (dBm)	17.02	16.58	16.72	19.36	19.14	18.19
IEEE 802.11 g						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Average Conducted Output Power (dBm)	16.61	17.71	17.57	17.63	17.75	17.49
IEEE 802.11 n HT20						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Average Conducted Output Power (dBm)	19.45	15.17	14.99	13.41	14.71	14.45
IEEE 802.11 n HT40						
Frequency (MHz)	Antenna 0			Antenna 1		
	2422	2437	2452	2422	2437	2452
Average Conducted Output Power (dBm)	10.92	10.89	10.72	12.06	12.31	13.23



Compliance Certification Services (Shenzhen) Inc.

Report No: C170824Z02-RP1_MPE

FCC ID: 2AF5PMD1600

Date of Issue: October 18, 2017

5GHz WIFI

IEEE 802.11 a									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5180	5200	5240	5180	5200	5240	5180	5200	5240
Average Conducted Output Power (dBm)	18.03	18.16	18.05	17.89	17.79	17.95	17.65	17.86	17.36
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5745	5785	5825	5745	5785	5825	5745	5785	5825
Average Conducted Output Power (dBm)	20.02	20.34	20.64	21.71	21.63	21.26	20.42	20.72	20.97
IEEE 802.11 n HT20									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5180	5200	5240	5180	5200	5240	5180	5200	5240
Average Conducted Output Power (dBm)	16.08	16.14	16.62	16.21	15.91	16.21	14.97	15.41	12.44
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5745	5785	5825	5745	5785	5825	5745	5785	5825
Average Conducted Output Power (dBm)	19.26	19.37	19.65	19.35	19.26	19.17	18.52	18.36	18.57
IEEE 802.11 n HT40									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5190	---	5230	5190	---	5230	5190	---	5230
Average Conducted Output Power (dBm)	13.58	---	14.05	13.97	---	14.30	14.77	---	15.15
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5755	---	5795	5755	---	5795	5755	---	5795
Average Conducted Output Power (dBm)	18.91	---	19.07	19.56	---	19.65	18.51	---	18.65
IEEE 802.11 ac 80									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	---	5210	---	---	5210	---	---	5210	---
Average Conducted Output Power (dBm)	---	18.61	---	---	18.36	---	---	17.69	---
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	---	5775	---	---	5775	---	---	5775	---
Average Conducted Output Power (dBm)	---	18.87	---	---	19.44	---	---	18.69	---

4.2 Manufacturing tolerance

2.4GHz WIFI

IEEE 802.11 b						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	17.0	16.0	16.0	19.0	19.0	18.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11 g						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	16.0	17.0	17.0	17.0	17.0	17.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11 n HT20						
Frequency (MHz)	Antenna 0			Antenna 1		
	2412	2437	2462	2412	2437	2462
Target (dBm)	19.0	15.0	14.0	13.0	14.0	14.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0
IEEE 802.11 n HT40						
Frequency (MHz)	Antenna 0			Antenna 1		
	2422	2437	2452	2422	2437	2452
Target (dBm)	10.0	10.0	10.0	12.0	12.0	13.0
Tolerance ±(dB)	1.0	1.0	1.0	1.0	1.0	1.0

5GHz WIFI

[illegible]

**Compliance Certification Services (Shenzhen) Inc.**

Report No: C170824Z02-RP1_MPE

FCC ID: 2AF5PMD1600

Date of Issue: October 18, 2017

IEEE 802.11 n HT40 (average)									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5190	---	5230	5190	---	5230	5190	---	5230
Target (dBm)	13.05	---	13.05	13.30	---	13.30	14.15	---	14.15
Tolerance $\pm$ (dB)	1.0	---	1.0	1.0	---	1.0	1.0	---	1.0
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	5755	---	5795	5755	---	5795	5755	---	5795
Target (dBm)	18.00	---	19.00	19.00	---	19.00	18.00	---	18.00
Tolerance $\pm$ (dB)	1.0	---	1.0	1.0	---	1.0	1.0	---	1.0
IEEE 802.11 ac 80 (average)									
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	---	5210	---	---	5210	---	---	5210	---
Target (dBm)	---	17.61	---	---	17.36	---	---	17.69	---
Tolerance $\pm$ (dB)	---	1.0	---	---	1.0	---	---	1.0	---
Frequency (MHz)	Antenna 2			Antenna 3			Antenna 4		
	---	5775	---	---	5775	---	---	5775	---
Target (dBm)	---	18.00	---	---	19.00	---	---	18.00	---
Tolerance $\pm$ (dB)	---	1.0	---	---	1.0	---	---	1.0	---



4.3 Measurement Results

4.3.1 Standalone MPE

2.4G WLAN

Antenna 0

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 b	18.00	63.0957	2	1.5849	100%	0.0199	1.0000
IEEE 802.11 g	18.00	63.0957	2	1.5849	100%	0.0199	1.0000
IEEE 802.11 n HT20	20.00	100.0000	2	1.5849	100%	0.0315	1.0000
IEEE 802.11 n HT40	11.00	12.5893	2	1.5849	100%	0.0040	1.0000

Antenna 1

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 b	20.00	100.0000	2	1.5849	100%	0.0315	1.0000
IEEE 802.11 g	18.00	63.0957	2	1.5849	100%	0.0199	1.0000
IEEE 802.11 n HT20	15.00	31.6228	2	1.5849	100%	0.0100	1.0000
IEEE 802.11 n HT40	14.00	25.1189	2	1.5849	100%	0.0079	1.0000

5G WLAN

Antenna 2

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 a	21.00	125.8925	3	1.9953	100%	0.0500	1.0000
IEEE 802.11 n HT20	20.00	100.0000	3	1.9953	100%	0.0397	1.0000
IEEE 802.11 n HT40	20.00	100.0000	3	1.9953	100%	0.0397	1.0000
IEEE 802.11 ac 80	19.00	79.4328	3	1.9953	100%	0.0315	1.0000

Antenna 3

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 a	22.00	158.4893	3	1.9953	100%	0.0629	1.0000
IEEE 802.11 n HT20	20.00	100.0000	3	1.9953	100%	0.0397	1.0000
IEEE 802.11 n HT40	20.00	100.0000	3	1.9953	100%	0.0397	1.0000
IEEE 802.11 ac 80	20.00	100.0000	3	1.9953	100%	0.0397	1.0000



Antenna 4

Mode	Output power		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm ²)	MPE Limits (mW/cm ²)
	(dBm)	(mW)					
IEEE 802.11 a	21.00	125.8925	3	1.9953	100%	0.0500	1.0000
IEEE 802.11 n HT20	19.00	79.4328	3	1.9953	100%	0.0315	1.0000
IEEE 802.11 n HT40	19.00	79.4328	3	1.9953	100%	0.0315	1.0000
IEEE 802.11 ac 80	19.00	79.4328	3	1.9953	100%	0.0315	1.0000

Remark:

1. Maximum average power including tune-up tolerance;
2. MPE use distance is 20cm from manufacturer declaration of user manual.

4.3.2 Simultaneous transmission MPE

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

$\sum$ of MPE ratios ≤ 1.0

4.3.2.1 2.4GWLAN and 5GWLAN simultaneous transmission

We all conditions, recorded worst case at 3 antennas at 5GWLAN and 2 antennas at 2.4GWLAN simultaneous.

Antenna 0 and Antenna for 2.4GWLAN

Mode	MPE _{Antenna 0} (mW/cm ²)	MPE _{Antenna 1} (mW/cm ²)	$\sum$ MPE ratios	Limit	Results
IEEE 802.11b	0.0199	0.0315	N/A	1.0	Pass
IEEE 802.11g	0.0199	0.0199	N/A	1.0	Pass
IEEE 802.11n HT20	0.0315	0.0100	0.0415	1.0	Pass
IEEE 802.11n HT40	0.0040	0.0079	0.0119	1.0	Pass

Antenna 0, Antenna 1 and Antenna 2 for 5GWLAN

Mode	MPE _{Antenna 2} (mW/cm ²)	MPE _{Antenna 3} (mW/cm ²)	MPE _{Antenna 4} (mW/cm ²)	$\sum$ MPE ratios	Limit	Results
IEEE 802.11 a	0.0500	0.0629	0.0500	N/A	1.000	Pass
IEEE 802.11n HT20	0.0397	0.0397	0.0315	0.1109	1.000	Pass
IEEE 802.11n HT40	0.0397	0.0397	0.0315	0.1109	1.000	Pass
IEEE 802.11 ac 80	0.0315	0.0397	0.0315	0.1027	1.000	Pass

**Compliance Certification Services (Shenzhen) Inc.**

Report No: C170824Z02-RP1 _MPE

FCC ID: 2AF5PMD1600

Date of Issue: October 18, 2017

Maximum Simultaneous transmission MPE Ratio for 2.4GWLAN and 5GWLAN

Maximum MPE ratio 2.4GWLAN	Maximum MPE ratio 5GWLAN	Σ MPE ratios	Limit	Results
0.0489	0.1212	0.1701	1.0	Pass

Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- END OF REPORT-----