

TEST REPORT

CERTIFICATE OF CONFORMITY

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)
Report No.: RFCJWN-WTW-P26060465
FCC ID: 2AF77-BCM10300U
Product: Security Camera
Brand: blink or 
Model No.: BCM10300U
Received Date: 2026/6/25
Test Date: 2026/7/16 ~ 2026/7/30
Issued Date: 2026/8/17

Applicant: Immedia Semiconductor LLC

Address: 100 Riverpark Drive, Suite 125, North Reading, MA 01864, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City 244, Taiwan

Test Location(1): No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 333, Taiwan

Test Location(2): No. 70, Wenming Rd., Guishan Dist., Taoyuan City 333, Taiwan

FCC Registration / 788550 / TW0003 for Test Location(1)

Designation Number: 281270 / TW0032 for Test Location(2)

Approved by:



, **Date:**

2026/8/17

Jeremy Lin / Project Engineer

This test report consists of 65 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.



Prepared by : Jessica Cheng / Senior Specialist

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Table of Contents

Release Control Record	4
1 Certificate	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Supplementary Information	6
3 General Information	7
3.1 General Description	7
3.2 Antenna Description of EUT	8
3.3 Channel List	9
3.4 Test Mode Applicability and Tested Channel Detail	10
3.5 Duty Cycle of Test Signal	11
3.6 Test Program Used and Operation Descriptions	12
3.7 Connection Diagram of EUT and Peripheral Devices	12
3.8 Configuration of Peripheral Devices and Cable Connections	12
4 Test Instruments	13
4.1 RF Output Power	13
4.2 Power Spectral Density	13
4.3 6 dB Bandwidth	13
4.4 Conducted Out of Band Emissions	13
4.5 AC Power Conducted Emissions	14
4.6 Unwanted Emissions below 1 GHz	15
4.7 Unwanted Emissions above 1 GHz	16
5 Limits of Test Items	17
5.1 RF Output Power	17
5.2 Power Spectral Density	17
5.3 6 dB Bandwidth	17
5.4 Conducted Out of Band Emissions	17
5.5 AC Power Conducted Emissions	17
5.6 Unwanted Emissions below 1 GHz	17
5.7 Unwanted Emissions above 1 GHz	18
6 Test Arrangements	19
6.1 RF Output Power	19
6.1.1 Test Setup	19
6.1.2 Test Procedure	19
6.2 Power Spectral Density	19
6.2.1 Test Setup	19
6.2.2 Test Procedure	19
6.3 6 dB Bandwidth	20
6.3.1 Test Setup	20
6.3.2 Test Procedure	20
6.4 Conducted Out of Band Emissions	21
6.4.1 Test Setup	21
6.4.2 Test Procedure	21
6.5 AC Power Conducted Emissions	22
6.5.1 Test Setup	22
6.5.2 Test Procedure	22
6.6 Unwanted Emissions below 1 GHz	23
6.6.1 Test Setup	23
6.6.2 Test Procedure	24
6.7 Unwanted Emissions above 1 GHz	25
6.7.1 Test Setup	25
6.7.2 Test Procedure	25
7 Test Results of Test Item	26

7.1	RF Output Power.....	26
7.2	Power Spectral Density	28
7.3	6 dB Bandwidth	30
7.4	Conducted Out of Band Emissions	32
7.5	AC Power Conducted Emissions	36
7.6	Unwanted Emissions below 1 GHz	38
7.7	Unwanted Emissions above 1 GHz.....	40
8	Pictures of Test Arrangements	64
9	Information of the Testing Laboratories	65

Release Control Record

Issue No.	Description	Date Issued
RFCJWN-WTW-P26060465	Original release.	2026/8/17

1 Certificate

Product: Security Camera

Brand: blink or 

Test Model: BCM10300U

Sample Status: Engineering sample

Applicant: Immedia Semiconductor LLC

Test Date: 2026/7/16 ~ 2026/7/30

Standard: 47 CFR FCC Part 15, Subpart C (Section 15.247)

Measurement procedure: ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024
KDB 558074 D01 15.247 Meas Guidance v05r02

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.247)			
Standard / Clause	Test Item	Result	Remark
15.247(b)	RF Output Power	Pass	Meet the requirement of limit.
15.247(e)	Power Spectral Density	Pass	Meet the requirement of limit.
15.247(a)(2)	6 dB Bandwidth	Pass	Meet the requirement of limit.
15.247(d)	Conducted Out of Band Emissions	Pass	Meet the requirement of limit.
15.207	AC Power Conducted Emissions	Pass	Minimum passing margin is -17.34 dB at 0.66600 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions below 1 GHz	Pass	Minimum passing margin is -7.1 dB at 943.74 MHz
15.205 / 15.209 / 15.247(d)	Unwanted Emissions above 1 GHz	Pass	Minimum passing margin is -8.1 dB at 2483.50 MHz
15.203	Antenna Requirement	Pass	No antenna connector is used.

Note: Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Parameter	Specification	Expanded Uncertainty (k=2) (±)
RF Output Power	-	1.371 dB
Power Spectral Density	-	1.017 dB
6 dB Bandwidth	-	206.5 Hz
Conducted Out of Band Emissions	9 kHz ~ 40 GHz	2.79 dB
AC Power Conducted Emissions	9 kHz ~ 30 MHz	3.23 dB
Unwanted Emissions below 1 GHz	9 kHz ~ 30 MHz	3 dB
	30 MHz ~ 1 GHz	2.93 dB
Unwanted Emissions above 1 GHz	1 GHz ~ 18 GHz	1.76 dB
	18 GHz ~ 40 GHz	1.77 dB

The other instruments specified are routine verified to remain within the calibrated levels, no measurement uncertainty is required to be calculated.

2.2 Supplementary Information

There is not any deviation from the test standards for the test method, and no modifications required for compliance.

3 General Information

3.1 General Description

Product	Security Camera
Brand	blink or 
Test Model	BCM10300U
Status of EUT	Engineering sample
Power Supply Rating	5Vdc
Modulation Type	GFSK
Modulation Technology	DTS
Transfer Rate	Up to 2 Mbps
Operating Frequency	2.402 GHz ~ 2.48 GHz
Number of Channel	40
Output Power	2.972 mW (4.73 dBm)

Note:

1. The EUT uses following accessories.

Item	Brand	Model	Specification
Power Adapter	blink	A726-050150U-US1	AC Input: 100-240Vac, 50/60Hz Max 0.3A DC Output: 5Vdc, 1.5A DC Output Cable: Shielded USB cable (2.0m)

2. There are Bluetooth and WLAN (2.4 GHz & 5 GHz) technology used for the EUT.

3. Bluetooth and WLAN (2.4 GHz & 5 GHz) technologies cannot transmit at same time.

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 Antenna Description of EUT

The antenna information is listed as below.

Antenna Net Gain(dBi)	Frequency range	Antenna Type	Connector Type
4.57	2412	PIFA	N/A
4.17	2442	PIFA	N/A
2.31	2472	PIFA	N/A
4.48	5180	PIFA	N/A
3.58	5320	PIFA	N/A
3.95	5500	PIFA	N/A
2.87	5745	PIFA	N/A
2.05	5825	PIFA	N/A

* Detail antenna specification please refer to antenna datasheet and/or antenna measurement report.

3.3 Channel List

40 channels are provided for BT-LE:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480

3.4 Test Mode Applicability and Tested Channel Detail

Worst Case:	Y-AXIS
-------------	--------

Following channel(s) was (were) selected for the final test as listed below:

Test Item	Mode	Tested Channel	Modulation	Data Rate Parameter
RF Output Power	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kb/s
	BT-LE 500k	0, 19, 39	GFSK	500kb/s
Power Spectral Density	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kb/s
	BT-LE 500k	0, 19, 39	GFSK	500kb/s
6 dB Bandwidth / Conducted Out of Band Emissions	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kb/s
	BT-LE 500k	0, 19, 39	GFSK	500kb/s
AC Power Conducted Emissions	BT-LE 2M	39	GFSK	2Mb/s
Unwanted Emissions below 1 GHz	BT-LE 2M	39	GFSK	2Mb/s
Unwanted Emissions above 1 GHz	BT-LE 1M	0, 19, 39	GFSK	1Mb/s
	BT-LE 2M	0, 19, 39	GFSK	2Mb/s
	BT-LE 125k	0, 19, 39	GFSK	125kb/s
	BT-LE 500k	0, 19, 39	GFSK	500kb/s


3.5 Duty Cycle of Test Signal

BT-LE 1M: Duty cycle = $2.14 \text{ ms} / 2.49 \text{ ms} \times 100\% = 85.9\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.66 \text{ dB}$

BT-LE 2M: Duty cycle = $1.08 \text{ ms} / 1.87 \text{ ms} \times 100\% = 57.8\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 2.38 \text{ dB}$

BT-LE 125k: Duty cycle = $17.1 \text{ ms} / 17.45 \text{ ms} \times 100\% = 98.0\%$


BT-LE 500k: Duty cycle = $4.58 \text{ ms} / 5 \text{ ms} \times 100\% = 91.6\%$, duty factor = $10 * \log (1/\text{Duty cycle}) = 0.38 \text{ dB}$



3.6 Test Program Used and Operation Descriptions

Controlling software Tara Term Version 4.106 has been activated to set the EUT under transmission condition continuously at specific channel frequency.

3.7 Connection Diagram of EUT and Peripheral Devices



3.8 Configuration of Peripheral Devices and Cable Connections

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A	Adapter	blink	A726-050150U-US1	N/A	N/A	Supplied by applicant

ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1	USB typeC Cable	1	2	Yes	N/A	Supplied by applicant

4 Test Instruments

The calibration interval of the all test instruments are 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.1 RF Output Power

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2026/5/21	2027/5/20
Peak Power Analyzer Keysight	8990B	MY51000485	2026/1/23	2027/1/22
USB Power Sensor Anritsu	MA24408A	12994	2025/12/5	2026/12/4
Wideband Power Sensor Keysight	N1923A	MY58020002	2026/1/26	2027/1/25
		MY58140009	2026/1/26	2027/1/25

Notes:

1. The test was performed in HY - Oven room(Hwaya).
2. Tested Date: 2026/7/21

4.2 Power Spectral Density

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Fixed Attenuator Woken	00800A1K01A-10	00800A1K01A-10-01	2026/5/21	2027/5/20
MXA Signal Analyzer Keysight	N9020B	MY60110462	2026/5/5	2027/5/4
Signal & Spectrum Analyzer R&S	FSV3044	101505	2026/6/15	2027/6/14
	FSW26	102023	2025/11/14	2026/11/13
	FSW43	101582	2026/5/2	2027/5/1
Signal Analyzer R&S	FSV40	100980	2026/5/14	2027/5/13
Software BV	ADT_RF Test Software V7.6.5.4	N/A	N/A	N/A
Spectrum Analyzer R&S	FSU26	101645	2025/7/28	2026/7/27
	FSU43	101261	2026/5/4	2027/5/3

Notes:

1. The test was performed in HY - Oven room(Hwaya).
2. Tested Date: 2026/7/21

4.3 6 dB Bandwidth

Refer to section 4.2 to get the tested date and information of the instruments.

4.4 Conducted Out of Band Emissions

Refer to section 4.2 to get the tested date and information of the instruments.

4.5 AC Power Conducted Emissions

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
50 ohm terminal resistance	E1-011279	04	2025/12/4	2026/12/3
	E1-011280	05	2025/12/4	2026/12/3
	E1-011311	09	2025/12/4	2026/12/3
DC LISN Schwarzbeck	NNBM 8126G	8126G-069	2025/11/3	2026/11/2
Diode Pulse Limiter Schwarzbeck	VTSD 9561 F-N	01445	2026/4/18	2027/4/17
EMI Test Receiver R&S	ESCI	100613	2025/11/27	2026/11/26
Extension Power Line EMCI	EMCI-EXP-EU-US	023	2026/3/6	2027/3/5
LISN R&S	ENV216	101826	2026/3/6	2027/3/5
	ESH3-Z5	100311	2025/8/28	2026/8/27
RF Coaxial Cable Woken	5D-FB	Cable-cond1-01	2026/1/3	2027/1/2
Software BVADT	BVADT_Cond_ V7.4.1.0	N/A	N/A	N/A
V-LISN Schwarzbeck	NNBL 8226-2	8226-142	2025/8/27	2026/8/26

Notes:

1. The test was performed in HY - Conduction 1.
2. Tested Date: 2026/7/27

4.6 Unwanted Emissions below 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
Bi_Log Antenna Schwarzbeck	VULB 9168	9168-1213	2025/9/18	2026/9/17
Loop Antenna TESEQ	HLA 6121	45745	2025/9/1	2026/8/31
MXE EMI Receiver Keysight	N9038B	MY60180019	2026/1/14	2027/1/13
Preamplifier EMCI	EMC330N	980782	2026/1/13	2027/1/12
RF Coaxial Cable EMCI	EMCCFD400-NM-NM-500	201233	2026/1/13	2027/1/12
	EMCCFD400-NM-NM-3000	201235	2026/1/13	2027/1/12
	EMCCFD400-NM-NM-9000	201236(with PAD)	2026/1/13	2027/1/12
Signal & Spectrum Analyzer R&S	FSW43	101867	2026/2/11	2027/2/10
Software BV ADT	ADT_Radiated_ V7.7.1.1.1	N/A	N/A	N/A
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8(Wenming).
2. Tested Date: 2026/7/27

4.7 Unwanted Emissions above 1 GHz

Description Manufacturer	Model No.	Serial No.	Calibrated Date	Calibrated Until
Antenna Tower Max-Full	MFT-151SS-0.5T	N/A	N/A	N/A
Horn Antenna RFSPIN	DRH18-E	210103A18E	2025/11/9	2026/11/8
Horn Antenna Schwarzbeck	BBHA 9170	9170-1049	2025/11/9	2026/11/8
MXE EMI Receiver Keysight	N9038B	MY60180019	2026/1/14	2027/1/13
Preamplifier EMCI	EMC118A45SE	980808	2025/12/24	2026/12/23
	EMC184045SE	980788	2026/1/13	2027/1/12
RF Coaxial Cable EMCI	EMC101G-KM-KM-2000	201254	2026/1/13	2027/1/12
		201255	2026/1/13	2027/1/12
	EMC101G-KM-KM-5000	201261	2026/1/13	2027/1/12
	EMC104-SM-SM-1000	210102	2026/1/13	2027/1/12
	EMC104-SM-SM-3000	201231	2026/1/13	2027/1/12
	EMC104-SM-SM-9000	201243	2026/1/13	2027/1/12
Signal & Spectrum Analyzer R&S	FSW43	101867	2026/2/11	2027/2/10
Software BV ADT	ADT_Radiated_ V7.7.1.1.1	N/A	N/A	N/A
Turn Table Max-Full	MF-7802BS	N/A	N/A	N/A
Turn Table Controller Max-Full	MF-7802BS	MF780208674	N/A	N/A

Notes:

1. The test was performed in WM - 966 chamber 8(Wenming).
2. Tested Date: 2026/7/16 ~ 2026/7/30

5 Limits of Test Items

5.1 RF Output Power

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30 dBm)

5.2 Power Spectral Density

The maximum of power spectral density measurement is 8 dBm in any 3 kHz.

5.3 6 dB Bandwidth

The minimum of 6 dB bandwidth measurement is 0.5 MHz.

5.4 Conducted Out of Band Emissions

Below 20 dB of the highest emission level of operating band (in 100 kHz Resolution Bandwidth).

5.5 AC Power Conducted Emissions

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.

5.6 Unwanted Emissions below 1 GHz

Radiated emissions up to 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).

5.7 Unwanted Emissions above 1 GHz

Radiated emissions above 1 GHz which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20 dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
Above 960	500	3


Notes:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000 MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

6 Test Arrangements

6.1 RF Output Power

6.1.1 Test Setup



Note: The correction factor has already been compensated by the instrument.

6.1.2 Test Procedure

Peak Power:

A peak power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak power sensor. Record the power level.


The power meter video bandwidth is greater than or equal to the DTS bandwidth and use a fast responding diode detector.

Average Power:

Average power sensor was used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst. Duty factor is not added to measured value.

6.2 Power Spectral Density

6.2.1 Test Setup




Note: The correction factor has already been compensated by the instrument.

6.2.2 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span > 1.5 times the DTS bandwidth.
- Set the RBW to: 3 kHz.
- Set the VBW $\geq 3 \times$ RBW.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

6.3 6 dB Bandwidth

6.3.1 Test Setup




Note: The correction factor has already been compensated by the instrument.

6.3.2 Test Procedure

- a. Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz.
- b. Set the VBW $\geq [3 \times \text{RBW}]$.
- c. Detector = peak.
- d. Trace mode = max-hold.
- e. Sweep = No faster than coupled (auto) time.
- f. Allow the trace to stabilize.
- g. Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value.

6.4 Conducted Out of Band Emissions

6.4.1 Test Setup



Note: The correction factor has already been compensated by the instrument.

6.4.2 Test Procedure

MEASUREMENT PROCEDURE REF


- Set instrument center frequency to DTS channel center frequency.
- Set the span to ≥ 1.5 times the DTS bandwidth.
- Set the RBW = 100 kHz.
- Set the VBW ≥ 300 kHz.
- Detector = peak.
- Sweep time = No faster than coupled (auto) time.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum PSD level.

MEASUREMENT PROCEDURE OOB

- Set the center frequency and span to encompass frequency range to be measured. Note that the frequency range might need to be divided into multiple frequency ranges to retain frequency resolution.
- Set RBW = 100 kHz.
- Set VBW ≥ 300 kHz.
- Detector = peak.
- Sweep = No faster than coupled (auto) time.
- Trace Mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level.

6.5 AC Power Conducted Emissions

6.5.1 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.5.2 Test Procedure


- Exploratory ac power-line conducted emission measurements: The EUT shall be operated on the mid channel and in the mode with highest output power unless the fundamental operates in the AC power-line emission test range then the EUT shall be operated in the range of typical modes of operation.
- The EUT was placed on a 0.8 meter to the top of table and placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50 uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched. Emission levels under (Limit – 20 dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9 kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15 MHz-30 MHz.


6.6 Unwanted Emissions below 1 GHz

6.6.1 Test Setup

For Radiated emission below 30 MHz



For Radiated emission above 30 MHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.6.2 Test Procedure

For Radiated emission below 30 MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode (however, peak detector measurements may be used to determine compliance with QP requirements), except for the frequency band (9 kHz to 90 kHz and 110 kHz to 490 kHz) set to average detect function and peak detect function.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 200 Hz at frequency below 150 kHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9 kHz or 10 kHz at frequency (150 kHz to 30 MHz).
3. All modes of operation were investigated and the worst-case emissions are reported.

For Radiated emission above 30 MHz


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-peak(QP) detect function, Average(AV) detect function, Peak(PK) detect function and specified bandwidth with maximum hold mode when the test frequencies less than or equal to 1 GHz.

Notes:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz (however, peak detector measurements may be used to determine compliance with QP requirements).
2. All modes of operation were investigated and the worst-case emissions are reported.

6.7 Unwanted Emissions above 1 GHz

6.7.1 Test Setup



For the actual test configuration, please refer to the attached file (Test Setup Photo).

6.7.2 Test Procedure

- The EUT was placed on the top of a rotating table 1.5 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver/spectrum analyzer was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Notes:

- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) and Average detection (AV) at frequency above 1 GHz.
- For fundamental and harmonic signal measurement, the resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10 Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1 GHz.
- All modes of operation were investigated and the worst-case emissions are reported.

7 Test Results of Test Item

7.1 RF Output Power

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan
--------------	----------------	---------------------------	--------------	------------	------

For Peak Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.6	4.15	30	Pass
19	2440	2.612	4.17	30	Pass
39	2480	2.6	4.15	30	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.938	4.68	30	Pass
19	2440	2.924	4.66	30	Pass
39	2480	2.972	4.73	30	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 125k

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.594	4.14	30	Pass
19	2440	2.667	4.26	30	Pass
39	2480	2.71	4.33	30	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

BT-LE 500k

Chan.	Chan. Freq. (MHz)	Peak Power (mW)	Peak Power (dBm)	Power Limit (dBm)	Test Result
0	2402	2.624	4.19	30	Pass
19	2440	2.71	4.33	30	Pass
39	2480	2.729	4.36	30	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the output power limit shall not be reduced.

For Average Power

BT-LE 1M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.41	3.82
19	2440	2.427	3.85
39	2480	2.438	3.87

BT-LE 2M

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.427	3.85
19	2440	2.432	3.86
39	2480	2.443	3.88

BT-LE 125k

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.421	3.84
19	2440	2.489	3.96
39	2480	2.506	3.99

BT-LE 500k

Chan.	Chan. Freq. (MHz)	Average Power (mW)	Average Power (dBm)
0	2402	2.443	3.88
19	2440	2.518	4.01
39	2480	2.529	4.03

7.2 Power Spectral Density

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan
--------------	----------------	---------------------------	--------------	------------	------

BT-LE 1M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-11.62	8	Pass
19	2440	-11.58	8	Pass
39	2480	-11.44	8	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 2M

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-15.21	8	Pass
19	2440	-15.19	8	Pass
39	2480	-15.04	8	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 125k

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-3.50	8	Pass
19	2440	-3.43	8	Pass
39	2480	-3.31	8	Pass


Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

BT-LE 500k

Chan.	Chan. Freq. (MHz)	PSD (dBm/3kHz)	PSD Limit (dBm/3kHz)	Test Result
0	2402	-3.65	8	Pass
19	2440	-3.61	8	Pass
39	2480	-3.52	8	Pass

Note: The antenna gain is 4.57 dBi $\leq$ 6 dBi, so the power density limit shall not be reduced.

Spectrum Plot of Maximum Value



7.3 6 dB Bandwidth

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan
--------------	----------------	---------------------------	--------------	------------	------

BT-LE 1M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.68	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.68	0.5	Pass

BT-LE 2M

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	1.27	0.5	Pass
19	2440	1.27	0.5	Pass
39	2480	1.27	0.5	Pass





BT-LE 125k

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.72	0.5	Pass
19	2440	0.71	0.5	Pass
39	2480	0.72	0.5	Pass

BT-LE 500k

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)	Test Result
0	2402	0.67	0.5	Pass
19	2440	0.68	0.5	Pass
39	2480	0.67	0.5	Pass

Spectrum Plot of Minimum Value



7.4 Conducted Out of Band Emissions

Input Power:	120 Vac, 60 Hz	Environmental Conditions:	25°C, 60% RH	Tested By:	Ivan
--------------	----------------	---------------------------	--------------	------------	------

BT-LE 1M



BT-LE 2M



BT-LE 125k



BT-LE 500k




7.5 AC Power Conducted Emissions

RF Mode	BT LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Vanness Huang		

Phase Of Power : Line (L)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.39759	9.85	17.85	11.59	27.70	21.44	57.90	47.90	-30.20	-26.46
2	0.51400	9.86	18.89	12.46	28.75	22.32	56.00	46.00	-27.25	-23.68
3	0.66600	9.88	25.53	18.78	35.41	28.66	56.00	46.00	-20.59	-17.34
4	0.85000	9.89	17.30	10.81	27.19	20.70	56.00	46.00	-28.81	-25.30
5	1.57400	9.96	14.14	8.06	24.10	18.02	56.00	46.00	-31.90	-27.98
6	4.64200	10.07	11.36	5.01	21.43	15.08	56.00	46.00	-34.57	-30.92

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




RF Mode	BT LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	150 kHz ~ 30 MHz	Detector Function & Resolution Bandwidth	Quasi-Peak (QP) / Average (AV), 9 kHz
Input Power	120 Vac, 60 Hz	Environmental Conditions	25 °C, 75% RH
Tested By	Vanness Huang		

Phase Of Power : Neutral (N)										
No	Frequency (MHz)	Correction Factor (dB)	Reading Value (dBuV)		Emission Level (dBuV)		Limit (dBuV)		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.40180	9.82	14.94	10.33	24.76	20.15	57.82	47.82	-33.06	-27.67
2	0.53000	9.83	16.69	12.15	26.52	21.98	56.00	46.00	-29.48	-24.02
3	0.65800	9.84	22.06	17.17	31.90	27.01	56.00	46.00	-24.10	-18.99
4	0.83361	9.86	14.86	10.14	24.72	20.00	56.00	46.00	-31.28	-26.00
5	0.96600	9.87	14.10	9.57	23.97	19.44	56.00	46.00	-32.03	-26.56
6	1.09400	9.88	10.99	6.63	20.87	16.51	56.00	46.00	-35.13	-29.49

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




7.6 Unwanted Emissions below 1 GHz

RF Mode	BT LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	45.52	23.1 QP	40.0	-16.9	1.31 H	82	35.7	-12.6
2	148.34	22.7 QP	43.5	-20.8	1.71 H	148	35.1	-12.4
3	255.04	27.6 QP	46.0	-18.4	1.83 H	245	41.1	-13.5
4	372.41	25.8 QP	46.0	-20.2	1.72 H	190	35.7	-9.9
5	783.69	35.6 QP	46.0	-10.4	1.85 H	214	36.2	-0.6
6	943.74	38.9 QP	46.0	-7.1	1.06 H	49	37.4	1.5

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.




RF Mode	BT LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	30 MHz ~ 1 GHz	Detector Function & Bandwidth	QP: RB=120 kHz, DET=Quasi-Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	35.82	24.4 QP	40.0	-15.6	1.42 V	116	38.1	-13.7
2	124.09	23.2 QP	43.5	-20.3	1.85 V	293	37.7	-14.5
3	236.61	27.1 QP	46.0	-18.9	1.71 V	115	41.2	-14.1
4	296.75	27.0 QP	46.0	-19.0	1.20 V	114	38.8	-11.8
5	482.99	27.7 QP	46.0	-18.3	1.86 V	29	34.5	-6.8
6	796.30	34.5 QP	46.0	-11.5	1.74 V	155	35.2	-0.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit of frequency range 30 MHz ~ 1 GHz.
5. The frequency range 9 kHz ~ 30 MHz: all emissions are more than 20 dB below the limit, therefore do not be recorded in this report.



7.7 Unwanted Emissions above 1 GHz

RF Mode	BT LE-1M	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=510 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.9 PK	74.0	-16.1	1.00 H	297	25.6	32.3
2	2390.00	43.4 AV	54.0	-10.6	1.00 H	297	11.1	32.3
3	*2402.00	98.8 PK			1.00 H	297	66.5	32.3
4	*2402.00	97.3 AV			1.00 H	297	65.0	32.3
5	4804.00	48.7 PK	74.0	-25.3	1.25 H	116	44.8	3.9
6	4804.00	35.7 AV	54.0	-18.3	1.25 H	116	31.8	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.8 PK	74.0	-17.2	1.74 V	248	24.5	32.3
2	2390.00	43.5 AV	54.0	-10.5	1.74 V	248	11.2	32.3
3	*2402.00	100.6 PK			1.74 V	248	68.3	32.3
4	*2402.00	99.3 AV			1.74 V	248	67.0	32.3
5	4804.00	49.0 PK	74.0	-25.0	1.82 V	251	45.1	3.9
6	4804.00	36.0 AV	54.0	-18.0	1.82 V	251	32.1	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-1M	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=510 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	99.0 PK			1.00 H	288	66.7	32.3
2	*2440.00	97.7 AV			1.00 H	288	65.4	32.3
3	4880.00	48.8 PK	74.0	-25.2	1.26 H	122	45.1	3.7
4	4880.00	35.6 AV	54.0	-18.4	1.26 H	122	31.9	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	101.2 PK			1.66 V	268	68.9	32.3
2	*2440.00	99.7 AV			1.66 V	268	67.4	32.3
3	4880.00	49.0 PK	74.0	-25.0	1.85 V	253	45.3	3.7
4	4880.00	35.9 AV	54.0	-18.1	1.85 V	253	32.2	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-1M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=510 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.8 PK			1.02 H	294	65.4	32.4
2	*2480.00	96.0 AV			1.02 H	294	63.6	32.4
3	2483.50	57.6 PK	74.0	-16.4	1.02 H	294	25.2	32.4
4	2483.50	45.2 AV	54.0	-8.8	1.02 H	294	12.8	32.4
5	4960.00	49.1 PK	74.0	-24.9	1.30 H	125	45.1	4.0
6	4960.00	35.9 AV	54.0	-18.1	1.30 H	125	31.9	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	99.2 PK			1.66 V	266	66.8	32.4
2	*2480.00	98.0 AV			1.66 V	266	65.6	32.4
3	2483.50	56.5 PK	74.0	-17.5	1.66 V	266	24.1	32.4
4	2483.50	45.2 AV	54.0	-8.8	1.66 V	266	12.8	32.4
5	4960.00	49.2 PK	74.0	-24.8	1.22 V	248	45.2	4.0
6	4960.00	36.1 AV	54.0	-17.9	1.22 V	248	32.1	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-2M	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.00 H	297	24.7	32.3
2	2390.00	43.4 AV	54.0	-10.6	1.00 H	297	11.1	32.3
3	*2402.00	98.6 PK			1.00 H	297	66.3	32.3
4	*2402.00	95.1 AV			1.00 H	297	62.8	32.3
5	4804.00	49.0 PK	74.0	-25.0	1.25 H	116	45.1	3.9
6	4804.00	35.9 AV	54.0	-18.1	1.25 H	116	32.0	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	1.74 V	248	24.9	32.3
2	2390.00	43.6 AV	54.0	-10.4	1.74 V	248	11.3	32.3
3	*2402.00	100.4 PK			1.74 V	248	68.1	32.3
4	*2402.00	97.1 AV			1.74 V	248	64.8	32.3
5	4804.00	49.1 PK	74.0	-24.9	1.82 V	251	45.2	3.9
6	4804.00	36.1 AV	54.0	-17.9	1.82 V	251	32.2	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-2M	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	98.7 PK			1.00 H	288	66.4	32.3
2	*2440.00	95.4 AV			1.00 H	288	63.1	32.3
3	4880.00	48.9 PK	74.0	-25.1	1.26 H	122	45.2	3.7
4	4880.00	35.7 AV	54.0	-18.3	1.26 H	122	32.0	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	100.8 PK			1.66 V	268	68.5	32.3
2	*2440.00	97.5 AV			1.66 V	268	65.2	32.3
3	4880.00	49.1 PK	74.0	-24.9	1.85 V	253	45.4	3.7
4	4880.00	35.9 AV	54.0	-18.1	1.85 V	253	32.2	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-2M	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.9 PK			1.02 H	294	65.5	32.4
2	*2480.00	94.0 AV			1.02 H	294	61.6	32.4
3	2483.50	56.8 PK	74.0	-17.2	1.02 H	294	24.4	32.4
4	2483.50	45.3 AV	54.0	-8.7	1.02 H	294	12.9	32.4
5	4960.00	49.1 PK	74.0	-24.9	1.30 H	125	45.1	4.0
6	4960.00	36.1 AV	54.0	-17.9	1.30 H	125	32.1	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	99.2 PK			1.66 V	266	66.8	32.4
2	*2480.00	95.7 AV			1.66 V	266	63.3	32.4
3	2483.50	57.0 PK	74.0	-17.0	1.66 V	266	24.6	32.4
4	2483.50	45.2 AV	54.0	-8.8	1.66 V	266	12.8	32.4
5	4960.00	49.5 PK	74.0	-24.5	1.22 V	248	45.5	4.0
6	4960.00	36.4 AV	54.0	-17.6	1.22 V	248	32.4	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-125K	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.7 PK	74.0	-17.3	1.00 H	297	24.4	32.3
2	2390.00	43.5 AV	54.0	-10.5	1.00 H	297	11.2	32.3
3	*2402.00	98.7 PK			1.00 H	297	66.4	32.3
4	*2402.00	96.9 AV			1.00 H	297	64.6	32.3
5	4804.00	48.6 PK	74.0	-25.4	1.25 H	116	44.7	3.9
6	4804.00	35.5 AV	54.0	-18.5	1.25 H	116	31.6	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.0 PK	74.0	-17.0	1.74 V	248	24.7	32.3
2	2390.00	43.4 AV	54.0	-10.6	1.74 V	248	11.1	32.3
3	*2402.00	100.7 PK			1.74 V	248	68.4	32.3
4	*2402.00	99.1 AV			1.74 V	248	66.8	32.3
5	4804.00	48.9 PK	74.0	-25.1	1.82 V	251	45.0	3.9
6	4804.00	35.7 AV	54.0	-18.3	1.82 V	251	31.8	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-125K	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	99.0 PK			1.00 H	288	66.7	32.3
2	*2440.00	97.7 AV			1.00 H	288	65.4	32.3
3	4880.00	48.5 PK	74.0	-25.5	1.26 H	122	44.8	3.7
4	4880.00	35.4 AV	54.0	-18.6	1.26 H	122	31.7	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	101.2 PK			1.66 V	267	68.9	32.3
2	*2440.00	99.7 AV			1.66 V	267	67.4	32.3
3	4880.00	48.8 PK	74.0	-25.2	1.85 V	253	45.1	3.7
4	4880.00	35.8 AV	54.0	-18.2	1.85 V	253	32.1	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-125K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.6 PK			1.02 H	294	65.2	32.4
2	*2480.00	95.7 AV			1.02 H	294	63.3	32.4
3	2483.50	57.9 PK	74.0	-16.1	1.02 H	294	25.5	32.4
4	2483.50	45.2 AV	54.0	-8.8	1.02 H	294	12.8	32.4
5	4960.00	49.0 PK	74.0	-25.0	1.30 H	125	45.0	4.0
6	4960.00	35.9 AV	54.0	-18.1	1.30 H	125	31.9	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	99.5 PK			1.66 V	266	67.1	32.4
2	*2480.00	97.7 AV			1.66 V	266	65.3	32.4
3	2483.50	57.3 PK	74.0	-16.7	1.66 V	266	24.9	32.4
4	2483.50	45.0 AV	54.0	-9.0	1.66 V	266	12.6	32.4
5	4960.00	49.1 PK	74.0	-24.9	1.22 V	248	45.1	4.0
6	4960.00	36.1 AV	54.0	-17.9	1.22 V	248	32.1	4.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-500K	Channel	CH 0 : 2402 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=300 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	57.2 PK	74.0	-16.8	1.00 H	297	24.9	32.3
2	2390.00	43.7 AV	54.0	-10.3	1.00 H	297	11.4	32.3
3	*2402.00	98.8 PK			1.00 H	297	66.5	32.3
4	*2402.00	97.2 AV			1.00 H	297	64.9	32.3
5	4804.00	48.9 PK	74.0	-25.1	1.25 H	116	45.0	3.9
6	4804.00	35.7 AV	54.0	-18.3	1.25 H	116	31.8	3.9
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	2390.00	56.9 PK	74.0	-17.1	1.74 V	248	24.6	32.3
2	2390.00	43.4 AV	54.0	-10.6	1.74 V	248	11.1	32.3
3	*2402.00	100.9 PK			1.74 V	248	68.6	32.3
4	*2402.00	99.3 AV			1.74 V	248	67.0	32.3
5	4804.00	49.1 PK	74.0	-24.9	1.82 V	251	45.2	3.9
6	4804.00	36.0 AV	54.0	-18.0	1.82 V	251	32.1	3.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-500K	Channel	CH 19 : 2440 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=300 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	99.3 PK			1.00 H	288	67.0	32.3
2	*2440.00	97.9 AV			1.00 H	288	65.6	32.3
3	4880.00	48.8 PK	74.0	-25.2	1.85 H	253	45.1	3.7
4	4880.00	35.8 AV	54.0	-18.2	1.85 H	253	32.1	3.7
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2440.00	101.4 PK			1.66 V	268	69.1	32.3
2	*2440.00	99.9 AV			1.66 V	268	67.6	32.3
3	4880.00	49.0 PK	74.0	-25.0	1.85 V	283	45.3	3.7
4	4880.00	36.0 AV	54.0	-18.0	1.85 V	283	32.3	3.7

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * " : Fundamental frequency, the limit was restricted at the RF Output Power.

RF Mode	BT LE-500K	Channel	CH 39 : 2480 MHz
Frequency Range	1 GHz ~ 25 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=300 Hz, DET=Peak
Input Power	120 Vac, 60 Hz	Environmental Conditions	23 °C, 67% RH
Tested By	Karl Lee		

Antenna Polarity & Test Distance : Horizontal at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	97.6 PK			1.02 H	294	65.2	32.4
2	*2480.00	95.9 AV			1.02 H	294	63.5	32.4
3	2483.50	56.3 PK	74.0	-17.7	1.02 H	294	23.9	32.4
4	2483.50	45.9 AV	54.0	-8.1	1.02 H	294	13.5	32.4
5	4960.00	48.6 PK	74.0	-25.4	1.30 H	125	44.6	4.0
6	4960.00	35.7 AV	54.0	-18.3	1.30 H	125	31.7	4.0
Antenna Polarity & Test Distance : Vertical at 3 m								
No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	*2480.00	99.4 PK			1.66 V	266	67.0	32.4
2	*2480.00	97.9 AV			1.66 V	266	65.5	32.4
3	2483.50	57.2 PK	74.0	-16.8	1.66 V	266	24.8	32.4
4	2483.50	45.1 AV	54.0	-8.9	1.66 V	266	12.7	32.4
5	4960.00	48.9 PK	74.0	-25.1	1.22 V	248	44.9	4.0
6	4960.00	35.9 AV	54.0	-18.1	1.22 V	248	31.9	4.0


Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. Margin value = Emission Level – Limit value
4. The other emission levels were very low against the limit.
5. " * ": Fundamental frequency, the limit was restricted at the RF Output Power.


Plot of Band Edge

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=510 Hz, DET=Peak
-----------------	--------------------	-------------------------------	---


BT LE-1M Channel 0




BT LE-1M Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)

Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	--------------------	-------------------------------	--


BT LE-2M Channel 0




BT LE-2M Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	--------------------	-------------------------------	--




BT LE-125K Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)




Vertical (Average)


Frequency Range	2.31 GHz ~ 2.5 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=300 Hz, DET=Peak
-----------------	--------------------	-------------------------------	---




BT LE-500K Channel 39




Horizontal (Peak)



Horizontal (Average)




Vertical (Peak)



Vertical (Average)

Plot of Other Emission


Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=510 Hz, DET=Peak
-----------------	----------------	-------------------------------	---



Notes:


1. For radiated emission test data, complete spectral plots shall be presented in the report only for the worst-case scenarios of each mode within each operating frequency band.
2. The frequency range 18 GHz ~ 25 GHz: After investigation, no any emissions were found to exist, therefore they are not recorded in this report.

Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=1 kHz, DET=Peak
-----------------	----------------	-------------------------------	--



- Notes:
1. For radiated emission test data, complete spectral plots shall be presented in the report only for the worst-case scenarios of each mode within each operating frequency band.
 2. The frequency range 18 GHz ~ 25 GHz: After investigation, no any emissions were found to exist, therefore they are not recorded in this report.


Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=10 Hz, DET=Peak
-----------------	----------------	-------------------------------	--



Notes:

1. For radiated emission test data, complete spectral plots shall be presented in the report only for the worst-case scenarios of each mode within each operating frequency band.
2. The frequency range 18 GHz ~ 25 GHz: After investigation, no any emissions were found to exist, therefore they are not recorded in this report.

Frequency Range	1 GHz ~ 18 GHz	Detector Function & Bandwidth	PK: RB=1 MHz, VB=3 MHz, DET=Peak AV: RB=1 MHz, VB=300 Hz, DET=Peak
-----------------	----------------	-------------------------------	---



Notes:

1. For radiated emission test data, complete spectral plots shall be presented in the report only for the worst-case scenarios of each mode within each operating frequency band.
2. The frequency range 18 GHz ~ 25 GHz: After investigation, no any emissions were found to exist, therefore they are not recorded in this report.

8 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo)

9 Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-(0)2-26052180

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-(0)3-6668565 (SIP)

Tel: 886-(0)3-5120595 (WD)

Hwa Ya EMC/RF/Safety/SAR Lab & Wenming EMC/RF Lab

Tel: 886-(0)3-3183232

Email: service.adt@bureauveritas.com

Web Site: <http://ee.bureauveritas.com.tw>

The address and road map of all our labs can be found in our web site also.

--- END ---