



Shenzhen Huaxia Testing Technology Co., Ltd

1F., Block A of Tongsheng Technology Building, Huahui Road, Dalang Street, Longhua District, Shenzhen, China

Telephone: +86-755-26648640
Fax: +86-755-26648637
Website: www.cqa-cert.com

Report Template Version: V03
Report Template Revision Date: Mar.1st, 2017

RF Exposure Evaluation Report

Report No. : CQASZ170701366EW-03

Applicant: 1MORE INC.

Address of Applicant: Tianliao Building F14 East Block (New Materials Industrial Park), Xueyuan Road, Nanshan District, Shenzhen, China

Manufacturer: 1MORE Shen Zhen Acoustic Technology Co., Ltd.

Address of Manufacturer: Tianliao Building 1403-1411, Zone A Tianliao Industrial Park, Taoyuan Street, Nanshan District, Shenzhen, P.R. China

Factory: RISUNTEK INC

Address of Factory: Jiuwei Industrial Zone, Qishi Town, 523000 Dongguan City, Guangdong Province, P.R. China

Equipment Under Test (EUT):

Product: 1MORE iBFree Sport Bluetooth In-Ear Headphones

Model No.: E1013BT

Brand Name: 1MORE

FCC ID: 2AF8ZE1013BT


Standards: 47 CFR Part 1.1307
47 CFR Part 2.1093
KDB447498D01 General RF Exposure Guidance v06

Date of Test: 2018-01-14 to 2018-01-19

Date of Issue: 2018-01-19

Test Result : PASS*


Tested By:


(Aaron Ma)

Reviewed By:


(Owen Zhou)

Approved By:


(Jack Ai)



* In the configuration tested, the EUT complied with the standards specified above.

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of CQA, this report can't be reproduced except in full.

2 Version

Revision History Of Report

Report No.	Version	Description	Issue Date
CQASZ170701366EW-03	Rev.01	Initial report	2018-01-19

3 Contents

	Page
1 COVER PAGE.....	1
2 VERSION	2
3 CONTENTS	3
4 GENERAL INFORMATION.....	4
4.1 CLIENT INFORMATION.....	4
4.2 GENERAL DESCRIPTION OF EUT	4
5 SAR EVALUATION	5
5.1 RF EXPOSURE COMPLIANCE REQUIREMENT	5
5.1.1 <i>Standard Requirement</i>	5
5.1.2 <i>Limits</i>	5
5.1.3 <i>EUT RF Exposure</i>	5

4 General Information

4.1 Client Information

Applicant:	1MORE INC.
Address of Applicant:	Tianliao Building F14 East Block (New Materials Industrial Park), Xueyuan Road, Nanshan District, Shenzhen, China
Manufacturer:	1MORE Shen Zhen Acoustic Technology Co., Ltd.
Address of Manufacturer:	Tianliao Building 1403-1411, Zone A Tianliao Industrial Park, Taoyuan Street, Nanshan District, Shenzhen, P.R. China
Factory:	RISUNTEK INC
Address of Factory:	Jiuwei Industrial Zone, Qishi Town, 523000 Dongguan City, Guangdong Province, P.R. China

4.2 General Description of EUT

Product Name:	1MORE iBFree Sport Bluetooth In-Ear Headphones
Model No.:	E1013BT
Trade Mark:	1MORE
Hardware Version:	V3.0
Software Version:	V1.0
Operation Frequency:	2402MHz~2480MHz
Bluetooth Version:	V4.2
Modulation Type:	BT classic: GFSK, $\pi/4$ DQPSK, 8DPSK BLE: GFSK
Number of Channel:	BT classic:79 BLE:40
Sample Type:	portable production
Test Software of EUT:	Blue test 1.0 (manufacturer declare)
Antenna Type:	Integral antenna
Antenna Gain:	0dBi
Power Supply:	lithium battery:DC3.7V, Charge by DC5.0V

5 SAR Evaluation

5.1 RF Exposure Compliance Requirement

5.1.1 Standard Requirement

According to KDB447498D01 General RF Exposure Guidance v06

4.3.1. Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.1.2 Limits

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$$\left[\frac{\text{max. power of channel, including tune-up tolerance, mW}}{\sqrt{f(\text{GHz})}} \right] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR, where}$$

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.1.3 EUT RF Exposure

For BT: Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-2.59
Middle	-3.24
Highest	-4.25
$\pi/4$ DQPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-1.22
Middle	-1.45
Highest	-2.17
8DPSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-1.00
Middle	-1.07
Highest	-1.81

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ1701366EW-01

For BLE:

Measurement Data

GFSK mode	
Test channel	Peak Output Power (dBm)
Lowest	-6.68
Middle	-8.00
Highest	-9.21

Remark: The Conducted Peak Output Power data refer to report Report No.: CQASZ1701366EW-02

The worst case data: 8DPSK_lowest channel

The Max Conducted Peak Output Power is -1.00dBm in lowest channel(2.402GHz);

The best case gain of the antenna is 0dBi.

EIRP= -1.00dBm + 0dBi = -1.00dBm

-1.00dBm logarithmic terms convert to numeric result is nearly 0.794mW

According to the formula. calculate the EIRP test result:

$$\left[\frac{\text{(max. power of channel, including tune-up tolerance, mW)}}{\text{(min. test separation distance, mm)}} \right] \cdot \sqrt{f(\text{GHz})}$$

General RF Exposure = $(0.794\text{mW} / 5 \text{ mm}) \times \sqrt{2.402\text{GHz}} = 0.246$ ①

SAR requirement:

S= 3.0

② ;

① < ②.

So the SAR report is not required.