Report No.: DDT-R16Q0719-5E1

Issued Date: Aug. 27, 2016

FCC CERTIFICATION TEST REPORT

FOR

Applicant	:	Grid Connect Inc.
Address	:	1630 W. Dieh1 Rd. Naperville, Illinois 60563 USA
Equipment under Test	:	GC-WIFI300-SMT-01
Model No.	:	/
FCC ID	:	2AFC3WIFI300SMT01
Manufacturer	:	Globalscale Technologies Inc.
Address	:	5F, No. 2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China

Issued By: Dongguan Dongdian Testing Service Co., Ltd.

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808

Tel: +86-0769-22891499 Http://www.dgddt.com

REPORT

TABLE OF CONTENTS

Test report declares....4
1. Summary of test results....5
2. General test information....6
2.1. Description of EUT....6
2.2. Table for Filed Antenna....6
2.3. Assistant equipment used for test....6
2.4. Block diagram of EUT configuration for test....7
2.5. Deviations of test standard....7
2.6. Test environment conditions....7
2.7. Test laboratory....7
2.8. Measurement uncertainty....8
3. Equipment used during test....9
4. 6dB Bandwidth and 99% Bandwidth....10
4.1. Block diagram of test setup....10
4.2. Limits....10
4.3. Test Procedure....10
4.4. Test Result....11
4.5. Original test data....11
5. Maximum Peak Output Power....15
5.1. Block diagram of test setup....15
5.2. Limits....15
5.3. Test Procedure....15
5.4. Test Result....15
6. Power Spectral Density....16
6.1. Block diagram of test setup....16
6.2. Limits....16
6.3. Test Procedure....16
6.4. Test Result....16
6.5. Original test data....17
7. Emissions in non-restricted frequency bands....20
7.1. Block diagram of test setup....20
7.2. Limits....20
7.3. Test Procedure....20
7.4. Test Result....20
7.5. Original test data....21
8. Emissions in restricted frequency bands....42
8.1. Block diagram of test setup....42

8.2. Limit 43
8.3. Test Procedure 44
8.4. Test result 45
9. Band Edge Compliance 49
9.1. Block diagram of test setup 49
9.2. Limit 49
9.3. Test Procedure 49
9.4. Test result 49
10. Power Line Conducted Emission 62
10.1. Block diagram of test setup 62
10.2. Power Line Conducted Emission Limits(Class B) 62
10.3. Test Procedure 62
10.4. Test Result 63
11. Antenna Requirements 66
11.1. Limit 66
11.2. Result 66
12. Test setup photograph 67
13. Photos of the EUT 69

TEST REPORT DECLARE

Applicant	:	Grid Connect Inc.
Address	:	1630 W. Dieh1 Rd. Naperville, Illinois 60563 USA
Equipment under Test	:	GC-WIFI300-SMT-01
Model No	:	/
Manufacturer	:	Globalscale Technologies Inc.
Address	:	5F, No. 2 Building, Minxing Industrial Park, Minkang Road, Minzhi Street, Baoan District, Shenzhen, Guangdong, China

Test Standard Used: FCC Rules and Regulations Part 15 Subpart C: 2015

Test procedure used: ANSI C63.10:2013, ANSI C63.4:2014, KDB558074 D01 DTS Meas Guidance V03r02.

We Declare:

The equipment described above is tested by Dongguan Dongdian Testing Service Co., Ltd and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Dongguan Dongdian Testing Service Co., Ltd is assumed of full responsibility for the accuracy and completeness of these tests.

After test and evaluation, our opinion is that the equipment provided for test compliance with the requirement of the above FCC standards.

Report No:	DDT-R16Q0719-5E1		
Date of Test:	July 28, 2016~Aug. 27, 2016	**Date of Report**:	Aug. 27, 2016

Prepared By: ***Approved By:***

Leo Liu/Engineer ***Kevin Feng/EMC Manager***

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Dongguan Dongdian Testing Service Co., Ltd.

1. Summary of test results

The EUT have been tested according to the applicable standards as referenced below.		
Description of Test Item	**Standard**	**Results**
6dB Bandwidth and 99% Bandwidth	FCC Part 15: 15.247 KDB558074	PASS
Peak Output Power	FCC Part 15: 15.247 KDB558074	PASS
Power Spectral Density	FCC Part 15: 15.247 KDB558074	PASS
Emissions in non-restricted frequency bands	FCC Part 15: 15.247 KDB558074	PASS
Emissions in restricted frequency bands	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 ANSI C63.4:2014 KDB558074	PASS
Band Edge Compliance	FCC Part 15: 15.209 FCC Part 15: 15.247 ANSI C63.10: 2013 ANSI C63.4:2014 KDB558074	PASS
Power Line Conducted Emission	FCC Part 15: 15.207 ANSI C63.10: 2013 ANSI C63.4:2014	PASS
Antenna requirement	FCC Part 15: 15.203	PASS

2. General test information

2.1. Description of EUT

EUT* Name	:	GC-WIFI300-SMT-01
Model Number	:	/
EUT function description	:	Please reference user manual of this device
Power supply	:	DC 3.3V from DC Power Source
Radio Technology	:	IEEE802.11b/g/n
FCC Operation frequency	:	IEEE 802.11b: 2412MHz—2462MHz IEEE 802.11g: 2412MHz—2462MHz IEEE 802.11n HT20: 2412MHz—2462MHz
Modulation	:	IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Antenna Type	:	Please refer to section 2.2
Date of Receipt	:	July 28, 2016
Sample Type	:	Series production

Note1: EUT is the ab.of equipment under test.

Channle information							
CH	Frequency	CH	Frequency	CH	Frequency	CH	Frequency
1	2412	5	2432	9	2452	/	/
2	2417	6	2437	10	2457	/	/
3	2422	7	2442	11	2462	/	/
4	2427	8	2447	/	/	/	/

2.2. Table for Filed Antenna

Ant.	Model Name	Antenna Type	Connector	Gain (dBi)
1	/	PCB antenna	NA	0
2	N2420	integral antenna	TPX port	3.8
3	VTWFA-3	external antenna	Reversed polarity external non standard port	3.0

Note: The EUT has three antennas.
One of Ant. 1, Ant.2 or Ant. 3 can be used as transmitting/receiving antenna.
The EUT supports the antenna with TX SISO function only.
Ant 1 Ant 2 Ant 3 all have been tested ,only worse case with Ant 2 is reported for conducted and radiated emission test .

2.3. Assistant equipment used for test

Description of Assistant equipment	Manufacturer	Model number or Type	EMC Compliance	SN
Notebook	DELL	Latitude D610	FCC DOC	00045-534-136-300
Mouse	HP	M-SBF96	FCC DOC	417441-001

2.4. Block diagram of EUT configuration for test



EUT was connected to control to a special test jig provided by manufacturer which has a standard RSS-232 connector to connect to Notebook, and the Notebook will run a special test software "Labtool –mw302" provided by manufacturer to control EUT work in Continuous TX mode (>98% duty cycle), and select test channel, wireless mode and data rate.

Tested mode, channel, and data rate information			
Mode	data rate (Mpbs) (see Note)	Channel	Frequency (MHz)
IEEE 802.11b	11	LCH :CH1	2412
	11	MCH: CH6	2437
	11	HCH: CH11	2462
IEEE 802.11g	6	LCH :CH1	2412
	6	MCH: CH6	2437
	6	HCH: CH11	2462
IEEE 802.11n HT20	13	LCH :CH1	2412
	13	MCH: CH6	2437
	13	HCH: CH11	2462
Note: According exploratory test, EUT will have maximum output power in those data rate, so those data rate were used for all test.			

2.5. Deviations of test standard

No Deviation

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	21-25℃
Humidity range:	40-75%
Pressure range:	86-106kPa

2.7. Test laboratory

Dongguan Dongdian Testing Service Co., Ltd

Add: No. 17, Zongbu Road 2, Songshan Lake Sci&Tech, Industry Park, Dongguan City, Guangdong Province, China, 523808 Tel: +86-0769-22891499 http://www.dgddt.com

FCC Registration Number: 270092 Industry Canada site registration number: 10288A-1

2.8. Measurement uncertainty

Test Item	Uncertainty
Bandwidth	±1.1%
Peak Output Power(Conducted)(Spectrum analyzer)	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.38dB(3.6GHz≤ f < 8GHz)
Peak Output Power(Conducted)(Power Sensor)	0.74dB
Dwell Time	±0.6%
Conducted spurious emissions	0.86dB(10 MHz ≤ f < 3.6GHz);
	1.40dB(3.6GHz≤ f < 8GHz)
	1.66dB(8GHz≤ f < 22GHz)
Uncertainty for radio frequency (RBW<20KHz)	3×10-8
Temperature	±0.4℃
Humidity	±2%
Uncertainty for Radiation Emission test (30MHz-1GHz)	±3.14 dB (Antenna Polarize: V)
	±3.16 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1GHz-18GHz)	±4.14dB(1-6GHz)
	±4.46dB (6GHz-18Gz)
Uncertainty for Power line conduction emission test	2.44dB (150KHz-30MHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment used during test

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
RF Connected Test					
Spectrum analyzer	R&S	FSU26	1166.1660.26	2015/10/24	1Year
Vertor Signal Generator	R&S	SMBV100A	1407.6004K02	2015/10/24	1Year
MXG Vector Signal Generator	Agilent	N5182A	/	2016/06/17	1Year
Power Sensor	Agilent	U2021XA	MY55150010	2016/04/18	1Year
Power Sensor	Agilent	U2021XA	MY55150011	2016/04/19	1Year
DC Power Source	MATRIS	MPS-3005L-3	D813058W	2015/10/24	1Year
Attenuator	Mini-Circuits	BW-S10W2	101109	2015/08/18 2016/08/18	1Year
RF Cable	Micable	C10-01-01-1	100309	2015/08/18 2016/08/18	1Year
Test Software	JS Tonscend	JS1120-2	Ver.2.5	N/A	N/A
USB Data acquisition	Agilent	U2531A	TW55043503	N/A	N/A
Auto control Unit	JS Tonscend	JS0806-2	158060010	N/A	N/A
Radiated Emission Test					
EMI Test Receiver	R&S	ESU8	100316	2015/10/24	1Year
Spectrum analyzer	R&S	FSU26	1166.1660.26	2015/10/24	1Year
Trilog Broadband Antenna	Schwarzbeck	VULB9163	9163-462	2016/05/30	1 Year
Active Loop antenna	Schwarzbeck	FMZB-1519	1519-038	2015/10/24	1 Year
Double Ridged Horn Antenna	R&S	HF907	100276	2015/10/31	1 Year
Pre-amplifier	A.H.	PAM-0118	360	2015/08/18 2016/08/18	1 Year
RF Cable	HUBSER	CP-X2	W11.03	2015/10/24	1Year
RF Cable	HUBSER	CP-X1	W12.02	2015/10/24	1 Year
MI Cable	HUBSER	C10-01-01-1M	1091629	2015/10/24	1 Year
Test software	Audix	E3	V 6.11111b	/	/
Power Line Conducted Emissions Test					
Test Receiver	R&S	ESU8	100316	2015/10/25	1 Year
LISN 1	R&S	ENV216	101109	2015/10/25	1 Year
Pulse Limiter	R&S	ESH3-Z2	101242	2015/10/25	1 Year
CE Cable 1	HUBSER	ESU8/RF2	W10.01	2015/10/25	1 Year
Test software	Audix	E3	V 6.11111b	/	/

4. 6dB Bandwidth and 99% Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6dB bandwidth shall be at least 500 KHz

4.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

4.4. Test Result

EUT Set Mode	CH or Frequency	6 dB bandwidth	99% dB bandwidth
		Result (MHz)	Result (MHz)
11b	CH1	9.667	13.267
	CH6	9.600	13.400
	CH11	9.600	13.440
11g	CH1	16.560	16.480
	CH6	16.600	16.640
	CH11	16.560	16.680
11n HT 20	CH1	17.880	17.720
	CH6	17.880	17.720
	CH11	16.560	16.520
Limit: >500KHz			Conclusion: PASS
Test Date : July 28, 2016			Test Engineer : Toby

4.5. Original test data

Graphs	
11B/LCH	
11B/MCH	

11B/HCH	
11G/LCH	
11G/MCH	

11G/HCH	 Date: 28.JUL.2016 03:00:09
11N20/LCH	 Date: 28.JUL.2016 03:02:44
11N20/MCH	 Date: 28.JUL.2016 03:08:42

11N20/HCH	 RBW 100 kHz VBW 300 kHz SWT 15 ms Ref 20 dBm Att 30 dB Offset 10.2 dB Marker 4 [T1] -12.74 dBm 2.470280000 GHz OBW 16.520000000 MHz Marker 1 [T1] -6.42 dBm 2.456400000 GHz Marker 3 [T1] -12.45 dBm 2.453720000 GHz Temp 1 [T1 OBW] -12.45 dBm 2.453720000 GHz Temp 2 [T1 OBW] -11.97 dBm 2.470240000 GHz D1 -12.423 dBm Center 2.462 GHz 4 MHz/ Span 40 MHz Date: 28.JUL.2016 03:11:01

5. Maximum Peak Output Power

5.1. Block diagram of test setup

Same as scetion 4.1

5.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

5.3. Test Procedure

(1) Connect each EUT's antenna output to power sensor by RF cable and attenuator

(2) Measure the PK output power of each antenna port by power sensor.

5.4. Test Result

EUT Set Mode	CH	Result(dBm)
		Peak
11b	CH1	16.54
	CH6	16.50
	CH11	15.74
11g	CH1	16.24
	CH6	16.04
	CH11	16.12
11n HT20	CH1	14.05
	CH6	13.23
	CH11	14.24
Limit: 30dBm (PK power)		Conclusion: PASS
Test Date : July 28, 2016		Test Engineer : Toby

6. Power Spectral Density

6.1. Block diagram of test setup

Same as scetion 4.1

6.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

6.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Set the spectrum analyzer as follows:

Center frequency	DTS Channel center frequency
RBW:	3 kHz ≤ RBW ≤ 100 kHz
VBW:	≥ 3RBW
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.

(4) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

6.4. Test Result

EUT Set Mode	CH or Frequency	Result	EUT Set Mode	CH or Frequency	Result
11b	CH1	-4.500	11n HT 20	CH1	-13.620
	CH6	-4.190		CH6	-13.230
	CH11	-3.120		CH11	-13.130
11g	CH1	-12.000	/	/	/
	CH6	-11.830		/	/
	CH11	-10.970		/	/
Limit: <8dBm/3KHz			Conclusion: PASS		
Test Date : July 28, 2016			Test Engineer : Toby		

6.5. Original test data

Graphs	
11B/LCH	
11B/MCH	
11B/HCH	

11G/LCH	
11G/MCH	
11G/HCH	

11N20/LCH	
11N20/MCH	
11N20/HCH	

7. Emissions in non-restricted frequency bands

7.1. Block diagram of test setup

Same as scetion 4.1

7.2. Limits

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

7.3. Test Procedure

(1) Connect EUT's antenna output to spectrum analyzer by RF cable.

(2) Establish a reference level by using the following procedure:

Center frequency	DTS Channel center frequency
RBW:	100KHz
VBW:	300KHz
Span	1.5times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.

(4) Set the spectrum analyzer as follows:

RBW:	100KHz
VBW:	300KHz
Span	Encompass frequency range to be measured
Number of measurement points	⩾ span/RBW
Detector Mode:	Peak
Sweep time:	auto
Trace mode	Max hold

(5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

7.4. Test Result

EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)	EUT Set Mode	CH or Frequency	Measured Range	Result (dBm)
11b	CH1	30MHz-25GHz	PASS	11n HT 20	CH1	30MHz-25GHz	PASS
		2.3GHz-2.43GHz	PASS			2.3GHz-2.43GHz	PASS
	CH6	30MHz-25GHz	PASS		CH6	30MHz-25GHz	PASS
	CH11	30MHz-25GHz	PASS		CH11	30MHz-25GHz	PASS
		2.45GHz-2.6GHz	PASS			2.45GHz-2.6GHz	PASS
11g	CH1	30MHz-25GHz	PASS	/	/		
		2.3GHz-2.43GHz	PASS				
	CH6	30MHz-25GHz	PASS		/		
	CH11	30MHz-25GHz	PASS		/		
		2.45GHz-2.6GHz	PASS				
Test Date : July 28, 2016				Test Engineer : Toby			

7.5. Original test data

11B_LCH_Graphs	
Pref/11B/LCH	
Puw/11B/LCH	



Date: 28.JUL.2016 02:27:52



Date: 28.JUL.2016 02:28:00



Date: 28.JUL.2016 02:28:08



Date: 28.JUL.2016 02:28:16



Date: 28.JUL.2016 02:53:07

11B_MCH_Graphs

Pref/11B/MCH



Date: 28.JUL.2016 02:29:52

Puw/11B/MCH	 Date: 28.JUL.2016 02:29:59  Date: 28.JUL.2016 02:30:05  Date: 28.JUL.2016 02:30:13



Date: 28.JUL.2016 02:30:21



Date: 28.JUL.2016 02:30:29

11B_HCH_Graphs

Pref/11B/HCH



Date: 28.JUL.2016 02:32:14

Puw/11B/HCH	 Date: 28.JUL.2016 02:32:21  Date: 28.JUL.2016 02:32:27  Date: 28.JUL.2016 02:32:35



Date: 28.JUL.2016 02:32:43



Date: 28.JUL.2016 02:32:51



Date: 28.JUL.2016 02:53:37

11G LCH Graphs

Pref/11G/LCH	 Date: 28.JUL.2016 02:54:30
Puw/11G/LCH	 Date: 28.JUL.2016 02:54:37  Date: 28.JUL.2016 02:54:43



Date: 28.JUL.2016 02:54:51



Date: 28.JUL.2016 02:54:59



Date: 28.JUL.2016 02:55:07

	 Date: 28.JUL.2016 02:54:15
11G_MCH_Graphs	
Pref/11G/MCH	 Date: 28.JUL.2016 02:59:02
Puw/11G/MCH	 Date: 28.JUL.2016 02:59:09



Date: 28.JUL.2016 02:59:15



Date: 28.JUL.2016 02:59:23



Date: 28.JUL.2016 02:59:31

	
11G_HCH_Graphs	
Pref/11G/HCH	
Puw/11G/HCH	



Date: 28.JUL.2016 03:01:36



Date: 28.JUL.2016 03:01:44



Date: 28.JUL.2016 03:01:52

	 Date: 28.JUL.2016 03:01:59  Date: 28.JUL.2016 03:01:08
11N20_LCH_Graphs	
Pref/11N20/LCH	 Date: 28.JUL.2016 03:03:57

/11N20/LCH	 Date: 28.JUL.2016 03:04:04  Date: 28.JUL.2016 03:04:10  Date: 28.JUL.2016 03:04:18



Date: 28.JUL.2016 03:04:26



Date: 28.JUL.2016 03:04:34



Date: 28.JUL.2016 03:03:42

11N20 MCH Graphs

Pref/11N20/MCH	 Date: 28.JUL.2016 03:09:41
Puw/11N20/MCH	 Date: 28.JUL.2016 03:09:47  Date: 28.JUL.2016 03:09:53



Date: 28.JUL.2016 03:10:01



Date: 28.JUL.2016 03:10:09



Date: 28.JUL.2016 03:10:17

11N20 HCH Graphs

Pref/11N20/HCH	
Puw/11N20/HCH	 



Date: 28.JUL.2016 03:12:36



Date: 28.JUL.2016 03:12:44



Date: 28.JUL.2016 03:12:52


RBW 100 kHz
VBW 300 kHz
SWT 10 ms
Ref 20 dBm
Att 30 dB
Marker 4 [T1]
-45.52 dBm
2.483600000 GHz
Marker 1 [T1]
-6.47 dBm
2.456400000 GHz
Marker 2 [T1]
-47.20 dBm
Marker 3 [T1]
-49.15 dBm
Offset 10.2 dB
D1 -26.47 dBm
Center 2.4835 GHz
10 MHz/
Span 100 MHz
Date: 28.JUL.2016 03:12:00

8. Emissions in restricted frequency bands

8.1. Block diagram of test setup

In 3m Anechoic Chamber Test Setup Diagram for 9KHz-30MHz



In 3m Anechoic Chamber Test Setup Diagram for 30MHz-1GHz



In 3m Anechoic Chamber Test Setup Diagram for frequency above 1GHz



Note: For harmonic emissions test a appropriate high pass filter was inserted in the input port of AMP.

8.2. Limit

8.2.1 FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
[1]0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	([2])

8.2.2 FCC 15.209 Limit.

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(KHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(KHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5

216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

Note: (1)The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz and above 1000MHz.Radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30MHz, measurement may be performed at a distance closer then that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$Limit_{3m}(dBuV/m)= Limit_{30m}(dBuV/m) + 40Log(30m/3m)$$

8.2.3 Limit for this EUT

All the emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

8.3. Test Procedure

(1) EUT height should be 0.8m for below 1GHz at a semi - anechoic chamber while EUT height should be 1.5m for above 1GHz at full chamber or semi - anechoic chamber ground with absorbers.

(2) The antenna used as below table.

Test frequency range	Test antenna used	Measuring distance
9KHz-30MHz	Active Loop antenna	3 m
30MHz-1GHz	Trilog Broadband Antenna	3 m
1GHz-18GHz	Double Ridged Horn Antenna(1GHz-18GHz)	3 m
18GHz-40GHz	Horn Antenna(18GHz-40GHz)	1 m

According ANSI C63.10:2013 clause 6.4.4.2 and 6,5.3, for measurements below 30 MHz, the loop antenna was positioned with its plane vertical from the EUT and rotated about its vertical axis for maximum response at each azimuth position around the EUT. And the loop antenna also be positioned with its plane horizontal at the specified distance from the EUT. The center of the loop is 1 m above the ground. for measurement above 30MHz, the Trilog Broadband Antenna or Horn Antenna was located 3m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9KHz to 25GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1m to 4m(Except loop antenna, it's fixed 1m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9KHz to 25GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18GHz to 25GHz, so below final test was performed with frequency range from 9KHz to 18GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1m and 4m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipments and all of the interface cables were changed according to ANSI C63.10 2013 on Radiated Emission test.

(5) The emissions from 9KHz to 1GHz were measured based on CISPR QP detector except for the frequency bands 9-90KHz, 110-490KHz, for emissions from 9KHz-90KHz,110KHz-490KHz and above 1GHz were measured based on average detector, for emissions above 1GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9KHz to 1GHz, QP or average values were measured with EMI receiver with below RBW

Frequency band	RBW
9KHz-150KHz	200Hz
150KHz-30MHz	9KHz
30MHz-1GHz	120KHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1MHz, VBW is set at 3MHz for Peak measure; RMS detector RBW 1MHz VBW 3MHz for Average measure(according ANSI C63.10:2013 clause 4.2.3.2.3 procedure for average measure).

8.4. Test result

PASS. (See below detailed test result)

All the emissions except fundamental emission from 9KHz to 25GHz were comply with 15.209 limit.
Note1: According exploratory test no any obvious emission were detected from 9kHz to 30MHz and 18GHz to 25GHz, so the final test was performed with frequency range from 30MHz to 18GHz and recorded in below.

Note2: For emissions below 1GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1GHz, the final test was only performed with EUT working in 11b, Tx CH6 mode.

Radiated Emission test (below 1GHz)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	: /
Power Supply	: DC 3.3V	**Test Mode**	: Tx Mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 VULB9163/3m/VERTICAL
Memo	:		

Data: 19



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	68.87	17.34	7.94	4.05	29.33	40.00	-10.67	QP	VERTICAL
2	82.07	17.40	7.96	4.16	29.52	40.00	-10.48	QP	VERTICAL
3	103.08	18.74	11.75	4.32	34.81	43.50	-8.69	QP	VERTICAL
4	115.73	25.46	10.24	4.40	40.10	43.50	-3.40	QP	VERTICAL
5	191.75	19.58	9.91	4.85	34.34	43.50	-9.16	QP	VERTICAL
6	365.54	12.25	15.11	5.66	33.02	46.00	-12.98	QP	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	: /
Power Supply	: DC 3.3V	**Test Mode**	: Tx Mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 VULB9163/3m/HORIZONTAL
Memo	:		

Data: 20



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	119.44	22.40	9.42	4.41	36.23	43.50	-7.27	QP	HORIZONTAL
2	199.99	17.52	10.30	4.90	32.72	43.50	-10.78	QP	HORIZONTAL
3	250.30	18.82	12.30	5.14	36.26	46.00	-9.74	QP	HORIZONTAL
4	300.37	18.01	13.41	5.38	36.80	46.00	-9.20	QP	HORIZONTAL
5	365.54	13.59	15.11	5.66	34.36	46.00	-11.64	QP	HORIZONTAL
6	400.43	17.62	15.71	5.80	39.13	46.00	-6.87	QP	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss.
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

Radiated Emission test (above 1GHz)

Freq (MHz)	Read level (dBμV)	Antenna Factor (dB/m)	PRM Factor (dB)	Cable Loss (dB)	Result Level (dBμV/m)	Limit (dBμ V/m)	Margin (dB)	Detector type	Polarization
11b CH1									
1329.00	49.74	24.73	29.37	4.49	49.59	74.00	-24.41	Peak	VERTICAL
4824.00	33.26	33.73	29.32	8.50	46.17	54.00	-7.83	Average	VERTICAL
4824.00	45.09	33.73	29.32	8.50	58.00	74.00	-16.00	Peak	VERTICAL
7236.00	33.68	36.39	30.52	10.63	50.18	74.00	-23.82	Peak	VERTICAL
1329.00	44.23	24.73	29.37	4.49	44.08	74.00	-29.92	Peak	HORIZONTAL
4824.00	36.60	33.73	29.32	8.50	49.51	54.00	-4.49	Average	HORIZONTAL
4824.00	49.27	33.73	29.32	8.50	62.18	74.00	-11.82	Peak	HORIZONTAL
7236.00	36.28	36.39	30.52	10.63	52.78	74.00	-21.22	Peak	HORIZONTAL
11b CH6									
1322.00	44.36	24.70	29.37	4.49	44.18	74.00	-29.82	Peak	HORIZONTAL
4874.00	36.07	33.72	29.33	8.56	49.02	54.00	-4.98	Average	HORIZONTAL
4874.00	51.23	33.72	29.33	8.56	64.18	74.00	-9.82	Peak	HORIZONTAL
7311.00	37.86	36.45	30.57	10.69	54.43	74.00	-19.57	Peak	HORIZONTAL
1329.00	52.05	24.73	29.37	4.49	51.90	74.00	-22.10	Peak	VERTICAL
4874.00	33.27	33.72	29.33	8.56	46.22	54.00	-7.78	Average	VERTICAL
4874.00	44.33	33.72	29.33	8.56	57.28	74.00	-16.72	Peak	VERTICAL
7311.00	36.49	36.45	30.57	10.69	53.06	74.00	-20.94	Peak	VERTICAL
11b CH11									
1329.00	51.82	24.73	29.37	4.49	51.67	74.00	-22.33	Peak	VERTICAL
4924.00	33.00	33.71	29.34	8.60	45.97	54.00	-8.03	Average	VERTICAL
4924.00	44.33	33.71	29.34	8.60	57.30	74.00	-16.70	Peak	VERTICAL
7386.00	36.64	36.51	30.65	10.75	53.25	74.00	-20.75	Peak	VERTICAL
1329.00	44.82	24.73	29.37	4.49	44.67	74.00	-29.33	Peak	HORIZONTAL
4924.00	36.98	33.71	29.34	8.60	49.95	54.00	-4.05	Average	HORIZONTAL
4924.00	53.81	33.71	29.34	8.60	66.78	74.00	-7.22	Peak	HORIZONTAL
7386.00	39.46	36.51	30.65	10.75	56.07	74.00	-17.93	Peak	HORIZONTAL

Note: 1.30MHz~18GHz: (Scan with 11b, 11g and 11n HT20, the worst case is 11b Mode)

2. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

9. Band Edge Compliance

9.1. Block diagram of test setup



9.2. Limit

All restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with RSS-Gen Issue 3 clause 7.2.5 (Same as FCC 15.209) limits.

9.3. Test Procedure

Same with clause 8.3 except change investigated frequency range from 2100MHz to 2450MHz and 2450MHz to 2500MHz.

Remark: All restriction band have been tested, and only the worse case is shown in report.

9.4. Test result

PASS. (See below detailed test result)

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11b CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 3



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2375.16	42.62	29.72	29.38	6.01	48.97	74.00	-25.03	Peak	VERTICAL
2	2390.00	44.58	29.78	29.41	6.01	50.96	74.00	-23.04	Peak	VERTICAL
3	2400.00	41.09	29.82	29.44	6.03	47.50	54.00	-6.50	Average	VERTICAL
4	2400.00	59.08	29.82	29.44	6.03	65.49	74.00	-8.51	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11b CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 4



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2340.00	40.90	29.58	29.32	5.96	47.12	74.00	-26.88	Peak	HORIZONTAL
2	2390.00	46.62	29.78	29.41	6.01	53.00	74.00	-21.00	Peak	HORIZONTAL
3	2400.00	44.48	29.82	29.44	6.03	50.89	54.00	-3.11	Average	HORIZONTAL
4	2400.00	64.11	29.82	29.44	6.03	70.52	74.00	-3.48	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11b CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 9



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	40.59	30.14	29.71	6.15	47.17	54.00	-6.83	Average	HORIZONTAL
2	2483.50	57.39	30.14	29.71	6.15	63.97	74.00	-10.03	Peak	HORIZONTAL
3	2487.90	41.00	30.15	29.71	6.15	47.59	54.00	-6.41	Average	HORIZONTAL
4	2487.90	57.37	30.15	29.71	6.15	63.96	74.00	-10.04	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11b CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 10



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	30.64	30.14	29.71	6.15	37.22	54.00	-16.78	Average	VERTICAL
2	2483.50	47.72	30.14	29.71	6.15	54.30	74.00	-19.70	Peak	VERTICAL
3	2488.25	30.97	30.16	29.71	6.15	37.57	54.00	-16.43	Average	VERTICAL
4	2488.25	49.36	30.16	29.71	6.15	55.96	74.00	-18.04	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11g CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 11



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	42.94	30.14	29.71	6.15	49.52	74.00	-24.48	Peak	HORIZONTAL
2	2498.40	41.39	30.19	29.75	6.15	47.98	74.00	-26.02	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11g CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 12



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	39.13	30.14	29.71	6.15	45.71	74.00	-28.29	Peak	VERTICAL
2	2491.15	41.66	30.17	29.73	6.15	48.25	74.00	-25.75	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11g CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 13



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2338.68	42.32	29.57	29.32	5.94	48.51	74.00	-25.49	Peak	VERTICAL
2	2390.00	46.30	29.78	29.41	6.01	52.68	74.00	-21.32	Peak	VERTICAL
3	2396.64	34.26	29.80	29.42	6.03	40.67	54.00	-13.33	Average	VERTICAL
4	2396.64	48.44	29.80	29.42	6.03	54.85	74.00	-19.15	Peak	VERTICAL
5	2400.00	44.20	29.82	29.44	6.03	50.61	74.00	-23.39	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11g CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 14



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2375.04	44.89	29.72	29.38	5.98	51.21	74.00	-22.79	Peak	HORIZONTAL
2	2390.00	41.81	29.78	29.41	6.01	48.19	74.00	-25.81	Peak	HORIZONTAL
3	2400.00	46.88	29.82	29.44	6.03	53.29	74.00	-20.71	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11n HT20 CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 15



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2385.48	46.37	29.76	29.41	6.01	52.73	74.00	-21.27	Peak	HORIZONTAL
2	2390.00	44.02	29.78	29.41	6.01	50.40	74.00	-23.60	Peak	HORIZONTAL
3	2400.00	33.90	29.82	29.44	6.03	40.31	54.00	-13.69	Average	HORIZONTAL
4	2400.00	52.22	29.82	29.44	6.03	58.63	74.00	-15.37	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11n HT20 CH1
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 16



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2349.00	41.01	29.61	29.33	5.96	47.25	74.00	-26.75	Peak	VERTICAL
2	2390.00	44.75	29.78	29.41	6.01	51.13	74.00	-22.87	Peak	VERTICAL
3	2400.00	46.61	29.82	29.44	6.03	53.02	74.00	-20.98	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11n HT20 CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/VERTICAL
Memo	:		

Data: 17



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	39.79	30.14	29.71	6.15	46.37	74.00	-27.63	Peak	VERTICAL
2	2496.75	43.49	30.19	29.75	6.15	50.08	74.00	-23.92	Peak	VERTICAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Site	: DDT 3m Chamber	D:\2016 Report Data\16Q0719-5\RE.EM6	
Test Date	: 2016-07-29	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: DC 3.3V	**Test Mode**	: 11n HT20 CH11
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**Antenna/Distance**	: 2015 HF907/3m/HORIZONTAL
Memo	:		

Data: 18



Item (Mark)	Freq (MHz)	Read Level (dBµV)	Antenna Factor (dB/m)	PRM Factor dB	Cable Loss dB	Result Level (dBµV/m)	Limit Line (dBµV/m)	Over Limit (dB)	Detector	Polarization
1	2483.50	41.99	30.14	29.71	6.15	48.57	74.00	-25.43	Peak	HORIZONTAL
2	2496.20	44.51	30.19	29.73	6.15	51.12	74.00	-22.88	Peak	HORIZONTAL

Note: 1. Result Level = Read Level + Antenna Factor + Cable loss - PRM Factor.
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

10. Power Line Conducted Emission

10.1. Block diagram of test setup



10.2. Power Line Conducted Emission Limits(Class B)

Frequency	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Note 1: * Decreasing linearly with logarithm of frequency.

Note 2: The lower limit shall apply at the transition frequencies.

10.3. Test Procedure

The EUT and Support equipment, if needed, were put placed on a non-metallic table, 80cm above the ground plane.

All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4.

All support equipment power received from a second LISN.

Emissions were measured on each current carrying line of the EUT using an EMI Test Receiver connected to the LISN powering the EUT.

The Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.

During the above scans, the emissions were maximized by cable manipulation.

After the preliminary scan, we found the test mode producing the highest emission level.

The EUT configuration and worse cable configuration of the above highest emission levels were recorded for reference of the final test.

EUT and support equipment were set up on the test bench as per the configuration with highest emission

level in the preliminary test.

A scan was taken on both power lines, Neutral and Line, recording at least the six highest emissions.

Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit.

The test data of the worst-case condition(s) was recorded.

The bandwidth of test receiver is set at 9 KHz.

10.4. Test Result

PASS. (See below detailed test result)

Note1: All emissions not reported below are too low against the prescribed limits.
Note2: "-----" means peak detection; "-----" mans average detection

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2016 report data\16Q0719-5\CE.EM6	
Test Date	: 2016-08-02	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx Mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**LISN**	: 2015 ENV216/NEUTRAL
Memo	:		

Data: 2



Item (Mark)	Freq (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.22	20.57	9.61	0.02	9.86	40.06	52.83	-12.77	Average	NEUTRAL
2	0.22	28.97	9.61	0.02	9.86	48.46	62.83	-14.37	QP	NEUTRAL
3	0.31	17.27	9.61	0.02	9.86	36.76	50.06	-13.30	Average	NEUTRAL
4	0.31	22.41	9.61	0.02	9.86	41.90	60.06	-18.16	QP	NEUTRAL
5	0.61	15.47	9.61	0.03	9.86	34.97	46.00	-11.03	Average	NEUTRAL
6	0.61	19.68	9.61	0.03	9.86	39.18	56.00	-16.82	QP	NEUTRAL

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

TR-4-E-010 Conducted Emission Test Result

Test Site	: DDT 1# Shield Room	E:\2016 report data\16Q0719-5\CE.EM6	
Test Date	: 2016-08-02	**Tested By**	: Toby
EUT	: GC-WIFI300-SMT-01	**Model Number**	:
Power Supply	: AC 120V/60Hz	**Test Mode**	: Tx Mode
Condition	: Temp:24.5'C,Humi:55%, Press:100.1kPa	**LISN**	: 2015 ENV216/LINE
Memo	:		

Data: 4



Item (Mark)	Freq (MHz)	Read Level (dBµV)	LISN Factor (dB)	Cable Loss (dB)	Pulse Limiter Factor (dB)	Result Level (dBµV)	Limit Line (dBµV)	Over Limit (dB)	Detector	Phase
1	0.20	17.66	9.61	0.02	9.86	37.15	53.71	-16.56	Average	LINE
2	0.20	29.66	9.61	0.02	9.86	49.15	63.71	-14.56	QP	LINE
3	0.22	19.99	9.61	0.02	9.86	39.48	52.79	-13.31	Average	LINE
4	0.22	31.40	9.61	0.02	9.86	50.89	62.79	-11.90	QP	LINE
5	0.30	17.95	9.61	0.02	9.86	37.44	50.15	-12.71	Average	LINE
6	0.30	21.95	9.61	0.02	9.86	41.44	60.15	-18.71	QP	LINE

Note: 1. Result Level = Read Level +LISN Factor + Pulse Limiter Factor + Cable loss.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz—150 kHz), 9 kHz (150 kHz—30 MHz).
4. Step size: 80Hz (0.009MHz-0.15MHz), 4 kHz (0.15MHz-30MHz), Scan time: auto.

11. Antenna Requirements

11.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

11.2. Result

The antennas used for this product are integral antenna , PCB antenna and external antenna with reversed polarity antenna port .

12. Test setup photograph





13. Photos of the EUT







Ant.1





Ant.2



Ant.2





END OF REPORT