



# **FCC TEST REPORT**

## **FCC PART 15 SUBPART C 15.249**

**Test report**  
**On Behalf of**  
**King-Sound Electronic & Technology Co., Ltd.**  
**For**  
**Foldable Rubberized Wireless Headphones**

**Model No.: MI-BTH16**

**FCC ID: 2AFCE-MI-BTH16**

**Prepared for :** King-Sound Electronic & Technology Co., Ltd.  
No.2, XianShuiHu Road, ShiJin, PinShan, ShenZhen, China.

**Prepared By :** Shenzhen HUAKE Testing Technology Co., Ltd.  
1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park, Fuhai  
Street, Bao'an District, Shenzhen City, China

**Date of Test:** Oct. 18, 2018 ~ Nov. 02, 2018  
**Date of Report:** Nov. 08, 2018  
**Report Number:** HK1809271169E



## TEST RESULT CERTIFICATION

**Applicant's name** ..... King-Sound Electronic & Technology Co., Ltd.  
**Address** ..... No.2, XianShuiHu Road, ShiJin, PinShan, ShenZhen, China.  
**Manufacture's Name** ..... King-Sound Electronic & Technology Co., Ltd.  
**Address** ..... No.2, XianShuiHu Road, ShiJin, PinShan, ShenZhen, China.  
**Factory's Name** ..... King-Sound Electronic & Technology Co., Ltd.  
**Address** ..... No.2, XianShuiHu Road, ShiJin, PinShan, ShenZhen, China.

### Product description

**Trade Mark:** ..... MERKURY  
**Product name** ..... Foldable Rubberized Wireless Headphones  
**Model and/or type reference** ... MI-BTH16  
**Standards** ..... FCC Rules and Regulations Part 15 Subpart C Section 15.249  
ANSI C63.10: 2013

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen HUAKE Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen HUAKE Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Date of Test** ..... :  
**Date (s) of performance of tests** ..... : Oct. 18, 2018 ~ Nov. 02, 2018  
**Date of Issue** ..... : Nov. 07, 2018  
**Test Result** ..... : **Pass**

Testing Engineer :

(Gary Qian)

Technical Manager :

(Eden Hu)

Authorized Signatory :

(Jason Zhou)



| <b>Table of Contents</b>                                   | <b>Page</b> |
|------------------------------------------------------------|-------------|
| 1 . TEST SUMMARY                                           | 4           |
| 2 . GENERAL INFORMATION                                    | 5           |
| 2.1 GENERAL DESCRIPTION OF EUT                             | 5           |
| 2.2 OPERATION OF EUT DURING TESTING                        | 6           |
| 2.3 DESCRIPTION OF TEST SETUP                              | 7           |
| 2.4 MEASUREMENT INSTRUMENTS LIST                           | 8           |
| 3. RADIATED EMISSION                                       | 9           |
| 3.1. MEASUREMENT PROCEDURE                                 | 9           |
| 3.2. TEST SETUP                                            | 11          |
| 3.3. TEST RESULT                                           | 12          |
| 4. BAND EDGE EMISSION                                      | 18          |
| 4.1. MEASUREMENT PROCEDURE                                 | 18          |
| 4.2 TEST SETUP                                             | 18          |
| 4.3 RADIATED TEST RESULT                                   | 19          |
| 5. BANDWIDTH                                               | 23          |
| 5.1. MEASUREMENT PROCEDURE                                 | 23          |
| 5.2. TEST SETUP                                            | 23          |
| 5.3. TEST RESULT                                           | 24          |
| 6. FCC LINE CONDUCTED EMISSION TEST                        | 28          |
| 6.1. LIMITS OF LINE CONDUCTED EMISSION TEST                | 28          |
| 6.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST         | 28          |
| 6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST | 29          |
| 6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST       | 29          |
| 6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST           | 30          |
| APPENDIX A: PHOTOGRAPHS OF TEST SETUP                      | 32          |
| APPENDIX B: PHOTOGRAPHS OF EUT                             | 35          |



## 1. TEST SUMMARY

### 1.1 TEST PROCEDURES AND RESULTS

| FCC RULES      | DESCRIPTION OF TEST | RESULT    |
|----------------|---------------------|-----------|
| §15.249&15.209 | Radiated Emission   | Compliant |
| §15.249&15.209 | Band Edges Emission | Compliant |
| §15.215        | 20dB bandwidth      | Compliant |
| §15.207        | Conducted Emission  | Compliant |

### 1.2 TEST FACILITY

Test Firm : Shenzhen HUAKE Testing Technology Co., Ltd.

Address : 1F, B2 Building, Junfeng Zhongcheng Zhizao Innovation Park,  
Fuhai Street, Bao'an District, Shenzhen City, China

Designation Number: : CN1229

Test Firm Registration Number : 616276

### 1.3 MEASUREMENT UNCERTAINTY

Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty(9kHz-30MHz) = 3.08dB, k=2

Radiated emission expanded uncertainty(30MHz-1000MHz) = 4.42dB, k=2

Radiated emission expanded uncertainty(Above 1GHz) = 4.06dB, k=2



## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                        |                                              |
|------------------------|----------------------------------------------|
| Operation Frequency    | 2.402 GHz to 2.480GHz                        |
| Maximum field strength | 91.86dBuV/m(AV)@3m                           |
| Bluetooth Version      | V4.2                                         |
| Modulation             | GFSK, $\pi/4$ -DQPSK for BR/EDR              |
| Number of channels     | 79 for BR/EDR                                |
| Antenna Gain           | -58dBi                                       |
| Antenna Designation    | PCB Antenna (Met 15.203 Antenna requirement) |
| Hardware Version       | 1.0                                          |
| Software Version       | 1.0                                          |
| Power Supply           | DC 3.7V by adapter                           |

BR/EDR channel List

| Frequency Band | Channel Number | Frequency |
|----------------|----------------|-----------|
| 2400~2483.5MHZ | 0              | 2402MHZ   |
|                | 1              | 2403MHZ   |
|                | :              | :         |
|                | 38             | 2440 MHZ  |
|                | 39             | 2441 MHZ  |
|                | 40             | 2442 MHZ  |
|                | :              | :         |
|                | 77             | 2479 MHZ  |
|                | 78             | 2480 MHZ  |



## 2.2 OPERATION OF EUT DURING TESTING

| NO. | TEST MODE DESCRIPTION         |
|-----|-------------------------------|
| 1   | Low channel GFSK              |
| 2   | Middle channel GFSK           |
| 3   | High channel GFSK             |
| 4   | Low channel $\pi/4$ -DQPSK    |
| 5   | Middle channel $\pi/4$ -DQPSK |
| 6   | High channel $\pi/4$ -DQPSK   |


Note:

1. Only the data of the worst case recorded in the test report.
2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.




## 2.3 DESCRIPTION OF TEST SETUP

Configure 1: (Normal hopping)



**Note:** Owing to the EUT has own battery, and testing may be performed while adapter or PC removed.

Configure 2: (Control continuous TX)



## 2.4. EQUIPMENT USED IN EUT SYSTEM

| Item | Equipment               | Mfr/Brand | Model/Type No.  | Remark    |
|------|-------------------------|-----------|-----------------|-----------|
| 1    | Wireless Speaker Bottle | HONGLIANG | HL8478          | EUT       |
| 2    | Battery                 | DL        | 502030          | Accessory |
| 3    | PC                      | APPLE     | A1465           | A.E       |
|      | IPOD                    | APPLE     | A1367           | A.E       |
| 4    | Control box             | GZUT      | N/A             | A.E       |
| 5    | Adapter                 | IPRO      | NTR-S01         | A.E       |
| 6    | USB Cable               | N/A       | 1.0m unshielded | A.E       |



## 2.5. MEASUREMENT INSTRUMENTS LIST

### TEST EQUIPMENT OF CONDUCTED EMISSION TEST

| Item | Equipment                               | Manufacturer | Model No. | Serial No. | Last Cal.     | Cal. Interval |
|------|-----------------------------------------|--------------|-----------|------------|---------------|---------------|
| 1.   | L.I.S.N.<br>Artificial Mains<br>Network | R&S          | ENV216    | HKE-002    | Dec. 28, 2017 | 1 Year        |
| 2.   | Receiver                                | R&S          | ESCI 7    | HKE-010    | Dec. 28, 2017 | 1 Year        |

### TEST EQUIPMENT OF RADIATED EMISSION TEST

| Item | Equipment                | Manufacturer    | Model No.    | Lab Equipment No. | Last Cal.     | Cal. Interval |
|------|--------------------------|-----------------|--------------|-------------------|---------------|---------------|
| 1.   | Spectrum analyzer        | Agilent         | N9020A       | HKE-048           | Dec. 28, 2017 | 1 Year        |
| 2.   | Preamplifier             | Schwarzbeck     | BBV 9743     | HKE-006           | Dec. 28, 2017 | 1 Year        |
| 3.   | EMI Test Receiver        | Rohde & Schwarz | ESCI 7       | HKE-010           | Dec. 28, 2017 | 1 Year        |
| 4.   | Bilog Broadband Antenna  | Schwarzbeck     | VULB9163     | HKE-012           | Dec. 28, 2017 | 1 Year        |
| 5.   | Loop Antenna             | Schwarzbeck     | FMZB 1519 B  | HKE-014           | Dec. 28, 2017 | 1 Year        |
| 6.   | Horn Antenna             | Schwarzbeck     | 9120D        | HKE-013           | Dec. 28, 2017 | 1 Year        |
| 7.   | Broad-band Horn Antenna  | A-INFOMW        | LB-180400-KF | HKE-031           | Dec. 28, 2017 | 1 Year        |
| 8.   | Pre-amplifier            | EMCI            | EMC051845SE  | HKE-015           | Dec. 28, 2017 | 1 Year        |
| 9.   | Pre-amplifier            | Agilent         | 83051A       | HKE-016           | Dec. 28, 2017 | 1 Year        |
| 10.  | Filter<br>(2.4-2.483GHz) | Micro-tronics   | 087          | --                | N/A           | N/A           |
| 11.  | Radiation Cable 1        | MXT             | HK1          | R05               | N/A           | N/A           |
| 12.  | Radiation Cable 2        | MXT             | HK1          | R06               | N/A           | N/A           |



### 3. RADIATED EMISSION

#### 3.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 0.8 or 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer. Place the measurement antenna away from each area of the EUT determined to be a source of emissions at the specified measurement distance, while keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response. The measurement antenna may have to be higher or lower than the EUT, depending on the radiation pattern of the emission and staying aimed at the emission source for receiving the maximum signal. The final measurement antenna elevation shall be that which maximizes the emissions. The measurement antenna elevation for maximum emissions shall be restricted to a range of heights of from 1 m to 4 m above the ground or reference ground plane.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum values.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High - Low scan is not required in this case.



The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter    | Setting                                                       |
|-----------------------|---------------------------------------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RBW 200Hz for QP                                  |
| Start ~Stop Frequency | 150KHz~30MHz/RBW 9KHz for QP                                  |
| Start ~Stop Frequency | 30MHz~1000MHz/RBW 120KHz for QP                               |
| Start ~Stop Frequency | 1GHz~26.5GHz<br>1.5MHz/5MHz for Peak, 1.5MHz/10Hz for Average |

| Receiver Parameter    | Setting                         |
|-----------------------|---------------------------------|
| Start ~Stop Frequency | 9KHz~150KHz/RBW 200Hz for QP    |
| Start ~Stop Frequency | 150KHz~30MHz/RBW 9KHz for QP    |
| Start ~Stop Frequency | 30MHz~1000MHz/RBW 120KHz for QP |

#### Test limit for Standard FCC15.249

| Fundamental Frequency | Field Strength of Fundamental<br>(millivolts/meter) | Field Strength of Harmonics<br>(microvolts/meter) |
|-----------------------|-----------------------------------------------------|---------------------------------------------------|
| 900-928MHz            | 50                                                  | 500                                               |
| 2400-2483.5MHz        | 50                                                  | 500                                               |
| 5725-5875MHz          | 50                                                  | 500                                               |
| 24.0-24.25GHz         | 250                                                 | 2500                                              |

#### Test limit for Standard FCC 15.209


| Frequency<br>(MHz) | Distance<br>Meters | Field Strengths Limit                                           |                |
|--------------------|--------------------|-----------------------------------------------------------------|----------------|
|                    |                    | $\mu$ V/m                                                       | dB( $\mu$ V)/m |
| 0.009 ~ 0.490      | 300                | 2400/F(kHz)                                                     | ---            |
| 0.490 ~ 1.705      | 30                 | 24000/F(kHz)                                                    | ---            |
| 1.705 ~ 30         | 30                 | 30                                                              | ---            |
| 30 ~ 88            | 3                  | 100                                                             | 40.0           |
| 88 ~ 216           | 3                  | 150                                                             | 43.5           |
| 216 ~ 960          | 3                  | 200                                                             | 46.0           |
| 960 ~ 1000         | 3                  | 500                                                             | 54.0           |
| Above 1000         | 3                  | Other: 74.0 dB( $\mu$ V)/m (Peak) 54.0 dB( $\mu$ V)/m (Average) |                |

Remark:


- (1) Emission level  $\text{dB}\mu\text{V} = 20 \log \text{Emission level } \mu\text{V/m}$
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.

### 3.2. TEST SETUP


Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz



RADIATED EMISSION TEST SETUP ABOVE 1000MHz






### 3.3. TEST RESULT

#### RADIATED EMISSION BELOW 30MHZ

No emission found between lowest internal used/generated frequencies to 30MHz.

#### RADIATED EMISSION 30MHz- 1GHZ FOR BR/EDR

|               |                                         |                     |            |
|---------------|-----------------------------------------|---------------------|------------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16   |
| Temperature : | 20 °C                                   | Relative Humidity : | 48%        |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V    |
| Test Mode :   | Mode 1                                  | Polarization :      | Horizontal |




#### Suspected Data List

| NO. | Freq.<br>[MHz] | Level<br>[dBμV/m] | Factor<br>[dB] | Limit<br>[dBμV/m] | Margin<br>[dB] | Height<br>[cm] | Angle<br>[°] | Polarity |
|-----|----------------|-------------------|----------------|-------------------|----------------|----------------|--------------|----------|
| 1   | 30.0000        | 25.55             | 12.59          | 40.00             | 14.45          | 100            | 45           | Vertical |
| 2   | 49.4000        | 20.92             | 14.36          | 40.00             | 19.08          | 200            | 179          | Vertical |
| 3   | 72.6800        | 21.49             | 11.27          | 40.00             | 18.51          | 150            | 187          | Vertical |
| 4   | 155.130        | 21.81             | 14.26          | 43.50             | 21.69          | 100            | 97           | Vertical |
| 5   | 384.050        | 25.33             | 18.06          | 46.00             | 20.67          | 150            | 227          | Vertical |
| 6   | 641.100        | 31.23             | 23.54          | 46.00             | 14.77          | 150            | 278          | Vertical |



|               |                                         |                     |          |
|---------------|-----------------------------------------|---------------------|----------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16 |
| Temperature : | 20 °C                                   | Relative Humidity : | 48%      |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V  |
| Test Mode :   | Mode 1                                  | Polarization :      | Vertical |



| Suspected Data List |             |                |             |                |             |             |           |            |
|---------------------|-------------|----------------|-------------|----------------|-------------|-------------|-----------|------------|
| NO.                 | Freq. [MHz] | Level [dBμV/m] | Factor [dB] | Limit [dBμV/m] | Margin [dB] | Height [cm] | Angle [°] | Polarity   |
| 1                   | 37.7600     | 20.08          | 14.11       | 40.00          | 19.92       | 150         | 63        | Horizontal |
| 2                   | 55.2200     | 20.54          | 13.92       | 40.00          | 19.46       | 200         | 166       | Horizontal |
| 3                   | 119.240     | 21.64          | 12.82       | 43.50          | 21.86       | 150         | 176       | Horizontal |
| 4                   | 164.830     | 23.30          | 13.78       | 43.50          | 20.20       | 200         | 111       | Horizontal |
| 5                   | 384.050     | 24.10          | 18.06       | 46.00          | 21.90       | 100         | 358       | Horizontal |
| 6                   | 683.780     | 31.00          | 24.19       | 46.00          | 15.00       | 100         | 62        | Horizontal |

## RESULT: PASS

### Note:

Factor=Antenna Factor + Cable loss, Margin=Result-Limit.

The “Factor” value can be calculated automatically by software of measurement system.

The mode 1 is the worst case, and only the data of the worst case recorded in this test report.

## FIELD STRENGTH OF FUNDAMENTAL FOR BR/EDR

|                   |                                         |                     |            |
|-------------------|-----------------------------------------|---------------------|------------|
| EUT :             | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16   |
| Temperature :     | 20 °C                                   | Relative Humidity : | 48%        |
| Pressure :        | 1010 hPa                                | Test Voltage :      | DC 3.7V    |
| Test Modulation : | GFSK                                    | Polarization :      | Horizontal |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 2402.021                                              | 78.40         | 13.46  | 91.86          | 114      | -22.14 | peak       |
| 2402.021                                              | 71.36         | 13.46  | 84.82          | 94       | -9.18  | AVG        |
| 2441.021                                              | 77.40         | 13.88  | 91.28          | 114      | -22.72 | peak       |
| 2441.021                                              | 70.41         | 13.88  | 84.29          | 94       | -9.71  | AVG        |
| 2480.021                                              | 76.59         | 14.11  | 90.70          | 114      | -23.30 | peak       |
| 2480.021                                              | 69.77         | 14.11  | 83.88          | 94       | -10.12 | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |

|                   |                                         |                     |          |
|-------------------|-----------------------------------------|---------------------|----------|
| EUT :             | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16 |
| Temperature :     | 20 °C                                   | Relative Humidity : | 48%      |
| Pressure :        | 1010 hPa                                | Test Voltage :      | DC 3.7V  |
| Test Modulation : | GFSK                                    | Polarization :      | Vertical |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 2402.021                                              | 78.19         | 13.46  | 91.65          | 114      | -22.35 | peak       |
| 2402.021                                              | 71.12         | 13.46  | 84.58          | 94       | -9.42  | AVG        |
| 2441.021                                              | 77.05         | 13.88  | 90.93          | 114      | -23.07 | peak       |
| 2441.021                                              | 70.21         | 13.88  | 84.09          | 94       | -9.91  | AVG        |
| 2480.021                                              | 76.30         | 14.11  | 90.41          | 114      | -23.59 | peak       |
| 2480.021                                              | 69.48         | 14.11  | 83.59          | 94       | -10.41 | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |



## RADIATED EMISSION ABOVE 1GHZ FOR BR/EDR

|               |                                         |                     |            |
|---------------|-----------------------------------------|---------------------|------------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16   |
| Temperature : | 20 ℃                                    | Relative Humidity : | 48%        |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V    |
| Test Mode :   | Mode 1                                  | Polarization :      | Horizontal |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 4804.042                                              | 42.39         | 7.12   | 49.51          | 74       | -24.49 | peak       |
| 4804.042                                              | 39.25         | 7.12   | 46.37          | 54       | -7.63  | AVG        |
| 7206.063                                              | 38.46         | 9.84   | 48.3           | 74       | -25.7  | peak       |
| 7206.063                                              | 37.22         | 9.84   | 47.06          | 54       | -6.94  | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |

|               |                                         |                     |          |
|---------------|-----------------------------------------|---------------------|----------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16 |
| Temperature : | 20 ℃                                    | Relative Humidity : | 48%      |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V  |
| Test Mode :   | Mode 1                                  | Polarization :      | Vertical |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 4804.042                                              | 41.26         | 7.12   | 48.38          | 74       | -25.62 | peak       |
| 4804.042                                              | 39.33         | 7.12   | 46.45          | 54       | -7.55  | AVG        |
| 7206.063                                              | 38.31         | 9.84   | 48.15          | 74       | -25.85 | peak       |
| 7206.063                                              | 37.54         | 9.84   | 47.38          | 54       | -6.62  | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |



|               |                                         |                     |            |
|---------------|-----------------------------------------|---------------------|------------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16   |
| Temperature : | 20 °C                                   | Relative Humidity : | 48%        |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V    |
| Test Mode :   | Mode 2                                  | Polarization :      | Horizontal |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 4804.042                                              | 42.34         | 7.12   | 49.46          | 74       | -24.54 | peak       |
| 4804.042                                              | 38.74         | 7.12   | 45.86          | 54       | -8.14  | AVG        |
| 7206.063                                              | 38.93         | 9.84   | 48.77          | 74       | -25.23 | peak       |
| 7206.063                                              | 38.26         | 9.84   | 48.1           | 54       | -5.9   | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |

|               |                                         |                     |          |
|---------------|-----------------------------------------|---------------------|----------|
| EUT :         | Foldable Rubberized Wireless Headphones | Model Name. :       | MI-BTH16 |
| Temperature : | 20 °C                                   | Relative Humidity : | 48%      |
| Pressure :    | 1010 hPa                                | Test Voltage :      | DC 3.7V  |
| Test Mode :   | Mode 2                                  | Polarization :      | Vertical |

| Frequency                                             | Meter Reading | Factor | Emission Level | Limits   | Margin | Value Type |
|-------------------------------------------------------|---------------|--------|----------------|----------|--------|------------|
| (MHz)                                                 | (dBμV)        | (dB)   | (dBμV/m)       | (dBμV/m) | (dB)   |            |
| 4804.042                                              | 39.76         | 7.12   | 46.88          | 74       | -27.12 | peak       |
| 4804.042                                              | 38.64         | 7.12   | 45.76          | 54       | -8.24  | AVG        |
| 7206.063                                              | 38.22         | 9.84   | 48.06          | 74       | -25.94 | peak       |
| 7206.063                                              | 35.04         | 9.84   | 44.88          | 54       | -9.12  | AVG        |
| Remark:                                               |               |        |                |          |        |            |
| Factor = Antenna Factor + Cable Loss – Pre-amplifier. |               |        |                |          |        |            |

**Note:** Other emissions from 8G to 25 GHz are considered as ambient noise. No recording in the test report.  
Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.  
The “Factor” value can be calculated automatically by software of measurement system.  
The GFSK modulation was the worst case and only the data of worst recorded in this report.


## 4. BAND EDGE EMISSION

### 4.1. MEASUREMENT PROCEDURE

1. The EUT operates at transmitting mode. The operate channel is tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
2. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission: (a) PEAK: RBW=1MHz, VBW=3MHz , Sweep=AUTO  
(b) AVERAGE: RBW=1MHz ; VBW=1/on time(1kHz), Sweep=AUTO
3. Other procedures refer to clause 3.1.

### 4.2 TEST SETUP

RADIATED EMISSION TEST SETUP






### 4.3 RADIATED TEST RESULT

FOR BR/EDR

(Worst modulation: GFSK)


TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
|     |    | MHz      | dBuV    | dBuV/m | dBuV/m      | dBuV/m | dB     |          | cm             | degree       |         |
| 1   |    | 2371.858 | 24.26   | 13.46  | 37.72       | 74.00  | -36.28 | peak     |                |              |         |
| 2   |    | 2390.000 | 27.67   | 13.46  | 41.13       | 74.00  | -32.87 | peak     |                |              |         |
| 3   |    | 2400.000 | 39.44   | 13.46  | 52.90       | 74.00  | -21.10 | peak     |                |              |         |
| 4   | X  | 2402.000 | 82.09   | 13.46  | 95.55       | 74.00  | 21.55  | peak     |                |              |         |
| 5   | *  | 2402.000 | 74.11   | 13.46  | 87.57       | 54.00  | 33.57  | AVG      | 100            | 141          |         |



## TEST PLOT OF BAND EDGE FOR LOW CHANNEL –Vertical



| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
|     |    | MHz      | dBuV    | dBuV/m | dBuV/m      | dBuV/m | dB     |          | cm             | degree       |         |
| 1   |    | 2368.100 | 24.89   | 13.46  | 38.35       | 74.00  | -35.65 | peak     |                |              |         |
| 2   |    | 2390.000 | 28.17   | 13.46  | 41.63       | 74.00  | -32.37 | peak     |                |              |         |
| 3   |    | 2400.000 | 37.44   | 13.46  | 50.90       | 74.00  | -23.10 | peak     |                |              |         |
| 4   | X  | 2402.000 | 81.59   | 13.46  | 95.05       | 74.00  | 21.05  | peak     |                |              |         |
| 5   | *  | 2402.000 | 73.66   | 13.46  | 87.12       | 54.00  | 33.12  | AVG      | 100            | 246          |         |



## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL –Horizontal


106.0 dBuV/m



| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
|     |    | MHz      | dBuV    | dBuV/m | dBuV/m      | dBuV/m | dB     |          | cm             | degree       |         |
| 1   | X  | 2480.000 | 77.78   | 14.11  | 91.89       | 74.00  | 17.89  | peak     |                |              |         |
| 2   | *  | 2480.000 | 69.64   | 14.11  | 83.75       | 54.00  | 29.75  | AVG      | 100            | 145          |         |
| 3   |    | 2483.500 | 25.66   | 14.13  | 39.79       | 74.00  | -34.21 | peak     |                |              |         |
| 4   |    | 2484.967 | 24.26   | 14.14  | 38.40       | 74.00  | -35.60 | peak     |                |              |         |



## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



| No. | Mk | Freq.    | Reading | Factor | Measurement | Limit  | Over   | Detector | Antenna Height | Table Degree | Comment |
|-----|----|----------|---------|--------|-------------|--------|--------|----------|----------------|--------------|---------|
|     |    | MHz      | dBuV    | dBuV/m | dBuV/m      | dBuV/m | dB     |          | cm             | degree       |         |
| 1   | X  | 2480.000 | 77.17   | 14.11  | 91.28       | 74.00  | 17.28  | peak     |                |              |         |
| 2   | *  | 2480.000 | 69.13   | 14.11  | 83.24       | 54.00  | 29.24  | AVG      | 100            | 221          |         |
| 3   |    | 2483.500 | 22.72   | 14.13  | 36.85       | 74.00  | -37.15 | peak     |                |              |         |
| 4   |    | 2485.517 | 22.53   | 14.14  | 36.67       | 74.00  | -37.33 | peak     |                |              |         |

**RESULT: PASS**

**Note:** Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.




## 5. BANDWIDTH

### 5.1. MEASUREMENT PROCEDURE

1. The EUT was placed on the top of the turntable 1.5 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Set the EUT Work on the operation frequency individually.
3. Set Span = approximately 2 to 5 times the OBW, centered on a hopping channel  
The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately 3\* RBW; Sweep = auto; Detector function = peak
4. Set SPA Trace 1 Max hold, then View.

### 5.2. TEST SETUP






### 5.3. TEST RESULT

|                 |                 |
|-----------------|-----------------|
| TEST ITEM       | 20DB BANDWIDTH  |
| TEST MODULATION | GFSK for BR/EDR |


| Test Data (MHz) |       | Criteria |
|-----------------|-------|----------|
| Low Channel     | 1.070 | PASS     |
| Middle Channel  | 1.060 | PASS     |
| High Channel    | 1.070 | PASS     |

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL






## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL






|                 |                           |
|-----------------|---------------------------|
| TEST ITEM       | 20DB BANDWIDTH            |
| TEST MODULATION | $\pi$ /4-DQPSK for BR/EDR |


| Test Data (MHz) |       | Criteria |
|-----------------|-------|----------|
| Low Channel     | 1.365 | PASS     |
| Middle Channel  | 1.366 | PASS     |
| High Channel    | 1.353 | PASS     |

TEST PLOT OF BANDWIDTH FOR LOW CHANNEL






## TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



## TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL





## 6. FCC LINE CONDUCTED EMISSION TEST


### 6.1. LIMITS OF LINE CONDUCTED EMISSION TEST

| Frequency     | Maximum RF Line Voltage |                |
|---------------|-------------------------|----------------|
|               | Q.P.( dBuV)             | Average( dBuV) |
| 150kHz~500kHz | 66-56                   | 56-46          |
| 500kHz~5MHz   | 56                      | 46             |
| 5MHz~30MHz    | 60                      | 50             |

Note:

1. The lower limit shall apply at the transition frequency.
2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz.

### 6.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST





### **6.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
2. Support equipment, if needed, was placed as per ANSI C63.10.
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
4. All support equipments received DC 3.7V/60Hz power from a LISN, if any.
5. The EUT received DC 5V power from adapter which received DC 3.7V/60Hz power from a LISN.
6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.
9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.


### **6.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST**

1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less -2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
3. The test data of the worst case condition(s) was reported on the Summary Data page.



## 6.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

### Line Conducted Emission Test Line 1-L



#### Suspected List


| NO. | Freq.<br>[MHz] | Level<br>[dBμV] | Factor<br>[dB] | Limit<br>[dBμV] | Margin<br>[dB] | Detector |
|-----|----------------|-----------------|----------------|-----------------|----------------|----------|
| 1   | 0.2175         | 47.19           | 10.05          | 62.91           | 15.72          | PK       |
| 2   | 0.4380         | 44.56           | 10.05          | 57.10           | 12.54          | PK       |
| 3   | 0.8700         | 41.59           | 10.06          | 56.00           | 14.41          | PK       |
| 4   | 1.0905         | 42.91           | 10.07          | 56.00           | 13.09          | PK       |
| 5   | 2.1795         | 39.49           | 10.16          | 56.00           | 16.51          | PK       |
| 6   | 2.8365         | 38.09           | 10.21          | 56.00           | 17.91          | PK       |

#### Final Data List

| NO. | Freq.<br>[MHz] | Factor<br>[dB] | QP<br>Value<br>[dBμV] | QP<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AV<br>Value<br>[dBμV] | AV<br>Limit<br>[dBμV] | AV<br>Margin<br>[dB] |
|-----|----------------|----------------|-----------------------|-----------------------|----------------------|-----------------------|-----------------------|----------------------|
| 1   | 0.2175         | 10.05          | 43.67                 | 62.91                 | 19.24                | 36.25                 | 52.91                 | 16.66                |
| 2   | 0.4342         | 10.05          | 43.31                 | 57.17                 | 13.86                | 35.16                 | 47.17                 | 12.01                |
| 3   | 0.8651         | 10.06          | 38.65                 | 56.00                 | 17.35                | 28.98                 | 46.00                 | 17.02                |
| 4   | 1.0823         | 10.07          | 39.49                 | 56.00                 | 16.51                | 29.26                 | 46.00                 | 16.74                |
| 5   | 2.1715         | 10.16          | 31.74                 | 56.00                 | 24.26                | 20.77                 | 46.00                 | 25.23                |
| 6   | 2.8318         | 10.21          | 28.50                 | 56.00                 | 27.50                | 19.62                 | 46.00                 | 26.38                |



## Line Conducted Emission Test Line 2-N



## Suspected List

| NO. | Freq.<br>[MHz] | Level<br>[dBμV] | Factor<br>[dB] | Limit<br>[dBμV] | Margin<br>[dB] | Detector |
|-----|----------------|-----------------|----------------|-----------------|----------------|----------|
| 1   | 0.1545         | 42.23           | 10.03          | 65.75           | 23.52          | PK       |
| 2   | 0.2175         | 47.67           | 10.05          | 62.91           | 15.04          | PK       |
| 3   | 0.4335         | 45.33           | 10.05          | 57.19           | 11.86          | PK       |
| 4   | 0.6450         | 35.79           | 10.05          | 56.00           | 20.21          | PK       |
| 5   | 1.0860         | 42.52           | 10.07          | 56.00           | 13.48          | PK       |
| 6   | 1.9590         | 38.81           | 10.14          | 56.00           | 17.19          | PK       |

## Final Data List

| NO. | Freq.<br>[MHz] | Factor<br>[dB] | QP<br>Value<br>[dBμV] | QP<br>Limit<br>[dBμV] | QP<br>Margin<br>[dB] | AV<br>Value<br>[dBμV] | AV<br>Limit<br>[dBμV] | AV<br>Margin<br>[dB] |
|-----|----------------|----------------|-----------------------|-----------------------|----------------------|-----------------------|-----------------------|----------------------|
| 1   | 0.1580         | 10.02          | 34.91                 | 65.67                 | 30.76                | 23.19                 | 55.67                 | 32.48                |
| 2   | 0.2153         | 10.05          | 47.10                 | 63.00                 | 15.90                | 38.10                 | 53.00                 | 14.90                |
| 3   | 0.4297         | 10.05          | 43.57                 | 57.26                 | 13.69                | 36.62                 | 47.26                 | 10.64                |
| 4   | 0.6440         | 10.05          | 33.50                 | 56.00                 | 22.50                | 26.28                 | 46.00                 | 19.72                |
| 5   | 1.0752         | 10.07          | 39.60                 | 56.00                 | 16.40                | 30.67                 | 46.00                 | 15.33                |
| 6   | 1.9394         | 10.14          | 30.35                 | 56.00                 | 25.65                | 21.69                 | 46.00                 | 24.31                |



**RESULT: PASS**

Note: All the test modes had been tested, the mode 1 was the worst case. Only the data of the worst case would be record in this test report.



## APPENDIX A: PHOTOGRAPHS OF TEST SETUP


### FCC RADIATED EMISSION TEST SETUP







### FCC LINE CONDUCTED EMISSION TEST SETUP



## APPENDIX B: PHOTOGRAPHS OF EUT

TOP VIEW OF EUT



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT



BACK VIEW OF EUT





LEFT VIEW OF EUT




RIGHT VIEW OF EUT



VIEW OF EUT (PORT)




OPEN VIEW OF EUT-1






OPEN VIEW OF EUT-2




VIEW OF BATTERY




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3





**SERIES COLOR SAMPLE**

**TOP VIEW OF EUT**



**BOTTOM VIEW OF EUT**






FRONT VIEW OF EUT



BACK VIEW OF EUT





LEFT VIEW OF EUT




RIGHT VIEW OF EUT



VIEW OF EUT (PORT)




OPEN VIEW OF EUT







# VIEW OF BATTERY




## INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3





**SERIES COLOR SAMPLE**

**TOP VIEW OF EUT**




**BOTTOM VIEW OF EUT**



FRONT VIEW OF EUT



BACK VIEW OF EUT





LEFT VIEW OF EUT



RIGHT VIEW OF EUT



VIEW OF EUT (PORT)



OPEN VIEW OF EUT







VIEW OF BATTERY




INTERNAL VIEW OF EUT-1



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3





VIEW OF ADAPTER (AE)



The adapter was supplied by HUA

-----END OF REPORT-----