

6	5	4	3	2	1
ISO NO: EDW-19-8-0201		<Release>		REV	ZONE
		ALL		Initial Design	ENG
				Eva Liang	APPROVED
				Haley	ISSUED DATE
					2019/02/11

Detail A
Scale: 2:1

Front

Side

Back

Notes:

1. No dregs or insufficient soldering. Solder thickness 0.3~1.7mm
2. The solder must be smooth and full to the edges of the pad. The solder must not extend outside of the pad area.
3. The connector position has special orientation to the PCB as per drawing.
4. All material must be RoHS compliant.
5. Open/short QC, VSWR required.
6. Soldered area.

	Name	P/N	Material	Finish	QTY
1	FXP840 FPCB	100112E020011A	Polymer 0.24t	Black	1
2	1.13 Coaxial Cable	001817K010000A	FEP	Black	1
3	IPEX MHF4L	001817K010000A	Copper Alloy	Au Ni Plated	1
4	Double-Sided Adhesive	100112E020011A	3M 467	Brown Liner	1
5	Clamp	001817K010000A	Phosphor Bronze	Sn Plated	4

UNLESS OTHERWISE SPECIFIED
TOLERANCES ON:

XX.± 0.5 .XX± 0.1
X.± 0.3 .XXX± 0.05

APPROVED BY: Haley

CHECKED BY: Haley

DRAWN BY: Eva Liang

DATE: 2019/02/11

UNIT: mm

THIRD ANGLE PROJECTION

MAT'L:

FINISH:

SCALE: 2/1

CUSTOMERS SIGNATURE / DATE

TAOGLAS. TW Design Centre

This drawing and its inherent design concepts are property of Taoglas. Not to be copied or given to third parties without the written consent of Taoglas.

TITLE: :24/5.8GHz Flex PCB Antenna 76mm 1.13 IPEX MHF4L
w/ Cable Clamp and 3M 467 adhesive

PART NO. : FXP840.54.0076A.ii

REV

D01

A