Prüfbericht-Nr.: *Test Report No.:*	**50157575 001**	**Auftrags-Nr.:** *Order No.:*	144187872	**Seite 1 von 15** *Page 1 of 15*
Kunden-Referenz-Nr.: *Client Reference No.:*	N/A	**Auftragsdatum:** *Order date:*	20.06.2018	
Auftraggeber: *Client:*	**HK TECH SCIENCE & TECHNOLOGY CO.,LTD Xiehe Industrial B Zone, Laimei Road, Chenghai District, 515800, Shantou, Guangdong, China**			
Prüfgegenstand: *Test item:*	**Short Range Device - Radio Controlled Toy Quadcopter (2.4GHz)**			
Bezeichnung / Typ-Nr.: *Identification / Type No.:*	**FX-22C**			
Auftrags-Inhalt: *Order content:*	FCC Certification			
Prüfgrundlage: *Test specification:*	**FCC Part 15 Subpart C ANSI C63.10-2013**			
Wareneingangsdatum: *Date of receipt:*	08.02.2018			
Prüfmuster-Nr.: *Test sample No.:*	A000696486-001			
Prüfzeitraum: *Testing period:*	25.04.2018			
Ort der Prüfung: *Place of testing:*	TÜV Rheinland Hong Kong Ltd			
Prüflaboratorium: *Testing laboratory:*	TÜV Rheinland Hong Kong Ltd			
Prüfergebnis*: *Test result*:*	Pass			



geprüft von / *tested by:*			**kontrolliert von** / *reviewed by:*		
05.07.2018	Kevin Wong / Project Manager		05.07.2018	Mika Chan / Project Manager	
Datum *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*	**Datum** *Date*	**Name / Stellung** *Name / Position*	**Unterschrift** *Signature*

Sonstiges / *Other:* **FCC ID: 2AFDJHKFX8GW**

This report covers partial test requirement under CFR47 FCC Part 15: Subpart C Section 15.247.
This report should be read in conjunction with report number 171027003RFC-1.

Zustand des Prüfgegenstandes bei Anlieferung: Prüfmuster vollständig und unbeschädigt
Condition of the test item at delivery: *Test item complete and undamaged*

* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend	5 = mangelhaft
	P(ass) = entspricht o.g. Prüfgrundlage(n)		F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	N/T = nicht getestet
Legend:	*1 = very good*	*2 = good*	*3 = satisfactory*	*4 = sufficient*	*5 = poor*
	P(ass) = passed a.m. test specification(s)		*F(ail) = failed a.m. test specification(s)*	*N/A = not applicable*	*N/T = not tested*

Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.

This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.

Table of Content

Page

Cover Page 1

Table of Content 2

Product information 4

Manufacturers declarations 4

Product function and intended use 4

Submitted documents 5

Independent Operation Modes 5

Related Submittal(s) Grants 5

Remark 5

Test Set-up and Operation Mode 6

Principle of Configuration Selection 6

Test Operation and Test Software 6

Special Accessories and Auxiliary Equipment 6

Countermeasures to achieve EMC Compliance 6

Test Methodology 7

Radiated Emission 7

Field Strength Calculation 7

Test Setup Diagram 8

Test Facility 10

Test Laboratory Information 10

List of Test and Measurement Instruments 11

Measurement Uncertainty 12

Results FCC Part 15 – Subpart C 13

FCC 15.203 – Antenna Requirement 1 ..... Pass 13

FCC 15.204 – Antenna Requirement 2 ..... N/A 13

FCC 15.207 – Conducted Emission on AC Mains ..... Pass 13

FCC 15.247 (a)(2) – 6dB Bandwidth Measurement ..... Pass 14

FCC 15.247(b)(3) – Maximum Peak Couducted Output Power ..... Pass 14

FCC 15.247(e) – Power Spectral Density ..... Pass 15

FCC 15.247(d) – Spurious Conducted Emissions ..... Pass 15

Appendix 1 – Test protocols ..... **15 pages**

Appendix 2 – EUT External Photos ..... **3 pages**

Appendix 3 – EUT Internal Photos ..... **2 pages**

Appendix 4 – RF exposure information ..... **2 pages**

Product information

Manufacturers declarations

	Transceiver
Operating frequency range	2412MHz
Type of modulation	802.11b: DSSS (CCK, DQPSK, DBPSK)
Number of channels	1
Type of antenna	Internal Antenna
Antenna gain (dBi)	2.5 dBi
Power level	fix
Type of equipment	stand alone radio device
Connection to public utility power line	No
Nominal voltage	V_{nor}: 3.7VDC
Independent Operation Modes	Transmitting

Product function and intended use

The submitted sample FX-22C is radio controlled toy helicopter embedded with WiFi camera. It is intended to use in following electromagnetic environment: residential and urban outdoors.

FCC ID: 2AFDJHKFX8GW

Models	Product description
FX-22C, FX-2, FX-3, FX-3V, FX-4, FX-4VCI, FX-4V, FX-5, FX-5W, FX-6, FX-6C, FX-6CI, FX-7, FX-7C, FX-7CI, FX-7S, FX-8A, FX-8E, FX-8C, FX-8G, FX-9A, FX-9E, FX-9C, FX-11, FX-12V, FX-12, FX-13, FX-14, FX-15, FX-15C, FX-15CI, FX-16, FX-16C, FX-16CI, FX-17, FX-18, FX-19, FX-20, FX-21, FX-22A, FX-22E, FX-23, FX-24, FX-25, FX-25CI, FX-26,FX-26CI, FX-27A, FX-27E, FX-27C, FX-28, FX-29, FX-29CI, FX-29A, FX-29E, FX-30, FX-31, FX-32, FX-33, FX-34, FX-35A, FX-35E, FX-35C, FX-36, FX-37, D2, D3, D3V, D4, D4VCI, D4V, D5, D5W, D6, D6C, D6CI, D7, D7C, D7CI, D7S, D8A, D8E, D8C, D8G, D9A, D9E, D9C, D11, D12V, D12, D13, D14, D15, D15C, D15CI, D16, D16C, D16CI, D17, D18, D19, D20, D21, D22A, D22E, D22C, D23, D24, D25, D25CI, D26, D27A, D27E, D27C, D28, D29, D29CI, D29A, D29E, D30, D31, D32, D33, D34, D35A, D35E, D35C, D36, D37	**Short Range Device - Radio Controlled Toy Quadcopter (2.4GHz)**

Submitted documents

Circuit Diagram
Block Diagram
Technical Description
User manual
Label

Independent Operation Modes

The basic operation modes are:

- Transmitting mode.

For further information refer to User Manual

Related Submittal(s) Grants

- none

Remark

The test results in this test report are only relevant to the tested sample and does not involve any assessment in the production.

Test Set-up and Operation Mode

Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Test Operation and Test Software

Test operation should refer to test methodology.

- During test, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power was selected according to the instruction given by the manufacturer. The setting of the RF output power expected by the customer shall be fixed on the firmware of the final end product.

Special Accessories and Auxiliary Equipment

The product has been tested together with the following additional accessories:

- Personal Computer (Provided by TÜV Rheinland Hong Kong Ltd)
  Manufacturer: Lenovo
  Model: 80Q6.
  S/N: PF0BEWWR

Countermeasures to achieve EMC Compliance

- none

Test Methodology

Radiated Emission

The radiated emission measurements of the transmitter part were performed according to the procedures in ANSI C63.10-2013.

For measurement below 1GHz - the equipment under test (EUT) was placed at the middle of the 80 cm height turntable. For measurement above 1GHz - the EUT was placed at the middle of the 1.5 m height turntable and RF absorbing material was placed on ground plane between turntable and measuring antenna. During the testing, the EUT was operated standalone and arranged for maximum emissions. The EUT was tested in three orthogonal planes.

The investigation is performed with the EUT rotated 360 ˚ , the antenna height scanned between 1m and 4m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations. Repeat the measurement steps until the maximum emissions were obtained.

All radiated tests were performed at an antenna to EUT with 3 meters distance, unless stated otherwise in particular parts of this test report.

Field Strength Calculation

The field strength at 3 m was established by adding the meter reading of the spectrum analyzer to the factors associated with antenna correction factor, cable loss, preamplifiers and filter attenuation.

The equation is expressed as follow:

FS = R + AF + CF + FA – PA

Where FS = Field Strength in dBuV/m at 3 meters.
R = Reading of Spectrum Analyzer in dBuV.
AF = Antenna Factor in dB.
CF = Cable Attenuation Factor in dB.
FA = Filter Attenuation Factor in dB.
PA = Preamplifier Factor in dB.

FA and PA are only be used for the measuring frequency above 1 GHz.

Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test



Note: Measurements above 1 GHz are done with a table height of 1.5m. In addition, there is RF absorbing material on the floor of the test site for above 1GHz measurement.

Diagram of Measurement Equipment Configuration for Mains Conduction Measurement (if applicable)



Diagram of Equipment Configuration for Antenna-port Conducted Measurement (if applicable)



Test Facility

Test Laboratory Information

TÜV Rheinland Hong Kong Ltd.
Address: 3-4, 11/F., Fou Wah Industrial Building, 10-16 Pun Shan Street, Tsuen Wan, N.T., Hong Kong·
Tel.: +852 2192 1000
Fax: +852 2192 1001
Email service-gc@tuv.com
Web: www.tuv.com

The test facility is recognized or accredited by the following organizations:

FCC

Type	:	Accredited Test Firm
Designation Number	:	HK0013
Test Firm Registration Number	:	371735
Scope	:	Intentional Radiators

List of Test and Measurement Instruments

TÜV Rheinland Hong Kong Ltd

Radio Test

Equipment	Manufacturer	Type	Cal. Date	Due Date
Spectrum Analyzer	R & S	FSP30	28-Sep-17	28-Sep-18

Measurement Uncertainty

The estimated combined standard uncertainty for antenna conducted emission is ±2.1dB

The reported expanded uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor of k=2, which for the level of confidence is approximately 95%.

Results FCC Part 15 – Subpart C

FCC 15.203 – Antenna Requirement 1		**Pass**
FCC Requirement:	No antenna other than that furnished by the responsible party shall be used with the device	
Results:	a) Antenna type: b) Manufacturer and model no: c) Peak Gain:	Integral PCB antenna N/A 2.5 dBi
Verdict:	Pass	

FCC 15.204 – Antenna Requirement 2		**N/A**
FCC Requirement:	An intentional radiator may be operated only with the antenna with which it is authorized. If an antenna is marketed with the intentional radiator, it shall be of a type which is authorized with the intentional radiator.	
Results:	Only one integral antenna can be used.	
Verdict:	N/A	

FCC 15.207 – Conducted Emission on AC Mains	**Pass**
There is no AC power input or output ports on the EUT.	

FCC 15.247 (a)(2) – 6dB Bandwidth Measurement			Pass
FCC Requirement: Systems using digital modulation techniques may operate in the 902 – 928 MHz, 2400 – 2483.5 MHz, and 5725 – 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500kHz.			
Test Specification : ANSI C63.10 – 2013 Test date : 25.04.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3.7VDC Temperature : 23ºC Humidity : 50%			
Results: For test protocols please refer to Appendix 1			
Channel frequency (MHz)	**6 dB left (MHz)**	**6 dB right (MHz)**	**6dB bandwidth (MHz)**
2412	2406.960	2416.960	10.00

FCC 15.247(b)(3) – Maximum Couducted (Average) Output Power			Pass
FCC Requirement: For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850MHz bands: 1 Watt (30dBm)			
Test Specification : ANSI C63.10 – 2013 Test date : 25.04.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3.7VDC Temperature : 23ºC Humidity : 50%			
Results: For test protocols please refer to Appendix 1			
802.11b			
Frequency (MHz)	**Measured Output Power (dBm)**	**Limit (W/dBm)**	**Verdict**
2412	17.89	1 / 30.0	Pass

FCC 15.247(e) – Power Spectral Density	Pass
FCC Requirement:	For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
Test Specification : ANSI C63.10 – 2013 Test date : 25.04.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3.7VDC Temperature : 23ºC Humidity : 50%	
Results:	For test protocols please refer to Appendix 1.

Operating frequency (MHz)	Power density (dBm)	Limit (dBm)	Verdict
2412	3.04	8.0	Pass

FCC 15.247(d) – Spurious Conducted Emissions	Pass
Test Specification : ANSI C63.10 – 2013 Test date : 25.04.2018 Mode of operation : Tx mode Port of testing : Temporary antenna port Supply voltage : 3.7VDC Temperature : 23ºC Humidity : 50%	
FCC Requirement:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Results:	Pre-scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Only the worst cases is shown below. For test protocols refer to Appendix 1

Operating frequency (MHz)	Spurious frequency (MHz)	Spurious Level (dBm)	Reference value (dBm)	Delta (dB)	Verdict
2412	No peak found	---	3.04	---	Pass

Appendix 1

Test protocols

6 dB Bandwidth Measurement

TX frequency: 2412MHz



Maximum Conducted (Average) Output power

TX frequency: 2412MHz



Power Spectral Density

TX frequency: 2412MHz



Spurious Conducted Emissions

TX frequency: 2412MHz






RBW 100 kHz
VBW 300 kHz
SWT 200 ms
Marker 1 [T1]
-39.70 dBm
2.964000000 GHz
Ref 20 dBm
Att 50 dB
1 PK
MAXH
A
1
3DB
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Start 1 GHz
200 MHz/
Stop 3 GHz


RBW 100 kHz
VBW 300 kHz
SWT 1 s
Marker 1 [T1]
-30.39 dBm
7.920000000 GHz
Ref 20 dBm
Att 50 dB
1 PK
MAXH
A
1
3DB
20
10
0
-10
-20
-30
-40
-50
-60
-70
-80
Start 3 GHz
1 GHz/
Stop 13 GHz


RBW 100 kHz
VBW 300 kHz
Marker 1 [T1]
-21.13 dBm
24.256000000 GHz
Ref 20 dBm
Att 50 dB
SWT 1.2 s
1 PK
MAXH
A
3DB
Start 13 GHz
1.2 GHz/
Stop 25 GHz


RBW 100 kHz
VBW 300 kHz
Marker 1 [T1]
-41.19 dBm
2.492600000 GHz
Ref 20 dBm
Att 50 dB
SWT 5 ms
1 PK
MAXH
A
3DB
Center 2.4835 GHz
5 MHz/
Span 50 MHz

Appendix 2

EUT External Photos



External View



External View

Appendix 3

EUT Internal Photos



Internal View



Internal View



Internal View



Internal View



Internal View



Internal View

Appendix 4

RF Exposure Information

Maximum transmitter power:

Frequency (MHz)	Maximum peak output power (dBm)	Output power(mW)
2412	17.89	61.52

According to the manufacturer's installation instruction, the EUT operating in standalone mobile exposure conditions which minimum test separation distance is 20cm between the antenna and radiating structures of the device and nearby persons.

For Maximum Permissible Exposure (MPE) evaluation, the maximum power density at 20 cm from this mobile transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498.

Evaluation:

The maximum conducted output power of WIFI is 61.52mW,

The power density at 20cm = $(61.52mW \times 1)/4\pi R^2$
= $0.0122\ mWcm^{-2}$

Conclusion:
In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 $mWcm^{-2}$ for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons.