



**BUREAU
VERITAS**

Test Report No.: FS150401N006

RF EXPOSURE REPORT

Applicant	Jmatek Limited
Address	Suite 808A, Tower A, Manulife Financial Centre, 223-231 Wai Yip Street, Kwun Tong, Kowloon, Hong Kong

Manufacturer or Supplier	KAIPING NEW WIDETECH ELECTRONIC CO. LTD.
Address	First building No. 40 Xing Da Road, Shuiko Town, Kaiping city, Guangdong, 529300 CHINA
Product	Portable air conditioner
Brand Name	Honeywell
Model	MN13CESWWF
Additional Model & Model Difference	MN10CESF, MN12CESF, MN10CESWWF, MN10CESBBF, MN12CESWWF, MN12CESBBF, MN13CESF, MN13CESBBF, MN13CHESF
Date of tests	Apr. 01, 2015 ~ Apr. 22, 2015

☒ FCC Part 2 (Section 2.1091)

☒ KDB 447498 D03

☒ IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Heise Chen Project Engineer/ EMC Department	Approved by Chris Chen Assistant Manager / EMC Department
	 Date: Apr. 22, 2015

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FS150401N006

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS150401N006	Original release	Apr. 22, 2015

Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com

1. CERTIFICATION

FCC ID:	2AFDNP01
PRODUCT:	Portable air conditioner
BRAND NAME:	Honeywell
MODEL NO.:	MN13CESWWF
ADDITIONAL NO.:	MN10CESF, MN12CESF, MN10CESWWF, MN10CESBBF, MN12CESWWF, MN12CESBBF, MN13CESF, MN13CESBBF, MN13CHESF
TEST SAMPLE:	Engineering Sample
APPLICANT:	Jmatek Limited
TESTED DATE:	Apr. 22, 2015
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D03
	IEEE C95.1

NOTE: Additional models (see above table) are identical with the test model MN13CESWWF except the identify by numerical and character, their meaning as below:

MN --- family model which same cabinet, electrical.

10/12/13—represents for BTC, e.g. 10 for 10000BTU, 12 for 12000BTU, 13 for 13000BTU.

CES—represents features cool, LED display.

WW—represents main unit in white color.

BB – represents main unit in Black color.

F– Wi-Fi version.

Remark: Without WW, BB means basic version in silver and black color.

RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

2. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



4. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Total Gain (dBi)	Antenna Type
Chain 0	1.0	1.0	PCB Antenna

5. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FREQUENCY BAND (MHz)	MAX POWER (mW)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	137.721	1.0	20	0.0274	1.00

Conclusion

Therefore device complies with FCC's RF radiation exposure limits for general population in mobile exposure category (distance > 20cm)

--- END ---