

**A Radio Test Report**

**FOR**

**Acorn Mobility Services Limited**

**ON**

**Acorn180 Stair Lift System**

**T573 Hand Held Remote**

**Document No.TRA-025851-01-47-03B**

**HULL**

Unit E, South Orbital Trading Park, Hedon Road, Hull, HU9 1NJ, UK.  
**T** +44 (0)1482 801801 **F** +44 (0)1482 801806 **E** test@tracglobal.com  
[www.tracglobal.com](http://www.tracglobal.com)

**TRaC Wireless Test Report** : TRA-025851-01-47-03B

**Applicant** : Acorn Mobility Services Limited

**Apparatus** : T573 hand held remote

**Specification(s)** : FCC CFR47 Part 15.249 & RSS-210 Issue 8

**Purpose of Test** : Certification

**FCC ID** : 2AFDQACORN180REMOTE

**Authorised by** : John Charters  
Digitally signed by John Charters  
DN: cn=John Charters, o=TRAC Global  
Ltd, ou=Radio Product Manager,  
email=john.charters@tracglobal.com,  
c=GB  
Date: 2015.07.30 16:08:28 +01'00'

: Radio Product Manager

**Issue Date** : 30<sup>th</sup> July 2015

**Authorised Copy Number** : PDF

**Contents**

|             |                                                            |    |
|-------------|------------------------------------------------------------|----|
| Section 1:  | Introduction                                               | 4  |
| 1.1         | General                                                    | 4  |
| 1.2         | Tests Requested By                                         | 5  |
| 1.3         | Manufacturer                                               | 5  |
| 1.4         | Apparatus Assessed                                         | 5  |
| 1.5         | Test Result Summary                                        | 6  |
| 1.6         | Notes relating to the assessment                           | 7  |
| 1.7         | Deviations from Test Standards                             | 7  |
| Section 2:  | Measurement Uncertainty                                    | 8  |
| 2.1         | Measurement Uncertainty Values                             | 8  |
| Section 3:  | Modifications                                              | 10 |
| 3.1         | Modifications Performed During Assessment                  | 10 |
| Section 4   | General Test Procedures                                    | 11 |
| 4.1         | Radiated Test Setup and Procedures                         | 11 |
| 4.2         | AC Powerline Conducted Emissions Test Setup and Procedures | 12 |
| 4.3         | Antenna Port Conducted Emissions                           | 12 |
| 4.4         | Power Supply Variation                                     | 13 |
| 4.5         | Thermal Variation                                          | 13 |
| 4.6         | Time Domain Measurements                                   | 13 |
| Appendix A: | Formal Emission Test Results                               | 14 |
| A1          | Transmitter Intentional Emission Radiated                  | 15 |
| A2          | Transmitter Bandwidth                                      | 16 |
| A3          | Radiated Electric Field Emissions                          | 17 |
| Appendix B: | Supporting Graphical Data                                  | 19 |
| Appendix C: | Additional Test and Sample Details                         | 23 |
| C1          | Test samples                                               | 24 |
| C2          | EUT operating mode during testing                          | 25 |
| C3          | EUT Configuration Information                              | 26 |
| C4          | List of EUT Ports                                          | 27 |
| C5          | Details of Equipment Used                                  | 28 |
| Appendix D: | Additional Information                                     | 29 |
| Appendix E: | Calculation of the duty cycle correction factor            | 30 |
| Appendix F: | Photographs and Figures                                    | 31 |
| Appendix G: | General SAR test reduction and exclusion guidance          | 33 |
| Appendix H: | MPE Calculation                                            | 34 |

**Section 1:****Introduction****1.1 General**

This report contains an assessment of an apparatus against Electromagnetic Compatibility Standards based upon tests carried out on samples submitted to the Laboratory.

Test performed by: TRaC Global [ ]  
Unit E  
South Orbital Trading Park  
Hedon Road  
Hull, HU9 1NJ.  
United Kingdom.

Telephone: +44 (0) 1482 801801  
Fax: +44 (0) 1482 801806

TRaC Global [X]  
Unit 1  
Pendle Place  
Skelmersdale  
West Lancashire, WN8 9PN  
United Kingdom

Telephone: +44 (0) 1695 556666  
Fax: +44 (0) 1695 577077

Email: [test@tracglobal.com](mailto:test@tracglobal.com)  
Web site: <http://www.tracglobal.com>

Tests performed by: A Tosif

Report author: A Tosif

**This report must not be reproduced except in full without prior written permission from TRaC Global Ltd.**

## **1.2 Tests Requested By**

This testing in this report was requested by:

Acorn Mobility Services Limited  
Telecom House  
Millennium Business Park  
Steeton  
Station Road  
BD20 6RB  
UK

## **1.3 Manufacturer**

As above

## **1.4 Apparatus Assessed**

The following apparatus was assessed between: 5<sup>th</sup> May 2015 and 18<sup>th</sup> May 2015

- Acorn180 Stair Lift System - T573 hand held remote

The Acorn180 Stair Lift System consists of a T565 chair controller, a T567 hinge controller and a T573 hand held remote. All of the above equipments contain the same radio module that operates in 902 MHz – 928 MHz band.

This report only covers the testing done on T573 hand held remote. TRA-025851-01-47-01B and TRA-025851-01-47-02B cover the testing done on T565 chair controller and T567 hinge controller, respectively.

## 1.5 Test Result Summary

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

The statements relating to compliance with the standards below apply ONLY as qualified in the notes and deviations stated in sections 1.6 to 1.7 of this test report.

Full details of test results are contained within Appendix A. The following table summarises the results of the assessment.

| Test Type                                 | FCC Regulation                                           | IC Regulation                                     | Measurement standard | Result |
|-------------------------------------------|----------------------------------------------------------|---------------------------------------------------|----------------------|--------|
| Spurious Emissions Radiated               | Title 47 of the CFR:<br>Part 15 Subpart (c) 15.249(a)(d) | RSS-210 Issue 8<br>December 2010<br>Annex 2 A2.9  | ANSI<br>C63.10:2009  | Pass   |
| Unintentional Radiated Spurious Emissions | Title 47 of the CFR:<br>Part 15 Subpart (b) 15.109       | RSS-Gen Issue 4<br>November 2014<br>Section 7.1.2 | ANSI<br>C63.10:2009  | N/A*   |
| AC Power line conducted emissions (PLCE)  | Title 47 of the CFR:<br>Part 15 Subpart (c) 15.207       | RSS-Gen Issue 4<br>November 2014<br>Section 8.8   | ANSI<br>C63.10:2009  | N/A#   |
| Intentional Emission Frequency            | Title 47 of the CFR:<br>Part 15 Subpart (c) 15.249 (a)   | RSS-210 Issue 8<br>December 2010<br>Annex 2 A2.9  | ANSI<br>C63.10:2009  | Pass   |
| Intentional Emission Field Strength       | Title 47 of the CFR:<br>Part 15 Subpart (c) 15.249 (a)   | RSS-210 Issue 8<br>December 2010<br>Annex 2 A2.9  | ANSI<br>C63.10:2009  | Pass   |
| Intentional Emission Band Occupancy       | Title 47 of the CFR:<br>Part 15 Subpart (c) 15.215 (c)   | RSS-Gen Issue 4<br>November 2014<br>Section 4.6.1 | ANSI<br>C63.10:2009  | Pass   |

\* EUT is a transmitter only device.

# EUT is a battery powered device.

Abbreviations used in the above table:

CFR : Code of Federal Regulations  
REFE : Radiated Electric Field Emissions

ANSI : American National Standards Institution  
PLCE : Power Line Conducted Emissions

## **1.6 Notes relating to the assessment**

With regard to this assessment, the following points should be noted:

The results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

The apparatus was set up and exercised using the configurations, modes of operation and arrangements defined in this report only.

Particular operating modes, apparatus monitoring methods and performance criteria required by the standards tested to have been performed except where identified in Section 1.7 of this test report (Deviations from Test Standards).

For emissions testing, throughout this test report, "Pass" indicates that the results for the sample as tested were below the specified limit (refer also to Section 2, Measurement Uncertainty).

Where relevant, the apparatus was only assessed using the monitoring methods and susceptibility criteria defined in this report.

All testing with the exception of testing at the Open Area Test Site was performed under the following environmental conditions:

|             |               |
|-------------|---------------|
| Temperature | : 20 to 22 °C |
| Humidity    | : 45 to 75 %  |

All dates used in this report are in the format dd/mm/yy.

This assessment has been performed in accordance with the requirements of ISO/IEC 17025.

## **1.7 Deviations from Test Standards**

There were no deviations from the standards tested to.

**Section 2:****Measurement Uncertainty****2.1 Measurement Uncertainty Values**

For the test data recorded the following measurement uncertainty was calculated:

**Radio Testing – General Uncertainty Schedule**

*All statements of uncertainty are expanded standard uncertainty using a coverage factor of 1.96 to give a 95% confidence where no required test level exists.*

**[1] Adjacent Channel Power**

Uncertainty in test result = **1.86dB**

**[2] Carrier Power**

Uncertainty in test result (Power Meter) = **1.08dB**

Uncertainty in test result (Spectrum Analyser) = **2.48dB**

**[3] Effective Radiated Power**

Uncertainty in test result = **4.71dB**

**[4] Spurious Emissions**

Uncertainty in test result = **4.75dB**

**[5] Maximum frequency error**

Uncertainty in test result (Power Meter) = **0.113ppm**

Uncertainty in test result (Spectrum Analyser) = **0.265ppm**

**[6] Radiated Emissions, field strength OATS 14kHz-18GHz Electric Field**

Uncertainty in test result (14kHz – 30MHz) = **4.8dB**,

Uncertainty in test result (30MHz – 1GHz) = **4.6dB**,

Uncertainty in test result (1GHz – 18GHz) = **4.7dB**

**[7] Frequency deviation**

Uncertainty in test result = **3.2%**

**[8] Magnetic Field Emissions**

Uncertainty in test result = **2.3dB**

**[9] Conducted Spurious**

Uncertainty in test result – Up to 8.1GHz = **3.31dB**

Uncertainty in test result – 8.1GHz – 15.3GHz = **4.43dB**

Uncertainty in test result – 15.3GHz – 21GHz = **5.34dB**

Uncertainty in test result – Up to 26GHz = **3.14dB**

**[10] Channel Bandwidth**

Uncertainty in test result = **15.5%**

**[11] Amplitude and Time Measurement – Oscilloscope**

Uncertainty in overall test level = **2.1dB**,  
Uncertainty in time measurement = **0.59%**,  
Uncertainty in Amplitude measurement = **0.82%**

**[12] Power Line Conduction**

Uncertainty in test result = **3.4dB**

**[13] Spectrum Mask Measurements**

Uncertainty in test result = **2.59% (frequency)**  
Uncertainty in test result = **1.32dB (amplitude)**

**[14] Adjacent Sub Band Selectivity**

Uncertainty in test result = **1.24dB**

**[15] Receiver Blocking – Listen Mode, Radiated**

Uncertainty in test result = **3.42dB**

**[16] Receiver Blocking – Talk Mode, Radiated**

Uncertainty in test result = **3.36dB**

**[17] Receiver Blocking – Talk Mode, Conducted**

Uncertainty in test result = **1.24dB**

**[18] Receiver Threshold**

Uncertainty in test result = **3.23dB**

**[19] Transmission Time Measurement**

Uncertainty in test result = **7.98%**

## **Section 3:**

## **Modifications**

### **3.1 Modifications Performed During Assessment**

No modifications were performed during the assessment

## Section 4

## General Test Procedures

### 4.1 Radiated Test Setup and Procedures

Radiated electromagnetic emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked, using a peak detector and where applicable worst case determined for function, operation, orientation etc for both vertical and horizontal polarisations

If the EUT connects to auxiliary equipment and is table or floor standing, the configurations prescribed in ANSI C63.10 are followed. Alternatively, a layout closest to normal use (as declared by the provider) is employed, (see EUT setup photographs for more detail).

For devices with intentional emissions below 30 MHz, a shielded loop antenna is used as the test antenna. It is placed at a 1 meter receive height and appropriate low frequency magnetic field extrapolation to the regulatory limit distance is employed. The EUT is rotated through 360° in the azimuth.

Emissions between 30 MHz and 1 GHz are measured using calibrated broadband antennas. Emissions above 1 GHz are characterized using standard gain horn antennas. Pre-amplifiers and filters are used where required. Care is taken to ensure that test receiver resolution bandwidth, video bandwidth and detector type(s) meet the regulatory requirements.

For both horizontal and vertical polarizations, the EUT is then rotated through 360° in azimuth until the highest emission is detected. At the previously determined azimuth the test antenna is raised and lowered from 1 to 4 m in height until a maximum emission level is detected, this maximum value is recorded.

Where regulations allow for direct measurement of field strength, power values measured on the test receiver / analyzer are converted to dBuV/m at the regulatory distance, using:

$$FS = PR + AF + CL - PA + KG + DC - CF \text{ (dBuV/m)}$$

Where:

PR is the power recorded on receiver / spectrum analyzer (dBuV),

AF is the test antenna factor in dB/m,

CL is the cable loss in dB,

PA is the pre-amplifier gain dB (when applicable),

DC is duty correction factor (when applicable) in dB, and

CF is a distance correction (employed only for measurements at alternate distance to limit) in dB.

This field strength value is then compared with the regulatory limit.

If effective radiated power (ERP) or effective isotropic radiated power (EIRP) is required, it is computed as per ANSI C63.10

$$P = \frac{(Ed)^2}{30G}$$

Where

$P$  is the power, in W

$E$  is the measured peak field strength, in V/m

$d$  is the distance at which the measurement was made, in m

$G$  is the numeric gain of the radiating element

If the gain of the radiating element is not known, then either the effective radiated power (ERP) or the effective isotropic radiated power (EIRP) may be calculated from the measured peak field strength, by using either  $G = 1.64$  or  $G = 1$ , respectively.

## **4.2 AC Powerline Conducted Emissions Test Setup and Procedures**

AC Powerline Conducted Emissions from the EUT are checked first by preview scans with Peak and average detectors covering both live and neutral lines. A spectrum analyser is used to determine if any periodic emissions are present. Preview scans are performed in standby or receive mode if the device is subject to these requirements. For transmit mode of operation the device is set to one of the following modes.

- Transmitting operating at full power (single mode device)
- Transmitting at freq / modulation that gives highest output power (multi mode device)
- Transmitter operating in normal TX mode (e.g. FHSS, TDMA etc)

Formal measurements using the correct detector(s) and bandwidth are made on frequencies identified from the preview scans.

Battery Power devices are not subject to power line conducted emissions measurements when it is powered solely by its internal battery.

## **4.3 Antenna Port Conducted Emissions**

Antenna port conducted emissions can include, but are not limited to, Carrier power, Power Spectral Density, Occupied bandwidth and spurious emission.

Spurious Emissions from the EUT are checked first by preview scans. Preview scans for all spectrum and modulation characteristics are checked to identify frequencies to perform formal measurements on.

Formal measurements are made on frequencies identified from the preview scans and fundamental emission(s). Measurements are made using the correct instrumentation (inc. power meter, receiver, spectrum analyser) that operate with the required detector(s) and bandwidth.

Care is taken to ensure the measurement instrument is not overloaded by the presence of the transmitted signal by use of external attenuation and filtering where required.

Measured levels are corrected for cables, attenuators, and filters. If applicable, for the specific measurement, antenna gain is also taken into account.

#### **4.4 Power Supply Variation**

Tests at extreme supply voltages are made if required by the procedures specified in the test standard, and results of this testing are detailed in this report.

In the case the EUT is designed for operation from a lead-acid battery power source, the extreme test voltages are evaluated between 90% and 130% of the nominal battery voltage declared by the manufacturer.

For float charge applications using gel-cell type batteries, extreme test voltages are evaluated between 85% and 115% of the nominal battery voltage declared.

For all battery operated equipment, worst case intentional and spurious emissions are re-checked employing a new (fully charged) battery.

#### **4.5 Thermal Variation**

Tests at extreme temperatures are made if required by the procedures specified in the test standard, and results of this testing are detailed in this report.

Tests are performed at the upper and lower extremes as required and typically at 10° steps between.

Before any temperature measurements are made, the equipment is allowed to reach a thermal balance in the test chamber.

#### **4.6 Time Domain Measurements**

Time domain measurements are made for (but not limited to) use in duty cycle correction, to ensure compliance with time restrictions on certain types of devices.

If measurements of a transmitter's on time are required these are performed with a spectrum analyser in the time domain or with an oscilloscope and RF detector. If time on a specific frequency is required (e.g. FHSS timing) the measurement can only be made with a spectrum analyser.

The triggering, timescale and amplitude settings are adjusted according to the signal to be measured on a case by case basis.

For devices with sharp rise/fall times measurements are made between RF reaching full power ( $T_{on}$ ) and RF dropping to the measurement instrument noise floor ( $T_{off}$ ). For longer rise times measurements are made for  $T_{on}$  and  $T_{off}$  at the RF level required by the occupied bandwidth measurement (e.g. 6 dB, 20 dB etc).

**Appendix A:****Formal Emission Test Results**

Abbreviations used in the tables in this appendix:

|      |                                 |      |                                |
|------|---------------------------------|------|--------------------------------|
| Spec | : Specification                 | ALSR | : Absorber Lined Screened Room |
| Mod  | : Modification                  | OATS | : Open Area Test Site          |
| EUT  | : Equipment Under Test          | ATS  | : Alternative Test Site        |
| SE   | : Support Equipment             | Ref  | : Reference                    |
| L    | : Live Power Line               | Freq | : Frequency                    |
| N    | : Neutral Power Line            | MD   | : Measurement Distance         |
| E    | : Earth Power Line              | SD   | : Spec Distance                |
| Pk   | : Peak Detector                 | Pol  | : Polarisation                 |
| QP   | : Quasi-Peak Detector           | H    | : Horizontal Polarisation      |
| Av   | : Average Detector              | V    | : Vertical Polarisation        |
| CDN  | : Coupling & decoupling network |      |                                |

**A1 Transmitter Intentional Emission Radiated**

| Test Details           |                                                              |
|------------------------|--------------------------------------------------------------|
| Regulation             | Part15 Subpart (c) 15.249 (a) / RSS-210 Issue 8 Annex 2 A2.9 |
| Measurement standard   | ANSI C63.10:2009                                             |
| EUT sample number      | S09                                                          |
| Modification state     | 0                                                            |
| SE in test environment | None                                                         |
| SE isolated from EUT   | None                                                         |
| EUT set up             | Refer to Appendix C                                          |
| Temperature            | 22°C                                                         |

| Frequency (MHz) | Meas. Rx (dBμV) | Cable Loss (dB) | Ant Factor (dB/m) | Field Strength (dBμV/m) | Field Strength (mV/m) | Limit (mV/m) | Verdict |
|-----------------|-----------------|-----------------|-------------------|-------------------------|-----------------------|--------------|---------|
| 915.0           | 65.4            | 4.4             | 23.5              | 93.2                    | 45.7                  | 50.0         | Pass    |

- Notes:**
- 1 Receiver detector @ fc = Quasi Peak / 120kHz bandwidth
  - 2 When battery powered the EUT was powered with new batteries

- Test Method:**
- 1 As per Radio – Noise Emissions, ANSI C63.10:2009
  - 2 Measuring distances 3m
  - 3 EUT 0.8 metre above ground plane
  - 4 Emissions maximised by rotation of EUT, on an automatic turntable. Raising and lowering the receiver antenna between 1m & 4m. Horizontal and vertical polarisations of the receive antenna. EUT orientation in three orthogonal planes. Maximum results recorded

**A2 Transmitter Bandwidth**

| <b>Test Details:</b>   |                                               |
|------------------------|-----------------------------------------------|
| Regulation             | Part 15.215 (c) / RSS-Gen Issue 4 Section 6.6 |
| Measurement standard   | ANSI C63.10:2009                              |
| EUT sample number      | S09                                           |
| Modification state     | 0                                             |
| SE in test environment | None                                          |
| SE isolated from EUT   | None                                          |
| EUT set up             | Refer to Appendix C                           |
| Temperature            | 23°C                                          |

| <b>Band occupancy @ -20 dBc</b> |                          |                           |                              |
|---------------------------------|--------------------------|---------------------------|------------------------------|
| <b>FREQ.<br/>(MHz)</b>          | <b>f lower<br/>(MHz)</b> | <b>f higher<br/>(MHz)</b> | <b>Occupied BW<br/>(kHz)</b> |
| 915.0                           | 914.935256               | 915.078045                | 142.789                      |

The 20dB Bandwidth of the carrier must be contained within the frequency band 902 MHz to 928 MHz.

| <b>99% Band occupancy</b> |                          |                           |                              |
|---------------------------|--------------------------|---------------------------|------------------------------|
| <b>FREQ.<br/>(MHz)</b>    | <b>f lower<br/>(MHz)</b> | <b>f higher<br/>(MHz)</b> | <b>Occupied BW<br/>(kHz)</b> |
| 915.0                     | 914.89984                | 915.113782                | 213.942                      |

**A3 Radiated Electric Field Emissions**

Preliminary scans were performed using a peak detector with the RBW = 100 kHz. The radiated electric field emission test applies to all spurious emissions and harmonics emissions. The EUT was set to transmit as required.

The following test site was used for final measurements as specified by the standard tested to:

3m open area test site : ☐

3m alternative test site : ☒

| Test Details           |                                                                         |
|------------------------|-------------------------------------------------------------------------|
| Regulation             | Part 15 Subpart (c) Clause 15.249 (a)(d) / RSS-210 Issue 8 Annex 2 A2.9 |
| Measurement standard   | ANSI C63.10:2009                                                        |
| Frequency range        | 30MHz-10GHz                                                             |
| EUT sample number      | S09                                                                     |
| Modification state     | 0                                                                       |
| SE in test environment | None                                                                    |
| SE isolated from EUT   | None                                                                    |
| EUT set up             | Refer to Appendix C                                                     |
| Temperature            | 25°C                                                                    |

The worst case emissions are listed below:

| Ref No. | Freq. (MHz) | Det. | Meas. Rx (dBµV) | Cable Loss (dB) | Ant Factor (dB/m) | Pre Amp (dB) | HPF Loss (dB) | Duty Cycle Corr. (dB) | Field Strength (dBµV/m) | Field Strength (µV/m) | Limit (µV/m) |
|---------|-------------|------|-----------------|-----------------|-------------------|--------------|---------------|-----------------------|-------------------------|-----------------------|--------------|
| 1.      | 815.0       | Qp   | 10.3            | 4.0             | 22.3              | N/A          | N/A           | N/A                   | 36.6                    | 67.6                  | 200.0        |
| 2.      | 825.0       | Qp   | 9.8             | 4.0             | 22.5              | N/A          | N/A           | N/A                   | 36.3                    | 65.3                  | 200.0        |
| 3.      | 845.0       | Qp   | 15.8            | 4.0             | 22.5              | N/A          | N/A           | N/A                   | 42.3                    | 130.9                 | 200.0        |
| 4.      | 855.0       | Qp   | 15.4            | 4.1             | 22.5              | N/A          | N/A           | N/A                   | 42.0                    | 125.5                 | 200.0        |
| 5.      | 875.0       | Qp   | 8.0             | 4.2             | 22.3              | N/A          | N/A           | N/A                   | 34.5                    | 52.8                  | 200.0        |
| 6.      | 945.0       | Qp   | 10.2            | 4.4             | 24.3              | N/A          | N/A           | N/A                   | 38.8                    | 87.2                  | 200.0        |
| 7.      | 1830.0      | Pk   | 66.6            | 2.7             | 27.1              | 36.4         | N/A           | N/A                   | 60.0                    | 1000.0                | 5000.0       |
| 8.      | 1830.0      | Av   | 66.6            | 2.7             | 27.1              | 36.4         | N/A           | 10.9                  | 49.1                    | 283.5                 | 500.0        |
| 9.      | 2745.0      | Pk   | 54.3            | 2.6             | 29.1              | 36.1         | 0.7           | N/A                   | 50.5                    | 336.1                 | 5000.0       |
| 10.     | 2745.0      | Av   | 49.8            | 2.6             | 29.1              | 36.1         | 0.7           | N/A                   | 46.1                    | 201.8                 | 500.0        |

No further emissions were detected within 20dB of the limit.

**Notes:**

- 1 Any testing performed below 30 MHz was performed using a magnetic loop antenna in accordance with ANSI C63.10:2009 section 4.5, Table 1. For emissions below 30MHz the cable losses are assumed to be negligible.
- 2 In accordance with 15.35(b), above 1 GHz, emissions measured using a peak detector shall not exceed a level 20 dB above the average limit.
- 3 Testing was performed with the EUT orientated in three orthogonal planes and the maximum emissions level recorded. In addition, the EUT antenna was varied within its range of motion in order to maximise emissions.
- 4 For Frequencies below 1 GHz, RBW= 120 kHz, testing was performed with CISPR16 compliant test receiver with QP detector. Above 1 GHz tests were performed using a spectrum analyser using the following settings:
 

|         |               |
|---------|---------------|
| Peak    | RBW=VBW= 1MHz |
| Average | RBW=VBW= 1MHz |

The upper and lower frequency of the measurement range was decided according to 47 CFR Part 15 Clause 15.33(a) and 15.33(a) (1).

Radiated emission limits 47 CFR part 15 Clause 15.249 (a) / RSS-210 Issue 8 Annex 2 A2.9 for harmonics is 500uV/m. Radiated emission limits 47 CFR part 15 Clause 15.249 (d) / RSS-210 Issue 8 Annex 2 A2.9 for all emission outside the specified frequency band, except for harmonic, shall be attenuated by at least 50dB below the level of the fundamental or to the general radiated emission limits in 47 CFR part 15 Clause 15.209 / RSS-Gen Issue 4 Section 7.1.2 (given below), whichever is the lesser attenuation.

| Frequency of emission (MHz) | Field strength (µV/m) | Measurement Distance (m) | Field strength (dBµV/m) |
|-----------------------------|-----------------------|--------------------------|-------------------------|
| 0.009-0.490                 | 2400/F(kHz)           | 300                      | 67.6/F (kHz)            |
| 0.490-1.705                 | 24000/F(kHz)          | 30                       | 87.6/F (kHz)            |
| 1.705-30                    | 30                    | 30                       | 29.5                    |
| 30-88                       | 100                   | 3                        | 40.0                    |
| 88-216                      | 150                   | 3                        | 43.5                    |
| 216-960                     | 200                   | 3                        | 46.0                    |
| Above 960                   | 500                   | 3                        | 54.0                    |

- (a) Where results have been measured at one distance, and a signal level displayed at another, the results have been extrapolated using the following formula:

$$\text{Extrapolation (dB)} = 20 \log_{10} \left( \frac{\text{measurement distance}}{\text{specification distance}} \right)$$

- (b) The levels may have been rounded for display purposes.
- (c) The following table summarises the effect of the EUT operating mode, internal configuration and arrangement of cables / samples on the measured emission levels:

|                                                                                                                                                                                                                                                                                                                                | See (i) | See (ii) | See (iii) | See (iv) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------|-----------|----------|
| Effect of EUT operating mode on emission levels                                                                                                                                                                                                                                                                                |         | ✓        |           |          |
| Effect of EUT internal configuration on emission levels                                                                                                                                                                                                                                                                        |         | ✓        |           |          |
| Effect of Position of EUT cables & samples on emission levels                                                                                                                                                                                                                                                                  |         | ✓        |           |          |
| (i) Parameter defined by standard and / or single possible, refer to Appendix C<br>(ii) Parameter defined by client and / or single possible, refer to Appendix C<br>(iii) Parameter had a negligible effect on emission levels, refer to Appendix C<br>(iv) Worst case determined by initial measurement, refer to Appendix C |         |          |           |          |


**Appendix B:****Supporting Graphical Data**

This appendix contains graphical data obtained during testing.

Notes:


- (a) The radiated electric field emissions and conducted emissions graphical data in this appendix is preview data. For details of formal results, refer to Appendix A.
- (b) The time and date on the plots do not necessarily equate to the time of the test.
- (c) Where relevant, on power line conducted emission plots, the limit displayed is the average limit, which is stricter than the quasi peak limit.
- (d) Appendix C details the numbering system used to identify the sample and its modification state.
- (e) The plots presented in this appendix may not be a complete record of the measurements performed, but are a representative sample, relative to the final assessment.

Occupied Bandwidth and Transmitter on time




Date: 8.MAY.2015 15:01:37

20dB Bandwidth



Date: 8.MAY.2015 14:57:22


99% Bandwidth




Date: 6.MAY.2015 16:41:26

Transmitter on time in 100 ms

Radiated Spurious Emissions




30 MHz – 1 GHz



Date: 6.MAY.2015 15:38:48

1 GHz – 5 GHz




Date: 6.MAY.2015 15:39:57

5 GHz – 10 GHz


AC Power line Conducted Emissions

Conducted emissions on Mains 9kHz-30MHz ESHS10 + UH396



Transmit

Conducted emissions on Mains 9kHz-30MHz ESHS10 + UH396



Receive

**Appendix C:****Additional Test and Sample Details**

This appendix contains details of:

1. The samples submitted for testing.
2. Details of EUT operating mode(s)
3. Details of EUT configuration(s) (see below).
4. EUT arrangement (see below).

Throughout testing, the following numbering system is used to identify the sample and it's modification state:

**Sample No:** Sxx Mod w

where:

|    |                       |           |
|----|-----------------------|-----------|
| xx | = sample number       | eg. S01   |
| w  | = modification number | eg. Mod 2 |

The following terminology is used throughout the test report:

**Support Equipment (SE)** is any additional equipment required to exercise the EUT in the applicable operating mode. Where relevant SE is divided into two categories:

SE in test environment: The SE is positioned in the test environment and is not isolated from the EUT (e.g. on the table top during REFE testing).

SE isolated from the EUT: The SE is isolated via filtering from the EUT. (e.g. equipment placed externally to the ALSR during REFE testing).

**EUT configuration** refers to the internal set-up of the EUT. It may include for example:

- Positioning of cards in a chassis.
- Setting of any internal switches.
- Circuit board jumper settings.
- Alternative internal power supplies.

Where no change in EUT configuration is **possible**, the configuration is described as "single possible configuration".

**EUT arrangement** refers to the termination of EUT ports / connection of support equipment, and where relevant, the relative positioning of samples (EUT and SE) in the test environment.

For further details of the test procedures and general test set ups used during testing please refer to the related document "EMC Test Methods – An Overview", which can be supplied by TRaC Global upon request.

**C1 Test samples**

The following samples of the apparatus were submitted by the client for testing:

| Sample No. | Description           | Hardware Build Level | Software Revision Level | Identification  |
|------------|-----------------------|----------------------|-------------------------|-----------------|
| S09        | T573 hand held remote | T573-005             | V0.090                  | B00023612000130 |

The following samples of apparatus were submitted by the client as host, support or drive equipment (auxiliary equipment):

| Sample No. | Description | Identification |
|------------|-------------|----------------|
| None       |             |                |

The following samples of apparatus were supplied by TRaC Global as support or drive equipment (auxiliary equipment):

| Identification | Description |
|----------------|-------------|
| None           |             |

**C2 EUT operating mode during testing**

During testing, the EUT was exercised as described in the following tables:

| Test                              | Description of Operating Mode: Transmit                                                 |
|-----------------------------------|-----------------------------------------------------------------------------------------|
| All tests detailed in this report | EUT actively transmitting on required channels, with and without modulation as required |

### **C3 EUT Configuration Information**

The EUT was submitted for testing in one single possible configuration.

**C4 List of EUT Ports**

The tables below describe the termination of EUT ports:

Sample : S09  
Tests : All

| Port                                                   | Description of Cable Attached | Cable length | Equipment Connected |
|--------------------------------------------------------|-------------------------------|--------------|---------------------|
| EUT is a battery powered device with no external ports |                               |              |                     |

**C5 Details of Equipment Used**

| TRaC No | Equipment Type | Equipment Description     | Manufacturer | Last Cal Calibration | Calibration Period | Due For Calibration |
|---------|----------------|---------------------------|--------------|----------------------|--------------------|---------------------|
| UH004   | ESVS10         | Receiver                  | R&S          | 24/03/2015           | 12                 | 24/03/2016          |
| UH191   | CBL611/A       | Bilog                     | Chase        | 26/02/2015           | 24                 | 26/02/2017          |
| UH281   | FSU46          | Spectrum Analyser         | R&S          | 24/04/2015           | 12                 | 24/04/2016          |
| L138    | 3115           | 1-18GHz Horn              | EMCO         | 17/10/2013           | 24                 | 17/10/2015          |
| L572    | 8449B          | Pre Amp                   | Agilent      | 10/02/2015           | 12                 | 10/02/2016          |
| REF940  | ATS            | Radio Chamber - PP        | Rainford EMC | 08/09/2014           | 24                 | 08/09/2016          |
| REF940  | ATS            | IC Reg Radio Chamber - PP | Rainford EMC | 19/11/2014           | 36                 | 19/11/2017          |

**Appendix D:**

**Additional Information**

This report contains no additional information.

**Appendix E:****Calculation of the duty cycle correction factor**

Using a spectrum analyser in zero span mode, centred on the fundamental carrier frequency with a RBW of 1MHz and a video Bandwidth of 1MHz the sweep time is set accordingly to capture the pulse train. The transmit pulse widths and period is measured. Any applicable plot will be contained in appendix B of this test report.

If the pulse train is less than 100 ms, including blanking intervals, the duty cycle is calculated by averaging the sum of the pulse widths over one complete pulse train. However if the pulse train exceeds 100ms then the duty cycle is calculated by averaging the sum of the pulse widths over the 100ms width with the highest average value. (The duty cycle is the value of the sum of the pulse widths in one period (or 100 ms), divided by the length of the period (or 100 ms). The duty cycle correction factor is then expressed in dB and the peak emissions adjusted accordingly to give an average value of the emission.

Correction factor (dB) =  $20 \times \text{Log}_{10}$  (Calculated Duty Cycle)

For the pulse train period greater than 100 ms

Duty cycle = (the sum of the highest average value pulse widths over 100ms) / 100 ms

e.g.

$$= \frac{7.459\text{ms}}{100\text{ms}} = 0.07459$$

0.07459 Or 7.459 %

So

Correction factor (dB) =  $20 \times \text{Log}_{10}$  (0.07459) = -22.54 dB

Duty cycle correction may not be applicable / required by the device covered in this report. The correction factor above is for example of how the correction is calculated. Any applicable duty cycle used will be recorded in the relevant results sections of this report.

## **Appendix F:**

## **Photographs and Figures**


The following photographs were taken of the test samples:

1. Radiated electric field emissions arrangement: overview
2. Radiated electric field emissions arrangement: close up

Photograph 1



Photograph 2



**Appendix G:****General SAR test reduction and exclusion guidance****KDB 447498**

## Section 4.3 General SAR test reduction and exclusion guidance

For Standalone SAR exclusion consideration, when SAR Exclusion Threshold requirement in KDB 447498 is satisfied, standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.

The SAR Test Exclusion Threshold for 100 MHz to 6 GHz will be determined as follows.

$$\text{SAR Exclusion Threshold (SARET)} = \text{Step 1} + \text{Step 2}$$

**Step 1**

$$NT = [(MP/TSD^A) * \sqrt{f_{GHz}}]$$

|                  |   |                                                                                |
|------------------|---|--------------------------------------------------------------------------------|
| NT               | = | Numeric Threshold (3.0 for 1-g SAR and 7.5 for 10-g SAR)                       |
| MP               | = | Max Power of channel (mW) (including tune-up tolerance)                        |
| TSD <sup>A</sup> | = | Min Test separation Distance or 50mm (whichever is lower) = 5mm (in this case) |

We can transpose this formula to allow us to find the maximum power of a channel allowed and compare this to the measured maximum power.

$$= [(NT \times TSD^A) / \sqrt{f_{GHz}}]$$

For Distances Greater than 50 mm Step 2 applies

**Step 2**

$$(TSD^B - 50\text{mm}) * 10$$

Where:

$$TSD^B = \text{Min Test separation Distance (mm)} = 50$$

**Note:** Step 2 doesn't apply here as the TSD<sup>A</sup> is less than 50 mm

**Operating Frequency 915 MHz**

$$\begin{aligned} \text{SARET} &= [(3.0 \times 5) / \sqrt{0.915}] \\ \text{SARET} &= 15.68 \text{ mW} \end{aligned}$$

| Channel Frequency (MHz) | EIRP (mW) | SAR Exclusion Threshold (mW) | SAR Evaluation |
|-------------------------|-----------|------------------------------|----------------|
| 915.0                   | 0.63      | 15.68                        | Not Required   |

**Therefore standalone SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.**

**Appendix H:****MPE Calculation****Prediction of MPE limit at a given distance**

For purposes of these requirements mobile devices are defined by the FCC and Industry Canada as transmitters designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between radiating structures and the body of the user or nearby persons. These devices are normally evaluated for exposure potential with relation to the MPE limits. As the 20cm separation specified under FCC and Industry Canada rules may not be achievable under normal operation of the EUT, an RF exposure calculation is needed to show the minimum distance required to be less than the power density limit, as required under FCC and Industry Canada rules.

Equation from IEEE C95.1

$$S = \frac{EIRP}{4\pi R^2} \text{ re - arranged } R = \sqrt{\frac{EIRP}{S 4\pi}}$$

Where:

S = power density

R = distance to the centre of radiation of the antenna

EIRP = EUT Maximum power

Result

| Prediction Frequency (MHz) | Maximum EIRP (mW) | Power density limit (S) (mW/cm <sup>2</sup> ) | Distance (R) cm required to be less than power density limit |
|----------------------------|-------------------|-----------------------------------------------|--------------------------------------------------------------|
| 915.0                      | 0.63              | 0.61                                          | 0.29                                                         |

