



RADIO TEST REPORT

Applicant	:	XGIMI Technology Co., Ltd
Address of Applicant	:	Building No.4, Zone A, No.1129, Shijicheng Road, Chengdu High-tech Zone, Sichuan Pilot Free Trade Zone, China
Manufacturer	:	XGIMI Technology Co., Ltd
Address of Manufacturer	:	Building No.4, Zone A, No.1129, Shijicheng Road, Chengdu High-tech Zone, Sichuan Pilot Free Trade Zone, China
Equipment under Test	:	Bluetooth Remote Control
Model No.	:	B975C
FCC ID	:	2AFENB975C
IC	:	27045-B975C
Test Standard(s)	:	FCC Rules and Regulations Part 15 Subpart C, ANSI C63.10-2020, RSS-247 Issue 4 July 24, 2025, RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021), ANSI C63 10-2020+Cor.1-2023+C63.10a- 2024+Errata to C63.10a-2024
Report No.	:	DDT-RE25093012-5E01
Issue Date	:	2025/12/02
Issue By	:	Guangdong Dongdian Testing Service Co., Ltd. Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808

REPORT

Table of Contents

1.	Summary of Test Results	6
2.	General Test Information.....	7
2.1.	Description of EUT	7
2.2.	Accessories of EUT	8
2.3.	Block diagram of EUT configuration for test.....	8
2.4.	Decision of final test mode	9
2.5.	Deviations of test standard	9
2.6.	Test environment conditions	9
2.7.	Test laboratory	9
2.8.	Measurement uncertainty	10
3.	Equipment Used During Conductive Test	11
4.	6 dB Bandwidth	12
4.1.	Block diagram of test setup	12
4.2.	Limits	12
4.3.	Test procedure	12
4.4.	Test result.....	13
4.5.	Test graphs	14
5.	99% Bandwidth	16
5.1.	Block diagram of test setup	16
5.2.	Limits	16
5.3.	Test procedure	16
5.4.	Test result.....	17
5.5.	Test graphs	18
6.	Maximum Peak Output Power.....	20
6.1.	Block diagram of test setup	20
6.2.	Limits	20
6.3.	Test procedure	20
6.4.	Test result.....	21
6.5.	Test graphs	22
7.	Power Spectral Density	24
7.1.	Block diagram of test setup	24
7.2.	Limits	24
7.3.	Test procedure	24
7.4.	Test result.....	25
7.5.	Test graphs	26
8.	Band Edge Compliance (Conducted Method)	28

8.1.	Block diagram of test setup	28
8.2.	Limits	28
8.3.	Test procedure	28
8.4.	Test result.....	29
8.5.	Test graphs	30
9.	RF Conducted Spurious Emissions.....	32
9.1.	Block diagram of test setup	32
9.2.	Limits	32
9.3.	Test procedure	32
9.4.	Test result.....	33
9.5.	Test graphs	34
10.	Antenna Requirements.....	40
10.1.	Limit.....	40
10.2.	Result	40
11.	Radiated Emission	41
11.1.	Test equipment.....	41
11.2.	Block diagram of test setup	42
11.3.	Limits	43
11.4.	Assistant equipment used for test	45
11.5.	Test procedure	45
11.6.	Test result.....	46
11.7.	Test data	47
12.	Band Edge Compliance.....	63
12.1.	Test equipment.....	63
12.2.	Block diagram of test setup	63
12.3.	Limits	63
12.4.	Assistant equipment used for test	64
12.5.	Test procedure	64
12.6.	Test result.....	64
12.7.	Test data	65
13.	Test Setup Photograph	73
14.	Photos of the EUT	75

Test Report Declare

Applicant	:	XGIMI Technology Co., Ltd
Address of Applicant	:	Building No.4, Zone A, No.1129, Shijicheng Road, Chengdu High-tech Zone,Sichuan Pilot Free Trade Zone,China
Equipment under Test	:	Bluetooth Remote Control
Model No.	:	B975C
Manufacturer	:	XGIMI Technology Co., Ltd
Address of Manufacturer	:	Building No.4, Zone A, No.1129, Shijicheng Road, Chengdu High-tech Zone, Sichuan Pilot Free Trade Zone,China

Test Standard Used:
FCC Rules and Regulations Part 15 Subpart C,
ANSI C63.10-2020,
RSS-247 Issue 4 July 24, 2025,
RSS-Gen Issue 5, Apr. 2018, Amendment 2 (February 2021),
ANSI C63 10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024

We Declare:
The equipment described above is tested by Guangdong Dongdian Testing Service Co., Ltd. and in the configuration tested the equipment complied with the standards specified above. The test results are contained in this test report and Guangdong Dongdian Testing Service Co., Ltd. is assumed of full responsibility for the accuracy and completeness of these tests.

Report No.:	DDT-RE25093012-5E01		
Date of Receipt:	2025/10/14	Date of Test:	2025/10/14 - 2025/11/14

Created: Chen Ziqin	Reviewed: Zoe Peng	Approved: Ella Gong
		
2025/12/01	2025/12/01	2025/12/02

Note: This report applies to above tested sample only. This report shall not be reproduced in parts without written approval of Guangdong Dongdian Testing Service Co., Ltd.

Revision History

Version	Revision Content	Issue Date	Approved
V0	Initial issue	2025/12/02	Ella Gong

1. Summary of Test Results

No.	Test Parameter	Clause No.	Condition	Result
1	6 dB Bandwidth and 99% Bandwidth	47 CFR Part 15 15.247(a)(2), RSS-247 clause 6.3.1, RSS-Gen clause 6.7	/	Pass
2	Peak Output Power	47 CFR Part 15 15.247(b)(3), RSS-247 clause 6.3.2	/	Pass
3	Power Spectral Density	47 CFR Part 15 15.247(e), RSS-247 clause 6.3.1	/	Pass
4	RF Conducted Spurious Emissions	47 CFR Part 15 15.247(d), RSS-247 clause 6.6	/	Pass
5	Radiated Emission	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
6	Band Edge Compliance	47 CFR Part 15 15.205, 47 CFR Part 15 15.209, 47 CFR Part 15 15.247(d), RSS-247 clause 6.6, RSS-Gen clause 8.9, RSS-Gen clause 8.10	/	Pass
7	Antenna Requirement	47 CFR Part 15 15.203, RSS-Gen clause 6.8	/	Pass
8	Power Line Conducted Emissions	47 CFR Part 15 15.207(a), RSS-Gen clause 8.8	/	N/A
Note: N/A is an abbreviation for Not Applicable, and means this item is not applicable for this device or no need to test according to standard.				

2. General Test Information

2.1. Description of EUT

EUT Name	: Bluetooth Remote Control
Model Number	: B975C
Difference of model number	: /
EUT Function Description	: Please reference user manual of this device
Power Supply	: DC 3V
Antenna Type	: PCB Antenna
Max Antenna Gain(dBi)	: -1.1

Radio Specification	: Bluetooth LE
Operation Frequency	: 2402 MHz to 2480 MHz
Modulation	: GFSK

Bluetooth LE 1Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468
6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		
Bluetooth LE 2Mbps Channel information					
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	14	2430	28	2458
1	2404	15	2432	29	2460
2	2406	16	2434	30	2462
3	2408	17	2436	31	2464
4	2410	18	2438	32	2466
5	2412	19	2440	33	2468

6	2414	20	2442	34	2470
7	2416	21	2444	35	2472
8	2418	22	2446	36	2474
9	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454	/	
13	2428	27	2456	/	
The channels denoted with the grey background are excluded, because they are primary advertising channel only for the Bluetooth LE 1Mbps according to the Bluetooth Core Specification.					

Note: The above EUT information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications or User's Manual. The above Antenna information is declared by manufacturer and for more detailed features description please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

“☑” means to be chosen or applicable; “☐” means don't to be chosen or not applicable; This note applies to entire report.

2.2. Accessories of EUT

Accessories	Manufacturer	Model number	Description
/	/	/	/

2.3. Block diagram of EUT configuration for test



2.4. Decision of final test mode

According pre-test, the worst test modes were reported as below:

Test software: RTL8762x_RFTTestTool.exe

The test software was used to control EUT work in Continuous Tx mode, and select test channel, wireless mode as below table:

The pathloss of external cable: 0.5dB (According to the manufacturer's claims)

Tested mode, Tx Power Setting, Channel, and Frequency			
Mode	Setting Tx Power	Channel	Frequency (MHz)
GFSK 1M	0XA0	CH0	2402
	0XA0	CH19	2440
	0XA0	CH39	2480
GFSK 2M	0XA0	CH1	2404
	0XA0	CH19	2440
	0XA0	CH38	2478

2.5. Deviations of test standard

No deviation.

2.6. Test environment conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature range:	+15°C to +35 °C
Humidity range:	20% to 75%
Pressure range:	86 kPa to106 kPa

Note: The specific temperature and humidity information of each test item refers to the temperature and humidity record in the corresponding test data.

2.7. Test laboratory

Guangdong Dongdian Testing Service Co., Ltd.

Add.: Unit 2, Building 1, No. 17, Zongbu 2nd Road, Songshan Lake Park, Dongguan, Guangdong, China, 523808.

Tel.: +86-0769-38826678, <http://www.dgddt.com>, Email: ddt@dgddt.com.

CNAS Accreditation No. L6451; A2LA Accreditation Number: 3870.01

FCC Designation Number: CN1182, Test Firm Registration Number: 540522

Innovation, Science and Economic Development Canada Site Registration Number: 10288A

Conformity Assessment Body identifier: CN0048

VCCI facility registration number: C-20087, T-20088, R-20123, R-20240, G-20118

2.8. Measurement uncertainty


Test Item	Uncertainty
Bandwidth	1.1%
Peak Output Power (Conducted) (Spectrum analyzer)	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Peak Output Power (Conducted) (Power Sensor)	0.74 dB
Power Spectral Density	0.74 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.38 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$)
Frequencies Stability	6.7×10^{-8} (Antenna couple method) 5.5×10^{-8} (Conducted method)
Conducted spurious emissions	0.86 dB ($10 \text{ MHz} \leq f < 3.6 \text{ GHz}$); 1.40 dB ($3.6 \text{ GHz} \leq f < 8 \text{ GHz}$) 1.66 dB ($8 \text{ GHz} \leq f < 26.5 \text{ GHz}$)
Uncertainty for radio frequency (RBW < 20 kHz)	3×10^{-8}
Temperature	0.4 °C
Humidity	2 %
Uncertainty for Radiation Emission test (9 kHz – 30 MHz)	3.44 dB
Uncertainty for Radiation Emission test (30 MHz - 1 GHz)	4.70 dB (Antenna Polarize: V) 4.84 dB (Antenna Polarize: H)
Uncertainty for Radiation Emission test (1 GHz - 40 GHz)	4.10 dB (1 - 6 GHz) 4.40 dB (6 GHz - 18 GHz) 3.54 dB (18 GHz - 26 GHz) 4.30 dB (26 GHz - 40 GHz)
Uncertainty for Power line conduction emission test	3.34dB (150KHz-30MHz) 3.72dB (9KHz-150KHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

3. Equipment Used During Conductive Test

Equipment	Manufacturer	Model No.	Serial Number	Due Date
☑RF Connected Test (RF Measurement System 4#)				
Signal &Spectrum Analyzer	R&S	FSV3044	101173	2026/03/28
Wideband Radio Communication Tester	R&S	CMW500	168801	2026/03/28
MXG Vector Signal Generator	Agilent	N5182A	MY48180737	2026/03/28
PSG Vector Signal Generator	Agilent	E8267D	US49060192	2026/08/10
RF Control Unit	Tonscend	JS0806-2	21I8060485	2026/03/28
TEMP&HUMI Programmable Chamber	ZHIXIANG	ZXGDJS-150L	ZX170110-A	2026/03/28
Test Software	Tonscend	JS1120-3	V3.6.21	N/A

4. 6 dB Bandwidth

4.1. Block diagram of test setup



4.2. Limits

For direct sequence systems, the minimum 6 dB bandwidth shall be at least 500 kHz

4.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.8.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for 6 dB Bandwidth:

RBW:	100 kHz
VBW:	$\geq [3 \times \text{RBW}]$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 6 dB bandwidth of signal, and record the results in the report.


4.4. Test result

Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Test Mode	Antenna	Frequency [MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	0.70	2401.65	2402.35	0.5	PASS
		2440	0.72	2439.64	2440.36	0.5	PASS
		2480	0.71	2479.64	2480.35	0.5	PASS
BLE_2M	Ant1	2404	1.37	2403.32	2404.69	0.5	PASS
		2440	1.36	2439.33	2440.70	0.5	PASS
		2478	1.38	2477.32	2478.70	0.5	PASS


4.5. Test graphs





5. 99% Bandwidth

5.1. Block diagram of test setup



5.2. Limits

Just for Report.

5.3. Test procedure

- (1) The test according to ANSI C63.10 clause 6.9.3.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously
- (4) Use the following spectrum analyzer settings for the 99% Bandwidth:


RBW:	1% to 5% of the OBW
VBW:	approximately three times RBW
Span:	between 1.5 times and 5.0 times the OBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, measure the 99% bandwidth of signal, and record the results in the report.


5.4. Test result

Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Test Mode	Antenna	Frequency [MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit [MHz]	Verdict
BLE_1M	Ant1	2402	1.0472	2401.4759	2402.5231	---	---
		2440	1.0525	2439.4710	2440.5236	---	---
		2480	1.0484	2479.4721	2480.5205	---	---
BLE_2M	Ant1	2404	2.0620	2402.9632	2405.0252	---	---
		2440	2.0717	2438.9572	2441.0290	---	---
		2478	2.0654	2476.9558	2479.0212	---	---


5.5. Test graphs





6. Maximum Peak Output Power

6.1. Block diagram of test setup



6.2. Limits

For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. If transmitting antennas of directional gain greater than 6dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi, the e.i.r.p shall not exceed 4W.

6.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.9.1.1.
- (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
- (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
- (4) Use the following spectrum analyzer settings for the maximum peak output power measurement:


RBW:	≥DTS bandwidth
VBW:	≥3 x RBW
Span	≥3 x RBW
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (5) Allow the trace to stabilize, use peak marker function to determine the peak amplitude level.


6.4. Test result

Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Test Mode	Antenna	Frequency [MHz]	Conducted Peak Power[dBm]	Conducted Limit[dBm]	EIRP[dBm]	EIRP Limit[dBm]	Verdict
BLE_1M	Ant1	2402	2.23	≤30	1.13	≤36	PASS
		2440	1.31	≤30	0.21	≤36	PASS
		2480	1.45	≤30	0.35	≤36	PASS
BLE_2M	Ant1	2404	2.31	≤30	1.21	≤36	PASS
		2440	1.31	≤30	0.21	≤36	PASS
		2478	1.57	≤30	0.47	≤36	PASS


6.5. Test graphs





7. Power Spectral Density

7.1. Block diagram of test setup



7.2. Limits

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

7.3. Test procedure

- (1) The test according to ANSI C63.10 clause 11.10.2.
 - (2) Connect EUT's antenna output to spectrum analyzer by RF cable, the path loss was compensated to the results.
 - (3) Set the EUT as maximum power setting and enable the EUT transmit continuously.
 - (4) Use the following spectrum analyzer settings for Power Spectral Density measurement:


Center frequency	DTS Channel center frequency
RBW:	$3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$
VBW:	$\geq 3\text{RBW}$
Span	1.5 times the DTS bandwidth
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
 - (5) Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.


7.4. Test result

Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Test Mode	Antenna	Frequency [MHz]	Result [dBm/3kHz]	Limit [dBm/3kHz]	Verdict
BLE_1M	Ant1	2402	-9.78	≤8.00	PASS
		2440	-10.25	≤8.00	PASS
		2480	-10.29	≤8.00	PASS
BLE_2M	Ant1	2404	-12.64	≤8.00	PASS
		2440	-12.87	≤8.00	PASS
		2478	-13.31	≤8.00	PASS


7.5. Test graphs





8. Band Edge Compliance (Conducted Method)

8.1. Block diagram of test setup



8.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

8.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Then mark the maximum amplitude of all unwanted emissions outside of the authorized frequency band.


8.4. Test result

Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Mode	Frequency [MHz]	Measured Range	Verdict
GFSK 1M	2402	2.310 GHz - 2.410 GHz	Pass
	2480	2.470 GHz - 2.500 GHz	Pass
GFSK 2M	2404	2.310 GHz - 2.410 GHz	Pass
	2478	2.470 GHz - 2.500 GHz	Pass


8.5. Test graphs





9. RF Conducted Spurious Emissions

9.1. Block diagram of test setup



9.2. Limits

In any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

9.3. Test procedure

- (1) Connect EUT's antenna output to spectrum analyzer by RF cable.
- (2) Establish a reference level by using the following procedure:

Center frequency	Test frequency
RBW:	100 kHz
VBW:	300 kHz
Span	Wide enough to capture the peak level of the in-band emission
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold
- (3) Allow the trace to stabilize, use the peak marker function to determine the maximum peak power level to establish the reference level.
- (4) Set the spectrum analyzer as follows:

RBW:	100 kHz
VBW:	300 kHz
Span	Encompass frequency range to be measured
Number of measurement points	$\geq \text{Span/RBW}$
Detector Mode:	Peak
Sweep time:	Auto
Trace mode	Max hold


Allow the trace to stabilize, use the peak marker function to determine the maximum amplitude of all unwanted emissions outside of the authorized frequency band

9.4. Test result


Test Engineer:	Huang Yanwen	Test Site:	RF Measurement system 4#
Ambient Condition:	26.8°C,47.9%RH	Test Date:	2025.11.14-2025.11.14
Test Power Supply:	DC 3.3V	Sample Number:	S25093012-006

Mode	Frequency [MHz]	Verdict
GFSK 1M	2402	Pass
	2440	Pass
	2480	Pass
GFSK 2M	2404	Pass
	2440	Pass
	2478	Pass

9.5. Test graphs













10. Antenna Requirements

10.1. Limit

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6 dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For intentional device, according to RSS-Gen issue 5 section 6.8.

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

10.2. Result


The antenna used for this product as Antenna information described in section 2.1 of the report, and there is no other antenna than that furnished by the responsible party shall be used with the device.


11. Radiated Emission

11.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

11.2. Block diagram of test setup





11.3. Limits

(1) FCC 15.205 Restricted frequency band

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.1772&4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.2072&4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

²Above 38.6

RSS-Gen section 8.10 Restricted frequency bands*

MHz	MHz	MHz	GHz
0.090-0.110	12.51975-12.52025	240-285	3.5-4.4
0.495-0.505	12.57675-12.57725	322-335.4	4.5-5.15
2.1735-2.1905	13.36-13.41	399.9-410	5.35-5.46
3.020-3.026	16.42-16.423	608-614	7.25-7.75
4.125-4.128	16.69475-16.69525	960-1427	8.025-8.5
4.1772&4.17775	16.80425-16.80475	1435-1626.5	9.0-9.2
4.2072&4.20775	25.5-25.67	1645.5-1646.5	9.3-9.5
5.677-5.683	37.5-38.25	1660-1710	10.6-12.7
6.215-6.218	73-74.6	1718.8-1722.2	13.25-13.4
6.26775-6.26825	74.8-75.2	2200-2300	14.47-14.5
6.31175-6.31225	108-138	2310-2390	15.35-16.2
8.291-8.294	149.9-150.05	2483.5-2500	17.7-21.4
8.362-8.366	156.52475-156.52525	2655-2900	22.01-23.12
8.37625-8.38675	156.7-156.9	3260-3267	23.6-24.0
8.41425-8.41475	162.0125-167.17	3332-3339	31.2-31.8
12.29-12.293	167.72-173.2	3345.8-3358	36.43-36.5
			Above 38.6

* Certain frequency bands listed in table and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

(2) FCC 15.209 Limit & RSS-Gen section 8.9 Limit

FREQUENCY	DISTANCE	FIELD STRENGTHS LIMIT	
MHz	Meters	uV/m	dBuV/m
0.009 ~ 0.490	300	2400/F(kHz)	67.6-20log(F)
0.490 ~ 1.705	30	24000/F(kHz)	87.6-20log(F)
1.705 ~ 30.0	30	30	29.54
30~88	3	100	40.0
88~216	3	150	43.5
216~960	3	200	46.0
960~1000	3	500	54.0
Above 1000	3	74.0 dBuV/m(Peak)	
		54.0 dBuV/m(Average)	

Note:

(1) The emission limits shown in the above table are based on measurements employing a CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz and above 1000 MHz, radiated emissions limits in these three bands are based on measurements employing an average detector.

(2) At frequencies below 30 MHz, measurement may be performed at a distance closer than that specified, and the limit at closer measurement distance can be extrapolated by below formula:

$$\text{Limit}_{3m}(\text{dBuV/m}) = \text{Limit}_{30m}(\text{dBuV/m}) + 40\log(30m/3m)$$

(3) Limit for this EUT

The emissions appearing within 15.205 restricted frequency bands shall not exceed the limits shown in 15.209, and the emissions appearing within RSS-Gen section 8.10 Restricted frequency bands shall not exceed the limits shown in RSS-Gen section 8.9, all the other emissions shall be at least 20 dB below the fundamental emissions or comply with 15.209 limits and RSS-Gen section 8.9 limits.

11.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

11.5. Test procedure

(1) EUT was placed on a non-metallic table, 80 cm above the ground plane inside a semi-anechoic chamber for below 1G and 150 cm above the ground plane inside a fully-anechoic chamber for above 1G.

(2) Test antenna was located 3 m from the EUT on an adjustable mast, and the antenna used as below table.

Test frequency range	Test antenna used	Test antenna distance
9 kHz - 30 MHz	Active Loop antenna	3 m
30 MHz - 1 GHz	Trilog Broadband Antenna	3 m
1 GHz - 18 GHz	Double Ridged Horn Antenna(1 GHz-18 GHz)	3 m
18 GHz - 40 GHz	Horn Antenna(18 GHz-40 GHz)	1 m

According to ANSI C63.10 clause 6.4.6 and 6.5.3, for measurements below 30 MHz, Antenna was located 3 m from EUT, the loop antenna was positioned in three antenna orientations (parallel, perpendicular, and round-parallel), for each measurement antenna alignment, the EUT shall be rotated through 0° to 360° on a turntable, and the lowest height of the magnetic antenna shall be 1 m above the ground. For measurement above 30 MHz, the Trilog Broadband Antenna or Horn Antenna was located 3 m from EUT, Measurements were made with the antenna positioned in both the horizontal and vertical planes of Polarization, and the measurement antenna was varied from 1 m to 4 m. in height above the reference ground plane to obtain the maximum signal strength.

(3) Below pre-scan procedure was first performed in order to find prominent frequency spectrum radiated emissions from 9 kHz to 25 GHz:

(a) Scanning the peak frequency spectrum with the antenna specified in step (3), and the EUT was rotated 360 degree, the antenna height was varied from 1 m to 4 m (Except loop antenna, it's fixed 1 m above ground.)

(b) Change work frequency or channel of device if practicable.

(c) Change modulation type of device if practicable.

(d) Change power supply range from 85% to 115% of the rated supply voltage

(e) Rotated EUT though three orthogonal axes to determine the attitude of EUT arrangement produces highest emissions.

Spectrum frequency from 9 kHz to 25 GHz (tenth harmonic of fundamental frequency) was investigated, and no any obvious emission were detected from 18 GHz to 25 GHz, so below final test was performed with frequency range from 9 kHz to 18 GHz.

(4) For final emissions measurements at each frequency of interest, the EUT was rotated and the antenna height was varied between 1 m and 4 m in order to maximize the emission. Measurements in both horizontal and vertical polarities were made and the data was recorded. In order to find the maximum emission, the relative positions of equipment and all of the interface cables were changed according to ANSI C63.10 on Radiated Emission test.

(5) The emissions from 9 kHz to 1 GHz were measured based on CISPR QP detector except for the frequency bands 9 - 90 kHz, 110 - 490 kHz, for emissions from 9 kHz - 90 kHz, 110 kHz - 490 kHz and above 1 GHz were measured based on average detector, for emissions above 1 GHz, peak emissions also be measured and need comply with Peak limit.

(6) The emissions from 9 kHz to 1 GHz, QP or average values were measured with EMI receiver with below RBW.

Frequency band	RBW
9 kHz - 150 kHz	200 Hz
150 kHz - 30 MHz	9 kHz
30 MHz - 1 GHz	120 kHz

(7) For emissions above 1GHz, both Peak and Average level were measured with Spectrum Analyzer, and the RBW is set at 1 MHz, VBW is set at 3 MHz for Peak measure; According ANSI C63.10 clause 4.1.5.2.2 procedure for average measure.

(8) For portable device, X axis, Y axis, Z axis are tested, and worse setup is reported.

(9) According exploratory test, the emission levels are 20 dB below the limit detected from 9 kHz to 30 MHz and 18 GHz to 25 GHz, so the final test was performed with frequency range from 30 MHz to 18 GHz and recorded in below.

(10) For 30 MHz ~ 25 GHz: (Scan with all mode, the worst case is reported)

(11) For emissions below 1 GHz, according exploratory explorer test, when change Tx mode and channel, have no distinct influence on emissions level, so for emissions below 1 GHz, the final test was only performed with EUT working in worst mode.

11.6. Test result

PASS. (See below detailed test result)

11.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-07

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Below 1G\1

Memo:

Sample Numbel:S25093012-006



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	41.564	40.62	12.93	3.93	25.18	40.00	14.82	QP	Horizontal
2	50.368	37.12	13.25	3.98	22.05	40.00	17.95	QP	Horizontal
3	57.627	31.23	12.89	4.04	15.86	40.00	24.14	QP	Horizontal
4	72.223	36.74	9.43	4.17	18.04	40.00	21.96	QP	Horizontal
5	107.483	23.93	11.24	4.34	7.20	43.50	36.30	QP	Horizontal
6	970.980	24.95	21.96	7.29	22.73	54.00	31.27	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-07

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Below 1G\2

Memo:

Sample Numbler:S25093012-006



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	32.066	36.34	10.90	3.81	18.75	40.00	21.25	QP	Vertical
2	41.652	35.63	12.96	3.93	20.22	40.00	19.78	QP	Vertical
3	53.088	39.11	13.22	4.00	24.03	40.00	15.97	QP	Vertical
4	72.528	38.7	9.34	4.18	19.92	40.00	20.08	QP	Vertical
5	103.634	30.01	10.75	4.32	12.78	43.50	30.72	QP	Vertical
6	984.002	25.92	22.52	7.32	24.36	54.00	29.64	QP	Vertical

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.
3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-07

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Below 1G\3

Memo:

Sample Numbler:S25093012-006



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.232	40.17	10.45	3.78	22.10	40.00	17.90	QP	Horizontal
2	41.564	40.36	12.93	3.93	24.92	40.00	15.08	QP	Horizontal
3	50.192	37.81	13.32	3.98	22.81	40.00	17.19	QP	Horizontal
4	57.385	32.92	12.82	4.04	17.48	40.00	22.52	QP	Horizontal
5	71.971	35.42	9.50	4.17	16.79	40.00	23.21	QP	Horizontal
6	143.986	28.43	8.61	4.56	9.26	43.50	34.24	QP	Horizontal

Note:

1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-11-07

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Below 1G\4

Memo:

Sample Numbler:S25093012-006



Final Data List									
NO.	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	30.126	37.11	10.47	3.78	19.06	40.00	20.94	QP	Vertical
2	41.681	36.48	12.97	3.93	21.08	40.00	18.92	QP	Vertical
3	53.875	38.62	13.38	4.01	23.71	40.00	16.29	QP	Vertical
4	72.528	38.59	9.34	4.18	19.81	40.00	20.19	QP	Vertical
5	99.504	28.11	11.70	4.30	11.81	43.50	31.69	QP	Vertical
6	902.695	24.82	22.12	7.12	22.18	46.00	23.82	QP	Vertical

Note:


1. Result Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.

3. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-31 **Tested By:** Li Xiongbin
EUT: Bluetooth Remote Control **Model Number:** B975C
Test Mode: TX BLE1M 2402MHz Mode **Power Supply:** Battery
Condition: Temp:23.8°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\1
Memo: Sample Numbler:S25093012-006

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3810.100	46.84	30.78	4.55	-39.62	42.55	74.00	31.45	PK	Horizontal
2	4558.100	46.67	31.99	4.95	-39.76	43.85	74.00	30.15	PK	Horizontal
3	4804.600	53.12	32.17	5.12	-39.78	50.63	74.00	23.37	PK	Horizontal
4	9160.000	42.45	38.88	6.78	-38.78	49.33	74.00	24.67	PK	Horizontal
5	11392.100	41.56	39.71	7.57	-39.60	49.24	74.00	24.76	PK	Horizontal
6	16002.500	40.73	38.00	8.62	-39.60	47.75	74.00	26.25	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\2

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3884.900	46.60	30.72	4.56	-39.65	42.23	74.00	31.77	PK	Vertical
2	4804.600	52.13	32.17	5.12	-39.78	49.64	74.00	24.36	PK	Vertical
3	5411.500	46.22	32.88	5.40	-39.72	44.78	74.00	29.22	PK	Vertical
4	7497.400	44.09	36.88	5.79	-39.85	46.91	74.00	27.09	PK	Vertical
5	9017.200	41.52	38.64	6.80	-38.62	48.34	74.00	25.66	PK	Vertical
6	11412.500	42.50	39.68	7.58	-39.60	50.16	74.00	23.84	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2440MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\3

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3793.100	46.66	30.75	4.54	-39.62	42.33	74.00	31.67	PK	Horizontal
2	4082.100	46.42	31.14	4.63	-39.71	42.48	74.00	31.52	PK	Horizontal
3	4881.100	51.98	33.02	5.17	-39.79	50.38	74.00	23.62	PK	Horizontal
4	7602.800	44.35	36.24	5.83	-39.84	46.58	74.00	27.42	PK	Horizontal
5	9032.500	42.07	38.76	6.80	-38.64	48.99	74.00	25.01	PK	Horizontal
6	12060.200	42.94	39.30	7.81	-39.55	50.50	74.00	23.50	PK	Horizontal

Note:


1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date: 2025-10-31 **Tested By:** Li Xiongbin
EUT: Bluetooth Remote Control **Model Number:** B975C
Test Mode: TX BLE1M 2440MHz Mode **Power Supply:** Battery
Condition: Temp:23.8°C;Humi:54.6% **Test Site:** DDT 3# Chamber
File Path: d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\4
Memo: Sample Numbler:S25093012-006

**Suspected Data List**

NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3810.100	47.26	30.78	4.55	-39.62	42.97	74.00	31.03	PK	Vertical
2	4881.100	50.59	33.02	5.17	-39.79	48.99	74.00	25.01	PK	Vertical
3	7488.900	43.99	36.83	5.79	-39.85	46.76	74.00	27.24	PK	Vertical
4	9029.100	42.77	38.73	6.80	-38.63	49.67	74.00	24.33	PK	Vertical
5	11509.400	42.54	38.78	7.61	-39.60	49.33	74.00	24.67	PK	Vertical
6	13391.300	41.81	40.07	8.02	-38.84	51.06	74.00	22.94	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\5

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3803.300	47.63	30.86	4.54	-39.62	43.41	74.00	30.59	PK	Horizontal
2	4111.000	47.32	31.19	4.65	-39.71	43.45	74.00	30.55	PK	Horizontal
3	4959.300	49.96	33.08	5.22	-39.80	48.46	74.00	25.54	PK	Horizontal
4	7441.300	44.12	36.62	5.77	-39.86	46.65	74.00	27.35	PK	Horizontal
5	8078.800	43.13	37.22	6.04	-39.71	46.68	74.00	27.32	PK	Horizontal
6	12208.100	42.95	39.22	7.81	-39.43	50.55	74.00	23.45	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\6

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4138.200	46.31	31.41	4.66	-39.71	42.67	74.00	31.33	PK	Vertical
2	4602.300	46.99	31.41	4.98	-39.76	43.62	74.00	30.38	PK	Vertical
3	4961.000	49.57	33.08	5.22	-39.80	48.07	74.00	25.93	PK	Vertical
4	7415.800	44.00	36.67	5.77	-39.86	46.58	74.00	27.42	PK	Vertical
5	9137.900	42.47	38.76	6.78	-38.75	49.26	74.00	24.74	PK	Vertical
6	12293.100	42.23	39.39	7.81	-39.37	50.06	74.00	23.94	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2404MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\7

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4151.800	48.34	31.48	4.67	-39.72	44.77	74.00	29.23	PK	Horizontal
2	4806.300	52.07	32.20	5.12	-39.78	49.61	74.00	24.39	PK	Horizontal
3	7410.700	43.93	36.68	5.76	-39.86	46.51	74.00	27.49	PK	Horizontal
4	9144.700	42.60	38.89	6.78	-38.76	49.51	74.00	24.49	PK	Horizontal
5	11405.700	41.66	39.74	7.57	-39.60	49.37	74.00	24.63	PK	Horizontal
6	15608.100	39.25	38.96	8.45	-39.17	47.49	74.00	26.51	PK	Horizontal

Note:

- Level = Reading + Cable loss + Antenna Factor + AMP
- If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
- Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2404MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\8

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4122.900	47.16	31.28	4.65	-39.71	43.38	74.00	30.62	PK	Vertical
2	4808.000	51.09	32.23	5.12	-39.78	48.66	74.00	25.34	PK	Vertical
3	7369.900	43.18	36.88	5.75	-39.86	45.95	74.00	28.05	PK	Vertical
4	9058.000	41.98	38.76	6.79	-38.66	48.87	74.00	25.13	PK	Vertical
5	12305.000	42.54	39.39	7.81	-39.36	50.38	74.00	23.62	PK	Vertical
6	15784.900	40.25	38.25	8.53	-39.36	47.67	74.00	26.33	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2440MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\9

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4141.600	46.29	31.43	4.67	-39.71	42.68	74.00	31.32	PK	Horizontal
2	4553.000	46.68	32.06	4.95	-39.76	43.93	74.00	30.07	PK	Horizontal
3	4881.100	51.61	33.02	5.17	-39.79	50.01	74.00	23.99	PK	Horizontal
4	7320.600	44.11	37.00	5.73	-39.87	46.97	74.00	27.03	PK	Horizontal
5	9029.100	43.10	38.73	6.80	-38.63	50.00	74.00	24.00	PK	Horizontal
6	11563.800	43.58	38.67	7.64	-39.60	50.29	74.00	23.71	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2440MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\10

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	3805.000	46.05	30.84	4.54	-39.62	41.81	74.00	32.19	PK	Vertical
2	4281.000	46.22	31.70	4.76	-39.73	42.95	74.00	31.05	PK	Vertical
3	4881.100	51.44	33.02	5.17	-39.79	49.84	74.00	24.16	PK	Vertical
4	7480.400	44.02	36.78	5.79	-39.85	46.74	74.00	27.26	PK	Vertical
5	9209.300	42.49	38.40	6.77	-38.83	48.83	-	-	PK	Vertical
6	12301.600	41.83	39.40	7.81	-39.36	49.68	74.00	24.32	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2478MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\11

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4117.800	46.38	31.24	4.65	-39.71	42.56	74.00	31.44	PK	Horizontal
2	4955.900	49.50	33.09	5.22	-39.80	48.01	74.00	25.99	PK	Horizontal
3	7640.200	43.73	36.84	5.84	-39.84	46.57	74.00	27.43	PK	Horizontal
4	9044.400	41.66	38.86	6.79	-38.65	48.66	74.00	25.34	PK	Horizontal
5	10934.800	41.64	39.63	7.36	-39.61	49.02	74.00	24.98	PK	Horizontal
6	15512.900	39.52	38.56	8.41	-39.06	47.43	74.00	26.57	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2478MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\12

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	4129.700	47.40	31.34	4.66	-39.71	43.69	74.00	30.31	PK	Vertical
2	4957.600	49.18	33.08	5.22	-39.80	47.68	74.00	26.32	PK	Vertical
3	7477.000	43.41	36.76	5.79	-39.85	46.11	74.00	27.89	PK	Vertical
4	9345.300	42.09	38.75	6.76	-38.98	48.62	74.00	25.38	PK	Vertical
5	12184.300	42.14	39.25	7.81	-39.45	49.75	74.00	24.25	PK	Vertical
6	15606.400	39.37	38.97	8.45	-39.17	47.62	74.00	26.38	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.


3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

12. Band Edge Compliance

12.1. Test equipment

Equipment	Manufacturer	Model No.	Serial No.	Cal Due To
Micro-Tronics filters	REBES	BRM50702	DDT-ZC03242	/
Pre-amplifier	SONOMA	310N	DDT-ZC01969	2026/07/06
RF Cable	N/A	W24.02 HL-562	DDT-ZC04022	2026/03/28
RF cable	Yuhu Technology	JCTB810-NJ-NJ-9M	DDT-ZC02538	2026/03/28
RF cable	Zhongke Junchuang	JCT26S-NJ-NJ-1.5M	DDT-ZC02762	/
RF cable	Yuhu Technology	ZT26S-SMAJ-SMAJ-1M	DDT-ZC02037	2026/10/10
RF Cable	N/A	W13.02 AP1-X2	DDT-ZC04023	2026/03/28
Pre-amplifier	COM-POWER	PAM-840A	DDT-ZC01693	2026/03/28
Pre-amplifier	COM-POWER	PAM-118A	DDT-ZC01293	2026/08/10
High pass filter	Micro-Tronics	HPM50102	DDT-ZC00561	2026/03/28
EMI TEST RECEIVER	R&S	ESU26	DDT-ZC01909	2026/03/28
High pass filter	Micro-Tronics	HPM50108	DDT-ZC00560	2026/03/28
High Pass filter	Xi'an Xingbo	XBLBQ-GTA67	DDT-ZC02179	2026/03/28
Micro-Tronics filters	REBES	BRM50716	DDT-ZC03240	/
Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	DDT-ZC00506	2026/04/01
Trilog Broadband Antenna	Schwarzbeck	VULB 9163	DDT-ZC02050	2026/07/25
Hochgewinn-Hornantenne	SCHWARZBEC K	BBHA 9120 D	DDT-ZC02129	2026/08/11
Active Loop Antenna	Schwarzbeck	FMZB1519	DDT-ZC00524	2026/08/18
PSA Series Spectrum Analyzer	Agilent	E4447A	DDT-ZC00517	2026/03/28

12.2. Block diagram of test setup



12.3. Limits

All restriction band should comply with 15.209 and RSS-Gen section 8.9 limits, other emission should be at least 20 dB below the fundamental.

12.4. Assistant equipment used for test

Assistant equipment	Manufacturer	Model number	Description	other
/	/	/	/	/

12.5. Test procedure

Same with Radiated Emission except change investigated frequency range.

Remark: All restriction band have been tested, and only the worst case is shown in report.

12.6. Test result

PASS. (See below detailed test result)

12.7. Test data

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\13

Memo:

Sample Numbel:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2361.630	13.19	27.63	3.74	0.00	44.56	74.00	29.44	PK	Horizontal
2	2390.000	10.67	27.46	3.78	0.00	41.91	74.00	32.09	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2402MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\14

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2380.890	13.45	27.51	3.77	0.00	44.73	74.00	29.27	PK	Vertical
2	2390.000	10.38	27.46	3.78	0.00	41.62	74.00	32.38	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\15

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	11.48	27.54	3.88	0.00	42.90	74.00	31.10	PK	Horizontal
2	2489.197	13.18	27.59	3.88	0.00	44.65	74.00	29.35	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE1M 2480MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\16

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	10.62	27.54	3.88	0.00	42.04	74.00	31.96	PK	Vertical
2	2490.085	13.28	27.60	3.88	0.00	44.76	74.00	29.24	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbin

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2404MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\17

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2362.000	13.48	27.63	3.74	0.00	44.85	74.00	29.15	PK	Horizontal
2	2390.000	9.45	27.46	3.78	0.00	40.69	74.00	33.31	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP
2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2404MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\18

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2377.510	12.88	27.53	3.76	0.00	44.17	74.00	29.83	PK	Vertical
2	2390.000	10.62	27.46	3.78	0.00	41.86	74.00	32.14	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2478MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\19

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	10.97	27.54	3.88	0.00	42.39	74.00	31.61	PK	Horizontal
2	2489.164	12.56	27.59	3.88	0.00	44.03	74.00	29.97	PK	Horizontal

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

TR-4-E-009 Radiated Emission Test Result

Test Date:

2025-10-31

Tested By:

Li Xiongbín

EUT:

Bluetooth Remote Control

Model Number:

B975C

Test Mode:

TX BLE2M 2478MHz Mode

Power Supply:

Battery

Condition:

Temp:23.8°C;Humi:54.6%

Test Site:


DDT 3# Chamber

File Path:

d:\ts\2025 report date\Q25093012-5E\FCC Above 1G BLE\20

Memo:

Sample Numbler:S25093012-006



Suspected Data List										
NO	Freq. [MHz]	Reading [dBμV/m]	Antenna Factor [dB]	Cable loss [dB]	AMP [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Detector	Polarity
1	2483.500	9.73	27.54	3.88	0.00	41.15	74.00	32.85	PK	Vertical
2	2491.627	13.52	27.62	3.89	0.00	45.03	74.00	28.97	PK	Vertical

Note:

1. Level = Reading + Cable loss + Antenna Factor + AMP

2. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.

3. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.

14. Photos of the EUT

Please refer to DDT-Q25093012-6E appendix I

-----End Report-----