



TESTING LABORATORY
CERTIFICATE#4323.01



FCC PART 15.247

TEST REPORT

For

Altenergy Power System Inc.

No.1, Yatai Road, Jiaxing Zhejiang, 314050 P.R. China

FCC ID: 2AFGRECUR


Report Type: Original Report	Product Type: Energy Communication Unit
Project Engineer:	<u>Tyrone Wang</u> 
Report Number:	<u>RSHF201207001-00B</u>
Report Date:	<u>2020-12-28</u>
Reviewed By:	<u>Oscar Ye</u> 
Prepared By:	Bay Area Compliance Laboratories Corp. (Kunshan) No.248 Chenghu Road, Kunshan, Jiangsu province, China Tel: +86-0512-86175000 Fax: +86-0512-88934268 www.baclcorp.com.cn

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE.....	8
BLOCK DIAGRAM OF TEST SETUP	9
SUMMARY OF TEST RESULTS.....	11
TEST EQUIPMENT LIST	12
FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)	13
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	17
FACTOR & OVER LIMIT CALCULATION.....	17
TEST RESULTS SUMMARY	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP.....	20
EMI TEST RECEIVER SETUP.....	21
TEST PROCEDURE	21
TEST RESULTS SUMMARY	21
TEST DATA	22
FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH	42
APPLICABLE STANDARD	42
TEST PROCEDURE	42
TEST DATA	42
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	49
APPLICABLE STANDARD	49
TEST PROCEDURE	49
TEST DATA	49
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	51
APPLICABLE STANDARD	51
TEST PROCEDURE	51
TEST DATA	51

FCC §15.247(e) - POWER SPECTRAL DENSITY	55
APPLICABLE STANDARD	55
TEST PROCEDURE	55
TEST DATA	55

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Applicant	Altenergy Power System Inc.
Tested Model:	ECU-R
Series Model:	ECU-B,LCU
Model Difference:	Model names
Product Type	Energy Communication Unit
Power Supply	DC 5V
RF Function:	2.4G Wi-Fi
Operating Band/Frequency:	2412-2462 MHz(802.11b/g/n20)
Channel Number:	11(802.11b/g/n20)
Channel Separation:	5 MHz
Modulation Type:	DSSS,OFDM
Antenna Type:	Omni antenna
*Maximum Antenna Gain:	2.0 dBi

Note: The Maximum Antenna Gain was declared by the manufacturer.*

*All measurement and test data in this report was gathered from production sample serial number: 20201207001.
(Assigned by the BACL. The EUT supplied by the applicant was received on 2020-12-07)*

Objective

This report is prepared on behalf of *Altenergy Power System Inc.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions' rules.

The tests were performed in order to determine Compliant with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

FCC Part 15.247 Zigbee DTS submissions with FCC ID: 2AFGRECUR.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliant Testing of Unlicensed Wireless Devices and FCC 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliant Laboratories Corp. (Kunshan). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Item		Uncertainty
AC Power Lines Conducted Emissions		3.19dB
RF conducted test with spectrum		0.9dB
RF Output Power with Power meter		0.5dB
Radiated emission	30MHz~1GHz	6.11dB
	1GHz~6GHz	4.45dB
	6GHz~18GHz	5.23dB
	18GHz~40GHz	5.65dB
Occupied Bandwidth		0.5kHz
Temperature		1.0°C
Humidity		6%

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Kunshan) to collect test data is located on the No.248 Chenghu Road, Kunshan, Jiangsu province, China.

Bay Area Compliance Laboratories Corp. (Kunshan) Lab is accredited to ISO/IEC 17025 by A2LA (Lab code: 4323.01) and the FCC designation No. CN1185 under the FCC KDB 974614 D01 and CAB identifier CN0004 under the ISSED requirement. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

Test channel list is as below:

For 802.11b, 802.11g and 802.11n-HT20 mode, EUT was tested with Channel 1, 6 and 11;

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	7	2442
2	2417	8	2447
3	2422	9	2452
4	2427	10	2457
5	2432	11	2462
6	2437	/	/

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

RF test tool: xshell


Pre-scan with all the data rates, and the worst case was performed as below:

Mode	Data Rate	*Power Level Setting
802.11b	1 Mbps	8
802.11g	6 Mbps	7
802.11n-HT20	MCS0	7


Note: The Power Level Setting was declared by the applicant.*

Duty Cycle:


802.11b Mode Middle Channel



802.11g Mode Middle Channel



802.11n-HT20 Mode Middle Channel



Mode	Duty Cycle (%)	T(ms)	1/T(kHz)	10log(1/x)
802.11b	100	/	/	0
802.11g	100	/	/	0
802.11n-HT20	100	/	/	0

Note: "x" means the Duty Cycle.

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	Adapter	SK02T-0500200U	19091101000602
DELL	Notebook	E6410	3094742521

External I/O Cable


Cable Description	Length(m)	From	To
Power Cable	1.0	EUT	Adapter
RJ45 Cable	1.5	EUT	Notebook
Power Cable	1.0	Adapter	LISN/AC Source

Block Diagram of Test Setup


For Conducted Emissions:



For Radiated Emissions (Below 1GHz):



For Radiated Emissions (Above 1GHz):



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (I), §1.1310 & §2.1091	Maximum Permissible Exposure (MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.247(d)	Spurious Emissions at Antenna Port	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test (Chamber 1#)					
Rohde & Schwarz	EMI Test Receiver	ESCI	100195	2020-12-14	2021-12-13
Sunol Sciences	Broadband Antenna	JB3	A090413-1	2020-08-05	2023-08-04
Sonoma Instrument	Pre-amplifier	310N	171205	2020-08-14	2021-08-13
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-8	008	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-9	009	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-10	010	2020-08-15	2021-08-14
Radiated Emission Test (Chamber 2#)					
Rohde & Schwarz	EMI Test Receiver	ESU40	100207	2020-04-01	2021-03-31
ETS-LINDGREN	Horn Antenna	3115	9207-3900	2020-07-15	2023-07-14
ETS-LINDGREN	Horn Antenna	3116	00084159	2019-12-12	2022-12-11
A.H.Systems, inc	Amplifier	PAM-0118P	512	2020-02-20	2021-02-19
SELECTOR	Amplifier	EM18G40G	060726	2020-03-22	2021-03-21
MICRO-TRONICS	Band Reject Filter	BRM50702	G024	2020-08-05	2021-08-04
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Rohde & Schwarz	Auto test Software	EMC32	100361	N/A	N/A
MICRO-COAX	Coaxial Cable	Cable-6	006	2020-12-12	2021-12-11
MICRO-COAX	Coaxial Cable	Cable-11	011	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-12	012	2020-08-15	2021-08-14
MICRO-COAX	Coaxial Cable	Cable-13	013	2020-08-15	2021-08-14
RF Conducted Test					
Rohde & Schwarz	EMI Test Receiver	ESIB26	100146	2020-12-14	2021-12-13
Agilent	Power Meter	N1912A	MY5000492	2020-11-18	2021-11-17
Agilent	Power Sensor	N1921A	MY54210024	2020-11-18	2021-11-17
Narda	Attenuator	10dB	010	2020-08-15	2021-08-14
Altenergy Power System Inc.	RF Cable	Altenergy Power System Inc. C01	/	Each Time	N/A
Conducted Emission Test					
Rohde & Schwarz	EMI Test Receiver	ESR	1316.3003K03-101746-zn	2020-08-05	2021-08-04
Rohde & Schwarz	LISN	ENV216	3560655016	2019-11-30	2020-11-29
Audix	Test Software	e3	V9	N/A	N/A
Rohde & Schwarz	Pulse limiter	ESH3-Z2	0357.8810.54	2020-08-10	2021-08-09
MICRO-COAX	Coaxial Cable	Cable-15	015	2020-08-15	2021-08-14

*** Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Kunshan) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §1.1310 & §2.1091 –MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart §2.1091 and subpart §1.1310, systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

Mode	Frequency Range (MHz)	Antenna Gain		Target Output Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)	MPE Ratio
		(dBi)	(numeric)	(dBm)	(mW)				
802.11b	2412~2462	2.00	1.58	13.5	22.39	20	0.0070	1.0	0.0070
802.11g		2.00	1.58	17.5	56.23	20	0.0177	1.0	0.0177
802.11n-HT20		2.00	1.58	18.0	63.10	20	0.0198	1.0	0.0198
Zigbee	2405~2480	2.00	1.58	11.0	12.59	20	0.0040	1.0	0.0040

Note:

- 1) The tune-up output power was declared by the manufacturer.
- 2) Wi-Fi and Zigbee can transmit simultaneously. The worst condition is 802.11n-HT20 of Wi-Fi & Zigbee, as below:

$$\sum_i \frac{S_i}{S_{Limit,i}} = 0.0040/1.0 + 0.0198/1.0 = 0.0238 < 1.0$$

Conclusion: The device meets FCC MPE at 20 cm distance.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine Compliant with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an omni antenna and the antenna gain is 2.0 dBi, the antenna was permanently attached, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC §15.207(a)

EUT Setup



The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

ANSI C63.10-2013 clause 6.2

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

Factor & Over Limit Calculation

The Corrected Factor is calculated by adding LISN VDF (Voltage Division Factor), Cable Loss and Transient Limiter Attenuation. The basic equation is as follows:

$$\text{Factor (dB)} = \text{LISN VDF (dB)} + \text{Cable Loss (dB)} + \text{Transient Limiter Attenuation (dB)}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit of 7 dB means the emission is 7 dB above the limit. The equation for over limit calculation is as follows:

$$\text{Over Limit (dB)} = \text{Read level (dB}\mu\text{V)} + \text{Factor (dB)} - \text{Limit (dB}\mu\text{V)}$$

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Part 15.207.

Test Data


Environmental Conditions

Temperature:	23.1 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa

The testing was performed by Tyrone Wang on 2020-12-14.


EUT operation mode: Transmitting

AC 120V/60 Hz, Line



		Read		Limit	Over	
	Freq	Level	Factor	Level	Line	Limit Remark
	MHz	dBuV	dB	dBuV	dBuV	dB
1	0.170	17.00	19.83	36.83	54.94	-18.11 Average
2	0.170	38.50	19.83	58.33	64.94	-6.61 QP
3	0.186	16.51	19.82	36.33	54.20	-17.87 Average
4	0.186	37.51	19.82	57.33	64.20	-6.87 QP
5	0.237	13.80	19.82	33.62	52.22	-18.60 Average
6	0.237	33.70	19.82	53.52	62.22	-8.70 QP
7	0.336	7.59	19.82	27.41	49.31	-21.90 Average
8	0.336	26.19	19.82	46.01	59.31	-13.30 QP
9	0.421	4.00	19.74	23.74	47.42	-23.68 Average
10	0.421	20.80	19.74	40.54	57.42	-16.88 QP
11	0.464	2.10	19.75	21.85	46.63	-24.78 Average
12	0.464	18.20	19.75	37.95	56.63	-18.68 QP

AC 120V/60 Hz, Neutral



	Freq	Read Level	Factor	Level	Limit Line	Over Limit	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	
1	0.151	19.10	19.82	38.92	55.96	-17.04	Average
2	0.151	40.00	19.82	59.82	65.96	-6.14	QP
3	0.171	17.80	19.83	37.63	54.90	-17.27	Average
4	0.171	38.10	19.83	57.93	64.90	-6.97	QP
5	0.221	14.80	19.82	34.62	52.79	-18.17	Average
6	0.221	34.10	19.82	53.92	62.79	-8.87	QP
7	0.277	11.70	19.82	31.52	50.90	-19.38	Average
8	0.277	30.40	19.82	50.22	60.90	-10.68	QP
9	0.387	6.20	19.76	25.96	48.12	-22.16	Average
10	0.387	22.40	19.76	42.16	58.12	-15.96	QP
11	0.604	1.80	19.75	21.55	46.00	-24.45	Average
12	0.604	14.60	19.75	34.35	56.00	-21.65	QP

Note:

- 1) Factor (dB) = LISN VDF (dB) + Cable Loss (dB) + Transient Limiter Attenuation (dB)
- 2) Over Limit (dB) = Read level (dBμV) + Factor (dB) - Limit (dBμV)


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209 and FCC 15.247 limits.

EMI Test Receiver Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver setup was set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	120 kHz	300 kHz	120 kHz	QP
Above 1GHz	1MHz	3 MHz	/	PK
	1MHz	3 MHz	/	Ave.

Test Procedure

According to ANSI C63.10-2013 clause 6.5, 6.6 and 6.7.

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

Corrected Amplitude (dB μ V/m) = Meter Reading (dB μ V) + Antenna Factor (dB/m) + Cable Loss (dB) - Amplifier Gain (dB)

The “**Margin**” column of the following data tables indicates the degree of Compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Test Results Summary

According to the recorded data in following table, the EUT complied with the FCC Title 47, Part 15, Subpart C, section 15.205, 15.209 and 15.247.

Test Data

Environmental Conditions

Temperature:	22.3~23.5 °C
Relative Humidity:	50-55 %
ATM Pressure:	101-102 kPa


The testing was performed by Tyrone Wang from 2020-12-14 to 2020-12-28.

EUT operation mode: Transmitting

Spurious Emission Test:

30MHz-1GHz:

Pre-scan with 802.11b, 802.11g, 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11n-HT20 mode in Y-axis of orientation** was recorded.



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
30.125912	27.80	100.0	V	114.0	-4.8	40.00	12.20
35.941450	24.12	100.0	V	108.0	-9.1	40.00	15.88
47.581250	25.05	100.0	V	154.0	-16.9	40.00	14.95
125.666500	23.28	100.0	V	142.0	-11.3	43.50	20.22
159.131450	34.78	200.0	H	352.0	-12.7	43.50	8.72
207.388750	34.25	100.0	V	351.0	-12.2	43.50	9.25

1GHz-18GHz:**802.11b Mode:**


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dB μ V/m) = Corrected Factor (dB/m) + Reading (dB μ V)
 Margin (dB) = Limit (dB μ V/m) – Corrected Amplitude (dB μ V/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1061.200000	41.89	---	200.0	H	243.0	-18.7	74.00	32.11
1061.200000	---	31.76	150.0	H	243.0	-18.7	54.00	22.24
2125.400000	---	28.56	150.0	V	271.0	-14.0	54.00	25.44
2125.400000	38.33	---	150.0	V	271.0	-14.0	74.00	35.67
3412.300000	---	26.98	150.0	H	352.0	-9.0	54.00	27.02
3412.300000	37.38	---	200.0	H	352.0	-9.0	74.00	36.62
4824.000000	---	49.61	150.0	V	50.0	-5.5	54.00	4.39
4824.000000	52.48	---	150.0	V	50.0	-5.5	74.00	21.52
14594.900000	---	40.03	200.0	V	33.0	6.3	54.00	13.97
14594.900000	49.41	---	150.0	V	33.0	6.3	74.00	24.59
17943.900000	---	42.23	200.0	V	89.0	8.8	54.00	11.77
17943.900000	53.01	---	200.0	V	89.0	8.8	74.00	20.99

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	31.00	150.0	H	256.0	-18.7	54.00	23.00
1061.200000	41.94	---	150.0	H	256.0	-18.7	74.00	32.06
1499.800000	---	29.69	200.0	V	230.0	-16.4	54.00	24.31
1499.800000	40.09	---	200.0	V	230.0	-16.4	74.00	33.91
2127.100000	---	28.20	200.0	V	283.0	-13.9	54.00	25.80
2127.100000	38.13	---	200.0	V	283.0	-13.9	74.00	35.87
4874.000000	---	51.71	150.0	V	41.0	-5.4	54.00	2.29
4874.000000	58.45	---	150.0	V	41.0	-5.4	74.00	15.55
12080.600000	---	37.66	150.0	V	55.0	3.7	54.00	16.34
12080.600000	46.40	---	150.0	V	55.0	3.7	74.00	27.60
17535.900000	---	42.14	200.0	V	52.0	8.9	54.00	11.86
17535.900000	51.64	---	200.0	V	52.0	8.9	74.00	22.36

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV /m)	Average (dBμV /m)	Height (cm)	Polar (H/V)				
1061.200000	43.37	---	200.0	V	252.0	-18.7	74.00	30.63
1061.200000	---	32.19	200.0	V	252.0	-18.7	54.00	21.81
1596.700000	---	31.42	200.0	H	244.0	-16.0	54.00	22.58
1596.700000	39.03	---	200.0	H	244.0	-16.0	74.00	34.97
2128.800000	---	30.27	150.0	V	252.0	-13.9	54.00	23.73
2128.800000	38.35	---	150.0	V	252.0	-13.9	74.00	35.65
4924.000000	---	52.99	150.0	V	50.0	-5.3	54.00	1.01
4924.000000	57.59	---	150.0	V	50.0	-5.3	74.00	16.41
12078.900000	---	37.29	200.0	H	225.0	3.7	54.00	16.71
12078.900000	47.09	---	200.0	H	225.0	3.7	74.00	26.91
17469.600000	---	43.39	150.0	V	186.0	8.8	54.00	10.61
17469.600000	52.79	---	150.0	V	186.0	8.8	74.00	21.21

802.11g Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel: 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1042.500000	42.34	---	200.0	V	243.0	-18.8	74.00	31.66
1042.500000	---	32.09	200.0	V	243.0	-18.8	54.00	21.91
1498.100000	---	29.82	150.0	V	213.0	-16.4	54.00	24.18
1498.100000	39.09	---	150.0	V	213.0	-16.4	74.00	34.91
2130.500000	36.69	---	150.0	V	289.0	-13.9	74.00	37.31
2130.500000	---	28.59	150.0	V	289.0	-13.9	54.00	25.41
4824.000000	51.33	---	200.0	V	52.0	-5.5	74.00	22.67
4824.000000	---	44.24	200.0	V	52.0	-5.5	54.00	9.76
7236.000000	---	39.68	150.0	V	105.0	0.4	54.00	14.32
7236.000000	45.98	---	150.0	V	105.0	0.4	74.00	28.02
17705.900000	---	41.81	200.0	H	174.0	8.9	54.00	12.19
17705.900000	53.15	---	200.0	H	174.0	8.9	74.00	20.85

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	32.19	200.0	V	256.0	-18.7	54.00	21.81
1061.200000	43.29	---	200.0	V	256.0	-18.7	74.00	30.71
2130.500000	---	28.30	150.0	V	270.0	-13.9	54.00	25.70
2130.500000	38.23	---	150.0	V	270.0	-13.9	74.00	35.77
4874.000000	---	35.13	200.0	V	71.0	-5.4	54.00	18.87
4874.000000	44.12	---	200.0	V	71.0	-5.4	74.00	29.88
7159.100000	44.78	---	150.0	V	321.0	0.3	74.00	29.22
7159.100000	---	35.31	150.0	V	321.0	0.3	54.00	18.69
14120.600000	---	38.98	200.0	V	3.0	6.2	54.00	15.02
14120.600000	49.30	---	200.0	V	3.0	6.2	74.00	24.70
17981.300000	---	43.58	200.0	H	107.0	8.8	54.00	10.42
17981.300000	52.96	---	200.0	H	107.0	8.8	74.00	21.04

High Channel: 2462MHz

Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dB μ V/m)	Margin (dB)
	MaxPeak (dB μ V/m)	Average (dB μ V/m)	Height (cm)	Polar (H/V)				
1061.200000	41.63	---	200.0	H	3.0	-18.7	74.00	32.37
1061.200000	---	30.75	200.0	H	3.0	-18.7	54.00	23.25
2128.800000	37.64	---	150.0	V	276.0	-13.9	74.00	36.36
2128.800000	---	27.59	150.0	V	276.0	-13.9	54.00	26.41
4924.000000	44.44	---	200.0	V	36.0	-5.3	74.00	29.56
4924.000000	---	36.42	200.0	V	36.0	-5.3	54.00	17.58
7237.300000	---	34.81	150.0	H	3.0	0.5	54.00	19.19
7237.300000	43.94	---	150.0	H	3.0	0.5	74.00	30.06
14447.000000	---	40.40	200.0	V	315.0	6.5	54.00	13.60
14447.000000	49.13	---	200.0	V	315.0	6.5	74.00	24.87
17466.200000	---	42.92	150.0	H	311.0	8.8	54.00	11.08
17466.200000	51.92	---	150.0	H	311.0	8.8	74.00	22.08

802.11n-HT20 Mode:


(Pre-scan in the X,Y and Z axes of orientation, the worst case **Y-axis of orientation** was recorded)

Note:

1. This test was performed with the 2.4-2.5GHz notch filter.
2. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)
 Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)
 Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

Low Channel : 2412MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1042.500000	40.93	---	150.0	H	335.0	-18.8	74.00	33.07
1042.500000	---	31.90	150.0	H	335.0	-18.8	54.00	22.10
1561.000000	38.24	---	200.0	H	324.0	-16.1	74.00	35.76
1561.000000	---	27.14	200.0	H	324.0	-16.1	54.00	26.86
2125.400000	35.96	---	150.0	V	335.0	-14.0	74.00	38.04
2125.400000	---	27.37	150.0	V	335.0	-14.0	54.00	26.63
4824.000000	50.62	---	150.0	V	64.0	-5.5	74.00	23.38
4824.000000	---	43.57	150.0	V	64.0	-5.5	54.00	10.43
8097.500000	---	36.75	200.0	H	324.0	1.7	54.00	17.25
8097.500000	44.79	---	200.0	H	324.0	1.7	74.00	29.21
17379.500000	---	43.04	150.0	V	14.0	8.5	54.00	10.96
17379.500000	51.74	---	150.0	V	14.0	8.5	74.00	22.26

Middle Channel: 2437MHz


Full Spectrum



Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	42.34	---	200.0	H	323.0	-18.7	74.00	31.66
1061.200000	---	30.83	200.0	H	323.0	-18.7	54.00	23.17
1561.000000	38.96	---	150.0	H	345.0	-16.1	74.00	35.04
1561.000000	---	29.20	150.0	H	345.0	-16.1	54.00	24.80
2130.500000	37.64	---	200.0	V	283.0	-13.9	74.00	36.36
2130.500000	---	29.32	200.0	V	283.0	-13.9	54.00	24.68
4874.000000	44.70	---	150.0	V	49.0	-5.4	74.00	29.30
4874.000000	---	33.99	150.0	V	49.0	-5.4	54.00	20.01
8650.000000	---	34.61	200.0	V	308.0	1.5	54.00	19.39
8650.000000	44.66	---	200.0	V	308.0	1.5	74.00	29.34
17491.700000	---	41.97	150.0	H	310.0	8.9	54.00	12.03
17491.700000	52.08	---	150.0	H	310.0	8.9	74.00	21.92

High Channel : 2462MHz


Full Spectrum




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
1061.200000	---	31.48	200.0	H	345.0	-18.7	54.00	22.52
1061.200000	41.27	---	200.0	H	345.0	-18.7	74.00	32.73
2127.100000	37.64	---	150.0	V	271.0	-13.9	74.00	36.36
2127.100000	---	27.86	150.0	V	271.0	-13.9	54.00	26.14
3680.900000	37.43	---	200.0	V	271.0	-8.2	74.00	36.57
3680.900000	---	27.67	200.0	V	271.0	-8.2	54.00	26.33
4924.000000	45.73	---	150.0	V	50.0	-5.3	74.00	28.27
4924.000000	---	38.54	150.0	V	50.0	-5.3	54.00	15.46
13529.000000	---	39.51	200.0	H	358.0	5.7	54.00	14.49
13529.000000	48.77	---	200.0	H	358.0	5.7	74.00	25.23
17491.700000	---	43.17	150.0	H	268.0	8.9	54.00	10.83
17491.700000	52.02	---	150.0	H	268.0	8.9	74.00	21.98

18GHz-25GHz:

Pre-scan with 802.11b, 802.11g and 802.11n-HT20 modes of operation in the X,Y and Z axes of orientation, the worst case **middle channel of 802.11n-HT20 mode in Y-axis of orientation** was recorded

Vertical

Date: 17.DEC.2020 09:37:11

Horizontal

Date: 17.DEC.2020 09:39:55

Restricted Bands Emissions Test:

Note:

1. Corrected Factor (dB/m) = Antenna factor (RX) (dB/m) + Cable Loss (dB) – Amplifier Factor (dB)

Corrected Amplitude (dBμV/m) = Corrected Factor (dB/m) + Reading (dBμV)

Margin (dB) = Limit (dBμV/m) – Corrected Amplitude (dBμV/m)

802.11b Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	---	41.74	150.0	V	181.0	-2.9	54.00	12.26
2390.00	45.82	---	150.0	V	181.0	-2.9	74.00	28.18
High Channel: 2462MHz								
2483.50	---	42.86	200.0	V	134.0	-2.5	54.00	11.14
2483.50	48.02	---	200.0	V	134.0	-2.5	74.00	25.98

802.11g Mode: (Pre-scan in the X, Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)


Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	46.25	---	200.0	V	56.0	-2.9	74.00	27.75
2390.00	---	41.70	200.0	V	56.0	-2.9	54.00	12.30
High Channel: 2462MHz								
2483.50	46.58	---	150.0	V	339.0	-2.5	74.00	27.42
2483.50	---	43.16	150.0	V	339.0	-2.5	54.00	10.84

802.11n-HT20 Mode: (Pre-scan in the X,Y and Z axes of orientation, the worst case Y-axis of orientation was recorded)

Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	MaxPeak (dBμV/m)	Average (dBμV/m)	Height (cm)	Polar (H/V)				
Low Channel: 2412MHz								
2390.00	---	42.72	150.0	V	359.0	-2.9	54.00	11.28
2390.00	45.37	---	150.0	V	359.0	-2.9	74.00	28.63
High Channel: 2462MHz								
2483.50	45.93	---	200.0	V	339.0	-2.5	74.00	28.07
2483.50	---	43.32	200.0	V	339.0	-2.5	54.00	10.68

Transmitting simultaneously test:**30MHz-1GHz**


(The worst case 802.11n-HT20 middle Channel of Wi-Fi and middle Channel of Zigbee mode transmitting simultaneously in Z-axis of orientation was recorded)



Frequency (MHz)	Corrected Amplitude	Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
	QuasiPeak (dBμV/m)	Height (cm)	Polar (H/V)				
42.927900	16.43	100.0	V	204.0	-13.2	40.00	23.57
152.091000	28.57	200.0	H	158.0	-12.4	43.50	14.93
159.037350	29.19	200.0	H	344.0	-12.7	43.50	14.31
207.437650	36.17	100.0	V	25.0	-12.2	43.50	7.33
241.957650	25.23	100.0	V	271.0	-13.4	46.00	20.77
281.231250	25.89	200.0	V	217.0	-11.8	46.00	20.11

1GHz-18GHz:


(The worst case 802.11n-HT20 middle Channel of Wi-Fi and middle Channel of Zigbee mode transmitting simultaneously in Z-axis of orientation was recorded)




Frequency (MHz)	Corrected Amplitude		Rx Antenna		Turntable Degree	Corrected Factor (dB/m)	Limit (dBµV/m)	Margin (dB)
	MaxPeak (dBµV/m)	Average (dBµV/m)	Height (cm)	Polar (H/V)				
1438.600000	---	21.14	150.0	H	339.0	-16.7	54.00	32.86
1438.600000	30.20	---	150.0	H	339.0	-16.7	74.00	43.80
3357.900000	---	29.32	200.0	V	110.0	-9.2	54.00	24.68
3357.900000	35.96	---	200.0	V	110.0	-9.2	74.00	38.04
4874.000000	---	38.72	200.0	H	207.0	-5.4	54.00	15.28
4874.000000	48.51	---	200.0	H	207.0	-5.4	74.00	25.49
4924.000000	---	39.68	200.0	H	207.0	-5.3	54.00	14.32
4924.000000	50.90	---	200.0	H	207.0	-5.3	74.00	23.10
7311.000000	---	42.83	150.0	H	199.0	0.6	54.00	11.17
7311.000000	47.45	---	150.0	H	199.0	0.6	74.00	26.55
9748.200000	---	39.61	200.0	V	292.0	2.0	54.00	14.39
9748.200000	47.22	---	200.0	V	292.0	2.0	74.00	26.78

18GHz - 25GHz



(The worst case 802.11n-HT20 middle Channel of Wi-Fi and middle Channel of Zigbee mode transmitting simultaneously in Z-axis of orientation was recorded)

Horizontal


Date: 28.DEC.2020 13:31:56

Vertical


Date: 28.DEC.2020 13:30:23

Conducted Spurious Emissions at Antenna Port**802.11b Mode Low Channel****802.11b Mode Middle Channel**


802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



FCC §15.247(a) (2) - 6 dB EMISSION BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.8.1

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) $\geq 3 * \text{RBW}$.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.



Test Data

Environmental Conditions

Temperature:	23.5 °C
Relative Humidity:	52 %
ATM Pressure:	101.5 kPa


The testing was performed by Tyrone Wang on 2020-12-14.

EUT operation mode: Transmitting


Test Result: Pass

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (MHz)
802.11b Mode			
Low	2412	10.160	≥ 0.5
Middle	2437	10.160	≥ 0.5
High	2462	10.160	≥ 0.5
802.11g Mode			
Low	2412	16.323	≥ 0.5
Middle	2437	16.353	≥ 0.5
High	2462	16.273	≥ 0.5
802.11n-HT20 Mode			
Low	2412	17.315	≥ 0.5
Middle	2437	17.315	≥ 0.5
High	2462	17.475	≥ 0.5


802.11b Mode Low Channel




802.11b Mode Middle Channel




802.11b Mode High Channel




802.11g Mode Low Channel




802.11g Mode Middle Channel




802.11g Mode High Channel




802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



802.11n-HT20 Mode High Channel



FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, Compliant with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.9.1.3

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall use a fast-responding diode detector.

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	23.2 °C
Relative Humidity:	53 %
ATM Pressure:	101.3 kPa

The testing was performed by Tyrone Wang on 2020-12-14.

EUT operation mode: Transmitting

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)	Result
802.11b Mode				
Low	2412	11.35	30	Pass
Middle	2437	12.16	30	Pass
High	2462	13.07	30	Pass
802.11g Mode				
Low	2412	17.11	30	Pass
Middle	2437	17.39	30	Pass
High	2462	17.22	30	Pass
802.11n-HT20 Mode				
Low	2412	17.27	30	Pass
Middle	2437	17.57	30	Pass
High	2462	17.41	30	Pass

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates Compliant with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

According to ANSI C63.10-2013 sub-clause 6.10.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

Test Data

Environmental Conditions


Temperature:	23.1 °C
Relative Humidity:	55 %
ATM Pressure:	101.3 kPa

The testing was performed by Tyrone Wang on 2020-12-14.


EUT operation mode: Transmitting

Test Result: Compliant


802.11b Mode Left Side




802.11b Mode Right Side




802.11g Mode Left Side




802.11g Mode Right Side



802.11n-HT20 Mode Left Side



802.11n-HT20 Mode Right Side



FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

According to ANSI C63.10-2013 sub-clause 11.10.2

The following procedure shall be used if maximum peak conducted output power was used to determine Compliant, and it is optional if the maximum conducted (average) output power was used to determine Compliant:

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 * \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Data

Environmental Conditions

Temperature:	23.1 °C
Relative Humidity:	55 %
ATM Pressure:	102.5 kPa

The testing was performed by Tyrone Wang on 2020-12-14.

EUT operation mode: Transmitting

Test Result: Pass

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
802.11b Mode			
Low	2412	-16.56	≤ 8
Middle	2437	-15.05	≤ 8
High	2462	-14.28	≤ 8
802.11g Mode			
Low	2412	-18.46	≤ 8
Middle	2437	-18.65	≤ 8
High	2462	-17.85	≤ 8
802.11n-HT20 mode			
Low	2412	-17.76	≤ 8
Middle	2437	-17.56	≤ 8
High	2462	-17.29	≤ 8

Ref Lvl 20 dBm

Marker 1 [T1] -16.56 dBm

2.41005937 GHz

RBW 3 kHz

VBW 10 kHz

SWT 4.3 s

RF Att 20 dB

Unit dBm

11 dB Offset

1 [T1] -16.56 dBm

2.41005937 GHz

1MAX

1MAX

Center 2.412 GHz

1.525 MHz/

Span 15.25 MHz

Date: 14. DEC. 2020 16:10:36

11 dB Offset

Ref Lvl 20 dBm

Marker 1 [T1] -15.05 dBm

2.43606789 GHz

RBW 3 kHz

VBW 10 kHz

SWT 4.3 s

RF Att 20 dB

Unit dBm

▼ 1 [T1] -15.05 dBm

2.43606789 GHz

1MAX



1



Center 2.437 GHz

1.525 MHz/


Span 15.25 MHz

Date: 14. DEC. 2020 16:11:29


802.11b Mode High Channel**802.11g Mode Low Channel**

802.11g Mode Middle Channel**802.11g Mode High Channel**

802.11n-HT20 Mode Low Channel



802.11n-HT20 Mode Middle Channel



REF Lvl 20 dBm
 Ref Lvl 20 dBm
 Marker 1 [T1]
 -17.29 dBm
 2.46066010 GHz
 RBW 3 kHz
 VBW 10 kHz
 SWT 7.4 s
 RF Att 20 dB
 Unit dBm
 11 dB Offset
 1 [T1]
 -17.29 dBm
 2.46066010 GHz
 1MAX
 1MAX
 Center 2.462 GHz
 2.622 MHz/
 Span 26.22 MHz
 Date: 14. DEC. 2020 16:18:46

Declarations

1: BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk '*'. Customer model name, addresses, names, trademarks etc. are not considered data.

2: Unless otherwise stated the results shown in this test report refer only to the sample(s) tested.

3: Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

4: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval.

5: This report cannot be reproduced except in full, without prior written approval of the Company.

6: This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

******* END OF REPORT *******