



**CFR 47 FCC PART 15 SUBPART C  
ISED RSS-247 ISSUE 2**

**CERTIFICATION TEST REPORT**

*For*

**Kami Secure Home Entry Sensor**

**MODEL NUMBER: YNS.2018**

**PROJECT NUMBER: 4788825511**

**REPORT NUMBER: 4788825511-4**

**FCC ID: 2AFIB-YNS2018**

**IC: 20436-YNS2018**

**ISSUE DATE: Mar. 6, 2019**

*Prepared for*

**Shanghai Xiaoyi Technology Co., Ltd.**

*Prepared by*

**UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch  
Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake  
Hi-Tech Development Zone Dongguan, People's Republic of China**

**Tel: +86 769 22038881**

**Fax: +86 769 33244054**

**Website: [www.ul.com](http://www.ul.com)**



Revision History

| Rev. | Issue Date | Revisions     | Revised By |
|------|------------|---------------|------------|
| V0   | 03/06/2019 | Initial Issue |            |



| Summary of Test Results                                                                                                                                                                                             |                                           |                                                                                                            |              |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------------------------------------------------|--------------|
| Clause                                                                                                                                                                                                              | Test Items                                | FCC/IC Rules                                                                                               | Test Results |
| 1                                                                                                                                                                                                                   | 6dB Bandwidth and 99% Occupied Bandwidth  | FCC Part 15.247 (a) (2)<br>RSS-247 Clause 5.2 (a)<br>ISED RSS-Gen Clause 6.7                               | Pass         |
| 2                                                                                                                                                                                                                   | Peak Conducted Output Power               | FCC Part 15.247 (b) (3)<br>RSS-247 Clause 5.4 (d)                                                          | Pass         |
| 3                                                                                                                                                                                                                   | Power Spectral Density                    | FCC Part 15.247 (e)<br>RSS-247 Clause 5.2 (b)                                                              | Pass         |
| 4                                                                                                                                                                                                                   | Conducted Bandedge and Spurious Emission  | FCC Part 15.247 (d)<br>RSS-247 Clause 5.5                                                                  | Pass         |
| 5                                                                                                                                                                                                                   | Radiated Bandedge and Spurious Emission   | FCC Part 15.247 (d)<br>FCC Part 15.209<br>FCC Part 15.205<br>RSS-247 Clause 5.5<br>RSS-GEN Clause 8.9&8.10 | Pass         |
| 6                                                                                                                                                                                                                   | Conducted Emission Test For AC Power Port | FCC Part 15.207<br>RSS-GEN Clause 8.8                                                                      | Pass         |
| 7                                                                                                                                                                                                                   | Antenna Requirement                       | FCC Part 15.203<br>RSS-GEN Clause 6.8                                                                      | Pass         |
| Remark:<br>1) The measurement result for the sample received is <Pass> according to < CFR 47 FCC PART 15 SUBPART C, ISED RSS-GEN Issue 5 and ISED RSS-247 Issue 2> when <Accuracy Method> decision rule is applied. |                                           |                                                                                                            |              |



## TABLE OF CONTENTS

|                                                        |           |
|--------------------------------------------------------|-----------|
| <b>1. ATTESTATION OF TEST RESULTS .....</b>            | <b>5</b>  |
| <b>2. TEST METHODOLOGY .....</b>                       | <b>6</b>  |
| <b>3. FACILITIES AND ACCREDITATION .....</b>           | <b>6</b>  |
| <b>4. CALIBRATION AND UNCERTAINTY .....</b>            | <b>7</b>  |
| 4.1. MEASURING INSTRUMENT CALIBRATION .....            | 7         |
| 4.2. MEASUREMENT UNCERTAINTY.....                      | 7         |
| <b>5. EQUIPMENT UNDER TEST .....</b>                   | <b>8</b>  |
| 5.1. DESCRIPTION OF EUT .....                          | 8         |
| 5.2. MAXIMUM OUTPUT POWER .....                        | 8         |
| 5.3. CHANNEL LIST.....                                 | 9         |
| 5.4. TEST CHANNEL CONFIGURATION.....                   | 9         |
| 5.5. THE WORSE CASE POWER SETTING PARAMETER.....       | 9         |
| 5.6. DESCRIPTION OF AVAILABLE ANTENNAS.....            | 9         |
| 5.7. TEST ENVIRONMENT.....                             | 10        |
| 5.8. DESCRIPTION OF TEST SETUP .....                   | 11        |
| <b>6. MEASURING INSTRUMENT AND SOFTWARE USED .....</b> | <b>12</b> |
| <b>7. MEASUREMENT METHODS .....</b>                    | <b>13</b> |
| <b>8. ANTENNA PORT TEST RESULTS.....</b>               | <b>14</b> |
| 8.1. ON TIME AND DUTY CYCLE.....                       | 14        |
| 8.2. 6 dB DTS BANDWIDTH AND 99% BANDWIDTH.....         | 16        |
| 8.3. PEAK CONDUCTED OUTPUT POWER .....                 | 20        |
| 8.4. POWER SPECTRAL DENSITY .....                      | 23        |
| 8.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS .....   | 26        |
| <b>9. RADIATED TEST RESULTS.....</b>                   | <b>39</b> |
| 9.1. RESTRICTED BANDEDGE.....                          | 44        |
| 9.2. SPURIOUS EMISSIONS (1~18GHz).....                 | 48        |
| 9.4. SPURIOUS EMISSIONS 18G ~ 26GHz .....              | 54        |
| 9.5. SPURIOUS EMISSIONS 30M ~ 1 GHz .....              | 56        |
| 9.6. SPURIOUS EMISSIONS BELOW 30M .....                | 58        |
| <b>10. ANTENNA REQUIREMENTS.....</b>                   | <b>61</b> |



## 1. ATTESTATION OF TEST RESULTS

### Applicant Information

Company Name: Shanghai Xiaoyi Technology Co., Ltd.  
Address: 6F, Building E, No. 2889, Jinke Road Shanghai, China

### Manufacturer Information

Company Name: Shanghai Xiaoyi Technology Co., Ltd.  
Address: 6F, Building E, No. 2889, Jinke Road Shanghai, China

### EUT Description

EUT Name: Kami Secure Home Entry Sensor  
Model: YNS.2018  
Sample Number: 2008942  
Sample Received Date: January 7, 2019  
Date of Tested: Jan. 7~ Mar. 4, 2019

| APPLICABLE STANDARDS         |              |
|------------------------------|--------------|
| STANDARD                     | TEST RESULTS |
| CFR 47 FCC PART 15 SUBPART C | PASS         |
| ISED RSS-247 Issue 2         | PASS         |
| ISED RSS-GEN Issue 5         | PASS         |

Tested By:

Kebo Zhang  
Engineer Project Associate

Check By:

Shawn Wen  
Laboratory Leader

Approved By:

Stephen Guo  
Laboratory Manager



## 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 558074 D01 DTS Meas Guidance v05, KDB 414788 D01 Radiated Test Site v01r01, CFR 47 FCC Part 2, CFR 47 FCC Part 15, ANSI C63.10-2013, ISED RSS-247 Issue 2 and ISED RSS-GEN Issue 5.

## 3. FACILITIES AND ACCREDITATION

|                           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Test Location             | UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Address                   | Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Accreditation Certificate | <p><b>A2LA (Certificate No.: 4102.01)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p><b>FCC (FCC Designation No.: CN1187)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p><b>IC(Company No.: 21320)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320.</p> <p><b>VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)</b><br/>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793.</p> <p>Facility Name:<br/>Chamber D, the VCCI registration No. is G-20019 and R-20004<br/>Shielding Room B , the VCCI registration No. is C-20012 and T-20011</p> |

Note:

1. All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China
2. The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.
3. For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OATS.



## 4. CALIBRATION AND UNCERTAINTY

### 4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognize national standards.

### 4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Test Item                                                                                                                                     | Uncertainty         |
|-----------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Uncertainty for Conduction emission test                                                                                                      | 3.62dB              |
| Uncertainty for Radiation Emission test(include Fundamental emission)<br>(9KHz-30MHz)                                                         | 2.2dB               |
| Uncertainty for Radiation Emission test(include Fundamental emission)<br>(30MHz-1GHz)                                                         | 4.00dB              |
| Uncertainty for Radiation Emission test<br>(1GHz to 40GHz)( include Fundamental emission)                                                     | 5.78dB(1-18GHz)     |
|                                                                                                                                               | 5.23dB (18GHz-26Gz) |
|                                                                                                                                               | 5.64dB (26GHz-40Gz) |
| Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2. |                     |



## 5. EQUIPMENT UNDER TEST

### 5.1. DESCRIPTION OF EUT

|                       |                               |                     |
|-----------------------|-------------------------------|---------------------|
| Product Name:         | Kami Secure Home Entry Sensor |                     |
| Model No.:            | YNS.2018                      |                     |
| Product Description   | Operation Frequency           | 2405 MHz ~ 2455 MHz |
|                       | Modulation Type               | Data Rate           |
|                       | Modulation Type               | O-QPSK              |
| Channels Step:        | Channels with 5MHz step       |                     |
| Sample Type:          | Fixed production              |                     |
| Test power grade:     | 10(manufacturer declare)      |                     |
| Test software of EUT: | SSCOM (manufacturer declare)  |                     |
| Antenna Type:         | Internal Antenna              |                     |
| Antenna Gain:         | 2.0 dBi                       |                     |
| Power Supply          | Battery                       | DC 3.0V             |

### 5.2. MAXIMUM OUTPUT POWER

| Antenna | Mode   | Frequency (MHz) | Channel Number | Max PK Conducted Power (dBm) |
|---------|--------|-----------------|----------------|------------------------------|
| 1       | Zigbee | 2405-2455       | 11-21          | 7.05                         |



### 5.3. CHANNEL LIST

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|---------|-----------------|
| 11      | 2405            | 12      | 2410            | 13      | 2415            | 14      | 2420            |
| 15      | 2425            | 16      | 2430            | 17      | 2435            | 18      | 2440            |
| 19      | 2445            | 20      | 2450            | 21      | 2455            |         |                 |

### 5.4. TEST CHANNEL CONFIGURATION

| Test Mode | Test Channel        | Frequency                 |
|-----------|---------------------|---------------------------|
| Zigbee    | CH 11, CH 16, CH 21 | 2405MHz, 2430MHz, 2455MHz |

### 5.5. THE WORSE CASE POWER SETTING PARAMETER

| The Worse Case Power Setting Parameter under 2400 ~ 2483.5MHz Band |                         |              |     |     |
|--------------------------------------------------------------------|-------------------------|--------------|-----|-----|
| Test Software                                                      |                         | SecureCRT    |     |     |
| Modulation Type                                                    | Transmit Antenna Number | Test Channel |     |     |
|                                                                    |                         | LCH          | MCH | HCH |
| O-QPSK                                                             | 1                       | 5            | 5   | 5   |

### 5.6. DESCRIPTION OF AVAILABLE ANTENNAS

| Ant. | Frequency (MHz) | Antenna Type     | Antenna Gain (dBi) |
|------|-----------------|------------------|--------------------|
| 1    | 2405-2455       | Internal Antenna | 2.0                |

| Test Mode | Transmit and Receive Mode | Description                                            |
|-----------|---------------------------|--------------------------------------------------------|
| Zigbee    | 1TX, 1RX                  | Chain 1 can be used as transmitting/receiving antenna. |



## 5.7. TEST ENVIRONMENT

| Environment Parameter | Selected Values During Tests |           |
|-----------------------|------------------------------|-----------|
| Relative Humidity     | 50 ~ 60%                     |           |
| Atmospheric Pressure: | 1025Pa                       |           |
| Temperature           | TN                           | 23 ~ 28°C |
| Voltage:              | VL                           | N/A       |
|                       | VN                           | DC 3.0V   |
|                       | VH                           | N/A       |

Note: VL= Lower Extreme Test Voltage  
VN= Nominal Voltage  
VH= Upper Extreme Test Voltage  
TN= Normal Temperature



## 5.8. DESCRIPTION OF TEST SETUP

### SUPPORT EQUIPMENT

| Item | Equipment | Brand Name | Model Name | P/N |
|------|-----------|------------|------------|-----|
| 1    | Laptop    | ThinkPad   | E550c      | N/A |

### I/O CABLES

| Cable No | Port       | Connector Type | Cable Type | Cable Length(m) | Remarks |
|----------|------------|----------------|------------|-----------------|---------|
| 1        | USB to TTL | USB to TTL     | USB        | 2.0 m           | N/A     |


### ACCESSORY

| Item | Accessory | Brand Name | Model Name | Description |
|------|-----------|------------|------------|-------------|
| 1    | N/A       | N/A        | N/A        | N/A         |

### TEST SETUP

The EUT can work in engineer mode with a software through a PC.

### SETUP DIAGRAM FOR TEST





## 6. MEASURING INSTRUMENT AND SOFTWARE USED

| Conducted Emissions                 |                                         |                  |                                  |               |               |                |                |
|-------------------------------------|-----------------------------------------|------------------|----------------------------------|---------------|---------------|----------------|----------------|
| Used                                | Equipment                               | Manufactur       | Model No.                        | Serial No.    | Upper Cal.    | Last Cal.      | Next Cal.      |
| <input checked="" type="checkbox"/> | EMI Test Receiver                       | R&S              | ESR3                             | 101961        | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | Two-Line V-Network                      | R&S              | ENV216                           | 101983        | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| Software                            |                                         |                  |                                  |               |               |                |                |
| Used                                | Description                             |                  | Manufacturer                     | Name          |               | Version        |                |
| <input checked="" type="checkbox"/> | Test Software for Conducted disturbance |                  | UL                               | Antenna port  |               | Ver. 7.2       |                |
| Radiated Emissions                  |                                         |                  |                                  |               |               |                |                |
| Used                                | Equipment                               | Manufactur       | Model No.                        | Serial No.    | Upper Cal.    | Last Cal.      | Next Cal.      |
| <input checked="" type="checkbox"/> | MXE EMI Receiver                        | KESIGHT          | N9038A                           | MY564000      | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | Hybrid Log Periodic Antenna             | TDK              | HLP-3003C                        | 130960        | Jan.09, 2016  | Sept. 17, 2018 | Sept. 17, 2021 |
| <input checked="" type="checkbox"/> | Preamplifier                            | HP               | 8447D                            | 2944A0909     | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | EMI Measurement Receiver                | R&S              | ESR26                            | 101377        | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | Horn Antenna                            | TDK              | HRN-0118                         | 130939        | Jan. 09, 2016 | Sept. 17,2018  | Sept. 17, 2021 |
| <input checked="" type="checkbox"/> | High Gain Horn                          | Schwarzbe        | BBHA-9170                        | 691           | Jan.06, 2016  | Aug. 11, 2018  | Aug. 11, 2019  |
| <input checked="" type="checkbox"/> | Preamplifier                            | TDK              | PA-02-0118                       | TRS-305-00066 | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | Preamplifier                            | TDK              | PA-02-2                          | TRS-307-00003 | Dec.12,2017   | Dec. 10, 2018  | Dec. 10, 2019  |
| <input checked="" type="checkbox"/> | Loop antenna                            | Schwarzbe        | 1519B                            | 00008         | Mar. 26,      | Mar. 26, 2016  | Mar. 26, 2019  |
| Software                            |                                         |                  |                                  |               |               |                |                |
| Used                                | Description                             |                  | Manufacturer                     | Name          |               | Version        |                |
| <input checked="" type="checkbox"/> | Test Software for Radiated disturbance  |                  | Farad                            | EZ-EMC        |               | Ver. UL-3A1    |                |
| Other instruments                   |                                         |                  |                                  |               |               |                |                |
| Used                                | Equipment                               | Manufactur<br>er | Model No.                        | Serial No.    | Upper Cal.    | Last Cal.      | Next Cal.      |
| <input checked="" type="checkbox"/> | Spectrum Analyzer                       | Keysight         | N9030A                           | MY55410512    | Dec.12,2017   | Dec.10,2018    | Dec.10,2019    |
| <input checked="" type="checkbox"/> | Power Sensor                            | Keysight         | U2021XA                          | MY57030004    | Dec.12,2017   | Dec.10,2018    | Dec.10,2019    |
| <input checked="" type="checkbox"/> | Power Meter                             | Keysight         | N1911A                           | MY55416024    | Dec.12,2017   | Dec.11,2018    | Dec.10,2019    |
| <input checked="" type="checkbox"/> | High Pass Filter                        | Wainwright       | WHKX10-5850-6500-1800-40SS       | 4             | Dec.12,2017   | Dec.11,2018    | Dec.10,2019    |
| <input checked="" type="checkbox"/> | Band Reject Filter                      | Wainwright       | WRCJV20-5440-5470-5725-5755-60SS | 1             | Dec.12,2017   | Dec.11,2018    | Dec.10,2019    |



## 7. MEASUREMENT METHODS

| No. | Test Item                                     | KDB Name                             | Section |
|-----|-----------------------------------------------|--------------------------------------|---------|
| 1   | 6 dB Bandwidth                                | KDB 558074 D01 DTS Meas Guidance v05 | 8.2     |
| 2   | Peak Output Power                             | KDB 558074 D01 DTS Meas Guidance v05 | 8.3.1.3 |
| 3   | Power Spectral Density                        | KDB 558074 D01 DTS Meas Guidance v05 | 8.4     |
| 4   | Out-of-band emissions in non-restricted bands | KDB 558074 D01 DTS Meas Guidance v05 | 8.5     |
| 5   | Out-of-band emissions in restricted bands     | KDB 558074 D01 DTS Meas Guidance v05 | 8.6     |
| 6   | Band-edge                                     | KDB 558074 D01 DTS Meas Guidance v05 | 8.7     |
| 7   | Conducted Emission Test For AC Power Port     | ANSI C63.10-2013                     | 6.2     |



## 8. ANTENNA PORT TEST RESULTS

### 8.1. ON TIME AND DUTY CYCLE


#### LIMITS

None; for reporting purposes only

#### PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method

#### TEST SETUP



#### TEST ENVIRONMENT

|                     |         |                   |          |
|---------------------|---------|-------------------|----------|
| Temperature         | 25°C    | Relative Humidity | 58 %     |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 3.0 V |

#### RESULTS

| Mode   | On Time (msec) | Period (msec) | Duty Cycle x (Linear) | Duty Cycle (%) | Duty Cycle Correction Factor (db) | 1/T Minimum VBW (KHz) | Final setting For VBW (KHz) |
|--------|----------------|---------------|-----------------------|----------------|-----------------------------------|-----------------------|-----------------------------|
| Zigbee | 100.3          | 100.3         | 1                     | 100            | 0                                 | 100                   | 0.01                        |


Note:

Duty Cycle Correction Factor= $10\log(1/x)$ .

Where: x is Duty Cycle (Linear)

Where: T is On Time (transmit duration)

If that calculated VBW is not available on the analyzer then the next higher value should be used.





## 8.2. 6 dB DTS BANDWIDTH AND 99% BANDWIDTH

### LIMITS

| CFR 47FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 2 |                        |                              |                       |
|-------------------------------------------------------------|------------------------|------------------------------|-----------------------|
| Section                                                     | Test Item              | Limit                        | Frequency Range (MHz) |
| CFR 47 FCC 15.247(a)(2)<br>ISED RSS-247 5.2 (a)             | 6dB Bandwidth          | $\geq 500\text{KHz}$         | 2400-2483.5           |
| ISED RSS-Gen Clause 6.6                                     | 99% Occupied Bandwidth | For reporting purposes only. | 2400-2483.5           |


### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

|                  |                                                                                                                    |
|------------------|--------------------------------------------------------------------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test                                                                     |
| Detector         | Peak                                                                                                               |
| RBW              | For 6 dB Bandwidth :100K<br>For 99% Occupied Bandwidth :1% to 5% of the occupied bandwidth                         |
| VBW              | For 6dB Bandwidth : $\geq 3 \times \text{RBW}$<br>For 99% Occupied Bandwidth : approximately $3 \times \text{RBW}$ |
| Trace            | Max hold                                                                                                           |
| Sweep            | Auto couple                                                                                                        |

Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB/99% relative to the maximum level measured in the fundamental emission.

### TEST SETUP






## TEST ENVIRONMENT



|                     |         |                   |         |
|---------------------|---------|-------------------|---------|
| Temperature         | 25°C    | Relative Humidity | 58 %    |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 30 V |

## RESULTS

| Channel | 6dB bandwidth (MHz) | 99% bandwidth (MHz) | Result |
|---------|---------------------|---------------------|--------|
| Low     | 1.668               | 2.2700              | Pass   |
| Middle  | 1.686               | 2.2476              | Pass   |
| High    | 1.675               | 2.2545              | Pass   |

## TEST GRAPHS







### 8.3. PEAK CONDUCTED OUTPUT POWER

#### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 2 |                   |                 |                       |
|--------------------------------------------------------------|-------------------|-----------------|-----------------------|
| Section                                                      | Test Item         | Limit           | Frequency Range (MHz) |
| CFR 47 FCC 15.247(b)(3)<br>ISED RSS-247 5.4 (e)              | Peak Output Power | 1 watt or 30dBm | 2400-2483.5           |

#### TEST PROCEDURE


Connect the UUT to the spectrum analyzer and use the following settings:

|                  |                                                |
|------------------|------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector         | Peak                                           |
| RBW              | $\geq$ DTS bandwidth                           |
| VBW              | $\geq 3 \times$ RBW                            |
| Span             | $3 \times$ RBW                                 |
| Trace            | Max hold                                       |
| Sweep time       | Auto couple.                                   |


Allow trace to fully stabilize and use peak marker function to determine the peak amplitude level.

#### TEST SETUP

for peak power measurement:



for average power measurement:





## TEST ENVIRONMENT


|                     |         |                   |          |
|---------------------|---------|-------------------|----------|
| Temperature         | 25°C    | Relative Humidity | 58 %     |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 3.0 V |



## RESULTS

| Test Channel | Maximum Conducted Output Power (PK) | Result |
|--------------|-------------------------------------|--------|
|              | (dBm)                               |        |
| Low          | 7.05                                | Pass   |
| Middle       | 6.64                                | Pass   |
| High         | 6.23                                | Pass   |

| Test Channel | Maximum Conducted Output Power (AV) | Result |
|--------------|-------------------------------------|--------|
|              | (dBm)                               |        |
| Low          | 7.02                                | Pass   |
| Middle       | 6.56                                | Pass   |
| High         | 6.17                                | Pass   |

## TEST GRAPHS







## 8.4. POWER SPECTRAL DENSITY

### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 2 |                        |                         |                       |
|--------------------------------------------------------------|------------------------|-------------------------|-----------------------|
| Section                                                      | Test Item              | Limit                   | Frequency Range (MHz) |
| CFR 47 FCC §15.247 (e)<br>ISED RSS-247 5.2 (b)               | Power Spectral Density | 8 dBm in any 3 kHz band | 2400-2483.5           |

### TEST PROCEDURE


Connect the UUT to the spectrum analyser and use the following settings:

|                  |                                                      |
|------------------|------------------------------------------------------|
| Center Frequency | The center frequency of the channel under test       |
| Detector         | Peak                                                 |
| RBW              | $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ |
| VBW              | $\geq 3 \times \text{RBW}$                           |
| Span             | $1.5 \times \text{DTS bandwidth}$                    |
| Trace            | Max hold                                             |
| Sweep time       | Auto couple.                                         |

Allow trace to fully stabilize and use the peak marker function to determine the maximum amplitude level within the RBW.

If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

### TEST SETUP





### TEST ENVIRONMENT



|                     |         |                   |          |
|---------------------|---------|-------------------|----------|
| Temperature         | 25°C    | Relative Humidity | 58 %     |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 3.0 V |

### RESULTS TABLE

| Test Channel | Power Spectral Density (dBm/100kHz) | Limit (dBm/3kHz) | Result |
|--------------|-------------------------------------|------------------|--------|
| Low          | 3.066                               | 8                | PASS   |
| Middle       | 2.604                               | 8                | PASS   |
| High         | 2.178                               | 8                | PASS   |

### TEST GRAPHS:







## 8.5. CONDUCTED BANDEDGE AND SPURIOUS EMISSIONS

### LIMITS

| CFR 47 FCC Part15 (15.247) Subpart C<br>ISED RSS-247 ISSUE 2 |                                                 |                                                                                                                               |
|--------------------------------------------------------------|-------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| Section                                                      | Test Item                                       | Limit                                                                                                                         |
| CFR 47 FCC §15.247 (d)<br>ISED RSS-247 5.5                   | Conducted<br>Bandedge and<br>Spurious Emissions | at least 20 dB below that in the 100 kHz<br>bandwidth within the band that contains the<br>highest level of the desired power |

### TEST PROCEDURE

Connect the UUT to the spectrum analyser and use the following settings:

|                  |                                                |
|------------------|------------------------------------------------|
| Center Frequency | The center frequency of the channel under test |
| Detector         | Peak                                           |
| RBW              | 100KHz                                         |
| VBW              | $\geq 3 \times \text{RBW}$                     |
| Span             | 1.5 x DTS bandwidth                            |
| Trace            | Max hold                                       |
| Sweep time       | Auto couple.                                   |


Use the peak marker function to determine the maximum PSD level.

|                    |                                                                               |
|--------------------|-------------------------------------------------------------------------------|
| Span               | Set the center frequency and span to encompass frequency range to be measured |
| Detector           | Peak                                                                          |
| RBW                | 100KHz                                                                        |
| VBW                | $\geq 3 \times \text{RBW}$                                                    |
| measurement points | $\geq \text{span}/\text{RBW}$                                                 |
| Trace              | Max hold                                                                      |
| Sweep time         | Auto couple.                                                                  |

Use the peak marker function to determine the maximum amplitude level.



### TEST SETUP



### TEST ENVIRONMENT

|                     |         |                   |          |
|---------------------|---------|-------------------|----------|
| Temperature         | 25°C    | Relative Humidity | 58 %     |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 3.0 V |



### Part I: CONDUCTED BANDEDGE

#### RESULTS TABLE

| Test Mode | Test Channel | Carrier Power[dBm] | Max. Spurious Level [dBm] | Limit [dBm] | Verdict |
|-----------|--------------|--------------------|---------------------------|-------------|---------|
| Zigbee    | LCH          | 3.521              | -41.014                   | -19.91      | PASS    |
|           | HCH          | 1.940              | -40.644                   | -19.62      | PASS    |



## TEST GRAPHS





**Part II: CONDUCTED SPURIOUS EMISSIONS**

**RESULTS TABLE**


| Test Mode | Channel | Pref(dBm) | Puw(dBm) | Verdict |
|-----------|---------|-----------|----------|---------|
| Zigbee    | LCH     | 2.94      | <Limit   | PASS    |
|           | MCH     | 2.54      | <Limit   | PASS    |
|           | HCH     | 2.04      | <Limit   | PASS    |



## TEST GRAPHS



Pref test Plot




Puw test Plot












### Pref test Plot



### Puw test Plot















### Pref test Plot



### Puw test Plot









## 9. RADIATED TEST RESULTS

### LIMITS

Please refer to CFR 47 FCC §15.205 and §15.209

Please refer to ISSED RSS-GEN Clause 8.9 and Clause 8.10

Radiation Disturbance Test Limit for FCC (Class B)(9KHz-1GHz)

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009~0.490     | 2400/F(KHz)                       | 300                           |
| 0.490~1.705     | 24000/F(KHz)                      | 30                            |
| 1.705~30.0      | 30                                | 30                            |
| 30~88           | 100                               | 3                             |
| 88~216          | 150                               | 3                             |
| 216~960         | 200                               | 3                             |
| 960~1000        | 500                               | 3                             |

Note: 1) At frequencies at or above 30 MHz, measurements may be performed at a distance other than what is specified provided: measurements are not made in the near field except where it can be shown that near field measurements are appropriate due to the characteristics of the device; and it can be demonstrated that the signal levels needed to be measured at the distance employed can be detected by the measurement equipment. Measurements shall not be performed at a distance greater than 30 meters unless it can be further demonstrated that measurements at a distance of 30 meters or less are impractical. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse linear-distance for field strength measurements; inverse-linear-distance-squared for power density measurements).

(2) At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). This paragraph (f) shall not apply to Access BPL devices operating below 30 MHz.


Radiation Disturbance Test Limit for FCC (Above 1G)

| Frequency (MHz) | dB(uV/m) (at 3 meters) |         |
|-----------------|------------------------|---------|
|                 | Peak                   | Average |
| Above 1000      | 74                     | 54      |

About Restricted bands of operation please refer to RSS-Gen section 8.10 and FCC §15.205 (a)

## TEST SETUP AND PROCEDURE

Below 30MHz




The setting of the spectrum analyser

|       |                                                            |
|-------|------------------------------------------------------------|
| RBW   | 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz) |
| VBW   | 200Hz (From 9kHz to 0.15MHz)/ 9KHz (From 0.15MHz to 30MHz) |
| Sweep | Auto                                                       |
| Trace | Max hold                                                   |

1. The testing follows the guidelines in ANSI C63.10-2013
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Below 1G and above 30MHz




The setting of the spectrum analyser

|          |          |
|----------|----------|
| RBW      | 120K     |
| VBW      | 300K     |
| Sweep    | Auto     |
| Detector | Peak/QP  |
| Trace    | Max hold |

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1G




The setting of the spectrum analyser

|          |                             |
|----------|-----------------------------|
| RBW      | 1M                          |
| VBW      | PEAK: 3M<br>AVG: see note 6 |
| Sweep    | Auto                        |
| Detector | Peak                        |
| Trace    | Max hold                    |

1. The testing follows the guidelines in ANSI C63.10-2013.
2. The EUT was arranged to its worst case and then tune the antenna tower (1.5 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector. For the Duty Cycle and Correction Factor please refer to clause 8.1. ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

Note 2: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.


### **TEST ENVIRONMENT**

|                     |         |                   |          |
|---------------------|---------|-------------------|----------|
| Temperature         | 25°C    | Relative Humidity | 58 %     |
| Atmosphere Pressure | 101 kPa | Test Voltage      | DC 3.0 V |

### **RESULTS**

## 9.1. RESTRICTED BANDEDGE

### RESTRICTED BANDEDGE (LOW CHANNEL, HORIZONTAL)




| No. | Frequency<br>(MHz) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark  |
|-----|--------------------|--------------------|-------------------|----------------|---------|
| 1   | 2343.6394          | 52.35              | 74.00             | -21.65         | Peak    |
|     |                    | 38.98              | 54.00             | -15.02         | Average |
| 2   | 2390.0000          | 51.91              | 74.00             | -22.09         | Peak    |
|     |                    | 39.69              | 54.00             | -14.31         | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
 3. AVG: VBW=10 Hz.  
 4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (LOW CHANNEL, VERTICAL)**




| No. | Frequency | Result   | Limit    | Margin | Remark  |
|-----|-----------|----------|----------|--------|---------|
|     | (MHz)     | (dBuV/m) | (dBuV/m) | (dB)   |         |
| 1   | 2346.2196 | 52.66    | 74.00    | -21.34 | Peak    |
|     |           | 39.64    | 54.00    | -14.36 | Average |
| 2   | 2390.0000 | 52.38    | 74.00    | -21.62 | Peak    |
|     |           | 39.44    | 54.00    | -14.56 | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10 Hz.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, HORIZONTAL)**




| No. | Frequency | Result   | Limit    | Margin | Remark  |
|-----|-----------|----------|----------|--------|---------|
|     | (MHz)     | (dBuV/m) | (dBuV/m) | (dB)   |         |
| 1   | 2483.5000 | 52.55    | 74.00    | -21.45 | Peak    |
|     |           | 39.96    | 54.00    | -14.04 | Average |
| 2   | 2526.8047 | 52.62    | 74.00    | -21.38 | Peak    |
|     |           | 39.59    | 54.00    | -14.41 | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10 Hz.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



**RESTRICTED BANDEDGE (HIGH CHANNEL, VERTICAL)**




| No. | Frequency | Result   | Limit    | Margin | Remark  |
|-----|-----------|----------|----------|--------|---------|
|     | (MHz)     | (dBuV/m) | (dBuV/m) | (dB)   |         |
| 1   | 2483.5000 | 52.13    | 74.00    | -21.87 | Peak    |
|     |           | 39.12    | 54.00    | -14.88 | Average |
| 2   | 2508.5509 | 52.07    | 74.00    | -21.93 | Peak    |
|     |           | 38.43    | 54.00    | -15.57 | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10 Hz.  
4. Only the worst case emission was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.



## 9.2. SPURIOUS EMISSIONS (1~18GHz)


### HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, HORIZONTAL)



| No. | Frequency  | Result    | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|-----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV /m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1196.0654  | 37.14     | 74.00        | -36.86        | --          | --           | Peak    |
| 2   | 3477.5796  | 45.41     | 74.00        | -28.59        | --          | --           | Peak    |
| 3   | 4252.7088  | 45.84     | 74.00        | -28.16        | --          | --           | Peak    |
| 4   | 7740.7901  | 48.57     | 74.00        | -25.43        | --          | --           | Peak    |
| 5   | 14066.8445 | 52.97     | 74.00        | -21.03        | --          | --           | Peak    |
| 6   | 17197.3662 | 55.28     | 74.00        | -18.72        | --          | --           | Peak    |
|     |            | 44.63     | --           | --            | 54.00       | -9.37        | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10Hz.  
4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


**HARMONICS AND SPURIOUS EMISSIONS (LOW CHANNEL, VERTICAL)**



| No. | Frequency  | Result   | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV/m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1199.3998  | 37.66    | 74.00        | -36.34        | --          | --           | Peak    |
| 2   | 1795.5985  | 41.79    | 74.00        | -32.21        | --          | --           | Peak    |
| 3   | 6285.5476  | 47.82    | 74.00        | -26.18        | --          | --           | Peak    |
| 4   | 11581.4302 | 50.48    | 74.00        | -23.52        | --          | --           | Peak    |
| 5   | 14056.8428 | 53.30    | 74.00        | -20.70        | --          | --           | Peak    |
| 6   | 17629.9383 | 55.07    | 74.00        | -18.93        | --          | --           | Peak    |
|     |            | 44.70    | --           | --            | 54.00       | -9.30        | Average |

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10Hz.  
4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, HORIZONTAL)



| No. | Frequency  | Result   | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV/m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1795.5985  | 39.90    | 74.00        | -34.10        | --          | --           | Peak    |
| 2   | 2588.5295  | 43.61    | 74.00        | -30.39        | --          | --           | Peak    |
| 3   | 4565.2609  | 45.74    | 74.00        | -28.26        | --          | --           | Peak    |
| 4   | 8003.3339  | 48.19    | 74.00        | -25.81        | --          | --           | Peak    |
| 5   | 12446.5744 | 51.94    | 74.00        | -22.06        | --          | --           | Peak    |
| 6   | 17049.8416 | 54.92    | 74.00        | -19.08        | --          | --           | Peak    |
|     |            | 44.46    | --           | --            | 54.00       | -9.54        | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10Hz.  
4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.


### HARMONICS AND SPURIOUS EMISSIONS (MID CHANNEL, VERTICAL)



| No. | Frequency  | Result   | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV/m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1196.7322  | 38.39    | 74.00        | -35.61        | --          | --           | Peak    |
| 2   | 1798.9330  | 40.84    | 74.00        | -33.16        | --          | --           | Peak    |
| 3   | 2294.4315  | 48.35    | 74.00        | -25.65        | --          | --           | Peak    |
| 4   | 8010.8351  | 49.21    | 74.00        | -24.79        | --          | --           | Peak    |
| 5   | 13924.3207 | 52.65    | 74.00        | -21.35        | --          | --           | Peak    |
| 6   | 17177.3629 | 54.65    | 74.00        | -19.35        | --          | --           | Peak    |
|     |            | 44.28    | --           | --            | 54.00       | -9.72        | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
 2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
 3. AVG: VBW=10Hz.  
 4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
 5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

### HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, HORIZONTAL)




| No. | Frequency  | Result   | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV/m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1395.4652  | 38.29    | 74.00        | -35.71        | --          | --           | Peak    |
| 2   | 2583.1944  | 43.98    | 74.00        | -30.02        | --          | --           | Peak    |
| 3   | 8078.3464  | 49.25    | 74.00        | -24.75        | --          | --           | Peak    |
| 4   | 11468.9115 | 51.03    | 74.00        | -22.97        | --          | --           | Peak    |
| 5   | 14024.3374 | 53.76    | 74.00        | -20.24        | --          | --           | Peak    |
| 6   | 17164.8608 | 55.34    | 74.00        | -18.66        | --          | --           | Peak    |
|     |            | 43.86    | --           | --            | 54.00       | -10.14       | Average |

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10Hz.  
4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.



**HARMONICS AND SPURIOUS EMISSIONS (HIGH CHANNEL, VERTICAL)**




| No. | Frequency  | Result    | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark  |
|-----|------------|-----------|--------------|---------------|-------------|--------------|---------|
|     | (MHz)      | (dBuV /m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |         |
| 1   | 1502.8343  | 43.03     | 74.00        | -30.97        | --          | --           | Peak    |
| 2   | 2373.7913  | 47.45     | 74.00        | -26.55        | --          | --           | Peak    |
| 3   | 6353.0588  | 47.64     | 74.00        | -26.36        | --          | --           | Peak    |
| 4   | 11391.3986 | 50.96     | 74.00        | -23.04        | --          | --           | Peak    |
| 5   | 13976.8295 | 53.51     | 74.00        | -20.49        | --          | --           | Peak    |
| 6   | 17129.8550 | 54.87     | 74.00        | -19.13        | --          | --           | Peak    |
|     |            | 44.05     | --           | --            | 54.00       | -9.95        | Average |

- Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. AVG: VBW=10Hz.  
4. Filter losses were only considered in then spurious frequency bands and the authorized Band was not corrected for BRF losses.  
5. Proper operation of the transmitter prior to adding the filter to the measurement chain.

## 9.4. SPURIOUS EMISSIONS 18G ~ 26GHz


### SPURIOUS EMISSIONS (LCH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)



| No. | Frequency  | Result   | Limit    | Margin | Limit    | Margin | Remark |
|-----|------------|----------|----------|--------|----------|--------|--------|
|     | (MHz)      | (dBuV/m) | (Peak)   | (Peak) | (Ave)    | (Ave)  |        |
|     |            |          | (dBuV/m) | (dB)   | (dBuV/m) | (dB)   |        |
| 1   | 18245.6746 | 46.81    | 74.00    | -27.19 | 54.00    | -7.19  | peak   |
| 2   | 19504.6505 | 45.39    | 74.00    | -28.61 | 54.00    | -8.61  | peak   |
| 3   | 20624.2124 | 45.30    | 74.00    | -28.70 | 54.00    | -8.70  | peak   |
| 4   | 21957.1457 | 45.48    | 74.00    | -28.52 | 54.00    | -8.52  | peak   |
| 5   | 24654.4654 | 46.20    | 74.00    | -27.80 | 54.00    | -7.80  | peak   |
| 6   | 25769.7770 | 48.90    | 74.00    | -25.10 | 54.00    | -5.10  | peak   |

Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. Peak: Peak detector.  
4. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.

**SPURIOUS EMISSIONS (LCH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



| No. | Frequency  | Result    | Limit (Peak) | Margin (Peak) | Limit (Ave) | Margin (Ave) | Remark |
|-----|------------|-----------|--------------|---------------|-------------|--------------|--------|
|     | (MHz)      | (dBuV /m) | (dBuV/m)     | (dB)          | (dBuV/m)    | (dB)         |        |
| 1   | 18152.1652 | 45.94     | 74.00        | -28.06        | 54.00       | -8.06        | peak   |
| 2   | 19593.9094 | 45.43     | 74.00        | -28.57        | 54.00       | -8.57        | peak   |
| 3   | 21706.3706 | 45.66     | 74.00        | -28.34        | 54.00       | -8.34        | peak   |
| 4   | 24726.7227 | 47.36     | 74.00        | -26.64        | 54.00       | -6.64        | peak   |
| 5   | 24726.7227 | 47.36     | 74.00        | -26.64        | 54.00       | -6.64        | peak   |
| 6   | 25638.8639 | 49.11     | 74.00        | -24.89        | 54.00       | -4.89        | peak   |


Note: 1. If Peak Result complies with AV limit, AV Result is deemed to comply with AV limit.  
2. Test setup: RBW: 1 MHz, VBW: 3 MHz, Sweep time: auto.  
3. Peak: Peak detector.  
4. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.

Note: All test mode has been tested, only the worst data record in the report



## 9.5. SPURIOUS EMISSIONS 30M ~ 1 GHz

### SPURIOUS EMISSIONS (LCH CHANNEL, WORST-CASE CONFIGURATION, HORIZONTAL)




| No. | Frequency<br>(MHz) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|--------------------|-------------------|----------------|--------|
| 1   | 48.4318            | 17.60              | 40.00             | -22.40         | QP     |
| 2   | 125.1665           | 21.79              | 43.50             | -21.71         | QP     |
| 3   | 167.9478           | 22.10              | 43.50             | -21.40         | QP     |
| 4   | 228.8699           | 27.89              | 46.00             | -18.11         | QP     |
| 5   | 457.8128           | 30.18              | 46.00             | -15.82         | QP     |
| 6   | 722.8433           | 32.53              | 46.00             | -13.47         | QP     |

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.  
3. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.



**SPURIOUS EMISSIONS (LCH CHANNEL, WORST-CASE CONFIGURATION, VERTICAL)**



| No. | Frequency | Result   | Limit    | Margin | Remark |
|-----|-----------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 47.3647   | 20.92    | 40.00    | -19.08 | QP     |
| 2   | 74.1394   | 16.53    | 40.00    | -23.47 | QP     |
| 3   | 127.5918  | 21.25    | 43.50    | -22.25 | QP     |
| 4   | 228.8699  | 22.72    | 46.00    | -23.28 | QP     |
| 5   | 457.8128  | 29.74    | 46.00    | -16.26 | QP     |
| 6   | 724.2984  | 33.24    | 46.00    | -12.76 | QP     |

Note: 1. If Peak Result complies with QP limit, QP Result is deemed to comply with QP limit.  
2. Test setup: RBW: 120 kHz, VBW: 300 kHz, Sweep time: auto.  
3. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.


Note: All test mode has been tested, only the worst data record in the report



## 9.6. SPURIOUS EMISSIONS BELOW 30M

### SPURIOUS EMISSIONS (LCH CHANNEL, WORST-CASE CONFIGURATION)

| Channel | Frequency Range | Verdict |
|---------|-----------------|---------|
| MCH     | 9KHz~150KHz     | PASS    |




| No. | Frequency<br>(MHz) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.0220             | -32.19             | 40.75             | -72.94         | Peak   |
| 2   | 0.0269             | -33.94             | 39.01             | -72.95         | Peak   |
| 3   | 0.0439             | -36.23             | 34.75             | -70.98         | Peak   |
| 4   | 0.0659             | -38.45             | 31.23             | -69.68         | Peak   |
| 5   | 0.0879             | -40.91             | 28.73             | -69.64         | Peak   |
| 6   | 0.1100             | -42.80             | 26.78             | -69.58         | Peak   |

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.



| Channel | Frequency Range | Verdict |
|---------|-----------------|---------|
| MCH     | 150KHz~490KHz   | PASS    |




| No. | Frequency<br>(MHz) | Result<br>(dBuV/m) | Limit<br>(dBuV/m) | Margin<br>(dB) | Remark |
|-----|--------------------|--------------------|-------------------|----------------|--------|
| 1   | 0.2037             | -35.67             | 21.42             | -57.09         | Peak   |
| 2   | 0.2288             | -35.43             | 20.41             | -55.84         | Peak   |
| 3   | 0.2976             | -37.58             | 18.13             | -55.71         | Peak   |
| 4   | 0.3425             | -37.29             | 16.91             | -54.20         | Peak   |
| 5   | 0.4235             | -35.88             | 14.86             | -50.74         | Peak   |
| 6   | 0.4634             | -20.61             | 13.76             | -34.37         | Peak   |

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.



| Channel | Frequency Range | Verdict |
|---------|-----------------|---------|
| MCH     | 490KHz~30MHz    | PASS    |



| No. | Frequency | Result   | Limit    | Margin | Remark |
|-----|-----------|----------|----------|--------|--------|
|     | (MHz)     | (dBuV/m) | (dBuV/m) | (dB)   |        |
| 1   | 0.9268    | 12.43    | 28.26    | -15.83 | Peak   |
| 2   | 1.3960    | 8.31     | 24.70    | -16.39 | Peak   |
| 3   | 1.8712    | 4.50     | 29.54    | -25.04 | Peak   |
| 4   | 2.3287    | 1.52     | 29.54    | -28.02 | Peak   |
| 5   | 2.7773    | -2.48    | 29.54    | -32.02 | Peak   |
| 6   | 3.9902    | -1.72    | 29.54    | -31.26 | Peak   |

Note:

1. If Peak Result complies with AV and QP limit, AV and QP Result are deemed to comply with AV limit.
2. Pre-testing all test modes and all test channels, but only data of the worst case is shown in this test report.



## 10. ANTENNA REQUIREMENTS

### Applicable requirements

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

### RESULTS

Complies

**END OF REPORT**

Page 61 of 61