

TEST REPORT

Product Name : Comet Q
Model Number : GL-RMQ1
FCC ID : 2AFIW-RMQ1

Prepared for : GL Technologies (Hong Kong) Limited
Address : Unit 601, Building 5W, Hong Kong Science Park, Shatin,
N.T., Hong Kong

Prepared by : EMTEK (SHENZHEN) CO., LTD.
Address : Building 69, Majialong Industry Zone, Nanshan District,
Shenzhen, Guangdong, China

Tel: (0755) 26954280
Fax: (0755) 26954282

Report Number : ENS2512300108W01801R
Date(s) of Tests : May 18, 2026 to May 21, 2026
Date of Issue : May 22, 2026

\$二维码\$

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION	4
2. Description of Equipment Under Test	6
3. SAR Measurement System	7
3.1 Definition of Specific Absorption Rate (SAR)	7
3.2 SPEAG DASY System	7
3.2.1 Robot	8
3.2.2 Probes	9
3.2.3 Data Acquisition Electronics (DAE)	9
3.2.4 Phantoms	10
3.2.5 Device Holder	11
3.2.6 System Validation Dipoles	11
3.2.7 Tissue Simulating Liquids	12
3.3 SAR System Verification	14
3.4 SAR Measurement Procedure	15
3.4.1 Area & Zoom Scan Procedure	15
3.4.2 VolumeScan Procedure	15
3.4.3 Power Drift Monitoring	16
3.4.4 Spatial Peak SAR Evaluation	16
3.4.5 SAR Averaged Methods	16
4. SAR Measurement Evaluation	17
4.1 Applicable Standards	17
4.2 EUT Testing Position	17
4.2.1 Hand-held usage of the device, not at the head or torso	17
4.2.2 SAR Test Exclusion Evaluations	19
4.3 Tissue Verification	21
4.4 System Validation	21
4.5 System Verification	22
4.6 Maximum Output Power	23
4.6.1 Maximum Conducted Power	23
4.7 SAR Testing Results	29
4.7.1 SAR Test Reduction Considerations	29
4.7.2 SAR Results for Body Exposure Condition	30
4.7.3 2.4GHz 802.11g/n OFDM SAR Test Exclusion Consideration:	32
4.7.4 SAR Measurement Variability	33
5. Calibration of Test Equipment	34
6. Measurement Uncertainty	35
7. Information on the Testing Laboratories	39
 Appendix A.SAR Plots of System Verification	
Appendix B.SAR Plots of SAR Measurement	
Appendix C.Calibration Certificate for Probe and Dipole	
Appendix D.Photographs of EUT and Setup	

Modified Information

Version	Report No.	Revision Date	Summary
Ver.1.0	ENS2512300108W01801R	/	Original Report

1. TEST RESULT CERTIFICATION

Applicant : GL Technologies (Hong Kong) Limited
Address : Unit 601, Building 5W, Hong Kong Science Park, Shatin, N.T., Hong Kong
Manufacturer : GL Technologies (Hong Kong) Limited
Address : Unit 601, Building 5W, Hong Kong Science Park, Shatin, N.T., Hong Kong
EUT : Comet Q
Model Name : GL-RMQ1
Trademark : **GL·iNet**


Measurement Procedure Used:

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 2 (2.1093) , IEEE/ANSI C95.1:2006, IEEE 1528:2013 (KDB 865664 D01 v01r04, KDB 865664 D02 v01r02, KDB 248227 D01 v02r02 KDB 447498 D01 v06, KDB 616217 D04 v01r02)	PASS
This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.	

CERTIFICATION: The above equipment have been tested by EMTEK (SHENZHEN) CO., LTD. Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. This report shall not be reproduced, except in full, without the written approval of EMTEK (SHENZHEN) CO., LTD.

Date of Test : May 18, 2026 to May 21, 2026

Prepared by : 
Cai Junjiong/Editor

Reviewer : 
Xia Lili/Supervisor

Approved & Authorized Signer : 
Wang Li/Manager

Summary of Maximum SAR Value:

Frequency Band		Maximum Report SAR (W/kg)1g	
		Body SAR _{1g} (0 mm Gap)(W/kg)	Limbs SAR _{10g} (0 mm Gap)(W/kg)
		Antenna	Antenna
WIFI	2.4G WLAN	0.520	0.242
	5.2G WLAN	0.750	0.302
	5.3G WLAN	0.834	0.311
	5.6G WLAN	0.653	0.264
	5.8G WLAN	0.366	0.136
Maximum Report SAR		0.834	0.311
Limits (W/kg)		1.60	4.00
Test Verdict		PASS	PASS

Note:

1. The SAR limit (**Head & Body: SAR_{1g}1.6 W/kg, Extremity: SAR_{10g} 4.0 W/kg**)for general population/uncontrolled exposure is specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-2006.

2. Description of Equipment Under Test

EUT Type	Comet Q
Trade Mark	GL Technologies (Hong Kong) Limited
Model Name	GL-RMQ1
Tx Frequency Bands (Unit: MHz)	2412-2472MHz for 802.11b/g/ n(HT20) 2422-2462MHz for 802.11n(HT40) 5150MHz-5250MHz for 802.11a/n(HT20)/ n(HT40)/ac(VHT20) /ac(VHT40) /ax(HE20) /ax(HE40) 5250MHz-5350MHz for 802.11a/n(HT20)/ n(HT40)/ac(VHT20) /ac(VHT40) /ax(HE20) /ax(HE40) 5470MHz-5725MHz for 802.11a/n(HT20)/ n(HT40)/ac(VHT20) /ac(VHT40) /ax(HE20) /ax(HE40) 5725MHz-5850MHz for 802.11a/n(HT20)/ n(HT40)/ac(VHT20) /ac(VHT40) /ax(HE20) /ax(HE40)
Uplink Modulations	DSSS for 802.11b OFDM for 802.11a/g/n/ac/ax
Maximum Tune-up Conducted Power (Unit: dBm)	WLAN 2.4G:14.50 WLAN 5.2G:11.50 WLAN 5.3G:12.00 WLAN 5.6G:11.50 WLAN 5.8G:11.50
Power Supply	type C cable 5V 2A
Antenna Type	Dual-band WIFI FPC Bracket Antenna

3. SAR Measurement System

3.1 Definition of Specific Absorption Rate (SAR)

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$

SAR is expressed in units of Watts per kilogram (W/kg)

SAR measurement can be related to the electrical field in the tissue by

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

3.2 SPEAG DASY System

DASY system consists of high precision robot, probe alignment sensor, phantom, robot controller, controlled measurement server and near-field probe. The robot includes six axes that can move to the precision position of the DASY5 software defined. The DASY software can define the area that is detected by the probe. The robot is connected to controlled box. Controlled measurement server is connected to the controlled robot box. The DAE includes amplifier, signal multiplexing, AD converter, offset measurement and surface detection. It is connected to the Electro-optical coupler (ECO). The ECO performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC.




Fig-3.1 DASY System Setup

3.2.1 Robot

The DASYsystem uses the high precision robots from Stäubli SA (France). For the 6-axis controller system, the robot controller version (DASY5: CS8c) from Stäubli is used. The Stäubli robot series have many features that are important for our application:

- High precision (repeatability ± 0.035 mm)
- High reliability (industrial design)
- Jerk-free straight movements
- Low ELF interference (the closed metallic construction shields against motor control fields)




Fig-3.2 DASY5

3.2.2 Probes

The SAR measurement is conducted with the dosimetric probe. The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency.

Model	EX3DV4	
Construction	Symmetrical design with triangular core. Built-in shielding against static charges. PEEK enclosure material (resistant to organic solvents, e.g., DGBE).	
Frequency	10 MHz to 6 GHz Linearity: ± 0.2 dB	
Directivity	± 0.3 dB in HSL (rotation around probe axis) ± 0.5 dB in tissue material (rotation normal to probe axis)	
Dynamic Range	10 μ W/g to 100 mW/g Linearity: ± 0.2 dB (noise: typically < 1 μ W/g)	
Dimensions	Overall length: 337 mm (Tip: 20 mm) Tip diameter: 2.5 mm (Body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

3.2.3 Data Acquisition Electronics (DAE)

Model	DAE4	
Construction	Signal amplifier, multiplexer, A/D converter and control logic. Serial optical link for communication with DASY embedded system (fully remote controlled). Two step probe touch detector for mechanical surface detection and emergency robot stop.	
Measurement Range	-100 to +300 mV (16 bit resolution and two range settings: 4mV, 400mV)	
Input Offset Voltage	< 5 μ V (with auto zero)	
Input Bias Current	< 50 fA	
Dimensions	60 x 60 x 68 mm	


3.2.4 Phantoms

Model	Twin SAM	
Construction	The shell corresponds to the specifications of the Specific Anthropomorphic Mannequin (SAM) phantom defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents evaporation of the liquid. Reference markings on the phantom allow the complete setup of all predefined phantom positions and measurement grids by teaching three points with the robot.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2 ± 0.2 mm (6 ± 0.2 mm at ear point)	
Dimensions	Length: 1000 mm Width: 500 mm Height: adjustable feet	
Filling Volume	approx. 25 liters	

Model	ELI	
Construction	Phantom for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI is fully compatible with the IEC 62209-2 standard and all known tissue simulating liquids. ELI has been optimized regarding its performance and can be integrated into our standard phantom tables. A cover prevents evaporation of the liquid. Reference markings on the phantom allow installation of the complete setup, including all predefined phantom positions and measurement grids, by teaching three points. The phantom is compatible with all SPEAG dosimetric probes and dipoles.	
Material	Vinylester, glass fiber reinforced (VE-GF)	
Shell Thickness	2.0 ± 0.2 mm (bottom plate)	
Dimensions	Major axis: 600 mm Minor axis: 400 mm	
Filling Volume	approx. 30 liters	

3.2.5 Device Holder

Model	Mounting Device	
Construction	In combination with the Twin SAM Phantom or ELI4, the Mounting Device enables the rotation of the mounted transmitter device in spherical coordinates. Rotation point is the ear opening point. Transmitter devices can be easily and accurately positioned according to IEC, IEEE, FCC or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat).	
Material	POM	


Model	Laptop Extensions Kit	
Construction	Simple but effective and easy-to-use extension for Mounting Device that facilitates the testing of larger devices according to IEC 62209-2 (e.g., laptops, cameras, etc.). It is lightweight and fits easily on the upper part of the Mounting Device in place of the phone positioner.	
Material	POM, Acrylic glass, Foam	

3.2.6 System Validation Dipoles

Model	D-Serial	
Construction	Symmetrical dipole with 1/4 balun. Enables measurement of feedpoint impedance with NWA. Matched for use near flat phantoms filled with tissue simulating solutions.	
Frequency	750 MHz to 5800 MHz	
Return Loss	> 20 dB	
Power Capability	> 100 W ($f < 1\text{GHz}$), > 40 W ($f > 1\text{GHz}$)	

3.2.7 Tissue Simulating Liquids

For SAR measurement of the field distribution inside the phantom, the phantom must be filled with homogeneous tissue simulating liquid to a depth of at least 15 cm. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm. The nominal dielectric values of the tissue simulating liquids in the phantom and the tolerance of 5% are listed in Table-3.1.



The dielectric properties of the head tissue simulating liquids are defined in IEEE1528, and KDB 865664 D01 Appendix A. For the body tissue simulating liquids, the dielectric properties are defined in KDB 865664 D01 Appendix A. The dielectric properties of the tissue simulating liquids were verified prior to the SAR evaluation using a dielectric assessment kit and a network analyzer.

Table-3.1 Targets of Tissue Simulating Liquid

Frequency (MHz)	Target Permittivity	Range of $\pm 5\%$	Target Conductivity	Range of $\pm 5\%$
For Head				
750	41.9	39.8 ~ 44.0	0.89	0.85 ~ 0.93
835	41.5	39.4 ~ 43.6	0.90	0.86 ~ 0.95
900	41.5	39.4 ~ 43.6	0.97	0.92 ~ 1.02
1450	40.5	38.5 ~ 42.5	1.20	1.14 ~ 1.26
1640	40.3	38.3 ~ 42.3	1.29	1.23 ~ 1.35
1750	40.1	38.1 ~ 42.1	1.37	1.30 ~ 1.44
1800	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
1900	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2000	40.0	38.0 ~ 42.0	1.40	1.33 ~ 1.47
2300	39.5	37.5 ~ 41.5	1.67	1.59 ~ 1.75
2450	39.2	37.2 ~ 41.2	1.80	1.71 ~ 1.89
2600	39.0	37.1 ~ 41.0	1.96	1.86 ~ 2.06
3500	37.9	36.0 ~ 39.8	2.91	2.76 ~ 3.06
5200	36.0	34.2 ~ 37.8	4.66	4.43 ~ 4.89
5300	35.9	34.1 ~ 37.7	4.76	4.52 ~ 5.00
5500	35.6	33.8 ~ 37.4	4.96	4.71 ~ 5.21
5600	35.5	33.7 ~ 37.3	5.07	4.82 ~ 5.32
5800	35.3	33.5 ~ 37.1	5.27	5.01 ~ 5.53

The following table gives the recipes for tissue simulating liquids.

Table-3.2 Recipes of Tissue Simulating Liquid

Tissue Type	Bactericide	DGBE	HEC	NaCl	Sucrose	Triton X-100	Water	Diethylene Glycol Mono-hexylether
H750	0.2	-	0.2	1.5	56.0	-	42.1	-
H835	0.2	-	0.2	1.5	57.0	-	41.1	-
H900	0.2	-	0.2	1.4	58.0	-	40.2	-
H1450	-	43.3	-	0.6	-	-	56.1	-
H1640	-	45.8	-	0.5	-	-	53.7	-
H1750	-	47.0	-	0.4	-	-	52.6	-
H1800	-	44.5	-	0.3	-	-	55.2	-
H1900	-	44.5	-	0.2	-	-	55.3	-
H2000	-	44.5	-	0.1	-	-	55.4	-
H2300	-	44.9	-	0.1	-	-	55.0	-
H2450	-	45.0	-	0.1	-	-	54.9	-
H2600	-	45.1	-	0.1	-	-	54.8	-
H3500	-	8.0	-	0.2	-	20.0	71.8	-
H5G	-	-	-	-	-	17.2	65.5	17.3

3.3 SAR System Verification

The system check verifies that the system operates within its specifications. It is performed daily or before every SAR measurement. The system check uses normal SAR measurements in the flat section of the phantom with a matched dipole at a specified distance. The system verification setup is shown as below.




Fig-3.4 System Verification Setup

The validation dipole is placed beneath the flat phantom with the specific spacer in place. The distance spacer is touch the phantom surface with a light pressure at the reference marking and be oriented parallel to the long side of the phantom. The spectrum analyzer measures the forward power at the location of the system check dipole connector. The signal generator is adjusted for the desired forward power (250 mW is used for 700 MHz to 3 GHz, 100 mW is used for 3.5 GHz to 6 GHz) at the dipole connector and the power meter is read at that level. After connecting the cable to the dipole, the signal generator is readjusted for the same reading at power meter.

After system check testing, the SAR result will be normalized to 1W forward input power and compared with the reference SAR value derived from validation dipole certificate report. The deviation of system check should be within 10 %.

3.4 SAR Measurement Procedure

According to the SAR test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

The SAR measurement procedures for each of test conditions are as follows:

- (a) Make EUT to transmit maximum output power
- (b) Measure conducted output power through RF cable
- (c) Place the EUT in the specific position of phantom
- (d) Perform SAR testing steps on the DASY system
- (e) Record the SAR value

3.4.1 Area & Zoom Scan Procedure

First Area Scan is used to locate the approximate location(s) of the local peak SAR value(s). The measurement grid within an Area Scan is defined by the grid extent, grid step size and grid offset. Next, in order to determine the EM field distribution in a three-dimensional spatial extension, Zoom Scan is required. The Zoom Scan is performed around the highest E-field value to determine the averaged SAR-distribution over 10 g. According to KDB 865664D01, the resolution for Area and Zoom scan is specified in the table below.

Items	≤ 2 GHz	2-3 GHz	3-4 GHz	4-5 GHz	5-6 GHz
Area Scan ($\Delta x, \Delta y$)	≤ 15 mm	≤ 12 mm	≤ 12 mm	≤ 10 mm	≤ 10 mm
Zoom Scan ($\Delta x, \Delta y$)	≤ 8 mm	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 4 mm
Zoom Scan (Δz)	≤ 5 mm	≤ 5 mm	≤ 4 mm	≤ 3 mm	≤ 2 mm
Zoom Scan Volume	≥ 30 mm	≥ 30 mm	≥ 28 mm	≥ 25 mm	≥ 22 mm

Note:

When zoom scan is required and report SAR is ≤ 1.4 W/kg, the zoom scan resolution of $\Delta x / \Delta y$ (2-3GHz: ≤ 8 mm, 3-4GHz: ≤ 7 mm, 4-6GHz: ≤ 5 mm) may be applied.

3.4.2 VolumeScan Procedure

The volume scan is used for assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

3.4.3 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASY measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drift more than 5%, the SAR will be retested.

3.4.4 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

3.4.5 SAR Averaged Methods

In DASY, the interpolation and extrapolation are both based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation.

Extrapolation routines are used to obtain SAR values between the lowest measurement points and the inner phantom surface. The extrapolation distance is determined by the surface detection distance and the probe sensor offset. The uncertainty increases with the extrapolation distance. To keep the uncertainty within 1% for the 1 g and 10 g cubes, the extrapolation distance should not be larger than 5 mm.

4. SAR Measurement Evaluation

4.1 Applicable Standards

KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04

KDB 865664 D02 RF Exposure Reporting v01r02

KDB 248227 D01 802.11 Wi-Fi SAR v02r02

KDB 447498 D01 General RF Exposure Guidance v06


FCC 47 CFR Part 2 (2.1093)

4.2 EUT Testing Position

4.2.1 Hand-held usage of the device, not at the head or torso

When SAR measurement is necessary for hand-held devices that do not transmit while at the head or torso, a flat phantom may be used. To assess this type of device, the device shall be placed directly against the flat phantom as shown in Figure 11, for the sides of the device that are in contact with the hand for the intended use.


NOTE Concerning a measurement phantom representing the hand, there are practical difficulties in specifying a unique hand holding position that is applicable to all devices. Additional studies are needed for devising a representative method for evaluating SAR in the hand of hand-held devices (whether or not they are hand-operated devices). Future versions of this document are intended to contain a test method based on scientific data and rationale.



IEC

Fig-4.1 Test position for hand-held devices, not used at the head or torso

<Antenna Location>



The separation distance for antenna to edge:

Antenna	To Left Side (mm)	To Right Side (mm)	To Top Side (mm)	To Bottom Side (mm)	To Front Face (mm)	To Rear Face (mm)
WLAN Antenna	30	30	5	55	5	15

4.2.2 SAR Test Exclusion Evaluations

According to KDB 447498 D01, the SAR test exclusion condition is based on source-based time-averaged maximum conducted output power, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions. The SAR exclusion threshold is determined by the following formula.

1. For the test separation distance ≤ 50 mm

$$\frac{\text{Max. Tune up Power}_{(\text{mW})}}{\text{Min. Test Separation Distance}_{(\text{mm})}} \times \sqrt{f_{(\text{GHz})}} \leq 3.0 \text{ for SAR-1g, } \leq 7.5 \text{ for SAR-10g}$$

When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion.

2. For the test separation distance > 50 mm, and the frequency at 100 MHz to 1500 MHz

$$\left[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times \left(\frac{f_{(\text{MHz})}}{150} \right) \right]_{(\text{mW})}$$

3. For the test separation distance > 50 mm, and the frequency at > 1500 MHz to 6 GHz

$$[(\text{Threshold at 50 mm in Step 1}) + (\text{Test Separation Distance} - 50 \text{ mm}) \times 10]_{(\text{mW})}$$

<Antenna for WLAN >

Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	RearFace			LeftSide			RightSide			TopSide			BottomSide		
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?	Ant. to Surface (mm)	Calculated Result	Require SAR Testing?
WLAN 2.4G	14.5	28.18	15	2.9	Yes	30	1.5	No	30	1.5	No	5	8.8	Yes	55	146 mW	No
WLAN 5.2G	13.0	19.95	15	3.0	Yes	30	1.5	No	30	1.5	No	5	9.1	Yes	55	116 mW	No
WLAN 5.3G	12.0	15.85	15	2.4	Yes	30	1.2	No	30	1.2	No	5	7.3	Yes	55	115 mW	No
WLAN 5.6G	11.5	14.13	15	2.2	Yes	30	1.1	No	30	1.1	No	5	6.7	Yes	55	114 mW	No
WLAN 5.8G	14.5	28.18	15	2.9	Yes	30	1.5	No	30	1.5	No	5	8.8	Yes	55	146 mW	No
Mode	Max. Tune-up Power (dBm)	Max. Tune-up Power (mW)	FrontFace														
			Ant. to Surface (mm)	Calculated Result	Require SAR Testing?												
WLAN 2.4G	14.5	28.18	5	8.8	Yes												
WLAN 5.2G	13.0	19.95	5	9.1	Yes												
WLAN 5.3G	12.0	15.85	5	7.3	Yes												
WLAN 5.6G	11.5	14.13	5	6.7	Yes												
WLAN 5.8G	14.5	28.18	5	8.8	Yes												

Note:

1. When separation distance ≤ 50 mm and the calculated result shown in above table is ≤ 3.0 for SAR-1g exposure condition, or ≤ 7.5 for SAR-10g exposure condition, the SAR testing exclusion is applied.

2. When separation distance > 50 mm and the device output power is less than the calculated result (power threshold, mW) shown in above table, the SAR testing exclusion is applied.
3. Display diagonal size greater than 20cm, reference KDB 616217, test distance 0mm (no needn to test face up)



4.3 Tissue Verification

The measuring results for tissue simulating liquid are shown as below.

Test Date	Tissue Type	Frequency (MHz)	Liquid Temp. (°C)	Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Target Conductivity (σ)	Target Permittivity (ϵ_r)	Conductivity Deviation (%)	Permittivity Deviation (%)
May 18, 2026	Head	2450	22.8	1.78	40.11	1.80	39.20	-1.11	2.32
May 19, 2026	Head	5250	22.7	4.75	36.87	4.71	35.90	0.85	2.70
May 20, 2026	Head	5600	22.4	5.13	36.14	5.07	35.50	1.18	1.80
May 21, 2026	Head	5750	21.8	5.22	35.61	5.22	35.40	0.00	0.59

Note:

The dielectric properties of the tissue simulating liquid must be measured within 24 hours before the SAR testing and within $\pm 5\%$ of the target values. Liquid temperature during the SAR testing must be within $\pm 2^\circ\text{C}$.

4.4 System Validation

The SAR measurement system was validated according to procedures in KDB 865664 D01. The validation status in tabulated summary is as below.

Test Date	Probe S/N	Calibration Point		Measured Conductivity (σ)	Measured Permittivity (ϵ_r)	Validation for CW			Validation for Modulation		
						Sensitivity Range	Probe Linearity	Probe Isotropy	Modulation Type	Duty Factor	PAR
May 18, 2026	3970	Head	2450	1.78	40.11	Pass	Pass	Pass	CW	N/A	Pass
May 19, 2026	3970	Head	5250	4.75	36.87	Pass	Pass	Pass	CW	N/A	Pass
May 20, 2026	3970	Head	5600	5.13	36.14	Pass	Pass	Pass	CW	N/A	Pass
May 21, 2026	3970	Head	5750	5.22	35.61	Pass	Pass	Pass	CW	N/A	Pass

4.5 System Verification

The measuring result for system verification is tabulated as below.

Test Date	Mode	Frequency (MHz)	1W Target SAR-1g (W/kg)	Measured SAR-1g (W/kg)	Normalized to 1W SAR-1g (W/kg)	Deviation (%)	Dipole S/N	Probe S/N	DAE S/N
May 18, 2026	Head	2450	51.60	13.08	52.32	1.40	927	3970	1418
May 19, 2026	Head	5250	77.70	7.93	79.30	2.06	1169	3970	1418
May 20, 2026	Head	5600	82.40	8.57	85.70	4.00	1169	3970	1418
May 21, 2026	Head	5750	78.50	8.05	80.50	2.55	1169	3970	1418

Note:

Comparing to the reference SAR value provided by SPEAG, the validation data should be within its specification of 10 %. The result indicates the system check can meet the variation criterion and the plots can be referred to Appendix A of this report.

4.6 Maximum Output Power

4.6.1 Maximum Conducted Power

The maximum conducted power (Unit: dBm) including tune-up tolerance is shown as below.

Mode	2.4G WLAN	5.2G WLAN	5.3G WLAN	5.6G WLAN	5.8G WLAN
802.11b	12.00	N/A	N/A	N/A	N/A
802.11g	14.50	N/A	N/A	N/A	N/A
802.11a	N/A	13.00	12.00	11.50	11.50
802.11n HT20	14.00	11.50	10.50	11.50	10.50
802.11n HT40	13.50	11.50	10.00	11.00	10.50
802.11ac VHT20	N/A	10.50	9.50	11.00	10.00
802.11ac VHT40	N/A	10.50	9.00	11.00	9.00
802.11ax HE20	14.00	11.00	10.00	11.50	9.00
802.11ax HE40	13.50	10.50	9.00	11.50	9.50

<WLAN 2.4G>

Mode	802.11b		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Conducted Power	8.16	9.17	11.51
Mode	802.11g		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Conducted Power	13.42	13.80	14.26
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Conducted Power	12.86	13.22	13.75
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	3 (2422)	6 (2437)	9 (2452)
Conducted Power	12.85	13.15	13.28
Mode	802.11ax (HE20)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	11 (2462)
Conducted Power	12.74	13.01	13.64
Mode	802.11ax (HE40)		
Channel / Frequency (MHz)	1 (2412)	6 (2437)	9 (2452)
Conducted Power	12.85	13.11	13.21

<WLAN 5.2G>

Mode	802.11a		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Conducted Power	12.78	12.58	11.60
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Conducted Power	11.29	11.19	10.30
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	38 (5190)	46 (5230)	
Conducted Power	11.14	10.44	
Mode	802.11ac (VHT20)		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Conducted Power	10.09	10.18	9.25
Mode	802.11ac (VHT40)		
Channel / Frequency (MHz)	38 (5190)	46 (5230)	
Conducted Power	10.26	9.38	
Mode	802.11ax (HE20)		
Channel / Frequency (MHz)	36 (5180)	40 (5200)	48 (5240)
Conducted Power	10.26	10.59	9.33
Mode	802.11ax (HE40)		
Channel / Frequency (MHz)	38 (5190)	46 (5230)	
Conducted Power	10.19	9.37	

<WLAN 5.3G>

Mode	802.11a		
Channel / Frequency (MHz)	52 (5260)	58 (5280)	64 (5320)
Conducted Power	11.72	11.49	10.47
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	52 (5260)	58 (5280)	64 (5320)
Conducted Power	10.25	9.90	9.28
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	54 (5270)		62 (5310)
Conducted Power	9.92		8.99
Mode	802.11ac (VHT20)		
Channel / Frequency (MHz)	52 (5260)	58 (5280)	64 (5320)
Conducted Power	9.31	8.85	8.06
Mode	802.11ac (VHT40)		
Channel / Frequency (MHz)	54 (5270)		62 (5310)
Conducted Power	8.99		8.10
Mode	802.11ax (HE20)		
Channel / Frequency (MHz)	52 (5260)	58 (5280)	64 (5320)
Conducted Power	9.56	9.02	8.23
Mode	802.11ax (HE40)		
Channel / Frequency (MHz)	54 (5270)		62 (5310)
Conducted Power	8.95		8.41

<WLAN 5.6G>

Mode	802.11a		
Channel / Frequency (MHz)	100 (5500)	116 (5580)	140 (5700)
Conducted Power	10.41	11.24	5.61
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	100 (5500)	116 (5580)	140 (5700)
Conducted Power	10.55	11.41	4.74
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	102 (5510)	110 (5550)	134 (5670)
Conducted Power	10.66	9.86	5.20
Mode	802.11ac (VHT20)		
Channel / Frequency (MHz)	100 (5500)	116 (5580)	140 (5700)
Conducted Power	10.56	10.66	4.32
Mode	802.11ac (VHT40)		
Channel / Frequency (MHz)	102 (5510)	110 (5550)	134 (5670)
Conducted Power	10.60	10.33	5.39
Mode	802.11ax (HE20)		
Channel / Frequency (MHz)	100 (5500)	116 (5580)	140 (5700)
Conducted Power	10.87	11.38	4.46
Mode	802.11ax (HE40)		
Channel / Frequency (MHz)	102 (5510)	110 (5550)	134 (5670)
Conducted Power	11.02	10.17	5.47

<WLAN 5.8G>

Mode	802.11a		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Conducted Power	11.20	9.79	9.80
Mode	802.11n (HT20)		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Conducted Power	10.19	8.57	8.41
Mode	802.11n (HT40)		
Channel / Frequency (MHz)	151 (5755)	159 (5795)	
Conducted Power	10.17	8.78	
Mode	802.11ac (VHT20)		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Conducted Power	9.72	7.96	7.62
Mode	802.11ac (VHT40)		
Channel / Frequency (MHz)	151 (5755)	159 (5795)	
Conducted Power	8.99	7.34	
Mode	802.11ax (HE20)		
Channel / Frequency (MHz)	149 (5745)	157 (5785)	165 (5825)
Conducted Power	8.75	7.19	7.14
Mode	802.11ax (HE40)		
Channel / Frequency (MHz)	151 (5755)	159 (5795)	
Conducted Power	9.07	7.47	

4.7 SAR Testing Results

4.7.1 SAR Test Reduction Considerations

<KDB 447498 D01, General RF Exposure Guidance>

Testing of other required channels within the operating mode of a frequency band is not required when the reported SAR for the mid-band or highest output power channel is:

- (1) ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
- (2) ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
- (3) ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz

<KDB 248227 D01, SAR Guidance for Wi-Fi Transmitters>

- (1) For handsets operating next to ear, hotspot mode or mini-tablet configurations, the initial test position procedures were applied. The test position with the highest extrapolated peak SAR will be used as the initial test position. When the reported SAR of initial test position is ≤ 0.4 W/kg, SAR testing for remaining test positions is not required. Otherwise, SAR is evaluated at the subsequent highest peak SAR positions until the reported SAR result is ≤ 0.8 W/kg or all test positions are measured.
- (2) For WLAN 2.4 GHz, the highest measured maximum output power channel for DSSS was selected for SAR measurement. When the reported SAR is ≤ 0.8 W/kg, no further SAR testing is required. Otherwise, SAR is evaluated at the next highest measured output power channel. When any reported SAR is > 1.2 W/kg, SAR is required for the third channel. For OFDM modes (802.11g/n), SAR is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and it is ≤ 1.2 W/kg.
- (3) For WLAN 5GHz, the initial test configuration was selected according to the transmission mode with the highest maximum output power. When the reported SAR of initial test configuration is > 0.8 W/kg, SAR is required for the subsequent highest measured output power channel until the reported SAR result is ≤ 1.2 W/kg or all required channels are measured. For other transmission modes, SAR is not required when the highest reported SAR for initial test configuration is adjusted by the ratio of subsequent test configuration to initial test configuration specified maximum output power and it is ≤ 1.2 W/kg.

4.7.2 SAR Results for Body Exposure Condition

Body SAR:

Plot No.	Band	Mode	Test Position	Antenna	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	1g Extremity SAR (W/kg)	Scaling Factor	Scaled SAR-1g (W/kg)	Duty cycle(%)	Duty cycle Factor	Final 1g Scaled SAR (W/kg)
1	802.11b	-	Rear Face	-	6	9.50	9.17	0.05	0.243	1.079	0.262	100	1.00	0.262
	802.11b	-	Front Face	-	6	9.50	9.17	-0.03	0.352	1.079	0.380	100	1.00	0.380
	802.11b	-	Top Side	-	6	9.50	9.17	0.10	0.482	1.079	0.520	100	1.00	0.520
2	802.11a	-	Rear Face	-	40	13.00	12.58	0.00	0.298	1.102	0.328	89.17	1.12	0.368
	802.11a	-	Front Face	-	40	13.00	12.58	0.14	0.402	1.102	0.443	89.17	1.12	0.497
	802.11a	-	Top Side	-	40	13.00	12.58	-0.03	0.607	1.102	0.669	89.17	1.12	0.750
3	802.11a	-	Rear Face	-	58	11.50	11.49	-0.19	0.316	1.002	0.317	85.89	1.16	0.369
	802.11a	-	Front Face	-	58	11.50	11.49	0.15	0.428	1.002	0.429	85.89	1.16	0.499
	802.11a	-	Top Side	-	58	11.50	11.49	0.04	0.714	1.002	0.716	85.89	1.16	0.834
4	802.11a	-	Rear Face	-	116	11.50	11.24	-0.14	0.267	1.062	0.283	87.50	1.14	0.323
	802.11a	-	Front Face	-	116	11.50	11.49	0.19	0.417	1.002	0.418	87.50	1.14	0.478
	802.11a	-	Top Side	-	116	11.50	11.49	0.00	0.570	1.002	0.571	87.50	1.14	0.653
5	802.11a	-	Rear Face	-	157	10.00	9.79	-0.19	0.148	1.050	0.155	86.88	1.15	0.178
	802.11a	-	Front Face	-	157	10.00	9.79	0.19	0.201	1.050	0.211	86.88	1.15	0.243
	802.11a	-	Top Side	-	157	10.00	9.79	0.07	0.303	1.050	0.318	86.88	1.15	0.366

Limbs SAR:

Plot No.	Band	Mode	Test Position	Antenna	Ch.	Max. Tune-up Power (dBm)	Measured Conducted Power (dBm)	Power Drift (dB)	10g Extremity SAR (W/kg)	Scaling Factor	Scaled SAR-10g (W/kg)	Duty cycle(%)	Duty cycle Factor	Final 10g Scaled SAR (W/kg)
1	802.11b	-	Rear Face	-	6	9.50	9.17	0.05	0.080	1.079	0.086	100	1.00	0.086
	802.11b	-	Front Face	-	6	9.50	9.17	-0.03	0.174	1.079	0.188	100	1.00	0.188
	802.11b	-	Top Side	-	6	9.50	9.17	0.10	0.224	1.079	0.242	100	1.00	0.242
2	802.11a	-	Rear Face	-	40	13.00	12.58	0.00	0.099	1.102	0.109	89.17	1.12	0.122
	802.11a	-	Front Face	-	40	13.00	12.58	0.14	0.186	1.102	0.205	89.17	1.12	0.230
	802.11a	-	Top Side	-	40	13.00	12.58	-0.03	0.244	1.102	0.269	89.17	1.12	0.302
3	802.11a	-	Rear Face	-	58	11.50	11.49	-0.19	0.112	1.002	0.112	85.89	1.16	0.130
	802.11a	-	Front Face	-	58	11.50	11.49	0.15	0.203	1.002	0.203	85.89	1.16	0.236
	802.11a	-	Top Side	-	58	11.50	11.49	0.04	0.266	1.002	0.267	85.89	1.16	0.311
4	802.11a	-	Rear Face	-	116	11.50	11.24	-0.14	0.083	1.062	0.088	87.50	1.14	0.101
	802.11a	-	Front Face	-	116	11.50	11.49	0.19	0.172	1.002	0.172	87.50	1.14	0.197
	802.11a	-	Top Side	-	116	11.50	11.49	0.00	0.230	1.002	0.231	87.50	1.14	0.264
5	802.11a	-	Rear Face	-	157	10.00	9.79	-0.19	0.032	1.050	0.034	86.88	1.15	0.039
	802.11a	-	Front Face	-	157	10.00	9.79	0.19	0.098	1.050	0.103	86.88	1.15	0.119
	802.11a	-	Top Side	-	157	10.00	9.79	0.07	0.112	1.050	0.118	86.88	1.15	0.136

Note:

1. SAR tests use the same power level as RF tests.

4.7.3 2.4GHz 802.11g/n OFDM SAR Test Exclusion Consideration:

Modulation Mode	P _{avg} (dBm)	P _{avg} (mW)	Reported SAR (W/Kg)	Adjusted SAR (W/kg)	Limit (W/Kg)	SAR Test Exclusion
802.11b(DSSS)	12.00	15.85	0.242	/	/	/
802.11g(OFDM)	14.50	28.18	/	0.430	1.2	Yes
802.11n(OFDM)	14.00	25.12	/	0.384	1.2	Yes

Note:

When the highest *reported* SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.



4.7.4 SAR Measurement Variability

According to KDB 865664 D01, SAR measurement variability was assessed for each frequency band, which is determined by the SAR probecalibration point and tissue-equivalent medium used for the device measurements. When both head and body tissue-equivalent media are required for SAR measurements in a frequency band, the variability measurement procedures should be applied to the tissue medium with the highest measured SAR, using the highest measured SAR configuration for that tissue-equivalent medium. Alternatively, if the highest measured SAR for both head and body tissue-equivalent media are ≤ 1.45 W/kg and the ratio of these highest SAR values, i.e., largest divided by smallest value, is ≤ 1.10 , the highest SAR configuration for either head or body tissue-equivalent medium maybe used to perform the repeated measurement. These additional measurements are repeated after the completion of all measurements requiring the same head or body tissue-equivalent medium in a frequency band. The test device should be returned to ambient conditions (normal room temperature) with the battery fully charged before it is re-mounted on the device holder for the repeated measurement(s) to minimize any unexpected variations in the repeated results.

SAR repeated measurement procedure:

1. When the highest measured SAR is < 0.80 W/kg, repeated measurement is not required.
2. When the highest measured SAR is ≥ 0.80 W/kg, repeat that measurement once.
3. If the ratio of largest to smallest SAR for the original and first repeated measurements is > 1.20 , or when the original or repeated measurement is ≥ 1.45 W/kg, perform a second repeated measurement.
4. If the ratio of largest to smallest SAR for the original, first and second repeated measurements is > 1.20 , and the original, first or second repeated measurement is ≥ 1.5 W/kg, perform a third repeated measurement.

Band	Test Position	Fr.	Original Measured SAR-1g (W/kg)	1st Repeated SAR-1g (W/kg)	L/S Ratio	2nd Repeated SAR-1g (W/kg)	L/S Ratio	3rd Repeated SAR-1g (W/kg)	L/S Ratio
N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A

Test Engineer: Junjiong Cai

5. Calibration of Test Equipment

Equipment	Manufacturer	Model	SN	Cal. Date	Cal. Interval
System Validation Dipole	SPEAG	D2450V2	927	May. 09, 2025	3 Year
System Validation Dipole	SPEAG	D5GHzV2	1169	May. 08, 2025	3 Year
Dosimetric E-Field Probe	SPEAG	EX3DV4	3970	Jun. 05, 2025	1 Year
Data Acquisition Electronics	SPEAG	DAE4	1418	Jun. 05, 2025	1 Year
ENA Series Network Analyzer	Agilent	E5071B	MY42404246	May. 8, 2026	1 Year
Signal Analyzer	Rohde & Schwarz	FSV30	103039	May. 8, 2026	1Year
Signal Generator	Agilent	N5181A	MY50145187	May. 8, 2026	1 Year
Power Sensor	BOONTON	51011EMC	34236	May. 9, 2026	1 Year
Power Meter	BOONTON	4232A	10539	May. 9, 2026	1 Year
Power Sensor	BOONTON	51011EMC	36164	May. 9, 2026	1 Year
Electronic Thermometer	Hegao	HTC-1	\	Apr. 7, 2026	1 Year
Directional Coupler	MILMEGA	DC6180AM1	0340463	May. 8, 2026	1 Year

6. Measurement Uncertainty

Source of Uncertainty	Tolerance (±%)	Probability Distribution	Divisor	Ci 1g	Ci 10g	Standard Uncertainty 1g (±%)	Standard Uncertainty 10g (±%)	Vi Veff
Measurement System								
Probe calibration	6.65	Normal	2	1	1	3.325	3.325	∞
Probe calibration drift	5.00	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞
Probe Linearity	0.3	Rectangular	$\sqrt{3}$	1	1	0.173	0.173	∞
System detection limits	1.00	Rectangular	$\sqrt{3}$	1	1	0.577	0.577	∞
Broadband signal	3.150	Rectangular	$\sqrt{3}$	1	1	1.819	1.819	∞
Axial Isotropy	0.250	Rectangular	$\sqrt{3}$	1	1	0.102	0.102	∞
Hemispherical Isotropy	1.300	Rectangular	1	0.71	0.71	0.531	0.531	∞
Boundary effect	1	Rectangular	1	0.71	0.71	3.325	3.325	∞
Response Time	0.00	Normal	1	1	1	0.000	0.000	∞
Integration Time	1.70	Normal	1	1	1	1.700	1.700	∞
RF ambient conditions-reflections	3.00	Normal	1	1	1	3.000	3.000	∞
Probe positioning with respect to phantom shell	6.70	Normal	1	0.143	0.143	0.337	0.337	∞
Data processing errors	0.35	Normal	1	0.143	0.143	0.350	0.350	∞
Phantom and device (DUT) errors								
Measurement of phantom conductivity(σ)	4.00	Normal	1	1	1	3.120	2.840	∞
Liquid conductivity(temperature uncertainty)	2.50	Rectangular	$\sqrt{3}$	0.78	0.71	1.126	1.025	∞
Shell permittivity	5.00	Rectangular	$\sqrt{3}$	0.00	0.00	0.000	0.000	∞
Distance between the radiating element of the DUT and the phantom	0.26	Normal	1	2	2	0.520	0.520	∞
Repeatability of positioning the DUT or source against the phantom	2.90	Normal	1	1	1	2.900	2.900	∞
Device holder uncertainty	3.60	Normal	1	1	1	3.600	3.600	∞
Effect of operating mode on probe sensitivity	3.30	Rectangular	$\sqrt{3}$	1	1	1.905	1.905	∞
Time-average SAR	5.000	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞
SAR drift measurement	5.00	Normal	1	1	1	5.000	5.000	∞
Corrections to the SAR result								

Phantom deviation from target (ϵ', σ)	1.900	Normal	1	1.00	0.84	1.900	1.596	∞
SAR scaling	5.000	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞
Combined Standard Uncertainty						10.659	10.473	
Expanded Uncertainty (K=2)						21.317	20.947	

Uncertainty budget for frequency range 600 MHz to 3 GHz



Source of Uncertainty	Tolerance (±%)	Probability Distribution	Divisor	Ci 1g	Ci 10g	Standard Uncertainty 1g (±%)	Standard Uncertainty 10g (±%)	Vi Veff
Measurement System								
Probe calibration	6.65	Normal	2	1	1	3.325	3.325	∞
Probe calibration drift	5.00	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞
Probe Linearity	0.3	Rectangular	$\sqrt{3}$	1	1	0.173	0.173	∞
System detection limits	1.00	Rectangular	$\sqrt{3}$	1	1	0.577	0.577	∞
Broadband signal	3.150	Rectangular	$\sqrt{3}$	1	1	1.819	1.819	∞
Axial Isotropy	0.250	Rectangular	$\sqrt{3}$	0.71	0.71	0.102	0.102	∞
Hemispherical Isotropy	1.300	Rectangular	$\sqrt{3}$	0.71	0.71	0.531	0.531	∞
Boundary effect	1	Rectangular	1	1	1	0.577	0.577	∞
Response Time	0.00	Normal	1	1	1	0.000	0.000	∞
Integration Time	1.70	Normal	1	1	1	1.700	1.700	∞
RF ambient conditions-reflections	3.00	Normal	1	1	1	3.000	3.000	∞
Probe positioning with respect to phantom shell	6.70	Normal	1	0.05	0.05	0.337	0.337	∞
Data processing errors	0.35	Normal	1	1	1	0.350	0.350	∞
Phantom and device (DUT) errors								
Measurement of phantom conductivity(σ)	4.00	Normal	1	0.78	0.71	3.120	2.840	∞
Liquid conductivity(temperature uncertainty)	2.50	Rectangular	$\sqrt{3}$	0.78	0.71	1.126	1.025	∞
Shell permittivity	5.00	Rectangular	$\sqrt{3}$	0.00	0.00	0.000	0.000	∞
Distance between the radiating element of the DUT and the phantom	0.26	Normal	1	2	2	0.520	0.520	∞
Repeatability of positioning the DUT or source against the phantom	2.90	Normal	1	1	1	2.900	2.900	∞
Device holder uncertainty	3.60	Normal	1	1	1	3.600	3.600	∞
Effect of operating mode on probe sensitivity	3.30	Rectangular	$\sqrt{3}$	1	1	1.905	1.905	∞
Time-average SAR	5.000	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞
SAR drift measurement	5.750	Normal	1	1	1	5.750	5.750	∞
Corrections to the SAR result								
Phantom deviation from target (ϵ', σ)	1.900	Normal	1	1.00	0.84	1.900	1.596	∞
SAR scaling	5.000	Rectangular	$\sqrt{3}$	1	1	2.887	2.887	∞

Combined Standard Uncertainty		11.132	10.955	
Expanded Uncertainty (K=2)		22.264	21.909	

Uncertainty budget for frequency range 3 GHz to 6 GHz



7. Information on the Testing Laboratories

We, EMTEK (SHENZHEN) CO., LTD., were founded in 2000 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Site Description
EMC Lab.

: **Accredited by CNAS**

The Certificate Registration Number is L2291.

The Laboratory has been assessed and proved to be in compliance with
CNAS-CL01 (identical to ISO/IEC 17025:2017)

Accredited by FCC

Designation Number: CN1204

Test Firm Registration Number: 882943

Accredited by A2LA

The Certificate Number is 4321.01.

Accredited by Industry Canada

The Conformity Assessment Body Identifier is CN0008

Name of Firm

: EMTEK (SHENZHEN) CO., LTD.

Site Location

: Building 69, Majialong Industry Zone, Nanshan District, Shenzhen,
Guangdong, China

If you have any comments, please feel free to contact us at the following:

Add: Bldg 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China

TEL: 86-755-26954280

FAX: 86-755-26954282

Email: csg@emtek.com.cn

Web Site: www.emtek.com.cn

The road map of all our labs can be found in our web site also.

--- End of Report ---

Appendix A. SAR Plots of System Verification

The plots for system verification with largest deviation for each SAR system combination are shown as Appendix A.



Appendix B. SAR Plots of SAR Measurement

The SAR plots for highest measured SAR in each exposure configuration, wireless mode and frequency band combination are shown as Appendix B.



Appendix C. Calibration Certificate for Probe and Dipole

The calibration certificates are shown as Appendix C.



Appendix D. Photographs of EUT and Setup

The photographs of EUT and Setup are shown as Appendix D.



声 明 Statement

1. 本报告无授权批准人签字及“检验检测专用章”无效。
1. This report is invalid without the signature of the authorized approver and "special seal for testing".
2. 未经许可本报告不得部分复制。
2. This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效，委托方对样品的代表性和资料的真实性负责。
3. The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内，仅作为客户委托、科研、教学或内部质量控制等目的使用。
4. The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定，未考虑不确定度所带来的风险，本实验室不承担相关责任，特别约定、标准或规范中有明确规定的除外。
5. The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检验报告若有异议，请于收到报告之日起 20 日内提出。
6. Objections shall be raised within 20 days from the date receiving the report.