



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2AFIW-SFT1200

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

Product Name:	AC1200 Wireless Travel Router
Trade Mark:	GL.iNET
Model/Type reference:	GL-SFT1200
Listed Model(s):	/
Frequency band (Operating)	WLAN: 2.412GHz ~ 2.462GHz RLAN: 5.150GHz ~ 5.250GHz RLAN: 5.725GHz ~ 5.850GHz
Device category	☐ Portable (<5mm separation) ☐ Mobile (>20cm separation) ☒ Fixed (>20cm separation) ☐ Others ____
Exposure classification	☐ Occupational/Controlled exposure (S=5mW/cm2) ☒ General Population/Uncontrolled exposure (S=1mW/cm2)
Antenna diversity	☐ Single antenna ☒ Multiple antennas ☐ Tx diversity ☐ Rx diversity ☐ Tx/Rx diversity
Antenna technology:	Beamforming Mode
Antenna delivery:	2.4GHz: 2*TX + 2*RX 5GHz: 2*TX + 2*RX
Antenna 1 and 2 gain: (Max)	2.4GHz WIFI: 3.79dBi 5GHz WIFI U-NII-1: 4.12dBi 5GHz WIFI U-NII-3: 4.25dBi
Antenna 1 + 2 Directional gain: (Max)	2.4GHz: 6.80dBi 5GHz WIFI U-NII-1: 7.13dBi 5GHz WIFI U-NII-3: 7.26dBi
Evaluation applied	☒ MPE Evaluation ☐ SAR Evaluation

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cnca.cn



Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

Friis transmission formula: $P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot R^2)$

Where

P_d = Power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, We will know the distance where the MPE limit is reached.

Measurement Result

Only show the value of the worst antenna.

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)
WLAN 802.11b	2462	3.79	16.52	16±1	17	0.02386	1.000
WLAN 802.11g	2412	3.79	12.14	12±1	13	0.00950	1.000
WLAN 802.11n(HT20)	2437	6.80	14.20	14±1	15	0.03011	1.000
WLAN 802.11n(HT40)	2437	6.80	11.15	11±1	12	0.01509	1.000
RLAN U-NII-1 802.11a	5180	4.12	16.36	16±1	17	0.02575	1.000
RLAN U-NII-1 802.11n(HT20)	5180	7.13	18.88	19±1	20	0.10274	1.000
RLAN U-NII-1 802.11n(HT40)	5190	7.13	15.15	15±1	16	0.04090	1.000
RLAN U-NII-1 802.11ac(VHT20)	5180	7.13	18.93	19±1	20	0.10274	1.000
RLAN U-NII-1 802.11ac(VHT40)	5190	7.13	14.64	14±1	15	0.03249	1.000
RLAN U-NII-1 802.11ac(VHT80)	5210	7.13	14.20	14±1	15	0.03249	1.000
RLAN U-NII-3 802.11a	5785	4.25	15.76	15±1	16	0.02107	1.000
RLAN U-NII-3 802.11n(HT20)	5745	7.26	18.33	18±1	19	0.08161	1.000
RLAN U-NII-3 802.11n(HT40)	5755	7.26	18.35	18±1	19	0.08161	1.000
RLAN U-NII-3 802.11ac(VHT20)	5745	7.26	18.34	18±1	19	0.08161	1.000
RLAN U-NII-3 802.11ac(VHT40)	5755	7.26	18.31	18±1	19	0.08161	1.000
RLAN U-NII-3 802.11ac(VHT80)	5775	7.26	17.92	18±1	19	0.08161	1.000



The WLAN and RLAN can transmit simultaneously

WLAN Power density at 20cm (mW/cm ²)	RLAN Power density at 20cm (mW/cm ²)	Total Power density at 20cm	Power density Limits
0.02386	0.02575	0.04961	1

Note:

For a more detailed features description, Please refer to the RF Test Report.

*****THE END*****