



Shenzhen CTL Testing Technology Co., Ltd.
Tel: +86-755-89486194 Fax: +86-755-26636041

FCC PART 15 SUBPART C TEST REPORT

FCC PART 15.249

Report Reference No.: CTL1508042170-WF

Compiled by:
(position+printed name+signature)

Jacky Chen
(File administrators)

Jacky Chen

Tested by:
(position+printed name+signature)

Allen Wang
(Test Engineer)

Allen Wang

Approved by:
(position+printed name+signature)

Tracy Qi
(Manager)

Tracy Qi

Product Name.....: Breathalyzer

Model/Type reference.....: AlcoREAL i-553

List Model(s).....: DRIVESAFE evoc, i Alco Supreme

Trade Mark.....: SKYFINE

FCC ID.....: 2AFL6-I-553

Applicant's name.....: **SKYFINE INC.LIMITED**

Address of applicant.....: Flat M, 23/F, Block 2, Goldfield Industrial Building, 144-150 Tai Lin
Pai Road ,Kwai Chung, NT, Hong Kong

Test Firm.....: **Shenzhen CTL Testing Technology Co., Ltd.**

Address of Test Firm.....: Floor 1-A, Baisha Technology Park, No.3011, Shahexi Road,
Nanshan District, Shenzhen, China 518055

Test specification.....:

Standard.....: **FCC Part 15.249:**Operation within the bands 920-928 MHz,
2400-2483.5 MHz, 5725-5850 MHz and 24.0 - 24.25 GHz.

TRF Originator.....: Shenzhen CTL Testing Technology Co., Ltd.

Master TRF.....: Dated 2011-01

Date of Receipt.....: Aug. 04, 2015

Date of Test Date.....: Aug. 05, 2015 –Aug. 12, 2015

Data of Issue.....: Aug. 13, 2015

Result.....: Positive

Shenzhen CTL Testing Technology Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen CTL Testing Technology Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen CTL Testing Technology Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

TEST REPORT

Test Report No. :	CTL1508042170-WF	Aug. 13, 2015 ----- Date of issue
--------------------------	-------------------------	---

Equipment under Test : Breathalyzer

Model /Type : AlcoREALi-553

Listed Models : DRIVESAFE evoc, i Alco Supreme

Applicant : SKYFINE INC.LIMITED

Address : Flat M, 23/F, Block 2, Goldfield Industrial Building,
144-150 Tai Lin Pai Road ,Kwai Chung, NT, Hong
Kong

Manufacturer : SKYFINE INC.LIMITED

Address : No.17, Bainishan Zhong Rd., Dalingshan Town,
Dongguan City, Guangdong Province, China

Test result	Pass *
--------------------	---------------

* In the configuration tested, the EUT complied with the standards specified page 5.

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.


**** Modified History ****

Version	Description	Issued Data	Report No.	Remark
Version 1.0	Initial Test Report Release	2015-08-13	CTL1508042170-WF	Tracy Qi



Table of Contents**Page**

1. SUMMARY.....	5
1.1. TEST STANDARDS.....	5
1.2. TEST DESCRIPTION.....	5
1.3. TEST FACILITY	6
1.4. STATEMENT OF THE MEASUREMENT UNCERTAINTY.....	6
2. GENERAL INFORMATION.....	7
2.1. ENVIRONMENTAL CONDITIONS	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. DESCRIPTION OF TEST MODES AND TEST FREQUENCY	7
2.4. EQUIPMENTS USED DURING THE TEST	8
2.5. RELATED SUBMITTAL(s) / GRANT (s).....	8
2.6. MODIFICATIONS.....	8
3. TEST CONDITIONS AND RESULTS	9
3.1. CONDUCTED EMISSIONS TEST	9
3.2. RADIATED EMISSIONS AND BAND EDGE	10
3.3. OCCUPIED BANDWIDTH MEASUREMENT	16
3.4. ANTENNA REQUIREMENT.....	17
4. TEST SETUP PHOTOS OF THE EUT	19
5. EXTERNAL AND INTERNAL PHOTOS OF THE EUT	20



1. SUMMARY

1.1. TEST STANDARDS

The tests were performed according to following standards:

[FCC Rules Part 15.249](#): Operation within the bands 902 - 928 MHz, 2400 - 2483.5 MHz, 5725 - 5875 MHz, and 24.0 - 24.25 GHz.

[ANSI C63.10:2013](#) and [ANSI C63.4:2014](#)

1.2. Test Description

FCC PART 15.249		
FCC Part 15.249(a)	Field Strength of Fundamental	PASS
FCC Part 15.209	Spurious Emission	PASS
FCC Part 15.209	Band edge	PASS
FCC Part 15.215(c)	20dB bandwidth	PASS
FCC Part 15.207	Conducted Emission	N/A
FCC Part 15.203	Antenna Requirement	PASS



1.3. Test Facility

1.3.1 Address of the test laboratory

Shenzhen CTL Testing Technology Co., Ltd.

Floor 1-A, Baisha Technology Park, No. 3011, Shahexi Road, Nanshan, Shenzhen 518055 China

There is one 3m semi-anechoic chamber and two line conducted labs for final test. The Test Sites meet the requirements in documents ANSI C63.4 and CISPR 22/EN 55022 requirements.

1.3.2 Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

IC Registration No.: 9618B

The 3m alternate test site of Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration No.: 9618B on November 13, 2013.

FCC-Registration No.: 970318

Shenzhen CTL Testing Technology Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 970318, December 19, 2013.

1.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen CTL Testing Technology Co., Ltd. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for CTL laboratory is reported:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.10dB	(1)
Radiated Emission	Above 1GHz	4.32dB	(1)
Conducted Disturbance	0.15~30MHz	3.20dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

2. GENERAL INFORMATION

2.1. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Relative Humidity:	55 %
Air Pressure:	101 kPa

2.2. General Description of EUT

Product Name:	Breathalyzer
Model/Type reference:	AlcoREAL i-553
Power supply:	DC 1.5V from battery
Bluetooth BLE	
Supported type:	Version 4.0 for low Energy
Modulation:	GFSK
Operation frequency:	2402MHz to 2480MHz
Channel number:	40
Channel separation:	2 MHz
Antenna type:	PCB Antenna
Antenna gain:	0dBi

Note: For more details, please refer to the user's manual of the EUT.

2.3. Description of Test Modes and Test Frequency

The Applicant provides communication tools software to control the EUT for staying in continuous transmitting (Duty Cycle more than 98%) and receiving mode for testing. There are 40 channels provided to the EUT and Channel 00/19/39 were selected to test.

Operation Frequency :

Channel	Frequency (MHz)
00	2402
02	2404
03	2406
⋮	⋮
19	2440
⋮	⋮
37	2476
38	2478
39	2480

The field strength of radiation emission was measured in the following position: EUT stand-up position (Yaxis), lie-down position (X, Z axis). The data show in this report only with the worst case setup. After exploratory measurement the worst case of Y axis was reported.

2.4. Equipments Used during the Test

Test Equipment	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Due Date
Bilog Antenna	Sunol Sciences Corp.	JB1	A061713	2015/06/02	2016/06/01
EMI Test Receiver	R&S	ESCI	103710	2015/06/02	2016/06/01
Spectrum Analyzer	Agilent	E4407B	MY41440676	2015/05/21	2016/05/20
Controller	EM Electronics	Controller EM 1000	N/A	2015/05/21	2016/05/20
Horn Antenna	Sunol Sciences Corp.	DRH-118	A062013	2015/05/19	2016/05/18
Active Loop Antenna	SCHWARZBECK	FMZB1519	1519-037	2015/05/19	2016/05/18
Amplifier	Agilent	8349B	3008A02306	2015/05/19	2016/05/18
Amplifier	Agilent	8447D	2944A10176	2015/05/19	2016/05/18
Temperature/Humidity Meter	Gangxing	CTH-608	02	2015/05/20	2016/05/19
High-Pass Filter	K&L	9SH10-2700/X1 2750-O/O	N/A	2015/05/20	2016/05/19
High-Pass Filter	K&L	41H10-1375/U1 2750-O/O	N/A	2015/05/20	2016/05/19
RF Cable	HUBER+SUHNER	RG214	N/A	2015/05/20	2016/05/19

The calibration interval was one year

2.5. Related Submittal(s) / Grant(s)

This submittal(s) (test report) is intended for FCC ID: 2AFL6-I-553 filing to comply with Section 15.249 of the FCC Part 15, Subpart C Rules.

2.6. Modifications

No modifications were implemented to meet testing criteria.

3. TEST CONDITIONS AND RESULTS

3.1. Conducted Emissions Test


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. The EUT is a tabletop system; a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.4:2014
2. Support equipment, if needed, was placed as per ANSI C63.4:2014
3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.4:2014
4. If a EUT received DC power from the USB Port of Notebook PC, the PC's adapter received AC120V/60Hz power through a Line Impedance Stabilization Network (LISN) which supplied power source and was grounded to the ground plane.
5. All support equipments received AC power from a second LISN, if any.
6. The EUT test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
7. Analyzer / Receiver scanned from 150 KHz to 30MHz for emissions in each of the test modes.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST RESULTS

Not applicable to this device, which is a battery supply device.

3.2. Radiated Emissions and Band Edge

Limit

According 15.249, the field strength of emissions from intentional radiators operated within 2400MHz-2483.5Mhz shall not exceed 94dB μ V/m(50mV/m):

FCC PART 15.249(d) Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.


In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a)

Radiated emission limits


Frequency (MHz)	Distance (Meters)	Radiated (dB μ V/m)	Radiated (μ V/m)
0.009-0.49	3	$20\log(2400/F(\text{KHz}))+40\log(300/3)$	$2400/F(\text{KHz})$
0.49-1.705	3	$20\log(24000/F(\text{KHz}))+40\log(30/3)$	$24000/F(\text{KHz})$
1.705-30	3	$20\log(30)+40\log(30/3)$	30
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

TEST CONFIGURATION


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz

**Test Procedure**

Remark: New battery is used during all test

- Below 1GHz measurement the EUT is placed on a turntable which is 0.8m above ground plane, and above 1GHz measurement EUT was placed on a low permittivity and low loss tangent turn table which is 1.5m above ground plane.
- Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0° to 360° to acquire the highest emissions from EUT
- And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- Repeat above procedures until all frequency measurements have been completed.

TEST RESULTS

Remark:

- By preliminary testing and verifying three axis (X, Y and Z) position of EUT transmitted status, it was found that "Z axis" position was the worst, and test data recorded in this report.
- New battery is used during all testing

For 9 KHz-30MHz


Frequency (MHz)	Corrected Reading (dBuV/m)@3m	FCC Limit (dBuV/m) @3m	Margin (dB)	Detector	Result
0.24	49.57	100.00	50.43	PK	PASS
1.50	56.26	64.08	7.82	QP	PASS
15.62	57.36	69.54	12.18	QP	PASS
25.47	48.41	69.54	21.13	QP	PASS

For 30MHz-1GHz

Horizontal

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 30.0 MHz 1.0 GHz MaxPeak 300.0 ms 120 kHz JB1

**MEASUREMENT RESULT: "CTL150812702_red"**


8/12/2015 8:42PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	26.00	21.1	40.0	14.0	---	0.0	0.00	HORIZONTAL
70.740000	15.40	8.4	40.0	24.6	---	0.0	0.00	HORIZONTAL
128.940000	21.80	14.9	43.5	21.7	---	0.0	0.00	HORIZONTAL
200.720000	20.20	14.4	43.5	23.3	---	0.0	0.00	HORIZONTAL
503.360000	27.00	20.4	46.0	19.0	---	0.0	0.00	HORIZONTAL
951.500000	34.00	26.7	46.0	12.0	---	0.0	0.00	HORIZONTAL

Vertical

SWEEP TABLE: "test (30M-1G)"

Short Description: Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 30.0 MHz 1.0 GHz MaxPeak 300.0 ms 120 kHz JB1

**MEASUREMENT RESULT: "CTL150812703_red"**

8/12/2015 8:44PM

Frequency MHz	Level dBµV/m	Transd dB	Limit dBµV/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	26.10	21.1	40.0	13.9	---	0.0	0.00	VERTICAL
57.160000	16.00	8.3	40.0	24.0	---	0.0	0.00	VERTICAL
127.000000	21.00	15.0	43.5	22.5	---	0.0	0.00	VERTICAL
212.360000	20.20	14.3	43.5	23.3	---	0.0	0.00	VERTICAL
551.860000	26.80	21.1	46.0	19.2	---	0.0	0.00	VERTICAL
947.620000	33.30	26.6	46.0	12.7	---	0.0	0.00	VERTICAL

For 1GHz to 25GHz**GFSK Mode (above 1GHz)**

Frequency(MHz):				2402		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	88.54	PK	114	25.46	55.14	28.78	4.61	0.00	33.40
1	2402.00	78.26	AV	94	15.74	44.86	28.78	4.61	0.00	33.40
2	2390.00	36.54	PK	74	37.46	3.22	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	45.54	PK	74	28.46	12.15	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	47.54	PK	74	26.46	43.03	33.49	6.91	35.89	4.51
4	4804.00	--	AV	54	--	--	--	--	--	--
5	5510.75	42.35	PK	74	31.65	34.70	34.75	7.32	34.41	7.65
5	5510.75	--	AV	54	--	--	--	--	--	--
6	7206.00	40.42	PK	74	33.58	29.31	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2402		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2402.00	89.79	PK	114	24.21	56.39	28.78	4.61	0.00	33.40
1	2402.00	80.54	AV	94	13.46	47.14	28.78	4.61	0.00	33.40
2	2390.00	37.69	PK	74	36.31	4.37	28.72	4.60	0.00	33.32
2	2390.00	--	AV	54	--	--	--	--	--	--
3	2400.00	45.87	PK	74	28.13	12.48	28.78	4.61	0.00	33.39
3	2400.00	--	AV	54	--	--	--	--	--	--
4	4804.00	46.25	PK	74	27.75	41.74	33.49	6.91	35.89	4.51
4	4804.00	--	AV	54	--	--	--	--	--	--
5	5005.25	42.11	PK	74	31.89	35.31	34.00	7.03	34.23	6.80
5	5005.25	--	AV	54	--	--	--	--	--	--
6	7206.00	40.20	PK	74	33.8	29.09	36.95	9.18	35.03	11.11
6	7206.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW 1MHz VBW 3MHz ,Peak detector for PK value , RBW 1MHz VBW 10Hz ,Peak detector for AV value.
7. For fundamental frequency :RBW 3MHz VBW 3MHz ,Peak detector for PK value , RBW 3MHz VBW 3MHz ,RMS detector for AV value.

Frequency(MHz):				2440		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	88.45	PK	114	25.55	54.94	28.85	4.65	0.00	33.51
1	2440.00	79.65	AV	94	14.35	46.14	28.85	4.65	0.00	33.51
2	4305.80	39.45	PK	74	34.55	34.65	32.83	6.59	34.63	4.80
2	4305.80	--	AV	54	--	--	--	--	--	--
3	4880.00	47.26	PK	74	26.74	41.01	33.60	6.95	34.30	6.25
3	4880.00	--	AV	54	--	--	--	--	--	--
4	5355.75	40.35	PK	74	33.65	32.45	34.70	7.23	34.03	7.90
4	5355.75	--	AV	54	--	--	--	--	--	--
5	7320.00	43.47	PK	74	30.53	31.78	37.46	9.23	35.00	11.69
5	7320.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2440		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2440.00	89.70	PK	114	24.3	56.19	28.85	4.66	0.00	33.51
1	2440.00	79.89	AV	94	14.11	46.38	28.85	4.66	0.00	33.51
2	4115.50	39.45	PK	74	34.55	34.90	32.81	6.47	34.73	4.55
2	4115.50	--	AV	54	--	--	--	--	--	--
3	4880.00	47.45	PK	74	26.55	41.20	33.60	6.95	34.30	6.25
3	4880.00	--	AV	54	--	--	--	--	--	--
4	5142.75	40.45	PK	74	33.55	33.07	34.42	7.11	34.15	7.38
4	5142.75	--	AV	54	--	--	--	--	--	--
5	7320.00	43.20	PK	74	30.8	31.51	37.46	9.23	35.00	11.69
5	7320.00	--	AV	54	--	--	--	--	--	--

REMARKS:

1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW 1MHz VBW 3MHz ,Peak detector for PK value , RBW 1MHz VBW 10Hz ,Peak detector for AV value.
7. For fundamental frequency :RBW 3MHz VBW 3MHz ,Peak detector for PK value , RBW 3MHz VBW 3MHz ,RMS detector for AV value.

Frequency(MHz):				2480		Polarity:			HORIZONTAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	88.78	PK	114	25.22	55.16	28.92	4.70	0.00	33.62
1	2480.00	79.32	AV	94	14.68	45.70	28.92	4.70	0.00	33.62
2	2483.50	45.54	PK	74	28.46	11.91	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	38.40	PK	74	35.6	4.72	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	48.65	PK	74	25.35	43.73	33.84	7.00	35.92	4.92
4	4960.00	--	AV	54	--	--	--	--	--	--
5	5975.75	42.45	PK	74	31.55	34.41	35.05	7.58	34.58	8.04
5	5975.75	--	AV	54	--	--	--	--	--	--
6	7440.00	40.26	PK	74	33.74	28.31	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

Frequency(MHz):				2480		Polarity:			VERTICAL	
No.	Frequency (MHz)	Emission Level (dBuV/m)		Limit (dBuV/m)	Margin (dB)	Raw Value (dBuV)	Antenna Factor (dB/m)	Cable Factor (dB)	Pre-amplifier (dB)	Correction Factor (dB/m)
1	2480.00	89.44	PK	114	24.56	55.82	28.92	4.70	0.00	33.62
1	2480.00	79.26	AV	94	14.74	45.64	28.92	4.70	0.00	33.62
2	2483.50	46.47	PK	74	27.53	12.84	28.93	4.70	0.00	33.63
2	2483.50	--	AV	54	--	--	--	--	--	--
3	2500.00	37.55	PK	74	36.45	3.87	28.96	4.72	0.00	33.68
3	2500.00	--	AV	54	--	--	--	--	--	--
4	4960.00	49.41	PK	74	24.59	44.49	33.84	7.00	35.92	4.92
4	4960.00	--	AV	54	--	--	--	--	--	--
5	6150.50	42.63	PK	74	31.37	34.28	35.19	7.82	34.66	8.35
5	6150.50	--	AV	54	--	--	--	--	--	--
6	7440.00	40.47	PK	74	33.53	28.52	37.64	9.28	34.97	11.95
6	7440.00	--	AV	54	--	--	--	--	--	--

REMARKS:


1. Emission level (dBuV/m) =Raw Value (dBuV)+Correction Factor (dB/m)
2. Correction Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor
3. Margin value = Limit value- Emission level.
4. -- Mean the PK detector measured value is below average limit.
5. The other emission levels were very low against the limit.
6. RBW 1MHz VBW 3MHz ,Peak detector for PK value , RBW 1MHz VBW 10Hz ,Peak detector for AV value.
7. For fundamental frequency :RBW 3MHz VBW 3MHz ,Peak detector for PK value , RBW 3MHz VBW 3MHz ,RMS detector for AV value.

3.3. Occupied Bandwidth Measurement

Limit

N/A

Test Configuration



Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 30 KHz RBW and 100 KHz VBW.

The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

Test Results

Modulation	Channel	99% OBW (MHz)	20dB bandwidth (MHz)	Result
GFSK	CH00	1.011	1.119	Pass
	CH19	1.009	1.126	
	CH39	1.012	1.125	

Test plot as follows:

The image shows a screenshot of an Agilent spectrum analyzer. The top bar displays the Agilent logo and the word 'R T'. Below this, the 'Ch Freq' is set to 2.402 GHz. The 'Occupied Bandwidth' measurement is highlighted in a dark box, showing a value of 1.0110 MHz. To the right of this, there are fields for 'Trig' and 'Free'. Below the measurement box, the 'Ref 10 dBm' and 'Atten 20 dB' are indicated. The main display area shows a frequency spectrum with a blue line representing the signal. Two diamond markers are placed on the spectrum, with arrows pointing to them from the left and right. The 'Center 2.402 GHz' and 'Span 3 MHz' are displayed at the bottom. The 'Res BW 30 kHz' and '#VBW 100 kHz' are also shown. On the right side of the screen, there are several buttons: 'Trace/View', 'Trace', 'Clear Write', 'Max Hold', 'Min Hold', 'View', 'Blank', and 'More'. The bottom right corner shows '1 of 2'.

Agilent R T

Trace/View

Ch Freq 2.44 GHz Trig Free

Occupied Bandwidth

1 2

Clear Write

Max Hold

Min Hold

View

Blank

More

1 of 2

Ref 10 dBm Atten 20 dB

#Peak

Log

10

dB/

Offset

0.5

dB

Center 2.44 GHz

#Res BW 30 kHz

#VBW 100 kHz

Span 3 MHz

Sweep 5 ms

Occupied Bandwidth

1.0092 MHz

Occ BW % Pwr 99.00 %

x dB -20.00 dB

Transmit Freq Error 5.484 kHz

x dB Bandwidth 1.126 MHz

Agilent R T

Ch Freq 2.48 GHz Trig Free

Occupied Bandwidth

Ref 10 dBm Atten 20 dB

#Peak

Log

10

dB/Offt

0.5 dB

Center 2.48 GHz

#Res BW 30 kHz

#VBW 100 kHz

Span 3 MHz

Sweep 5 ms

Occupied Bandwidth 1.0119 MHz

Occ BW % Pwr 99.00 %

x dB -20.00 dB

Transmit Freq Error 5.623 kHz

x dB Bandwidth 1.125 MHz

Trace/View

Trace

1 2

Clear Write

Max Hold

Min Hold

View

Blank

More 1 of 2

CH39

3.4. Antenna Requirement

Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


Refer to statement below for compliance.

The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.


Antenna Connected Construction

The antenna used in this product is an internal Antenna, The directional gains of antenna used for transmitting is 0 dBi.

BT
antenna



4. Test Setup Photos of the EUT






5. External and Internal Photos of the EUT


External Photos of EUT





Internal Photos of EUT

BT antenna



***** End of Report *****

