


Antenna Specification


ITEM	SPEC
Antenna type	PCB Antenna(B)
Center Frequency	2400Mhz 1.43dBi 2450Mhz 2.59dBi 2500Mhz 2.64dBi
MAX GAIN	2.90dbi
Polarization	Horizontal
Azimuth Beam Pattern	Omni-directional
Impedance	50ohm
Antenna Length	

Antenna Photo & Length(mm)




Coordinate System Reference:Antenna

Top view




Side view



2D Radiation pattern f = 2410MHz


E1 Face

2410.000MHz



E2 Face


2410.000MHz



2D Radiation pattern f = 2440MHz


E1 Face

2440.000MHz



E2 Face


2440.000MHz



2D Radiation pattern f = 2480MHz


E1 Face

2480.000MHz




E2 Face


2480.000MHz




3D Radiation pattern $f = 2410\text{MHz}$



3D Radiation pattern $f = 2450\text{MHz}$



3D Radiation pattern $f = 2480\text{MHz}$



Measurements summary

Frequency(GHz)	Gain(dBi)	CP Gain(dBi)	CO Gain(dBi)	Efficiency(dB)	Efficiency(%)
2400	1.43	--	--	--	32. 67%
2410	2.15	--	--	--	35. 24%
2420	2.27	--	--	--	37. 66%
2430	2.45	--	--	--	40. 2%
2440	2.38	--	--	--	41. 71%
2450	2.59	--	--	--	43. 25%
2460	2.70	--	--	--	40. 98%
2470	2.81	--	--	--	42. 14%
2480	2.90	--	--	--	44. 5%
2490	2.57	--	--	--	43. 22%
2500	2.64	--	--	--	42. 92%

Wireless-Tag Technology Co., Ltd

801, Block A, Building 6, Shenzhen International Innovation Valley, Dashi Road, Xili Community, Xili Street, Nanshan District, Shenzhen